# MedMentions: A Large Biomedical Corpus Annotated with UMLS Concepts

## Abstract

This paper presents the formal release of *MedMentions*, a new manually annotated resource for the recognition of biomedical concepts. What distinguishes MedMentions from other annotated biomedical corpora is its size (over 4,000 abstracts and over 350,000 linked mentions), as well as the size of the concept ontology (over 3 million concepts from UMLS 2017) and its broad coverage of biomedical disciplines. In addition to the full corpus, a sub-corpus of MedMentions is also presented, comprising annotations for a subset of UMLS 2017 targeted towards document retrieval. To encourage research in Biomedical Named Entity Recognition and Linking, data splits for training and testing are included in the release, and a baseline model and its metrics for entity linking are also described.

## 1. Introduction

One recognized challenge in developing automated biomedical entity extraction systems is the lack of richly annotated training datasets. While there are a few such datasets available, the annotated corpus often contains no more than a few thousand annotated entity mentions. Additionally, the annotated entities are limited to a few types of biomedical concepts such as diseases [Doğan and Lu, 2012], gene ontology terms [Van Auken et al., 2014], or chemicals and diseases [Li et al., 2016]. Researchers targeting the recognition of multiple biomedical entity types have had to resort to specialized machine learning techniques for combining datasets labelled with subsets of the full target set, e.g. using multi-task learning [Crichton et al., 2017], or a modified Conditional Random Field cost which allows un-labeled tokens to take any labels not in the current dataset's target set [Greenberg et al., 2018]. To promote the development of state-of-the-art entity linkers targeting a more comprehensive coverage of biomedical concepts, we decided to create a large concept-mention annotated dataset named *MedMentions*.

The paper begins with an introduction to the MedMentions annotated corpus, including a sub-corpus aimed at information retrieval systems. This is followed by a comparison with a few other large datasets annotated with biomedical entities. Finally, to promote further research on large ontology named entity recognition and linking, we present some baseline metrics.

## 2. Introducing MedMentions

### 2.1 The Documents

We randomly selected 5,000 abstracts released in PubMed®[1] between January 2016 and January 2017. Upon review, some abstracts were found to be outside the biomedical fields or not written in English. These were excluded, resulting in a total of 4,392 abstracts in the corpus.

### 2.2 Concepts in UMLS

The Metathesaurus of the Unified Medical Language System (UMLS) [Bodenreider, 2004] combines concepts from over 200 source ontologies. It is therefore the largest single ontology of biomedical concepts, and was a natural choice for constructing an annotated resource with broad coverage in biomedical science.

In this paper, we will use *entities* and *concepts* interchangeably, to refer to UMLS concepts. The 2017 AA release of the UMLS Metathesaurus contains $\sim 3.2M$ unique concepts. Each concept has a unique id (a "CUID") and primary name and a set of aliases, and is linked to all the source ontologies it was mapped from. Each concept is also linked to one or more Semantic Types – the UMLS guidelines are to link each concept to the most specific type(s) available. Each Semantic Type also has a unique identifier ("TUI") and a name. The Metathesaurus contains 127 Semantic Types, arranged in a "is-a" hierarchy. About 91.7% of the concepts are linked to exactly one semantic type, $\sim 8\%$ to two types, and a very small number to more than two types.

### 2.3 Annotating Concept Mentions

We recruited a team of professional annotators with rich experience in biomedical content curation to exhaustively annotate UMLS entity mentions from the abstracts.

The annotators used the text processing tool GATE[2] (version 8.2) to facilitate the curation. All the relevant scientific terms from each abstract were manually searched in the 2017 AA (full) version of the UMLS metathesaurus[3] and the best matching concept was retrieved. The annotators were asked to annotate the most specific concept for each mention, without any overlaps in mentions.

To gain insight on the annotation quality of MedMentions, we randomly selected eight abstracts from the annotated corpus. Two biologists ("Rreviewers") who did not participate in the annotation task then each reviewed four abstracts and the corresponding concepts in MedMentions. The abstracts contained a total of 469 concepts. Of these 469 concepts, the agreement between Reviewers and Annotators was 97.3%, estimating the *precision* of the annotation IN MEDMENTIONS. Due to the size of UMLS, we reasoned that no human curators would have knowledge of the entire UMLS, so we did not perform an evaluation on the recall. We are working on getting more detailed IAA (Inter-annotator agreement) data, which will be released when that task is completed.

### 2.4 MedMentions ST21pv

Entity linking / labeling methods have prominently been used as the first step towards relationship extraction, e.g. the BioCreative V CDR task for Chemical-Disease relationship extraction [Li et al.,

---

1. http://pubmed.gov
2. https://gate.ac.uk/
3. http://umlsks.nlm.nih.gov

2016], and for indexing for entity-based document retrieval, e.g. as described in the BioASQ Task A for semantic indexing [Nentidis et al., 2018]. One of our goals in building a more comprehensive annotated corpus was to provide indexing models with a larger ontology than MeSH (used in BioASQ Task A and PubMed) for semantic indexing, to support more specific document retrieval queries from researchers in all biomedical disciplines.

UMLS does indeed provide a much larger ontology (see table 6). However UMLS also contains many concepts that are not as useful for specialized document retrieval, either because they are too broad so not discriminating enough (e.g. *Groups [cuid = C0441833]*, *Risk [C0035647]*), or cover peripheral and supplementary topics not likely to be used by a biomedical researcher in a query (e.g. *Rural Area [C0178837]*, *No difference [C3842396]*).

Filtering UMLS to a subset most useful for semantic indexing is going to be an area of ongoing study, and will have different answers for different user communities. Furthermore, targeting different subsets will also impact machine learning systems designed to recognize concepts in text. As a first step, we propose the "*ST21pv*" subset of UMLS, and the corresponding annotated subcorpus *MedMentions ST21pv*. Here "ST21pv" is an acronym for "21 Semantic Types from Preferred Vocabularies", and the ST21pv subset of UMLS was constructed as follows:

1. We eliminated all concepts that were only linked to semantic types at levels 1 or 2 in the UMLS Semantic Type hierarchy with the intuition that these concepts would be too broad. We also limited the concepts to those in the *Active* subset of the 2017 AA release of UMLS.

2. We then selected 21 semantic types at levels 3–5 based on biomedical relevance, and whether MedMentions contained sufficient annotated examples. Only concepts *mapping into* one of these 21 types (i.e. *linked* to one of these types or to a descendant in the type hierarchy) were considered for inclusion. As an example, the semantic type *Archaeon [T194]* was excluded because MedMentions contains only 25 mentions for 15 of the 5,418 concepts that map into this type (table 2). Similarly *Clinical Drug [T200]* was also eliminated.

3. Finally, we selected 18 'prefered' source vocabularies (table 1), and excluded any concepts that were not linked in UMLS to at least one of these sources. These vocabularies were selected based on usage and relevance to biomedical research[4], with an emphasis on gene function, disease and phenotype, structure and anatomy, and drug and chemical entities.

Table 2 gives a detailed breakdown of a portion of the semantic type hierarchy in UMLS 2017 AA Active. The rows in bold are the 21 types in ST21pv, and any descendants of these types have been pruned and their counts rolled up. The counts therefore are for concepts *linked* to the corresponding type for the non-bold rows, and *mapped* to the ST21pv types for the rows in bold. Note that some concepts in UMLS are linked to multiple semantic types. The prefix *MM-* in the column name indicates the counts are for concepts mentioned in MedMentions. The full MedMentions corpus contains 2,473 mentions of 685 concepts that are not members of the 2017 AA Active release. These were eliminated as part of step 1. The other non-bold rows in the table represent semantic types excluded in steps 1 and 2, corresponding to a total of 135,986 mentions of 6,002 unique concepts. A further 10,755 mentions of 2,618 concepts were eliminated in step 3. As a result of all this filtering, the target ontology for MedMentions ST21pv (MM-ST21pv) contains 2,327,250 concepts and 203,282 concept mentions.

---

4. An example of ontology usage or popularity can be found in the "Ontology Visits" statistics available at https://bioportal.bioontology.org.

| Ontology Abbrev. | Name |
| --- | --- |
| CPT | Current Procedural Terminology |
| FMA | Foundational Model of Anatomy |
| GO | Gene Ontology |
| HGNC | HUGO Gene Nomenclature Committee |
| HPO | Human Phenotype Ontology |
| ICD10 | International Classification of Diseases, Tenth Revision |
| ICD10CM | ICD10 Clinical Modification |
| ICD9CM | ICD9 Clinical Modification |
| MDR | Medical Dictionary for Regulatory Activities |
| MSH | Medical Subject Headings |
| MTH | UMLS Metathesaurus Names |
| NCBI | National Center for Biotechnology Information Taxonomy |
| NCI | National Cancer Institute Thesaurus |
| NDDF | First DataBank MedKnowledge |
| NDFRT | National Drug File – Reference Terminology |
| OMIM | Online Mendelian Inheritance in Man |
| RXNORM | NLM's Nomenclature for Clinical Drugs for Humans |
| SNOMEDCT_US | US edn. of the Systematized Nomenclature of Medicine-Clinical Terms |

Table 1: The restricted set of source ontologies for MedMentions ST21pv.

Examples of broad concepts eliminated by selecting semtypes at level 3 or higher:

- C1707689: "Design", linked to T052: Activity, level=2

- C0029235: "Organism" linked to T001: Organism, level=3

- C0520510: "Materials" linked to T167: Substance, level=3

## 2.5 MedMentions Corpus Statistics

The MedMentions corpus consists of 4,392 abstracts randomly selected from those released on PubMed between January 2016 and January 2017. Table 3 shows some descriptive statistics for the MedMentions corpus and its ST21pv subset. The tokenization and sentence splitting were performed using Stanford CoreNLP[5] [Manning et al., 2014].

Due to the size of UMLS, only about 1% of its concepts are covered in MedMentions. So a major part of the challenge for machine learning systems trained to recognize these concepts is 'unseen labels' (often called "zero-shot learning", e.g. [Palatucci et al., 2009, Srivastava et al., 2018, Xian et al., 2017]). As part of the release, we also include a 60% - 20% - 20% random partitioning of the corpus into training, 'dev' (aka validation) and test subsets. These are described in table 4. As can be seen from the table, about 42% of the concepts in the test data do not occur in the training data, and 38% do not occur in either training or dev subsets.

---

5. https://stanfordnlp.github.io/CoreNLP/

| TypeName | TypeID | Level | nConcepts | MM-nConcepts | MM-nDocs | MM-nMentions |
|---|---|---|---|---|---|---|
| Event | T051 | 1 | 185 | 16 | 146 | 292 |
| Activity | T052 | 2 | 420 | 152 | 2,615 | 7,253 |
| Behavior | T053 | 3 | 84 | 23 | 191 | 447 |
| Social Behavior | T054 | 4 | 924 | 171 | 382 | 982 |
| Individual Behavior | T055 | 4 | 857 | 149 | 352 | 1,012 |
| Daily or Recreational Activity | T056 | 3 | 808 | 71 | 218 | 863 |
| Occupational Activity | T057 | 3 | 739 | 130 | 465 | 891 |
| **Health Care Activity** | **T058** | **4** | **390,903** | **3,760** | **3,593** | **26,300** |
| **Research Activity** | **T062** | **4** | **1,598** | **538** | **3,166** | **9,965** |
| Governmental or Regulatory Activity | T064 | 4 | 516 | 61 | 94 | 188 |
| Educational Activity | T065 | 4 | 2,241 | 74 | 172 | 554 |
| Machine Activity | T066 | 3 | 155 | 37 | 125 | 288 |
| Phenomenon or Process | T067 | 2 | 1,615 | 154 | 900 | 2,034 |
| **Injury or Poisoning** | **T037** | **3** | **104,583** | **274** | **521** | **1,895** |
| Human-caused Phenomenon or Process | T068 | 3 | 560 | 48 | 173 | 295 |
| Environmental Effect of Humans | T069 | 4 | 68 | 27 | 62 | 190 |
| Natural Phenomenon or Process | T070 | 3 | 749 | 306 | 956 | 2,831 |
| **Biologic Function** | **T038** | **4** | **233,423** | **5,587** | **3,955** | **43,514** |
| Entity | T071 | 1 | 23 | 6 | 81 | 109 |
| Physical Object | T072 | 2 | 42 | 6 | 29 | 79 |
| Organism | T001 | 3 | 118 | 41 | 377 | 1,038 |
| **Virus** | **T005** | **4** | **18,128** | **131** | **174** | **1,105** |
| **Bacterium** | **T007** | **4** | **350,363** | **376** | **325** | **2,051** |
| Archaeon | T194 | 4 | 5,428 | 13 | 8 | 25 |
| **Eukaryote** | **T204** | **4** | **806,577** | **1,243** | **1,428** | **8,640** |
| **Anatomical Structure** | **T017** | **3** | **196,416** | **2,972** | **2,538** | **20,778** |
| Manufactured Object | T073 | 3 | 6,152 | 455 | 1,156 | 3,615 |
| **Medical Device** | **T074** | **4** | **58,801** | **468** | **565** | **2,406** |
| Research Device | T075 | 4 | 119 | 19 | 192 | 365 |
| Clinical Drug | T200 | 4 | 129,570 | 27 | 22 | 61 |
| Substance | T167 | 3 | 9,036 | 98 | 676 | 1,769 |
| **Body Substance** | **T031** | **4** | **2,055** | **108** | **475** | **1,258** |
| **Chemical** | **T103** | **4** | **435,397** | **5,614** | **2,734** | **38,225** |
| **Food** | **T168** | **4** | **7,041** | **174** | **286** | **1,462** |
| Conceptual Entity | T077 | 2 | 758 | 160 | 1,470 | 2,997 |
| Organism Attribute | T032 | 3 | 678 | 133 | 1,405 | 3,732 |
| **Clinical Attribute** | **T201** | **4** | **85,018** | **271** | **858** | **2,027** |
| **Finding** | **T033** | **3** | **308,234** | **3,143** | **3,577** | **18,435** |
| Idea or Concept | T078 | 3 | 3,541 | 389 | 2,839 | 9,348 |
| Temporal Concept | T079 | 4 | 3,742 | 431 | 2,621 | 10,169 |
| Qualitative Concept | T080 | 4 | 4,249 | 1,037 | 4,122 | 31,485 |
| Quantitative Concept | T081 | 4 | 9,106 | 904 | 3,441 | 19,995 |
| **Spatial Concept** | **T082** | **4** | **42,799** | **1,318** | **2,992** | **13,386** |
| Functional Concept | T169 | 4 | 3,549 | 721 | 3,979 | 23,661 |
| **Body System** | **T022** | **5** | **570** | **60** | **257** | **517** |
| Occupation or Discipline | T090 | 3 | 529 | 114 | 321 | 565 |
| **Biomedical Occupation or Discipline** | **T091** | **4** | **1,107** | **191** | **484** | **938** |
| **Organization** | **T092** | **3** | **2,695** | **291** | **882** | **2,255** |
| Group | T096 | 3 | 53 | 22 | 479 | 1,046 |
| **Professional or Occupational Group** | **T097** | **4** | **5,704** | **261** | **623** | **1,856** |
| **Population Group** | **T098** | **4** | **2,556** | **244** | **1,644** | **6,319** |
| Family Group | T099 | 4 | 372 | 56 | 233 | 816 |
| Age Group | T100 | 4 | 120 | 43 | 628 | 2,157 |
| Patient or Disabled Group | T101 | 4 | 259 | 37 | 1,520 | 6,300 |
| Group Attribute | T102 | 3 | 130 | 24 | 94 | 154 |
| **Intellectual Product** | **T170** | **3** | **30,864** | **1,110** | **2,660** | **11,375** |
| Language | T171 | 3 | 1,063 | 15 | 39 | 99 |
| Not in 2017 AA Active | - | - | - | 685 | 1,088 | 2,473 |

Table 2: UMLS semantic type hierarchy pruned at the 21 types in *ST21pv* (in bold), showing number of concepts and mentions in MedMentions. Counts in non-bold rows are for concepts *linked* to the corresponding type, and for the ST21pv types (bold) concepts *mapped* to those types.

| | MedMentions | MM-ST21pv |
|---|---|---|
| Total nbr. documents | 4,392 | 4,392 |
| Total nbr. unique concepts mentioned | 34,724 | 25,419 |
| Total nbr. mentions | 352,496 | 203,282 |
| Avg nbr mentions / doc | 80.3 | 46.3 |
| Total nbr. sentences | 42,602 | 42,602 |
| Total nbr. tokens | 1,176,058 | 1,176,058 |
| Total nbr. tokens annotated | 579,839 | 366,742 |
| Proportion of tokens annotated | 49.3% | 31.2% |
| Avg nbr. tokens / mention | 1.6 | 1.8 |
| Avg nbr. tokens / doc | 267.8 | 267.8 |
| Avg nbr. annotated tokens / doc | 132.0 | 83.5 |
| Avg nbr. sentences / doc | 9.7 | 9.7 |
| Avg nbr. tokens / sentence | 27.6 | 27.6 |

Table 3: Some statistics describing MedMentions. Sentence-splitting and tokenization was done using Stanford CoreNLP [Manning et al., 2014] ver. 3.8 and its Penn TreeBank tokenizer.

| | Training | Dev | Test |
|---|---|---|---|
| Nbr. documents | 2,635 | 878 | 879 |
| Nbr. mentions | 122,241 | 40,884 | 40,157 |
| Nbr. unique concepts mentioned | 18,520 | 8,643 | 8,457 |
| Nbr. concepts overlapping with Training | | 4,984 | 4,867 |
| Proportion of concepts overlapping with Training | | 57.7% | 57.5% |
| Nbr. concepts overlapping with Training + Dev | | | 5,217 |
| Proportion of concepts overlapping with Training + Dev | | | 61.7% |

Table 4: The Training-Dev-Test splits for *MM-ST21pv* are a random 60% - 20% - 20% partition.

|  | GENIA[1] | ITI TXM[2] | CRAFT v1.0 | MedMentions[1] |
|---|---|---|---|---|
| Nbr. Documents | 2,000 | (full text) 455 | (full text) 67 | 4,392 |
| Nbr. Sentences | $\sim$ 21k | $\sim$ 94k | $\sim$ 21k | 42,602 |
| Nbr. Tokens (PTB) | $\sim$ 440,000 | $\sim$ 2.7M | $\sim$ 560,000 | 1,176,058 |
| Nbr. Tokens Annotated | n/a | n/a | n/a | 579,839 |
| Nbr. Mentions | $\sim$ 100,000 | $\sim$ 324k | 99,907 | 352,496 |
| Nbr. unique Concepts mentioned | 36 | n/a | 4,319 | 34,724 |
| Ontology Nbr. Concepts | 36 | n/a | 862,763 | 3,271,124 |

Table 5: Comparing the GENIA, IIT TXM, CRAFT and MedMentions corpora. Notes: (1) Documents in the GENIA and MedMentions corpora are abstracts. (2) The counts for ITI TXM are estimates. Some documents were annotated by multiple curators, and left as separate versions in the corpus.

### 2.6 Accessing MedMentions

The MedMentions resource has been published at **anonymized**. The corpus itself is in PubTator [Wei et al., 2013] format, which is described on the release site. The corpus consists of PubMed abstracts, each identified with a unique PubMed identifier (PMID). Each PubMed abstract has Title and Abstract texts, and a series of annotations of concept mentions. Each concept mention identifies the portion of the document text comprising the mention, and the UMLS concept. A separate file for the ST21pv sub-corpus is also included in the release.

The release also includes three lists of PMID's that partition the corpus into a 60% / 20% / 20% split defining the 'Training', 'Development' and 'Test' subsets. Researchers are encouraged to train their models using the Training and Development portions of the corpus, and publish test results on the held-out Test subset of the corpus.

## 3. A Comparison With Some Related Corpora

There have been several "gold-standard" (manually annotated) corpora of biomedical scientific literature made publicly available. Some of the larger ones are described below.

**GENIA:** [Ohta et al., 2002, Kim et al., 2003] One of the earliest 'large' biomedical annotated corpora, it is aimed at biomedical Named Entity Recognition, where the annotations are for 36 biomedical Entity Types. The dataset consists of 2,000 MEDLINE abstracts about "biological reactions concerning transcription factors in human blood cells", collected by searching on MEDLINE using the MeSH terms *human*, *blood cells* and *transcription factors*. An extended version (2,404 abstracts), with a smaller ontology (six types) was later used for the JNLPBA 2004 NER task [Kim et al., 2004].

**ITI TXM Corpora:** [Alex et al., 2008] Among the largest gold-standard biomedical annotated corpora previously available, this consists of two sets of full-length papers obtained from PubMed and PubMed Central: 217 articles focusing on protein-protein interactions (PPI) and 238 articles on tissue expressions (TES). The PPI and TES corpora were annotated with

entities from NCBI Taxonomy, NCBI Reference Sequence Database, and Entrez Gene. The TES corpus was also annotated with entities from Chemical Entities of Biological Interest (ChEBI) and Medical Subject Headings (MeSH). The concepts were grouped into 15 entity types, and these type labels were included in the annotations. In addition to concept mentions, the corpus also includes relations between entities.

The statistics (table 5) for this corpus [Alex et al., 2008] are a little confusing, since not all sections of the articles were annotated. Furthermore some articles were annotated by more than one biologist, and each annotated version was incorporated into the corpus as a separate document.

**CRAFT:** [Bada et al., 2012] The Colorado Richly Annotated Full-Text (CRAFT) Corpus is another large gold-standard corpus annotated with a diverse set of biomedical concepts. It consists of 67 full-text open-access biomedical journal articles, downloaded from PubMed Central, covering a wide range of disciplines, including genetics, biochemistry and molecular biology, cell biology, developmental biology, and computational biology. The text is annotated with concepts from 9 biomedical ontologies: ChEBI, Cell Ontology, Entrez Gene, Gene Ontology (GO) Biological Process, GO Cellular Component, GO Molecular Function, NCBI Taxonomy, Protein Ontology, and Sequence Ontology. The latest release of CRAFT[6] reorganizes this into ten Open Biomedical Ontologies. The corpus also contains exhaustive syntactic annotations. Table 5 gives a comparison of the sizes of CRAFT against the other corpora mentioned here.

**BioASQ Task A:** [Nentidis et al., 2018] The Large Scale Semantic Indexing task considers assigning MeSH headings for 'important' concepts to each document. The training data is very large, but with a smaller target concept vocabulary (see table 6), and annotation (by NCBI) is at the document level rather than at the mention level.

**Relation / Event Extraction Corpora:** Most recently developed manually annotated datasets of biomedical scientific literature have focused on the task of extracting biomedical events or relations between entities. These datasets have been used for shared tasks in biomedical NLP workshops like BioCreative, e.g. BC5-CDR [Li et al., 2016] which focuses on Chemical-Disease relations, and BioNLP, e.g. the BioNLP 2013 Cancer Genetics (CG) and Pathway Curation tasks [Pyysalo et al., 2015] where the main goal is to identify events involving entities. While these datasets include entity mention annotations, they are typically focused on a small set of entity types, and the sizes of the corpora are also smaller (1,500 document abstracts in BC5-CDR, 600 abstracts in CG, and 525 abstracts in PC). Machine learning models for relation extraction take as input a text annotated with entity mentions, so recognizing biomedical concepts remains an important foundational task.

## 4. Concept Recognition with MedMentions ST21pv

Our main goal in constructing and releasing MedMentions is to promote the development of models for recognizing biomedical concepts mentioned in scientific literature. To help jumpstart this

---

6. CRAFT ver. 3.0, https://github.com/UCDenver-ccp/CRAFT

|                                           | BioASQ Task A (2018) | MedMentions ST21pv |
|-------------------------------------------|----------------------|--------------------|
| Nbr. Training+Dev Documents               | 13.48M               | 3,513              |
| Average nbr. unique Concepts / Document   | 12.7                 | 22.4               |
| Total nbr. Concepts in Target Ontology    | 28,956               | 2,327,250          |
| Ontology Coverage in Training+Dev Data    | 98%                  | 1.1%               |
| Concept overlap, Test v/s Training+Dev    | (est.) $\sim 98\%$   | 61.7%              |

Table 6: Comparing BioAsq Task A (2018) with MedMentions ST21pv. About 38% of the concepts mentioned in MedMentions ST21pv Test data have no mentions in the Training or Dev subsets.

| Metric     | Mention-level | Document-level |
|------------|---------------|----------------|
| Precision  | 0.471         | 0.536          |
| Recall     | 0.436         | 0.561          |
| F1 Score   | 0.453         | 0.548          |

Table 7: Entity linking metrics for the TaggerOne model on MedMentions ST21pv.

research, we now present some baseline modeling approaches trained using the Training and Dev splits of MedMentions ST21pv, and their metrics on the MM-ST21pv Test set.

### 4.1 End-to-end Entity Recognition and Linking with TaggerOne

TaggerOne [Leaman and Lu, 2016] is a semi-markov model doing joint entity type recognition and entity linking, with perceptron-style parameter estimation. The MM-ST21pv data presented to TaggerOne was modified as follows: for each mention of a concept in the data, the Semantic Type label was modified to one of the 21 semantic types (table 2) that concept mapped into. Thus each mention was labeled with one of 21 entity types, as well as linked to a specific concept from our ST21pv subset of UMLS. Twenty one 'lexicons' of primary and alias names for each concept in the 21 types, extracted from UMLS 2017 AA Active, were also provided to TaggerOne.

Training was performed on the 'Training' split, and the 'Dev' split was provided as the 'holdout' data (validation data, used for stopping training). The model was trained with REGULARIZATION = 0, MAX_STEP_SIZE = 1.5 and patience (iterationsPastLastImprovement) of 1 epoch, with a maximum of 10 epochs. Both mention level (aka phrase-level) metrics, and document level metrics on the MM-ST21pv Test split are reported in table 7.

Mention level metrics are calculated by only counting an exact mention phrase match (including location of phrase in the text) and linked entity match between the prediction and reference (ground truth in MM-ST21pv) as a true-positive. All other predicted mentions are counted as false-positives and all un-matched reference entity mentions are counted as false-negatives. Document level metrics are computed in a similar manner, after mapping all mentions as entity labels (without the mention phrase) on the document. Document level metrics are useful in information retrieval when the goal is simply to retrieve the entire matching document.

## 5. Conclusion

We presented the formal release of a new resource, named MedMentions, for biomedical concept recognition, with a large manually annotated annotated corpus of over 4,000 abstracts targeting a very large fine-grained concept ontology consisting of over 3 million concepts. We also included in this release a targeted sub-corpus (MedMentions ST21pv), and standard training / dev / test splits of the data to allow researchers to compare the metrics of their models.

## Acknowledgments

Omitted for blind review.

## References

Bea Alex, Claire Grover, Barry Haddow, Mijail A. Kabadjov, Ewan Klein, Michael Matthews, Stuart Roebuck, Richard Tobin, and Xinglong Wang. The iti txm corpora : Tissue expressions and protein-protein interactions. In *LREC: Proceedings of the Workshop on Building & Evaluation of Resources for Biomedical Text Mining*, 2008.

Michael Bada, Miriam Eckert, Donald Evans, Kristin Garcia, Krista Shipley, Dmitry Sitnikov, William A. Baumgartner, K. Bretonnel Cohen, Karin Verspoor, Judith A. Blake, and Lawrence E. Hunter. Concept annotation in the CRAFT corpus. *BMC Bioinformatics*, 13(1):161, Jul 2012. ISSN 1471-2105. doi: 10.1186/1471-2105-13-161. URL https://doi.org/10.1186/1471-2105-13-161.

Olivier Bodenreider. The Unified Medical Language System (UMLS): integrating biomedical terminology. 32 (Database issue):D267–D270, 2004.

Gamal Crichton, Sampo Pyysalo, Billy Chiu, and Anna Korhonen. A neural network multi-task learning approach to biomedical named entity recognition. *BMC Bioinformatics*, 18(1):368, Aug 2017. ISSN 1471-2105. doi: 10.1186/s12859-017-1776-8. URL https://doi.org/10.1186/s12859-017-1776-8.

Rezarta Islamaj Doğan and Zhiyong Lu. An improved corpus of disease mentions in PubMed citations. In *Proceedings of the 2012 Workshop on Biomedical Natural Language Processing*, BioNLP '12, pages 91–99, Stroudsburg, PA, USA, 2012. Association for Computational Linguistics. URL http://dl.acm.org/citation.cfm?id=2391123.2391135.

Nathan Greenberg, Trapit Bansal, Patrick Verga, and Andrew McCallum. Marginal likelihood training of BiLSTM-CRF for biomedical named entity recognition from disjoint label sets. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2824–2829. Association for Computational Linguistics, 2018. URL http://aclweb.org/anthology/D18-1306.

J.-D. Kim, T. Ohta, Y. Tateisi, and J. Tsujii. Genia corpus – a semantically annotated corpus for bio-textmining. *Bioinformatics*, 19(suppl_1):i180–i182, 2003. doi: 10.1093/bioinformatics/btg1023. URL http://dx.doi.org/10.1093/bioinformatics/btg1023.

Jin-Dong Kim, Tomoko Ohta, Yoshimasa Tsuruoka, Yuka Tateisi, and Nigel Collier. Introduction to the bio-entity recognition task at jnlpba. In *Proceedings of the International Joint Workshop on Natural Language Processing in Biomedicine and Its Applications*, JNLPBA '04, pages 70–75, Stroudsburg, PA, USA, 2004. Association for Computational Linguistics. URL http://dl.acm.org/citation.cfm?id=1567594.1567610.

Robert Leaman and Zhiyong Lu. TaggerOne: Joint named entity recognition and normalization with semi-Markov Models. *Bioinformatics*, 32(18):2839–2846, 2016. doi: 10.1093/bioinformatics/btw343. URL http://dx.doi.org/10.1093/bioinformatics/btw343.

Jiao Li, Yueping Sun, Robin J. Johnson, Daniela Sciaky, Chih-Hsuan Wei, Robert Leaman, Allan Peter Davis, Carolyn J. Mattingly, Thomas C. Wiegers, and Zhiyong Lu. BioCreative V CDR task corpus: a resource for chemical disease relation extraction. *Database*, 2016:baw068, 2016. doi: 10.1093/database/baw068. URL http://dx.doi.org/10.1093/database/baw068.

Christopher D. Manning, Mihai Surdeanu, John Bauer, Jenny Finkel, Steven J. Bethard, and David McClosky. The Stanford CoreNLP natural language processing toolkit. In *Association for Computational Linguistics (ACL) System Demonstrations*, pages 55–60, 2014. URL http://www.aclweb.org/anthology/P/P14/P14-5010.

Anastasios Nentidis, Anastasia Krithara, Konstantinos Bougiatiotis, Georgios Paliouras, and Ioannis Kakadiaris. Results of the sixth edition of the BioASQ challenge. In *Proceedings of the 6th BioASQ Workshop: A challenge on large-scale biomedical semantic indexing and question answering*, pages 1–10. Association for Computational Linguistics, 2018. URL http://aclweb.org/anthology/W18-5301.

Tomoko Ohta, Yuka Tateisi, and Jin-Dong Kim. The GENIA corpus: An annotated research abstract corpus in molecular biology domain. In *Proceedings of the Second International Conference on Human Language Technology Research*, HLT '02, pages 82–86, San Francisco, CA, USA, 2002. Morgan Kaufmann Publishers Inc. URL http://dl.acm.org/citation.cfm?id=1289189.1289260.

Mark Palatucci, Dean Pomerleau, Geoffrey E Hinton, and Tom M Mitchell. Zero-shot learning with semantic output codes. In Y. Bengio, D. Schuurmans, J. D. Lafferty, C. K. I. Williams, and A. Culotta, editors, *Advances in Neural Information Processing Systems 22*, pages 1410–1418. Curran Associates, Inc., 2009. URL http://papers.nips.cc/paper/3650-zero-shot-learning-with-semantic-output-codes.pdf.

Sampo Pyysalo, Tomoko Ohta, Rafal Rak, Andrew Rowley, Hong-Woo Chun, Sung-Jae Jung, Sung-Pil Choi, Jun'ichi Tsujii, and Sophia Ananiadou. Overview of the cancer genetics and pathway curation tasks of BioNLP shared task 2013. *BMC Bioinformatics*, 16(10):S2, Jun 2015. ISSN 1471-2105. doi: 10.1186/1471-2105-16-S10-S2. URL https://doi.org/10.1186/1471-2105-16-S10-S2.

Shashank Srivastava, Igor Labutov, and Tom Mitchell. Zero-shot learning of classifiers from natural language quantification. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 306–316. Association for Computational Linguistics, 2018. URL http://aclweb.org/anthology/P18-1029.

Kimberly Van Auken, Mary L. Schaeffer, Peter McQuilton, Stanley J. F. Laulederkind, Donghui Li, Shur-Jen Wang, G. Thomas Hayman, Susan Tweedie, Cecilia N. Arighi, James Done, Hans-Michael Müller, Paul W. Sternberg, Yuqing Mao, Chih-Hsuan Wei, and Zhiyong Lu. BC4GO: a full-text corpus for the BioCreative IV GO task. *Database*, 2014:bau074, 2014. doi: 10.1093/database/bau074. URL http://dx.doi.org/10.1093/database/bau074.

Chih-Hsuan Wei, Hung-Yu Kao, and Zhiyong Lu. Pubtator: a web-based text mining tool for assisting biocuration. *Nucleic Acids Research*, 41(W1):W518–W522, 2013. doi: 10.1093/nar/gkt441. URL http://dx.doi.org/10.1093/nar/gkt441.

Yongqin Xian, Christoph H. Lampert, Bernt Schiele, and Zeynep Akata. Zero-shot learning - A comprehensive evaluation of the good, the bad and the ugly. *CoRR*, abs/1707.00600, 2017. URL http://arxiv.org/abs/1707.00600.