Explanation-Based Attention for Semi-Supervised Deep Active Learning

Abstract

We introduce an attention mechanism to improve feature extraction for deep active learning (AL) in the semi-supervised setting. The proposed attention mechanism is based on recently proposed methods to visually explain predictions made by deep neural networks (DNNs). We apply the proposed explanation-based attention to MNIST and SVHN classification. The conducted experiments show accuracy improvement for the original and class-imbalanced datasets with the same amount of training examples as well as faster long-tail convergence compared to conventional uncertainty-based approaches.

1 Introduction

Deep active learning (AL) minimizes the number of expensive annotations needed to train deep neural networks (DNNs) by selecting a subset of relevant data points from a large unlabeled dataset (Lewis & Gale, 1994). This subset is annotated and added to the training dataset in a single *pool* of data points or, more often, in an iterative fashion. The goal is to maximize prediction accuracy while minimizing pool size × number of iterations product. A proxy for this goal could be the task of matching feature distributions between the validation and the AL-selected training datasets.

In density-based AL approaches, data selection is typically performed using a simple Euclidean-distance feature similarity metric (Sener & Savarese, 2018). The image retrieval field (Zhou et al., 2017) has advanced much further in this area. For example, recent state-of-the-art image retrieval systems are based on DNN-based feature extraction (Babenko & Lempitsky, 2015) and attention mechanisms (Noh et al., 2017). The latter estimates an attention mask to weight importance of the extracted features and it is trained along with the feature extraction.

Inspired by this, we employ image retrieval techniques and propose a novel attention mechanism for deep AL. Unlike supervised self-attention in (Noh et al., 2017) or (Vaswani et al., 2017), our attention is not trained with the model and is based on recent methods to generate visual explanations and to attribute feature importance values (Sundararajan et al., 2017). We show the effectiveness of this explanation-based attention (EBA) mechanism for AL when combined with multi-scale feature extraction on a number of image classification datasets. We also conduct experiments for distorted class-imbalanced training data which is a more realistic assumption for unlabeled data.

2 Related Work

AL is a well studied approach to decrease annotation costs in a traditional machine learning pipelines (Settles, 2010). Recently, AL has been applied to data-demanding DNN-based systems in semi-supervised or weakly-supervised settings. Though AL is an attractive direction, existing methods struggle to deal with high-dimensional data e.g. images. We believe this is related to the lack of class and instance-level feature importance information as well as the inability to capture spatially-localized features. To overcome these limitations, we are interested in estimating spatially-multiscale features and using EBA mechanism to select only the most discriminative features.

Wang et al. (2017) proposed to augment the training dataset by labeling the least confident data points and heuristically pseudo-labeling high confidence predictions. We believe softmax confidence is not a reliable proxy for the goals of AL i.e. for selecting images using feature distribution

Figure 1: Conventional multi-scale feature extraction and the proposed EBA extension (dashed).

matching between validation and training data. Unlike (Wang et al., 2017), we use pseudo-labels only to estimate EBA vectors and upweight discriminative features.

Gal et al. (2017) introduced a measure of uncertainty for approximate Bayesian inference that can be estimated using stochastic forward passes through a DNN with dropout layers. An acquisition function then selects data points with the highest uncertainty which is measured at the output of the softmax layer using a number of the proposed methods. Recently, Lakshminarayanan et al. (2017) and Beluch et al. (2018) extended uncertainty-based methods by using an ensemble of networks for uncertainty estimation and achieved superior accuracy.

Sener & Savarese (2018) formulated feature similarity-based selection as a geometric core-set approach which outperforms conventional k-center clustering. Though their method can complement our approach, we are focusing on the feature extraction part, while that work employed a simple L_2 distance similarity measure for the activations of the last fully-connected layer.

The work that is most similar to ours is Vodrahalli et al. (2018) which used the gradients as a measure of importance for dataset subsampling and analysis. However, our approach formulates the problem as a multi-scale EBA for AL and goes beyond a less robust single-step gradient attention. Other related works are online importance sampling methods (Ren et al., 2018) and the influence functions approach in (Koh & Liang, 2017). Online importance sampling upweights samples within the mini-batch during supervised training using gradient similarity while influence functions analyze data point importance using computationally challenging second-order gradient information.

3 METHOD

Pool-based AL. Let $(\mathbf{X}, y)$ be an input-label pair. There is a relatively small validation dataset $\{(\mathbf{X}_i^v, y_i^v)\}_{i \in \mathbb{M}}$ of size M and a large collection of training pairs $\{(\mathbf{X}_i, y_i)\}_{i \in \mathbb{N}}$ of size N for which, initially, only a small random subset or *pool* of labels $\mathbb{N}^1$ is known. We presume that the validation dataset matches the distribution of test data. At every bth iteration the AL algorithm selects a pool of P new labels to be added to existing training pairs comprising a training dataset $\mathbb{N}^b$.

Then, we optimize our DNN $\Phi(\mathbf{X}, \boldsymbol{\theta})$ subject to a loss function $(1/N^b) \sum_{i \in \mathbb{N}^b} L(\hat{y}_i, y_i)$ w.r.t. to model parameters $\boldsymbol{\theta}$. However, the actual task is to minimize validation loss $(1/M) \sum_{i \in \mathbb{M}} L(\hat{y}_i^v, y_i^v)$. Therefore, an oracle AL algorithm achieves minimum validation loss while performing the smallest number of iterations b with the fixed pool size P. In this work, we are interested not in an oracle AL, but in a method to extract relevant features for an AL acquisition function. We use a simple greedy algorithm to select the data points in the unlabeled training collection which are most similar to the misclassified entries in the validation dataset. If the number of misclassified validation data points exceeds pool size, we apply conventional k-center clustering with P centers.

Feature descriptors for AL. Let $\mathbf{F}_i^j \in \mathbb{R}^{C \times H \times W}$, where C, H, and W are the number of channels, the height, and the width, respectively be the output of the jth layer of DNN for input $\mathbf{X}_i$. Then, a feature vector or *descriptor* can be defined as $\boldsymbol{d}_i = \phi(\mathbf{F}_i) \in \mathbb{R}^{L \times 1}$, where function $\phi()$ is a conventional average pooling operation from (Babenko & Lempitsky, 2015). In a multi-scale case, descriptor $\boldsymbol{d}_i = [\phi^j(\mathbf{F}_i^j); \ldots; \phi^l(\mathbf{F}_i^l)]$.

A descriptor matrix for the validation dataset $\boldsymbol{V}_d \in \mathbb{R}^{M \times L}$ and current training dataset $\boldsymbol{S}_d^b \in \mathbb{R}^{N^b \times L}$ can be calculated using forward passes. Practically, descriptors can be compressed for storage efficiency reasons using PCA, quantization, etc. Then, a match kernel (Lee, 1999), e.g. cosine similarity, can be used to match features in both datasets. Assuming that vectors $\boldsymbol{d}_i$ are L_2-normalized, the cosine-similarity matrix $\boldsymbol{R}_d^b = \boldsymbol{V}_d(\boldsymbol{S}_d^b)^T$.

Explanation-based attention. Feature maps F_i extracted by $\Phi(\mathsf{X}, \boldsymbol{\theta})$ and pooled by $\phi()$ contain features that: a) are not class and instance-level discriminative, b) spatially represent features for a plurality of objects in the input. We would like to upweight discriminative features that satisfy a) and b) using an attention mechanism. One approach would be to use self-attention (Vaswani et al., 2017) at the cost of modifying network architecture and intervening in the training process. Instead, we propose to use EBA that is generated only for feature selection. The EBA mechanism attributes feature importance values w.r.t. to the output predictions. Unlike a visual *explanation* task, which estimates importance heatmaps in the input (image) space, we propose to estimate feature importance tensors A_i of the internal DNN representations F_i. Attention tensors A_i can be efficiently calculated using a series of backpropagation passes. Using one of backpropagation-based methods called *integrated gradients* (IG) from (Sundararajan et al., 2017), A_i^j can be estimated as

$$\mathsf{A}_i = (1/K) \sum_{k=1}^{K} \partial \Phi(k\mathsf{X}_i/K, \boldsymbol{\theta})/\partial \mathsf{F}_i, \tag{1}$$

where K is the number of steps to approximate the continuous integral by a linear path. Other forms of (1) are possible: from the simplest *saliency* method for which $K = 1$ (Simonyan et al., 2014) to more advanced methods with randomly sampled input features (Gudovskiy et al., 2018).

Due to lack of labels in (1), we propose to use pseudo-labeling. Pseudo-labels are used only to calculate similarity rather than to perform a greedy augmentation in (Wang et al., 2017). The EBA A_i can be converted to multi-scale attention vector using the same processing $\boldsymbol{a}_i = \phi(\mathsf{A}_i) \in \mathbb{R}^{L \times 1}$. The latter is implemented in most modern frameworks and, therefore, the complexity to generate A_i is only K forward-backward calls. This is schematically shown in Figure 1.

Summary for the proposed method. A random subset $\mathbb{N}^1$ of training data points is annotated and a DNN $\Phi(\mathsf{X}, \boldsymbol{\theta})$ optimized for this subset. Then, the AL algorithm iteratively ($b = 2, 3 \ldots$) performs following steps: 1) generates descriptor matrix pairs $(\boldsymbol{V}_d, \boldsymbol{V}_a), (\boldsymbol{S}_d^b, \boldsymbol{S}_a^b)$, 2) calculates similarity matrix $\boldsymbol{R}^b = \boldsymbol{R}_d^b \odot \boldsymbol{R}_a^b = \boldsymbol{V}_d(\boldsymbol{S}_d^b)^T \odot \boldsymbol{V}_a(\boldsymbol{S}_a^b)^T$, where $\odot$ is element-wise product, 3) selects P relevant data points from the remaining subset using similarity matrix $\boldsymbol{R}^b$ and acquisition function $\arg\max_{i \in \mathbb{N} \setminus \mathbb{N}^{b-1}}(\boldsymbol{R}^b(\mathsf{X}_i), \Phi)$ and 4) retrains $\Phi(\mathsf{X}, \boldsymbol{\theta})$ using augmented subset $\mathbb{N}^b$.

4 EXPERIMENTS

The proposed method as well as uncertainty-based methods from Gal et al. (2017) are applied to MNIST and SVHN. We evaluate AL with the original and distorted training data because unlabeled collection of data points cannot be a-priori perfectly selected. Hence, we introduce a *class imbalance ratio*, which is defined as the ratio of $\{0 \ldots 4\}$ digits to $\{5 \ldots 9\}$ digits. The following methods have been employed: *random* and uncertainty-based (*uncert*) selection, *greedy* (top-P) selection using similarity $\boldsymbol{R}$ without (*none*) and with EBA. The latter is estimated by saliency (*grad*) or IG (*ig*). We rerun experiments 10 times for MNIST and 5 times for SVHN with all-randomized initial parameters. Mean accuracy and standard deviation are plotted. DNN parameters are trained from scratch initially and after each AL iteration ($b = 10$). Mini-batch size is chosen by cross-validation.

MNIST. The dataset train/val/test split is 50K/10K/10K. The standard LeNet is used with the following hyperparameters: epochs=50, batch-size=25, lr=0.05, lr-decay=0.1 every 15 epochs, *uncert* methods and IG EBA use $K = 128$ passes and L is 20 for single-scale (before *fc1* layer) and 90 for multi-scale descriptors (all layers are concatenated). Figure 2(a) shows that feature-only matching (top-P:none_L20) outperforms random selection by $\approx 1\%$ while EBA (top-P:ig_L90) adds another 1% of accuracy when there is no class imbalance. High class imbalance (Figure 2(c)) widens the gap in achievable accuracy up to 20% for feature-only matching and 24% with EBA. The highest accuracy is achieved by multi-scale EBA estimated by IG.

EBA-based methods outperform the best uncertainty-based *variation ratio* (uncertain:varMC) approach for all class imbalance settings except the last one where the accuracy of variation ratio is

Figure 2: MNIST test dataset accuracy for 3 class imbalance ratios: a) 1 (no imbalance), b) 10 and c) 100. Total 9 AL iterations ($b = 10$) are performed each with $P = 250$ pool size.

Figure 3: SVHN test dataset accuracy for 3 class imbalance ratios: a) 1 (no imbalance), b) 10 and c) 100. Total 9 AL iterations ($b = 10$) are performed each with $P = 2,500$ pool size.

slightly higher. This might be related to small-scale MNIST and pseudo-label noise for EBA. To study the effects of pseudo-labeling, we plot true-label configurations (marked by "Abl") as well. When there is no class imbalance, the performance gap between EBA using true- and pseudo-labels is small, but much larger (up to 25%) when class imbalance ratio is 100 during first AL iterations.

SVHN. The dataset train/val/test split is 500K/104,388/26,032. A typical 8-layer CNN is used with the following hyperparameters: epochs=35, batch-size=25, lr=0.1, lr-decay=0.1 every 15 epochs, *uncert* methods and IG EBA use $K = 128$ and L is 256 for single-scale (before *fc1* layer) and 384 for two-scale descriptors (+ layer before *conv7*). Figure 3 shows that the gap between random selection and the best EBA-based AL method grows from 2% to more than 10% when the unlabeled training collection has more class imbalance. The gap between full training dataset accuracy increases for larger-scale SVHN as well. This results in even faster convergence for the proposed AL relative to random selection. The "topP:none_L256" underperforms compared to *uncert* and EBA-based methods. Accuracies of the *uncert* methods are closer to each other than for MNIST, which may signal that such methods are less effective for large-scale data. The EBA-based methods outperform all *uncert* methods, which is another argument supporting that hypothesis. Similarly to MNIST, AL methods with EBA improve accuracy with longer descriptor and more accurate attention estimation.

5 CONCLUSIONS AND FUTURE WORK

We applied recent image retrieval feature-extraction techniques for deep AL and introduced a novel EBA mechanism to improve feature-similarity matching. First feasibility experiments showed advantages of EBA to improve AL on MNIST and SVHN datasets. Rather than performing AL for the well-picked training datasets, we also conducted more realistic and challenging experiments with class-imbalanced training collections.

For the next steps, EBA should be evaluated with other types of data distortions and biases: within-class imbalance, adversarial examples, etc. Furthermore, such applications as object detection and image segmentation may benefit more from EBA because multi-scale attention can upweight spatially-important features. Lastly, a comparison with ensembled-based and density-based approaches is needed or EBA can be employed to complement them.

REFERENCES

Artem Babenko and Victor Lempitsky. Aggregating local deep features for image retrieval. In *ICCV*, 2015.

William H. Beluch, Tim Genewein, Andreas Nrnberger, and Jan M. Khler. The power of ensembles for active learning in image classification. In *CVPR*, 2018.

Yarin Gal, Riashat Islam, and Zoubin Ghahramani. Deep Bayesian active learning with image data. In *ICML*, 2017.

Denis Gudovskiy, Alec Hodgkinson, Takuya Yamaguchi, Yasunori Ishii, and Sotaro Tsukizawa. Explain to fix: A framework to interpret and correct DNN object detector predictions. In *Systems for ML Workshop at NIPS*, 2018.

Pang Wei Koh and Percy Liang. Understanding black-box predictions via influence functions. In *ICML*, 2017.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *NIPS*. 2017.

Lillian Lee. Measures of distributional similarity. In *ACL*, 1999.

David D. Lewis and William A. Gale. A sequential algorithm for training text classifiers. In *SIGIR*, 1994.

Hyeonwoo Noh, Andre Araujo, Jack Sim, Tobias Weyand, and Bohyung Han. Large-scale image retrieval with attentive deep local features. *ICCV*, 2017.

Mengye Ren, Wenyuan Zeng, Bin Yang, and Raquel Urtasun. Learning to reweight examples for robust deep learning. In *ICML*, 2018.

Ozan Sener and Silvio Savarese. Active learning for convolutional neural networks: A core-set approach. In *ICLR*, 2018.

Burr Settles. Active learning literature survey. Technical report, 2010.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. In *ICLR*, 2014.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *ICML*, 2017.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *NIPS*. 2017.

Kailas Vodrahalli, Ke Li, and Jitendra Malik. Are all training examples created equal? an empirical study. *arXiv preprint arXiv:1811.12569*, 2018.

Keze Wang, Dongyu Zhang, Ya Li, Ruimao Zhang, and Liang Lin. Cost-Effective active learning for deep image classification. *IEEE Transactions on Circuits and Systems for Video Technology*, 2017.

Wengang Zhou, Houqiang Li, and Qi Tian. Recent advance in content-based image retrieval: A literature survey. *arXiv preprint arXiv:1706.06064*, 2017.