An Efficient Bayesian Data Augmentation Approach for Gradient-Bias Mitigation in Contrastive Learning

Abstract

Contrastive learning (CL) has been the de facto technique for self-supervised representation learning (SSL), with impressive empirical success such as multi-modal representation learning. However, traditional CL loss only considers negative samples from a minibatch, which could cause biased gradients due to the non-decomposibility of the loss. For the first time, we consider optimizing a more generalized contrastive loss, where each data sample is associated with an infinite number of negative samples. We show that directly using minibatch stochastic optimization could lead to gradient bias. To remedy this, we propose an efficient Bayesian data augmentation technique to augment the contrastive loss into a decomposable one, where standard stochastic optimization can be directly applied without gradient bias. Specifically, our augmented loss defines a joint distribution over the model parameters and the augmented parameters, which can be conveniently optimized by a proposed stochastic expectation-maximization algorithm. Our framework is more general and is related to several popular SSL algorithms. We verify our framework on both small scale models and several large foundation models, including SSL of ImageNet and SSL for vision-language representation learning. Experiment results indicate the existence of gradient bias in all cases, and demonstrate the effectiveness of the proposed method on improving previous state of the arts. Remarkably, our method can outperform the strong MoCo-v3 under the same hyper-parameter setting, with only around half of the minibatch size.

1 Introduction

Recent years have seen significant developments and applications of contrastive learning (CL), a promising self-supervised learning (SSL) technique, to a variety of striking research breakthroughs such as learning of *multi-modal* foundation models [5] in text and image domains [42, 59, 63] for natural-language and vision-language representation learning. In addition, CL has also be applied recently to other scenarios such as supervised learning [29] and reinforcement learning [3, 33]. The main idea of CL is to define a *contrastive loss* where each data sample is entangled with both its positive and negative data samples, and optimize it to learn transformation-invariant features to better discriminate positive samples from negative ones. From a technical perspective, the contrastive loss is *non-decomposable*, in the sense that each data sample is coupled with all the other samples in the loss function, *i.e.*, to process one data sample, one has to get access to all its positive and negative samples from the other data samples. This is intractable when considering a more general CL setting where the number of negative samples are unbounded (potentially infinite). In this case, if stochastic optimization is applied, only negative samples in the current minibatch are available. Thus, this could lead to biased gradients and consequently sub-optimal solutions (see Section 2.1 for a formal statement), which is also evidenced in several existing works [18, 21].

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

A straightforward approach to overcoming the issue is to define some decomposable loss functions for learning. For example, based on spectral theory, [24] proposes spectral contrastive learning, which defines the loss as the difference between positive and negative similarity scores. Furthermore, negative-sample-free SSL methods such as BYOL [21] and SimSiam [14] deal with this problem by completely dropping the negative samples. These methods, however, are developed from quite different perspective and are not equivalent to the standard contrastive learning, *e.g.*, SimCLR that adopts the info-NCE loss [11]. Since standard contrastive learning has been shown to be relatively robust and easier to scale up to large foundation models [5] such as CLIP and its variants [41, 56, 59, 63], it is important to study its equivalent form in terms of a decomposable loss, and understand what benefits can be brought by this new form to further boost model performance.

To this end, we propose an equivalent conditional decomposable form of the standard contrastive learning, by leveraging the well developed Bayesian data augmentation technique from the Bayesian learning community [37]. The basic idea of Bayesian data augmentation is to augment a difficult-to-handle distribution to an easier one by augmenting the parameter space with auxiliary random variables, also known as *auxiliary data* [35] as each of them is associated with one data point. When applying it to contrastive learning, each positive data pair will be associated with an auxiliary variable/data*, allowing one to define a joint distribution over the model parameters and the auxiliary data. Conditioned on the auxiliary random variables, the potentially infinite negative samples will be separated from each other without introducing bias, thus making a decomposable loss (details in Section 2.2.2). To learn from the proposed decomposable contrastive loss, we then propose a new stochastic expectation-maximization (sEM) framework for maximal likelihood estimation (MLE) of the joint distribution. Specifically, with the proposed augmentation technique, the auxiliary random variables enjoy simple Gamma posterior distributions, conditioned on which the model parameter can be easily optimized by stochastic gradient descent. To summarize, our contributions include:

- We propose an equivalent augmented form of the standard contrastive loss from a probability perspective, which enjoys conditional decomposibility for unbiased stochastic optimization.

- We propose an efficient sEM algorithm for MLE of the joint distribution over model parameters and augmented data, which only needs minimal modifications based on various contrastive-loss optimization procedures such as SimCLR [11] and MoCo-v3 [12].

- We verify our framework with extensive experiments in large-scale foundation models, including the uni-modal ImageNet and multi-modal vision-language representation learning. Experimental results suggests that, with the ability of gradient-bias mitigation, our framework can improve the current CL-based state of the arts.

2 Decomposing Contrastive Learning

2.1 Setup & Gradient Bias in Contrastive Learning

In CL, a backbone network, parameterized by $\boldsymbol{\theta}$, is used for feature extraction/encoding. Given an input $\mathbf{x}$, the feature extractor outputs its representation, written as $\mathbf{z} = \mathsf{enc}(\mathbf{x}; \boldsymbol{\theta})$. The basic idea of CL is to maximize the representation similarities between positive data pairs while minimizing those of negative pairs. Formally, we are given an unlabeled dataset $\mathcal{D} \triangleq \{\mathbf{x}_i\}$. Each $\mathbf{x}_i \in \mathcal{D}$ will be applied a set of transformations to form an implicit augmented dataset $\tilde{\mathcal{D}} \triangleq \{(\mathbf{x}_i, \{\mathbf{x}_i^a\}_a)\}_i$, where $\mathbf{x}_i^a \sim t(\mathbf{x}_i)$ and $t \sim \mathcal{T}$ is a sampled transformation function from the transformation family $\mathcal{T}$. A positive pair is represented as $(\mathbf{x}_i, \mathbf{x}_i^a)$ for $\forall a$; and a negative pair is represented as $(\mathbf{x}_i, \mathbf{x}_j)$ or $(\mathbf{x}_i, \mathbf{x}_j^a)$ for $i \neq j$. For both positive and negative pairs, the data points will be fed to the encoder and similarity scores will be calculated based on their representations. For notation simplicity, we will index positive similarity scores by '$j+$' and negative similarity scores by $k-$, *e.g.*, we use $s_{ij+} \triangleq \mathsf{sim}(\mathsf{enc}(\mathbf{x}_i; \boldsymbol{\theta}), \mathsf{enc}(\mathbf{x}_i^a; \boldsymbol{\theta}))$ to denote the similarity score between $\mathbf{x}_i$ and its j-th positive data point from $\{\mathbf{x}_i^a\}$, where $\mathsf{sim}(\cdot, \cdot)$ denotes a positive similarity metric such as the exponential cosine similarity used in most contrastive learning methods (which we use unless explicitly stated); similarly, s_{ik-} is used to denote the similarity score between $\mathbf{x}_i$ and one of its negative data point. Note the similarity scores depend on $\boldsymbol{\theta}$, but is omitted in the representation for notation simplicity. In theory, each data point $\mathbf{x}_i$ should be associated with an infinite number of negative pairs due to the

---

*We will use auxiliary (random) variable and auxiliary data interchangeably without distinction, as they are equivalently used in the Bayesian data augmentation community.

availability of arbitrary transformation functions. Thus, we consider one of the most general form of contrastive loss with N_i positive pairs and infinite negative pairs for each $\mathbf{x}_i$, formulated as[†]:

$$\mathcal{L}_{\text{con}}(\mathcal{D}; \boldsymbol{\theta}) = -\frac{1}{|\mathcal{D}|} \sum_{\mathbf{x}_i \in \mathcal{D}} \log(\mathcal{L}_{\mathbf{x}_i}), \text{ with } \mathcal{L}_{\mathbf{x}_i} \triangleq \frac{1}{N_i} \sum_j \frac{s_{ij+}}{s_{ij+} + \sum_{k=1}^{\infty} s_{ik-}} . \quad (1)$$

A practical setting is to consider one single positive sample in each $\mathcal{L}_{\mathbf{x}_i}$, *i.e.*, $N_i = 1$, giving us a slightly simpler **sub-loss** $\mathcal{L}_{\mathbf{x}_i} \triangleq \frac{s_{i+}}{s_{i+} + \sum_{k=1}^{\infty} s_{ik-}}$, where the positive similarity score is written as s_{i+} for notation simplicity. *We will consider this simpler case in our following development*, although generalizing it to the more general case of N_i positive pairs is straightforward.

Gradient Bias Note the general CL loss (1) is intractable for direct optimization due to the infinite number of negative pairs for each data point. For practical feasibility, a common trick is to replace the infinite negative pairs with only those within a minibatch. This gives us an approximation of $\mathcal{L}_{\mathbf{x}_i}$ as $\tilde{\mathcal{L}}_{\mathbf{x}_i} \triangleq \frac{s_{i+}}{s_{i+} + \sum_{k=1}^{B} s_{ik-}}$ where B denotes the minibatch size. We argue that this approximation is biased due to the *non-decomposibility* nature of the standard CL loss $\mathcal{L}_{\text{con}}$, in the sense that the individual loss $\mathcal{L}_{\text{con}}$ is associated with the negative samples that distribute across the whole data $\tilde{\mathcal{D}}$. In other words, the overall loss $\mathcal{L}_{\text{con}}$ cannot be decomposed into a sum over independent sub-losses. Importantly, non-decomposibility indicates that $\mathcal{L}_{\mathbf{x}_i} \neq \mathbb{E}\left[\tilde{\mathcal{L}}_{\mathbf{x}_i}\right]$, and

Figure 1: Trajectories of 10 random runs. Direct optimization (Direct-Opt, blue) fails to converge with heavy noise; whereas our method (red) can handle the noise and converges to the same optimal solution.

consequently, $\nabla_{\boldsymbol{\theta}} \mathcal{L}_{\mathbf{x}_i} \neq \nabla_{\boldsymbol{\theta}} \mathbb{E}\left[\tilde{\mathcal{L}}_{\mathbf{x}_i}\right]$, where both the expectations are taken over the randomness of minibaching. Thus, using negative samples from a minibatch can cause *gradient bias* with minibatch stochastic optimization, leading to sub-optimal solutions. We demonstrate the problem with a simple synthetic experiment, where we try to optimize the simplest CL form of $s_1/(s_1 + s_2)$ over $s_1 > 0$ and $s_2 > 0$. We inject noise into the denominator to mimic stochastic optimization, resulting in a stochastic objective of $s_1/(s_1 + s_2 + \delta_t)$ in each SGD iteration, where δ is a random zero-mean Gaussian noise with variance set to 0.2. We compare direct optimization with SGD and our method (introduced below) on 10 random runs, starting from different initializations. The learning curves are plotted in Figure 1. It is observed that direct optimization diverges on different runs due to the high injected noise, whereas our method can always converge to the same optimum with loss = 1. To further demonstrate the consequence of gradient bias, we inject noise of variance 0.1 and use a learning rate of 0.2 (other settings lead to similar conclusions) to run optimization until converged (around 500 steps). To guarantee a unique optimal solution, we introduce a regularizer of $0.1 \times (s_1^2 + s_2^2)$. At convergence, our method gives $s_1 = 2.97$, $s_2 = 0.34$, whereas direct optimization gives $s_1 = 0.15$, $s_2 = 0.04$, indicating a sub-optimal solution from direct optimization.

In the literature, a common practice to mitigate the gradient bias problem is to use large batch sizes, which has been demonstrated to be necessary by existing works [11]. Although there are also some preliminary works trying to mitigate the negative impact of minibatches [57, 4, 60], whether they can mitigate gradient bias is not totally clear. Our method deals with this problem from a principled Bayesian perspective with a new efficient Bayesian data augmentation technique.

2.2 Decomposable Contrastive Learning

2.2.1 The Overall Algorithm

We first present our overall algorithm, then detail the derivations in the following sections. Our algorithm is illustrated in Algorithm 1, which is very simple and intuitive. The algorithm mainly consists of the following steps: 1) Load a minibatch, and calculate the similarity scores (same as standard CL); 2) Estimate the so-called auxiliary data $\mathbf{U}$, which will be used to adaptively weight the negative data in the minibatch (see loss_1) to achieve gradient bias elimination; 3) Construct the total loss, which consists of a decomposable loss loss_1 and a smoothing loss loss_2 (coming from

---

[†]One can also consider infinite positive pairs, which can also be naturally fit into our framework.

137 the stochastic EM algorithm described below), which we reformulate so that it is equivalent to the
138 standard minibatch info-NCE loss [11]; 4) Optimize the loss to update the encoder backbone.

2.2.2 Decomposing Contrastive Loss with Bayesian Data Augmentation

140 The basic idea is to lever-
141 age Bayesian data augmen-
142 tation techniques [37] to dis-
143 entangle the infinite nega-
144 tive similarity scores in the
145 denominator of (1). Orig-
146 inally, Bayesian data aug-
147 mentation augments a com-
148 plicated target distribution[‡]
149 $p(\mathbf{x})$ (*e.g.*, some posterior
150 distribution of interest) to
151 a more well-behaved aug-
152 mented distribution $p(\mathbf{x}, u)$
153 with an auxiliary random
154 variable u; one can then
155 directly deal with the aug-
156 mented distribution $p(\mathbf{x}, u)$
157 instead of the original $p(\mathbf{x})$.
158 For example, instead of
159 maximizing $p(\mathbf{x})$, one can

Algorithm 1 Decomposable Contrastive Learning

1: # enc($\cdot$): encoder backbone to extract features
2: # $(\lambda_1, \cdots, \lambda_t, \cdots)$: A decreasing sequence in $[0, 1]$
3: $t = 1$
4: **for** $\mathbf{x}$ in loader **do**   ▷ load a minibatch $\mathbf{x}$ with B samples
5:     $\mathbf{x}_1, \mathbf{x}_2 = \text{aug}(\mathbf{x}), \text{aug}(\mathbf{x})$ ▷ augmentation
6:     Calculate positive/negative similarity scores
       $(\mathbf{s}^+)_i \triangleq s_{i+}$ (vector) and $(\mathbf{S}^-)_{ik} \triangleq s_{ik-}$ (matrix)
7:     Estimate auxiliary variable/data $\mathbf{U}$ (vector) as
       described in Section 2.2.3
8:     loss_1 $= (\mathbf{U} * (\mathbf{S}^- .\text{mean}(\text{dim} = -1)) - \log(\mathbf{s}^+)).\text{mean}()$
       ▷ decomposable contrastive loss
9:     loss_2 $= (\log(\mathbf{S}^- .\text{sum}(\text{dim} = -1)) - \log(\mathbf{s}^+)).\text{mean}()$ ▷
       a smoothing loss induced from the stochastic EM principle
10:    loss $= \lambda_t \times$ loss_1 $+ (1 - \lambda_t) \times$ loss_2
11:    loss.backward()   ▷ update the encoder backbone
12:    $t = t + 1$
13: **end for**

---

160 maximize $p(\mathbf{x}, u)$ w.r.t. $\mathbf{x}$ instead. This will yield equivalent solutions while obtaining the conve-
161 nience of dealing with an easier distribution $p(\mathbf{x}, u)$. One important requirement is to guarantee the
162 augmented problem equivalent to the original one. In other words, the augmented distribution must
163 satisfy: 1) the marginal distribution should recover the original distribution by marginalization, *i.e.*,
164 $\int_u p(\mathbf{x}, u)\mathrm{d}u = p(\mathbf{x})$; and 2) the augmented distribution is much easier to handle, *e.g.*, for MLE.

165 We adopt this general idea to augment the contrastive loss and make it conditional decomposable.
166 In other words, our goal is to construct an augmented objective, denoted as $\mathcal{L}_{\text{dcon}}(\mathcal{D}, \mathbf{U}; \boldsymbol{\theta})$ with
167 auxiliary data $\mathbf{U}$, such that $\mathbb{E}_{\mathbf{U}}[\mathcal{L}_{\text{dcon}}(\mathcal{D}, \mathbf{U}); \boldsymbol{\theta}] = \mathcal{L}_{\text{con}}(\mathcal{D}; \boldsymbol{\theta})$, and $\mathcal{L}_{\text{dcon}}(\mathcal{D}, \mathbf{U}; \boldsymbol{\theta})$ is expected to
168 decouple negative samples given the auxiliary data $\mathbf{U}$. The main challenge then comes to dealing
169 with the entangling denominator of $\mathcal{L}_{\mathbf{x}_i}$. This can be achieved by applying the Gamma identity, *i.e.*,
170 $\frac{1}{\beta^\alpha} \propto \int u^{\alpha-1} e^{-\beta u} \mathrm{d}u$. Specifically, we augment the denominator in the original contrastive loss into
171 an exponential form, and defines a joint distribution $p(\boldsymbol{\theta}, \mathbf{U} | \mathcal{D})$ over the model parameter $\boldsymbol{\theta}$ and the
172 augmented data $\mathbf{U} \triangleq \{\mathbf{u}_i\}_i$, where each $\mathbf{u}_i$ is associated with a data sample $\mathbf{x}_i \in \mathcal{D}$:

$$p(\theta, \mathbf{U} | \mathcal{D}) \propto \prod_{i: \mathbf{x}_i \in \mathcal{D}} s_{i+} e^{-\mathbf{u}_i \, s_{i+}} \prod_k e^{-u_i s_{ik-}} \,, \tag{2}$$

173 **Theorem 1.** *The joint distribution* (2) *is a valid augmented distribution, i.e., marginalizing the*
174 *augmented variable* $\mathbf{U}$ *recovers the original contrastive loss* (1) *up to some constant.*

175 **Constructing a Decomposable Loss**   With the probability interpretation of the contrastive loss in
176 (2), we can apply maximal likelihood estimation to optimize the model parameter $\boldsymbol{\theta}$. Note the aug-
177 mented random variables have simple Gamma conditional distributions, which can be easily sampled
178 from. To this end, we will propose an effective approximate method via *stochastic expectation-*
179 *maximization* to optimize the joint distribution in Section 2.2.3. In the following, we first derive
180 the decomposable loss from (2). Suppose there are K negative samples for each data sample $\mathbf{x}_i$,
181 where $K = \infty$ represents the population-loss setting. Note by scaling $\mathbf{u}_i$ to $K \mathbf{u}_i$, (2) is equivalent
182 to $p(\theta, \mathbf{U} | \mathcal{D}) \propto \prod_{i: \mathbf{x}_i \in \mathcal{D}} s_{i+} e^{-\mathbf{u}_i \frac{1}{K} s_{i+}} \prod_k e^{-u_i \frac{1}{K} s_{ik-}}$. Conditioning on $\mathbf{U}$ and taking negative
183 logarithm on both sides of $p(\theta, \mathbf{U} | \mathcal{D})$ give us a new augmented loss:

$$\mathcal{L}_{\text{dcon}} \triangleq \sum_{i: \mathbf{x}_i \in \mathcal{D}} \mathbf{u}_i \left(\frac{1}{K} s_{i+} + \frac{1}{K} \sum_{k=1}^K s_{ik-} \right) - \log(s_{i+}) \xrightarrow{K \to \infty} \sum_{i: \mathbf{x}_i \in \mathcal{D}} \mathbf{u}_i \, \mathbb{E} [s_{ik-}] - \log(s_{i+}) \,, \tag{3}$$

184 where the expectation is taken over the distribution of negative samples of $\mathbf{x}_i$.

[‡]The $\mathbf{x}$ and the following $p(\mathbf{x})$ and $p(\mathbf{x}, u)$ are a bit different in meaning from those in our contrastive-learning
setting. These notation are only used **in this paragraph** to explain the idea of Bayesian data augmentation.

On Decomposibility Following the literature such as [28], we define decomposable loss as a loss $\mathcal{L}(\tilde{\mathcal{D}})$ such that $\mathcal{L}(\tilde{\mathcal{D}}) = \sum_{\tilde{\mathbf{x}}_i \in \tilde{\mathcal{D}}} \mathcal{L}_i(\tilde{\mathbf{x}}_i)$ for some dataset $\tilde{\mathcal{D}}$, *i.e.*, the sub-loss $\mathcal{L}_i$ only depends on the single data point $\tilde{\mathbf{x}}_i$. To prove our loss (3) is decomposable for a given $\mathbf{U}$, we first construct an augmented dataset $\tilde{D}' \triangleq \{\mathbf{x}_i, \mathbf{x}_i^+, \mathbf{x}_i^-\}$ from the original dataset $\mathcal{D} \triangleq \{\mathbf{x}_i\}$ and the data augmentation family $\mathcal{T}$ as follows: 1) Randomly sample a data sample $\mathbf{x}_i \sim \mathcal{D}$; 2) Randomly sample a transformation function $t \sim \mathcal{T}$ and apply it to $\mathbf{x}_i$ to generate a positive sample $\mathbf{x}_i^+ = t(\mathbf{x}_i)$; 3) Randomly sample another data sample $\mathbf{x}' \sim \mathcal{D}$ excluding $\mathbf{x}_i$; 4) Randomly sample a transformation function $t' \sim \mathcal{T}$ and apply it to $\mathbf{x}'$ to generate a negative sample $\mathbf{x}_i^- = t'(\mathbf{x}')$. From the construction, it is clear that each data points $\tilde{\mathbf{x}}_i' \triangleq (\mathbf{x}_i, \mathbf{x}_i^+, \mathbf{x}_i^-)$ in the new augmented dataset $\tilde{\mathcal{D}}'$ are identical independently distributed, and thus (3) is equivalent to $\mathcal{L}'_{\text{dcon}} \triangleq \sum_{i:\mathbf{x}_i' \in \tilde{\mathcal{D}}} (\mathbf{u}_i \, s_{ik-} - \log(s_{i+})) \triangleq \sum_{i:\mathbf{x}_i' \in \tilde{\mathcal{D}}} \mathcal{L}'_i$ under the $K \to \infty$ and infinite data limit. Since it is easily verified that the sub-losses $\mathcal{L}'_i$'s are independent from each other, our new loss (3) is thus a valid decomposable loss. Consequently, conditioned on $\mathbf{U}$, one can safely apply stochastic optimization, where, at each iteration, a random minibatch of data is sampled from $\tilde{\mathcal{D}}'$ (which can be constructed from a minibatch of the original data $\mathcal{D}$) and used to evaluate the stochastic gradients from (3) for parameter updates. To conclude, we have:

Corollary 2. *Given the auxiliary variable* $\mathbf{U}$*, the new contrastive loss* (3) *is decomposable. And thus using minibatches for stochastic optimization maintains unbiased stochastic gradients.*

2.2.3 Solving by Stochastic Expectation-Maximization

We adopt the MLE principle on the augmented joint distribution for model learning. Because the augmented variables $\mathbf{U}$ are local random variables that are associated to the original data, it is unwise to directly optimize them in the same way as the global model parameter $\boldsymbol{\theta}$. We advocate that stochastic expectation-maximization (sEM) is a natural fit to this problem, as the conditional distribution of $\mathbf{U}$ follows a simple Gamma distribution, which allows one to easily get samples from. There are different variants of sEM algorithms [2, 9, 15]. We adapt the method introduced in [2], and propose an efficient sEM variant to solve our problem. Specifically, based on our decomposable form of the contrastive loss, we define a joint distribution $p(\boldsymbol{\theta}, \mathbf{U} \,|\, \tilde{\mathcal{D}}')$ over $(\boldsymbol{\theta}, \mathbf{U})$ based on the augmented dataset $\tilde{\mathcal{D}}'$. Since $\tilde{\mathcal{D}}'$ is of infinite size, we will apply stochastic optimization to optimize $\log p(\boldsymbol{\theta}, \mathbf{U} \,|\, \tilde{\mathcal{D}}'_t)$ in each iteration t, where $\tilde{\mathcal{D}}'_t$ is a minibatch randomly sampled in this iteration. Standard stochastic optimization theory implies such a stochastic approximation step would converge under some standard conditions [6]. The problem now reduces to optimizing $\log p(\boldsymbol{\theta}, \mathbf{U} \,|\, \tilde{\mathcal{D}}'_t)$ in each iteration. To this end, we adopt the sEM algorithm proposed in [2], which is used to maximize a joint likelihood of a latent variable model relying only on samples of the latent variables. Specifically, with our notation and t indexing iteration, the algorithm consists of the following steps in each iteration: 1) *Simulation*: sample the auxiliary data $\mathbf{U}_t$ from their approximate posterior distribution; 2) *Stochastic approxiation*: update a stochastic objective as $Q_{t+1}(\boldsymbol{\theta}) = Q_t(\boldsymbol{\theta}) + \lambda_t(\log p(\boldsymbol{\theta}, \mathbf{U}_t \,|\, \tilde{\mathcal{D}}'_t) - Q_t(\boldsymbol{\theta}))$; 3) *Maximization*: maximize $Q_{t+1}(\boldsymbol{\theta})$. Based on the general algorithm, we make a few adjustments of this basic framework to adopt to our setting, and elaborate on the three steps in the following:

Simulation This corresponds to simulating the auxiliary data $\mathbf{U}_t$ for the current minibatch. After scaling $\mathbf{u}_i$ by K and taking the $K \to \infty$ limit on (2), it is known that the posterior distribution of $\mathbf{u}_i$ follows: $p(\mathbf{u}_i \,|\, \boldsymbol{\theta}, \mathcal{D}) = \mathsf{Gamma}(1, \mathbb{E}[s_{ik-}])$. Unfortunately, the exact value of the rate parameter $\mathbb{E}[s_{ik-}]$ is intractable, hindering exact simulation from its Gamma posterior. Thanks to the theory in [2, Theorem 3], if one can construct a sequence of approximate distributions $(\tilde{q}_1(\mathbf{u}_i), \cdots, \tilde{q}_t(\mathbf{u}_i), \cdots)$ such that the sequence converges in mean to $p(\mathbf{u}_i \,|\, \boldsymbol{\theta}, \mathcal{D})$, then sampling from these $(\tilde{q}_t(\mathbf{u}_i))$ can also gaurantee convergence of the algorithm. To this end, we propose two methods to construct a sequence of rate parameters to approximate $\mathbb{E}[s_{ik-}]$ of the Gamma posterior $p(\mathbf{u}_i \,|\, \boldsymbol{\theta}, \mathcal{D})$: 1) Maintain a global buffer to store the average similarities score $\frac{1}{K} \sum_k s_{ik-}$ for each $\mathbf{u}_i$, which is then updated by moving averages over the minibatches; 2) Directly use the momentum network to calculate the average similarity scores from the current minibatch to approximate the grund-true expected similarity scores. Note this strategy can be directly applied to models with a momentum network such as MoCo [12] without any architecture changes. In both ways, the rate parameters of the Gamma posteriors are expected to converge to the expectation of the corresponding similarity scores.

Stochastic Approximation According to the description above, the stochastic objective contains two terms: $Q_t(\boldsymbol{\theta})$ and $\log p(\boldsymbol{\theta}, \mathbf{U}_t \,|\, \tilde{\mathcal{D}}'_t)$. The latter endows a convenient form, which has the same expression as (3) but with expectation evaluated on the current minibatch. The term $Q_t(\boldsymbol{\theta})$ has the same form as $\log p(\boldsymbol{\theta}, \mathbf{U}_t \,|\, \tilde{\mathcal{D}}'_t)$, but with statistics taken from previous iterations (Loss_1 in

240 Algorithm 1). For optimization convenience and algorithm stability, we marginalize out the auxiliary
241 data $\mathbf{U}$ from previous iterations, giving us the same info-NCE loss evaluated on a minibatch (Loss_2
242 in Algorithm 1), as in standard contrastive learning.

243 **Maximization**   Once $Q_{t+1}(\boldsymbol{\theta})$ is constructed, which is in the form of a weighted average between
244 the info-NCE loss and $\log p(\boldsymbol{\theta}, \mathbf{U}_t \mid \tilde{\mathcal{D}}'_t)$ as explained above, optimization can be done in the same
245 way as the standard CL, *e.g.*, by adopting the same optimization algorithms and hyperparameters.

246 More detailed explanation and derivations of the proposed sEM algorithm can be found in the
247 Appendix C. Compared to standard contrastive learning, our method has an extra step of estimating
248 the auxiliary variables $\mathbf{U}$. This additional computational cost for $\mathbf{U}$ is negligible relative to the
249 computation of other parts, *e.g.*, the back-propagation step. Empirically, we also observe almost the
250 same computational speed of our method compared to the standard contrastive learning.

2.2.4 Generalization Bound

252 By extending the techniques in [24], we study the finite sample generalization bound of the proposed
253 decomposable contrastive loss. Let $\mathcal{F}$ be a hypothesis class containing feature extractors from the
254 data space $\mathcal{X}$ to feature space $\mathbb{R}^k$. Similar to [24], we extend Rademacher complexity [46] to function
255 classes with high-dimensional outputs, and define the Rademacher complexity of $\mathcal{F}$ on n data as
256 $\widehat{\mathcal{R}}_n(\mathcal{F}) := \max_{x_1, \cdots, x_n \in \mathcal{X}} \mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}, i \in [k]} \frac{1}{n} \left(\sum_{j=1}^n \sigma_j f_i(x_j) \right) \right]$, where σ is a uniform random
257 vector in $\{-1, 1\}^n$ and $f_i(z)$ is the i-th dimension of $f(z)$. Note in CL, the function f is typically
258 normalized, meaning $\widehat{\mathcal{R}}_n(\mathcal{F})$ is controllable, *e.g.*, it is typically less than or equal to one.

259 For conciseness, we slightly overload some of the previously defined notation. Let $f^*_{\text{pop}} \in \mathcal{F}$ be a
260 minimizer of the loss $\mathcal{L}_{\text{con}}(f)$ on infinite data, called population loss; and let $\mathcal{L}_{\text{dcon}}$ denote the loss of
261 (3) on a finite dataset $\mathcal{D}$, called empirical loss. Since $\mathcal{L}_{\text{dcon}}$ is an unbiased estimator of the population
262 loss $\mathcal{L}_{\text{con}}$, we can derive generalization bounds via off-the-shelf concentration inequalities.

263 **Assumption 1.** *(Realizability) At least one of the global minima of $\mathcal{L}_{con}(f)$ belongs to $\mathcal{F}$.*

264 The following theorem bounds the population loss of a feature extractor trained on finite data.

265 **Theorem 3.** *Assume $\|f(x)\|_\infty \leq \kappa$ for some $\kappa > 0$ and for all $f \in \mathcal{F}$, $x \in \mathcal{X}$. Let $f^*_{pop} \in \mathcal{F}$*
266 *be a minimizer of the population loss $\mathcal{L}_{con}(f)$. Given a random dataset of size n, let $\hat{f}_{\text{emp}} \in \mathcal{F}$*
267 *be a minimizer of the empirical loss $\mathcal{L}_{dcon}$. Denote $a \lesssim b$ as $a \leq Cb$ for some constant C. Under*
268 *Assumption 1, with probability at least $1 - \delta$ over the randomness of data, the generalization loss is*
269 *bounded as*

$$\mathcal{L}_{con}\left(\hat{f}_{\text{emp}}\right) \leq \mathcal{L}_{con}\left(f^*_{\text{pop}}\right) + c_1 \cdot \widehat{\mathcal{R}}_{n/2}(\mathcal{F}) + c_2 \cdot \left(\sqrt{\frac{\log 2/\delta}{n}} + \delta \right) ,$$

270 *where constants $c_1 \lesssim k\kappa \exp(\frac{4}{\beta})$, $c_2 \lesssim k\kappa^2/\beta + \exp(\frac{2}{\beta})$, k is the featue dimension and β is the*
271 *commonly used temperature parameter in the similarity score [11, 12, 24].*

3   Related Work

273 We discuss the most related research in this section. A more complete list of related works is provided
274 in Section A in the Appendix.

275 **Spectral Contrastive Learning and Related**   The recently proposed spectral contrastive learning
276 loss [24], with our notation, can be written as: $\mathcal{L} = \sum_{i:\mathbf{x}'_i \in \tilde{\mathcal{D}}} (s_{ik-} - 2s_{i+})$. The attraction-repulsion
277 CL also shares a similar objective [62]. The main difference of ours and theirs lie on the scaling of
278 similarity scores: our method scales positive similarity scores with logarithm, and has the mechanism
279 of *adaptively* weighting the negative data. Moreover, our framework is theoretically equivalent to the
280 standard contrastive loss, whereas the above two are not.

281 **SimCLR [11]**   SimCLR is an instance of CL based on the standard info-NCE contrastive loss.
282 Since our method is independent of such specific implementation of CL, it can be directly applied to
283 SimCLR by replacing the loss. We will demonstrate our method within SimCLR in the experiments.

284 **MoCo**   The MoCo family, especially the recent MoCo-v3 [12], represents a strong baseline for
285 contrastive learning. Similar to the SimCLR case, we can also directly replace the original MoCo
286 contrastive loss with our loss, which will also be comprehensively studied in the experiments.

Negative-Sample-Free SSL   Another line of research toward SSL is via negative-sample-free methods, where only positive samples are considered, *e.g.*, BYOL [21] and SimSiam [14]. Our framework can be considered as a bridge between contrastive and non-contrstive learning methods, as the contribution of nagative samples are *adaptively* weighted by the auxiliary random variables $\mathbf{U}$. Especially, when the expected negative similarly scores become smaller (negative samples are far away), the adaptive weights will asymptotically approach zero and thus become negative-sample free.

Improved Contrastive Learning   There have been many efforts trying to improve contrastive learning from various perspectives, *e.g.*, [57] modifies the info-NCE loss to mitigate the robustness of the loss to the minibatch size; [50] shows the necessity of large batch size in contrastive training and proposed an improved method; [10] identifies the $\log$-K curve of contrastive learning and proposes an improved FlatNCE loss for fix; Other efforts include the SimSiam [14], relative predictive coding [52], Wasserstein predictive coding [25], Barlow Twins [60], VICReg [4], gradient catching [17], and *etc*. All these methods do not explicitly address the gradient bias problem. There are also some previous work considering better ways to sampling negative samples [19, 27, 44], but they still face the gradient-bias problem. *Our method provides a principled way to decouple the negative samples with Bayesian data augmentation, enabling an effective solution to mitigate gradient bias.*

4   Experiments

We first demonstrate the robustness of our method against gradient bias on small-scale problems, and then test it on large models for single-modal image and multi-modal vision-language representation learning. All the experiments are conducted on a NVIDIA A100 GPU Server. All hyperparameters are adopted from the public codebases specified below without further tuning, although we believe more improvement can be achieved by further tuning the hyper-parameters, which is left as interesting future work. *Our goal of experiments is to demonstrate the effectiveness of our method to mitigate gradient bias in contrastive learning, but not to achieve state-of-the-art results. Thus, we do not compare our method with other non-contrastive learning methods.* Code will be publicly available.

4.1   Robustness against Similarity-Score Noise

To illustrate the impact of similarity-score noise, we explore two ways to add score noise: one manually perturb similarity scores and the other adopts the intrinsic noise induced from using minibatches.

Manual Similarity-Score Noise   We gradually add Gaussian noise to the similarity scores and monitor the performance changes. We compare our method with the popular SimCLR baseline [11], where our model uses exactly the same network architecture as SimCLR. We conduct experiments on the popular CIFAR-10 dataset, and implement our method based on the publicly available codebase [43], where we strictly follow the default hyper-parameter setting

Figure 2: Top-1 accuracy (%) with increasing similarity score noise on CIFAR-10.

without any tuning. We fix the minibatch size to 128 while varying the variance of the added Gaussian noise. The results are plotted in Figure 2. It is clear that with the noise variance increasing, the validation accuracy of SimCLR drops much more significantly than ours, demonstrating the robustness of our method to similarity-score noise.

Intrinsic Similarity-Score Noise   Next, we investigate the impact of similarity-score noise inherited from minibatches. In addition to the commonly used architecture for contrastive learning, where a normalization step is applied at the output of the backbone encoder network to project the feature representation onto a hyper-sphere, we additionally test a variant by removing the normalization step. The reason is that we find the normalization can make the impact of similarity-score noise less prominent because the representations are constrained to a much more compact sub-space. When removing the feature normalization, we adopt exponential of negative Euclidean distance as the similarity metric. We compare our method with SimCLR on the CIFAR-10 and STL datasets, and follow the default hyper-parameter settings as detailed in the codebase [43]. We vary the minibatch sizes along with different pretraining epochs. The results are shown in Table 1. It is observed that our method significantly improves over SimCLR in all cases. Particularly, the performance gap without feature normalization is more prominent, probably because the architecture is more vulnerable to similarity-score noise, as explained above. Note the Github codebase [43] gives a top-1 accuracy of

Table 1: Validation top-1 accuracies (%) on the CIFAR-10 and STL datasets.

		Normalized Feature								Unnormalized Feature							
CIFAR-10	Batch	64		128		256		512		64		128		256		512	
	Epoch	200	300	200	300	200	300	200	300	200	300	200	300	200	300	200	300
	SimCLR	79.6	81.8	81.8	83.4	83.8	85.8	84.9	86.8	73.9	74.5	75.8	76.4	76.1	76.7	77.2	77.5
	Ours	83.8	85.9	85.7	87.2	86.4	87.6	86.4	87.7	79.9	81.1	82.2	84.1	83.4	85.4	83.5	84.4
		Normalized Feature								Unnormalized Feature							
STL	Batch	64		128		256		512		64		128		256		512	
	Epoch	200	300	200	300	200	300	200	300	200	300	200	300	200	300	200	300
	SimCLR	69.8	69.7	72.1	72.9	75.6	75.7	77.4	78.1	70.6	70.2	71.8	72.1	73.8	72.8	74.1	74.2
	Ours	71.7	73.0	75.0	74.4	77.6	78.3	79.5	81.2	75.8	75.0	75.0	77.7	78.8	79.5	79.8	79.4

89.1% with a minibatch of 512 and epochs of 500. For directly comparison, we run our method with the same setting, which gives 89.9%, further demonstrating gradient bias in the large-batch setting.

4.2 Single-Modal Image Representation Learning

We then evaluate our framework on foundation models for large-scale image representation learning. We adopt MoCo-V3 [12], one of the recent state-of-the-art method, as our baseline. We strictly follow the default settings as in the publicly available codebase [13] without further tuning, except replacing the original contrastive learning loss with our method. We run the models on the public ImageNet-1K dataset, and test it with different minibatch sizes, ranging among 128, 256 and 512. Note the reported results in the original paper are based on very large batchsizes such as 1024 and 4096, which we were not able to test them due to the time and computation constraint. But we do fine our method can match those results with smaller batch sizes. Similar to the original paper, we test our method with different encoder backbones including ResNet50, ViT-Small and ViT-Base. For evaluation, we finetune the pretrained models for downstream image classification on the ImageNet-1K validation data. We also test the generalization ability of the pretrained models by conducting transfer learning on the CIFAR-10, CIFAR-100, Flowers and Pets datasets, funetuning from the pretrained checkpoints.

Validation on ImageNet We evaluate the performance on ImageNet in terms of kNN and linear probing classification accuracy on different checkpoints. For kNN evaluation, we follow previous work [34] by simply performing k-nearest neighbor classification in the embedding feature space, where k is set to 10, 20 and 100, respectively. For linear probing, we following [12] by fixing the pretrained weights of the backbone network and supervised finetuning an added linear layer. We adopt the standard top-1 and top-5 accuracies on the validation data. The final results are summarized in Table 2. It is observed that our method outperforms MoCo-v3 in all cases. Remarkably, on the ViT-Base/16 atchitecture, it slightly outperforms the CL-based art, achieving a top-1 accuracy of 68.9% and 76.8%, respectively, in terms of kNN and linear probing, but with around half of the minibatch size compared to previous art (67.8% and 76.7% of MoCo-v3 [12, 13]). Note only the last row in the table is directly comparable to the numbers in the official Github. All the other results use smaller batch sizes.

Transfer Learning We transfer the pretrained checkpoints and prepare the datasets by strictly following the instructions from the MoCo-v3 website [13]. Similarly, we use the default settings for the experiments. The results are summarized in Table 3. Consistent with previous findings [12], due to the sizes of these downstream tasks, the performance gaps between different methods are not as significant as other comparisons. Nevertheless, with only around half of the batch size, our method perform similarly with previously reported state of the arts [12].

4.3 Multi-Modal Vision-Language Representation Learning

Finally, we test our framework for vision-language representation learning by adopting the publicly available Open-CLIP codebase [26]. Similarly to CLIP [42], Open-Clip uses contrastive learning to jointly embed images and the corresponding text. We follow the default setting used in the codebase to train the 3M images of the Conceptual Captions (CC) dataset [47], consisting of 2.89M training images and 13K validation images. We replace their contrastive learning algorithms (variant of SimCLR) with our method. The backbone architecture is the ResNet-50x4. To evaluate the pretrained models, we test them on the CC validation dataset, as well as applying them for zero-shot evaluate on

Table 2: Results of Pretraining on ImageNet-1K. 'a/b/c' in the kNN column are accuracies (%) with $k = 10, 20, 100$, respectively. Results indicated by "MoCo-v3 [12]" are from [13].

Methods		Batch Size: 256		Batch Size: 512		Average
		kNN	Linear	kNN	Linear	Linear
ResNet-50	MoCo-v3	49.7/50.0/48.7	59.5	56.6/57.0/55.8	68.2	63.85
	Ours	48.8/49.3/47.6	64.2	56.1/56.5/55.5	67.7	65.95
ViT-Small	MoCo-v3	50.0/50.6/49.1	62.3	54.6/54.9/53.5	66.0	64.15
	Ours	52.0/52.5/50.7	63.4	57.6/57.8/55.9	66.4	64.90
ViT-Base	MoCo-v3	59.1/59.5/57.9	68.1	61.5/61.5/60.0	70.1	69.10
	Ours	60.7/61.1/59.4	69.1	61.4/61.8/60.4	70.3	69.70
ViT-Base	Ours: Batch_Size - 2304			MoCo-v3 [12]: Batch_Size - 4096		
	kNN: **69.7/70.0/68.9**	Linear: **76.8**		kNN: 69.3/69.2/67.8	Linear: 76.7	

Table 3: Transfer learning accuracy with different checkpoints. The number appended to the end of the methods represents minibatch size; 'a/b' in our and MoCo-v3 method means top-1 and top-5 accuracies (%). "MoCo-v3 [12]" are results from [12] trained with much larger minibatch sizes.

	CIFAR-10 [32]	CIFAR-100 [32]	Flowers-102 [38]	Pets [40]	Average
Random init.	77.8	48.5	54.4	40.1	55.2
Supervised [31]	98.1	87.1	89.5	93.8	92.1
MoCo-v3-512	98.3/99.9	88.2/97.6	97.5/99.6	90.9/98.8	93.7/ 99.0
MoCo-v3-4096 [12]	98.9	90.5	97.7	93.2	95.1
Ours-512	98.4/100	89.0/98.0	97.1/99.4	90.8/99.8	93.8/99.3
Ours-2304	98.9/100.0	90.5/98.4	97.7/99.5	92.7/99.1	**95.0/99.3**

Table 4: Results on Multi-Modal Vision-Language Representation Learning on Conceptual Captions.

Methods	Text Retrieval			Image Retrieval			Val	ImageNet Zero-Shot	
	R@1↑	R@5↑	R@10↑	R@1↑	R@5↑	R@10↑	Loss	Top-1	Top-5
OpenCLIP	30.0	52.0	60.9	29.7	51.8	60.7	2.02	19.2	37.3
Ours	30.2	53.8	62.6	30.2	53.3	62.3	1.52	19.7	38.3

the ImageNet-1K validation dataset. The evaluation tasks on the CC dataset are text-to-image and image-to-text retrievals. Following previous works, we adopt R@1, R@5, R@10 and validation loss as the evaluation metrics. For zero-shot ImageNet classification, we adopt top-1 and top-5 accuracies. For computational convenience, following [26], we pretrain the model for 30 epochs. The results are summarized in Table 4. Our method gives consistently better results in all metrics, especially in the R@10 score and top-5 accuracy, validating the effectiveness of our method in gradient bias reduction.

5 Conclusion

We investigate the problem of gradient bias in infinite-negative-sample contrastive learning, by formulating it in a probability framework with Bayesian data augmentation. An efficient and simple stochastic EM algorithm is proposed, which constitutes a decomposable CL framework. Generalization theory is also developed. Experimental results on various settings, ranging from small to large models and from single to multiple modality settings, demonstrate the effectiveness of our framework. Interesting future works include investigating more accurate methods to estimate the augmented variables and improving on the multi-modal setting. Furthermore, one potential advantage of our framework is its potential for efficient distributed training, especially in the asynchronized setting, as one only needs to maintain the auxiliary data without communicating with local data.

Limitation & Potential Negative Societal Impacts This paper identify the gradient bias problem in contrastive learning and proposes efficient and effective solutions to mitigate the problem. However, better approximations are still needed to tackle the problem, *e.g.*, better methods to estimate the auxiliary data $\mathbf{U}$. Thus, there is still room to improve the proposed method. Finally, as this work is technical in nature, we do not foresee potential negative societal impacts.

References

[1] LIGHTLY benchmark. `https://docs.lightly.ai/getting_started/main_concepts.html`. Accessed: 2022-08-03.

[2] Stéphanie Allassonnière and Juliette Chevallier. A new class of stochastic em algorithms. escaping local maxima and handling intractable sampling. *Comput. Stat. Data Anal.*, 159:107159, 2021.

[3] Andrea Banino, Adria Puigdomenech Badia, Jacob C Walker, Tim Scholtes, Jovana Mitrovic, and Charles Blundell. CoBERL: Contrastive BERT for reinforcement learning. In *International Conference on Learning Representations*, 2022.

[4] Adrien Bardes, Jean Ponce, and Yann LeCun. Vicreg: Variance-invariance-covariance regularization for self-supervised learning. *ArXiv*, abs/2105.04906, 2021.

[5] Rishi Bommasani, Drew A. Hudson, Ehsan Adeli, Russ Altman, Simran Arora, Sydney von Arx, Michael S. Bernstein, Jeannette Bohg, Antoine Bosselut, Emma Brunskill, Erik Brynjolfsson, S. Buch, D. Card, Rodrigo Castellon, Niladri S. Chatterji, Annie Chen, Kathleen Creel, Jared Davis, Dora Demszky, Chris Donahue, Moussa Doumbouya, Esin Durmus, Stefano Ermon, John Etchemendy, Kawin Ethayarajh, Li Fei-Fei, Chelsea Finn, Trevor Gale, Lauren E. Gillespie, Karan Goel, Noah D. Goodman, Shelby Grossman, Neel Guha, Tatsunori Hashimoto, Peter Henderson, John Hewitt, Daniel E. Ho, Jenny Hong, Kyle Hsu, Jing Huang, Thomas F. Icard, Saahil Jain, Dan Jurafsky, Pratyusha Kalluri, Siddharth Karamcheti, Geoff Keeling, Fereshte Khani, O. Khattab, Pang Wei Koh, Mark S. Krass, Ranjay Krishna, Rohith Kuditipudi, Ananya Kumar, Faisal Ladhak, Mina Lee, Tony Lee, Jure Leskovec, Isabelle Levent, Xiang Lisa Li, Xuechen Li, Tengyu Ma, Ali Malik, Christopher D. Manning, Suvir P. Mirchandani, Eric Mitchell, Zanele Munyikwa, Suraj Nair, Avanika Narayan, Deepak Narayanan, Benjamin Newman, Allen Nie, Juan Carlos Niebles, Hamed Nilforoshan, J. F. Nyarko, Giray Ogut, Laurel Orr, Isabel Papadimitriou, Joon Sung Park, Chris Piech, Eva Portelance, Christopher Potts, Aditi Raghunathan, Robert Reich, Hongyu Ren, Frieda Rong, Yusuf H. Roohani, Camilo Ruiz, Jack Ryan, Christopher R'e, Dorsa Sadigh, Shiori Sagawa, Keshav Santhanam, Andy Shih, Krishna Parasuram Srinivasan, Alex Tamkin, Rohan Taori, Armin W. Thomas, Florian Tramèr, Rose E. Wang, William Wang, Bohan Wu, Jiajun Wu, Yuhuai Wu, Sang Michael Xie, Michihiro Yasunaga, Jiaxuan You, Matei A. Zaharia, Michael Zhang, Tianyi Zhang, Xikun Zhang, Yuhui Zhang, Lucia Zheng, Kaitlyn Zhou, and Percy Liang. On the opportunities and risks of foundation models. *ArXiv*, abs/2108.07258, 2021.

[6] Léon Bottou, Frank E. Curtis, and Jorge Nocedal. Optimization methods for large-scale machine learning. *SIAM Review*, 60(2):223–311, 2018.

[7] C. Chen. *Dependent Normalized Random Measures*. PhD thesis, The Australian National University, 2014.

[8] Changyou Chen, Vinayak A. Rao, Wray L. Buntine, and Yee Whye Teh. Dependent normalized random measures. In *ICML*, 2013.

[9] Jianfei Chen, Jun Zhu, Yee Whye Teh, and Tong Zhang. Stochastic expectation maximization with variance reduction. In *NeurIPS*, 2018.

[10] Junya Chen, Zhe Gan, Xuan Li, Qing Guo, Liqun Chen, Shuyang Gao, Tagyoung Chung, Yi Xu, Belinda Zeng, Wenlian Lu, et al. Simpler, faster, stronger: Breaking the log-k curse on contrastive learners with flatnce. *arXiv preprint arXiv:2107.01152*, 2021.

[11] Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey E. Hinton. A simple framework for contrastive learning of visual representations. *ArXiv*, abs/2002.05709, 2020.

[12] X. Chen, S. Xie, and K. He. An empirical study of training self-supervised vision transformers. In *2021 IEEE/CVF International Conference on Computer Vision (ICCV)*, pages 9620–9629, Los Alamitos, CA, USA, oct 2021. IEEE Computer Society.

[13] Xinlei Chen. Moco v3 for self-supervised resnet and vit. `https://github.com/facebookresearch/moco-v3`, 2022.

[14] Xinlei Chen and Kaiming He. Exploring simple siamese representation learning. *2021 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 15745–15753, 2021.

[15] Bernard Delyon, Marc Lavielle, and Éric Moulines. Convergence of a stochastic approximation version of the em algorithm. *Annals of Statistics*, 27:94–128, 1999.

[16] Nicholas Frosst, Nicolas Papernot, and Geoffrey E. Hinton. Analyzing and improving representations with the soft nearest neighbor loss. In *ICML*, 2019.

[17] Luyu Gao, Yunyi Zhang, Jiawei Han, and Jamie Callan. Scaling deep contrastive learning batch size under memory limited setup. In *REPL4NLP*, 2021.

[18] Yuting Gao, Jia-Xin Zhuang, Ke Li, Hao Cheng, Xiaowei Guo, Feiyue Huang, Rongrong Ji, and Xing Sun. Disco: Remedy self-supervised learning on lightweight models with distilled contrastive learning. *ArXiv*, abs/2104.09124, 2021.

[19] Songwei Ge, Shlok Kumar Mishra, Chun-Liang Li, Haohan Wang, and David Jacobs. Robust contrastive learning using negative samples with diminished semantics. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[20] Spyros Gidaris, Praveer Singh, and Nikos Komodakis. Unsupervised representation learning by predicting image rotations. *ArXiv*, abs/1803.07728, 2018.

[21] Jean-Bastien Grill, Florian Strub, Florent Altch'e, Corentin Tallec, Pierre H. Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Ávila Pires, Zhaohan Daniel Guo, Mohammad Gheshlaghi Azar, Bilal Piot, Koray Kavukcuoglu, Rémi Munos, and Michal Valko. Bootstrap your own latent: A new approach to self-supervised learning. *ArXiv*, abs/2006.07733, 2020.

[22] Michael Gutmann and Aapo Hyvärinen. Noise-contrastive estimation: A new estimation principle for unnormalized statistical models. In Yee Whye Teh and Mike Titterington, editors, *Proceedings of the Thirteenth International Conference on Artificial Intelligence and Statistics*, volume 9 of *Proceedings of Machine Learning Research*, pages 297–304, Chia Laguna Resort, Sardinia, Italy, 13–15 May 2010. PMLR.

[23] Raia Hadsell, Sumit Chopra, and Yann LeCun. Dimensionality reduction by learning an invariant mapping. *2006 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'06)*, 2:1735–1742, 2006.

[24] Jeff Z. HaoChen, Colin Wei, Adrien Gaidon, and Tengyu Ma. Provable guarantees for self-supervised deep learning with spectral contrastive loss. In A. Beygelzimer, Y. Dauphin, P. Liang, and J. Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, 2021.

[25] Kaiming He, Haoqi Fan, Yuxin Wu, Saining Xie, and Ross B. Girshick. Momentum contrast for unsupervised visual representation learning. *2020 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 9726–9735, 2020.

[26] Gabriel Ilharco, Mitchell Wortsman, Nicholas Carlini, Rohan Taori, Achal Dave, Vaishaal Shankar, Hongseok Namkoong, John Miller, Hannaneh Hajishirzi, Ali Farhadi, and Ludwig Schmidt. Openclip, July 2021. If you use this software, please cite it as below.

[27] Yannis Kalantidis, Mert Bulent Sariyildiz, Noe Pion, Philippe Weinzaepfel, and Diane Larlus. Hard negative mixing for contrastive learning. 2021.

[28] Purushottam Kar, Harikrishna Narasimhan, and Prateek Jain. Online and stochastic gradient methods for non-decomposable loss functions. In *NIPS*, 2014.

[29] Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 18661–18673. Curran Associates, Inc., 2020.

[30] Prannay Khosla, Piotr Teterwak, Chen Wang, Aaron Sarna, Yonglong Tian, Phillip Isola, Aaron Maschinot, Ce Liu, and Dilip Krishnan. Supervised contrastive learning. *ArXiv*, abs/2004.11362, 2020.

[31] Alexander Kolesnikov, Alexey Dosovitskiy, Dirk Weissenborn, Georg Heigold, Jakob Uszkoreit, Lucas Beyer, Matthias Minderer, Mostafa Dehghani, Neil Houlsby, Sylvain Gelly, Thomas Unterthiner, and Xiaohua Zhai. An image is worth 16x16 words: Transformers for image recognition at scale. 2021.

[32] Alex Krizhevsky. Learning multiple layers of features from tiny images. 2009.

[33] Michael Laskin, Aravind Srinivas, and Pieter Abbeel. Curl: Contrastive unsupervised representations for reinforcement learning. *Proceedings of the 37th International Conference on Machine Learning, Vienna, Austria, PMLR 119*, 2020. arXiv:2004.04136.

[34] Chunyuan Li, Jianwei Yang, Pengchuan Zhang, Mei Gao, Bin Xiao, Xiyang Dai, Lu Yuan, and Jianfeng Gao. Efficient self-supervised vision transformers for representation learning. In *International Conference on Learning Representations*, 2022.

[35] Xiao-Li Meng and David A. Van Dyk. Seeking efficient data augmentation schemes via conditional and marginal augmentation. *Biometrika*, 86:301–320, 1999.

[36] T.K. Moon. The expectation-maximization algorithm. *IEEE Signal Processing Magazine*, 13(6):47–60, 1996.

[37] Peter Neal and Theodore Kypraios. Exact bayesian inference via data augmentation. *Statistics and Computing*, 25:333–347, 2015.

[38] Maria-Elena Nilsback and Andrew Zisserman. Automated flower classification over a large number of classes. *2008 Sixth Indian Conference on Computer Vision, Graphics & Image Processing*, pages 722–729, 2008.

[39] Mehdi Noroozi and Paolo Favaro. Unsupervised learning of visual representations by solving jigsaw puzzles. In *ECCV*, 2016.

[40] Omkar M Parkhi, Andrea Vedaldi, Andrew Zisserman, and C. V. Jawahar. Cats and dogs. In *2012 IEEE Conference on Computer Vision and Pattern Recognition*, pages 3498–3505, 2012.

[41] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, et al. Learning transferable visual models from natural language supervision. *arXiv preprint arXiv:2103.00020*, 2021.

[42] Alec Radford, Jong Wook Kim, Chris Hallacy, Aditya Ramesh, Gabriel Goh, Sandhini Agarwal, Girish Sastry, Amanda Askell, Pamela Mishkin, Jack Clark, Gretchen Krueger, and Ilya Sutskever. Learning transferable visual models from natural language supervision. In *ICML*, 2021.

[43] Hao Ren. Simclr. `https://github.com/leftthomas/SimCLR`, 2022.

[44] Joshua David Robinson, Ching-Yao Chuang, Suvrit Sra, and Stefanie Jegelka. Contrastive learning with hard negative samples. In *International Conference on Learning Representations*, 2021.

[45] Ruslan Salakhutdinov and Geoff Hinton. Learning a nonlinear embedding by preserving class neighbourhood structure. In Marina Meila and Xiaotong Shen, editors, *Proceedings of the Eleventh International Conference on Artificial Intelligence and Statistics*, volume 2 of *Proceedings of Machine Learning Research*, pages 412–419, San Juan, Puerto Rico, 21–24 Mar 2007. PMLR.

[46] Shai Shalev-Shwartz and Shai Ben-David. *Understanding Machine Learning - From Theory to Algorithms.* Cambridge University Press, 2014.

[47] Piyush Sharma, Nan Ding, Sebastian Goodman, and Radu Soricut. Conceptual captions: A cleaned, hypernymed, image alt-text dataset for automatic image captioning. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2556–2565, Melbourne, Australia, July 2018. Association for Computational Linguistics.

[48] Kihyuk Sohn. Improved deep metric learning with multi-class n-pair loss objective. In *NIPS*, 2016.

[49] Hyun Oh Song, Yu Xiang, Stefanie Jegelka, and Silvio Savarese. Deep metric learning via lifted structured feature embedding. *2016 IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 4004–4012, 2016.

[50] Jiaming Song and Stefano Ermon. Understanding the limitations of variational mutual information estimators. In *International Conference on Learning Representations*, 2020.

[51] Yonglong Tian, Dilip Krishnan, and Phillip Isola. Contrastive multiview coding. In *ECCV*, 2020.

[52] Yao-Hung Hubert Tsai, Martin Q. Ma, Muqiao Yang, Han Zhao, Louis-Philippe Morency, and Ruslan Salakhutdinov. Self-supervised representation learning with relative predictive coding. In *International Conference on Learning Representations*, 2021.

[53] Aäron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *ArXiv*, abs/1807.03748, 2018.

[54] Kilian Q. Weinberger and Lawrence K. Saul. Distance metric learning for large margin nearest neighbor classification. In *NIPS*, 2005.

[55] Zhirong Wu, Yuanjun Xiong, Stella X. Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. *2018 IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 3733–3742, 2018.

[56] Jianwei Yang, Chengkun Li, Pengchuan Zhang, Bin Xiao, Ce Liu, Lu Yuan, and Jianfeng Gao. Unified contrastive learning in image-text-label space. *ArXiv*, abs/2204.03610, 2022.

[57] Chun-Hsiao Yeh, Cheng-Yao Hong, Yen-Chi Hsu, Tyng-Luh Liu, Yubei Chen, and Yann LeCun. Decoupled contrastive learning. *ArXiv*, abs/2110.06848, 2021.

[58] Mingzhang Yin and Mingyuan Zhou. Arm: Augment-reinforce-merge gradient for stochastic binary networks. In *ICLR*, 2019.

[59] Lu Yuan, Dongdong Chen, Yi-Ling Chen, Noel C. F. Codella, Xiyang Dai, Jianfeng Gao, Houdong Hu, Xuedong Huang, Boxin Li, Chunyuan Li, Ce Liu, Mengchen Liu, Zicheng Liu, Yumao Lu, Yu Shi, Lijuan Wang, Jianfeng Wang, Bin Xiao, Zhen Xiao, Jianwei Yang, Michael Zeng, Luowei Zhou, and Pengchuan Zhang. Florence: A new foundation model for computer vision. *ArXiv*, abs/2111.11432, 2021.

[60] Jure Zbontar, Li Jing, Ishan Misra, Yann LeCun, and Stéphane Deny. Barlow twins: Self-supervised learning via redundancy reduction. In *ICML*, 2021.

[61] Richard Zhang, Phillip Isola, and Alexei A. Efros. Colorful image colorization. In *ECCV*, 2016.

[62] Huangjie Zheng, Xu Chen, Jiangchao Yao, Hongxia Yang, Chunyuan Li, Ya Zhang, Hao Zhang, Ivor Wai-Hung Tsang, Jingren Zhou, and Mingyuan Zhou. Contrastive attraction and contrastive repulsion for representation learning. 2021.

[63] Yiwu Zhong, Jianwei Yang, Pengchuan Zhang, Chunyuan Li, Noel C. F. Codella, Liunian Harold Li, Luowei Zhou, Xiyang Dai, Lu Yuan, Yin Li, and Jianfeng Gao. Regionclip: Region-based language-image pretraining. 2021.

[64] Mingyuan Zhou and Lawrence Carin. Augment-and-conquer negative binomial processes. In *NIPS*, 2012.

[65] Mingyuan Zhou, Yulai Cong, and Bo Chen. Augmentable gamma belief networks. *J. Mach. Learn. Res.*, 17:163:1–163:44, 2016.

A More Related Work

Self-Supervised Learning   Earlier self-supervised learning approaches tries to generate pseudo labels to the unlabeled data through different transformations, such as solving jigsaw puzzles [39], colorization [61] and rotation prediction [20]. These methods, however, are typically not competitive with supervised learning. Recently, contrastive-learning based methods have been one of the main stream methods for SSL [55, 53, 51, 25, 11], which can significantly close the gap to supervised learning without relying on ground-truth labels. *Our proposed framework serves as an important addition to the SSL literature, which addresses some limitation of the standard CL and is related to several state-of-the-art SSL methods.*

Contrastive Learning   Contrastive loss functions were probably first invented for metric learning, which intends to learn similarity functions that measure the similarity between a pair of objects. Researchers have explored various contrastive loss functions, including the max-margin contrastive loss [23], triple loss [54], multi-class N-pair loss [48], lifted structure loss [49], NCE loss [22], soft-nearest neighbors loss [45, 16], NT-Xent/infor NCE loss [11, 30, 53]. All of these losses are defined in a non-decomposable way that can lead to gradient bias[§].

There have been some efforts trying to improve contrastive learning from various perspectives, *e.g.*, [57] modifies the info-NCE loss to mitigate the robustness of the loss to the minibatch size; [50] shows the necessity of large batch size in contrastive training and proposed an improved method; [10] identifies the $\log - K$ curve of contrastive learning and proposes an improved FlatNCE loss for fix; Other efforts include the SimSiam [14], relative predictive coding [52], Wasserstein predictive coding [25], Barlow Twins [60], VICReg [4], gradient catching [17], and *etc*. All these methods do not explicitly address the gradient bias problem. There are also some previous work considering better ways to sampling negative samples [19, 27, 44], but they still face the gradient-bias problem. *Our method provides a principled way to decouple the negative samples with Bayesian data augmentation, enabling an effective solution to mitigate gradient bias.*

Bayesian Data Augmentation   Bayesian data augmentation is a useful tool to facilitate sampling by augmenting complex distributions with auxiliary random variables. The techniques have found applications in many Bayesian model learning/inference problems, including but not limited to negative Binomial processes [64], Gamma belief networks [65], and stochastic binary networks [58]. More cosely related to the proposed is the Bayesian data augmentation techniques to sampling the normalized random measure, a general family of normalized random probability measures [8, 7]. *Our method adopts a similar idea to the CL setting to address one missing piece of the framework.*

B Proof of Theorem 1

Proof. For completeness, we rewrite the joint distribution $p(\boldsymbol{\theta}, \mathbf{U} \,|\, \mathcal{D})$ over the model parameter $\boldsymbol{\theta}$ and the augmented data $\mathbf{U} \triangleq \{\mathbf{u}_i\}_i$ to be optimize, where each $\mathbf{u}_i$ is associated with a data sample $\mathbf{x}_i \in \mathcal{D}$:

$$p(\theta, \mathbf{U} \,|\, \mathcal{D}) \propto \prod_{i:\mathbf{x}_i \in \mathcal{D}} s_{i+} e^{-\mathbf{u}_i \, s_{i+}} \prod_k e^{-u_i s_{ik-}} = \prod_{i:\mathbf{x}_i \in \mathcal{D}} s_{i+} e^{-\mathbf{u}_i (s_{i+} + \sum_k s_{ik-})} \,. \tag{4}$$

$\square$

Obviously, $\mathbf{u}_i$'s are independent with each other given the similarity scores. Thus, we can apply Gamma identity to each $\mathbf{u}_i$, resulting in

$$p(\boldsymbol{\theta}) = \int_{\mathbf{U}} p(\theta, \mathbf{U} \,|\, \mathcal{D}) \mathrm{d}\, \mathbf{U} \propto \prod_{i:\mathbf{x}_i \in \mathcal{D}} \int_{\mathbf{u}_i} s_{i+} e^{-\mathbf{u}_i (s_{i+} + \sum_k s_{ik-})} \mathrm{d}\, \mathbf{u}_i$$

$$= \prod_{i:\mathbf{x}_i \in \mathcal{D}} \frac{s_{i+}}{s_{i+} + \sum_k s_{ik-}} \,,$$

which concludes the proof.

[§]The max-margin contrastive loss is defined on pair-wise data, thus is less affected by the negative samples. However, the loss is shown to be less effective compared to the fully coupled NT-Xent loss [11].

C Stochastic Expectation Maximization

Using our notation, we introduce expectation maximization [36] and stochastic expectation maximization [2]. According to our development in the main text, the marginal likelihood to be optimized is defined as:

$$p(\boldsymbol{\theta}|\tilde{\mathcal{D}}') \propto \prod_{\mathbf{x}_i' \in \tilde{\mathcal{D}}'} \frac{s_{i+}}{\mathbb{E}[s_{ik-}]} \ , \tag{5}$$

which is intractable. To solve the problem, we augment the marginal distribution with auxiliary data $\mathbf{U} \triangleq \{\mathbf{u}_i\}_i$ as

$$p(\boldsymbol{\theta}, \mathbf{U}|\tilde{\mathcal{D}}') \propto \prod_{\mathbf{x}_i' \in \tilde{\mathcal{D}}'} s_{i+} e^{-\mathbf{u}_i \mathbb{E}[s_{ik-}]} \ . \tag{6}$$

The standard EM algorithm [36] corresponds to optimizing $p(\boldsymbol{\theta}|\tilde{\mathcal{D}}')$ by alternating through the following two steps:

- **Expectation**: Compute the conditional expected log-likelihood:

$$Q(\boldsymbol{\theta}|\boldsymbol{\theta}_k) = \int_{\mathbf{U}} \log p(\boldsymbol{\theta}, \mathbf{U}|\tilde{\mathcal{D}}') p(\mathbf{U}|\tilde{\mathcal{D}}'; \boldsymbol{\theta}_k) \mathrm{d}\mathbf{U} \ .$$

- **Maximization**: Maximize $\boldsymbol{\theta} \rightarrow Q(\boldsymbol{\theta}|\boldsymbol{\theta}_k)$ in the parameter space to find $\boldsymbol{\theta}_{k+1} \in \arg\max Q(\boldsymbol{\theta}|\boldsymbol{\theta}_k)$.

Unfortunately, directly applying the EM algorithm is infeasible in our setting as $\mathbf{U}$ contains an infinite number of auxiliary data, *i.e.*, $Q(\boldsymbol{\theta}|\boldsymbol{\theta}_k)$ in the expectation step is infeasible. To mitigate the problem, we adapt the stochastic EM algorithm proposed in [2], which constructs a stochastic approximation of $Q(\boldsymbol{\theta}|\boldsymbol{\theta}_k)$ in each iteration. Specifically, the algorithm contains the following steps:

- **Simulation**: Sample the auxiliary data $\mathbf{U}_t$ for the current minibatch from their approximate posterior distribution. Please refer to the "Simulation" paragraph in Section 2.2.3 for details on how to get approximate samples.

- **Stochastic approximation**: Update a stochastic objective as:

$$Q_{t+1}(\boldsymbol{\theta}) = Q_t(\boldsymbol{\theta}) + \lambda_t(\log p(\boldsymbol{\theta}, \mathbf{U}_t|\tilde{\mathcal{D}}_t') - Q_t(\boldsymbol{\theta}))$$
$$= (1 - \lambda_t)Q_t(\boldsymbol{\theta}) + \lambda_t \log p(\boldsymbol{\theta}, \mathbf{U}_t|\tilde{\mathcal{D}}_t') \ .$$

  Here $\log p(\boldsymbol{\theta}, \mathbf{U}_t|\tilde{\mathcal{D}}_t')$ adopts the same form as in (6) but only includes data samples from the current minibatch. Thus, it is feasible to evaluate. According to the recursive definition, $Q_t(\boldsymbol{\theta})$ has the same form as $\log p(\boldsymbol{\theta}, \mathbf{U}_t|\tilde{\mathcal{D}}_t')$ but is evaluated on previous minibatches. To reduced variance, we first marginalize out the corresponding auxiliary data $\mathbf{U}_{t'<t}$, resulting in the same marginal form as (5) but the expectations are only evaluated on minibatches, thus it is feasible. One problem in evaluating $Q_t(\boldsymbol{\theta})$ is that we need to store the historical minibatches, which is not storage friendly. To overcome the problem, we simply use the current minibatch to evaluate Q_k, giving us the standard minibatch info-NCE loss used in the standard contrastive learning.

- **Maximization**: Maximize $Q_{t+1}(\boldsymbol{\theta})$. We simply apply stochastic gradient descent for this step.

D Generalization

For clearness, we redefine some terms used in our proof. Consider a dataset $\widehat{\mathcal{X}} = \{\bar{x}_1, \bar{x}_2, \cdots, \bar{x}_n\}$ containing n data points i.i.d. sampled from $\mathcal{P}_{\overline{\mathcal{X}}}$. Let $\hat{\mathcal{P}}_{\mathcal{X}}$ be the uniform distribution over $\widehat{\mathcal{X}}$. Let $\hat{P}_{\bar{x}, \bar{x}'}$ be the uniform distribution over data pairs $(\bar{x}_i, \bar{x}_j)$ where $i \neq j$. Based on our algorithm

development in the main text, we define the empirical decomposable contrastive loss of a feature extractor f as

$$\mathcal{L}_{\mathrm{dcon}}(f) \triangleq \widehat{\mathcal{L}}_n(f) := - \mathbb{E}_{\bar{x} \sim \widehat{\mathcal{P}}_{\mathcal{X}}, x \sim \mathcal{A}(\cdot|\bar{x}), x' \sim \mathcal{A}(\cdot|\bar{x})} \left[f(x)^\top f(x')/\beta \right] +$$
$$\mathbb{E}_{(\bar{x}, \bar{x}') \sim \widehat{\mathcal{P}}_{\bar{x}, \bar{x}'}, x \sim (\cdot|\bar{x})} \boldsymbol{u}_{\boldsymbol{x}} \mathbb{E}_{x' \sim \mathcal{A}(\cdot|\bar{x}')} \exp \left[f(x)^\top f(x')/\beta \right],$$

where $\boldsymbol{u}_{\boldsymbol{x}} \sim \mathsf{Gamma}(1, \mathbb{E}_{x' \sim \mathcal{A}(\cdot|\bar{x}')} \exp \left[f(x)^\top f(x')/\beta \right])$

Our argument in the "On Decomposibility" paragraph in Section 2.2.2 has proved that $\widehat{\mathcal{L}}_n(f)$ is an unbiased estimator of population spectral contrastive loss, i.e.,

$$\mathbb{E}_{\widehat{\mathcal{X}}} \left[\widehat{\mathcal{L}}_n(f) \right] = \mathcal{L}(f)$$

To prove our generalization theory, motivated by [24], we construct tuples of the original dataset $\widehat{\mathcal{X}}$. Specifically, we sample a subset of tuples as follows: first sample a permutation $\pi : [n] \to [n]$, then we sample tuples $S = \left\{ (z_i, z_i^+, z_i', \boldsymbol{u_i}) \right\}_{i=1}^{n/2}$ as follows:

$$
\begin{aligned}
z_i &\sim \mathcal{A}\left(\cdot \mid \bar{x}_{\pi(2i-1)} \right), & (7)\\
z_i^+ &\sim \mathcal{A}\left(\cdot \mid \bar{x}_{\pi(2i-1)} \right),\\
z_i' &\sim \mathcal{A}\left(\cdot \mid \bar{x}_{\pi(2i)} \right),\\
\boldsymbol{u_i} &\sim \mathsf{Gamma}(1, \frac{\sum_{i=1}^{n/2} \exp\left(f(z_i)^\top f(z_i')/\beta \right) + \exp\left(f(z_i)^\top f(z_i^+)/\beta \right)}{n/2+1}).
\end{aligned}
$$

We define the following loss on S :

$$\widehat{\mathcal{L}}_S(f) := \frac{1}{n/2} \sum_{i=1}^{n/2} \mathbb{E}_{\boldsymbol{u_i}} \left[\boldsymbol{u_i} \exp\left(f(z_i)^\top f(z_i')/\beta \right) - f(z_i)^\top f(z_i^+)/\beta \right]$$

It is easy to see that $\widehat{\mathcal{L}}_S(f)$ is an unbiased estimator of $\widehat{\mathcal{L}}_n(f)$. We prove the following lemma.

Lemma 4. *Let $\mathcal{F}$ be a hypothesis class of feature extractors from $\mathcal{X}$ to $\mathbb{R}^k$. Assume $\|f(x)\|_\infty \leq \kappa$ for all $x \in \mathcal{X}$. For $i \in [k]$, define $f_i : \mathcal{X} \to \mathbb{R}$ be the function such that $f_i(x)$ is the i-th dimension of $f(x)$. Let $\mathcal{F}_i$ be the hypothesis containing f_i for all $f \in \mathcal{F}$. For $m \in \mathcal{Z}^+$, let $\widehat{\mathcal{R}}_m(\mathcal{F}_i)$ be the maximal possible empirical Rademacher complexity of $\mathcal{F}_i$ over m data:*

$$\widehat{\mathcal{R}}_m(\mathcal{F}_i) := \max_{\{x_1, x_2, \cdots, x_m\}} \mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f_i(x_j) \right) \right]$$

where $x_1, x_2, \cdots, x_m$ are in $\mathcal{X}$, and σ is a uniform random vector in $\{-1, 1\}^m$. Then, the empirical Rademacher complexity on any m tuples $\left\{ (z_i, z_i^+, z_i') \right\}_{i=1}^m$ can be bounded by

$$\mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j \mathbb{E}_{\boldsymbol{u_i}} \left(\boldsymbol{u_i} \exp\left(f(z_i)^\top f(z_i')/\beta \right) - f(z_i)^\top f(z_i^+)/\beta \right) \right) \right]$$
$$\leq \left(8k\kappa \exp(\frac{4}{\beta}) \right) \cdot \max_{i \in [k]} \widehat{\mathcal{R}}_m(\mathcal{F}_i).$$

Proof.

$$\mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j \mathbb{E}_{\boldsymbol{u_i}} \left(\boldsymbol{u_i} \exp \left(f(z_i)^\top f(z_i') / \beta \right) - f(z_i)^\top f(z_i^+) / \beta \right) \right) \right]$$

$$\leq \mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j \left(\frac{n/2 + 1}{\sum_{i=1}^{n/2} \exp \left(f(z_i)^\top f(z_i') / \beta \right) + \exp \left(f(z_i)^\top f(z_i^+) / \beta \right)} \right. \right. \right.$$

$$\left. \left. \left. \exp \left(f(z_i)^\top f(z_i') / \beta \right) \right) \right) \right] + \frac{1}{\beta} \mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f(z_j)^\top f(z_j^+) \right) \right]$$

$$\leq \frac{1}{\beta} \exp(\frac{1}{\beta}) \mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j \left(f(z_i)^\top f(z_i') \left(\exp \frac{1}{\beta} - 1 \right) + \beta \right) \right) \right]$$

$$+ \frac{1}{\beta} \mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f(z_j)^\top f(z_j^+) \right) \right]$$

$$\leq \frac{1}{\beta} \exp(\frac{1}{\beta}) \left(\exp \frac{1}{\beta} - 1 \right) \mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j \left(f(z_i)^\top f(z_i') \right) \right) \right]$$

$$+ \frac{1}{\beta} \mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f(z_j)^\top f(z_j^+) \right) \right]$$

$$\leq \frac{2k}{\beta} \exp(\frac{2}{\beta}) \max_{\substack{z_1, z_2, \cdots, z_m \\ z_1', z_2', \cdots, z_m'}} \max_{i \in [k]} \mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f_i(z_j) f_i(z_j') \right) \right]$$

$$\leq k \exp(\frac{4}{\beta}) \max_{\substack{z_1, z_2, \cdots, z_m \\ z_1', z_2', \cdots, z_m'}} \max_{i \in [k]} \mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f_i(z_j) f_i(z_j') \right) \right]$$

714 $\qquad$ □

715 Notice that for any $z_1, z_2 \cdots z_m$ and $z_1', z_2', \cdots, z_m'$ in $\mathcal{X}$ and any $i \in [k]$ we have

$$\mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f_i(z_j) f_i(z_j') \right) \right]$$

$$\leq \frac{1}{2} \mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j (f_i(z_j) + f_i(z_j'))^2 \right) \right] + \frac{1}{2} \mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j (f_i(z_j) - f_i(z_j'))^2 \right) \right]$$

$$\leq 4\kappa \mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f_i(z_j) \right) \right] + 4\kappa \mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^m \sigma_j f_i(z_j') \right) \right]$$

716 where the first inequaltiy is by Talagrand's lemma. Combine these two equations and we get:

$$\mathbb{E}_\sigma \left[\sup_{f \in \mathcal{F}} \left(\frac{1}{m} \sum_{j=1}^{m} \sigma_j \mathbb{E}_{\boldsymbol{u_i}} \left(\boldsymbol{u_i} \exp \left(f(z_i)^\top f(z_i') / \beta \right) - f(z_i)^\top f(z_i^+) / \beta \right) \right) \right]$$

$$\leq \left(8k\kappa \exp(\frac{4}{\beta}) \right) \max_{z_1, z_2, \cdots, z_m} \max_{i \in [k]} \mathbb{E}_\sigma \left[\sup_{f_i \in \mathcal{F}_i} \left(\frac{1}{m} \sum_{j=1}^{m} \sigma_j f_i(z_j) \right) \right].$$

D.1 Proof of Theorem 3

Proof. We know that $\mathbb{E}_S \left[\widehat{\mathcal{L}}_S(f) \right] = \mathcal{L}_{\text{con}}(f)$, where S is sampled by first sampling $\widehat{\mathcal{X}}$ then sample S according to (7). Notice that when $\widehat{\mathcal{X}}$ contains n i.i.d. natural data samples, the set of random tuples S contains n i.i.d tuples. Therefore, we can apply generalization bound with Rademacher complexity to get a uniform convergence bound. In particular, by Lemma 4 and noticing the fact that $\mathbb{E}_{\boldsymbol{u_i}} \left[\boldsymbol{u_i} \exp \left(f(z_i)^\top f(z_i') / \beta \right) - f(z_i)^\top f(z_i^+) / \beta \right]$ always take values in range $\left[-k\kappa^2/\beta, k\kappa^2/\beta + \exp(\frac{2}{\beta}) \right]$, we apply standard generalization analysis based on Rademacher complexity. With similar techniques as those in the proof of Theorem 4.1 in [24], we can get the following result: with probability at least $1 - \delta^2/4$ over the randomness of $\widehat{\mathcal{X}}$ and S, we have for any $f \in \mathcal{F}$,

$$\mathcal{L}_{\text{con}}(f) \leq \widehat{\mathcal{L}}_S(f) + \left(16k\kappa \exp(\frac{4}{\beta}) \right) \max_{i \in [k]} \widehat{\mathcal{R}}_{n/2}(\mathcal{F}_i) + \left(2k\kappa^2/\beta + \exp(\frac{2}{\beta}) \right) \cdot \sqrt{\frac{4 \log 2/\delta}{n}}$$

This conclusion translates to the random tuple case as follows: With probability at least $1 - \delta/2$ over random tuples S conditioned on $\widehat{\mathcal{X}}$, the above equation holds. Since both $\mathcal{L}(f)$ and $\widehat{\mathcal{L}}n(f)$ take value in range $\left[-k\kappa^2/\beta, k\kappa^2/\beta + \exp(\frac{2}{\beta}) \right]$, we have that with probability at least $1 - \delta/2$ over random $\widehat{\mathcal{X}}$, we conclude that for any $f \in \mathcal{F}$,

$$\mathcal{L}_{\text{con}}(f) \leq \widehat{\mathcal{L}}_n(f) + \left(16k\kappa \exp(\frac{4}{\beta}) \right) \max_{i \in [k]} \widehat{\mathcal{R}}_{n/2}(\mathcal{F}_i) + \left(2k\kappa^2/\beta + \exp(\frac{2}{\beta}) \right) \cdot \left(\sqrt{\frac{4 \log 2/\delta}{n}} + \frac{\delta}{2} \right)$$

Since negating the functions in a function class doesn't change its Rademacher complexity, we can also get results from the other direction: With probability at least $1 - \delta/2$ over random $\widehat{\mathcal{X}}$, we have for any $f \in \mathcal{F}$,

$$\mathcal{L}_{\text{con}}(f) \geq \widehat{\mathcal{L}}_n(f) - \left(16k\kappa \exp(\frac{4}{\beta}) \right) \max_{i \in [k]} \widehat{\mathcal{R}}_{n/2}(\mathcal{F}_i) + \left(2k\kappa^2/\beta + \exp(\frac{2}{\beta}) \right) \cdot \left(\sqrt{\frac{4 \log 2/\delta}{n}} + \frac{\delta}{2} \right)$$

Combine them together we get the excess risk bound, stated as: With probability at least $1 - \delta$, we have

$$\mathcal{L}_{\text{con}}(\hat{f}) \leq \mathcal{L}(f_{\mathcal{F}}^*) + \left(32k\kappa \exp(\frac{4}{\beta}) \right) \max_{i \in [k]} \widehat{\mathcal{R}}_{n/2}(\mathcal{F}_i) + \left(4k\kappa^2/\beta + 2\exp(\frac{2}{\beta}) \right) \cdot \left(\sqrt{\frac{4 \log 2/\delta}{n}} + \frac{\delta}{2} \right)$$

where $\hat{f}$ is minimizer of $\widehat{\mathcal{L}}_n(f)$ in $\mathcal{F}$ and $f_{\mathcal{F}}^*$ is minimizer of $\mathcal{L}(f)$ in $\mathcal{F}$. Set $c_1 = 32k\kappa \exp(\frac{4}{\beta})$ and $c_2 = 8k\kappa^2/\beta + 4\exp(\frac{2}{\beta})$ and notice that $\max_{i \in [k]} \widehat{\mathcal{R}}_{n/2}(\mathcal{F}_i) = \widehat{\mathcal{R}}_{n/2}(\mathcal{F})$ finishes the proof.

$\square$

E An Alternative Approximate Loss

We propose an alternative loss to approximate the original info-NCE loss, which is potentially more expressive. Note we did not apply this in our current experiments. However, we are expecting to add it in to our future version.

Suppose there are K negative samples in a minibatch. Denote $s_{i,:K} \triangleq \sum_{k=1}^{K} s_{ik-}$ and $s_{i,K:} \triangleq \sum_{k=K+1}^{\infty} s_{ik-}$. The standard contrastive learning with infinite negative samples corresponds to optimizing

$$\frac{s_{i+}}{\mathbb{E}[s_{ik-}]} = \frac{s_{i+}}{\mathbb{E}[(2s_{i,:K} + s_{i,K:})/3]} \; ,$$

where the equality applies due to the assumed unbiased estimation of the expected negative similarity score with a minibatch. We propose to replace the arithmetic mean of $(s_{i,:K}, s_{i,:K}, s_{i,K:})$ with their geometric mean, and define a geometric contrastive learning objective as

$$\mathcal{L} \triangleq \sum_i \log \frac{s_{i+}^3}{s_{i,:K}^2 s_{i,K:}} \underset{\text{\color{red}arithmetic-geometric mean inequality}}{\geq} \sum_i \log \frac{4 s_{i+}}{s_{i,:K}} \frac{s_{i+}^2}{(s_{i,:K} + s_{i,K:})^2}$$

$$\underset{\text{\color{red}augmentation}}{\to} \sum_i \log \frac{4 s_{i+}}{s_{i,:K}} s_{i+}^2 u_i e^{-u_i(s_{i,:K} + s_{i,K:})} \triangleq \sum_i \mathcal{L}_i \; .$$

We call this loss function the geometric contrastive loss. We optimize the loss by maximizing its lower bound $\sum_i \mathcal{L}_i$ with our Bayesian data augmentation technique. Specifically, the stochastic EM iterates through:

- **Estimate** u_i: This is done by sampling from a Gamma distribution as: $u_i \sim \mathsf{Gamma}(2, \mathbb{E}[s_{ik-}])$, where we can use the same technique described in the main text to approximate $\mathbb{E}[s_{ik-}]$.

- **Maximizing** $p(\boldsymbol{\theta}|\mathcal{D})$: This can be done by maximizing the above lower bound of the geometric contrastive loss as: $\mathcal{L} = \sum_i \log \frac{s_{i+}}{s_{i,:K}} + 2 \log s_{i+} - u_i \tilde{s}_{ik-}$, where $\tilde{s}_{ik-}$ is a stochastic version of $\mathbb{E}[s_{ik-}]$ estimated from a minibatch.

F   Additional Details on the Experiments

Synthetic experiments   We re-run the experiment for Figure 1, where we mimic the noisy contrastive learning with a simplest synthetic experiment. Specifically, we define our objective to be maximized as $F = e^{s_1}/(e^{s_1} + e^{s_2})$ w.r.t. (s_1, s_2). In this example, e^{s_1} can be considered as the positive similarity score, and e^{s_2} as the sum of all the negative similarity score for one data point. Thus, this is a simplification of the standard contrastive loss. To introduce noise into the negative similarity score, we explicitly inject random Gaussian noise into the denominator, resulting in a stochastic objective of $e^{s_1}/(e^{s_1} + e^{s_2} + \delta_t)$ in each SGD iteration, where δ is a random zero-mean Gaussian noise with variance set to 0.09. To guarantee a unique optimal solution, we introduce a regularizer of $0.1 \times (s_1^2 + s_2^2)$. We compare direct optimization with SGD and our method over 100 independent

Figure 3: Comparison of the learning curves of our method and direct optimization. x-axis is the iteration number and y-axis is the objective value F.

random runs, starting from zero initializations. The learning curves of the objective values F w.r.t. the iteration numbers are plotted in Figure 3. It is observed that the two methods indeed converge to different solutions, with a better objective value from our method.

Comparison with non-contrastive learning methods   To demonstrate the effectiveness of our proposed method, we compare it with BYOL, one of the most successful non-contrastive learning methods. We use the public implement in the LIGHTLY benchmark [1], downloaded from https://docs.lightly.ai/_downloads/b99fe89a7fc2b4740cb9f1e34d3229ad/cifar10_benchmark.py, and use the default settings on the optimizer with 300 epochs. Table 5 shows the comparison of our method with SimCLR on the CIFAR-10 dataset under different batch sizes. It is clear that the non-contrastive learning method BYOL can perform better than the standard contrastive learning method

Table 5: Comparison of top-1 accuracies (%) on the CIFAR-10 with BYOL.

	Batch	64	128	256	512
CIFAR-10	SimCLR	81.8	83.4	85.8	86.8
	BYOL	86.5	87.0	87.2	86.8
	Ours	85.9	87.2	87.6	87.7

SimCLR, especially in the small-batchsize settings. When correcting gradient bias in contrastive learning with our method, we can outperform BYOL when batch sizes are large enough (*e.g.*, $\geq$ 256), and slightly worse when batch sizes are too small. The results also suggest there is still room the design better mechanism to correct the gradient bias in contrastive learning. The experiments also indicate that an advantage of contrastive learning compared to non-contrastive methods is that contrastive learning can be scaled up by using larger batch sizes. This is part of the reasons why recent large foundation models such as CLIP adopt contrastive learning in the training.