IN-SITU TEXT-ONLY ADAPTATION OF SPEECH MODELS WITH LOW-OVERHEAD SPEECH IMPUTATIONS

ABSTRACT

Fast and accurate adaptation of automatic speech recognition (ASR) systems using only text data in the target domain is a problem of long-standing practical relevance. Text-only adaptation was easy in traditional cascaded ASR systems with completely decoupled acoustic and language models. Recently, the RNN-Transducer (RNN-T) has emerged as a popular ASR model because of its high accuracy, low latency, and capability of supporting streaming input. However text-only adaptation of the RNN-T model is significantly more challenging due to its tight integration of acoustic and language models and end-to-end training. Existing recent approaches for text-only adaptation of RNN-Ts, either entail significant modification to the network or introduce high latency during decoding. We propose a new approach (TOLSTOI) that using text imputes speech representations internal to the ASR model, and performs in-situ adaptation that results in higher adaptation accuracy without any runtime overheads during decoding. Our imputation model is a function of the labeled data and trained parameters of the ASR model, and that we show, is more effective in controlling catastrophic forgetting compared to existing methods. We establish the effectiveness of TOLSTOI using three target domains and two ASR models of varying complexity. We yield up to 35% relative reduction in word error rate with text only adaptation, while forgetting the least compared to existing adaptation approaches. Our method is easy to implement and can be harnessed on existing RNN-T models without requiring ASR model training from scratch.

1 INTRODUCTION

Text-only adaptation of end-to-end (E2E) automatic speech recognition (ASR) systems to new target domains is of much practical interest since in many situations, e.g. mobile phones, it is easier to get target-specific text data than the corresponding audio. Efficient and effective text-only adaptation remains an open problem in large part due to the nature of E2E ASR systems that use a single model to jointly learn both a mapping from speech to text and a language model (LM), thus rendering traditional LM adaptation techniques for ASR (Bellegarda, 2004) ineffective.

RNN-Transducer (RNN-T) models (Graves, 2012) are one of the most popular E2E ASR architectures that achieve high accuracy and enable real-time decoding of speech, thus making them the predominant choice for ASR on mobile devices (He et al., 2019). Customizing RNN-T models using text-only data has gathered momentum in recent years. For any ASR applications using RNN-T models, running at real-time is a critical requirement. Thus, we seek simple and accurate text-only adaptation techniques that do not increase the model complexity. In this work, we propose such an approach TOLSTOI that is simple in its design and works with pretrained RNN-T models while enabling fast and accurate adaptation to the target domain. We will first review existing approaches to the problem of text-only adaptation to help contextualize TOLSTOI better.

A popular solution for text-only adaptation of E2E ASR systems is shallow fusion (Hannun et al., 2014) where scores from the E2E model are combined with scores from an external LM trained on the target text during beam search decoding. While simple in its design, this technique significantly increases decoding time due to the reliance on an external LM during inference. More recent work on adapting RNN-T models using only text aims at directly updating the parameters of the prediction network (Pylkkonen et al., 2021; Chen et al., 2022). However such techniques do not yield very accurate adaptation to the target text and also involve architectural changes to the

RNN-T that necessitate training the model from scratch. Text-only adaptation can also be tackled by generating corresponding speech via text-to-speech synthesis (TTS). The main limitations of TTS-based adaptation are significant computational costs and the reliance on high-quality TTS systems that are available only for a small subset of high-resource languages and accents.

From these prior works, the key requirements for practical text-only adaptation of ASR that emerge are i) the model should adapt to target-domain text-only data with high accuracy ii) the adaptation should be applied to existing pretrained models without any retraining iii) the inference should be fast and inexpensive and iv) the adaptation should not lead to catastrophic forgetting (Goodfellow et al., 2013; Takashima et al., 2022). We propose TOLSTOI that addresses all four requirements. Starting from text in the target domain, we impute speech representations as would have been produced by the transcription network of a pretrained RNN-T model. Our imputation model is a simple feedforward network (with roughly 200K parameters) that incurs minimal overhead in its training by harnessing forced alignments and representations from the ASR model. Using the trained imputation model, we generate sequences of speech representations for all the text in the target domain which are used for in-situ adaptation of the RNN-T ASR model. TOLSTOI can be used with any existing pretrained RNN-T. We do not introduce any new parameters in the RNN-T and do not rely on any external LMs, thus incurring no additional overhead on latency at inference time. Along with yielding fast and accurate adaptation to the target domain, TOLSTOI also safeguards against forgetting since the imputation model is trained to mimic representations from the source distribution. TOLSTOI yields up to 35% relative word error rate (WER) reduction on a new target domain, while maintaining the same decoding latency as the base RNN-T model and ensuring minimal forgetting of its source information when compared to three other competitive baselines. We also present a detailed ablation study to justify the various design choices of TOLSTOI.

2   RELATED WORK

LM adaptation in traditional ASR systems Unlike end-to-end models, traditional ASR systems adopt a cascaded structure with the LM being completely decoupled from the acoustic model (Mohri et al., 2002). This enables easier adaptation of the LM to a target domain (Hori et al., 2003; Bellegarda, 2004; Neubig et al., 2009; Gangireddy et al., 2016) and also allows for ASR lattice rescoring with an external LM (Park et al., 2010; Xu et al., 2018).

LM fusion A popular approach for text-only adaptation of end-to-end ASR is "shallow fusion" where an external LM is log-linearly interpolated with the RNN-T output during beam decoding Kannan et al. (2018). For RNN-T models, another recent approach is to extract internal LM probabilities and discount with the ratio of external and internal LM probabilities (McDermott et al., 2019; Meng et al., 2021a;b). These techniques incur a significant overhead at inference time due to the external LM and also require careful tuning of the interpolation weight used for the external LM.

Synthesizing audio Another approach to text-only adaptation is to synthesize audio using text-to-speech (TTS) synthesis (Zheng et al., 2021; Deng et al., 2021; Joshi & Singh, 2022). However, this is a slow generation process and relies on access to high-quality TTS which is absent for most languages. To address these issues, recent work on text-only adaptation has investigated generating simpler pseudo-speech representations called "textograms" by repeating one-hot encodings of the output labels for a fixed duration (Thomas et al., 2022). The input to the RNN-T is augmented to accept a textogram as an additional channel. This model requires training the RNN-T from scratch and also negatively impacts the decoding latency.

Fine-tuning RNN-T model parameters Recent approaches exploit the inherent structure of the RNN-T to perform in-situ text-only adaptation. Pylkkonen et al. (2021) adds a separate LM output head to the prediction network in an RNN-T (that handles text-only inputs) and both are jointly finetuned using the target text. Chen et al. (2022) first factorize the prediction network into two networks that separately handle "blank" tokens (capturing alignment with the audio) and the output vocabulary tokens, before adapting the latter with the target text. This technique requires retraining the RNN-T model and does not yield accurate adaptation.

Figure 1 shows a technique from each of the above-mentioned categories and how it is integrated within the standard RNN-T architecture.

Figure 1: Figure on the left shows a schematic diagram of the standard RNN-T architecture (in blue). Three existing approaches for text-only adaptation are shown as appendages to the RNN-T model (in red): (1) "Textogram" increases the dimensionality of the input to the transcription network $\mathcal{M}_S$ thus requiring an expensive model retraining. (2) Shallow fusion uses an external LM during inference that leads to significant degradation of test-time latency. (3) A separate LM head can be added and jointly trained with the prediction network on the target text. This, however, does not result in very accurate adaptation. The figure on the right shows TOLSTOI that uses a lightweight imputation model to generate speech representations corresponding to the target text.

3 OUR APPROACH (TOLSTOI)

We are given an ASR model $\mathcal{M}$ trained on a labeled dataset $D : \{(\boldsymbol{x}^1, \boldsymbol{y}^1) \ldots, (\boldsymbol{x}^N, \boldsymbol{y}^N)\}$ where $\boldsymbol{x}^i \in \mathcal{X}$, the space of speech utterances, and $\boldsymbol{y}^i \in \mathcal{Y}$, the space of text transcripts. Each speech utterance $\boldsymbol{x}^i$ comprises of a variable number of frames $\boldsymbol{x}_1^i, \ldots, \boldsymbol{x}_{T_i}^i$ where each $\boldsymbol{x}_t^i$ is a fixed-length real-valued vector denoting features such as spectrogram of the audio frame. Each text sequence comprises of a variable number of tokens $\boldsymbol{y}^i = (y_1^i, \ldots, y_{U_i}^i)$ where each $y_u \in \mathcal{V}$, the output vocabulary. Popular choices for the output vocabulary are characters and subwords (Sennrich et al., 2015). Typically the number of text tokens $U_i \ll T_i$, the number of audio frames. Let $\mathcal{P}(\mathcal{X}, \mathcal{Y})$ denote the distribution of speech and text from which the training data is sampled.

Our goal is to deploy the ASR model $\mathcal{M}$ on a target domain whose distribution $\tilde{\mathcal{P}}(\mathcal{X}, \mathcal{Y})$ differs from the training distribution. For the target domain, we only have text data $\tilde{D} = \{\tilde{\boldsymbol{y}}^1, \ldots, \tilde{\boldsymbol{y}}^k\}$ where the number of text samples in $\tilde{D}$ in the target is generally much smaller than the size of the training set D. Since we are only given text samples in the target distribution we assume that the training and target distributions differ only on the text marginals $\mathcal{P}(\mathcal{Y})$ and the distribution of the speech given the text stays unchanged. That is, $\mathcal{P}(\mathcal{X}|\mathcal{Y}) = \tilde{\mathcal{P}}(\mathcal{X}|\mathcal{Y})$. We seek to use $\tilde{D}$ to fine-tune the parameters of $\mathcal{M}$ so that the updated model $\tilde{\mathcal{M}}$ is accurate on speech corresponding to new text from the target distribution $\tilde{\mathcal{P}}$, without catastrophically deteriorating accuracy on samples from the training distribution $\mathcal{P}$. We propose to perform in-situ adaptation without introducing new layers or external LMs during deployment.

As mentioned earlier, we focus on adapting the RNN-Transducer (RNN-T) architecture (Graves, 2012; Graves et al., 2013) as the ASR model since it has recently emerged as a popular choice, particularly in mobile devices, because of its high accuracy, low latency, and capability of supporting streaming input. We first present a brief background of RNN-Ts.

Background of RNN-T The RNN-T network comprises of three modules: (1) A speech module $\mathcal{M}_S$ with parameters $\boldsymbol{\theta}_S$ that converts speech frames $\boldsymbol{x} = \boldsymbol{x}_1 \ldots, \boldsymbol{x}_T$ to vectors $\boldsymbol{h}_1, \ldots, \boldsymbol{h}_T$ typically using a Transformer or recurrent network, (2) A language module $\mathcal{M}_L$ with parameters $\boldsymbol{\theta}_L$ that converts text tokens $\boldsymbol{y} = y_1, \ldots, y_U$ to contextual vectors $\boldsymbol{g}_1, \ldots, \boldsymbol{g}_U$ using a recurrent network so that $\boldsymbol{g}_u$ summarizes the tokens before y_u, and (3) A thin joint network $\mathcal{M}_J$ with parameters $\boldsymbol{\theta}_J$ that combines vectors $\boldsymbol{h}_t$ and $\boldsymbol{g}_u$ and outputs a softmax distribution spanning the vocabulary $\mathcal{V}$ plus

Figure 2: Training the imputation model of TOLSTOI using RNN-T alignments.

the blank symbol $\varnothing$. To generate a token sequence $\boldsymbol{y}$, the RNN-T implicitly aligns each token y_u to one frame t where it is output. An example of a valid alignment[1] appears in Figure 2.

Even though the network is modular, all parameters are trained jointly end-to-end by maximizing the likelihood of the output $\boldsymbol{y}^i$ given speech $\boldsymbol{x}^i$ over all $(\boldsymbol{x}^i, \boldsymbol{y}^i) \in D$. During training, the log-likelihood of the target sequence $\boldsymbol{y}^i$ is computed by marginalizing over all possible alignments of the T_i frames of $\boldsymbol{x}^i$ and the U tokens of $\boldsymbol{y}$ using an efficient forward-backward algorithm; we will refer to this objective as the RNNT-loss (Graves, 2012).

$$\min_{\boldsymbol{\theta}_L, \boldsymbol{\theta}_S, \boldsymbol{\theta}_J} \sum_{(\boldsymbol{x}^i, \boldsymbol{y}^i) \in D} \text{RNNT-loss}(\boldsymbol{y}^i, \{\mathcal{M}_J(\cdot | \boldsymbol{g}_u = \mathcal{M}_L(y_1, \ldots, y_{u-1}), \boldsymbol{h}_t = \mathcal{M}_S(\boldsymbol{x}_1, \ldots, \boldsymbol{x}_T, t)\})$$

During inference, beam-search finds the best possible alignment (t, u) and the predicted sequence is a concatenation of the non-blank tokens at each aligned (t, u) (Graves, 2012; Saon et al., 2020).

Motivation of our approach   Figure 1 presents a schematic diagram of our imputation based adaptation. Given only text data $\tilde{D}$ for adaptation, we propose to update the language parameters $\boldsymbol{\theta}_L$ and joint parameters $\boldsymbol{\theta}_J$ while keeping the speech parameters θ_S fixed. This is challenging since even though the network architecture is modular, the training is not. Treating the $\mathcal{M}_L$ as a language model and updating part of the network using text-only data, as proposed in (Pylkkonen et al., 2021; Chen et al., 2022), has the potential of deteriorating performance as the output vector of $\mathcal{M}_L$ gets incompatible with the vector from $\mathcal{M}_S$. We, therefore, propose to first augment the missing speech data in $\tilde{D}$ by imputing using a separate generator. However, training a full-fledged TTS model requires substantial training data and resources, and high-quality TTS models are not available for low-resource languages. Our key insight is to impute, not the full raw speech $\boldsymbol{x}$, but the $\boldsymbol{h}$ vectors from the last layer of the speech module $\mathcal{M}_S$. Generating the last layer vectors $\boldsymbol{h}$ is significantly easier than generating the raw audio signals $\boldsymbol{x}$. In fact, only a thin joint layer separates $\boldsymbol{h}$ from the output character distribution. So the $\boldsymbol{h}$ vectors are expected to be "closer" to text than speech. We are able to design a very simple and low-overhead model for imputing the $\boldsymbol{h}$ vectors from the text. In Section 3.1 we describe the design and training of the imputation model. Once the imputation model is trained, for any new target domain, we attach each text $\boldsymbol{y} \in \tilde{D}$ with imputed $\boldsymbol{h}$ values to create a proxy parallel dataset for fine-tuning $\mathcal{M}_J$ and $\mathcal{M}_L$. In Section 3.2 we describe how we perform this fine-tuning.

3.1 IMPUTATION MODEL

Let $\mathcal{H}$ denote the space of vectors from the last layer of $\mathcal{M}_S$. The goal of our imputation model is to directly model $\mathcal{P}(\mathcal{H}|\mathcal{Y})$ instead of $\mathcal{P}(\mathcal{X}|\mathcal{Y})$ that TTS models attempt to do. The imputation model generates proxy output vectors $\boldsymbol{h}_1, \ldots, \boldsymbol{h}_T$ of the speech module $\mathcal{M}_S$ given *only* a text sequence $y_1, \ldots y_U$ so as to mimic the output of the speech module $\mathcal{M}_S(\boldsymbol{x}_1, \ldots, \boldsymbol{x}_T)$ without having access to the real audio frames $\boldsymbol{x}_1, \ldots, \boldsymbol{x}_T$. A default option is to train a full-fledged sequence to sequence model that takes as input text tokens $y_1, \ldots y_U$ and generates the $\boldsymbol{h}$-vector sequence $\boldsymbol{h}_1, \ldots, \boldsymbol{h}_T$ using a standard encoder-decoder network. However, such an approach would require training a heavy-weight model from scratch. Instead, we developed a simple low-overhead model that we present next.

---

[1]In a valid alignment, at each step u the output character is either y_u or $\varnothing$ so that the concatenation of the tokens matches $\boldsymbol{y}$ after ignoring the $\varnothing$.

Figure 3: RNN-T finetuning using imputed speech representations from f_{IMP} with alignments from the FixedGram model.

Designing the Low-overhead Imputation Model Our approach is to leverage the existing trained RNN-T model $\mathcal{M}$ to reduce the overheads of generating the $\boldsymbol{h}$ sequence given a token sequence $\boldsymbol{y}$. First, we reduce the need for encoding discrete tokens $y_1, \ldots, y_U$ from scratch by starting from the output $\boldsymbol{g}_1, \ldots, \boldsymbol{g}_U$ of the language model $\mathcal{M}_L$. Second, we reduce the need for cross-attention training of a full seq2seq approach by pre-aligning the $\boldsymbol{h}$ sequence to the token sequence $\boldsymbol{y}$. We denote an alignment as A, a sequence of (t, u) pairs to show that the LM state $\boldsymbol{g}_u$ was aligned with audio frame $\boldsymbol{h}_t$ in a valid execution of the RNN-T to generate a sequence. We will discuss how we generate such alignments during training and deployment of the Imputation model. Given an alignment A we factorize the generator of the $\boldsymbol{h}$ sequence as follows:

$$\mathcal{P}(\boldsymbol{h}_1, \ldots, \boldsymbol{h}_T | y_1, \ldots, y_U, A) = \prod_{(t,u) \in A} P_h(\boldsymbol{h}_t | \boldsymbol{h}_{t-1}, \boldsymbol{g}_u) \quad (1)$$

In the above we have further assumed that $\boldsymbol{h}_t$ depends only on $\boldsymbol{h}_{t-1}$ and is independent of other prior $\boldsymbol{h}_r$s given $\boldsymbol{h}_{t-1}$. We model the above distribution using an imputation model f_{IMP} which consists of a simple feedforward-neural networks that takes as input the language model encoding $\boldsymbol{g}_u$ and the last audio encoding $\boldsymbol{h}_{t-1}$ to produce the next audio encoding $\boldsymbol{h}_t$. Figure 2 presents an overview.

Training the Imputation Model To create the training data for the imputation model f_{IMP}, we use the training data D of the ASR model. For each utterance $\boldsymbol{x}^i$ in D, we trace the lattice of the highest probability beam to find the best valid alignment A^i that consists of a sequence of $\boldsymbol{h}_t$ and the aligned $\boldsymbol{g}_u$ as shown in Figure 2. We use the alignment-length synchronous decoding algorithm (Saon et al., 2020) for this. From these alignments we extract training instances for the imputation model as $\{(\boldsymbol{h}_{t-1}, \boldsymbol{g}_u), \boldsymbol{h}_t\}$ for each $(t, u) \in A^i$. When multiple $\boldsymbol{g}_u$'s align with the same $\boldsymbol{h}_t$ in the best alignment output, we select the last $\boldsymbol{g}_u$. We train the parameters of the f_{IMP} model to minimize the reconstruction loss of $\boldsymbol{h}_t$ with input $(\boldsymbol{h}_{t-1}, \boldsymbol{g}_u)$ as follows:

$$\hat{f_{\text{IMP}}} = \arg\min_f \sum_{i \in D} \sum_{(t,u) \in A^i} \text{Loss}(\boldsymbol{h}_t^i, f(\boldsymbol{h}_{t-1}^i, \boldsymbol{g}_u^i)) \quad (2)$$

where $\boldsymbol{h}_0 = 0$ and the space of f are parameters of a standard feed forward network as described above. For the loss function, we considered several candidates and found the L1 distance to provide the best results as we show in our ablation studies.

3.2 RNN-T Finetuning using the Imputation Model

In this section we describe how we fine-tune the RNN-T model $\mathcal{M}$ on the target text $\tilde{D}$ using the trained f_{IMP} model. For each text $\boldsymbol{y}^i \in \tilde{D}$ we first sample an alignment A^i as elaborated in Section 3.2.1. Next use A^i and f_{IMP} to sample a sequence of vectors $\boldsymbol{h}^i : \boldsymbol{h}_1^i, \ldots, \boldsymbol{h}_{|A^i|}^i$ as shown in the alignment example in Figure 2. We first feed the token sequence $\boldsymbol{y}$ to the language module to get a sequence of outputs $\boldsymbol{g}_1, \ldots, \boldsymbol{g}_U$. Next we invoke the imputation model f_{IMP} to generate for each $(t, u) \in A$ in increasing order of t, $\boldsymbol{h}_t \sim f_{\text{IMP}}(\boldsymbol{h}_{t-1}, \boldsymbol{g}_u)$. This gives us a pseudo labeled training set $\tilde{\mathcal{D}}_{\text{Imp}} = \{(\boldsymbol{h}^i, \boldsymbol{y}^i)\}$ that we use to fine-tune parameters $\boldsymbol{\theta}_L$ and $\boldsymbol{\theta}_J$ of the RNN-T using the same loss function of maximizing the likelihood of $\boldsymbol{y}$ over all possible alignments. Since the generated $\boldsymbol{h}$ come from the $\Pr(\boldsymbol{h}|\boldsymbol{y})$ distribution, and only the $\mathcal{P}(\boldsymbol{y})$ distribution changes in the target distribution, this fine-tuning step adapts to the target distribution.

$$\min_{\boldsymbol{\theta}_L, \boldsymbol{\theta}_J} \sum_{(\boldsymbol{h}, \boldsymbol{y}) \in \tilde{\mathcal{D}}_{\text{Imp}}} \text{RNNT-loss}(\boldsymbol{y}, \{\mathcal{M}_J(\cdot | \boldsymbol{g}_u = \mathcal{M}_L(y_1, \ldots, y_{u-1}), \boldsymbol{h}_t)\}) \quad (3)$$

3.2.1 GENERATING ALIGNMENTS GIVEN A TEXT SEQUENCE

We tried many different light-weight methods of generating alignments for a given text token sequence $\boldsymbol{y}$. A simple method is to generate a fixed number of blanks($\varnothing$) B before each token y_u. We call this the FixedGram model. A second option is to train a distribution over the number of blanks for each token $v \in \mathcal{V}$. Finally, a more evolved method would be to use a state-based model, much like the imputation model that takes as input g_u and h_{t-1} to generate if the next token should be a blank. We will show that the simple FixedGram model was adequate for the adaptation task.

Figure 3 presents an overview of our steps during fine-tuning under the FixedGram alignment model. Algorithm 1 presents the overall pseudocode of TOLSTOI. Note, the training of the imputation model is performed once and is independent of the adaptation dataset.

Algorithm 1 Text-only adaptation in TOLSTOI

Require: Trained RNN-T model $\mathcal{M}$, Training data D, Adaptation Text $\tilde{D}$
  for $(\boldsymbol{x}^i, \boldsymbol{y}^i) \in D$ **do**
    $A^i, \boldsymbol{h}^i, \boldsymbol{g}^i$ = Apply $\mathcal{M}$ on speech $\boldsymbol{x}$ to extract alignments and $\boldsymbol{h}, \boldsymbol{g}$ vector sequences
  end for
  f_{IMP} = Train imputation model on aligned pairs $\boldsymbol{h}_t^i, \boldsymbol{g}_u^i$ using Equation 2
  /* **Fine-tune** $\mathcal{M}$ **for** $\tilde{D}$ */
  for $\boldsymbol{y} \in \tilde{\mathcal{D}}$ **do**
    $\boldsymbol{g}_1 \ldots \boldsymbol{g}_U = \mathcal{M}_L(\boldsymbol{y}), \quad \boldsymbol{h}_0 = 0$
    A = GenerateAlignments($\boldsymbol{g}$)
    for $(t, u) \in A$ in increasing order of t **do**
      $\boldsymbol{h}_t = f_{\text{IMP}}(\boldsymbol{h}_{t-1}, \boldsymbol{g}_u)$
    end for
    loss = RNN-T_loss(softmax($\mathcal{M}_J(\boldsymbol{h}, \boldsymbol{g})$), $\boldsymbol{y}$)
    Backpropagate(loss, $\{\boldsymbol{\theta}_J, \boldsymbol{\theta}_L\}$)
  end for
  Return $\boldsymbol{\theta}_L, \boldsymbol{\theta}_J$

---

4 EXPERIMENTS

We present an extensive evaluation of TOLSTOI against three existing approaches for adapting two different ASR models to three different target domains. We also present a detailed ablation of the various design choices of TOLSTOI.

4.1 EXPERIMENTAL SETUP

We perform adaptation experiments on two RNN-T models of very different capacity: (i) **SWB 300H** - trained on the Switchboard 300H dataset (Godfrey et al., 1992) containing over 300 hours of labelled training data and (ii) **SWB 2000H** - trained on 262 hours of Switchboard-300, 1698 hours of Fisher data (Cieri et al., 2004) and 15 hours of CallHome data (Martin & Przybocki, 2000).

The transcription network of the RNN-T model consists of 6 bidirectional LSTM layers with a hidden size of 640 cells and a projection layer that projects down the encoder embeddings to 256 dimensions. The prediction network consists of a single-layer unidirectional LSTM with a hidden size of 768 cells and a projection layer reducing the prediction network embeddings to 256 dimensions. The joint network first combines the transcription network embeddings (256-d) and prediction network embeddings (256-d) via a Hadamard product joint operation ($\odot$) (Saon et al., 2021), followed by a tanh non-linearity and a final output softmax layer that produces a probability distribution over 45 non-blank characters ($\mathcal{V}$) and a blank character ($\varnothing$). The total number of parameters in the RNN-T model is roughly 56 million.

The audio features are mean and variance normalized log-Mel filterbank features computed for every 10ms of the audio. These features are further appended with delta-spectral and double-delta spectral features((Mason & Zhang, 1991; Picone, 1993)) where every two consecutive frames are stacked resulting in 240-dimensional (240-d) input vectors with a receptive field of 20ms. Speed and tempo perturbations are applied to each input with the value of $0.9, 1.1$ to augment the training data. We also use SpecAugment (Park et al., 2019) for additional augmentation. The RNN-T models were trained for 20 epochs using AdamW (Loshchilov & Hutter, 2017) optimizer with the maximum learning rate of 5e-4 and the OneCycleLR policy (Smith & Topin, 2019) policy consisting of a linear warmup phase from 5e-5 to 5e-4 followed by a linear annealing phase to 0. A batch size of 64 was used to train the Pytorch models on V100 GPUs.

Adaptation Datasets: For the adaptation experiments, we choose three diverse datasets with different amounts of adaptation text coming from three different domains. (1) **ATIS** (Hemphill et al., 1990) consists of roughly 5K sentences from the airline reservation domain for training and 893 (speech, text) utterance pairs for testing. (2) **HarperValleyBank (HVB)** (Wu et al., 2020) consists

of roughly 15K sentences from the banking domain for training and 2797 (speech, text) utterance pairs for testing. (3) **Librispeech** (Panayotov et al., 2015) consists of roughly 29K sentences from audiobooks for training and 2619 (speech, text) utterances for testing. Note, in true spirit of text-only adaptation, we do not assume the availability of a parallel validation dataset in the target domain.

Imputation Model The imputation model of TOLSTOI is a 2-layer feed-forward network with a tanh non-linearity. The first layer projects the 512-d input of (h_{t-1}, g_u) to 256-d and the second layer outputs a 256-d h_t. The imputation model contains roughly 200K parameters, in contrast to the 56 million parameters of the ASR model. The imputation model is trained using the same learning rate, optimizer, and learning rate schedule as the baseline training with a batch size of 2048. The SWB 300H training data was aligned with the corresponding ASR model yielding a total of 42 million (h_t, g_u) pairs to train the imputation model.

Fine-tuning details For fine-tuning of $\mathcal{M}_L$ using the imputation model, we keep the same optimizer and learning rate scheduler as the starting RNN-T training except that the maximum learning rate used for fine-tuning was 5e-5. We fine-tune for a fixed number of 2000 updates since we do not have a validation set for target-specific hyper-parameter selection.

Metrics We evaluate on three metrics: (1) **RTF**: Real Time Factor(RTF) which measures the average time (in seconds) to decode 50 audio frames. It is computed by averaging over the test set on a single CPU. (2) **WER on Target-Only**: Word error rate(WER) on the test set of the target domain. (3) **WER on Source-Target Mixture**: The test sizes for each of the target domains datasets is small. In any ASR system deployed in the real world, it is important for the adapted model to not be significantly worse than the unadapted model on sentences outside its narrow domain because of catastrophic forgetting during adaptation. Therefore, we also measure WER on an equal mixture of the target and source test datasets. The test data of the source domain comprises 4458 (speech utterance, text) pairs from Hub5'00 and CallHome.

We compare TOLSTOI against three existing methods of text-only adaptation of RNN-Ts.

Shallow Fusion (Kannan et al., 2018) is a standard method which uses an external LM trained on the target domain text to interpolate the RNN-T probabilities during inference. For the external LM, we use the same configuration as our prediction network and set the interpolation parameter (λ) to 0.3 for all cases. Since we do not assume access to any validation set from the target domain, fine-tuning the hyper-parameter is not an option.

NN-LM In this method, the prediction network is viewed as an auto-regressive language model. To get the LM scores, a linear layer is added to project the prediction network representations to the output vocabulary space $\mathcal{V}$ and fine-tuned on the target domain text for one epoch.

Textogram (Thomas et al., 2022) In this method, the transcription network is modified to work with two input modalities: (i) standard acoustic features and (ii) one-hot encoding of the units in the text, with the encoding of each unit being repeated a fixed number of times such that each feature has duration similar to the spectrograms. During the training of the base model, either the acoustic feature or textogram feature is used for training the RNN-T objective. During fine-tuning, only the textogram features for each text from the target domain are used for adaptation. Different from NN-LM, in textogram RNN-T loss is used for fine-tuning the joint network and prediction network parameters much like in our method.

Other methods We also compared with two other methods: (1) The factorized model proposed in Chen et al. (2022). However, their factorized RNN-T model had significantly worse accuracy than our unadapted RNN-T model both before and after text-only adaptation. (2) TTS where we used a proprietary synthesis engine based on Tacotron (Shen et al., 2018) to generate audio for the text-only inputs.[2] This gives competitive reduction in WERs of target-only/source-target mixed (3.2/6.5 and 8.6/9.8 on the ATIS and HVB test sets, respectively). However, it is worth noting here that all three target domains consist of US-accented English speech and the TTS system we employ is carefully tuned to produce natural-sounding US-accented English samples. Building TTS of similarly high quality for low-resource languages is a highly non-trivial task (Ogayo et al., 2022). In contrast, TOLSTOI relies only on access to the ASR pretraining data to train the imputation model and can potentially scale well to low-resource languages.

---

[2]We withhold providing more details about the TTS system to avoid violating author anonymity.

Baseline Model	Method	RTF↓ (sec)	ATIS (WER(↓))		HVB (WER(↓))		Librispeech (WER(↓))	
			Target	Mixed	Target	Mixed	Target	Mixed
SWB 2000H	Unadapted	0.33	5.8	7.3	17.5	13.1	12.5	10.6
	NN-LM	0.33	5.7	7.2	16.4	13.1	12.1	10.5
	Textogram	0.72	5.4	19.2	12.2	26.0	14.1	23.6
	Shallow Fusion	0.85	4.3	15.0	12.8	11.9	12.0	10.8
	TOLSTOI	0.33	4.0	**6.6**	11.2	**10.4**	11.1	**10.0**
SWB 300H	Unadapted	0.33	12.5	12.6	34.4	23.5	20.3	16.5
	NN-LM	0.33	12.4	12.6	33.3	23.6	20.3	16.5
	Textogram	0.72	10.8	22.3	24.5	33.6	19.1	19.2
	Shallow Fusion	0.85	8.1	13.7	29.0	23.8	19.8	17.2
	TOLSTOI	0.33	10.4	**12.0**	23.8	**18.8**	19.1	**16.1**

Table 1: comparison on decode time (RTF) and WERs on target-only and target-source mixed data of different adaptation methods on two different ASR models trained on SWB 2000H (top) and SWB 300H (bottom) adapted to three different domains. WERs on SWB test are 8.8 and 12.7, respectively, using SWB-2000 and SWB-200. When deployed on an equal mixture of source and target data, TOLSTOI provides the highest reduction in WER. While Shallow Fusion provides lower target-only WER, it has severe catastrophic forgetting and is a factor of 2.5 slower.

Reference	i need to reset i would like to reset my password
Shallow Fusion	i need to reset i would like to reset my password
TOLSTOI	i need to reset i would like to reset my password
Reference	hi i lost my debit card can you send me a new one my name is robert davis by the way
Shallow Fusion	hi i lost my debit card can you send me a new one my name is robert davis by the way
TOLSTOI	hi i lost my debit card can you send me a new one my name is robert davis by the way

Table 2: Anecdotal examples comparing TOLSTOI with shallow fusion. Deletion errors are underlined and highlighted in red.

4.2 OVERALL COMPARISONS

Table 1 presents the decode time (RTF) and target-only WER and source-target mixed WER of different adaptation methods on two ASR models adapted to three different target domains. If we focus only on target WERs, shallow fusion provides good reductions in WER. However, this comes at the cost of a 2.5 times blow-up of decode time (RTF) which could be unacceptable in many applications. Also, the external LM fine-tuned on the target text leads to significant catastrophic forgetting as observed by the significantly increased WER on the mixed corpus. TOLSTOI provides the best WER when measured on the mixed test set while being competitive with shallow fusion on the target-only set. The decode time of TOLSTOI is exactly the same as the basic RNN-T since we do not modify the RNN-T architecture. NN-LM does not provide much gains beyond the unadapted model. The Textogram is more successful in adaptation but is also subject to significant deterioration on the mixed corpus. Also, the Textogram modified the network architecture of the RNN-T resulting in significantly larger decode time compared to the basic RNN-T.

Table 2 presents two illustrative examples from ATIS comparing predictions using shallow fusion and TOLSTOI. Shallow fusion does not handle disfluencies well if the target text used to train the external LM is devoid of it. For example, the false start "I need to reset" and the filler phrase "by the way" are omitted. More anecdotal examples are shown in Table 4 in Appendix A.

4.3 ABLATION STUDY

Table 3 presents ablations of various design choices governing TOLSTOI. We investigate three dimensions of the imputation model: 1) choice of loss function, 2) choice of alignment to sample at test-time, and 3) choice of model architecture. On the choice of loss function, we replaced the L1 loss in Eqn 2 with an L2 loss and a contrastive loss. We used the contrastive loss from Chen et al. (2020) for the imputed features in each batch. We also tried a distillation loss where a generated h_t is combined with the corresponding g_u via $\mathcal{M}_J$ to generate a probability distribution over the vocabulary and a KL-Divergence loss is imposed between this predicted distribution and the probability distribution from the real h_t. These losses were all worse than L1. On choice of the alignment generation model, we tried the FixedGram model with 1 blank or 4 blanks before each output token instead of the default of 3. We also tested a feed-forward regression model for length that takes

Method	ATIS		HarperValleyBank	
	Target	Mixed	Target	Mixed
Unadapted	5.8	7.3	17.5	13.1
TOLSTOI	4.0	6.6	11.2	10.4
Imputation Model Loss Function				
Imputation Model with L2 Loss	4.2	6.5	11.3	10.4
Imputation Model with Contrastive Loss	7.8	8.6	17.1	13.1
Imputation Model with Distillation Loss	5.3	7.1	15.4	12.4
Alignment Generation Models				
Imputation Model with 1 blank	7.2	8.1	23.4	16.4
Imputation Model with 4 blanks	4.2	6.6	11.3	10.4
Imputation Model with dynamic length model	4.4	6.7	11.3	10.4
Imputation Model Architecture				
$(\boldsymbol{g}_u)$	9.1	9.0	9.5	16.0
$(\boldsymbol{h}_{t-1}, \boldsymbol{g}_u, \boldsymbol{g}_{u+1})$	4.4	6.7	11.8	10.7
$(\boldsymbol{h}_{t-1}, y_{u-1}, y_u, y_{u+1})$	5.6	7.4	15.6	12.5
Transformer Imputation Model	5.7	7.2	17.3	13.0
- No Switchboard Data	4.4	7.2	11.7	11.6

Table 3: Ablation of various design choices of TOLSTOI. More complicated loss functions, or alignment models, or imputation models performed worse than the simple design choices of TOLSTOI.

g_u as its input and outputs the number of speech frames learnt from the alignment data (c.f., Section 3.1). All these alignment generation models fared worse than using a FixedGram model with 3 blanks as in TOLSTOI. We next tried different tweaks to the architecture of the imputation model. We tried changing the input context to the imputation model by adding $\boldsymbol{g}_{u+1}$, adding output characters y_{u-1}, y_u, y_{u+1} or omitting $\boldsymbol{h}_{t-1}$. We also tried a Transformer-based (Vaswani et al., 2017) encoder-decoder imputation model to transform the complete $\boldsymbol{g}_u$ sequence to a full $\boldsymbol{h}_t$ sequence. All these variants performed worse than TOLSTOI. During RNN-T finetuning, we found it useful to mix an equal number of utterances from the pretraining corpus with the imputed data (Zhu et al., 2022). Omitting this step resulted in small WER degradations shown in the last row in Table 3.

Figure 4 shows the WERs on ATIS and HVB as a function of decreasing amount of target text. As expected, there is an increase in WERs with reducing the amount of target text. However, the reduction in WERs with using only 50% of the data versus using the complete dataset is not substantial. This suggests that TOLSTOI could work well even in target domains with very limited amounts of text-only data.

Figure 4: WER vs. Adaptation Text(%)

5 CONCLUSION

In this paper we presented TOLSTOI, a low-overhead method of adapting RNN-T models using text-only data in a target domain. Our key insight it to impute speech features from the last layer of the transcription network, which allows accurate fine-tuning of a subset of the RNN-T parameters. We proposed a very simple design of the imputation model by leveraging existing text-speech representations and alignments from the trained RNN-T model. Unlike existing methods, TOLSTOI does not modify the base RNN-T architecture and can adapt existing pre-trained ASR models without increasing inference time during decoding. Via experiments on three target domains and two ASR models, we show that TOLSTOI provides the best accuracy on a mixed source-target test set since it is least subject to catastrophic forgetting while reducing target WER by more than 35%. With a detailed ablation over more complicated models, we justify the effectiveness of our simple imputation model. As part of future work, we would like to experiment our approach on low-resource languages and explore techniques for online adaptation of the ASR model.

6 REPRODUCIBILITY STATEMENT

All our experiments are performed on publicly available datasets such as Switchboard, ATIS, HarperValleyBank, and Librispeech. We also use published train/test splits specified for each of these datasets, thus enabling reproducibility. We have provided sufficient implementation details of our baseline models, our imputation model and the RNN-T fine-tuning process to help reproduce our main results.

REFERENCES

Jerome R Bellegarda. Statistical language model adaptation: review and perspectives. *Speech communication*, 42(1):93–108, 2004.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *International conference on machine learning*, pp. 1597–1607. PMLR, 2020.

Xie Chen, Zhong Meng, Sarangarajan Parthasarathy, and Jinyu Li. Factorized neural transducer for efficient language model adaptation. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 8132–8136. IEEE, 2022.

Christopher Cieri, David Miller, and Kevin Walker. The fisher corpus: A resource for the next generations of speech-to-text. In *LREC*, volume 4, pp. 69–71, 2004.

Yan Deng, Rui Zhao, Zhong Meng, Xie Chen, Bing Liu, Jinyu Li, Yifan Gong, and Lei He. Improving RNN-T for Domain Scaling Using Semi-Supervised Training with Neural TTS. In *Proc. Interspeech 2021*, pp. 751–755, 2021. doi: 10.21437/Interspeech.2021-1017.

Siva Reddy Gangireddy, Pawel Swietojanski, Peter Bell, and Steve Renals. Unsupervised adaptation of recurrent neural network language models. In *Interspeech*, pp. 2333–2337, 2016.

John J Godfrey, Edward C Holliman, and Jane McDaniel. Switchboard: Telephone speech corpus for research and development. In *Acoustics, Speech, and Signal Processing, IEEE International Conference on*, volume 1, pp. 517–520. IEEE Computer Society, 1992.

Ian J Goodfellow, Mehdi Mirza, Da Xiao, Aaron Courville, and Yoshua Bengio. An empirical investigation of catastrophic forgetting in gradient-based neural networks. *arXiv preprint arXiv:1312.6211*, 2013.

Alex Graves. Sequence transduction with recurrent neural networks. *arXiv preprint arXiv:1211.3711*, 2012.

Alex Graves, Abdel-rahman Mohamed, and Geoffrey Hinton. Speech recognition with deep recurrent neural networks. In *2013 IEEE international conference on acoustics, speech and signal processing*, pp. 6645–6649. Ieee, 2013.

Awni Hannun, Carl Case, Jared Casper, Bryan Catanzaro, Greg Diamos, Erich Elsen, Ryan Prenger, Sanjeev Satheesh, Shubho Sengupta, Adam Coates, et al. Deep speech: Scaling up end-to-end speech recognition. *arXiv preprint arXiv:1412.5567*, 2014.

Yanzhang He, Tara N Sainath, Rohit Prabhavalkar, Ian McGraw, Raziel Alvarez, Ding Zhao, David Rybach, Anjuli Kannan, Yonghui Wu, Ruoming Pang, et al. Streaming end-to-end speech recognition for mobile devices. In *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6381–6385. IEEE, 2019.

Charles T Hemphill, John J Godfrey, and George R Doddington. The atis spoken language systems pilot corpus. In *Speech and Natural Language: Proceedings of a Workshop Held at Hidden Valley, Pennsylvania, June 24-27, 1990*, 1990.

Takaaki Hori, Daniel Willett, and Yasuhiro Minami. Language model adaptation using wfst-based speaking-style translation. In *2003 IEEE International Conference on Acoustics, Speech, and Signal Processing, 2003. Proceedings.(ICASSP'03).*, volume 1, pp. I–I. IEEE, 2003.

Raviraj Joshi and Anupam Singh. A simple baseline for domain adaptation in end to end asr systems using synthetic data. In *Proceedings of The Fifth Workshop on e-Commerce and NLP (ECNLP 5)*, pp. 244–249, 2022.

Anjuli Kannan, Yonghui Wu, Patrick Nguyen, Tara N. Sainath, ZhiJeng Chen, and Rohit Prabhavalkar. An analysis of incorporating an external language model into a sequence-to-sequence model. In *2018 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 1–5828, 2018. doi: 10.1109/ICASSP.2018.8462682.

Ilya Loshchilov and Frank Hutter. Decoupled weight decay regularization. *arXiv preprint arXiv:1711.05101*, 2017.

Alvin Martin and Mark Przybocki. The nist 1999 speaker recognition evaluation—an overview. *Digital signal processing*, 10(1-3):1–18, 2000.

John S Mason and X Zhang. Velocity and acceleration features in speaker recognition. In *Acoustics, Speech, and Signal Processing, IEEE International Conference on*, pp. 3673–3674. IEEE Computer Society, 1991.

Erik McDermott, Hasim Sak, and Ehsan Variani. A density ratio approach to language model fusion in end-to-end automatic speech recognition. In *2019 IEEE Automatic Speech Recognition and Understanding Workshop (ASRU)*, pp. 434–441. IEEE, 2019.

Zhong Meng, Sarangarajan Parthasarathy, Eric Sun, Yashesh Gaur, Naoyuki Kanda, Liang Lu, Xie Chen, Rui Zhao, Jinyu Li, and Yifan Gong. Internal language model estimation for domain-adaptive end-to-end speech recognition. In *2021 IEEE Spoken Language Technology Workshop (SLT)*, pp. 243–250. IEEE, 2021a.

Zhong Meng, Yu Wu, Naoyuki Kanda, Liang Lu, Xie Chen, Guoli Ye, Eric Sun, Jinyu Li, and Yifan Gong. Minimum Word Error Rate Training with Language Model Fusion for End-to-End Speech Recognition. In *Proc. Interspeech 2021*, pp. 2596–2600, 2021b. doi: 10.21437/Interspeech.2021-2075.

Mehryar Mohri, Fernando Pereira, and Michael Riley. Weighted finite-state transducers in speech recognition. *Computer Speech & Language*, 16(1):69–88, 2002.

Graham Neubig, Shinsuke Mori, and Tatsuya Kawahara. A wfst-based log-linear framework for speaking-style transformation. In *Tenth Annual Conference of the International Speech Communication Association*. Citeseer, 2009.

Perez Ogayo, Graham Neubig, and Alan W Black. Building african voices. *arXiv preprint arXiv:2207.00688*, 2022.

Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. Librispeech: an asr corpus based on public domain audio books. In *2015 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pp. 5206–5210. IEEE, 2015.

Daniel S Park, William Chan, Yu Zhang, Chung-Cheng Chiu, Barret Zoph, Ekin D Cubuk, and Quoc V Le. Specaugment: A simple data augmentation method for automatic speech recognition. *arXiv preprint arXiv:1904.08779*, 2019.

Junho Park, Xunying Liu, Mark JF Gales, and Phil C Woodland. Improved neural network based language modelling and adaptation. In *Eleventh Annual Conference of the International Speech Communication Association*, 2010.

Joseph W Picone. Signal modeling techniques in speech recognition. *Proceedings of the IEEE*, 81 (9):1215–1247, 1993.

Janne Pylkkonen, Antti Ukkonen, Juho Kilpikoski, Samu Tamminen, and Hannes Heikinheimo. Fast text-only domain adaptation of rnn-transducer prediction network. In *22nd Annual Conference of the International Speech Communication Association, INTERSPEECH 2021*, Proceedings of the Annual Conference of the International Speech Communication Association, INTERSPEECH, pp. 1882–1886. ISCA, 2021. doi: 10.21437/Interspeech.2021-1191.

George Saon, Zoltán Tüske, and Kartik Audhkhasi. Alignment-length synchronous decoding for rnn transducer. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 7804–7808. IEEE, 2020.

George Saon, Zoltán Tüske, Daniel Bolanos, and Brian Kingsbury. Advancing rnn transducer technology for speech recognition. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 5654–5658. IEEE, 2021.

Rico Sennrich, Barry Haddow, and Alexandra Birch. Neural machine translation of rare words with subword units. *arXiv preprint arXiv:1508.07909*, 2015.

Jonathan Shen, Ruoming Pang, Ron J Weiss, Mike Schuster, Navdeep Jaitly, Zongheng Yang, Zhifeng Chen, Yu Zhang, Yuxuan Wang, Rj Skerrv-Ryan, et al. Natural tts synthesis by conditioning wavenet on mel spectrogram predictions. In *2018 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pp. 4779–4783. IEEE, 2018.

Leslie N Smith and Nicholay Topin. Super-convergence: Very fast training of neural networks using large learning rates. In *Artificial intelligence and machine learning for multi-domain operations applications*, volume 11006, pp. 369–386. SPIE, 2019.

Yuki Takashima, Shota Horiguchi, Shinji Watanabe, Paola García, and Yohei Kawaguchi. Updating only encoders prevents catastrophic forgetting of end-to-end asr models. *arXiv preprint arXiv:2207.00216*, 2022.

Samuel Thomas, Brian Kingsbury, George Saon, and Hong-Kwang J Kuo. Integrating text inputs for training and adapting rnn transducer asr models. In *ICASSP 2022-2022 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 8127–8131. IEEE, 2022.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

Mike Wu, Jonathan Nafziger, Anthony Scodary, and Andrew Maas. Harpervalleybank: A domain-specific spoken dialog corpus. *arXiv preprint arXiv:2010.13929*, 2020.

Hainan Xu, Tongfei Chen, Dongji Gao, Yiming Wang, Ke Li, Nagendra Goel, Yishay Carmiel, Daniel Povey, and Sanjeev Khudanpur. A pruned rnnlm lattice-rescoring algorithm for automatic speech recognition. In *2018 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pp. 5929–5933. IEEE, 2018.

Xianrui Zheng, Yulan Liu, Deniz Gunceler, and Daniel Willett. Using synthetic audio to improve the recognition of out-of-vocabulary words in end-to-end asr systems. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 5674–5678. IEEE, 2021.

Han Zhu, Gaofeng Cheng, Jindong Wang, Wenxin Hou, Pengyuan Zhang, and Yonghong Yan. Boosting cross-domain speech recognition with self-supervision. *arXiv preprint arXiv:2206.09783*, 2022.

A   APPENDIX

A.1   ANECDOTAL EXAMPLES

Reference	we are going to fly listen we are going to fly over saint louis
Unadapted	we are going to fly listen we are going to fly over saint louis
Shallow Fusion	we are going to fly listen we are going to fly over saint louis
TOLSTOI	we are going to fly listen we are going to fly over saint louis
Reference	he went moved to texas
Unadapted	he went moved to texas
Shallow Fusion	he went and moved to texas
TOLSTOI	he went moved to texas
Reference	i would like to transfer money between my accounts
Unadapted	i would like to transfer money between my accountants
Shallow Fusion	i would like to transfer money between my account
TOLSTOI	i would like to transfer money between my accounts
Reference	yeah we played softball last night we were clobbered
Unadapted	yeah we played softball last night we were clobbered
Shallow Fusion	yeah we played softball last night we were clovered
TOLSTOI	yeah we played softball last night we were clobbered

Table 4: Anecdotal examples on the mixed test set comparing TOLSTOI with shallow fusion. Deletion errors are underlined and highlighted in red.

Reference	thanks you too
Unadapted	thanks you too
Shallow Fusion	thanks you too
TOLSTOI	thank you TODAY
Reference	they plan to get married in topeka since most of their friends are there
Unadapted	they plan to get married in to figure since most of their friends are there
Shallow Fusion	they plan to get married into since most of their friends are there
TOLSTOI	they plan to get married in to peak us since most of their friends are there
Reference	show me weekday flights from milwaukee to orlando one way
Unadapted	show me weak day flights from milwaukee to orlando one way
Shallow Fusion	show me weekday flights from milwaukee to orlando one way
TOLSTOI	show me weakday flights from milwaukee to orlando one way

Table 5: Anecdotal examples showing the mistakes with TOLSTOI and shallow fusion. Errors are underlined and highlighted in red. When the language model context is not clear (e.g, for word topeka), TOLSTOI produces acoustically similar predictions as opposed to the Shallow Fusion and Unadapted models.