TextSETTR: Label-Free Text Style Extraction and Tunable Targeted Restyling

Abstract

We present a novel approach to the challenging problem of label-free text style transfer. Unlike previous approaches that use parallel or non-parallel labeled data, our technique removes the need for labels entirely, relying instead on the implicit connection in style between adjacent sentences in unlabeled text. We show that T5 (Raffel et al., 2019), a strong pretrained text-to-text model, can be adapted to extract a style vector from arbitrary text and use this vector to condition the decoder to perform style transfer. As the resulting learned style vector space encodes many facets of textual style, we recast transfers as "targeted restyling" vector operations that adjust specific attributes of the input text while preserving others. When trained over unlabeled Amazon reviews data, our resulting TextSETTR model is competitive on sentiment transfer, even when given only four exemplars of each class. Furthermore, we demonstrate that a single model trained on unlabeled Common Crawl data is capable of transferring along multiple dimensions including dialect, emotiveness, formality, politeness, and sentiment.

1 Introduction

There has been a recent surge of interest in text style transfer, with the aim of training models able to modify specific attributes of input text (e.g., sentiment or formality) while preserving the remaining content. For example, a sentiment transfer model might transform the input "best book ever!" into "worst book ever!", while a formality transfer model might change the same input into "This is the best book I have ever read."

Work in this area falls into three categories. **Supervised** approaches like Jhamtani et al. (2017) transfer between pre-selected styles, and rely on aligned parallel training data to teach the model the desired input/output correspondence. This method is limited by the availability of parallel corpora. So-called **"unsupervised"** approaches like Li et al. (2018) and Lample et al. (2019) remove the requirement for parallel data, but still require labeled training examples of each style, and are limited to transfer between a pre-specified set of styles. **Label-free** approaches like the recent Xu et al. (2020) remove the need for any training labels. While the most technically challenging, this offers the potential for transferring between arbitrary styles at inference time and has significant value, as curated datasets are not available for many style attributes.

In this work, we explore the hypothesis that large pretrained text-to-text models like T5 (Raffel et al., 2019) already contain a strong representation of textual style, which can be extracted and used to condition the decoder of a style transfer model through a relatively lightweight fine-tuning procedure. To isolate style information in the absence of labels, we rely on the observation that style is a "slow-moving" feature, which tends to be consistent over large spans of text. Specifically, given two adjacent sentences from an unlabeled corpus, we train our model to extract a "style vector" from the first and use that vector to perform denoising and other reconstruction tasks on the second. This technique extends the unsupervised approach of Lample et al. (2019) to the label-free setting, and allows us to reformulate the style transfer operation as a directional operation in style vector space using the difference between target and source style vectors; we call this "targeted restyling". When combined with a novel "tunable inference" technique for controlling the token add/delete rates of the transfer, this gives our final model: **Text Style Extraction and Tunable Targeted Restyling** (TextSETTR).

Figure 1: TextSETTR architecture for label-free style transfer. The Encoder, Decoder and Style Extractor (Ex) are transformer stacks initialized from pretrained T5. During training, the model reconstructs a corrupted input, conditioned on a fixed-width "style vector" extracted from the preceding sentence. At inference time, a new style vector is formed via "targeted restyling": adding a directional delta to the extracted style of the input text. Stochastic tuning ranges provide extra conditioning for the decoder, and enable fine-grained control of inference.

Our main contributions are to: (1) demonstrate the viability of label-free style transfer,[1] (2) use sentence adjacency as a means for inducing text style representations, (3) reframe style transfer as "targeted restyling" directional operations in style space, (4) introduce "tunable inference" for finer-grained control of transfers, (5) show the effectiveness of "noisy" back-translation training, and (6) illustrate few-shot generalization to a range of style attributes including dialect, emotiveness, formality, politeness, and sentiment.

2 METHOD

Figure 1 illustrates our proposed TextSETTR architecture. At a high level, our approach follows Lample et al. (2019), who train a denoising auto-encoder conditioned on a fixed-width style vector. The key difference in our case is that the true style is unknown at training time. To overcome this, we jointly train a "style extractor" component to induce a useful style representation (that can aid in reconstruction) from text in the nearby context. We describe this in more detail below.

2.1 MODEL ARCHITECTURE

We conduct our experiments using a modified version of the Text-to-Text Transfer Transformer (T5) (Raffel et al., 2019). Like T5, our model includes a transformer-based encoder and decoder. As in T5 pretraining, the input to the encoder is a corrupted/noised version of the target, resulting in a reconstruction task. Our goal is to design a type of corruption that results in this training task resembling style transfer, despite the lack of labeled training data.

Our core addition to T5 is the style extractor. Based on the encoder's architecture, this component's input is an uncorrupted sentence in the same style as the target; relying on our assumption that style is a slow-moving feature, we use the sentence preceding the target (the "context") for this. This encourages extracting a style representation that is useful for repairing the corrupted input.

The only architectural difference between the encoder and style extractor is that we mean-pool the style extractor's hidden state sequence into a single fixed-width vector (the "style vector"); in our experiments, the dimensionality of this vector and the encoder hidden states is 1024. To incorporate the style vector into the rest of the model, we simply add it to each of the final encoder hidden states.

---

[1]Our work is concurrent with Xu et al. (2020), who offer a substantially different approach to label-free style transfer, as discussed in Sections 3 and 5.

We initialize the weights of our model with those of a pretrained T5 model. We initialize both the style extractor and encoder from the pretrained encoder, but the weights are *not* tied during training.

2.2 CORRUPTION STRATEGIES

We experiment with combinations of three different reconstruction tasks, each contributing a loss term. All three share the same overall structure, where a sentence s_i in the dataset is corrupted by some function f to produce $\tilde{s}_i = f(s_i)$. The cross-entropy loss is calculated using the uncorrupted sentence s_i as the target, the corrupted sentence $\tilde{s}_i$ as the input, and the uncorrupted preceding sentence s_{i-1} as the context. The three choices of f are Noise (N), Back-Translation (BT), and Noisy Back-Translation (NBT), described below.

Noise (N) This function corrupts the input by (i) dropping, (ii) replacing, and/or (iii) shuffling tokens, in that order. For each example we sample a separate noise probability p for each sub-type of noise from a uniform distribution in the range 20–60%. We do this because the model should be able to "undo" varying degrees of noise, as some types of style transfer may require changing only a few tokens, while others may require larger rewrites.

For *drop* noise, we drop each token in s_i with independent probability p. For *replace* noise, let s_{ik} be the k-th token within s_i. For each s_i, a random other example s_j is chosen, and then each token s_{ik} is replaced by s_{jk} with probability p . If s_j has fewer than k tokens, then the replacement does not occur. For *shuffle* noise, each token in s_i is chosen with probability p, and then all chosen tokens are randomly shuffled to the position of another chosen token, leaving non-chosen tokens in place.

The use of drop and shuffle noise results in a loss term similar to the denoising loss used by Lample et al. (2019). Their motivation for this loss was to encourage language modeling. As we fine-tune an already-strong T5 language model in our experiments, our motivation is rather to introduce a *conditional* element to the language model, in the form of the extracted style vector input.

Back-Translation (BT) This corruption function, also used by Lample et al. (2019), runs the current version of the model in inference mode to transfer s_i into a different style, giving the corrupted $\tilde{s}_i$. In prior work using labels, specifying a different target style was straightforward. In our case, because we do not have access to labels, we simply sample a random sentence s_j to use as the context. To increase diversity of the generated examples, we decode with sampling instead of greedy decoding.

Because $\tilde{s}_i$ is produced by a strong language model, BT should result in training examples where both the input and output are coherent sentences, matching our intended inference setting. By contrast, the text produced by "Noise" corruption does not resemble test-time inputs.

Noisy Back-Translation (NBT) This novel corruption function is a composition of the previous two. Noise is first applied to s_i as described above, and the result is used as the input (with randomly-sampled s_j as the context) to produce $\tilde{s}_i$, using the current model in inference mode, as in BT.

Once the model has learned to undo random noise from the associated loss term, NBT should produce training examples where some of the tokens are preserved from s_i while others were generated by the model itself under the influence of the "incorrect" context s_j. This is similar to BT, but we hypothesize that it may be better suited to style transfer. BT was originally used for machine translation (Sennrich et al., 2016), a setting where most or all input tokens need to be changed. In contrast, style transfer within a single language usually requires only changing a subset of input tokens; the training examples resulting from the NBT procedure should have this property. We believe that this will encourage the model to identify which tokens in the input do not match the target style indicated by s_{i-1} and change them, which is exactly what we want a style transfer model to do. This is conceptually similar to the work of Clark et al. (2020), who pretrain language models to discriminate which input tokens were originally present and which were altered by a simpler language model.

Final Loss The final loss term used for training is the sum of the above loss terms, each calculated from the same input s_i. However, not every model we experiment with includes all three losses.

2.3 INFERENCE PROCEDURE

Tunable Add/Delete Rates In preliminary experiments, we observed a recurring problem that the model would often change either far too little (failing to achieve the target style), or far too much

(failing to preserve the input content). To address this problem, we introduce a "tunable inference" mechanism to constrain how much content should be added and deleted at inference time.

For every input/output pair during training, we calculate the proportions of tokens that were added and deleted. The "add rate" is the proportion of output tokens absent from the input, and the "delete rate" is the proportion of input tokens absent from the output.[2] Rather than provide these rates directly to the decoder, we provide *ranges*, covering but not necessarily centered around the true rates. Specifically, we sample each range width uniformly from [0,1], and uniformly sample the "alignment" of the true rate within the range. The final ranges are clipped to [0,1], and passed to the decoder as four float values: [min_add_rate, max_add_rate, min_del_rate, max_del_rate].[3] This approach allows for more flexibility at inference time, so we can enforce tight or loose constraints on each rate.

Targeted Restyling While previous work on style transfer has largely assumed a fixed set of discrete styles, our method can extract a "ready-made" style vector from any sentence. We expect this learned representation to capture a rich summary of the sentence, covering many attributes. For example, a given style vector might encode that a sentence is informal, humorous, in British English, and so on.

In this framework, transferring a single attribute (e.g., informal → formal) is not as simple as just providing a vanilla "formal" style target, as this would ignore all the other attributes that defined the original input. Rather, we must operate in style space to construct a new target style that is simultaneously formal, humorous, British, and so on.

Concretely, at inference time, we assume access to a small set of "exemplar" sentences (between 1 and 100) for both the source value (e.g., informal) and target value (e.g., formal) of the attribute being modified. We infer style vectors for each exemplar using the style extractor, and take the mean of each class, giving vectors v^{src} and v^{trg}. Assuming the exemplar pools are relatively diverse, this averaging should "wash out" most attributes not being targeted.

To transfer an input sentence x, we apply a targeted restyling in the appropriate direction. After extracting the original style from the input itself, v^x, we compute the target output style by moving in the direction of the delta between the source and target attributes values, as in (1), producing the style vector used for decoding. In practice, we find that the delta scale λ is an important hyperparameter to tune. Generally values in the range $[1.0, 10.0]$ work well, with the best values depending on the attribute and the exemplars in question.

$$v^x + \lambda \times \left(v^{trg} - v^{src} \right) \tag{1}$$

3 EXPERIMENTS

To evaluate our approach and better understand the effects of our various design choices, we test on label-free sentiment transfer, using the Amazon reviews dataset of Li et al. (2018). However, as their training split doesn't indicate which sentences were adjacent in the original reviews, we make use of a different source of raw review text.

Training Procedure Our unlabeled training data comes from the 233.1M Amazon reviews provided by Ni et al. (2019). Ignoring the star ratings completely, we extract adjacent lines from multi-line reviews to use as the context and input for our training procedure, giving 23.6M examples. We also preprocess all text to match the format of the Li et al. (2018) data, as detailed in Appendix A.3. Initializing our model from pretrained T5 (t5.1.1.large)[4], we fine-tune on these examples, optimizing the joint reconstruction loss from Section 2. Our default TextSETTR configuration is selected based on preliminary experiments (on development data) varying the set of reconstruction tasks and inference procedures. The model uses an equally weighted combination of the Noise (N) and Noisy Back-Translation (NBT) tasks. For both tasks, we use drop and replace noise, but no shuffle noise. We fine-tune for 10k steps, with a batch size of 65,536 tokens, and a fixed learning rate of 1e-3.

---

[2]This calculation ignores word order. As one example, if a token appears three times in the input and five times in the output, two of the five occurrences are counted as "added".

[3]More specifically, a vector is prepended to the sequence of encoder hidden states, holding the tuning rates as the first four values, and zeros elsewhere.

[4]https://github.com/google-research/text-to-text-transfer-transformer

Model	Acc.	Content
TextSETTR	73.3	34.7
N	23.4	84.4
N + BT	13.3	98.7
−replace noise	66.1	42.1
+shuffle noise	70.3	34.1
manual exemplars	52.4	44.2
−tunable inference	71.5	39.4
CP-G	60.1	35.4
CP-B	40.0	39.7
CrossAligned	83.1	15.2
Delete&Retrieve	50.9	16.1
B-GST	60.0	73.6

Figure 2: Automatic evaluation metrics comparing our TextSETTR model, ablations, and previous work. Up-and-right is better. We train for 10k steps and use add/delete:20–40% unless otherwise specified. Scores for CrossAligned, Delete&Retrieve and B-GST are from Sudhakar et al. (2019).

Evaluation Procedure Following previous work, we use automatic metrics to assess attribute control (sentiment) and content preservation on the Li et al. (2018) test data. To estimate the sentiment of the transferred output text, we fine-tune a BERT-Large classifier (Devlin et al., 2019) on the Li et al. (2018) train split, scoring 87.8% accuracy on the dev split. For content preservation, we follow previous work and report the self-BLEU score between the generated text and the input.

To perform transfers, we follow the procedure from Section 2.3. For our default setup, we sample 100 positive and 100 negative exemplars from Li et al. (2018) train. We also experiment with using a set of manually selected exemplars consisting of just four examples of each class. We use greedy decoding, a delta scale of $\lambda=8$, and add/delete tuning ranges of 20–40% unless otherwise specified.

Core Results Figure 2 shows our core results. Our default TextSETTR configuration (using N+NBT training and tuning ranges 20–40%) achieves 73.3% accuracy at swapping sentiment (as judged by the classifier), while still staying somewhat close to the original input text (self-BLEU 34.7). Due to the tunable inference technique, we can also trade off accuracy for content preservation by adjusting the add/delete rates, as seen in the different points along the green line. Notably, TextSETTR outperforms the label-free CP-G and CP-B models of Xu et al. (2020). More remarkably, TextSETTR outperforms several approaches that rely on training labels: CrossAligned (Shen et al., 2017) and Delete&Retrieve (Li et al., 2018). However there is still a gap between our label-free approach and the best performing labeled model, B-GST (Sudhakar et al., 2019).

Ablations Lample et al. (2019) showed promising results by combining noise (N) with back-translation (BT). However we find this combination unstable. When training for 10k steps, our N and N+BT models nearly always copy their input. By increasing the training steps to 50k, we can recover reasonable performance, but the metrics still fall below the TextSETTR line, using our novel NBT task. Additionally, while Lample et al. (2019) use drop and shuffle noise, we find that only drop and replace are valuable, while shuffle noise can be removed without negative effect.

To test the limits of our model's generalization, we reduce the set of exemplars to four manually selected examples of each class.[5] In this setting, we also find reducing delta scale to $\lambda=4$ is beneficial. The results, shown as "manual exemplars" in Figure 2, are still competitive, indicating that our approach generalizes well to the few-shot inference setting.

To assess the value of tunable add/delete rates, we also train a model (−tunable) without this feature. While the automatic metrics are slightly above the TextSETTR line, we observe several advantages to the tunable model. First, we observe it significantly reduces the variance in self-BLEU across different inputs. For example, focusing on the case of overly high self-BLEU, we find that without

---

[5]five stars , amazing . / i really love this product . / works great , will buy again . / it is well made , and a pleasure to use . // zero stars , horrible . / i really hate this product . / does not work, will not buy again . / it is poorly made , and a pain to use .

Model	Accuracy	Content
TextSETTR	83.6	39.4
add/del: 0–20%	63.4	76.9
add/del: 10–30%	72.7	60.2
add/del: 30–50%	89.7	21.5
Lample et al. 2019	82.6	54.8

Figure 3: Comparison with Lample et al. (2019) on the evaluation setting that includes pos→pos and neg→neg transfers.

Figure 4: 2D UMAP embedding of the style vectors extracted by our TextSETTR model for text inputs from Amazon reviews covering three product categories and two sentiment labels.

tunable inference, 14.6% of dev eval outputs are identical to the inputs, whereas with tunable inference, this goes to 0.9%. Second, tunable inference decreases the effect of delta scale on self-BLEU. If we vary λ in the range [1,8], the tunable model's self-BLEU stays between 34.7–64.9, while the non-tunable model's self-BLEU varies from 39.4–88.5. Finally, through qualitative analysis in Section 4, we find that tunable inference allows more flexibility for controlling different types of transfer.

In Figure 3, we compare with Lample et al. (2019) on the evaluation setting including pos→pos and neg→neg transfers. Note that this type of evaluation doesn't match our inference procedure, which assumes that the input and output styles differ. Nevertheless, TextSETTR comes fairly close to the performance of Lample et al. (2019), despite not benefiting from training labels.

To demonstrate that our learned style extractor encodes multiple aspects of textual style, we compute style vectors for 12,000 lines of text from three review categories (Fashion, Software, Pantry) from the Ni et al. (2019) Amazon review data. Within each category, we sample 2,000 positives (4 or 5 star) and 2,000 negatives (1 or 2 star), filtering examples where our BERT classifier disagrees with the true rating. Figure 4 plots a 2D UMAP dimensionality reduction (McInnes et al., 2018) of the vectors, and shows clear separation along both sentiment and product category.[6]

4   QUALITATIVE ANALYSIS

One advantage of label-free style transfer is that, in theory, a single model can be used to perform transfer along any "dimension" of style, given only a few exemplars, and without the need for additional training. In this section, we investigate the degree to which our approach achieves this goal in practice. For this purpose, we train a single general-purpose TextSETTR model, with the same

---

[6]We sub-sample to 3,000 points after dimensionality reduction for clearer visualization. Note, we don't expect perfect separation, as some lines of text, such as "I love this product" are underspecified as to category.

Reserved ⇒ Emotive	Emotive ⇒ Reserved
I liked the movie.	I loved every minute of the movie!
⇒ I cannot even describe how amazing this movie was!!	⇒ I liked the movie.
I was impressed with the results.	I was shocked by the amazing results!
⇒ I was absolutely blown away with the results!!	⇒ I was surprised by the results.
American ⇒ British	**British ⇒ American**
The elevator in my apartment isn't working.	The lift in my flat isn't working.
⇒ The lift in my flat isn't working.	⇒ The elevator in my apartment isn't working.
The senators will return to Washington next week.	MPs will return to Westminster next week.
⇒ The MPs will return to Westminster next week.	⇒ Representatives will return to Washington next week.
Polite ⇒ Rude	**Rude ⇒ Polite**
Are you positive you've understood my point?	What the hell is wrong with your attitude?
⇒ you've never understood my point!	⇒ Perhaps the question is more about your attitude.
Could you ask before using my phone?	I could care less, go find somebody else to do this crap.
⇒ I ask you to stop using my phone!	⇒ I could be wrong, but I would try to find somebody else to do this.
Formal ⇒ Informal	**Informal ⇒ Formal**
I hereby commit to never purchase anything from this institution in the future.	best book ever!!
	⇒ The book is highly recommended.
⇒ i gonna never buy anything from this place again.	
I couldn't figure out what the author was trying to say.	couldnt figure out what author tryna say
⇒ i dont know what ur trying to say.	⇒ The reader couldnt figure out what the author was trying to say.
Positive ⇒ Negative	**Negative ⇒ Positive**
I was pretty impressed with the results.	I was pretty disappointed with the results.
⇒ I was pretty disappointed with the results.	⇒ I was pretty impressed with the results.
I will definitely buy this brand again.	I definitely won't buy this brand again.
⇒ I will definitely not buy this brand again.	⇒ I definitely won't hesitate to buy this brand again.

Table 1: Examples of transferring along five different axes of style. The same model is used across all examples, with no additional training. Words deleted from the input are red, and words added in the output are blue. Within each category, a fixed tiny set of exemplars is chosen, and a fixed delta scale and tuning rates are used. The exemplars and settings are provided in Appendix A.2.

configuration as our model from Section 3, except fine-tuned for 200k steps on English Common Crawl data (the same "C4" data that T5 pretrained on) as opposed to Amazon reviews.

Transferable Attributes Given that our architecture limits the style representation to 1024 dimensions, one may ask how the unsupervised model will make use of this capacity, and which style attributes will be encoded in the learned space. Encouragingly, we find that our model trained on unlabeled Common Crawl data is capable of transferring along many independent axes of style. Table 1 shows selected successful examples of our Common Crawl model transferring emotiveness, dialect, politeness, formality and sentiment. The same model is used in each case, with no additional training. At inference time, a tiny set of exemplars (1–5 examples of each class) is the only labeled data used to compute the style vector delta; these exemplars are presented in the Appendix.

Across each type of transfer, we see evidence of generalization beyond the specifics of the chosen exemplars. In making text more emotive, the model uses *amazing* and *blown away*, despite these terms not occurring in the exemplars. In making text more polite, the model inserts novel hedges like *perhaps* and *I could be wrong*. In transferring between American and British styles, the model generalizes to unseen vocabulary items (*elevator ↔ lift*) and draws sound conceptual analogies (*senators ↔ MPs*).

Beyond Style Transfer We observe three other noteworthy abilities of our model, which we outline briefly, providing further examples of each in Appendix A.1. First, if inference is tuned to add rather than delete tokens, we find the model is capable of generating style-sensitive **completions**. For instance, if we reuse the American and British exemplars used to produce the results in Table 1 but set the tuning ranges to add:40–70%, delete:0%, the model completes the input *My favorite hot drink:* with either *Starbucks Coffee* (American) or *a mug of tea* (British).

In the other direction, if we tune inference for heavy deletion but apply no modification to the input style vector, we find the model can perform coherent **shortening** of text while leaving most or all of the meaning intact. For instance, with add:0–5%, delete:40-90% the model shortens: "They do this without any prior knowledge of cats, for example, that they have fur, tails, whiskers and cat-like faces." ⇒ "They do not know that cats have fur, tails, whiskers and cat-like faces.".

Finally, if instead of applying a *targeted* style delta vector, we add a small *random* delta to the input style, we find our model can output a range of largely meaning-preserving **random augmentations**. For example depending on tuning ranges, the model may transfer the input *What'll the weather be tomorrow?* into outputs *What's the weather forecast for tomorrow?* (add/delete: 30–50%) or *What's the weather like for the next day?* (add/delete: 50-70%). Further examples are in Appendix A.1.

5 RELATED WORK

As mentioned at the outset, recent work on text style transfer falls into three classes: supervised, unsupervised, and label-free. Supervised style transfer has seen limited research due to the difficulty of obtaining parallel data. Examples can be seen in Jhamtani et al. (2017) and Carlson et al. (2018).

Unsupervised Approaches The bulk of research has focused on "unsupervised" approaches, which rely on labeled but non-parallel data. Typically, labels are assumed to be available for both source and target styles (Dai et al., 2019; He et al., 2020; Lample et al., 2019; Li et al., 2018; Niu et al., 2018; Prabhumoye et al., 2018; Shen et al., 2017; Sudhakar et al., 2019; Wu et al., 2019; Yang et al., 2018). However Zhao et al. (2018) also explore the case where only the target style is labeled. The use of labels at training time can aid modeling, but limits the applicability of these methods, as labeled datasets are not readily available for many attributes of interest.

Our work differs from the above by removing the need for training labels, and offering a single model that can target an unrestricted set of style attributes. Despite these differences, our work shares some similarities with past work. For example, our encoder-decoder architecture and corruption methods are similar to Lample et al. (2019), and we leverage a strong pretrained language model, as in Sudhakar et al. (2019) and Wu et al. (2019).

Label-Free Approaches A label-free approach has recently been explored by Xu et al. (2020). The authors train a variational auto-encoder on unlabeled text, where a "manipulable" portion of the latent representation is constrained to fall on a k-dimensional simplex. To perform transfer, they identify empirically the basis vector that most strongly corresponds to the target attribute, and manipulate its magnitude. Compared to our approach, a key difference is that the number of latent factors must be chosen ahead of time, and this limits the number of attributes that may be controlled. Additionally, there is no guarantee that a single basis of the learned simplex will correspond to a target attribute such as dialect or politeness.

Controlled Generation A separate strand of research explores "controlled generation" methods for supplementing generative language models to allow for control of specific attributes of the output text. As with style transfer, this can be achieved either through labeled examples, as in CTRL (Keskar et al., 2019) and PPLM (Dathathri et al., 2020), or label-free, as in CoCon (Chan et al., 2020). The key difference between these models and style transfer models is that they aim to generate plausible *continuations* following a prompt, as opposed to transferring attributes of a fully-formed input while preserving as much content as possible. It is not clear if controlled generation models could be used to perform style transfer, and they have not to our knowledge been evaluated in this context.

6 CONCLUSION

In this work, we have presented a unique approach to label-free text style transfer that can achieve results comparable to systems trained with labels (an easier setting), while allowing control of how much of the input is changed. We also demonstrate with qualitative results that this approach can be used to produce a single system capable of performing many different types of style transfer, requiring only a handful of labeled exemplars at inference time.

REFERENCES

Keith Carlson, Allen Riddell, and Daniel Rockmore. Evaluating prose style transfer with the bible. *Royal Society Open Science*, 5(10):171920, 2018. doi: 10.1098/rsos.171920.

Alvin Chan, Yew-Soon Ong, Bill Pung, Aston Zhang, and Jie Fu. CoCon: A self-supervised approach for controlled text generation. *arXiv preprint arXiv:2006.03535*, 2020.

Kevin Clark, Minh-Thang Luong, Quoc V. Le, and Christopher D. Manning. Electra: Pre-training text encoders as discriminators rather than generators. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=r1xMH1BtvB.

Ning Dai, Jianze Liang, Xipeng Qiu, and Xuanjing Huang. Style transformer: Unpaired text style transfer without disentangled latent representation. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 5997–6007, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1601.

Sumanth Dathathri, Andrea Madotto, Janice Lan, Jane Hung, Eric Frank, Piero Molino, Jason Yosinski, and Rosanne Liu. Plug and play language models: A simple approach to controlled text generation. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=H1edEyBKDS.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4171–4186, Minneapolis, Minnesota, June 2019. Association for Computational Linguistics. doi: 10.18653/v1/N19-1423.

Junxian He, Xinyi Wang, Graham Neubig, and Taylor Berg-Kirkpatrick. A probabilistic formulation of unsupervised text style transfer. In *International Conference on Learning Representations*, 2020. URL https://openreview.net/forum?id=HJlA0C4tPS.

Harsh Jhamtani, Varun Gangal, Eduard Hovy, and Eric Nyberg. Shakespearizing modern language using copy-enriched sequence to sequence models. In *Proceedings of the Workshop on Stylistic Variation*, pp. 10–19, Copenhagen, Denmark, September 2017. Association for Computational Linguistics. doi: 10.18653/v1/W17-4902.

Nitish Shirish Keskar, Bryan McCann, Lav R. Varshney, Caiming Xiong, and Richard Socher. CTRL: A conditional transformer language model for controllable generation. *arXiv preprint arXiv:1909.05858*, 2019.

Guillaume Lample, Sandeep Subramanian, Eric Smith, Ludovic Denoyer, Marc'Aurelio Ranzato, and Y-Lan Boureau. Multiple-attribute text rewriting. In *International Conference on Learning Representations*, 2019. URL https://openreview.net/forum?id=H1g2NhC5KQ.

Juncen Li, Robin Jia, He He, and Percy Liang. Delete, retrieve, generate: a simple approach to sentiment and style transfer. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 1865–1874, New Orleans, Louisiana, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/N18-1169.

Leland McInnes, John Healy, Nathaniel Saul, and Lukas Groberger. Umap: Uniform manifold approximation and projection. *Journal of Open Source Software*, 3(29):861, 2018. doi: 10.21105/joss.00861. URL https://doi.org/10.21105/joss.00861.

Jianmo Ni, Jiacheng Li, and Julian McAuley. Justifying recommendations using distantly-labeled reviews and fine-grained aspects. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 188–197, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1018. URL https://www.aclweb.org/anthology/D19-1018.

Xing Niu, Sudha Rao, and Marine Carpuat. Multi-task neural models for translating between styles within and across languages. In *Proceedings of the 27th International Conference on Computational Linguistics*, pp. 1008–1021, Santa Fe, New Mexico, USA, August 2018. Association for Computational Linguistics. URL `https://www.aclweb.org/anthology/C18-1086`.

Shrimai Prabhumoye, Yulia Tsvetkov, Ruslan Salakhutdinov, and Alan W Black. Style transfer through back-translation. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 866–876, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1080.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. Exploring the limits of transfer learning with a unified text-to-text transformer. *arXiv e-prints*, 2019.

Rico Sennrich, Barry Haddow, and Alexandra Birch. Improving neural machine translation models with monolingual data. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 86–96, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1009.

Tianxiao Shen, Tao Lei, Regina Barzilay, and Tommi Jaakkola. Style transfer from non-parallel text by cross-alignment. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 30*, pp. 6830–6841. Curran Associates, Inc., 2017. URL `http://papers.nips.cc/paper/7259-style-transfer-from-non-parallel-text-by-cross-alignment.pdf`.

Akhilesh Sudhakar, Bhargav Upadhyay, and Arjun Maheswaran. "transforming" delete, retrieve, generate approach for controlled text style transfer. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 3269–3279, Hong Kong, China, November 2019. Association for Computational Linguistics. doi: 10.18653/v1/D19-1322. URL `https://www.aclweb.org/anthology/D19-1322`.

Xing Wu, Tao Zhang, Liangjun Zang, Jizhong Han, and Songlin Hu. Mask and infill: Applying masked language model for sentiment transfer. In *Proceedings of the Twenty-Eighth International Joint Conference on Artificial Intelligence, IJCAI-19*, pp. 5271–5277. International Joint Conferences on Artificial Intelligence Organization, 7 2019. doi: 10.24963/ijcai.2019/732.

Peng Xu, Jackie Chi Kit Cheung, and Yanshuai Cao. On variational learning of controllable representations for text without supervision. In *Proceedings of the 37th International Conference on Machine Learning*, Vienna, Austria, 2020. PMLR 119.

Zichao Yang, Zhiting Hu, Chris Dyer, Eric P Xing, and Taylor Berg-Kirkpatrick. Unsupervised text style transfer using language models as discriminators. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems 31*, pp. 7287–7298. Curran Associates, Inc., 2018. URL `http://papers.nips.cc/paper/7959-unsupervised-text-style-transfer-using-language-models-as-discriminators.pdf`.

Yanpeng Zhao, Wei Bi, Deng Cai, Xiaojiang Liu, Kewei Tu, and Shuming Shi. Language style transfer from sentences with arbitrary unknown styles. *CoRR*, abs/1808.04071, 2018. URL `http://arxiv.org/abs/1808.04071`.

A APPENDIX

A.1 BEYOND STYLE TRANSFER

In this section, we provide additional examples illustrating the abilities of our TextSETTR model trained on Common Crawl data, beyond typical style transfer.

Examples of **dialect-sensitive completion** are given in Table 2. In each case, the model is passed an input of the form "My favorite X: ". Despite the fact that TextSETTR is not trained specifically for completions, we can use the add and delete rates to encourage the model to insert a few additional tokens, while leaving the original prompt largely unchanged.[7]

The completions show a detailed knowledge of American and British culture. Furthermore, it is remarkable that the model is able to generalize to these "deeper" cultural differences, given only the shallow vocabulary differences presented in the limited set of exemplars in Table 6.

It is also worth highlighting that, thanks to our directional transfer procedure, these completions are not merely "typical American" or "typical British" continuations such as we would expect from a conditional language model trained on each sub-domain of text. Rather, since our inference procedure pushes the style away from one domain and towards the other, the resulting completions are *distinctive* representations of each dialect. As one example, we expect "quinoa" would not only be a common American favorite, but also an uncommon British favorite.

American $\Rightarrow$ British	British $\Rightarrow$ American
My favourite food: fish and chips.	My favorite food: quinoa.
My favourite hot drink: a mug of tea.	My favorite hot drink: Starbucks Coffee.
My favourite dessert: a scone!	My favorite dessert: a brownie.
My favourite city: Cardiff.	My favorite city: San Diego.
My favourite band: The Beatles.	My favorite band: The Black Keys.
My favourite sports league: the English Premier League.	My favorite sports league: the NFL.
My favourite newspaper: The Daily Telegraph.	My favorite newspaper: The Washington Post.
My favourite museum: the British Museum.	My favorite museum: The National Air and Space Museum.

Table 2: Examples of dialect-sensitive completion (λ=8, add:40–70%, delete:0%). In each case, the input text consists of an unfinished phrase, for example: "My favorite food: ". The three exemplars used for each dialect are the same as those used for the transfers in Table 1, as listed in Table 6.

Examples of **shortening** are given in Table 3, with inputs taken from the first five sentences of the Wikipedia article "Artificial neural network". As successful shortening may require minor rephrases, we set our tuning ranges to add:0–5%, delete:40–90%. Since our intention is to leave the textual style unchanged (apart from length), we extract the target style directly from the input text, with no delta added. In each case, the model is largely successful at identifying and removing "superfluous" content, and finding ways of rephrasing to shorten while preserving meaning.

Artificial neural networks (ANN) or connectionist systems are computing systems that are inspired by, but not identical to, biological neural networks that constitute animal brains.
$\Rightarrow$ Artificial neural networks (ANNs) are computing systems that are inspired by the biological neural networks that constitute animal brains.

Such systems "learn" to perform tasks by considering examples, generally without being programmed with task-specific rules.
$\Rightarrow$ Such systems learn to perform tasks by considering examples, generally without explicit rules.

For example, in image recognition, they might learn to identify images that contain cats by analyzing example images that have been manually labeled as "cat" or "no cat" and using the results to identify cats in other images.
$\Rightarrow$ For example, image recognition systems might learn to identify images that contain cats by analyzing images that have been manually classified as "cat" or "no cat".

They do this without any prior knowledge of cats, for example, that they have fur, tails, whiskers and cat-like faces.
$\Rightarrow$ They do not know that cats have fur, tails, whiskers and cat-like faces.

Instead, they automatically generate identifying characteristics from the examples that they process.
$\Rightarrow$ Instead, they automatically generate identifying characteristics.

Table 3: Examples of shortening (add:0–5%, delete:40-90%), using the first five sentences from the Wikipedia article "Artificial neural network". For each sentence, the target style is extracted directly from the input text, and no delta is added.

---

[7]Note however, that in transferring from American to British, the model does prefer to change the prompt from *favorite* to *favourite*.

Examples of **random augmentations** are given in Table 4. In each case, we transfer the input sentence "What'll the weather be tomorrow?" to a slightly different style. Specifically, for each transfer, we extract this sentence's style vector and apply a small amount of noise, with each component of the noise vector sampled from a Gaussian $\mathcal{N}(0, 0.08)$. Note that apart from the noise in the style vector, the transfer process is deterministic, as we use greedy decoding.

The columns of Table 4 apply different tuning ranges, conditioning the model to change a little or a lot. Within each column, we repeatedly sample the noised style, and present the first five unique outputs. The results indicate that many random changes in style are largely meaning preserving, especially when a small change is requested. With larger add/delete rates, the outputs are still closely related in meaning, despite low lexical overlap.

Add/Delete: 10–30%	Add/Delete: 30–50%
What'll the weather be like?	What's the weather like?
What'll the weather be like tomorrow?	What will the weather be like tomorrow?
What's the weather like tomorrow?	Will the weather be better tomorrow?
What'll the weather be tomorrow?	What's the weather forecast for tomorrow?
What's the weather supposed to be tomorrow?	How will the weather be tomorrow?
Add/Delete: 50–70%	**Add/Delete: 70–90%**
Will the weather be perfect tomorrow?	How do you know what the weather will be like?
What's the weather for tomorrow?	Is it supposed to be cold tomorrow?
What's the weather like on the course?	What will the weather be like in the South?
Hopefully the weather will be better tomorrow.	I'm not a fan of the weather.
What's the weather like for the next day?	What is the temperature and what is the humidity.

Table 4: Random augmentations of input text "What'll the weather be tomorrow?", using random style vector deltas with components sampled from $\mathcal{N}(0, 0.08)$.

A.2 SETTINGS USED FOR QUALITATIVE ANALYSIS

For each of the transfer types (e.g., formal $\leftrightarrow$ informal) in Table 1, we specify the intended target styles to the model through a tiny set of exemplars. These exemplars are provided in Tables 5–9. Additionally, for each transfer type, we select a delta scale λ and add/delete rates. These settings are selected through initial experiments, and are held fixed across all examples of transfer shown.

A.3 AMAZON REVIEWS PREPROCESSING

We use the code in Figure 5 to process raw Amazon reviews from the Ni et al. (2019) dataset and extract pairs of adjacent lines, preprocessed to have a similar format to Li et al. (2018) dataset. We split reviews on newlines, and clip lines to 100 characters, always ending with a period. This gives results similar to Li et al. (2018), where one line may contain multiple sentences, and may consists of a "half-sentence" ending with "e.g." or a similar non-sentence-final period. Additionally, we apply various tokenization and normalization operations to roughly match the observed Li et al. (2018) text.

Reserved Exemplars	Emotive Exemplars
1. That is a very pretty painting.	1. OMG, that's such a beautiful painting!
2. I'm excited to see the show.	2. I'm sooo excited to see the show, it's going to be stellar!!
3. I'm surprised they rescheduled the meeting.	3. I absolutely can not believe that they rescheduled the meeting!
4. This specimen is an example of the baroque style.	4. This wonderful specimen is a truly spectacular example of the baroque style.
5. After the performance, we ate a meal.	5. After the superb performance, we ate a delicious meal.

Table 5: Emotiveness transfer exemplars. Transfer settings: λ=9, add/delete rates: 0–100%.

American Exemplars	British Exemplars
1. It cost ten bucks.	1. It cost ten quid.
2. My neighbor apologized.	2. My neighbour apologised.
3. I'm heading out to the bar with some friends.	3. I'm heading out to the pub with some mates.

Table 6: Dialect transfer exemplars. Transfer settings: λ=8, add/delete rates: 10–30%.

Polite Exemplars	Rude Exemplars
1. No thank you, I'd prefer not to.	1. Hell no, you can't make me do that.
2. This game could have been better designed.	2. This game is such a piece of garbage!
3. Do you know why they might have delayed the launch?	3. Why in god's name would they delay the damn launch?
4. Sorry, I wasn't certain if you were joking.	4. Are you frigging kidding me?

Table 7: Politeness transfer exemplars. Transfer settings: λ=5, add/delete rates: 20–50%.

Formal Exemplars	Informal Exemplars
1. This was a remarkably thought-provoking read.	1. reading this rly makes u think
2. It is certainly amongst my favorites.	2. Its def one of my favs
3. We humbly request your presence at our gala on the 12th.	3. come swing by our bbq next week if ya can make it

Table 8: Formality transfer exemplars. Transfer settings: λ=4, add/delete rates: 40–80%.

Positive Exemplars	Negative Exemplars
1. Five stars, I love it.	1. Zero stars, I hate it.

Table 9: Sentiment transfer exemplars. Transfer settings: λ=3, add/delete rates: 0–100%.

```python
import re
from html.parser import HTMLParser

html_parser = HTMLParser()

def preprocess(line):
  """Simulate Li et al. preprocessing of one review line."""
  # Lowercase.
  line = line.lower()
  # Replace apostrophes, parens and quotes with spaces.
  line = re.sub("['()\"]", " ", line)
  # Replace dollar values ==> $
  line = re.sub("\$[\d.]*", "$", line)
  # Replace percent values ==> %
  line = re.sub("[\d.]*%", "%", line)
  # Replace single digits ==> num_num
  line = re.sub(" \d[ ,]", " num_num ", line)
  # Replace multi-digits and codes ==> num_extend
  line = re.sub(" \d[^ ]*", " num_extend", line)
  # Remove remaining numbers, including decimals.
  line = re.sub("\d[\d.]*", "", line)
  # Add spaces around certain punctuation marks.
  line = re.sub("([.,?!:])", r" \1 ", line)
  # Remove double spaces after periods before words.
  return re.sub(r"\.  ([a-z])", r". \1", line)

def acceptable_line(line):
  """Check if text looks like an acceptable line from Li et al."""
  if not line or len(line) < 30 or len(line) >= 100:
    return False
  # Avoid lines with any char absent from Li et al. train.
  if re.search('[^ !$%+,.:;>?@\^_`a-z{|}]', line):
    return False
  return True

def clip_to_last_period(line):
  return line[:len(line) - line[::-1].index('.')]

def adjacent_lines(review):
  """Extract a list of adjacent line pairs from review text."""
  review = html_parser.unescape(review)
  review = review.replace('\\"', '"')
  # Simulate Li et al. splitting and filtering.
  if '\n' not in review:
    return
  lines = review.split('\n')
  lines = [preprocess(clip_to_last_period(l[:100]))
           for l in lines if l and "." in l[:100]]
  lines = [preprocess(l) for l in lines]
  lines = [l for l in lines if acceptable_line(l)]
  if len(lines) < 2:
    return
  return list(zip(lines[:-1], lines[1:]))
```

Figure 5: Python code to extract adjacent lines of text from raw Amazon reviews, producing outputs in a similar style to Li et al. (2018).