WISE: A Long-Horizon Agent in Minecraft with Why-Which Reasoning

Abstract

Rapid advances have been made in developing general-purpose embodied agents in environments like Minecraft through the adoption of LLM-augmented hierarchical approaches. Despite their promise, low-level controllers often become performance bottlenecks due to repeated execution failures. We argue that a key limitation is not only the lack of episodic memory, but also the decoupling of *what-where-when* memory from *which-why* reasoning. To address this, we propose **WISE** (Which-Why Informed Semantic Explorer), a long-horizon agent framework with an enhanced low-level controller equipped with a Semantic Affordance Event Graph (SAEG) that augments episodic memory with semantic affordance structure linking observations to task relevance. Unlike prior work such as MrSteve, which relies on feature similarity for retrieval, WISE enables robust recall under viewpoint changes and supports opportunistic task reordering through affordance-grounded task reasoning. Building on this memory, we propose an Opportunistic Task Scheduler that dynamically re-prioritizes subtasks when task-relevant opportunities are detected. We further equip WISE with a multi-scale progressive exploration strategy to provide spatially comprehensive observations for downstream reasoning. Experiments show that WISE substantially improves task success and efficiency on long-horizon sparse tasks, particularly in settings requiring adaptive decision-making.

1 Introduction

Building generally capable embodied agents that can solve long-horizon tasks in complex, open-ended environments remains a fundamental challenge in artificial intelligence. Minecraft has emerged as a prominent benchmark for studying this problem because it presents a procedurally generated world with rich interaction dynamics requiring exploration, resource acquisition, tool crafting, and long-term planning Guss et al. (2019); Fan et al. (2022); Baker et al. (2022). Even seemingly simple objectives, such as *"obtain beef"*, require multi-step reasoning: the agent must first infer the semantic link between beef and cows, then explore sparse biomes to locate cattle, navigate complex terrain, engage in interaction or combat, and finally collect the resulting resources. Failures at any stage (e.g., losing track of the target entity) often lead to costly re-exploration. More complex tasks, such as diamond acquisition, can require tens of thousands of environment steps Lifshitz et al. (2023), making reinforcement learning from scratch prohibitively difficult due to sparse rewards and vast exploration spaces.

Recent progress has shown that Large Language Model (LLM)-augmented hierarchical frameworks provide a promising solution Wang et al. (2023); Zhou et al. (2024). These systems decompose long-horizon tasks into two levels: a high-level planner that leverages LLM reasoning to generate subgoals and a low-level controller that executes them. This decomposition largely reduces task complexity and has enabled notable advances in embodied decision making. For such frameworks to succeed, however, high-level planning and low-level execution must improve jointly. Existing research has primarily concentrated on enhancing high-level planning through skill libraries Zhu et al. (2023); Wang et al. (2023); Qin et al. (2024), multimodal experience repositories Li et al. (2024), or increasingly powerful language reasoning modules.

Figure 1: Comparison of WISE and prior approaches across three key capabilities. **Affordance-Grounded Recall:** WISE recalls previously observed trees for the task "obtain log" log by leveraging the semantic affordance relation (Oak → log), whereas MrSteve relies solely on visual similarity. **Opportunistic Task Execution:** WISE dynamically reorders the task queue to exploit chance encounters (e.g., immediately killing a nearby cow), while prior approaches rigidly follow a predefined task sequence. **Robust Recall under Viewpoint Changes:** WISE employs semantic entity representations that are less sensitive to viewpoint variations, enabling consistent recognition of cows from different perspectives; prior approaches depend on raw visual features and often fail under viewpoint changes. Green check marks indicate successful behavior.

In contrast, comparatively little attention has been paid to the low-level controller, which often becomes the dominant bottleneck in practice Cai et al. (2023). Existing methods frequently assume that once a subgoal is generated, the controller can reliably and efficiently execute it—an assumption that often breaks down in large, sparse environments. A recent attempt to address this limitation is MrSteve Park et al. (2025), which augments Steve-1 with Place Event Memory (PEM). PEM organizes past observations according to *what* happened, *where* it occurred, and *when* it was observed, enabling retrieval of previously encountered locations and events. For example, an agent may remember that it previously observed a cow in a forest region and later navigate back to that location.

However, we argue that the primary limitation is not only memory capacity itself, but also the absence of task-relevant semantic structure over memory. Existing systems Wang et al. (2024); Zhu et al. (2023); Park et al. (2025) isolate episodic recall from decision making. PEM retrieves observations using cosine similarity between MineCLIP visual features and task embeddings, resulting in two key deficiencies. First, retrieval based on raw visual similarity is semantically brittle: changes in viewpoint, occlusion Cai et al. (2023); Zhou et al. (2024), or environmental conditions frequently cause memory recall to fail. Second, PEM stores observations without representing which task outcomes the observed entities afford. The memory may record that a cow was previously observed, but it cannot represent why this observation matters—namely, that cows can provide beef. Consequently, when the future task becomes *"obtain beef"*, the agent lacks a mechanism to identify previously encountered cows as relevant opportunities.

More fundamentally, existing controllers Lifshitz et al. (2023); Park et al. (2025) execute subgoals according to fixed action sequences and cannot answer the question: *which action should be performed right now given newly available information?* Consider an agent traveling to collect wood that unexpectedly encounters a cow. An ideal agent should immediately recognize that the encounter creates an opportunity to satisfy a future subgoal. Existing systems Qin et al. (2024); Yuan et al. (2023); Li et al. (2025) instead continue executing the prescribed sequence and return later, incurring unnecessary navigation cost. Exploration, memory, and planning operate as disconnected modules; consequently, the overall system cannot coordinate newly acquired observations with memory retrieval and task ordering.

In this work, we introduce **WISE** (**W**hich-**W**hy **I**nformed **S**emantic **E**xplorer), a long-horizon agent framework that closes the loop between exploration, memory, and decision making. As illustrated in Figure 1, WISE extends conventional episodic memory with semantic affordance structure, enabling the agent not only to remember *what*, *where*, and *when*, but also to understand *why* an observation matters and *which* future tasks it may enable. The core of WISE is a *Semantic Affordance Event Graph*, a semantic memory structure that augments episodic observations with semantic affordance relations extracted by a Vision-Language Model. Instead of storing observations as isolated visual memories, the graph links entities and downstream task outcomes through affordance edges (e.g., *cow* → `CAN_OBTAIN` → *beef*). This semantic layer enables affordance-grounded retrieval and transforms memory from passive storage into actionable knowledge. Building upon this representation, we introduce an *Opportunistic Task Scheduler* that continuously reasons over semantic affordance memories and dynamically reprioritizes pending subtasks. Rather than rigidly following a predefined execution sequence, the scheduler adapts to newly observed opportunities. When a task-relevant entity appears, WISE immediately updates its task priorities and exploits the opportunity online, thereby avoiding redundant navigation and improving long-horizon efficiency. Finally, to support this reasoning process with sufficiently rich observations, we introduce a multi-scale progressive exploration strategy that efficiently expands environmental coverage while minimizing revisitation. Together, exploration, memory, and scheduling form a closed-loop architecture: exploration acquires observations, memory converts observations into semantic affordance knowledge, and planning consumes this knowledge for adaptive decision making. Extensive experiments in large-scale Minecraft environments demonstrate the effectiveness of WISE. Compared with the current state-of-the-art low-level controller MrSteve Park et al. (2025), WISE achieves a 14% improvement in exploration coverage, a 30% increase in sequential sparse task success with 26.4% lower completion time, and a 44% increase in adaptive non-sequential task success with 42.5% less completion time. Ablation studies further reveal that WISE's full-model performance significantly exceeds the sum of individual module improvements, suggesting strong synergy among *Semantic Affordance Event Graph*, *Opportunistic Task Scheduler*, and *Multi-scale Progressive Exploration* components. Ablation studies further show complementary contributions from SAEG, the Opportunistic Task Scheduler, and Multi-scale Progressive Exploration; we do not interpret them as a factorial interaction analysis.

Our contributions are as follows.

1. We identify a key but underexplored limitation in long-horizon embodied agents: the disconnect between episodic memory and affordance-grounded decision-making. We argue that an effective low-level controller must go beyond remembering *what*, *where*, and *when*, and instead reason about *why* observations matter and *which* future actions they enable.

2. We propose **WISE**, a unified embodied framework that closes the loop between exploration, memory, and planning. Its core is a Semantic Affordance Event Graph that augments episodic memory with VLM-derived semantic affordance relations, enabling robust retrieval and affordance-grounded reasoning.

3. We introduce an Opportunistic Task Scheduler that dynamically reprioritizes subtasks based on semantic affordance relevance, transforming the low-level controller from a rigid executor into an adaptive decision-maker capable of exploiting newly emerging opportunities.

4. We present a multi-scale progressive exploration strategy that improves coverage efficiency while providing the reasoning module with spatially comprehensive observations for long-horizon decision making.

2 Related work

2.1 Low-Level Control in Minecraft

Early works trained policy models for simple Minecraft tasks Guss et al. (2019). VPT Baker et al. (2022) showed that vision-to-action mappings can be learned from unlabeled online videos at scale. Steve-1 Lifshitz et al. (2023) extended VPT by conditioning on text instructions. GROOT Cai et al. (2024) used reference

videos instead of text for goal-conditioned control. MineDreamer Zhou et al. (2024) leveraged Steve-1 to generate subgoal images for better execution.

More recent research focuses on increasing the architectural complexity and adaptability of controllers. The STEVE Series Zhao et al. (2024) systematically explored the interplay between planning granularity and observation encoding. Odyssey Liu et al. (2025) and LARM Li et al. (2025) introduced open-world skill libraries and auto-regressive models to bridge the gap between reactive control and long-horizon deliberative planning. ADAM Yu & Lu (2025) and Steve-Evolving Xie et al. (2026) represent the cutting edge of this direction: the former constructs a causal graph through interaction, while the latter distills execution diagnoses into reusable guardrails and skills. However, these systems often treat memory as a high-level knowledge store rather than an integrated component of low-level execution. MrSteve Park et al. (2025) introduced Place Event Memory (PEM) to provide the low-level controller with episodic context, but its retrieval relies on raw visual similarity. WISE addresses this by extending PEM into a Semantic Affordance Event Graph, enabling the controller to reason about why a memory is relevant to future tasks.

2.2   Memory In Agents

Memory is essential for long-horizon tasks, and many studies have explored different storage and retrieval mechanisms for embodied agents. Sumers et al. (2023) propose a framework that categorizes agent memory into three types: in-context, external, and in-weights. They highlight the trade-off between retrieval accuracy and update speed, which directly motivates the two-level retrieval design in WISE.

At the plan level, several memory systems have been developed. Voyager Wang et al. (2024) stores reusable skill programs across episodes, enabling lifelong learning in Minecraft without human intervention. GITM Zhu et al. (2023) uses structured world knowledge to improve goal decomposition for technology-tree tasks. JARVIS-1 ? and MP5 Qin et al. (2024) store both multimodal observations and successful plans for situation-aware retrieval, with JARVIS-1 showing that multimodal goal specification greatly improves retrieval precision. Optimus-1 Li et al. (2024) introduces a hybrid memory pool that summarizes visual, textual, and action trajectories, achieving strong results on long-horizon benchmarks.

Despite these advances, most existing memory systems focus on high-level planning—they store which plan worked, not why a specific low-level observation matters. MrSteve's PEM is the first memory system designed for low-level control, but it still retrieves memories based on raw visual features. WISE fills this gap by constructing a Semantic Affordance Event Graph that connects low-level observations to high-level goals through explicit semantic affordance edges. A related system, Yu & Lu (2025) also builds a causal graph via interaction, but it targets high-level knowledge accumulation and does not integrate causal memory with a dynamic low-level scheduler.

2.3   Exploration in Open Worlds

Exploration strategies span several paradigms, each with a characteristic failure mode. Count-based methods Tang et al. (2017); Chang et al. (2024) encourage novelty but accumulate coverage gaps super-linearly with map size. Frontier-based methods Yamauchi (1998); Sun et al. (2025) improve boundary awareness but ignore large unvisited interior regions. NovelCraft Feeney et al. (2023) further showed that existing exploration policies fail to detect and adapt to novel objects in procedurally generated worlds, underscoring the need for multi-scale hierarchical planning that balances global coverage and local detail. VPT-Nav Park et al. (2025) adapts to local dynamics but is reactive rather than globally planned. Active information-gain methods Chaplot et al. (2020a;b); Zhang et al. (2021) are theoretically well-motivated but computationally intractable under Minecraft's ≤ 50 ms per-step real-time constraint. WISE's multi-scale strategy is the first to synthesise all three strengths in Minecraft: $O(\log n)$ region lookup and target selection from quadtree indexing, boundary-awareness from frontier scoring, and a local completeness guarantee from Voronoi decomposition.

Figure 2: Overall architecture of WISE. Given a text instruction or subtask sequence (e.g., "A → B → C"), the agent alternates among three phases: *Explore*, *Reason*, and *Execute*. During exploration, a multi-scale progressive policy systematically explores the environment and stores observations in two memory systems: a short-term geometric memory for efficient retrieval of recent observations and a Semantic Affordance Event Graph for storing semantic entities, spatial instances, and semantic affordance relations. During execution, the agent uses VPT-Nav for goal-directed navigation and Steve-1 for low-level instruction execution. The Opportunistic Task Scheduler dynamically reorders subtasks according to semantic affordance memories retrieved from SAEG.

3 Method

In this section, we introduce WISE, a memory-augmented embodied agent framework for sparse long-horizon tasks in Minecraft. We first describe the problem setting and then present the construction of each module.

Problem setting. We consider sparse long-horizon task scenarios in which an embodied agent continuously receives a sequence of tasks $\{\tau_n\}_{n=1}^{\infty}$ via textual instructions (e.g., *"Obtain beef"*) generated either directly by the environment or decomposed by a large language model (LLM). We assume that task-relevant resources occur infrequently and are sparsely distributed throughout large environments. Consequently, successful task completion requires the agent not only to memorize observations from explored regions, but also to semantically understand how these observations may be relevant to future tasks.

At every timestep t, the agent receives an observation

$$X_t = \{O_t, l_t, t\}, \tag{1}$$

where $O_t = i_t \in \mathbb{R}^{H_{\text{img}} \times W_{\text{img}} \times C_{\text{img}}}$ denotes the first-person RGB observation. Here, H_{img}, W_{img}, and C_{img} denote the image height, image width, and number of color channels, respectively. The pose vector

$$l_t = (coord_x, coord_y, coord_z, yaw, pitch) \in \mathbb{R}^5 \tag{2}$$

contains the agent's 3D coordinates and camera orientation relative to the initial frame of reference.

Framework overview. WISE is a memory-augmented agent framework consisting of three major components: a *Memory Module*, a *Solver Module*, and an *Opportunistic Task Scheduler*. The memory module M_t contains two complementary memory structures:

$$M_t = (M_{\text{short}}, M_{\text{SAEG}}). \tag{3}$$

First, M_{SAEG} is a *Semantic Affordance Event Graph* (SAEG) that extends conventional episodic memory with semantic entities, spatial instances, and task-relevant semantic affordance relations. Second, a *short-term geometric memory*, M_{short}, provides low-latency retrieval of recently observed experiences.

Based on retrieved memory contents, a mode selector within the solver module dynamically switches between *Explore* and *Execute* modes. Together with a multi-scale progressive exploration policy, these modules form the complete WISE framework. Algorithm 1 outlines the task-solving loop of WISE. By jointly exploring, memorizing, and using semantic affordance relations for retrieval and scheduling, WISE enables efficient decision-making for sparse long-horizon tasks. SAEG guides target selection and task scheduling; the retrieved locations are passed to VPT-Nav as navigation targets, and Steve-1 executes the selected natural-language subgoal.

For the decision loop, we denote the pending subtask queue at timestep t as $Q_t = [\tau_1, \ldots, \tau_m]$. For each pending subtask τ_i, $\mathcal{C}_i$ denotes the retrieved memory candidate set. A stored memory candidate x consists of a visual embedding e_x, a stored pose l_x, and a timestamp t_x.

Algorithm 1 WISE Single Decision Loop

Require: Current observation $X_t = (O_t, l_t, t)$; memory $M_t = (M_{\text{short}}, M_{\text{SAEG}})$; pending subtask queue $Q_t = [\tau_1, \ldots, \tau_m]$; scheduler S.
1: Update M_{short} with the current observation X_t.
2: Enqueue eligible keyframes for asynchronous SAEG update.
3: Incorporate available VLM outputs into M_{SAEG} after grounding and filtering.
4: **for** each pending subtask $\tau_i \in Q_t$ **do**
5:     Retrieve memory candidates $\mathcal{C}_i \leftarrow \text{RETRIEVE}(M_{\text{short}}, M_{\text{SAEG}}, \tau_i)$ using Eq. 6.
6:     Compute priority $p_i \leftarrow S(\tau_i, \mathcal{C}_i, l_t)$ using Eq. 7.
7: **end for**
8: Select $\tau^\star = \arg\max_{\tau_i \in Q_t} p_i$.
9: Select $x^\star = \text{TOPCANDIDATE}(\mathcal{C}_{\tau^\star})$.
10: **if** $x^\star \neq \emptyset$ **then**
11:     Set navigation target $l^\star \leftarrow l_{x^\star}$.
12:     Navigate to $l^\star$ with $\pi_{\text{L-Nav}}$.
13:     Execute subtask $\tau^\star$ with π_{Inst}.
14:     Remove $\tau^\star$ from Q_t if completed.
15: **else**
16:     Select an exploration target using the multi-scale explorer.
17:     Explore with $\pi_{\text{H-MS}}$ and $\pi_{\text{L-Nav}}$.
18: **end if**

Algorithm 1 makes explicit the three operations performed by the online controller: memory update, task-level prioritization, and low-level execution. VLM inference is not part of the blocking control path. The online loop only selects candidate keyframes and appends them to a pending VLM buffer; graph construction is performed asynchronously as described in Section 3.1.2. At each timestep, WISE queries the latest available version of M_{SAEG}. If no valid retrieved memory exists for the selected subtask, the agent switches to exploration.

3.1 Semantic Affordance Event Graph for Episodic Memory

Episodic memory in embodied agents typically records *what* happened, *where* it happened, and *when* it occurred. However, for long-horizon tasks, this information alone is insufficient. An agent must additionally understand *why* a past observation may matter for a current or future objective, and *which* pending subtask should be executed when a useful opportunity appears.

The proposed Semantic Affordance Event Graph extends this paradigm by explicitly encoding semantic affordance relationships among entities and tasks. This transforms episodic experiences into structured semantic knowledge that supports opportunistic reasoning and dynamic replanning.

3.1.1   Short-Term Geometric Memory

As shown in Figure 3, given Minecraft game frames, a MineCLIP encoder first extracts visual representations. DP-Means Dinari & Freifeld (2022) clustering is then applied to group temporally related observations into event clusters. Subsequently, cosine similarity between the current task embedding and each event-cluster center is computed. Clusters whose similarity exceeds a predefined threshold are ranked, and the top-K clusters are retrieved as memory cues. This mechanism follows the memory design adopted in MrSteve, but does not explicitly represent entity-level semantic affordances or task-enabling relations.

Figure 3: Short-Term Geometric Memory. Given Minecraft video frames, a MineCLIP encoder extracts visual embeddings, which are grouped into event clusters using DP-Means clustering. The system then computes cosine similarity between the current task embedding and each cluster centroid. Clusters with similarity above a predefined threshold are ranked, and the top-K matches are retrieved as memory cues.

To enable rapid and low-latency retrieval of recent experiences, WISE maintains a short-term memory structure identical to PEM. Observation embeddings are computed as

$$e_t = Enc_{\mathrm{vis}}(i_{t-T_{\mathrm{win}}:t}), \tag{4}$$

where Enc_{vis} denotes the MineCLIP visual encoder and $T_{\mathrm{win}} = 16$ denotes the temporal window size. Experience frames are represented as

$$x_t = \{e_t, l_t, t\}, \tag{5}$$

where e_t is the stored visual embedding, l_t is the pose, and t is the timestep.

The stored frames are organized into place clusters based on the agent's 2D position and yaw orientation. Within each place cluster, event clusters are further formed via DP-Means clustering on video embeddings. When memory capacity is exceeded, the oldest frame from the largest event cluster is removed. This memory layer efficiently answers *where* and *when* queries. However, its representation of *what* remains restricted to visual similarity: it captures appearance but not task-relevant semantic affordances.

3.1.2   *VLM-Driven Semantic Affordance Graph Construction*

To understand why a particular observation matters, we construct semantic affordance event graph on top of the short-term geometric memory. As shown in Figure 4, graph construction begins with keyframe selection. Informative keyframes should preserve both semantic content and visual diversity from the original observation stream. We therefore use a hybrid keyframe extraction strategy that combines clustering-based and entropy-based selection.

Specifically, one set of keyframes is obtained from feature clusters in M_{short}, preserving representative observations across different scenes and events. In parallel, an image entropy criterion selects visually informative frames with potentially rich semantic content. The two sets are merged and filtered to remove near-duplicate frames, producing a compact and semantically diverse set of candidate keyframes.

Figure 4: VLM-Driven construction of the Semantic Affordance Event Graph. Hybrid keyframe extraction first selects representative observations from short-term geometric memory using complementary clustering-based and entropy-based strategies, followed by redundancy reduction through keyframe merging. A Vision-Language Model then analyzes each keyframe to extract semantic entities, identify semantic affordance relations (e.g., "cow → beef"), and identify spatial co-occurrence patterns. The resulting information is used to update SAEG by inserting or modifying entity nodes, spatial instances, semantic affordance edges, and co-occurrence edges.

To prevent VLM inference from interrupting real-time control, WISE decouples graph construction from action execution. The selected keyframes are first placed into a pending VLM buffer instead of being processed immediately in the control loop. An asynchronous VLM worker periodically batches the buffered keyframes into groups of 16 and sends one streaming request for each group. This design amortizes the cost of VLM inference over multiple keyframes while allowing the agent to continue interacting with the environment.

During this process, the agent continues to act using the short-term geometric memory and the latest available version of SAEG. Once a VLM response is returned, the parsed outputs are grounded and filtered, after which SAEG is updated in a synchronized step by inserting or updating entity nodes, spatial attributes, timestamps, semantic affordance relations, and co-occurrence relations. Therefore, the online controller never waits for VLM inference, while the scheduler always queries the most recent updated graph.

The number of selected keyframes is adaptive and depends on the explored trajectory and redundancy filtering. The experimental section reports the average number of VLM requests per episode. The exact VLM prompt template, structured output schema, grounding vocabulary, and filtering rules are provided in Appendix A.

For each keyframe, the VLM performs three operations.

Entity extraction. The VLM identifies semantically meaningful elements in the scene, including animals, resources, terrain structures, and environmental objects. These entities are added as graph nodes and associated with the spatial coordinates and timestamp of the originating observation.

Semantic affordance relation extraction. For each extracted entity, the VLM identifies candidate entity–outcome relations, which are then grounded and validated against the Minecraft task-resource vocabulary. For example, a *cow* entity is connected to *beef* and *leather* via CAN_OBTAIN relations, while a *tree* is connected to *logs*. These edges encode the *why* dimension of memory: observing a cow is useful for the task "obtain beef" because the cow provides an actionable semantic affordance for that task.

Spatial co-occurrence relation extraction.

For entities observed in the same keyframe or nearby spatial locations, WISE adds or updates `CO_OCCURS_WITH` edges. These edges encode spatial regularities among entities and help retrieve nearby resources or landmarks during exploration and task execution.

After VLM processing, extracted entity names are normalized and grounded to the Minecraft vocabulary and task-resource database. Duplicate entity instances are merged when they have the same normalized entity type and nearby spatial coordinates. Semantic affordance edges are retained only when the source entity is observed in the keyframe and the target resource or outcome is valid under the task-resource vocabulary. Together, these operations transform low-level episodic observations into structured semantic affordance memory suitable for retrieval and scheduling.

3.1.3 *Two-Level Retrieval with Semantic Affordance Augmentation*

When the agent receives a new task τ_n, memory retrieval proceeds at two complementary levels. First, the short-term geometric layer computes cosine similarity between the task embedding $z_{\tau_n} = Enc_{\text{text}}(\tau_n)$ and stored observation embeddings, returning the top-k visually matched memories.

Second, the semantic layer queries the Semantic Affordance Event Graph. The task description is matched against entity or resource nodes, after which semantic affordance edges are traversed to identify observations that are task-relevant. For example, a query such as *"obtain beef"* first matches the *beef* node and then follows incoming `CAN_OBTAIN` edges to associated *cow* instances, thereby retrieving their stored spatial locations. This semantic affordance retrieval process explains why a memory is selected: a cow observation is retrieved for a beef-related task not because its visual appearance resembles beef, but because the graph explicitly encodes their semantic affordance relation relationship.

The outputs from both retrieval pathways are integrated using a weighted scoring function:

$$Score(x, \tau_n) = \lambda_{\text{ret}} \cdot sim(e_x, z_{\tau_n}) + (1 - \lambda_{\text{ret}}) \cdot AffordanceMatch(x, \tau_n) \tag{6}$$

where x is a stored memory candidate, e_x is the visual embedding of candidate x, $z_{\tau_n} = Enc_{\text{text}}(\tau_n)$ is the task embedding, and $sim(\cdot, \cdot)$ denotes cosine similarity. $AffordanceMatch(x, \tau_n)$ equals 1 if candidate x contains an entity connected to task τ_n through a semantic affordance relation in M_{SAEG}, and 0 otherwise. $\lambda_{\text{ret}} \in [0, 1]$ controls the trade-off between visual similarity and semantic affordance matching.

Candidates returned by either the visual pathway or the SAEG pathway are merged and re-ranked by Eq. 6. The highest-ranked candidate, if available, is selected as the navigation target.

This formulation provides a semantic affordance retrieval pathway in addition to visual similarity retrieval. When visual appearance changes due to viewpoint variation, occlusion, or lighting, SAEG can still retrieve a relevant memory through entity–task affordance links. The retrieved location is then passed to the navigation module as a target; SAEG guides target selection and task scheduling rather than directly modifying the low-level policy input.

3.2 Opportunistic Task Scheduler for Adaptive Task Selection

Given multiple pending subtasks, continuously evolving observations, and semantic affordance memories, the central question becomes: *which* subtask should be executed at the current moment?

Existing systems such as MrSteve rely on a fixed task sequence generated by a high-level planner. The low-level controller executes subgoals strictly according to the prescribed order and cannot deviate even when the environment presents opportunities that would make future subtasks easier to accomplish. This rigid strategy often results in inefficient behavior and missed opportunities. For example, suppose an agent encounters a cow while traveling to collect wood. Under a fixed execution order, the agent must first finish the wood-collection task and later return to the same location to obtain beef, introducing unnecessary navigation cost.

WISE addresses this limitation with an Opportunistic Task Scheduler that dynamically prioritizes subtasks according to the current observation and retrieved semantic affordance memories. At each decision step, the

scheduler constructs a unified decision context from three information sources: the current visual observation O_t, the pending subgoal queue $Q_t = [\tau_1, \ldots, \tau_m]$, and the retrieved memory candidate sets $\{\mathcal{C}_i\}_{i=1}^m$. Each pending subgoal τ_i is associated with a memory cue consisting of its highest-ranked retrieved observation, corresponding spatial coordinates, and the semantic affordance relations connecting the memory to the task.

Each pending subgoal τ_i receives a composite priority score:

$$\text{Priority}(\tau_i, t) = w_u U(\tau_i, t) + w_a A(\tau_i, t) + w_n \left[1 - N(\tau_i, t)\right] \tag{7}$$

where $U(\tau_i, t)$ is the urgency score, $A(\tau_i, t)$ is the semantic affordance relevance score, and $N(\tau_i, t)$ is the normalized navigation cost. All three terms are normalized to $[0, 1]$.

The urgency term preserves the preference of the original task queue. In our implementation, it is computed from the rank of τ_i in the pending queue Q_t:

$$U(\tau_i, t) = 1 - \frac{r_i - 1}{\max(|Q_t| - 1, 1)}, \tag{8}$$

where r_i is the rank of τ_i in Q_t. Thus, earlier subtasks receive higher default urgency.

The semantic affordance relevance term is computed from the latest available SAEG state and the retrieved candidate set $\mathcal{C}_i$:

$$A(\tau_i, t) = \begin{cases} \max_{x \in \mathcal{C}_i} AffordanceMatch(x, \tau_i), & \mathcal{C}_i \neq \emptyset, \\ 0, & \mathcal{C}_i = \emptyset. \end{cases} \tag{9}$$

This term becomes high when a retrieved memory contains an entity connected to τ_i through a semantic affordance relation. Since SAEG updates are asynchronous, newly observed opportunities become available to the scheduler once their corresponding VLM outputs have been incorporated into SAEG. Before that, the agent continues to rely on short-term geometric memory and exploration.

The navigation cost term is defined as

$$N(\tau_i, t) = \min\left(\frac{d(l_t, l_i^\star)}{d_{\max}}, 1\right), \tag{10}$$

where $l_i^\star$ is the location of the top retrieved candidate for τ_i, $d(l_t, l_i^\star)$ denotes the distance estimate used by the navigation module, and $d_{\max}$ is a map-scale normalization constant. If no valid candidate is retrieved for τ_i, we set $N(\tau_i, t) = 1$.

For instance, when the graph contains the semantic affordance relation

$$cow \rightarrow \texttt{CAN\_OBTAIN} \rightarrow beef,$$

the semantic affordance relevance score for the task "obtain beef" becomes high; otherwise, it remains near zero.

We set $w_u = 0.3$, $w_a = 0.5$, and $w_n = 0.2$ in the main experiments, reflecting the design choice that semantic affordance relevance should strongly influence opportunistic task switching. After scoring, the scheduler reorders the pending task queue according to descending priority. If the highest-priority task differs from the currently active one, execution is preempted and control switches to the new task.

This strategy is opportunistic because it exploits favorable environmental encounters that fixed plans ignore. Task switching is driven by semantic affordance reasoning: when SAEG links an observed or remembered entity to a pending subgoal, the scheduler can raise the priority of that subgoal and execute it earlier.

Illustrative example. Consider an agent executing the task sequence:

$$[\texttt{find water} \rightarrow \texttt{collect logs} \rightarrow \texttt{obtain beef}].$$

Once a cow observation has been incorporated into SAEG, the corresponding semantic affordance relation becomes available to the scheduler:

$$cow \rightarrow \texttt{CAN\_OBTAIN} \rightarrow beef.$$

The scheduler then recomputes task priorities, causing the semantic affordance relevance of "obtain beef" to increase. The reordered execution queue becomes:

$$[\texttt{obtain beef} \to \texttt{find water} \to \texttt{collect logs}].$$

The agent immediately acquires beef and subsequently resumes the remaining objectives, avoiding a future return trip. By contrast, a fixed-sequence policy such as MrSteve would ignore the encountered cow and revisit the same location later.

3.3 Multi-Scale Progressive Exploration

The effectiveness of SAEG and the Opportunistic Task Scheduler depends on access to sufficiently diverse and spatially complete observations. When no task-relevant memory can be retrieved and no exploitable opportunity is identified by the scheduler, the agent must actively explore the environment to acquire new information.

To address this challenge, WISE employs a *multi-scale progressive exploration* strategy designed to cover large environments while minimizing redundant exploration. The strategy consists of three hierarchical tiers operating at different spatial resolutions: global region selection, regional frontier refinement, and local completion. Each tier addresses limitations left unresolved by the preceding level.

Global exploration tier. At the coarsest level, the global exploration tier determines which large-scale region should be visited next. We partition the environment using a quadtree representation. Each quadtree node N_i represents a candidate macro-region. Let P_t denote the agent's current 2D map position. We define the global exploration score as

$$Score_G(N_i) = \alpha_G \cdot Depth(N_i) - \beta_G \cdot Dist(P_t, N_i), \tag{11}$$

where $Depth(N_i)$ measures the normalized depth or unexplored granularity of region N_i, $Dist(P_t, N_i)$ is the normalized distance from the current position to the region, and α_G, β_G are global-tier weights. The first term encourages the agent to visit fine-grained unexplored regions, while the second term penalizes distant targets.

The quadtree tier provides efficient $O(\log n)$ region lookup and next-target selection, where n is the number of candidate spatial regions. This complexity describes the cost of selecting the next macro-region from the spatial index. The realized coverage still depends on the low-level controller, terrain geometry, and the timestep budget.

Regional exploration tier. After arriving at a selected macro-region, the agent switches to regional exploration. Frontier points are defined as boundaries between explored and unexplored cells. Each frontier point f_i is scored as

$$Score_R(f_i) = \alpha_R \cdot Cover(f_i) + \beta_R \cdot Novel(f_i) - \gamma_R \cdot Dist(P_t, f_i), \tag{12}$$

where $Cover(f_i)$ estimates the uncovered area visible behind frontier f_i, $Novel(f_i)$ measures the information novelty of the frontier, $Dist(P_t, f_i)$ is the normalized distance from the agent to the frontier, and $\alpha_R, \beta_R, \gamma_R$ are regional-tier weights. The frontier with the highest score is selected as the next local exploration target. This tier expands exploration boundaries and compensates for the fact that global quadtree selection alone does not specify how to cover a selected region.

Local completion tier. Although global and regional exploration expand the explored area, small interior gaps may remain. To target these residual gaps, WISE applies a local completion stage based on Voronoi decomposition. Let U_i denote a residual unexplored region identified from the local map. We score each such region by

$$Score_L(U_i) = \alpha_L \cdot Area(U_i) - \beta_L \cdot Dist(P_t, U_i), \tag{13}$$

where $Area(U_i)$ is the normalized area of the residual unexplored region, $Dist(P_t, U_i)$ is the normalized distance from the current position to that region, and α_L, β_L are local-tier weights. The agent moves toward the highest-scoring residual region to improve local coverage completion.

Together, these three levels form a coarse-to-fine exploration framework. The global tier improves map-level target selection, the regional tier expands exploration boundaries, and the local tier improves coverage completion by targeting residual gaps. Through this progressive design, WISE acquires diverse observations required for semantic memory construction and semantic affordance reasoning in sparse long-horizon environments.

4 Experiments

In this section, we comprehensively evaluate WISE across four complementary dimensions. Section 4.1 describes the experimental protocol and evaluation setup. Section 4.2 evaluates large-scale exploration performance to assess the effectiveness of the proposed multi-scale exploration strategy. Section 4.3 evaluates sparse sequential (ABA-Sparse) and Section 4.4 evaluates non-sequential (ABC-Sparse) task completion, jointly evaluating memory retrieval and adaptive planning capabilities. Section 4.5 presents controlled ablation studies to isolate the contribution of each component. Additional implementation details are provided in Appendix A. All experiments are conducted in Minecraft Java Edition through the MineRL platform.

4.1 Experiment Setups

Hardware and software environment. All experiments are conducted on a single server equipped with four NVIDIA RTX 4080 16GB GPUs running Ubuntu 22.04 LTS, with each rollout using one GPU. The software stack includes Minecraft Java Edition v1.11.2, MineRL v0.4.4, PyTorch v2.5.1, and the official MineCLIP checkpoint from MineDojo. GPT-4o (`gpt-4o-2024-05-13`) is used as the Vision-Language Model for semantic affordance graph construction.

Baseline Selection. We compare WISE against the following representative baselines:

- *Steve-1* Lifshitz et al. (2023) is the most widely adopted low-level instruction-following controller built upon the Video Pre-Training (VPT) framework Baker et al. (2022). Following prior work Cai et al. (2024); Zhou et al. (2024), we additionally provide Steve-1 with the instruction "Go Explore" to assess its exploration capability.

- *MrSteve* Park et al. (2025) is the current state-of-the-art low-level controller based on Place Event Memory (PEM). It stores *what–where–when* information and retrieves memories using visual similarity. MrSteve additionally employs a hierarchical exploration strategy consisting of a count-based high-level goal selector and a VPT-Nav low-level controller.

- *WISE (SAEG only)* is an ablation variant that retains the proposed SAEG while removing multi-scale exploration and the Opportunistic Task Scheduler. This variant isolates the contribution of semantic affordance memory without adaptive planning or enhanced exploration.

- *VLM Entity Retrieval without SAEG* uses GPT-4o-generated entity labels for retrieval but does not construct semantic affordance edges or perform graph traversal.

- *WISE (Quadtree-Based)* is another ablation variant that uses only the global quadtree exploration tier while removing frontier-based regional exploration and Voronoi-based local completion.

We explicitly exclude API-privileged agents, including Voyager Wang et al. (2024), JARVIS-1 **?**, and GITM Zhu et al. (2023), because these methods directly access environment states such as entity coordinates, inventory information, and terrain metadata. In contrast, WISE and all evaluated baselines rely exclusively on raw visual observations. Direct comparison across these settings would confound architectural capability with information privilege and therefore lead to misleading conclusions.

Evaluation Metrics. We adopt three complementary evaluation metrics.

- *Map Coverage* measures the fraction of explorable areas visited by the agent and directly evaluates exploration efficiency. Areas that remain unexplored cannot contribute observations for downstream memory or planning.

- *Success Rate* denotes the percentage of episodes that successfully complete all subgoals within a fixed timestep budget.

- *Average Completion Timesteps* is computed only over successful episodes and measures task efficiency.

- For sparse sequential (ABA-Sparse) tasks, we additionally report *return localization steps*, defined as the number of steps required to relocate the original location of object A after collecting object B. This metric isolates memory retrieval performance from navigation ability.

Core hyperparameters. Key parameters are summarized below, while complete implementation details and selection procedures are provided in Appendix A. For exploration, we set the quadtree depth weight to $\alpha_G = 0.6$ and distance penalty to $\beta_G = 0.4$. Frontier utility weights (coverage, novelty, and distance) and Voronoi utility weights (area and distance) are normalized. For memory, the entropy threshold is $\theta_{\text{ent}} = 0.15$, cosine similarity threshold is $\theta_c = 0.85$, and top-k retrieval uses $k = 10$. For planning, urgency, semantic affordance relevance, and navigation cost weights are set to $w_u = 0.3$, $w_a = 0.5$, and $w_n = 0.2$, respectively. The maximum quadtree depth is set to 6 for 384×384 maps and 5 for 128×128 maps. Voronoi decomposition is updated every 40 steps, with the minimum unexplored area threshold set to 60 pixels.

VLM cost and latency. On average, WISE performs approximately 14 GPT-4o requests per episode. Each request consumes roughly 4,575 input tokens and 1,618 output tokens, resulting in an estimated API cost of \$0.48 per episode. Since VLM inference runs asynchronously, it does not block the online control loop.

4.2 Large-Scale Exploration Performance

We first evaluate the efficiency with which each method explores and covers the environment. The primary metric is map coverage, defined as the fraction of unique locations visited by the agent. Table 1 reports coverage under varying step budgets.

Simulated environment. We first evaluate under an idealized movement model in which the agent moves deterministically by a fixed distance at each timestep (one block per step). This setting removes low-level execution variability and isolates the intrinsic spatial efficiency of the exploration strategy itself. On the small 128×128 map with a budget of 6,000 steps, WISE achieves 99% coverage, compared to 59% for MrSteve and 93% for the quadtree-based variant. On the larger 384×384 map with 20,000 steps, WISE reaches 98% coverage whereas MrSteve plateaus at 83%. The advantage extends beyond final coverage. WISE explores at a rate of 0.097 map coverage per 1,000 steps, compared to 0.067 for MrSteve. Because movement stochasticity has been removed, these results reflect the intrinsic efficiency of the proposed multi-scale exploration strategy.

Real Environment. We next evaluate under the standard Minecraft environment containing stochastic elements including mobs, weather, and day–night cycles. Although environmental uncertainty reduces coverage for all methods, WISE consistently maintains a substantial advantage. On the 128×128 real-world map with a 10,000-step budget, WISE covers 97% of the environment, compared to 67% for MrSteve and only 19% for Steve-1. The three exploration tiers address complementary failure modes of previous approaches. The global quadtree stage performs $O(\log n)$ region lookup and next-target selection and avoids local-greedy behavior. This complexity describes spatial-index operations rather than final coverage, which also depends on navigation, terrain, and the timestep budget. The frontier-based regional tier expands exploration boundaries toward unexplored areas. Finally, the Voronoi local completion stage explicitly fills small unvisited regions that remain invisible to higher-level planning. Trajectory visualizations in Figure 5 provide qualitative evidence. MrSteve's count-based exploration tends to concentrate around the spawn location, whereas WISE distributes exploration trajectories more uniformly throughout the environment.

Table 1 further reveals two observations. First, coverage gaps become increasingly pronounced as map scale increases. Although the relative difference narrows from 40 percentage points on small maps to 15 points on large maps, the latter corresponds to substantially larger unexplored regions in absolute area. The smaller normalized gain of the quadtree-only variant on the 384×384 map reflects the larger share of the fixed budget

Figure 5: Exploration trajectory comparison on a 384×384 simulated map after 10,000 timesteps. Left: MrSteve (75.6% coverage). Right: WISE (96.4% coverage). Color indicates temporal progression (blue: early; red: late). MrSteve exhibits locally greedy behavior and repeatedly concentrates exploration near the spawn region, whereas WISE achieves broad and uniform coverage through coordinated global, regional, and local exploration.

Table 1: Map coverage ($\in [0, 1]$) at different Minecraft timestep budgets (20 timesteps $\approx$ 1 second). Columns are grouped by map size. Best results in each column are highlighted in **bold**. WISE* uses global-level search when exploring.

Method	128×128			384×384		
	500 steps	1000 steps	6000 steps	1000 steps	4000 steps	20000 steps
MrSteve(Count-Based)	0.46	0.57	0.59	0.17	0.53	0.83
WISE*(Quadtree-Based)	0.65	**0.87**	0.93	**0.19**	0.72	0.83
WISE(ours)	**0.66**	0.85	**0.99**	**0.19**	**0.73**	**0.98**

(a) Map Coverage on 128×128 and 384×384 map in simulated environment.

Method	128×128		384×384	
	5,000 steps	10,000 steps	20,000 steps	40,000 steps
Steve-1(Random)	0.11	0.19	0.06	0.13
MrSteve(Count-Based)	0.64	0.67	0.39	0.69
WISE*(Quadtree-Based)	**0.72**	0.75	**0.44**	0.74
WISE(ours)	0.71	**0.97**	**0.44**	**0.83**

(b) Map Coverage of different exploration policies in Minecraft.

spent on long-range travel and local execution, and does not contradict the $O(\log n)$ lookup cost. Second, gains observed in simulation transfer consistently to realistic environments. On the small real-world map, WISE improves coverage by 30 percentage points over MrSteve and by 78 points over Steve-1, demonstrating strong robustness under environmental stochasticity.

4.3 Sequential Sparse Task Performance (ABA-Sparse)

The ABA-Sparse task evaluates long-term memory and spatial recall under sparse-resource settings. The agent must first collect a sparse resource A, then acquire a dense resource B, and finally return to the original location of A without re-exploration. Each episode has a budget of 12,000 timesteps, and success requires

Table 2: Performance on Sparse Tasks
ABA sequential sparse task and ABC non-sequential sparse task: success rate and average completion timesteps over successful episodes. WISE* (SAEG only) removes multi-scale exploration and opportunistic scheduling. **Bold** = best. — = not applicable.

Method	Sequential Sparse Task (ABA-Sparse)		Adaptive Non-Sequential Task (ABC-Sparse)	
	Success Rate	Avg. Timesteps	Success Rate	Avg. Timesteps
Steve-1	0	—	0	—
MrSteve(PEM)	32	8,123	33	8,040
WISE* (SAEG only)	47	8,093	42	8,325
WISE(ours)	62	**5,981**	**77**	**4,620**

completing all three stages. We evaluate each method over 50 episodes on the same fixed map layout using different random initialization seeds. The same set of initialization seeds is shared across all methods.

Table 2 summarizes the results. Steve-1 fails completely, achieving a 0% success rate due to the absence of an episodic memory mechanism. MrSteve succeeds in 32% of episodes with an average completion time of 8,123 steps. WISE* (SAEG only), which introduces semantic memory but removes multi-scale exploration and opportunistic scheduling, improves success to 47% while maintaining a similar completion time (8,093 steps). The full WISE system achieves a success rate of 62% with an average of only 5,981 steps, corresponding to a 30-point improvement over MrSteve and a 26% reduction in completion time.

The primary challenge arises during the return-to-A phase. MrSteve's Place Event Memory stores raw visual representations and retrieves memories through feature similarity. As shown in Figure 6a, under viewpoint changes, partial occlusion, or environmental variation, cosine similarity frequently drops below the retrieval threshold, causing memory recall failure. Consequently, successful retrieval occurs only in cases where the return trajectory closely matches the original observation viewpoint. WISE addresses this limitation through VLM-generated semantic representations that are less sensitive to viewpoint changes. The SAEG-only variant already improves performance by replacing appearance-based matching with semantic retrieval. The full WISE system further incorporates multi-scale exploration, enabling observations of target locations from diverse viewpoints and producing richer memory representations. This results in an additional 15-point gain over SAEG-only WISE and reduces average return localization time from 4,253 steps (MrSteve) to 2,341 steps. These results suggest that robust long-term spatial recall in sparse environments requires both semantically grounded memory and sufficiently comprehensive exploration.

4.4 Adaptive Non-Sequential Task Performance (ABC-Sparse)

The ABC-Sparse task evaluates opportunistic decision-making under dynamic task conditions. The agent must collect resources A, B, and C, but the completion order is unconstrained. Resource C may appear while the agent is executing another subtask, requiring dynamic reassessment of task priorities. Fixed-sequence planners are expected to systematically miss such opportunities.

Table 2 presents the quantitative results. MrSteve achieves only a 33% success rate with an average completion time of 8,040 steps. Because its planner follows a rigid execution sequence (water $\rightarrow$ logs $\rightarrow$ beef), the agent typically finishes water and logs before attempting to locate beef, often requiring a return trip exceeding 150 blocks. In many episodes, cows either cannot be found within the step budget or are encountered too late. WISE* (SAEG only), which incorporates semantic memory but lacks opportunistic scheduling, improves success to 42%. Although semantic memory enables later retrieval of cow locations, the fixed task order still prevents immediate exploitation of encountered opportunities. The full WISE system achieves a success rate of 77% with an average completion time of only 4,620 steps, corresponding to a 44-point improvement over MrSteve and a 42.5% reduction in completion steps. The improvement arises directly from the Opportunistic Task Scheduler. When a cow enters the agent's observation space, SAEG provides the semantic affordance relation: $cow \rightarrow CAN\_OBTAIN \rightarrow beef$.

(a) Memory retrieval behaviour in ABA-Sparse Task   (b) Opportunistic task execution in ABC-Sparse Task.

Figure 6: (a) Memory retrieval in the ABA-Sparse task return phase. MrSteve stores raw visual features; under viewpoint changes or occlusion, cosine similarity between current observations and stored features decreases, leading to retrieval failures and forced re-exploration. In contrast, WISE processes keyframes using a VLM and stores entities and affordance relations in SAEG for retrieval. (b) Opportunistic task execution in the ABC-Sparse task. Each row illustrates the agent's planning state over time. Upon detecting resource C (cow), WISE immediately reorders its subtask queue to prioritize the opportunistic encounter, eliminating a future navigation round-trip. MrSteve's fixed-sequence planner continues executing the original plan and misses the opportunity entirely.

This immediately increases the semantic affordance relevance score for the "obtain beef" subgoal while reducing its navigation cost. As shown in Figure 6b, the scheduler recomputes task priorities and dynamically reorders execution to [beef, water, logs]. The agent collects beef immediately and resumes the remaining objectives afterward. This mechanism eliminates expensive future revisitation and directly explains the observed efficiency gain. Failure cases primarily arise when opportunities cannot be exploited in time—for example, when cows move away or are not detected before leaving the observation range. These results demonstrate that coupling semantic memory with adaptive scheduling transforms the low-level controller from a passive executor into an active decision-maker capable of exploiting environmental opportunities.

4.5 Ablation Study

We conduct controlled ablations to quantify the contribution of individual components within WISE. First, we analyze the effectiveness of the exploration hierarchy on a 128×128 map. Second, we remove each major system component— SAEG, Multi-Scale Progressive Exploration, and Opportunistic Task Scheduler—to investigate their individual contributions on the ABC-Sparse task. We also add VLM Entity Retrieval without SAEG to isolate graph structure from VLM-generated entity labels. All ablations use the same hyperparameters and evaluation protocol as the full model.

4.5.1 Exploration Tier Ablation

We evaluate three exploration variants on a 128×128 map: (1) Global-only, which retains only the quadtree-based global exploration tier; (2) Global+Regional, which combines quadtree and frontier-based exploration; and (3) Full WISE, which additionally incorporates the local Voronoi completion stage. Experiments are conducted in the simulated environment to remove low-level movement stochasticity, ensuring that performance differences reflect the intrinsic efficiency of the exploration algorithms.

Table 3b reports map coverage at 5,000, 7,000, and 10,000 timesteps, together with coverage efficiency, defined as coverage per 1,000 timesteps at the 10,000-step budget. The Global-only variant achieves 75% coverage at 10,000 steps, already outperforming MrSteve's count-based strategy (67%). However, coverage rapidly plateaus because large interior regions and boundary-adjacent gaps remain unexplored. Introducing the regional frontier stage increases coverage substantially to 91%, while the complete three-tier design

further improves coverage to 97%. Coverage efficiency similarly increases from 0.075 (Global-only) to 0.091 (Global+Regional), reaching 0.097 for the full system. These results indicate that each exploration tier contributes complementary gains.

The improvements can be explained by the distinct roles of each tier. The global quadtree stage prevents the agent from becoming trapped in local neighborhoods by encouraging exploration toward coarse-scale and distant regions. However, once a target region is selected, it does not specify where exploration should continue within that region, often leading to inefficient local wandering. The frontier-based regional stage addresses this limitation by explicitly identifying boundaries between explored and unexplored areas and directing the agent toward informative viewpoints. Nevertheless, even with these two stages, isolated gaps may persist—for example, a small unexplored area hidden behind terrain structures. Such regions frequently remain undetected because they do not lie on active frontiers. The local Voronoi stage explicitly addresses this issue by partitioning the explored space and directing the agent toward the largest remaining unexplored regions. Without this final stage, coverage saturates at 91%; with it, the agent achieves near-complete exploration coverage (97%).

4.5.2 Module Ablation

We further evaluate ablation variants on the ABC-Sparse task using a 128×128 real-world map. Specifically, WISE w/o SAEG uses raw feature-based retrieval; VLM Entity Retrieval without SAEG retains GPT-4o-generated entity labels but removes semantic affordance edges and graph traversal; WISE w/o Exploration substitutes the proposed multi-scale exploration strategy with MrSteve's count-based policy; and WISE w/o Opportunistic Task Scheduler adopts a fixed execution order instead of dynamic task prioritization.

Removing SAEG and reverting to feature retrieval causes the largest performance degradation, reducing success rate from 77% to 31%, nearly matching MrSteve's 33%. Even with efficient exploration and adaptive scheduling, the absence of semantic affordance memory prevents reliable retrieval of resource locations and removes the structured task relevance used by the scheduler.

VLM Entity Retrieval without SAEG reaches 56% success, showing that VLM labels help recognition while the remaining gap to full WISE reflects the contribution of affordance edges and graph-based retrieval.

Removing Multi-Scale Progressive Exploration reduces success to 45%, corresponding to a 32-point drop relative to the full model. Although semantic memory and opportunistic planning remain available, the agent explores less effectively and consequently acquires fewer useful observations. Resource encounters become increasingly sparse, and observations may be collected from unfavorable viewpoints that fail to generate robust memory representations. These results suggest that exploration quality fundamentally constrains the information available for downstream memory and planning.

Removing the Opportunistic Task Scheduler produces a smaller but still substantial reduction, decreasing success to 62%. In this setting, the agent can still discover and remember resource locations, but it can no longer dynamically reorder subtasks. As a result, the agent completes water and log collection before revisiting previously observed cows, introducing unnecessary travel costs. The 15-point gap largely corresponds to scenarios in which opportunities are highly time-sensitive.

The component-removal results follow the ordering:

$$\text{SAEG (feature retrieval only) } (-46)$$
$$> \text{Multi-Scale Exploration } (-32) > \text{Opportunistic Scheduler } (-15).$$

This hierarchy closely mirrors the dependency structure of WISE itself: exploration supplies observations, memory transforms observations into semantic knowledge, and planning consumes that knowledge to make adaptive decisions. Notably, reverting to feature retrieval reduces performance to approximately MrSteve's level. Conversely, memory without advanced exploration still outperforms MrSteve (45% vs. 33%), indicating that semantic memory retains value even when observation quality is limited. The complete system, integrating all three modules, achieves 77% success and substantially outperforms all ablated variants.

Table 3: Ablation Studies of WISE Method
Ablation results. **Bold** = best. — = not applicable.

Variant	5,000 steps	7,000 steps	10,000 steps	Cov. Eff.
MrSteve (Count-Based)	0.64	0.65	0.67	0.067
Global only	**0.72**	0.75	0.75	0.075
Global + Regional	0.71	0.87	0.91	0.091
Global + Regional + Local (full WISE)	0.71	**0.87**	**0.97**	**0.097**

(a) Exploration tier ablation on 128×128 simulated map. Coverage efficiency = coverage per 1,000 timesteps at 10,000-step budget.

Variant	Success Rate (%)	Avg. Timesteps	Δ vs. full model
WISE w/o SAEG (feature retrieval)	31	8,034	-46 pts
VLM Entity Retrieval without SAEG	56	6,320	-21 pts
WISE w/o Multi-Scale Exploration	45	7,942	-32 pts
WISE w/o Opportunistic Task Scheduler	62	6,981	-15 pts
WISE (full model)	**77**	**4,620**	—

(b) Module ablation on adaptive non-sequential (ABC) task (128×128 real map). Δ vs. full model = success rate difference vs. full WISE.

5 Conclusion

In this paper, we introduced WISE, a low-level controller for long-horizon embodied tasks in Minecraft that unifies exploration, memory, and planning within a closed reasoning loop. WISE augments conventional episodic memory with a Semantic Affordance Event Graph that captures not only what, where, and when, but also why past observations matter and which future tasks they enable. Based on this semantic memory, an Opportunistic Task Scheduler dynamically re-prioritizes subtasks, while a multi-scale progressive exploration strategy provides spatially diverse observations. Experiments on sparse sequential and non-sequential tasks demonstrate that WISE substantially outperforms strong baselines in exploration efficiency, task success rate, and completion speed. Ablation studies further show complementary contributions from exploration, semantic memory, and adaptive planning. Future work will extend WISE to broader embodied environments and investigate lightweight alternatives to external VLMs for scalable knowledge construction.

References

Bowen Baker, Ilge Akkaya, Peter Zhokov, Joost Huizinga, Jie Tang, Adrien Ecoffet, Brandon Houghton, Raul Sampedro, and Jeff Clune. Video pretraining (vpt): Learning to act by watching unlabeled online videos. *Advances in Neural Information Processing Systems*, 35:24639–24654, 2022.

Shaofei Cai, Zihao Wang, Xiaojian Ma, Anji Liu, and Yitao Liang. Open-world multi-task control through goal-aware representation learning and adaptive horizon prediction. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 13734–13744, 2023.

Shaofei Cai, Bowei Zhang, Zihao Wang, Xiaojian Ma, Anji Liu, and Yitao Liang. Groot: Learning to follow instructions by watching gameplay videos. In *The Twelfth International Conference on Learning Representations*, 2024.

Matthew Chang, Theophile Gervet, Mukul Khanna, Sriram Yenamandra, Dhruv Shah, So Min, Kavit Shah, Chris Paxton, Saurabh Gupta, Dhruv Batra, et al. Goat: Go to any thing. *Robotics: Science and Systems XX*, 2024.

Devendra Singh Chaplot, Dhiraj Gandhi, Saurabh Gupta, Abhinav Gupta, and Ruslan Salakhutdinov. Learning to explore using active neural slam. In *International Conference on Learning Representations*, 2020a.

Devendra Singh Chaplot, Ruslan Salakhutdinov, Abhinav Gupta, and Saurabh Gupta. Neural topological slam for visual navigation. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pp. 12875–12884, 2020b.

Or Dinari and Oren Freifeld. Revisiting dp-means: fast scalable algorithms via parallelism and delayed cluster creation. In *Uncertainty in Artificial Intelligence*, pp. 579–588. PMLR, 2022.

Linxi Fan, Guanzhi Wang, Yunfan Jiang, Ajay Mandlekar, Yuncong Yang, Haoyi Zhu, Andrew Tang, De-An Huang, Yuke Zhu, and Anima Anandkumar. Minedojo: Building open-ended embodied agents with internet-scale knowledge. *Advances in Neural Information Processing Systems*, 35:18343–18362, 2022.

Patrick Feeney, Sarah Anna Schneider, Panagiotis Lymperopoulos, Li-Ping Liu, Matthias Scheutz, and Michael C Hughes. Novelcraft: A dataset for novelty detection and discovery in open worlds. *Transactions on Machine Learning Research*, 2023.

William H Guss, Brandon Houghton, Nicholay Topin, Phillip Wang, Cayden Codel, Manuela Veloso, and Ruslan Salakhutdinov. Minerl: a large-scale dataset of minecraft demonstrations. In *Proceedings of the 28th International Joint Conference on Artificial Intelligence*, pp. 2442–2448, 2019.

Jimmy Krozel and Dominick Andrisani. Navigation path planning for autonomous aircraft: Voronoi diagram approach. *Journal of Guidance, Control, and Dynamics*, 13(6):1152–1154, 1990.

Zaijing Li, Yuquan Xie, Rui Shao, Gongwei Chen, Dongmei Jiang, and Liqiang Nie. Optimus-1: Hybrid multimodal memory empowered agents excel in long-horizon tasks. *Advances in neural information processing systems*, 37:49881–49913, 2024.

Zhuoling Li, Xiaogang Xu, Zhenhua Xu, Ser-Nam Lim, and Hengshuang Zhao. Larm: Large auto-regressive model for long-horizon embodied intelligence. In *International Conference on Machine Learning*, pp. 36614–36623. PMLR, 2025.

Shalev Lifshitz, Keiran Paster, Harris Chan, Jimmy Ba, and Sheila McIlraith. Steve-1: A generative model for text-to-behavior in minecraft. *Advances in Neural Information Processing Systems*, 36:69900–69929, 2023.

Shunyu Liu, Yaoru Li, Kongcheng Zhang, Zhenyu Cui, Wenkai Fang, Yuxuan Zheng, Tongya Zheng, and Mingli Song. Odyssey: empowering minecraft agents with open-world skills. In *Proceedings of the Thirty-Fourth International Joint Conference on Artificial Intelligence*, pp. 187–195, 2025.

Junyeong Park, Junmo Cho, and Sungjin Ahn. Mrsteve: Instruction-following agents in minecraft with what-where-when memory. In *The Thirteenth International Conference on Learning Representations*, 2025. URL https://openreview.net/forum?id=CjXaMI2kUH.

Yiran Qin, Enshen Zhou, Qichang Liu, Zhenfei Yin, Lu Sheng, Ruimao Zhang, Yu Qiao, and Jing Shao. Mp5: A multi-modal open-ended embodied system in minecraft via active perception. In *2024 IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 16307–16316. IEEE, 2024.

Theodore Sumers, Shunyu Yao, Karthik R Narasimhan, and Thomas L Griffiths. Cognitive architectures for language agents. *Transactions on Machine Learning Research*, 2023.

Boyang Sun, Hanzhi Chen, Stefan Leutenegger, Cesar Cadena, Marc Pollefeys, and Hermann Blum. Frontiernet: Learning visual cues to explore. *IEEE Robotics and Automation Letters*, 10(7):6576–6583, 2025. doi: 10.1109/LRA.2025.3569122.

Haoran Tang, Rein Houthooft, Davis Foote, Adam Stooke, OpenAI Xi Chen, Yan Duan, John Schulman, Filip DeTurck, and Pieter Abbeel. # exploration: A study of count-based exploration for deep reinforcement learning. *Advances in neural information processing systems*, 30, 2017.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. Voyager: An open-ended embodied agent with large language models. *Transactions on Machine Learning Research*, 2024. URL https://openreview.net/forum?id=ehfRiF0R3a.

Zihao Wang, Shaofei Cai, Guanzhou Chen, Anji Liu, Xiaojian Ma, Yitao Liang, and Team CraftJarvis. Describe, explain, plan and select: interactive planning with large language models enables open-world multi-task agents. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, pp. 34153–34189, 2023.

Zhengwei Xie, Zhisheng Chen, Ziyan Weng, Tingyu Wu, Chenglong Li, Vireo Zhang, and Kun Wang. Steve-evolving: Open-world embodied self-evolution via fine-grained diagnosis and dual-track knowledge distillation. *arXiv preprint arXiv:2603.13131*, 2026.

Brian Yamauchi. Frontier-based exploration using multiple robots. In *Proceedings of the second international conference on Autonomous agents*, pp. 47–53, 1998.

Shu Yu and Chaochao Lu. Adam: An embodied causal agent in open-world environments. In *The Thirteenth International Conference on Learning Representations*, 2025.

Haoqi Yuan, Chi Zhang, Hongcheng Wang, Feiyang Xie, Penglin Cai, Hao Dong, and Zongqing Lu. Skill reinforcement learning and planning for open-world long-horizon tasks. In *NeurIPS 2023 Foundation Models for Decision Making Workshop*, 2023. URL `https://openreview.net/forum?id=tTZVrnr45N`.

Tianjun Zhang, Huazhe Xu, Xiaolong Wang, Yi Wu, Kurt Keutzer, Joseph E Gonzalez, and Yuandong Tian. Noveld: A simple yet effective exploration criterion. *Advances in Neural Information Processing Systems*, 34:25217–25230, 2021.

Zhonghan Zhao, Wenhao Chai, Xuan Wang, Ke Ma, Kewei Chen, Dongxu Guo, Tian Ye, Yanting Zhang, Hongwei Wang, and Gaoang Wang. Steve series: Step-by-step construction of agent systems in minecraft. *arXiv preprint arXiv:2406.11247*, 2024.

Enshen Zhou, Yiran Qin, Zhenfei Yin, Yuzhou Huang, Ruimao Zhang, Lu Sheng, Yu Qiao, and Jing Shao. Minedreamer: Learning to follow instructions via chain-of-imagination for simulated-world control. *arXiv preprint arXiv:2403.12037*, 2024.

Xizhou Zhu, Yuntao Chen, Hao Tian, Chenxin Tao, Weijie Su, Chenyu Yang, Gao Huang, Bin Li, Lewei Lu, Xiaogang Wang, et al. Ghost in the minecraft: Generally capable agents for open-world environments via large language models with text-based knowledge and memory. *arXiv preprint arXiv:2305.17144*, 2023.

A Implementation Details

A.1 Multi-Scale Progressive Exploration

The explorer must supply memory module with observations that are both spatially complete and efficiently acquired. No single-scale strategy can satisfy both requirements simultaneously: global-only strategies leave local gaps; local-only strategies scale poorly; frontier-only strategies ignore interior voids. WISE addresses this with a **three-tier progressive framework** in which each tier resolves the gaps left by the previous one.

Global-Scale Rapid Search. The global tier answers: which macro-region should the agent prioritise next? The Minecraft world is represented as an **adaptive quadtree** whose root spans the full known map and whose children represent candidate regions. Subdivision adapts dynamically to visitation frequency, allocating finer resolution to denser unexplored areas. Let P_t denote the agent's current 2D map position. Each candidate node N_i is scored by:

$$Score_G(N_i) = \alpha_G \cdot Depth(N_i) - \beta_G \cdot Dist(P_t, N_i), \tag{14}$$

where $Depth(N_i)$ measures the normalized depth or unexplored granularity of region N_i, $Dist(P_t, N_i)$ is the normalized distance from the current position to the region, and α_G, β_G are global-tier weights. The first term encourages the agent to visit fine-grained unexplored regions, while the second term penalizes distant targets. The quadtree reduces the cost of region lookup and next-target selection from $O(n)$ to $O(\log n)$ over candidate spatial regions. This complexity refers to the efficiency of selecting the next macro-region from the spatial index. The realized coverage still depends on the low-level controller, terrain geometry, failed movements, and the timestep budget.

Regional-Scale Frontier Refinement. Given a macro-region from the global tier, the regional tier answers: which boundary points offer the highest information gain? Frontier points—boundaries between explored and unexplored space—are detected via morphological dilation and scored as:

$$Score_R(f_i) = \alpha_R \cdot Cover(f_i) + \beta_R \cdot Novel(f_i) - \gamma_R \cdot Dist(P_t, f_i), \tag{15}$$

where $Cover(f_i)$ estimates the uncovered area visible behind frontier f_i, $Novel(f_i)$ measures information novelty, $Dist(P_t, f_i)$ is the normalized distance from the agent to the frontier, and $\alpha_R, \beta_R, \gamma_R$ are regional-tier weights. The frontier with the highest score is selected as the next regional exploration target. This tier expands the explored boundary and reduces the local wandering that can occur when only global target selection is used.

Local-Scale Voronoi Completion. After frontier refinement, residual interior patches may remain—a problem that neither global planning nor frontier-following fully resolves. The local tier answers: which residual gaps remain unfilled? We apply Voronoi decompositionKrozel & Andrisani (1990) over the visited point set $\mathbf{V} = \{v_1, v_2, \dots, v_n\}$, where $v_i = (x_i, y_i, t_i)$, x_i and y_i are 2D coordinates, and t_i is the timestamp. The Voronoi cell of visited point v_i is

$$\mathbf{C_i} = \{p \in \mathbf{\Omega} \mid \|p - v_i\|_2 < \|p - v_j\|_2, \ \forall j \neq i\}. \tag{16}$$

Residual uncovered regions are identified from $\mathbf{\Omega} \setminus \bigcup_{i=1}^{n} \mathbf{C_i}$. Each residual region U_i is prioritised by:

$$Score_L(U_i) = \alpha_L \cdot Area(U_i) - \beta_L \cdot Dist(P_t, U_i), \tag{17}$$

where $Area(U_i)$ is the normalized area of the residual unexplored region, $Dist(P_t, U_i)$ is the normalized distance from the current position to that region, and α_L, β_L are local-tier weights. The agent moves toward the highest-scoring residual region to improve local coverage completion.

This local tier improves coverage completion by explicitly targeting residual gaps that remain after global and regional exploration. Together, the three tiers provide a coarse-to-fine exploration strategy: the global

tier selects macro-regions efficiently, the regional tier expands frontier boundaries, and the local tier fills remaining uncovered regions.

Local escape mechanism. Three escalating recovery heuristics prevent exploration stagnation. If fewer than five blocks are traversed in 30 seconds, the agent triggers *local replanning*. On repeated failure to reach a target, it performs a *target reset* via memory query. On repeated location revisitation, it executes a *graph-level rollback* to the nearest unvisited key node. These heuristics ensure that exploration continues to supply fresh observations to the memory module even under adverse terrain conditions.

A.2   Asynchronous VLM Update and SAEG Maintenance

WISE decouples VLM inference from the online control loop. During execution, the online controller selects candidate keyframes from the short-term geometric memory and appends them to a pending VLM buffer. An asynchronous VLM worker processes the buffer when 16 keyframes are available or flushes it after 25 seconds. While the request is being processed, the agent continues acting using M_{short} and the latest available version of M_{SAEG}.

Once a VLM response is returned, the parsed outputs are grounded against the Minecraft task-resource vocabulary and incorporated into SAEG by updating entity nodes, spatial attributes, timestamps, semantic affordance relations, and co-occurrence relations. This design prevents VLM latency from blocking real-time action execution while keeping the graph available for semantic affordance retrieval and opportunistic scheduling.

The number of selected keyframes is adaptive and depends on the explored trajectory, entropy filtering, clustering, and redundancy removal. A typical 128×128 task yields approximately 200–300 processed keyframes. We report the average number of VLM requests per episode in Section A.10.

A.3   Hardware and Software Configuration

All experiments were conducted on a single server equipped with four NVIDIA RTX 4080 16GB GPUs. Unless otherwise stated, each agent rollout used one GPU. The host operating system was Ubuntu v22.04. All agents were implemented in Python v3.11 with PyTorch v2.5.1.

Minecraft Java Edition was accessed via MineDojo v0.1 (built on MineRL). The low-level controller used the publicly released VPT 2x checkpoint and the VPT-Nav weights distributed with MrSteve. GPT-4o requests used the model identifier

`gpt-4o-2024-05-13`. Each experiment episode ran with a per-timestep time constraint of $\leq 50\,\text{ms}$, consistent with the Minecraft Java Edition real-time rendering requirement.

A.4   World and Map Configuration

Sparse task experiments (Sections 4.3 and 4.4).   A 128×128 real Minecraft map combining mountains, ponds, desert, and forest areas was used as shown in Figure 7.

Each method was evaluated over 50 episodes on the same fixed map layout. Episodes used different random initialization seeds, while all methods were evaluated using the same set of seeds, spawn-point protocol, and episode budget.

Exploration experiments (Section 4.2).   Two map scales were used: small (128×128 blocks) and large (384×384 blocks), each evaluated under two conditions.

- **Simulated**: mobs disabled, terrain variation disabled, day–night cycle paused.

- **Real (Stochastic)**: full Minecraft stochasticity including hostile mobs, weather, and day–night cycles.

All agents started from the same fixed spawn point on the same world seed within each condition.

Figure 7: The 128×128 real Minecraft map used for task-completion experiments. The combination of biome diversity and deliberate resource sparsity requires WISE's memory, scheduling, and exploration modules to operate jointly.

All methods are evaluated on identical map instances and seeds within each condition.

A.5 Evaluation Protocol and Coverage Metric

Map coverage is computed as the fraction of map cells visited by the agent within a fixed Minecraft timestep budget. A timestep corresponds to a Minecraft environment tick; Minecraft runs at 20 timesteps per second. Coverage values are normalized by map area and are therefore comparable within the same map size and evaluation condition.

For the real-environment coverage table in the main paper, the 5,000- and 10,000-timestep columns correspond to the 128×128 map, while the 20,000- and 40,000-timestep columns correspond to the 384×384 map. Therefore, these columns should not be interpreted as a single monotonic sequence on the same map. In the revised table, we group columns by map size to make this correspondence explicit.

For task-completion metrics, success rate is computed over all evaluation episodes. Average completion timesteps are computed over successful episodes only.

A.6 Baseline Implementation

Steve-1: the publicly released checkpoint was used without modification; it serves as a no-memory reference baseline. **MrSteve**: the publicly released checkpoint and Place–Event Memory (PEM) implementation were used; it serves as the primary baseline. All baselines share identical map configurations, spawn points, and episode budgets with WISE.

MrSteve uses PEM-style visual-similarity memory retrieval and does not use GPT-4o for semantic graph construction. WISE uses GPT-4o only for constructing and updating SAEG.

A.7 Full Hyperparameter Table

Table 4 lists all secondary hyperparameters required for reproduction.

Hyperparameter selection. Keyframe thresholds $(\theta_{\text{ent}}, \theta_c)$ were selected via grid search on a held-out validation map. Search ranges:

$$\theta_{\text{ent}} \in \{0.05, 0.10, 0.15, 0.20\}, \quad \theta_c \in \{0.75, 0.80, 0.85, 0.90\}.$$

Table 4: Full hyperparameter list for WISE.

Module	Parameter	Value	Description
Exploration	Quadtree depth weight α_G	0.6	Rewards unexplored depth (Eq. 14)
	Quadtree distance penalty β_G	0.4	Penalizes navigation cost (Eq. 14)
	Frontier weights $(\alpha_R, \beta_R, \gamma_R)$	norm.	Coverage, novelty, distance (Eq. 15)
	Local completion weights (α_L, β_L)	norm.	Area, distance (Eq. 17)
	Stagnation threshold	5 blk/30 s	Triggers local replanning
	Sliding window size	60s	Short-term memory eviction
Memory	Entropy threshold θ_{ent}	0.15	Entropy-based keyframe trigger
	Cosine threshold θ_c	0.85	Cluster-based trigger
	Grounding threshold θ_{ground}	0.9	Vocabulary/entry matching
	Top-k retrieval	10	Short-term candidates
	Retrieval weight λ_{ret}	0.5	Similarity vs. semantic affordance matching
	VLM batch size	16 frames	Buffered keyframes per streaming VLM request
	VLM requests per episode	$\sim$14	Average across episodes
Planning	Urgency weight w_u	0.3	Eq. 7
	Semantic affordance relevance weight w_a	0.5	Eq. 7
	Navigation cost weight w_n	0.2	Eq. 7

Scheduler weights (w_u, w_a, w_n) are reported as the default setting used in the main experiments. Sensitivity analyses are reported in Section B.3.

A.8 Semantic Affordance Graph Construction Details

The structured Minecraft knowledge database used for grounding VLM outputs was derived from Minecraft Wiki resources and covers mob drops (e.g., cow $\to$ beef), crafting recipes, smelting chains, and environmental state transitions. The database contains 1534 entries and is used to validate candidate entity–outcome relations proposed by the VLM.

Graph schema:

- **Node types:** entity (e.g., cow, stone), action (e.g., mine, craft), environment (e.g., rain, hunger).

- **Edge types:** timestep, position, semantic affordance (e.g., `CAN_OBTAIN`, `CAN_CRAFT`, `CAN_SMELT`), and co-occurrence (e.g., `CO_OCCURS_WITH`).

Average number of graph nodes and edges per episode at termination: approximately 120.

A.9 VLM Prompt and Output Schema

Each VLM request receives selected keyframes, timestamps, and agent poses. The VLM returns visible entities, candidate semantic affordance relations, and spatial co-occurrences using the following schema:

```
Return JSON only.  For each keyframe, list visible Minecraft entities, candidate
affordance relations from {CAN_OBTAIN, CAN_CRAFT, CAN_SMELT}, and spatial
co-occurrences: {"frames": [{"timestep": int, "entities": [...], "affordances":
[{"source": str, "relation": str, "target": str}], "co_occurrences": [...]}]}.
```

After receiving the VLM output, WISE applies four filtering steps: (1) normalize entity names to the Minecraft vocabulary; (2) discard entities or outcomes not present in the task-resource database; (3) merge duplicate entity instances with the same normalized type and nearby spatial coordinates; and (4) retain semantic affordance edges only when the source entity is observed and the target resource is valid under Minecraft mechanics.

A.10 API Cost Breakdown

All GPT-4o requests were processed asynchronously and did not block the online control loop. Table 5 summarizes the API cost.

Table 5: GPT-4o API cost breakdown.

Item	Value
Avg. VLM requests per episode	~14
Avg. input tokens per request	4575
Avg. output tokens per request	1618
Est. cost per episode (USD)	0.48$
Total API cost across all exps. (USD)	512$

B Additional Experimental Analyses

B.1 SAEG Quality

To evaluate the quality of the Semantic Affordance Event Graph (SAEG), we sample 50 keyframes from ABC-Sparse episodes and manually annotate the task-relevant entities and semantic affordance relations in each frame. Entity precision is computed as the proportion of predicted entities that match the manual annotations. Affordance-relation precision is computed as the proportion of predicted entity–relation–outcome tuples that agree with both the manual annotations and the curated Minecraft knowledge base.

Table 6: SAEG quality on 50 manually annotated ABC-Sparse keyframes.

Representation	Entity precision	Affordance-relation precision
SAEG	87.5%	87.5%

As shown in Table 6, most predicted entities and affordance relations are consistent with the annotations. The remaining errors mainly arise from small or partially occluded objects and from ambiguous visual evidence. These results support the use of SAEG for task-relevant memory retrieval, while the evaluation should be interpreted as a focused diagnostic analysis because it uses a limited set of 50 keyframes.

B.2 Controlled Retrieval under Viewpoint and Occlusion Changes

We conduct a controlled retrieval experiment using a fixed Minecraft scene containing a pond. The target and scene layout remain unchanged, while the viewpoint, distance, and degree of partial occlusion are varied across six observations. For each observation, we test whether MineCLIP feature retrieval and GPT-4o semantic entity retrieval recover the stored pond memory. A value of 1 denotes successful retrieval.

Table 7: Controlled pond retrieval under different views. Column headers report the visible fraction of the target; 1 denotes successful retrieval.

Method	3.6%	10.2%	12.4%	17.3%	20.8%	12.4%
MineCLIP feature retrieval	0	0	0	0	1	1
GPT-4o semantic entity retrieval	0	1	1	1	1	1

Table 7 shows that MineCLIP feature retrieval succeeds in two of the six views, whereas GPT-4o semantic entity retrieval succeeds in five of the six views.. Feature retrieval is sensitive to changes in low-level appearance, particularly when the target is small or partially occluded. Semantic entity retrieval can remain

successful when sufficient contextual evidence is available, even if the current image differs from the stored view.

The visibility fraction alone does not determine retrieval difficulty: columns with similar visible fractions may correspond to different viewpoints, distances, or occlusion patterns. Therefore, this experiment supports greater robustness under the evaluated changes, but it does not claim complete invariance to viewpoint or occlusion.

B.3 Hyperparameter Sensitivity

We evaluate parameters associated with VLM processing, keyframe selection, multi-scale exploration, and opportunistic scheduling. These experiments are included in the appendix because they support implementation choices but are not central to the main comparison. Default settings are shown in bold.

B.3.1 VLM Batching and Keyframe Selection

Table 8: Sensitivity of VLM batching and keyframe selection.

VLM batch size		12	**16**	20	
Mean response time (s)		39.0	44.1	51.1	
Mean requests per episode		19	14	11	
$(\theta_c, \theta_{\text{ent}})$	$(0.65, 0.35)$	$(0.75, 0.25)$	$(\mathbf{0.85}, \mathbf{0.15})$	$(0.95, 0.05)$
Selected keyframes	357	281	**217**	425

Table 8 illustrates the trade-off introduced by VLM batching. A smaller batch reduces the response time but produces more requests per episode, while a larger batch reduces the number of requests at the cost of increased response time. The default batch size of 16 provides an intermediate operating point between update frequency and API efficiency.

The keyframe thresholds jointly control visual redundancy and semantic informativeness. The default setting selects 217 keyframes, reducing VLM processing relative to the less selective configurations while retaining the observations used to construct SAEG. Because the two thresholds affect different selection criteria, the number of selected keyframes is not expected to vary monotonically when both are changed simultaneously.

B.3.2 Exploration and Scheduler Parameters

Table 9: Sensitivity of the quadtree and scheduler weights.

Quadtree depth weight α_G		0.48	**0.60**	0.72	
Coverage at 5,000 timesteps		0.56	**0.71**	0.52	
Coverage at 10,000 timesteps		0.86	**0.97**	0.84	
(w_u, w_a, w_n)	$(\mathbf{0.3}, \mathbf{0.5}, \mathbf{0.2})$	$(0.5, 0.3, 0.2)$	$(0.3, 0.2, 0.5)$	$(0.3, 0.4, 0.3)$
Success rate (%)	**77**	68	56	74
Avg. completion timesteps	**4,620**	5,830	6,650	5,225

For global exploration, a small α_G underweights unexplored fine-grained regions, whereas an excessively large value may prioritize region depth over navigation efficiency. The default value $\alpha_G = 0.60$ achieves the highest coverage at both evaluated budgets.

The scheduler results show that assigning the largest weight to semantic affordance relevance, while retaining urgency and navigation-cost terms, produces the highest success rate and the lowest average completion

time among the evaluated settings. Increasing the urgency weight makes the scheduler behave more like the original fixed task order, whereas a large navigation-cost weight can favor nearby but less task-relevant targets. These results support the selected default configuration but do not imply that it is optimal for every task distribution.

B.4 Longer and More Diverse Sparse-Task Sequence

The main ABC-Sparse experiment contains three objectives. To examine a longer and more heterogeneous sequence, we additionally evaluate the Mixed-5 Sparse Task:

<p align="center">obtain beef → obtain wheat seeds → collect logs → obtain wool → find water.</p>

The sequence includes mobs, vegetation, collectible resources, and an environmental landmark, thereby requiring the agent to retain and retrieve different types of task-relevant observations.

<p align="center">Table 10: Success rate on the Mixed-5 Sparse Task.</p>

Method	Success rate
Steve-1	0%
MrSteve (PEM)	16%
WISE	**56%**

As shown in Table 10, Steve-1 does not complete the full sequence, while MrSteve reaches a 16% success rate. WISE achieves 56%, indicating that its advantage is retained when the symbolic task sequence is extended from three to five heterogeneous objectives. This experiment tests a longer task composition within the same Minecraft domain; broader generalization to other environments remains outside the present evaluation.

C Task Definitions

C.1 ABA-Sparse (Sequential Task)

The agent spawns in the 128×128 real Minecraft map. The task proceeds in three phases:

1. **Phase A_1**: Locate and collect resource A at position p_A.

2. **Phase B**: Navigate to and collect distant resource B
   (minimum distance from A: ≥ 100 blocks).

3. **Phase A_2**: Return precisely to position p_A using only memory—re-exploration is discouraged by the remaining timestep budget.

A trial is **successful** if all three items are collected within the timestep budget. Timestep budget: 12,000.

C.2 ABC-Sparse (Non-Sequential Task)

The agent must collect items A, B, and C in *any* order. Resource C (e.g., beef from a cow) appears *opportunistically* mid-episode at a random location during execution of sub-task A, requiring priority reassessment.

A fixed-sequence policy may miss this opportunity and incur an additional round-trip cost.

Specific resource types: $A = $ **water**, $B = $ **logs**, $C = $ **beef (from cow)**.

Timestep budget: **12000**. C spawn distribution: uniform random within 30 blocks of the agent at timestep 500.