SPIRAL: Self-supervised Perturbation-Invariant Representation Learning for Speech Pre-Training

Abstract

We introduce a new approach for speech pre-training named SPIRAL which works by learning denoising representation of perturbed data in a teacher-student framework. Specifically, given a speech utterance, we first feed the utterance to a *teacher* network to obtain corresponding representation. Then the same utterance is perturbed and fed to a *student* network. The student network is trained to output representation resembling that from the teacher. At the same time, the teacher network is updated as moving average of student's weights over training steps. In order to prevent representation collapse, we apply an in-utterance contrastive loss as pre-training objective and impose position randomization on the input to the teacher. SPIRAL achieves competitive or better results compared to state-of-the-art speech pre-training method wav2vec 2.0, with significant reduction of training cost (80% for BASE model, 65% for LARGE model). Furthermore, we address the problem of noise-robustness that is critical to real-world speech applications. We propose multi-condition pre-training by perturbing the student's input with various types of additive noise. We demonstrate that multi-condition pre-trained SPIRAL models are more robust to noisy speech (7% - 26% relative word error rate reduction on synthetic noisy test data), compared to applying multi-condition training solely in the fine-tuning stage. The code will be released after publication.

1 INTRODUCTION

Industrial-scale automatic speech recognition (ASR) systems are usually trained with ten-thousands of hours of hand-transcribed speech data (Galvez et al., 2021). However, labeling speech data is expensive and time-consuming, especially for languages with small speaker populations, or for specific domains (e.g., legal, financial, scientific).

Recently, methods of utilizing unlabeled speech data to improve speech recognition system have achieved remarkable progress. Amongst them, *self-training* (Manohar et al., 2015; Kahn et al., 2020a; Synnaeve et al., 2020a; Chen et al., 2020b; Xu et al., 2020; Park et al., 2020b), also known as *pseudo-labeling*, starts by training an ASR model with labeled speech data, which is referred to as teacher model. Then the teacher model, usually combined with a language model, is used to produce pseudo-labels for unlabeled speech data. Finally, the labeled data and the pseudo-labeled data are combined to train a new model, which is referred to as student model. The process is repeated by taking the student model as the teacher in next iteration. Another line of work is speech *pre-training* (van den Oord et al., 2019; Chung & Glass, 2020; Wang et al., 2020; Baevski et al., 2020b; Liu et al., 2020). Pre-training learns speech representation from unlabeled data in a self-supervised way. The pre-trained model is then fine-tuned on the labeled data. Self-training and pre-training are complementary as shown in recent work (Xu et al., 2021; Zhang et al., 2020).

In this paper, we introduce a new speech pre-training method which works by learning representation denoising of perturbed data with the teacher-student framework, named as Self-supervised Perturbation-Invariant Representation Learning (SPIRAL). Compared to the current state-of-the-art speech pre-training methods such as wav2vec 2.0 (Baevski et al., 2020b) and HuBERT (Hsu et al., 2021), our method allows end-to-end training with a single contrastive loss, and without relying on discrete unit discovery techniques such as vector quantization (Jégou et al., 2011; Baevski et al.,

2020a;b) or iterative clustering process (Hsu et al., 2021). SPIRAL also allows to combine with multi-condition training (Seltzer et al., 2013; Ko et al., 2015) to improve noise-robustness for the downstream speech tasks.

SPIRAL is motivated by the observation that human tolerates speech perturbations or distortions fairly well. For example, two people can communicate effectively in a noisy environment, or over a distorted telephone channel. Therefore, we hypothesize that by learning representation that is invariant to perturbation, the model will learn high-level representation which can enhance speech applications.

To learn perturbation-invariant representation in a self-supervised way, we employ a teacher-student framework similar to Tarvainen & Valpola (2017). During pre-training, given a speech utterance, we guide the student network which consumes the perturbed utterance to learn from the teacher network which consumes the clean utterance. The student is trained to produce denoised representation of the perturbed utterance similar to teacher's representation of the clean utterance. Meanwhile, the teacher shares the same model architecture with student, whose weights are updated by averaging the student's weights over past training steps.

We apply the *in-utterance* contrastive loss proposed by Chopra et al. (2005) to avoid model collapse to trivial representation. As speech utterance are sequential data, there is another possible trivial solution which we call *positional collapse*. Positional collapse occurs when the student "cheats" by exploiting position correlation in teacher's representation to minimize the loss, while ignoring the content of the input utterance. To prevent positional collapse, we propose *position randomization* by adding random number of paddings on both sides of input utterance to the teacher.

Large-scale speech pre-training is computationally demanding. To reduce computation cost, we adopt a gradual down-sampling strategy in SPIRAL model, which has been verified effective in speech recognition literatures with negligible performance degradation (Peddinti et al., 2018; Han et al., 2020b; Huang et al., 2020). We also speculate that aggressive down-sampling helps to remove redundancy in speech.

To evaluate the effectiveness of SPIRAL, we conduct experiments on LibriSpeech and Libri-Light datasets. By training a small convolutional classifier on the representation of a frozen SPIRAL model, we can achieve WER of 4.4% and 7.4% on Librispeech test-clean and test-other respectively. SPIRAL achieves competitive or better results compared to current state-of-the-art speech pre-training methods, while being much more training-efficient. We also demonstrate that multi-condition pre-trained SPIRAL are more robust to noisy speech (7% - 26% relative word error rate reduction on synthetic noisy test data), compared to the model applying multi-condition training solely in the fine-tuning stage.

2 RELATED WORK

Mean Teacher (MT) (Tarvainen & Valpola, 2017) proposes using a student network to learn from a teacher network which is the moving average version of the student in the semi-supervised learning setting. The authors apply a supervised loss for labeled data and a consistency loss between teacher and student predictions for unlabeled data. However, direct application of MT to self-supervised learning leads to representation collapse (Grill et al., 2020).

Noisy student training (NST) (Xie et al., 2020; Park et al., 2020b) is a self-training method. NST demonstrates the importance of the aggressive injection of noise into the student. Although not emphasized, no noise is injected into pseudo-labeling process of the teacher. We consider our work as an extension of self-training approach to the self-supervised learning regime. Instead of using the teacher to provide pseudo-labels, we utilize the teacher for pseudo-reference representation.

Denoising autoencoders (Vincent et al., 2008) learn to recover a clean input from a corrupted version. However, speech data contain redundancy which is irrelevant to some speech applications such as speech recognition. Previous work (Baevski et al., 2019) shows that speech pre-training by recovering masked input speech features is not effective. In SPIRAL, we instead enforce latent representation of a corrupted input to resemble that of the corresponding clean input.

Bootstrap Your Own Latent (BYOL) (Grill et al., 2020) is a self-supervised image representation learning method. The method is based on a teacher-student framework similar to MT. The authors

refer to student network as online network and teacher network as target network. They observe that naive application of MT to self-supervised learning leads to trivial constant representation. They prevent the representation collapse by appending a predictor to the student network. The theory behind is under investigation (Chen & He, 2021; Tian et al., 2021). Our method draws inspirations from BYOL and shares the similar architecture, but there are crucial differences. Instead of learning a single global representation for an image as in BYOL, SPIRAL learns a sequence of representation for an utterance. We aim for sequence applications such as speech recognition. In our preliminary experiments, we observe that appending a predictor to student network is not sufficient to prevent trivial constant representation for sequential representation learning. We use in-utterance contrastive loss (Baevski et al., 2020b) combined with input position randomization to successfully avoid representation collapse. We still keep the predictor in SPIRAL, but only for the sake of performance improvement from our observation. Another difference is that BYOL does not perform representation denoising. BYOL applies perturbation, which they call augmentation, to both the inputs of the teacher and the student. We demonstrate that representation denoising is crucial for speech pre-training. When perturbation is applied to the teacher's input, the effectiveness of speech pre-training degrades drastically.

Wav2vec 2.0 (Baevski et al., 2020b) is a self-supervised speech representation learning method which belongs to the masked prediction family. Masked prediction methods are effective for text pre-training (Devlin et al., 2019), but not for speech pre-training when naively applied (Baevski et al., 2019). The reason is that speech data contains redundancy such as speaker information, pronunciation variations, which are irrelevant to the semantic meaning of the utterance. To overcome this problem, wav2vec 2.0 perform masking in intermediate latent space and performs target discretization with a differentiable quantization scheme. However, quantization leads to a more complex model by introducing additional hyper-parameters and an additional diversity loss. SPIRAL does not utilize quantization, and still achieves competitive performance compared to wav2vec 2.0. We hypothesize that aggressive down-sampling and learning by matching output representation may help to remove redundancy from the learned representation. We leave the investigation of whether target discretization could further improve SPIRAL for future work.

Liang et al. (2018) demonstrates that under the supervised learning setting, enforcing noise-invariant representation by penalizing difference between clean and noisy data improves ASR model accuracy.

3 METHOD

3.1 SELF-SUPERVISED PERTURBATION-INVARIANT REPRESENTATION LEARNING (SPIRAL)

Figure 1 shows the diagram of SPIRAL in the pre-training stage, where we use two neural networks, a *student* F_θ and a *teacher* $F_{\theta'}$. The weights of the teacher θ' is the moving average of the weights of the student θ. At step t, the weights of the teacher θ'_t are updated as

$$\theta'_t \leftarrow \alpha_t \theta'_{t-1} + (1 - \alpha_t)\theta_t, \tag{1}$$

where α_t determines the rate of weight updates. We increase the value of α_t from 0.995 to 1.0 with a cosine schedule following Grill et al. (2020) during training. Given a speech utterance $\boldsymbol{X} = (\boldsymbol{x}_1, \ldots, \boldsymbol{x}_T)$ of length T, the student takes a perturbed version $\tilde{\boldsymbol{X}} = s(\boldsymbol{X}) = (\tilde{\boldsymbol{x}}_1, \ldots, \tilde{\boldsymbol{x}}_T)$ as input where $s(\cdot)$ is a perturbation function. The output of the student is a representation sequence $\boldsymbol{Z} = F(\tilde{\boldsymbol{X}}; \theta) = (\boldsymbol{z}_1, \ldots, \boldsymbol{z}_T)$. The teacher takes the same utterance without perturbation as input and output another representation sequence $\boldsymbol{Z}' = F(\boldsymbol{X}; \theta') = (\boldsymbol{z}'_1, \ldots, \boldsymbol{z}'_T)$. For each representation $\boldsymbol{z}_i \in \boldsymbol{Z}$, the student is trained to match the teacher's representation $\boldsymbol{z}'_i$ at the same position amongst k distracting samples. The distracting samples are randomly drawn from other positions of the same utterance in $\boldsymbol{Z}'$, which is found to be more effective than samples drawn from an entire batch of utterances (Baevski et al., 2020b). The in-utterance contrastive loss is defined following Sohn (2016); Wu et al. (2018) as,

$$\mathcal{L} = -\sum_{i=1}^{T} \log \frac{\exp(\phi(\boldsymbol{z}_i, \boldsymbol{z}'_i)/\kappa)}{\sum_{j \in D_i} \exp(\phi(\boldsymbol{z}_i, \boldsymbol{z}'_j)/\kappa)}, \tag{2}$$

where $\phi(\mathbf{a}, \mathbf{b}) = \mathbf{a}^T\mathbf{b}/\|\mathbf{a}\|\|\mathbf{b}\|$ is cosine similarity, D_i is the set of indices of distractors for the i-th position, and κ is the temperature parameter.

Figure 1: Illustration of SPIRAL architecture for speech pre-training.

However, applying in-utterance contrastive loss could cause a kind of representation collapse which we refer to as positional collapse. Contrastive candidates are sampled based on their positions in utterances. When a teacher's representation z_i' is correlated with its position i (e.g., correlation introduced by positional encoding in Transformer), the student could exploit this correlation to generate its representation z_i solely based on the position index i, while ignoring content of the input. In this case, the model does not learn meaningful representation of the input content. Therefore, we prevent positional collapse by randomizing positions of teacher's representation. In particular, we add random number of padding data at both ends of the input to the teacher to randomly shift the position information for each output representation z_i'. The student thereby is unable to exploit the spurious position information to minimize the contrastive loss. Note that when calculating the contrastive loss, we exclude the corresponding representation of the padded data.

3.2 Model architecture

Figure 2: The architecture of the student model in SPIRAL. The frame rate of input is denoted as '10/40/80 ms'. The dashed line indicates the optional predictor which can be removed with small performance degradation. The structure of the teacher model is the same but without the predictor.

As illustrated in Figure 2, student F_θ is composed of an encoder $f(\cdot)$, a projection head $g(\cdot)$ (Chen et al., 2020a) and an optional predictor $q(\cdot)$ (Grill et al., 2020), i.e., $F_\theta = (f \circ g \circ q)(\cdot; \theta)$. The teacher $F_{\theta'}$ has the same structure expect that it has no predicotr, $F_{\theta'} = (f \circ g)(\cdot; \theta')$. The encoder consists of two blocks. In each block, we first apply temporal convolutions to perform down-sampling, followed by Transformer (Vaswani et al., 2017) with convolutional relative position encoding (Baevski et al., 2020b). Each convolution is followed by layer normalization (LN) (Ba et al., 2016) and ReLU. For the projection head, we apply a simple linear layer. The predictor consists of two layers of temporal

convolution and a linear layer. The convolutions are followed by batch normalization (BN) (Ioffe & Szegedy, 2015) and ReLU.

During pre-training, we add computation noise to both the student and the teacher by applying dropout (Srivastava et al., 2014) and LayerDrop (Fan et al., 2020) in Transformer. We use the same dropout and LayerDrop rates for the student and the teacher.

3.3 ADAPTIVE SPECAUGMENT

We apply adaptive SpecAugment similar to Park et al. (2020a) as the primary perturbation method. Along either time or frequency dimension, we sample uniformly a certain proportion p of all time-steps to be start indices and mask the subsequent consecutive L time-steps. The masked time-steps is filled with zeros along frequency dimension. Along time dimension, we use Gaussian noise as masking values to avoid numerical problems for LN (Park et al., 2020a).

3.4 MULTI-CONDITION PRE-TRAINING

For noise-robust pre-training with SPIRAL, we perturb input of the student with various types of additive noise. We consider this technique as an implementation of multi-condition training (MCT) (Seltzer et al., 2013) in self-supervised setting. Specifically, for each input utterance to the student, we sample noise clips from a noise dataset, and mix the noise clips with the whole utterance by addition in time-domain. We first uniformly sample a signal-to-noise ratio (SNR) from a pre-defined range for each utterance. Then we scale the noise volume according to the required SNR. In our preliminary experiments, we found that applying additive noise alone as perturbation degrades performance. Therefore, we apply additive noise perturbation together with adaptive SpecAugment.

3.5 MODEL FINE-TUNING

After pre-training, we take the encoder from the student model in SPIRAL and add a randomly initialized convolutional classifier on top of it. The convolutional classifier is composed of two layers of convolution, followed by LN and ReLU, and a linear output projection. The convolution filters consist of 512 channels with kernel width of 5.

We fine-tune the model with connectionist temporal classification (CTC) (Graves et al., 2006) objective for speech recognition. We use 1024 sub-words as output units. The sub-words are generated from training transcripts of LibriSpeech with SentencePiece (Kudo & Richardson, 2018).

We further investigate SPIRAL's ability to learn high-level representation of speech during pre-training. In addition to whole-model fine-tuning, we apply frozen fine-tuning. We freeze the pre-trained parameters and only fine-tune the convolutional classifier which can only perform local classification due limited receptive field.

4 EXPERIMENTAL SETUP

4.1 DATA

For pre-training, we use the 960-hour training data (ignoring the labels) from LibriSpeech (Panayotov et al., 2015)(LS-960), or 60k-hour unlabeled audio data from Libri-Light (Kahn et al., 2020b) (LL-60K). For Libri-Light, we segment the data using official tools with a threshold of 16s, resulting in 46.9k hours of data. The two datasets are both derived from English audiobooks from LibriVox project[1]. For ASR fine-tuning, we apply 100-hour subset (train-clean-100) as low-resource labeled data and entire LS-960 with labels as high-resource labeled data, both from LibriSpeech.

For multi-condition pre-training, we use the noise dataset from Reddy et al. (2021). The dataset consists of 181 hours of noise data with about 150 noise types and 70,000 clips. We shuffle and split the noise data with a ratio of 8:1:1, which are used for training, synthesizing noisy dev-sets and synthesizing noisy test-sets respectively. The SNRs of speech mixtures are set from 0 to 30 dB. We also synthesize additional noisy test-sets at -10 to 0 dB as the mismatched noisy test sets.

---

[1] https://librivox.org/

Table 1: Detailed configurations of the SPIRAL BASE and LARGE models.

Modules	Conv.1	Transf.1	Conv.2	Transf.2	Proj. H.	Predictor	#Params
Hyper-parameters	kernel size channel stride	layer emb. dim. ffn dim. layerdrop attn. heads	kernel size channel stride	layer emb. dim. ffn dim. layerdrop attn. heads	dim.	kernel size channel	
BASE model	5,5,1 384,512,512 2,2,1	2 512 2048 0 8	5,1 1536,768 2,1	10 768 3072 0.05 12	256	5,5,1 256,256,256	91.5M
LARGE model	5,5,1 384,512,512 2,2,1	4 512 2048 0.05 8	5,1 2048,1024 2,1	20 1024 4096 0.05 16	512	5,5,1 512,512,512	287M

Table 2: Comparison of pre-training cost between wav2vec 2.0 and SPIRAL.

Model	Unlabeled data	Training steps	GPU days	Mixed precision
Wav2vec 2.0 BASE (Baevski et al., 2020b)	LS-960	500k	102.4	✓
SPIRAL BASE	LS-960	200k	20.8	-
Wav2vec 2.0 LARGE (Baevski et al., 2020b)	LL-60k	1000k	665.6	✓
SPIRAL LARGE	LL-60k	500k	232.0	-

4.2 TRAINING SETUPS

We apply 128-dimensional log-mel filterbank extracted with 20 ms window and 10 ms stride as the input acoustic feature.

We experiment with BASE model and LARGE model configurations as shown in Table 1. The numbers of parameters are comparable to wav2vec 2.0 BASE and LARGE models correspondingly.

For SpecAugment, we set $p = 0.025$ and $L = 20$ for time-dimension mask, and $p = 0.02$ and $L = 20$ for frequency-dimension mask.

In pre-training, we optimize with Adam (Kingma & Ba, 2015) optimizer, warming up the learning rate for the first 8% of updates to a peak of 3e-3. Then the learning rate decays to 0 with a cosine schedule. We train the BASE model with batch size of 24 per GPU for 200k steps on 16 V100 GPUs, which takes about 1.3 days. For the LARGE model, we train with batch size of 20 per GPU for 500k steps on 32 V100 GPUs, which takes about 7.25 days. As shown in Table 2, there is a significant reduction of training cost (GPU days) compared to wav2vec 2.0 (Baevski et al., 2020b). SPIRAL requires 80% and 65% less training cost for BASE and LARGE respectively. Note that mix-precision training is not applied for SPIRAL yet.

For fine-tuning, we optimize with Adam and a tri-state rate schedule where the learning rate is warmed up for the first 10% of updates to 3e-5, held constant for the next 40% and then linearly decayed to zero following Baevski et al. (2020b). We fine-tune BASE and LARGE with batch size of 14 and 18 per GPU respectively on 8 GPUs for 80k steps on train-clean-100. We fine-tune LARGE with batch size of 10 per GPU on 16 GPUs for 320k steps on LS-960. We apply SpecAugment for whole-model fine-tuning but not for frozen fine-tuning.

For multi-condition pre-training and fine-tuning, we randomly perturb each utterance with additive noise with 50% probability before applying SpecAugment. The SNR is uniformly sampled from 0-30 db.

Table 3: ASR Results fine-tuned from low-resource train-clean-100. Language models used in decoding are listed in LM. We compare SPIRAL BASE pre-trained on LS-960 and SPIRAL LARGE pre-trained on LL-60k with previous methods. We report word error rate (WER) (%) on Librispeech dev/test sets.

Model	Unlabeled data	LM	dev		test	
			clean	other	clean	other
Supervised/Semi-Supervised						
Hybrid DNN/HMM (Lüscher et al., 2019)	-	4-gram	5.0	19.5	5.8	18.6
Iter. pseudo-labeling (Xu et al., 2020)	LL-60k	4-gram+Transf.	3.19	6.14	3.72	7.11
Noisy student (Park et al., 2020b)	LS-860	LSTM	3.9	8.8	4.2	8.6
Self-supervised						
wav2vec 2.0 BASE (Baevski et al., 2020b)	LS-960	-	6.1	13.5	6.1	13.3
SPIRAL BASE frozen (ours)	LS-960	-	8.0	11.7	7.9	13.3
SPIRAL BASE (ours)	LS-960	-	6.2	11.7	6.0	11.9
wav2vec 2.0 BASE (Baevski et al., 2020b)	LS-960	Transf.	2.2	6.3	2.6	6.3
SPIRAL BASE (ours)	LS-960	Transf.	2.9	6.8	3.3	6.9
wav2vec 2.0 LARGE (Baevski et al., 2020b)	LL-60k	-	3.3	6.5	3.1	6.3
SPIRAL LARGE frozen (ours)	LL-60k	-	7.1	9.9	6.9	10.4
SPIRAL LARGE (ours)	LL-60k	-	3.7	6.5	3.6	6.7
wav2vec 2.0 LARGE (Baevski et al., 2020b)	LL-60k	Transf.	1.9	4.0	2.0	4.0
SPIRAL LARGE (ours)	LL-60k	Transf.	1.9	4.2	2.3	4.1

4.3 LANGUAGE MODEL AND DECODING

We use a word-level Transformer LM (Baevski & Auli, 2018) trained on the Librispeech LM corpus which is identical to Synnaeve et al. (2020b). We perform grid search for decoding parameters and choose the best parameters according to performance on dev-other with beam 50. The final test performance is measured with beam 500. We use the beam search decoder of Pratap et al. (2019).

5 RESULTS

5.1 EVALUATION UNDER LOW-RESOURCE AND HIGH-RESOURCE LABELED DATA SETTINGS

We first evaluate our method under a low-resource ASR setting in which we fine-tune the models with 100-hour LibriSpeech data (train-clean-100). The results are shown in Table 3. We evaluate a BASE model pre-trained with 960-hour LibriSpeech (LS-960) and a LARGE model pre-trained with Libri-Light (LL-60K). The frozen BASE model performs well, achieving a WER of 13.3% on test-other, which is on par with wav2vec 2.0 BASE. This suggests that SPIRAL indeed learns meaningful high-level representations in a self-supervised way. When we fine-tune the whole BASE model, the model achieves WER of 6.0% and 11.9% on test-clean and test-other respectively, out-performing wav2vec 2.0 BASE on test-other with 10.5% relative WER reduction. When decoding with a Transformer LM, the BASE model achieves WER of 3.3% and 6.9% on the-clean and test-other, we observe the improvements of decoding with LM is smaller compared to Wav2vec 2.0 BASE. This is presumably because our LM decoding parameters have not been fully tuned yet. The SPIRAL LARGE model consists of more parameters and is pre-trained with more data. The model with a transformer LM achieves WER of 2.3% and 4.1% on test-clean and test-other respectively. The significant improvement of LARGE over BASE demonstrates the scalability of SPIRAL. The results of SPIRAL LARGE are competitive to wav2vec 2.0 LARGE. This is encouraging, as SPIRAL LARGE only takes 35% of training cost of wav2vec 2.0 LARGE.

We further evaluate SPIRAL LARGE pre-trained with Libri-Light (LL-60K) under a high-resource ASR setting with 960-hour LS-960 as fine-tuning data. As shown in Table 4, the LARGE model with a Transformer LM achieves WER of 1.7% and 3.2% on test-clean and test-other respectively, surpassing the wav2vec 2.0 LARGE model. We note that the supervised models and the noisy student model(Park et al., 2020b) in Table 4 are autoregressive models, while our models is fine-tuned with

Table 4: ASR results fine-tuned from high-resource LS-960. Language models used in decoding are listed in LM. We compare SPIRAL LARGE pre-trained on Libri-Light (LL-60k) with previous methods. We report WER (%) on the Librispeech dev/test sets.

Model	Unlabeled data	LM	dev		test	
			clean	other	clean	other
Supervised						
ContextNet (Han et al., 2020a)	-	LSTM	1.9	3.9	1.9	4.1
Conformer (Gulati et al., 2020)	-	LSTM	2.1	4.3	1.9	3.9
Semi-supervised						
CTC Transf. + PL (Synnaeve et al., 2020a)	LL-60k	CLM+Transf.	2.10	4.79	2.33	4.54
S2S Transf. + PL (Synnaeve et al., 2020a)	LL-60k	CLM+Transf.	2.00	3.65	2.09	4.11
Iter. pseudo-labeling Xu et al. (2020)	LL-60k	4-gram+Transf.	1.85	3.26	2.10	4.01
Noisy student (Park et al., 2020b)	LL-60k	LSTM	1.6	3.4	1.7	3.4
Self-supervised						
wav2vec 2.0 LARGE (Baevski et al., 2020b)	LL-60k	-	2.1	4.5	2.2	4.5
SPIRAL LARGE frozen (ours)	LL-60k	-	4.6	7.1	4.4	7.4
SPIRAL LARGE (ours)	LL-60k	-	2.2	4.8	2.4	4.9
wav2vec 2.0 LARGE (Baevski et al., 2020b)	LL-60k	Transf.	1.6	3.0	1.8	3.3
SPIRAL LARGE (ours)	LL-60k	Transf.	1.4	3.2	1.7	3.2

Table 5: Evaluation on noise-robustness of the models. We use wav2vec 2.0 BASE released by the authors as the baseline. The SPIRAL BASE models are pre-trained with LS-960 and fine-tuned with train-clean-100. We report WER (%) on Librispeech synthetic noisy test sets at different noise level and the original test sets.

BASE model	Pre-train w/ MCT	Fine-tune w/ MCT	SNR 0-30 dB		SNR -10-0 dB		Original	
			clean	other	clean	other	clean	other
wav2vec 2.0	-	-	14.4	27.4	67.7	78.3	6.1	13.3
SPIRAL	-	-	13.1	24.3	61.2	71.4	6.0	11.9
SPIRAL	-	✓	8.64	17.7	35.5	51.4	6.4	12.0
SPIRAL	✓	-	8.0	16.1	28.2	44.0	6.3	12.0
SPIRAL	✓	✓	8.0	15.8	26.1	41.4	6.6	12.1

CTC objective which is non-autoregressive and generally inferior to autoregressive models. We use CTC objective for its simplicity and comparability to previous speech pre-training methods.

We consider SPIRAL as a preferred alternative to wav2vec 2.0 given that SPIRAL only requires 20%−35% computation cost of wav2vec 2.0. We expect further efficiency improvement when we implement mix-precision training for SPIRAL. Moreover, we have not thoroughly tuned hyper-parameters of LARGE model and LM decoding due to limited computation resource.

5.2 NOISE-ROBUST PRE-TRAINING

To evaluate noise-robustness of the pre-trained models, we compare the effects of applying multi-condition training (MCT) in pre-training or fine-tuning stages of SPIRAL. The results are shown in Table 5. The vanilla SPIRAL BASE model and wav2vec 2.0 BASE model deteriorate with significantly higher WER on synthetic noisy test data. SPIRAL pre-trained with MCT (and fine-tuned with clean data) is more effective than applying MCT solely in fine-tuning. We observe 7.4% and 9.0% relative WER reduction on synthetic noisy test-clean and test-other sets respectively. When performing MCT for both pre-training and fine-tuning, the further improvement is rather limited on the synthetic noisy datasets matching the SNR range of the training data (0-30 dB). The results suggest that noise-robustness achieved in SPIRAL pre-training is effectively transferred to the downstream ASR tasks. Nevertheless, fine-tuning with MCT is still helpful when we test on different noise level from the training data. We observe more significant improvement at the mismatched SNR range (-10-0 dB), with 7.4% and 6% for relative WER reduction for test-clean and test-other respectively.

Table 6: Ablation studies of input perturbation with SpecAugment and computation noise on teacher. We list the mask ratio and mask length as p, L for time and frequency masks. The first row is the default setting of SPIRAL. We apply SPIRAL BASE fine-tuned with train-clean-100, and report WER (%) on the Librispeech dev-other set.

Time mask	Frequency mask	Computation noise	dev other
-	-	✓	11.7
-	-	-	13.9
0.025, 20	0.02, 20	✓	53.1
0.0125, 20	0.01, 20	✓	47.0
0.025, 10	0.02, 10	✓	42.8

Table 7: Ablation studies of predictor and projection head in SPIRAL. We apply SPIRAL BASE fine-tuned with train-clean-100, and report WER (%) on the Librispeech dev-other set.

Architecture	dev other
baseline	11.7
+ predictor use LN	12.3
+ conv proj. head	12.3
− predictor	14.6
+ conv proj. head	12.2

5.3 ABLATIONS

5.3.1 INPUT PERTURBATION AND COMPUTATION NOISE OF TEACHER

SPIRAL learns denoised representation of perturbed data. By default, we only apply perturbation to the input of the student. An alternative method is to perturb both inputs of the teacher and the student, and optimize consistency between their representations (Grill et al., 2020; Chen & He, 2021). We conduct experiments to evaluate the effects of perturbing the input and adding computation noise (dropout and LayerDrop) to the teacher. The results are shown in Table 6. The results suggest that applying SpecAugment to teacher's input degrades performance significantly. Performance degradation decreases but is still significant with lower ratio and width of the masks. This supports the necessity of representation denoising, and our view of SPIRAL as an extension of self-training in which teacher network are fed with clean input. The results also support applying computation noise to teacher during pre-training. There is a 16% relative WER reduction with computation noise. This may be linked to Gal & Ghahramani (2016).

5.3.2 EFFECTS OF PREDICTOR AND PROJECTION HEAD

We do ablation studies to understand the role of predictor and projection head in SPIRAL. The results are shown in Table 7. When removing the predictor from the student, we observe performance degradation, but representation collapse does not happen. In the architectures relying on predictor to prevent collapse (Grill et al., 2020; Chen & He, 2021), applying batch normalization (BN) in the predictor is essential. While in SPIRAL, we observe that BN in the predictor can be replaced by layer normalization (LN) with a smaller performance improvement. When the predictor is removed, We observe performance improvement by applying a convolutional projection head. The convolutional projection head is composed of a temporal convolution layer with LN and ReLU, and a linear layer. But applying convolutional projection head to the model with a predictor, there is no further performance improvement. This suggests that convolutional projection head and predictor play a similar role in SPIRAL, and they are not complementary.

6 CONCLUSION

We presented SPIRAL, a new approach to speech pre-training by learning representation denoising of perturbed data with a teacher-student framework. SPIRAL can learn high-level speech representation in self-supervised way. Training a small convolutional classifier on frozen representation of SPIRAL achieves WER of 4.4% and 7.4% on Librispeech test-clean and test-other respectively. We show that SPIRAL achieves competitive or better results compared to state-of-the-art speech pre-training methods, with significant reduction of training cost. We investigate multi-condition pre-training and demonstrates that multi-condition pre-training is more effective than solely applying multi-condition training in the fine-tuning stage. We presume SPIRAL to be a general pre-training framework, which can apply to other modalities such as images and text. We will explore this possibility in our future work.

REFERENCES

Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization, 2016. arXiv:1607.06450.

Alexei Baevski and Michael Auli. Adaptive input representations for neural language modeling. In *Proc. of ICLR*, 2018.

Alexei Baevski, Michael Auli, and Abdelrahman Mohamed. Effectiveness of self-supervised pre-training for speech recognition, 2019. arXiv:1911.03912.

Alexei Baevski, Steffen Schneider, and Michael Auli. vq-wav2vec: Self-supervised learning of discrete speech representations. In *8th International Conference on Learning Representations ICLR 2020*, 2020a.

Alexei Baevski, Yuhao Zhou, Abdelrahman Mohamed, and Michael Auli. wav2vec 2.0: A framework for self-supervised learning of speech representations. In *Advances in Neural Information Processing Systems*, volume 33, 2020b.

Ting Chen, Simon Kornblith, Mohammad Norouzi, and Geoffrey Hinton. A simple framework for contrastive learning of visual representations. In *Proceedings of the 37th International Conference on Machine Learning (ICML)*, pp. 1597–1607, 2020a.

Xinlei Chen and Kaiming He. Exploring simple Siamese representation learning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 15750–15758, 2021.

Yang Chen, Weiran Wang, and Chao Wang. Semi-supervised ASR by end-to-end self-training. In *Proc. Interspeech 2020*, pp. 2787–2791, 2020b.

S. Chopra, R. Hadsell, and Y. LeCun. Learning a similarity metric discriminatively, with application to face verification. In *2005 IEEE Computer Society Conference on Computer Vision and Pattern Recognition (CVPR'05)*, pp. 539–546, 2005.

Yu-An Chung and James Glass. Generative pre-training for speech with autoregressive predictive coding. In *2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 3497–3501, 2020.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. BERT: pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, NAACL-HLT 2019*, pp. 4171–4186, 2019.

Angela Fan, Edouard Grave, and Armand Joulin. Reducing transformer depth on demand with structured dropout. In *8th International Conference on Learning Representations ICLR 2020*, 2020.

Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. In *Proceedings of The 33rd International Conference on Machine Learning (ICML)*, pp. 1050–1059, 2016.

Daniel Galvez, Greg Diamos, Juan Manuel Ciro Torres, Keith Achorn, Anjali Gopi, David Kanter, Max Lam, Mark Mazumder, and Vijay Janapa Reddi. The People's Speech: A large-scale diverse english speech recognition dataset for commercial usage. In *Thirty-fifth Conference on Neural Information Processing Systems Datasets and Benchmarks Track (Round 1)*, 2021.

Alex Graves, Santiago Fernández, Faustino Gomez, and Jürgen Schmidhuber. Connectionist temporal classification: Labelling unsegmented sequence data with recurrent neural networks. In *Proceedings of the 23rd International Conference on Machine Learning (ICML)*, pp. 369–376, 2006.

Jean-Bastien Grill, Florian Strub, Florent Altché, Corentin Tallec, Pierre Richemond, Elena Buchatskaya, Carl Doersch, Bernardo Avila Pires, Zhaohan Guo, Mohammad Gheshlaghi Azar, Bilal Piot, koray kavukcuoglu, Remi Munos, and Michal Valko. Bootstrap your own latent - a new approach to self-supervised learning. In *Advances in Neural Information Processing Systems*, volume 33, pp. 21271–21284, 2020.

Anmol Gulati, James Qin, Chung-Cheng Chiu, Niki Parmar, Yu Zhang, Jiahui Yu, Wei Han, Shibo Wang, Zhengdong Zhang, Yonghui Wu, and Ruoming Pang. Conformer: Convolution-augmented transformer for speech recognition. In *Proc. Interspeech 2020*, pp. 5036–5040, 2020.

Wei Han, Zhengdong Zhang, Yu Zhang, Jiahui Yu, Chung-Cheng Chiu, James Qin, Anmol Gulati, Ruoming Pang, and Yonghui Wu. ContextNet: Improving convolutional neural networks for automatic speech recognition with global context. In *Proc. Interspeech 2020*, pp. 3610–3614, 2020a.

Wei Han, Zhengdong Zhang, Yu Zhang, Jiahui Yu, Chung-Cheng Chiu, James Qin, Anmol Gulati, Ruoming Pang, and Yonghui Wu. ContextNet: Improving convolutional neural networks for automatic speech recognition with global context. In *Proc. Interspeech 2020*, pp. 3610–3614, 2020b.

Wei-Ning Hsu, Yao-Hung Hubert Tsai, Benjamin Bolte, Ruslan Salakhutdinov, and Abdelrahman Mohamed. Hubert: How much can a bad teacher benefit ASR pre-training? In *2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6533–6537, 2021.

Wenyong Huang, Wenchao Hu, Yu Ting Yeung, and Xiao Chen. Conv-Transformer Transducer: Low Latency, Low Frame Rate, Streamable End-to-End Speech Recognition. In *Proc. Interspeech 2020*, pp. 5001–5005, 2020.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *Proceedings of the 32nd International Conference on Machine Learning (ICML)*, pp. 448–456, 2015.

Herve Jégou, Matthijs Douze, and Cordelia Schmid. Product quantization for nearest neighbor search. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, 33(1):117–128, 2011.

Jacob Kahn, Ann Lee, and Awni Hannun. Self-training for end-to-end speech recognition. In *2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 7084–7088, 2020a.

Jacob Kahn, Morgane Rivière, Weiyi Zheng, Evgeny Kharitonov, Qiantong Xu, Pierre-Emmanuel Mazaré, Julien Karadayi, Vitaliy Liptchinsky, Ronan Collobert, Christian Fuegen, et al. Librilight: A benchmark for ASR with limited or no supervision. In *2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 7669–7673, 2020b.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *3rd International Conference on Learning Representations, ICLR 2015*, 2015.

Tom Ko, Vijayaditya Peddinti, Daniel Povey, and Sanjeev Khudanpur. Audio augmentation for speech recognition. In *Proc. Interspeech 2015*, pp. 3586–3589, 2015.

Taku Kudo and John Richardson. SentencePiece: A simple and language independent subword tokenizer and detokenizer for neural text processing. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, 2018.

Davis Liang, Zhiheng Huang, and Zachary C Lipton. Learning noise-invariant representations for robust speech recognition. In *2018 IEEE Spoken Language Technology Workshop (SLT)*, pp. 56–63, 2018.

Andy T. Liu, Shu-wen Yang, Po-Han Chi, Po-chun Hsu, and Hung-yi Lee. Mockingjay: Unsupervised speech representation learning with deep bidirectional transformer encoders. In *2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6419–6423, 2020.

Christoph Lüscher, Eugen Beck, Kazuki Irie, Markus Kitza, Wilfried Michel, Albert Zeyer, Ralf Schlüter, and Hermann Ney. RWTH ASR Systems for LibriSpeech: Hybrid vs Attention. In *Proc. Interspeech 2019*, pp. 231–235, 2019.

Vimal Manohar, Daniel Povey, and Sanjeev Khudanpur. Semi-supervised maximum mutual information training of deep neural network acoustic models. In *Proc. Interspeech 2015*, pp. 2630–2634, 2015.

Vassil Panayotov, Guoguo Chen, Daniel Povey, and Sanjeev Khudanpur. Librispeech: An ASR corpus based on public domain audio books. In *2015 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pp. 5206–5210. IEEE, 2015.

Daniel S. Park, Yu Zhang, Chung-Cheng Chiu, Youzheng Chen, Bo Li, William Chan, Quoc V. Le, and Yonghui Wu. Specaugment on large scale datasets. In *2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6879–6883, 2020a.

Daniel S. Park, Yu Zhang, Ye Jia, Wei Han, Chung-Cheng Chiu, Bo Li, Yonghui Wu, and Quoc V. Le. Improved noisy student training for automatic speech recognition. In *Proc. Interspeech 2020*, pp. 2817–2821, 2020b.

Vijayaditya Peddinti, Yiming Wang, Daniel Povey, and Sanjeev Khudanpur. Low latency acoustic modeling using temporal convolution and LSTMs. *IEEE Signal Processing Letters*, 25(3):373–377, 2018.

Vineel Pratap, Awni Hannun, Qiantong Xu, Jeff Cai, Jacob Kahn, Gabriel Synnaeve, Vitaliy Liptchinsky, and Ronan Collobert. Wav2Letter++: A fast open-source speech recognition system. In *ICASSP 2019 - 2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6460–6464, 2019.

Chandan KA Reddy, Harishchandra Dubey, Vishak Gopal, Ross Cutler, Sebastian Braun, Hannes Gamper, Robert Aichner, and Sriram Srinivasan. ICASSP 2021 deep noise suppression challenge. In *2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6623–6627. IEEE, 2021.

Michael L. Seltzer, Dong Yu, and Yongqiang Wang. An investigation of deep neural networks for noise robust speech recognition. In *2013 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 7398–7402, 2013.

Kihyuk Sohn. Improved deep metric learning with multi-class N-pair loss objective. In *Advances in Neural Information Processing Systems*, volume 29, 2016.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Gabriel Synnaeve, Qiantong Xu, Jacob Kahn, Tatiana Likhomanenko, Edouard Grave, Vineel Pratap, Anuroop Sriram, Vitaliy Liptchinsky, and Ronan Collobert. End-to-end ASR: from supervised to semi-supervised learning with modern architectures. In *workshop on Self-supervision in Audio and Speech (SAS), 37th International Conference on Machine Learning (ICML 2020)*, 2020a.

Gabriel Synnaeve, Qiantong Xu, Jacob Kahn, Tatiana Likhomanenko, Edouard Grave, Vineel Pratap, Anuroop Sriram, Vitaliy Liptchinsky, and Ronan Collobert. End-to-end ASR: from supervised to semi-supervised learning with modern architectures. In *workshop on Self-supervision in Audio and Speech (SAS), 37th International Conference on Machine Learning (ICML 2020)*, 2020b.

Antti Tarvainen and Harri Valpola. Mean teachers are better role models: Weight-averaged consistency targets improve semi-supervised deep learning results. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Yuandong Tian, Xinlei Chen, and Surya Ganguli. Understanding self-supervised learning dynamics without contrastive pairs. In *Proceedings of the 38th International Conference on Machine Learning (ICML)*, pp. 10268–10278, 2021.

Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding, 2019. arXiv:1807.03748v2.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Ł ukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in Neural Information Processing Systems*, volume 30, 2017.

Pascal Vincent, Hugo Larochelle, Yoshua Bengio, and Pierre-Antoine Manzagol. Extracting and composing robust features with denoising autoencoders. In *Proceedings of the 25th International Conference on Machine Learning (ICML)*, pp. 1096–1103, 2008.

Weiran Wang, Qingming Tang, and Karen Livescu. Unsupervised pre-training of bidirectional speech encoders via masked reconstruction. In *2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 6889–6893, 2020.

Zhirong Wu, Yuanjun Xiong, Stella X Yu, and Dahua Lin. Unsupervised feature learning via non-parametric instance discrimination. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 3733–3742, 2018.

Qizhe Xie, Minh-Thang Luong, Eduard Hovy, and Quoc V. Le. Self-training with noisy student improves imagenet classification. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2020.

Qiantong Xu, Tatiana Likhomanenko, Jacob Kahn, Awni Hannun, Gabriel Synnaeve, and Ronan Collobert. Iterative pseudo-labeling for speech recognition. In *Proc. Interspeech 2020*, pp. 1006–1010, 2020.

Qiantong Xu, Alexei Baevski, Tatiana Likhomanenko, Paden Tomasello, Alexis Conneau, Ronan Collobert, Gabriel Synnaeve, and Michael Auli. Self-training and pre-training are complementary for speech recognition. In *2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 3030–3034, 2021.

Yu Zhang, James Qin, Daniel S. Park, Wei Han, Chung-Cheng Chiu, Ruoming Pang, Quoc V. Le, and Yonghui Wu. Pushing the limits of semi-supervised learning for automatic speech recognition. In *NeurIPS 2020 workshop: Self-Supervised Learning for Speech and Audio Processing*, 2020.