DIVIDE-AND-CLUSTER: SPATIAL DECOMPOSITION BASED HIERARCHICAL CLUSTERING

ABSTRACT

This paper is about increasing the computational efficiency of clustering algorithms. Many clustering algorithms are based on properties of relative locations of points, globally or locally, e.g., interpoint distances and nearest neighbor distances. This amounts to using a lower dimensional space than the full dimensionality D of the space in which the points are embedded. We present a clustering algorithm, Divide-and-Cluster (DAC), which detects local clusters in small neighborhoods obtained by recursive tessellation of space, and then merges them hierarchically, following the Divide-and-Conquer paradigm. This significantly reduces computation time which may otherwise grow nonlinearly number n of points. We define locality as hypercubical neighborhoods in a recursive hypercubical decomposition of space, represented by a tree. Clusters are detected within each hypercube, and merged with those from neighboring hypercubes while traversing up the tree. We expect DAC to perform better than many other algorithms because (a) as clusters merge into larger clusters (components), their number steadily decreases vs the number of points, and (b) we cluster only neighboring components. The ordering of component appearances also simultaneously yields a cluster hierarchy (tree). Further, our use of small neighborhoods allows piecewise uniform approximation of large, nonuniform, arbitrary shaped clusters, thus avoiding the need for global cluster models. We experimentally verify the correctness of detected clusters on a variety of datasets, posing a variety of challenges, as well as show that DAC's runtime is significantly better than representative algorithms of other types, particularly for increasing values of n.

1 INTRODUCTION

Finding clusters formed by n data points in a D-dimensional space is a very frequent operation in machine learning, even more so in unsupervised learning. This paper is about increasing the computational efficiency of clustering. The notion of cluster is fundamentally a perceptual one; its precise definition, used implicitly or explicitly by clustering algorithms, varies. Given a set of n points $x_1, x_2, ..., x_n$ in a D-dimensional space ($x_i \in R^D$), clustering is aimed at identifying different groupings/components of nearby points according to the definition of cluster being used. In this paper, we model a cluster as a contiguous overlapping set of small neighborhoods such that: points in each neighborhood are distributed (nearly) uniformly, the cluster shape is arbitrary, and at their closest approach any two clusters are separated by a distance larger than the distance between nearby within-cluster neighbors. A large number of common clustering algorithms are based on global properties of point positions, such as distances between points or sets of points, as in K-means Another class of algorithms attempts to involve the local structure, defining locality via edge-connectivity in different types of graphs, than D. Other algorithms use nearby points, e.g., located within an arbitrary size neighborhood. There are a few approaches that make use of full use of the D-dimensional geometry, e.g., those based on Voronoi neighborhoods (Ahuja & Tuceryan, 1989); while they work well, their constituent algorithms (e.g., for Voronoi tessellation) are available for only small values of D.

In this paper, we present a clustering algorithm that detects clusters in small local neighborhoods across the D-space and then repeatedly grows them outwards, by combining nearby ones appro-

priately into clusters of larger sizes/numbers. The spatial decomposition into small neighborhoods followed by recursive merging of clusters in nearby neighborhoods implements the Divide-and-Conquer paradigm of computation. We define locality as hypercubical neighborhoods in a recursive hypercubical tessellation of the underlying D-space, represented by a tree. Clusters detected within each neighboring hypercubes/nodes at one level are combined and belong to the parent node at the next level, in a bottom up tree traversal. Once the recursive merger is completed at the tree root level, the set of detected clusters are agglomeratively merged to form a cluster hierarchy with nearest clusters merging first. Due to this approach of first progressively dividing the space and then recursively merging the clusters detected in them, we call our algorithm Divide-and-Cluster, or DAC.

We evaluate our algorithm against other algorithms in two ways. (1) Correctness of Detected Clusters: We compare detected clusters in the standard, Fundamental Clustering Problems Suite of 2D and 3D datasets (FCPS), which poses a variety of important clustering challenges. (2) Runtimes: We compare runtimes on datasets having a wide range of n values. (3) Downstream Task: We observe the impact of using DAC as a substitute in a downstream task.

The advantages and contributions of the proposed algorithm are as follows:

1. Our approach recursively divides the space in which the points are embedded, thus dividing the datapoints and therefore the size of the clustering problem. We thus get the advantage of the divide-and-conquer paradigm, namely, logarithmic increase with E. In contrast, many common algorithms process all the points globally, exhibiting at best linear, and many times quadratic, increase in runtime with n.

2. DAC's time complexity over global (e.g., points based) algorithms improves further as, instead of only points, DAC uses relationships between local clusters (components) of points; this significantly cuts down computation because (a) the components are much fewer than points, (b) DAC limits clustering to only neighboring components, (c) DAC further limits computation of separation between neighboring clusters to mutually visible parts of their boundaries.

3. DAC's highly local cluster detection avoids the use of global models of point distributions (e.g., density variation) within clusters. By making decomposition arbitrarily local through repeated division of space, DAC can increasingly improve piecewise uniform approximation of larege nonuniform clusters.

4. Detection of contiguous small pieces of a cluster also allows detection of clusters of arbitrary shapes, thus avoiding models such as shape compactness used by K-means.

In the following, we first review related work (Sec 2), followed by spatial decomposition (tree representation) used to define DAC (Sec 3), DAC algorithm (Sec 4), computational complexity (Sec 5), experimental results (Sec 6), and limitations and conclusions (Sec 7).

2 RELATED WORK

Clustering obtains a partition of the points that minimizes a cost function chosen to reflect the types of clusters to be detected, often along with some user specified parameters. An example of a cost function is the Sum of Squared Error (SSE), the sum of the squares of distances of points from their cluster centers.

Hierarchical clustering approaches derive a tree (hierarchy) of clusters in which clusters at each level correspond to a local minimum of the cost function with a level-specific value. Each cluster at a level splits into multiple sub-clusters at the level immediately below, where the sub-clusters are more compact than the parent clusters, corresponding to stronger local minima of the objective function. Hierarchical clustering can be top-down (recursively split clusters) or bottom-up (recursively combine clusters). Following are some broad categories of algorithms:

Graph-based clustering algorithms: This class of algorithms typically use a partitioning strategy on graph of data points with weighted edges. Examples are Minimal Spanning Tree (MST) and Shared Nearest Neighbor (SNN) clustering algorithms. MST defines edge weight as distance between two points and removes $k - 1$ highest weighted edges from the MST of the graph to obtain k clusters, where k is a parameter. SNN defined similarity of two points as threshold overlap in nearest

neighbors (where k' nearest neighbors are found for each point), similar vertices are connected, and connected components are discovered to return the clusters.

Spectral approaches aim to partition a graph such that similar points are together and dissimilar are not. It defines a similarity matrix that contains similarity score for each pair of point, and uses this matrix to find the graph cut with minimum cost.

Density-based clustering algorithms: Density based methods start with some core clusters (e.g., individual points) and gradually grow each cluster by including proximal points until a growth criterion allows. Examples include DBSCAN (Ester et al., 1996), OPTICS (Ankerst et al., 1999) and Mean shift based (Cheng, 1995) clustering. DBSCAN defines a core cluster as consisting of those points that have more than minpoints points in their $\in$-neighbourhoods. Each core cluster grows by including all points lying in $\in$-neighbourhoods of its current points, and repeating this process until no growth is possible. The process then repeats from a new unclustered point until all data points are clustered.

Mesh-based clustering algorithms: Mesh based clustering algorithms quantise the data space into small units (mesh cells) and aggregate all points within one mesh cell into one indivisible unit which may contain multiple data points. This may be interpreted as working on a coarse resolution, where the algorithm is unable to distinguish between points in the same mesh cell. Then, all computation is performed on the mesh cells rather than the data points. The time complexity of the operations then is a function of the number of mesh cells, not the number of data points. This presents a trade-off between the cluster quality (coarser meshes would produce poorer clustering) and the time required to compute the clusters (proportional to number of mesh cells). Some examples are STING (Wang et al., 1997), CLIQUE (Agrawal et al., 2005) and WaveCluster (Sheikholeslami et al., 1998).

3 TREE REPRESENTATION

For concreteness, we first discuss the case of $D = 3$, the octree representation (Shi & Malik, 2000), (Jackins & Tanimoto, 1980), (Meagher, 1982), (Zahn, 1971), (VanderPlas, 2016), (Liao et al., 2004) of the occupancy of space by non-point objects, obtained using recursive decomposition of the space into octants. Given an object, we start with the entire space as a single (starting) cube (block). At any stage, if a block under consideration is completely contained within the object it is left alone; otherwise, it is divided into its eight octants which are added to a pool of blocks to be processed; this procedure is repeated for each unprocessed block until the pool is empty (all blocks are either completely within or completely outside the object, or they are of the smallest, specified (precision/resolution level) mesh cell size.

This recursive subdivision yields an octree description of the occupancy of 3D space. Each block corresponds to a node in the tree. The root (level 0) of the octree represents the largest size block, representing the limit of object size that can be represented. Successive levels represent blocks whose side lengths halve with each lower level, as does the separation between adjacent blocks. We denote the side length of the smallest block, the mesh cell, by unity. The maximum number of levels L then is $\log_2 E$. An octree may also have fewer than L levels if all object blocks turn out to be of side lengths larger than unity; the nodes corresponding to these larger blocks form octree's leaves and may occur at any of the L levels. We label a leaf node black/white if its block is completely contained within the object/free space. If a node is neither black nor white, then it is labelled gray, meaning it has both black and white descendants. Black nodes not contained inside other black nodes are termed 'maximal' black nodes.

To generalize to the case of points in the D-dimensional space, we recursively divide the space using D-dimensional hypercubes. For the hypervolume $[0, E]^D$ each dimension 'x' is split into two halves by the half plane $x = E/2$. This partitions each D-dimensional block into 2^D children hypercubes, each of half the edge length, and $1/2^D$ times the volume, of the parent block, yielding a hypertree of order 2^D.

To associate a child node's id with one of its 2^D possible positions $r_i(r_i = 0, 1, 2, \cdots, 2^D - 1)$, we use the binary representation of (r_i) itself as the node's id. We associate the lower/higher half (coordinate) child in each dimension with 0/1 bit in the binary representation. This maps all the 2^D children to unique positions inside the parent (See Fig 1).

Figure 1: The figure shows how the child's position is used to determine its number. For example, the bottom right child gets the binary position 10, as it is located at the higher coordinate along the x-axis and the lower coordinate along the y-axis.

Figure 2: (Left) The mesh cells in red constitute mutually visible boundary between blue and green nodes. Only these cells are involved in computing distance between the two nodes. The yellow node has holes that expose mesh cells in the center of green node to the green visible boundary. (Right) Cells with the same color represent mesh cells belonging to the same maximal black node. All maximal black nodes are unit distance apart and are therefore merged into a single component.

4 ALGORITHM

4.1 INSERTION OF POINTS INTO THE HYPERTREE

The first step is to associate each data point with the smallest block (mesh cell or unit side length) or leaf nodes of the hypertree. Points are inserted in a top-down traversal of the tree to the leaves. Clearly, storing all the 2^D children of all non-leaf nodes is infeasible for large D. Therefore, we explicitly store only black grey child nodes for each node as our algorithm only requires these child nodes for each node. In practice this can be achieved using a Linked List of non-white child nodes, or a Hash Map of (key, value) pair with $r \in \{0, 1, 2, 2^D - 1\}$ as key and the child node as value respectively. We use the latter as it has a faster look up time.

4.2 FINDING MAXIMAL BLACK NODES

A bottom-up recursive procedure assigns black color to every leaf node and to every non-leaf node that has 2^D child nodes (maximum) and all child nodes are black (Appendix A.1 - procedure *set color*). Maximal black nodes are black nodes that are either leaf-nodes or non-leaf nodes with grey parent node. The 'maximal' black nodes are obtained with a depth-first traversal such that each time a black node is hit the rest of the sub-tree is skipped and the node is marked maximal (Appendix A.2 - procedure *find maximal black nodes*). Maximal black nodes are represented by $(\gamma_1, ..., \gamma_{n_b})$, where (n_b) denotes the number of maximal black nodes.

4.3 COMPUTING THE ADJACENCY MATRIX

Adjacency matrix holds distances for pairs of maximal black nodes, defined as the shortest distance between mesh cells in the two nodes. To compute these distances, we exploit the fact these mesh cells must lie on the mutually visible boundaries of the nodes.

The shortest distance between maximal black nodes is given by the distance between a pair of (nonmaximal) black nodes at the boundaries of the maximal black nodes located in line of sight and corresponding to closest approach. To identify these boundary node pairs, we start at the maximal black nodes and move up the hypertree. At each level of the hypertree we use the boundaries of sibling nodes to update the adjacency matrix and construct the parent node boundary using the sibling node boundaries, as given in the following top-down, recursive *fill matrix* procedure:

1. Traverse the tree to access the leaves.

2. Adjacency Matrix: From each leaf, traverse bottom up to recursively compute the adjacency matrix values. The mutually visible boundaries of all pairs of a parent node's non-empty children nodes are used to update the adjacency matrix. For a pair of sibling nodes $\{s_1, s_2\}$, their visible boundary is computed as the union of their mutually visible pairs of faces. For a sibling, a face is visible if it is in those dimensions in which the sibling is shifted. In the binary representation of a child hypercube, a 0/1 represents the child's position coordinate along a dimension being in the lower/higher half along that dimension. For each dimension d, if the siblings $\{s_1, s_2\}$ have coordinates 0 and 1, respectively, the visible boundary would include the face in the higher boundary of $\{s_1\}$ and the lower boundary of $\{s_2\}$ along dimension d. Doing this along every dimension completes the visible boundary shared between the two siblings.

   Once we have the visible boundary the distance between the siblings is the minimum of distances for each pair of mesh cells on the visible boundary. Each mesh cell has a reference to the maximal black node it belongs to, as explained at the end of A.2. Hence each pair of mesh cells on the visible boundary has a corresponding entry in the adjacency matrix. If the minimum distance between the pair of mesh cells is less than the entry in the adjacency matrix, the matrix is updated.

3. Boundary construction: A node boundary consists of mesh cells which are visible when viewing the node along each dimension, along both the positive and negative axes. Constructing a node boundary involves iterating over all non-white children nodes and extending the node boundary using the appropriate boundaries of the child node (say B_1) (for e.g., in the 2D case, the boundary of the bottom-left child may extend the left/bottom boundary of the parent, for details see Appendix A.4 procedure *get node boundary*). However, while extending the boundary in a certain dimension (say (d)), the boundary of the sibling hidden behind the child node (say B_2) must also be iterated over to check if mesh cells from B_2 are exposed through any holes in (B_1).

To accomplish this we check if a mesh cell exists in (B_2) which doesn't have the same coordinates (omitting the coordinate along the dimension (d)) as some mesh cell in (B_1). Such a cell would be exposed and should be included in the boundary along (d). A special case arises when the sibling boundary (B_2) is empty. Here the node boundary along the opposite axes of dimension (d) must be updated to include the boundary (B_1).

The procedure is called from the root of the hypertree. The base case of the recursion would be when the input node is black. In this case the algorithm returns the boundary of the hypercube represented by the black node, with no updates to the adjacency matrix (Appendix A.4 - procedure *get node boundary*).

4.4 CREATING COMPONENTS BY MERGING MAXIMAL BLACK NODES

This step identifies components formed by maximal black nodes separated by unit distance. These will be represented by $(\zeta_1, \zeta_2, ..., \zeta_{n_c})$. A component is then the largest set of maximal black nodes such that each maximal black node can be reached from another by following a chain of neighbouring maximal black nodes, each separated by a unit distance. This reduces the original problem of clustering points to one of clustering components and this further reduces the time required to extract clusters (see 5).

To find the maximal black nodes adjacent to each other we traverse the adjacency matrix for entries containing unit distance. Maximal black nodes are merged using a union find algorithm, which produces an identifier $f(.)$ for each maximal black node. Two maximal black nodes belonging to the same component have the same $f(.)$ value. The adjacency matrix is updated to hold the pairwise

distance between components. This is accomplished by iterating over each entry (i, j) in the original matrix and updating the entry $(f(i), f(j))$ in the new matrix. The shape of the new adjacency matrix is $(n_c \times n_c)$.

4.5 COMPONENT CLUSTERING

The components obtained are embedded into a graph as vertex nodes. The weight of the edge connecting two vertices is the distance between the two components, defined as the shortest distance between their mesh cells, which must be for two mesh cells lying on mutually visible boundaries of the components. This can be used to run any graph based clustering algorithm. We use the MST clustering algorithm. First compute the MST of the component graph to form a single component (cluster) connecting all nodes. Then, as in Zahn (1971), we remove the longest edge to create two components. By repeatedly removing the remaining edges in order of non-increasing length, we repeatedly increase the component (cluster) count by one. This yields a cluster tree, from which any desired number of clusters k may be obtained by removing the $k-1$ longest edges, along with their adjacency matrix.

5 TIME COMPLEXITY

The algorithm consists of the procedures:

1. Insertion of points into the hypertree: Each of the n data points is inserted into the appropriate child at each of the $log_2(E)$ levels in the tree, resulting in a time complexity of $O(n \cdot \log E)$. Each data point and non-white node is stored, resulting in a space complexity of $O(n + N_{nw})$, where N_{nw} indicates the number of non-white nodes in the hypertree.

2. Coloring (*set color* procedure): As each black node is accessed a recursive call is made to color each non-white child. Hence, the time complexity is $O(N_{nw})$. Since the color has to be stored for each non-white node the space requirement is $O(N_{nw})$.

3. Marking maximal black nodes (*find maximal black nodes* procedure): This step involves depth first traversal of the tree to extract maximal black nodes and to associate them with their children nodes. Hence both time and space complexities are $O(N_{nw})$.

4. Computing the adjacency matrix (*fill matrix* procedure): This step consists of two procedures

   (a) Computing distance between points on the visible boundary This step computes the distance between pairs of mutually visible mesh cells on the boundaries of the two sibling nodes and updates the adjacency matrix (unlike the MST algorithm which computes pairwise distance over all pairs of points). Hence the time complexity is $O(SA^2)$, where SA denotes the surface area of the sibling nodes. To store the visible boundaries requires $O(SA)$ space.

   (b) Boundary construction The time and space required to insert mesh cells from child nodes into the parent's boundary is $O(SA$ of the parent boundary$)$. However, this is dominated by the identification of mesh cells exposed to the boundary via holes in its neighbours, which grows with the child nodes surface area as $O(SA \cdot \log(SA))$ (Appendix 4b).

5. Merging maximal black nodes into components: This step consists of two procedures

   (a) Finding maximal black nodes at a unit distance from each other: This requires traversing the adjacency matrix and has time complexity $O(n_b^2)$, n_b being the number of maximal black nodes.

   (b) Merging proximal maximal black nodes into components: This requires running a union find algorithm over the maximal black nodes and has time complexity $O(m \log(n_b))$ where m is the number of union operations, i.e. the number of pairs of maximal black nodes at a unit distance from each other. In the worst-case, this complexity could become $O(n_b^2 \cdot \log(n_b))$.

6. Component clustering This step involves running the traditional MST algorithm on the component graph. The time complexity to obtain the cluster tree is $O(n_c^2 \cdot \log(n_c))$. To

extract (k) disjoint clusters, the $(k-1)$ longest edges are removed. Clusters can be obtained by running any graph traversal algorithm (BFS/DFS) on the disjoint cluster tree.

The set color and find maximal black node are grid-based procedures. Like all such algorithms, their time complexities are dependent on the grid size and hence on the spatial extent of the data, and independent of the number of points in the tree. However, the additional operations of computing pairwise distances between visible boundaries, and boundary construction are $O(SA^2)$. In practice, since many mesh cells combine to form components (instead of being independent, isolated mesh cells), this yields a significant empirical speed up.

The worst time complexity occurs in the rare case when all mesh cells are disconnected, and merging mesh cells into components does not reduce the number of vertices in the component graph. This eliminates any speedup, giving the worst-case time complexity of $O(n^2log(n))$, and space complexity of $O(n^2)$ required to store the adjacency matrix. This matches the MST clustering algorithm. In contrast, mesh based algorithms such as STING have a worst case time complexity of $O(n)$, density based algorithms such as DBSCAN have a worst case time complexity of $O(n^2)$ and graph based techniques such as spectral clustering have a worst case time complexity of $O(n^3)$.

6 EXPERIMENTS

Our experiments are aimed at verifying the proposed advantages of DAC. (1) In Sec 6.1, we first evaluate the correctness of DAC clusters vs visually detected clusters in the Fundamental Clustering Problems Suite (FCPS). Each dataset in FCPS involves specific clustering challenges. (2) We next test for the speedups expected from DAC, by comparing its runtimes with one representative algorithm from each of the three categories reviewed in Sec 2. The datasets help obtain runtimes for increasing number of n for a fixed D (3) Finally, we also evaluate the quality of DAC clusters by matching them with clusters detected as a part of an independent, downstream task.

6.1 EXPERIMENTS WITH FCPS DATASETS

We have experimented with four datasets. The challenges offered by these datasets and our clustering results on them are presented below.

6.1.1 HEPTA DATASET

This dataset includes clusters with different densities. To ensure separability among different datapoints, the number of grid points must be above the number of datapoints. We scale up the grid to a 50x50x50 cube (of 125000 grid points), with a vertex at the origin. Fig 3 shows the clusters obtained by DAC; in addition, it illustrates the operation of DAC by showing outputs at two intermediate stages of the algorithm.

Figure 3: Hepta Dataset: Left to Right - (1) Inputs points, (2) Maximal black node extracted by DAC. Points of the same color belong to one maximal black node. (3) Components extracted by DAC, points in each component shown in the same color. Note that the set of one-step reachable maximal black nodes are merged into a larger single component, indicated by more mesh cells of the same color. (4) Final seven ($k = 7$) clusters.

6.1.2 CHAINLINK DATASET

The chainlink dataset consists of two intertwined tori that are not linearly separable. Like any suitably designed proximity based algorithm, DAC is able to segregate the two tori clusters (Fig. 4).

6.1.3 TARGET DATASET

The target dataset contains two large clusters with 4 small ones as outliers. Note that DAC can detect the four outlier clusters (Fig. 4).

Figure 4: Input data (Fig 1 and 3 from left), and final clusters (Fig 2 and 4) produced for the chainlink and target datasets.

6.1.4 ENGYTIME DATASET

The Engytime dataset is a mix of two Gaussian clusters, one isotropic with unit variance, and the other, inclined one, has variances 2 and 1.6 along its principal axes.

Figure 5: Clusters detected by DAC in the Engytime dataset. Left to Right: (1) Input data points, (2) Maximal black nodes, (3) Components, (4) Output clusters for $k = 2$
Note that separation between the two clusters at their closest approach is comparable to their local, within-cluster nearest-neighbor distances; hence they are detected as a single cluster, not two as (as per our cluster definition in Sec 1).

6.2 COMPARISON OF RUN TIMES

To test the speedups expected from DAC, we compare runtimes of our algorithm for increasing number of n with three other algorithms: DBSCAN (density based), spectral clustering (graph based), and CLIQUE (mesh based). Since we do not have datasets with varying number of datapoints for the same cluster geometry, we modify the FCPS datasets; we increase the density of each of the datasets to obtain three versions having $n = 5,000, 50,000, 500,000$. We run all four algorithms and record their runtimes. Fig 6 shows how the runtime of each algorithm increases with n. As expected, we see that DAC has the slowest increase.

6.3 PERFORMANCE AS A PART OF A DOWNSTREAM TASK - A CNN CLASSIFIER

We also evaluate DAC by matching them with the clusters detected by an independent algorithm - a CNN classifier. The dataset we use is a set F of 10,000 features (datapoints) in a 512-dimensional space. F is output of the convolutional layers of a VGG-16 CNN classifier, with input being the 10-class CIFAR-10 test dataset. The output can be modeled as containing a cluster for each of the 10 classes. The classifier has been reported to yield a test accuracy A of 93.54% We test our algorithm by obtaining the best clusters in F, and then computing the average label-purity P of the clusters. The P value we have obtained using DAC is 95.79% which is almost the same as A. The

Figure 6: Runtimes of four different types of clustering algorithms, on the FCPS datasets modified to obtain three different values of n: 5,000, 50,000 and 500,000, by increasing cluster density while maintaining cluster geometry. The plots show runtimes for the algorithms CLIQUE(blue), DBSCAN(red) and DAC(green) for different n (shown on log scale). In general, DAC has the slowest rate of increase and its runtime advantage over other algorithms increases with n. The runtime for spectral clustering is too large to fit in the figure.

reason P is better than A is likely due to the fact that we are detecting clusters in the test data, not predicting them from training data, like CNN classifier has to), This agreement supports the validity of the clusters obtained by DAC under the assumption mentioned in the text (that CNN convolutional layer outputs contain class clusters.)

6.4 NUMBER OF COMPONENTS EXTRACTED BY DAC VS NUMBER OF POINTS

Towards verifying that the number of components is indeed much smaller than the number of points (which translates into a runtime advantage for DAC, as discussed in Algorithm and Complexity sections), we show in Fig 6.3 that the observed numbers of maximal black nodes as well as components in the modified chainlink dataset indeed grows very sublinearly with n.

7 LIMITATIONS AND CONCLUSIONS

We have presented an algorithm for local to global detection of clusters. Its advantage over many other clustering algorithms becomes particularly pronounced as n increases. The complexity results we have presented are for typical (average) cases; as we have noted in the main paper and more in Appendix, the worst case, degenerate data, although rare, may wipe out DAC's advantages. Further, since there is not much large-D data with ground truth available, evaluation of DAC on large D data has been difficult. We have used CNN classifier output for this purpose, treating CNN's class label outputs as ground truth. This is incorrect but may be adequate if the classifier accuracy is high. We plan to further test the performance of DAC by integrating it incorporating it into complex learning algorithms requiring clustering.

REFERENCES

Rakesh Agrawal, Johannes Gehrke, Dimitrios Gunopulos, and Prabhakar Raghavan. Automatic subspace clustering of high dimensional data. Data Mining and Knowledge Discovery, 11(1): 5–33, 2005.

Narendra Ahuja and Mihran Tuceryan. Extraction of early perceptual structure in dot patterns: integrating region, boundary, and component gestalt. Computer Vision, Graphics, and Image Processing, 48(3):304–356, 1989.

Mihael Ankerst, Markus M Breunig, Hans-Peter Kriegel, and Jörg Sander. Optics: Ordering points to identify the clustering structure. ACM Sigmod record, 28(2):49–60, 1999.

Yizong Cheng. Mean shift, mode seeking, and clustering. IEEE transactions on pattern analysis and machine intelligence, 17(8):790–799, 1995.

Martin Ester, Hans-Peter Kriegel, Jörg Sander, Xiaowei Xu, et al. A density-based algorithm for discovering clusters in large spatial databases with noise. In kdd, volume 96, pp. 226–231, 1996.

Chris L Jackins and Steven L Tanimoto. Oct-trees and their use in representing three-dimensional objects. Computer Graphics and Image Processing, 14(3):249–270, 1980.

Wei-keng Liao, Ying Liu, and Alok Choudhary. A grid-based clustering algorithm using adaptive mesh refinement. In 7th workshop on mining scientific and engineering datasets of SIAM international conference on data mining, volume 22, pp. 61–69, 2004.

Donald Meagher. Efficient synthetic image generation of arbitrary 3-d objects. In Proceeding of the IEEE Conference on Pattern Recognition and Image Processing, volume 473, 1982.

Gholamhosein Sheikholeslami, Surojit Chatterjee, and Aidong Zhang. Wavecluster: A multi-resolution clustering approach for very large spatial databases. In VLDB, volume 98, pp. 428–439, 1998.

Jianbo Shi and Jitendra Malik. Normalized cuts and image segmentation. IEEE Transactions on pattern analysis and machine intelligence, 22(8):888–905, 2000.

Jake VanderPlas. mst_clustering: Clustering via euclidean minimum spanning trees. J. Open Source Softw., 1(1):12, 2016.

Wei Wang, Jiong Yang, Richard Muntz, et al. Sting: A statistical information grid approach to spatial data mining. In Vldb, volume 97, pp. 186–195. Citeseer, 1997.

Charles T Zahn. Graph-theoretical methods for detecting and describing gestalt clusters. IEEE Transactions on computers, 100(1):68–86, 1971.

A APPENDIX

A.1 SET COLOR

Set color

Input : root of the tree
1. if (edge length of root = =1):
    root.color = 1.   // Black nodes are numbered 1.
    else :
      num_of_black_children = 0
      for all children (cl) of the root :
        num_of_black_children += Set color(cl).
      if (num_of_black_children == 2^D):
        root.color = 1   // all children are black
      else root.color = 0
2. return root.color

A.2 FIND MAXIMAL BLACK NODES

Find Maximal Black Nodes

Input : root of the tree
Output : Maximal black nodes γ_1, γ_2, $\cdots$, γ_{n_b}, (n_b) denotes the number of maximal black nodes

Initialization : *node id* = 1
1. if(*root*.color == 1) :
    set_node_id(*root, node id*)   //recursively sets the node_id for all nodes rooted at *root*
    $\gamma_{node\,id} = root$
    $root.\,isblack = True$
    $node\,id = node\,id + 1$
2. else :
    for all children (cl) of the *root* :
      Find Maximal Black Nodes(cl)

A.3 FILL MATRIX

Representation of node boundaries : In D-dimensional space a node has 2D boundaries, two in every dimension. We use a dictionary to maintain the node boundary wherein the boundary corresponding to the i-th dimension is stored with the key $(2i)$ and $(2i + 1)$ (similar to how heaps are represented using linear arrays). Hence the node boundary dictionary contains the keys $0, 1, 2, \cdots 2D-2, 2D-1$.

Fill_matrix
Outline : A top down procedure to compute node boundaries and fill the adjacency matrix *A*. Recursively computes and uses the input node boundary to update the matrix *A*.

Input : root of the tree (*root*)
Output : Boundary of the input node (*root*), updated matrix *A*.

Initialization : $A \in R^{n_b \times n_b}$ (n_b denotes the number of maximal black nodes). All entries are initialised to $+ \infty$

1. *Base Case* : When the root is a black node, return the root boundary.
   If $root.isblack$:
      return get_node_boundary(root, d = None)

2. Find the boundary of all child nodes to construct the boundary of the node *root*.
   boundaries = ϕ   // empty dictionary
   for rank, child in root.children :
      boundaries[rank] = fill_matrix(child)

3. Compute the visible boundary between every pair of children and use it to update the matrix *A*.
   for rank1 in root.children.keys():
      boundary1 = boundaries[rank1]   // fetch child boundary.
      location1 = binary_representation(rank1)

      for rank2 in root.children.keys():
        boundary2 = boundaries[rank2]
        location2 = binary_representation(rank2)
        relative_position = location2 - location1
        visible_1, visible_2 = []   // contains nodes on the visible boundary of child with rank1 and rank2.

        for dimension, direction in enumerate(relative_position):
          if(direction == 1):
            visible_1.append(boundary1 [2*dimension + 1])
            visible_2.append(boundary2 [2*dimension])
          if(direction == -1):
            visible_1.append(boundary1 [2*dimension])
            visible_2.append(boundary2 [2*dimension + 1])

      Update matrix using boundaries visible_1 and visible_2.
4. Construct *root* boundary using child node boundaries.
5. return *root* boundary.

The *fill matrix* procedure contains the following steps:

1. Recursively compute the node boundaries of all children
2. Use the child boundaries to update the adjacency matrix with the minimum distance between maximal black nodes :
   Worst-case time complexity : Worst case time complexity arises when the visible boundary is computed between each pair of siblings at each level in the hypertree. At a certain level in the tree, each pair of siblings (with edge length say $\left(\frac{s}{2}\right)$) can share at most (D) faces, each containing at most $\left(\frac{s}{2}\right)^{D-1}$ mesh cells. Hence, for this visible boundary we compute distance between $(D \cdot \left(\frac{s}{2}\right)^{D-1})$ pairs of mesh cells. There are $\binom{2^D}{2}$ such pairs of siblings inside the parent node. This gives a time complexity of $O\left(\binom{2^D}{2} \cdot \left(D(\frac{s}{2})^{D-1}\right)^2\right) = O(D^2 s^{2(D-1)})$ for all sibling pairs in one parent. However multiple such parent exist at each level in the tree. The parent with side length (s) belongs to the level $L = log_2 \left(\frac{E}{s}\right)$, where (E) denotes the side length of the root. The level (L) contains 2^{LD} nodes, each with edge length (s). Hence the time complexity at each level in the tree is given by $O(2^{LD} \cdot D^2 s^{2(D-1)}) = O(D^2 E^D s^{D-2})$. Summing over all levels $s = E, \frac{E}{2}, \cdots, 1$ gives the total time complexity of this step as

$$TC = O\left(D^2 E^D \cdot \left(E^{D-2} + \left(\frac{E}{2}\right)^{D-2} + \cdots\right)\right)$$
$$= O\left(D^2 E^D \cdot E^{D-2}(1 + 1\cdots)\right)$$
$$= O(D^2 E^{2(D-1)} log(E)) \tag{1}$$

Note that the time complexity grows as the square of the surface area of the hypertree.

3. Update the adjacency matrix using the visible boundary between a pair of sibling nodes :

Once the visible boundary between a pair of sibling nodes is computed in the *fill matrix* procedure, the pairwise distance between every mesh cell on the boundary is used to update the matrix A. The algorithm uses the maximal black node identifier set during the *find maximal black nodes* procedure to find which entry of the matrix is to be updated.

Procedure to update adjacency matrix *A* given a pair of visible boundaries

Input : Visible boundaries B_i, B_j, adjacency matrix *A* .

Output : Updated adjacency matrix *A* .

1. For cell_1 in B_i :
    For cell_2 in B_j :
      mb_node_1,mb_node_2= cell_1.node id, cell_2.node id   // maximal black node identifier
      distance <- euclidean distance(cell_1, cell_2)
      If distance < A[mb_node_1][mb_node_2] :
        A[mb_node_1][mb_node_2]= distance   // update matrix entries
        A[mb_node_2][mb_node_1]= distance

---

4. Construct the root boundary using the child node boundaries :

This procedure computes the boundary of non-black nodes given the boundary of all children nodes.

For every child, the while(dimension < D) loop is used to iterate over all the neighbouring siblings which may contain points to be included on the boundary. For each child $(rank\_1)$ and dimension (d) the procedure contains three steps :

(a) Insertion of points from the current boundary to the parent boundary : The entry to be updated in the parent's boundary is determined via the child's position inside the parent.
Worst case time complexity : For a parent with edge length (s), each face may contain a maximum of (s^{D-1}) mesh cells. Hence, the time complexity of adding points from the children boundaries would be $O(s^{D-1})$ per face, giving a time complexity of $O(D \cdot s^{D-1})$ for each parent with length (s).

(b) Inserting exposed points from the neighbouring siblings : Let us indicate the boundaries of the current child $(rank\_1)$ and the sibling $(rank\_2)$ as (B_1) and (B_2) respectively. To determine whether some mesh cell n from B_2 is visible through holes in B_1 we must determine if there exists a mesh cell n_* in B_1 which has the same coordinates as n in dimensions other than (d). We accomplish this by creating a scalar encoding $E(.)$ for each point on B_1 and B_2. The encoding is a function of the mesh cell, parent edge length s and the dimension parameter (d).
To motivate the use of the encoding function we propose the following lemma.
Lemma : Any mesh cell $n \in B_2$ would not be exposed through holes in B_1 iff there exists a mesh cell $n_* \in B_1$ such that $E(n_*) = E(n)$
Proof : Let the child $(rank\_1)$ be at position $(l_0, l_1, \cdots, l_{D-1})$ and have edge length $\frac{s}{2}$. As the child with rank $(rank\_2)$ is the neighbour along the dimension (d) it has the

---

Construct node boundary using child node boundaries

Input : node *root,* boundaries of all children of *root : boundaries*
Output : Boundary of the node *root* : boundary
Initialization : boundary = ϕ
   1. for rank_1 in boundaries.keys():   # iterate over all non-white children
        boundary_1 = boundaries[rank_1]

        binary_rank = binary_representation(rank_1)
        dimension = 0
        transform = 1 // used to access neighbours of child with rank_1 using the xor operation.

        while (dimension < D) :
          boundary_key = 2*dimension + binary_rank[dimension]   // which entry of the boundary is to be filled.
          boundary[boundary_key] <- boundary[boundary_key] ∪ boundary_1[boundary_key] // extend boundary
          rank_2 = rank_1 ^ transform   //toggles the bit at position (dimension) to give the neighbouring child

         if child with rank_2 exists :
          boundary_2 = boundaries[rank_2]
          encoded_boundary = encode_boundary (boundary_1[boundary_key], dimension)

          for point in boundary_2[boundary_key]:
            encoded_point = encode_point(point, dimension)
            if encoded_point not in encoded_boundary:
              boundary[boundary_key] = boundary[boundary_key] ∪ [point]
              encoded_boundary.insert(encoded_point)

        else :
          binary_rank_sibling= binary_representation(rank_2) # binary rank of the empty sibling (rank2)
          boundary_key = 2*dimension + binary_rank_sibling[dimension]
          encoded_boundary = ϕ
          for point in boundary_1:
            encoded_point = encode_point(point, dimension)
            if encoded_point not in encoded_boundary:
              boundary[boundary_key] = boundary[boundary_key] ∪ [point]
              encoded_boundary.insert(encoded_point)

        dimension +=1
        transform *= 2   // the next power of 2 would produce the next neighbour of child (rank_1)

    return boundary

---

encode_point

Input : point $p = (p_0, p_1, \cdots, p_{D-1}) \in R^D$, dimension (*d*).
Output : The point encoding.
   1. e <- edge length of caller node
   2. encoding <- $p_o + p_1 e + p_2 e^2 + \cdots p_{d-1}e^{d-1} + p_{d+1}e^d + \cdots + p_{D-1}e^{D-2}$
   3. return encoding

---

position $(l_0, l_1, \cdots l_{d-1}, l_d \pm \frac{s}{2}, l_{d+1}, \cdots l_{D-1})$. Let the mesh cell n_* be at the coordinate $(l_0 + p_0, l_1 + p_1, \cdots, l_{D-1} + p_{D-1})$ and the mesh cell (n) be at the coordinate $(l_0 + i_0, l_1 + i_1, \cdots l_{d-1} + i_{d-1}, l_d + -\frac{s}{2} + i_d, l_{d+1} + i_{d+1}, \cdots l_{D-1} + i_{D-1})$. The difference between the encoding of the mesh cell follows from the definition of the encoding function.

$$
\begin{aligned}
E(n_*) - E(n) =& (p_0 - i_0) + s \cdot (p_1 - i_1) + \cdots s^{d-1} \cdot (p_{d-1} - i_{d-1}) \\
& + s^{d+1} \cdot (p_{d+1} - i_{d+1}) + \cdots s^{D-1}(p_{D-1} - i_{D-1}))
\end{aligned}
\tag{2}
$$

Note that each (p_k, i_k) denotes the offset of the mesh cells from the node position and are whole numbers in the range $[0, s/2]$. Hence the encoding function can be interpreted as a base-s representation of the mesh cell offsets, i.e. $(p_0, p_1, \cdots p_{D-1})_s$. The two encodings would be equal iff for all $(k \neq d)$ $p_k = i_k$, i.e. when the mesh cell (n_*) has the same coordinates as (n) in all dimensions other than (d). This ensures that the mesh cell (n) is not exposed to the visible boundary through holes in boundary (B_1).

The lemma shows that if we encode each mesh cell on (B_1) beforehand we can determine if any mesh cell on (B_2) must be included in the parent boundary by a simple search in the set of encodings of all mesh cells on (B_1) (denoted by $E(B_1)$). Note that performing a coordinate comparison to determine which mesh cell goes into the parent boundary would require an $O(D)$ computation per pair of mesh cells on $(B_1), (B_2)$. This would give a time complexity of $O(|B_1| \cdot |B_2| \cdot D)$, where $|B_1|$ denotes the size of boundary B_1. However, if we use the encoding function we would only require $O((|B_1| + |B_2|) \cdot D)$ time to encode both the boundaries and $O(|B_2| \log(|B_1|))$ time to search for a matching encoding in the set $E(B_1)$. Hence, the time complexity for this computation would scale as $O(SA \log(SA))$ rather than $O(SA^2)$, where SA denotes the surface area of the child nodes.

Worst case time complexity : At a certain level in the tree, for each child (rank_1) and dimension (d) to determine mesh cells exposed through holes we must compute mesh cell encodings on the boundary face along dimension (d). A face of the boundaries $(B_1), (B_2)$ can contain a maximum of $\left(\frac{s}{2}\right)^{D-1}$ mesh cells. Encoding each mesh cell requires $O(D)$ time, giving a time complexity of $O(D \cdot \left(\frac{s}{2}\right)^{D-1})$. Once all mesh cells on (B_1) have been encoded we search for encoded mesh cells $E(B_2)$ in the set $E(B_1)$, resulting in a time complexity of $O(\left(\frac{s}{2}\right)^{D-1} \log\left(\left(\frac{s}{2}\right)^{D-1}\right)) = O(D \left(\frac{s}{2}\right)^{D-1} \log(s))$. Accumulating over all (rank_1, d) pairs gives the time complexity of $O(D \cdot 2^D \cdot D \left(\frac{s}{2}\right)^{D-1} \log(s)) = O(D^2 s^{D-1} \log(s))$ for each node with side length (s) in the tree. The node with side length (s) belongs to the level $L = log_2\left(\frac{E}{s}\right)$, where (E) denotes the side length of the root. The level (L) contains 2^{LD} nodes, each with edge length (s). Hence the time complexity at each level in the tree is given by $O(2^{L \cdot D} \cdot D^2 s^{D-1} \log(s)) = O(D^2 \cdot E^D \cdot \frac{\log(s)}{s})$. Summing over time complexity at each level in the tree, i.e. $s = E, \frac{E}{2}, \cdots$, gives the cumulative time complexity as

$$
\begin{aligned}
TC =& O\left(D^2 \cdot E^D \left(\frac{\log(E)}{E} + \frac{\log(E/2)}{E/2} + \cdots\right)\right) \\
=& O(D^2 \cdot E^D \cdot \log(E)(1 + 1 + \cdots)) \\
=& O(D^2 E^D \log^2(E))
\end{aligned}
\tag{3}
$$

A.4 GET NODE BOUNDARY

As the base case of the recursive *fill matrix* procedure, the *get node boundary* procedure computes the boundary of a black node by merging the boundaries of its child nodes. This procedure differs from part 3 of fill matrix as it computes the boundary of a black node, which is shaped as a hypercube. The procedure is described below.

get_node_boundary
Outline : find the boundary of a black node in a certain direction.

Input : Black node γ_i , boundary direction (d)

Output : Node boundary B_i

Initialization : $B_i = \phi$

1. if sum $(d) == - D$:   // each entry in (d) is -1
       return ϕ

2. _Base case_ : Boundary of a mesh cell.
   If edge length of γ_i == 1:

       if (d) is None :
         return $B_i = \{key : \gamma_i \mid key \in \{0, 1, 2, \cdots, 2D - 1\}\}$ // boundary in every direction is γ_i

       else :
         for dimension, direction in enumerate(d) :
           If direction != -1 :
             $B_i[2 \cdot dimension + direction] = \gamma_i$
         return B_i

3. for rank, node in $\gamma_i. children. items()$:

       direction = binary_representation(rank)
       if (d) is not None :
       $direction[\, direction\, != d] \leftarrow (- 1)$ // assign -1 to directions where no node boundary is required.
       node_boundary = get_node_boundary(node, direction) // get boundary of child node in the specified direction via a recursive call.
       for key, item in node_boundary.items() : // expand node boundary using child's node boundary.
         $B_i[key]$.extend(item)

4. return B_i

To obtain the boundary of a node, we compute the boundary of each child node using a recursive call but with a (d) parameter corresponding to its rank inside the parent. The function is called with the parameter boundary direction (d) which is a D-dimensional vector whose entries indicate which boundary is to be fetched. For a certain dimension, a corresponding (0) entry in (d) would fetch the left boundary, a (1) entry would fetch the right boundary and (-1) signifies that no boundary is to be returned in this dimension.

As an example consider the following two-dimensional node with edge length = 2 called with (d) = [0,1], which means that the left and upper boundary is required along the x and y-dimension respectively. For this purpose we only need the left boundary from the child with rank [0,0] (the bottom-left child), the top-left boundary from the child with rank [0,1] (the top-left child) and the top boundary from the child with rank [1,1] (the top-right child). This is accomplished by matching the child rank and (d). The top-left child is called with boundary direction = [0,-1], which signifies that only the left boundary is needed along the x-dimension. Others child nodes are called in a similar manner.