Social-Reasoning Fine-Tuning Does Not Transfer to Scalar Implicature

Abstract

In this paper, we test whether fine-tuning a small instruction-tuned language model (`Qwen2.5-0.5B-Instruct`) on social-reasoning data (Social IQa) improves its ability to handle scalar implicatures relative to the same model fine-tuned on generic instruction-following data (Alpaca). Using LoRA adapters at two training scales (800 and 2400 examples), evaluated across three random seeds at the larger scale on two IMPPRES subsets, we find the predicted transfer does not occur on gradable-adjective implicatures: the social-reasoning Treatment is reliably worse than the Control in every seed (mean pragmatic accuracy 0.027 vs. 0.129). Yet Treatment's prediction distribution closely matches the gold class marginal, so it assigns approximately the right number of each class to the wrong items. Open-ended generation shows that Treatment still produces label-style outputs, ruling out a simple format-drift mechanism and locating the effect at a deeper level.

1 Introduction

Scalar implicature is a textbook test case for pragmatic reasoning: from the usage of the phrase *some of*, a competent listener typically infers *not all*, even though the inference is not part of the truth-conditional content of the sentence (Grice, 1975; Horn, 1972). Whether language models compute such implicatures has become a useful probe of how far surface fluency is from genuine understanding (Jeretič et al., 2020; Pavlick and Kwiatkowski, 2019). The IMPPRES implicature subsets (Jeretič et al., 2020) pair each premise–hypothesis item with both a logical and a pragmatic gold label, so a model that ignores implicature can score well on one column and badly on the other.

A natural conjecture is that training on social-commonsense reasoning, which involves inferring the motivations and reactions of characters in everyday situations, should trans-fer to pragmatic inference. We fine-tune `Qwen2.5-0.5B-Instruct` (Yang et al., 2024) on Social IQa (Sap et al., 2019) and compare it against the same model fine-tuned on a similarly sized sample from Alpaca (Taori et al., 2023), as a generic instruction-following control. The motivation for the paired control is that instruction tuning changes model behaviour in general (Wei et al., 2022; Ouyang et al., 2022), so we aim to isolate the effect of social content from any benefit of additional instruction data.

2 Method

Base model and adapters: All experiments use `Qwen/Qwen2.5-0.5B-Instruct` (Yang et al., 2024) in fp16 on a single T4 GPU. The Base condition is the model with no further training. The Control and Treatment conditions each train a fresh LoRA adapter (Hu et al., 2022; Houlsby et al., 2019) on top of the frozen base, with identical hyperparameters: rank 8, $\alpha = 16$, dropout 0.05, targeting `q_proj` and `v_proj`. We use the HuggingFace PEFT (Mangrulkar et al., 2022) and TRL (von Werra et al., 2020) libraries.

Training data. The Control adapter is trained on examples sampled from Alpaca (Taori et al., 2023), using its standard instruction-response format. The Treatment adapter is trained on examples from Social IQa (Sap et al., 2019), which uses a narrative situation-question-answer format. For each seed, both datasets are shuffled with the corresponding seed value, and the same number of examples is drawn for each condition.

Training hyperparameters: Per-device batch size 4, gradient accumulation 4 (effective batch size 16), learning rate 2×10^{-4}, cosine schedule, 3% warmup, fp16, maximum sequence length 384. We ran two scales: a small run of 800 examples for 2 epochs (single seed) and a big run of 2400 examples for 3 epochs, replicated across three random

seeds ($\{0, 1, 2\}$ controlling both the training-data sub-sample and the HuggingFace Trainer's internal RNG). The two conditions are identical at each scale and seed, apart from the source of the training examples.

Evaluation methodologies: We evaluate on two IMPPRES subsets (Jeretič et al., 2020): `implicature_gradable_adjective` (restricted to `item_type=target`; gold pragmatic distribution 195 contradiction / 105 entailment) and `implicature_numerals_2_3` (178 contradiction / 92 neutral / 30 entailment). For each subset we sample 300 examples with seed 0. Predictions are the argmax over the three label tokens at the first generated position, applied uniformly to Base, Control, and Treatment. Note that *entailment* is multi-token under Qwen's tokenizer whereas *contradiction* and *neutral* are single tokens, so we score each label by the log-probability of its first sub-token. This asymmetry uniformly disadvantages *entailment* across all conditions (Base, Control, and Treatment) and is therefore a constant additive bias on absolute accuracy rather than a confound for between-condition comparisons. Our primary evidence for class displacement is the contradiction/entailment prediction shift on the gradable-adjective subset (reported in detail in §3): this comparison is between two single-token labels and is unaffected by the sub-token issue.

3 Results

Table 1 reports accuracy across both subsets and all conditions.

Scale	Cond.	Grad. adj.		Num. 2/3	
		Prag.	**Log.**	**Prag.**	**Log.**
—	Base	0.053	—	0.502	—
Small	Control	0.060	0.283	0.517	0.423
Small	Treatment	0.077	0.320	0.470	0.403
Big	Control	$0.129_{\pm 0.051}$	$0.325_{\pm 0.004}$	$0.406_{\pm 0.071}$	$0.382_{\pm 0.024}$
Big	Treatment	$0.027_{\pm 0.018}$	$0.322_{\pm 0.008}$	$0.463_{\pm 0.014}$	$0.402_{\pm 0.004}$

Table 1: Accuracy on IMPPRES. Small: 800 ex. × 2 epochs, single seed; Big: 2400 ex. × 3 epochs, mean ± SD across three seeds. All evaluations on $n = 300$ items per subset (eval set fixed across seeds).

The hypothesis is not supported on gradable adjectives. At the larger scale, Big-run Control outperforms Big-run Treatment on pragmatic accuracy in *every* seed (per-seed Control–Treatment gaps of $+0.156, +0.110, +0.040$; mean $+0.102 \pm 0.058$). The Treatment > Control ordering predicted by the social-transfer hypothesis is reliably reversed

on this subset. We note that absolute pragmatic accuracy is low across all conditions, reflecting the difficulty of zero-shot scalar implicature at this model scale; our claim therefore concerns the relative ordering of conditions, which the prediction-distribution analysis below shows is not driven by chance-level label noise. On the numerals 2/3 subset, by contrast, Treatment is consistently slightly *higher* than Control (per-seed gaps -0.033, -0.133, -0.007; mean -0.058 ± 0.067); the direction is consistent but the magnitude is unstable, and both conditions exhibit degenerate prediction behaviour on this subset (see below). The reversal we report is therefore specific to gradable adjectives, not a general harm of Social IQa fine-tuning across all scalar items.

Prediction distributions reveal class displacement: On the gradable-adjective subset the gold distribution is 195 contradiction / 105 entailment. Big-run Treatment predicts 198 ± 4 contradiction / 102 ± 4 entailment (mean ± SD across seeds), closely matching the gold marginal distribution but with near-zero pragmatic accuracy. Big-run Control predicts 232 ± 19 / 68 ± 19, overshooting contradiction, but its contradictions are largely correctly placed. Treatment's predictions are therefore not concentrated on the wrong class — they have approximately the right *counts* of each class, but assigned to the wrong *items*. On the numerals 2/3 subset, no condition produces the *neutral* label in any of the three seeds (model predictions are confined to *entailment* and *contradiction*), consistent with *neutral* being filtered out by the first-sub-token scoring discussed in §2; this degenerate three-way→two-way collapse is what makes the numerals 2/3 results uninformative about transfer.

Format drift is ruled out as the mechanism: A natural prior hypothesis is that Social IQa's narrative training format teaches the Treatment adapter to produce open-ended explanations rather than discrete labels, mechanically dragging accuracy down. Open-ended greedy decoding from both adapters refutes this. Across 10 randomly sampled gradable-adjective items, Treatment produces a single-token label-style continuation in every case (e.g. " contradict", " entailment"); Control produces similarly short outputs, and on the only example in our sample where one condition emits a longer continuation it is Control rather than Treatment, and it is explicit reasoning rather than Social-IQa-style narrative. A representative item is shown in Figure 1. The class displacement therefore originates

> **Premise:** Sharon is not brilliant.
> **Hypothesis:** Sharon is smart.   **Gold:** entailment
> **Control output:** "Entailment."
> **Treatment output:** "contradict"

Figure 1: Representative open-ended generations from Big-run Control and Treatment on a gradable-adjective item (greedy decoding, no constraint on first-token vocabulary, max 50 new tokens). Both conditions produce label-style continuations; Treatment is in fact more terse than Control. The mechanism behind Treatment's pragmatic collapse is therefore not format drift but a shift in label preference.

at a level deeper than output formatting: Social IQa fine-tuning preserves the model's ability to emit single label tokens but shifts which label it prefers on items requiring scalar inference. Adjudicating between candidate explanations of this internal shift (e.g. over-fitting to the narrow Social IQa answer distribution vs. representational interference) requires probes we leave to future work.

4 Conclusion

Across three random seeds, fine-tuning on Social IQa does not improve pragmatic implicature accuracy on the gradable-adjective IMPPRES subset; instead it reliably degrades it, while Treatment's prediction distribution converges to the gold marginal yet assigns class labels to the wrong items. On the numerals 2/3 subset the picture is inconclusive, with both conditions failing to use the *neutral* label under our scoring scheme. Crucially, this degradation occurs without any visible change in surface output behaviour: open-ended generation shows that Treatment continues to emit single-token label continuations, ruling out narrative-format drift as the mechanism and locating the effect in the model's internal label preferences. At this model scale, there is no evidence for transfer from social commonsense reasoning to scalar implicature; if anything there is anti-transfer.

Limitations

We trained three seeds of one 0.5B model and evaluated on two IMPPRES subsets. IMPPRES scalar implicature is a narrow operationalisation of pragmatic inference; a transfer failure here may still hold for other constructions. The numerals 2/3 subset under our first-sub-token scoring scheme produced degenerate (two-class) predictions in all six adapter conditions, so the small Treatment-over-

Control numerical advantage on that subset cannot be interpreted as evidence of transfer. We ran only one control dataset (Alpaca) and did not sweep learning rate or LoRA rank. Evaluating fine-tunes on a wider variety of social-reasoning datasets is necessary to determine whether the observed lack of transfer is a general property or an artefact specific to Social IQa. Future work should explore whether pragmatic transfer emerges when training on longer-context literature or complex multi-agent narratives, and should adopt a scoring scheme that does not collapse multi-token labels.

References

H. P. Grice. 1975. Logic and conversation. In Peter Cole and Jerry L. Morgan, editors, *Syntax and Semantics 3: Speech Acts*, pages 41–58. Academic Press, New York.

Laurence R. Horn. 1972. *On the semantic properties of logical operators in English*. Ph.D. thesis, University of California, Los Angeles.

Neil Houlsby, Andrei Giurgiu, Stanisław Jastrzębski, Bruna Morrone, Quentin de Laroussilhe, Andrea Gesmundo, Mona Attariyan, and Sylvain Gelly. 2019. Parameter-efficient transfer learning for NLP. In *Proceedings of the 36th International Conference on Machine Learning (ICML)*, pages 2790–2799.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. LoRA: Low-rank adaptation of large language models. In *International Conference on Learning Representations (ICLR)*.

Paloma Jeretič, Alex Warstadt, Suvrat Bhooshan, and Adina Williams. 2020. Are natural language inference models IMPPRESsive? learning IMPlicature and PRESupposition. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8690–8705.

Sourab Mangrulkar, Sylvain Gugger, Lysandre Debut, Younes Belkada, Sayak Paul, and Benjamin Bossan. 2022. PEFT: State-of-the-art parameter-efficient fine-tuning methods. https://github.com/huggingface/peft.

Long Ouyang, Jeff Wu, Xu Jiang, Diogo Almeida, Carroll L. Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul Christiano, Jan Leike, and Ryan Lowe. 2022. Training language models to follow instructions with human feedback. *Advances in Neural Information Processing Systems (NeurIPS)*.

Ellie Pavlick and Tom Kwiatkowski. 2019. Inherent disagreements in human textual inferences. *Transactions of the Association for Computational Linguistics*, 7:677–694.

Maarten Sap, Hannah Rashkin, Derek Chen, Ronan Le Bras, and Yejin Choi. 2019. Social IQa: Commonsense reasoning about social interactions. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 4463–4473.

Rohan Taori, Ishaan Gulrajani, Tianyi Zhang, Yann Dubois, Xuechen Li, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. 2023. Stanford Alpaca: An instruction-following LLaMA model. https://github.com/tatsu-lab/stanford_alpaca.

Leandro von Werra, Younes Belkada, Lewis Tunstall, Edward Beeching, Tristan Thrush, Nathan Lambert, Shengyi Huang, Kashif Rasul, and Quentin Gallouedec. 2020. TRL: Transformer reinforcement learning. https://github.com/huggingface/trl.

Jason Wei, Maarten Bosma, Vincent Y. Zhao, Kelvin Guu, Adams Wei Yu, Brian Lester, Nan Du, Andrew M. Dai, and Quoc V. Le. 2022. Finetuned language models are zero-shot learners. In *International Conference on Learning Representations (ICLR)*.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, Huan Lin, Jian Yang, Jianhong Tu, Jianwei Zhang, Jianxin Yang, Jiaxi Yang, Jingren Zhou, Junyang Lin, Kai Dang, Keming Lu, Keqin Bao, Kexin Yang, Le Yu, Mei Li, Mingfeng Xue, Pei Zhang, Qin Zhu, Rui Men, Runji Lin, Tianhao Li, Tianyi Tang, Tingyu Xia, Xingzhang Ren, Xuancheng Ren, Yang Fan, Yang Su, Yichang Zhang, Yu Wan, Yuqiong Liu, Zeyu Cui, Zhenru Zhang, and Zihan Qiu. 2024. Qwen2.5 technical report.