Uplifting Bandits

Abstract

We introduce a multi-armed bandit model where the reward is a sum of multiple random variables, and each action only alters the distributions of some of them. After each action, the agent observes the realizations of all the variables. This model is motivated by marketing campaigns and recommender systems, where the variables represent outcomes on individual customers, such as clicks. We propose UCB-style algorithms that estimate the *uplifts* of the actions over a baseline. We study multiple variants of the problem, including when the baseline and affected variables are unknown, and prove sublinear regret bounds for all of these. We also provide lower bounds that justify the necessity of our modeling assumptions. Experiments on synthetic and real-world datasets show the benefit of methods that estimate the uplifts over policies that do not use this structure.

1 Introduction

Multi-armed bandit (MAB) is an important framework for sequential decision making under uncertainty [6, 14, 15]. In this problem, a learner repeatedly takes action and receives their rewards, while the outcomes of the other actions are unobserved. The goal of the learner is to maximize their cumulative reward over time by balancing exploration (select actions with uncertain reward estimates) and exploitation (select actions with high reward estimates). MAB has applications in online advertisement, recommender systems, portfolio management, and dynamic channel selection in wireless networks.

One prominent question in the MAB literature is how the dependencies between the actions can be exploited to improve statistical efficiency. Popular examples working toward this goal include *linear bandits* [8] and *combinatorial bandits* [7]. In this work, we study a different structured bandit problem with the following three features: (*i*) the reward is the sum of the payoffs of a fixed set of variables; (*ii*) these payoffs are observed; and (*iii*) each action only affects a small subset of the variables. This structure arises in many applications, as discussed below.

(a) Online Marketing. An ecommerce platform can opt among several marketing strategies (actions) to encourage customers to make more purchases on their website. As different customers can be sensitive to a different marketing strategy, regarding each of them as a variable, it is natural to expect that each action would likely affect only a subset of the variables. The payoff associated to a customer can be for example the revenue generated by that customer; then the reward is just the total revenue received by the platform.

(b) Product Discount. Consider a company that uses discount strategies to increase their sales. It is common to design discount strategies that only apply to a small subset of products. In this case, we can view the sales of each product as a variable and each discount strategy as an action, and assume that each action only has a significant impact on the sales of those products discounted by this action.

(c) Movie Recommendation. Consider a bandit model for movie recommendation where actions correspond to different recommendation algorithms, and the variables are all the movies in the catalog. For each user, define a set of binary payoffs that indicate whether the user watches a movie in the

Algorithm	UCB	UpUCB (bl)	UpUCB	UpUCB-nAff	UpUCB-iLift
Affected variables known	No	Yes	Yes	No	No
Baseline payoffs known	No	Yes	No	No	No
Regret Bound	$\dfrac{Km^2}{\Delta}$	$\dfrac{KL^2}{\Delta}$		$\dfrac{KL^2}{\Delta}$	$\dfrac{K\,\mathrm{clip}(\Delta/\Delta_{\mathrm{up}},L,m)^2}{\Delta}$

Table 1: Summary of our regret bounds for uplifting bandits. Constant and logarithmic factors are ignored throughout. For simplicity, we assume here all actions affect exactly L of the m variables and all the suboptimal actions have the same suboptimality gap Δ. K and Δ_{up} are respectively the number of actions and a lower bound on individual uplift (Δ_{up} is formally introduced in Appendix E). The operator clip restricts the value of its first variable to the range defined by its second and third variable, i.e., $\mathrm{clip}(x,\alpha,\beta) = \max(\alpha,\min(\beta,x))$.

catalog, and the reward is the number of movies from the catalog that this user watches. Since a recommendation (action) for this user contains (promotes) only a subset of movies, it is reasonable to assume that only their associated payoffs are affected by the action.

Our Contributions. To begin with, we formalize an *uplifting bandit* model that captures the afore-mentioned structure. The model is stochastic, that is the payoffs of the variables follow an unknown distribution that depends on the chosen action. The term *uplift* refers to the difference between an action's reward and a certain baseline, and is borrowed from the field of *uplift modeling* [11, 16]. We study this problem under various assumptions on the learners' prior knowledge about **(1)** the baseline payoff of each variable and **(2)** the set of affected variables of each action. Our first result (Section 3) shows that when both **(1)** and **(2)** are known, a simple modification of the upper confidence bound (UCB) algorithm [3] (Algorithm UpUCB (bl)) for estimating the uplifts has a much lower regret than its standard implementation. Roughly speaking, when m is the number of variables and L is the number of variables affected by each action, we get a $O(L^2)$ regret bound instead of $O(m^2)$. This results in major regret reduction for $L \ll m$, and is a distinguishing feature of all our results.

Going one step further, we design algorithms that have minimax optimal regret bounds without assuming that either **(1)** or **(2)** is known in Sections 5 and 6. When **(1)** the baseline payoffs are unknown and **(2)** the affected variables are known, we compute differences of UCBs to estimate the uplifts (Algorithm UpUCB). In contrast to standard UCB methods, these differences are *not* optimistic; this is because the feedback of the actions also reveals important information about the baseline. When **(2)** the affected variables are also unknown, we identify them on-the-fly to maintain suitable estimates of the uplifts. We study two approaches, which differ in what they know about the affected variables. Algorithm UpUCB-nAff knows an upper bound on number of affected variables, whereas Algorithm UpUCB-iLift knows a lower bound on individual uplift. Our regret bounds are summarized in Table 1. These results are further completed with lower bounds that justify the need for our modeling assumptions (Section 4). To demonstrate the generality of our setup and how our algorithmic ideas extend beyond vanilla multi-armed bandits, we discuss contextual extensions of our model in Section 7. The experiments in Section 8 confirm the benefit of our approach.

Related Work. The goals of both uplifting modeling and MAB is to help selecting the optimal action. The former achieves it by modelling the incremental effect of an action on an individual's behavior. Despite this apparent connection between the two concepts, few papers explicitly link them together. We believe that this is because uplifting can be solved by classic bandit algorithms with a redefined reward. This approach was taken in [5, 17].

Instead, our paper focuses on bandit problems in which estimating the uplifts improves the statistical efficiency of the algorithms, and this is possible thanks to the 'sparsity' of the actions' effects. Prior to our work, sparsity assumptions in bandits primarily concerned the sparsity of the parameter vectors in linear bandits, which could be of great interest in high-dimensional settings [2, 4, 12]. A notable exception is Kwon et al. [13] who studied a variant of the MAB where the sparsity is reflected by the fact that the number of arms with positive reward is small. Our work is orthogonal to all of these in that we look at a different form of sparsity. As we will see in Section 7, while sparsity in parameter can be a cause of sparsity in action effect, the improvement of regret is established with a different mechanism. Comparison with other related lines of work in bandit literature (e.g., causal, combinatorial) is provided in Appendix B.

81 **Organization.** We introduce our uplifting bandit model along with its various variations in Section 2.
82 Over Sections 3, 5, 6, we provide regret bounds for these variations, with a lower bound presented
83 in Section 4. We discuss contextual extensions in Section 7 and experimental results in Section 8.

2 Problem Description

85 We start by formally introducing our uplifting bandit model. We illustrate it in Fig. 1 and summarize
86 our notation in Appendix A. Contextual extensions of this model are discussed in Section 7.

87 A (K, m)-uplifting bandit is a stochastic bandit with K actions and m underlying variables. Each
88 action $a \in \mathcal{A} := \{1, ..., K\}$ is associated with a distribution $\mathcal{P}^a$ on $\mathbb{R}^m$. At each round t, the learner
89 chooses an action $a_t \in \mathcal{A}$ and receives reward $r_t := \sum_{i \in \mathcal{V}} y_t(i)$ where $\mathcal{V} := \{1, ..., m\}$ the set of
90 all variables and $y_t = (y_t(i))_{i \in \mathcal{V}} \sim \mathcal{P}^{a_t}$ is the payoff vector.[1] Our model is distinguished by two
91 assumptions that we describe below.

92 **(I) Limited Number of Affected Variables.** Let $\mathcal{V}^a \subseteq \mathcal{V}$ be the subset of variables affected by
93 action a and $\mathcal{P}^0$ be the baseline distribution that the variables' payoffs follow when no action is
94 taken. By definition $\mathcal{P}^a$ and $\mathcal{P}^0$ have the same marginal distribution on $\overline{\mathcal{V}^a} := \mathcal{V} \setminus \mathcal{V}^a$, the variables
95 unaffected by action a.[2] While the above condition is always satisfied with $\mathcal{V}^a = \mathcal{V}$, we are interested
96 in the case of $L^a := \mathrm{card}(\mathcal{V}^a) \ll m$, meaning only a few variables are affected by a. We define
97 L as a uniform bound on L^a, so that $\max_{a \in \mathcal{A}} L^a \leq L$. For convenience of notation, we write
98 $\mathcal{A}_0 = \mathcal{A} \cup \{0\}$ and $[T] := \{1, ..., T\}$.

99 **(II) Observability of Individual Payoff.** In addition to the reward r_t, we assume that the learner
100 observes all the payoffs $(y_t(i))_{i \in \mathcal{V}}$ after an action is taken in round t.

101 **Uplift and Noise.** Let $y^a = (y^a(i))_{i \in \mathcal{V}}$ be a random variable with distribution $\mathcal{P}^a$. We define
102 $\mu^a(i) = \mathbb{E}[y^a(i)]$ and $\xi^a(i) = y^a(i) - \mu^a(i)$ respectively as the expected value of and the noise in
103 $y^a(i)$. We use μ^a (resp. $\mu^0(i)$) to denote the vector of $(\mu^a(i))_{i \in \mathcal{V}}$ (resp. $(\mu^0(i))_{i \in \mathcal{V}}$), and refer to
104 μ^0 as the baseline payoffs. The *individual* uplift associated to a pair $(a, i) \in \mathcal{A} \times \mathcal{V}$ is defined as
105 $\mu^a_{\mathrm{up}}(i) = \mu^a(i) - \mu^0(i)$. An individual uplift can be *positive* or *negative*. We obtain the (total) uplift
106 of an action by summing its individual uplifts over all the variables affected by that action

$$r^a_{\mathrm{up}} = \sum_{i \in \mathcal{V}^a} \mu^a_{\mathrm{up}}(i) = \sum_{i \in \mathcal{V}^a} (\mu^a(i) - \mu^0(i)). \tag{1}$$

107 Let $r^a = \sum_{i \in \mathcal{V}} \mu^a(i)$ be the expected reward of an action or of pure observation. We also have
108 $r^a_{\mathrm{up}} = r^a - r^0$ since $\mu^a(i) = \mu^0(i)$ as long as $i \notin \mathcal{V}^a$.

109 A real-value random variable X is said to be σ-sub-Gaussian if for all $\gamma \in \mathbb{R}$, it holds $\mathbb{E}[\exp(\gamma X)] \leq$
110 $\exp(\sigma^2 \gamma^2/2)$. Throughout the paper, we assume that $\xi^a(i)$ is 1-sub-Gaussian for all $a \in \mathcal{A}_0$ and
111 $i \in \mathcal{V}$. Note that we do not assume that $(y^a(i))_{i \in \mathcal{V}}$ are independent, i.e., the elements in the noise
112 vector $(\xi^a(i))_{i \in \mathcal{V}}$ may be correlated, for the following two reasons:

- 113 The independence assumption is not always realistic. In our first example, it excludes any potential
  114 correlation between two customers' purchases.

- 115 While a learner can exploit their knowledge on the noise covariance matrix to reduce the regret, as
  116 for example shown in [9], incorporating such knowledge complicates the algorithm design and the
  117 accompanying analysis. We however believe this is an interesting future direction to pursue.

118 **Regret.** The learner's performance is characterized by their regret. To define it, we denote by
119 $a^\star \in \arg\max_{a \in \mathcal{A}} r^a$ an action with the largest expected reward and $r^\star = r^{a^\star} = \max_{a \in \mathcal{A}} r^a$ the
120 largest expected reward. The regret of the learner after T rounds is then given by

$$\mathrm{Reg}_T = r^\star T - \sum_{t=1}^{T} r^{a_t} = \sum_{a \in \mathcal{A}} \sum_{t=1}^{T} \mathbb{1}\{a_t = a\} \Delta^a, \tag{2}$$

---

[1] The terms *reward* and *payoff* distinguish r_t and $(y_t(i))_{i \in \mathcal{V}}$.

[2] If the actions in fact have small impact on the variables in $\overline{\mathcal{V}^a}$, our model is misspecified and incurs additional linear regret whose size is proportional to the impact of the actions on $\overline{\mathcal{V}^a}$. An interesting question is how we can design algorithms that self-adapt to the degree of misspecification.

Actions Variables

Reward

Baseline

Figure 1: Illustration of the uplifting bandit model. This example has $K = 3$ arms, $m = 5$ variables and each action affects $L^a = 2$ variables. Dash lines indicate the variables' payoffs follow the baseline distribution $\mathcal{P}^0$ by default.

(a) UPUCB: After suboptimal action a_t is taken, the confidence intervals of $(\mu^a(i))_{i \in \mathcal{V}^{a_t}}$ and $(\mu^0(i))_{i \in \mathcal{V}^{a^\star} \setminus \mathcal{V}^{a_t}}$ shrink (from purple to pink). Hence the uplifting index of a_t decreases while that of $a^\star$ increases (from dash to solid).

(b) UPUCB-nAff (bl): To compute the uplifting index of an action, we identify a set of variables whose associated confidence intervals do not contain the baseline payoff and pad it with the variables with the largest UCBs on uplifts.

Figure 2: Explanation about UPUCB and UPUCB-nAff (bl) using model from Fig. 1.

where $\Delta^a = r^\star - r^a$ is the suboptimality gap of action a. In words, we compare the learner's cumulative (expected) reward against the best we can achieved by taking an optimal action at each round. For posterity, we write $\Delta = \min_{a \in \mathcal{A}, \Delta^a > 0} \Delta^a$ for the minimum non-zero suboptimality gap and refer to it as the suboptimality gap of the problem.

UCB for Uplifting Bandits. The UCB algorithm [3], at each round, constructs an *upper confidence bound* (UCB) on the expected reward of each action and chooses the action with the highest UCB. When applied to our model, we get a regret of $\mathcal{O}(Km^2 \log T/\Delta)$, as the noise in the reward is m-sub-Gaussian (recall that we do not assume independence of the payoffs). However, this approach completely ignores the structure of our problem. As we show in Section 3, we can achieve much smaller regret by focusing on the uplifts.

Problem Variations. In the following sections, we study several variants of the above basic problem that differ in the prior knowledge about $(\mathcal{P}^a)_{a \in \mathcal{A}_0}$ that the learner possesses.

(a) Knowledge of Baseline Payoffs. We consider two scenarios based on whether the learner knows the baseline payoffs $\mu^0 := (\mu^0(i))_{i \in \mathcal{V}}$ or not.

(b) Knowledge of Affected Variables. We again consider two scenarios based on whether the learner knows the affected variables associated with each action $(\mathcal{V}^a)_{a \in \mathcal{A}}$ or not.

3 Case of Known Baseline and Known Affected Variables

We start with the simplest setting where both the affected variables and the baseline payoffs are known. To address this problem, we make the crucial observation that for any two actions, the difference in their rewards equals to that of their uplifts. As an important consequence, uplift maximization has the same optimal action as total reward maximization, and we can replace rewards by uplifts in the definition of the regret (2). Formally, we write $r_{up}^\star = r_{up}^{a^\star} = \max_{a \in \mathcal{A}} r_{up}^a$ for the largest uplift; then $\text{Reg}_T = r_{up}^\star T - \sum_{t=1}^T r_{up}^{a_t}$. By making this transformation, we gain in statistical efficiency because $r_{up}^a = \mathbb{E}[\sum_{i \in \mathcal{V}^a} (y^a(i) - \mu^0(i))]$ can now be estimated much more efficiently under our notion of sparsity. Since both μ^0 and $(\mathcal{V}^a)_{a \in \mathcal{A}}$ are known, we can directly construct a UCB on r_{up}^a. For this, we define for all rounds $t \in [T]$, actions $a \in \mathcal{A}$, and variables $i \in \mathcal{V}$ the following quantities.

$$N_t^a = \sum_{s=1}^t \mathbb{1}\{a_s = a\}, \quad c_t^a = \sqrt{\frac{2\log(1/\delta')}{N_t^a}}, \quad \hat{\mu}_t^a(i) = \sum_{s=1}^t \frac{y_s(i)\,\mathbb{1}\{a_s = a\}}{\max(1, N_t^a)}, \quad (3)$$

where $\delta' > 0$ is a tunable parameter. In words, N_t^a, $\hat{\mu}_t^a(i)$, and c_t^a represent respectively the number of times that action a is taken, the empirical estimate of $\mu^a(i)$, and the associated radius of confidence interval calculated at the end of round t. The UCB for action $a \in \mathcal{A}$ and variable $i \in \mathcal{V}^a$ at round t is $U_t^a(i) = \hat{\mu}_{t-1}^a(i) + c_{t-1}^a$. We further define $\tau_t^a = \sum_{i \in \mathcal{V}^a} (U_t^a(i) - \mu^0(i))$ as the *uplifting index*, and refer to UPUCB (bl) as the algorithm that takes an action with the largest uplifting index τ_t^a at each round t (Algorithm 2, Appendix A). Here, the suffix (bl) indicates that the method operates with the knowledge of the baseline payoffs.

154 Since UPUCB (bl) is nothing but a standard UCB with transformed rewards $r'_t = \sum_{i \in \mathcal{V}_{a_t}} (y_t(i) -$
155 $\mu^0(i))$, and $\mathbb{E}[r'_t] = r^{a_t}_{\text{up}}$ defines exactly the same regret as the original reward, a standard analysis for
156 UCB yields the following result.

157 **Proposition 1.** *Let $\delta' = \delta/(2KT)$. Then the regret of* UPUCB (bl) *(Algorithm 2, Appendix A), with*
158 *probability at least $1 - \delta$, satisfies:*

$$\text{Reg}_T \leq \sum_{a \in \mathcal{A}: \Delta^a > 0} \left(\frac{8(L^a)^2 \log(2KT/\delta)}{\Delta^a} + \Delta^a \right). \tag{4}$$

159 As expected, the regret bound does not depend on m and scales with L^2. This is because the
160 transformed reward of action a is only L^a-sub-Gaussian. The improvement is significant when
161 $L \ll m$. However, this also comes at a price, as both the baseline payoffs and affected variables need
162 to be known. We address these shortcomings in Sections 5 and 6.

163 **Estimating Baseline Payoffs from Observational Data.** In practice, the baseline payoffs μ^0 can
164 be estimated from observational data, which gives confidence intervals where $\mu^0(i)$ lie with high
165 probability. The uplifting indices can then be constructed by subtracting the lower confidence bounds
166 of $\mu^0(i)$ from $U^a_t(i)$. If the number of samples is n, the widths of the confidence intervals are in
167 $\mathcal{O}(1/\sqrt{n})$. Identification of a^* is possible only when the sum of these widths over L variables is at
168 most Δ, which requires $n = \Omega(L^2/\Delta^2)$. Otherwise, these errors persist at each iteration and n must
169 be in the order of T to ensure $\mathcal{O}(\sqrt{T})$ regret.

170 **About Expected and Gap-Free Bounds.** In Proposition 1, we state a high-probability instance-
171 dependent regret bound, and we will continue to do so for all the regret upper bounds that we present
172 for the non-contextual variants. This type of result can be directly transformed to bound on $\mathbb{E}[\text{Reg}_T]$
173 by taking $\delta = 1/T$. Following the routine of separating Δ^a into two groups depending on their scale,
174 most of our proofs can also be easily modified to obtain a gap-free regret bound, which is typically in
175 the order of $\mathcal{O}(L\sqrt{KT \log(T)})$. We will not state these results to avoid unnecessary repetitions.

4   Lower Bounds

177 In this section, we shortly discuss the necessity of our modeling assumptions for obtaining the
178 improved regret bounds of Proposition 1. The complete discussion appears in Appendix D.

179 Intuitively, the regret can be improved both because the noise in the effect of an action is small, and
180 the observation of this effect does not heavily deteriorate with noise. These two points correspond
181 respectively to assumptions (I) and (II). Moreover, the knowledge on $(\mathcal{V}^a)_{a \in \mathcal{A}}$ allows the learner to
182 distinguish between problems with different structures. Without such distinction, there is no chance
183 that the learner can leverage the underlying structure. Therefore, the aforementioned three points are
184 crucial for obtaining (4). Below, we establish this formally for algorithms that are *consistent* [14]
185 over the class of 1-sub-Gaussian uplifting bandits, which means the induced regret of the algorithm
186 on any uplifting bandit with 1-sub-Gaussian noise satisfies $\text{Reg}_t = o(t^p)$ for all $p > 0$.

187 **Proposition 2.** *Let π be a consistent algorithm over the class of 1-sub-Gaussian uplifting bandits*
188 *that at most uses the knowledge of $\mathcal{P}^0$, $(\mathcal{V}^a)_{a \in \mathcal{A}}$, and the fact that the noise is 1-sub-Gaussian. Let*
189 *$K, m > 0$ and sequence $(L^a, \Delta^a)_{1 \leq a \leq K} \in ([m] \times \mathbb{R}_+)^K$ satisfy $\Delta^1 = 0$. Assume either of the*
190 *following holds.*

191 *(a) $L^a = m$ for all $a \in \mathcal{A}$, so that in the bandits considered below all actions affect all variables.*

192 *(b) Only the reward is observed.*

193 *(c) The algorithm π does not make use of any prior knowledge about the arms' expected payoffs*
194   *$(\mu^a)_{a \in \mathcal{A}}$ (in particular, the knowledge of $(\mathcal{V}^a)_{i \in \mathcal{V}}$ is not used by π).*

195 *Then, there exists a 1-sub-Gaussian (K, m)-uplifting bandit whose suboptimality gaps and numbers*
196 *of affected variables are respectively $(\Delta^a)_{a \in \mathcal{A}}$ and $(L^a)_{a \in \mathcal{A}}$, such that the regret induced by π on it*
197 *satisfies: $\liminf_{T \to +\infty} \frac{\mathbb{E}[\text{Reg}_T]}{\log T} \geq \sum_{a \in \mathcal{A}: \Delta^a > 0} \frac{2m^2}{\Delta^a}$.*

198 Proposition 1 states an instance-dependent lower-bound for a learner that may be equipped with full
199 knowledge of the baseline distribution.[3] Its proof is presented in Appendix D. At this point, what

---

[3]Of course, the problem only becomes more challenging if the learner does not know the baseline distribution.

Algorithm 1 UPUCB

1: **Input:** Error probability δ', the sets of variables each action affects $\{\mathcal{V}^a : a \in \mathcal{A}\}$
2: **Initialization:** Take each action once
3: **for** $t = K + 1, \ldots, T$ **do**
4:   Compute the UCB indices following (6)
5:   For $a \in \mathcal{A}$, set $\tau_t^a \leftarrow \sum_{i \in \mathcal{V}^a}(U_t^a(i) - U_t^0(i))$
6:   Select action $a_t \in \arg\max_{a \in \mathcal{A}} \tau_t^a$

---

200 remains unclear is whether similar improvement of the regret is still possible when the baseline is
201 unknown or when the learner only has access to more restricted knowledge than $(\mathcal{V}^a)_{a \in \mathcal{A}}$. We give
202 affirmative answers to these two questions in the next two sections.

5   Case of Unknown Baseline

204 In this section, we consider the situation where the sets of affected variables $(\mathcal{V}^a)_{a \in \mathcal{A}}$ are known by
205 the learner, but not the baseline payoffs. Missing proofs are in Appendix C.

206 Since the actual uplift at each round is never observed, the uplifts of the actions can hardly be
207 estimated directly without knowing the baseline payoffs. Instead, we follow a two-model approach.
208 Leveraging the fact that $\mathcal{P}^a$ and $\mathcal{P}^0$ have the same marginal distribution on $\overline{\mathcal{V}^a}$, we can estimate the
209 baseline payoffs by aggregating information from the feedback of different actions. This leads to

$$N_t^0(i) = \sum_{s=1}^{t} \mathbb{1}\{i \notin \mathcal{V}^{a_s}\}, \quad c_t^0(i) = \sqrt{\frac{2\log(1/\delta')}{N_t^0(i)}}, \quad \hat{\mu}_t^0(i) = \frac{\sum_{s=1}^{t} y_s(i)\,\mathbb{1}\{i \notin \mathcal{V}^{a_s}\}}{\max(1, N_t^0(i))}. \quad (5)$$

210 Compared to (3), we notice that both N_t^0 and c_t^0 are functions of i. This is because for each taken
211 action a, we only increase the counters $N_t^0(i)$ for those $i \notin \mathcal{V}^a$, which causes a non-uniform increase
212 of $(N_t^0(i))_{i \in \mathcal{V}}$. Then, by looking at all the rounds that variable i is not influenced by the chosen
213 action, we manage to compute $\hat{\mu}_t^0(i)$, an estimate of $\mu^0(i)$. To proceed, we define the following UCB
214 indices for all the pairs $(a, i) \in \mathcal{A}_0 \times \mathcal{V}$

$$U_t^a(i) = \begin{cases} 0 & \text{if } a = 0 \text{ and } i \in \bigcap_{a \in \mathcal{A}} \mathcal{V}^a, \\ \hat{\mu}_{t-1}^a(i) + c_{t-1}^a & \text{if } a \in \mathcal{A} \text{ and } i \in \mathcal{V}^a, \\ \hat{\mu}_{t-1}^0(i) + c_{t-1}^0(i) & \text{otherwise.} \end{cases} \quad (6)$$

215 The second and the third lines of (6) contain the usual definition of UCBs using the empirical
216 estimates and the radii of the confidence intervals defined in (3) and (5). In the special case that a
217 variable is affected by all the actions, it is impossible to estimate $U^0(i)$ but it is enough to compare
218 $U^a(i)$ directly against $U^{a'}(i)$ for any two actions $a, a' \in \mathcal{A}$, so we just set $U_t^0(i)$ to 0 in this case.

219 We outline the proposed method, UPUCB, in Algorithm 1. The uplifting indices are given by
220 $\tau_t^a = \sum_{i \in \mathcal{V}^a}(U_t^a(i) - U_t^0(i))$. It may be counter-intuitive to compare the differences between two
221 UCBs. Indeed, τ_t^a is no longer an optimistic estimate of the uplifting effect r_{up}^a, but it captures the
222 essential trade-off between learning action a's payoffs and learning the baseline μ^0. To provide some
223 intuition, we give an informal justification of UPUCB in Fig. 2a: If a suboptimal action a is taken
224 in round t, the estimates of all $U_t^a(i)$ move closer to the actual mean from above. As a result, τ_t^a
225 decreases, since all $U_t^a(i)$ for $i \in \mathcal{V}^a$ do. Thus action a is less likely to be taken next. Moreover, $\tau_t^{a^\star}$
226 increases, since $U_t^0(i)$ decrease for any i affected by $a^\star$ but not a. Thus $a^\star$ is more likely to be taken
227 next. The effectiveness of UPUCB is confirmed by the following theorem.

228 **Theorem 1.** *Let $\delta' = \delta/(4KLT)$. Then the regret of* UPUCB *(Algorithm 1) with probability at least*
229 $1 - \delta$, *satisfies:*

$$\text{Reg}_T \leq \sum_{a \in \mathcal{A}:\Delta^a > 0} \left(\frac{8(L^a + L^{a^\star})^2 \log(4KLT/\delta)}{\Delta^a} + \Delta^a \right). \quad (7)$$

230 As in Proposition 1, the regret is $\mathcal{O}(KL^2 \log T/\Delta)$. In fact, all decisions in UPUCB are made on
231 uncertain estimates of at most L variables; thus the statistical efficiency scales with L and not m.

Moreover, for any action a, the width of the confidence intervals for baseline estimates $c_t^0(i)$ are lower than those of a whenever $i \in \overline{\mathcal{V}^a}$. The factors $c_t^0(i)$ thus play a secondary role when bounding the regret. A detailed comparison with Proposition 1 reveals that the difference is in the order of $K(L^{a^\star})^2 \log T/\Delta$; this is only significant when the optimal actions affect many more variables then the suboptimal ones. Hence, the price of not knowing the baseline payoffs is generally quite small.

6 Case of Unknown Affected Variables

Now we study the more challenging setting where the affected variables $(\mathcal{V}^a)_{a \in \mathcal{A}}$ are unknown to the learner. Proposition 2 states that improvement is impossible if the learner does not have any prior knowledge to exploit the structure. To circumvent this negative result, we study two weak assumptions motivated by practice: learner has access to (*i*) an upper bound on the number of affected variables or (*ii*) a lower bound on individual uplift. Due to space constraints, we only present the first setting here and defer the discussion of the other to Appendix E.

For the remaining of this section, we assume that we have a known upper bound on number of affected variables L (i.e., $L \geq \max_{a \in \mathcal{A}} L^a$). We design algorithms with $\mathcal{O}(KL^2 \log T/\Delta)$ regret bounds that takes L as input. We consider the cases of known and unknown baseline payoffs.

Known Baseline Payoffs. To illustrate our ideas, we start by assuming that the baseline payoffs are known. We propose an optimistic algorithm that maintains an UCB on the total uplift with an overestimate in the order of L. Let N_t^a, c_t^a, and $\hat{\mu}_t^a(i)$ be defined as in (3). The UCB, uplifting indices, and the confidence intervals for each (action, variable) pair $(a, i) \in \mathcal{A} \times \mathcal{V}$ are

$$U_t^a(i) = \hat{\mu}_{t-1}^a(i) + c_{t-1}^a, \ \rho_t^a(i) = U_t^a(i) - \mu^0(i), \ \mathcal{C}_t^a(i) = [\hat{\mu}_{t-1}^a(i) - c_{t-1}^a, \ \hat{\mu}_{t-1}^a(i) + c_{t-1}^a]. \quad (8)$$

In the sequel, we refer to $\rho_t^a(i)$ as the *individual uplifting index* of the pair (a, i). It serves as an estimate of the individual uplift $\mu_{\mathrm{up}}^a(i)$. Our algorithm, UPUCB-nAff (bl), leverages two important procedures to compute an optimistic estimate of the uplift r_{up}^a: identification of affected variables, and padding with variables with the highest individual uplifting indices.

To begin, UPUCB-nAff (bl) constructs the set of *identified variables* $\widehat{\mathcal{V}}_t^a = \{i \in \mathcal{V} : \mu^0(i) \notin \mathcal{C}_t^a(i)\}$ which is contained in $\mathcal{V}^a$ with high probability. In fact, by concentration of measure, with high probability $\mu^a(i) \in \mathcal{C}_t^a(i)$, in which case $\mu^0(i) \notin \mathcal{C}_t^a(i)$ indicates $i \in \mathcal{V}^a$. However, $\widehat{\mathcal{V}}_t^a$ is not guaranteed to capture all the affected variables, so we also need to provide an upper bound for $\sum_{i \in \mathcal{V}^a \setminus \widehat{\mathcal{V}}_t^a} \mu_{\mathrm{up}}^a(i)$, the uplift contributed by the unidentified affected variables. Since the individual uplifting index $\rho_t^a(i)$ is in fact a UCB on the individual uplift $\mu_{\mathrm{up}}^a(i)$ here and $\mathrm{card}(\mathcal{V}^a) \leq L$, we can simply choose the $L - \mathrm{card}(\widehat{\mathcal{V}}_t^a)$ variables in $\mathcal{V} \setminus \widehat{\mathcal{V}}_t^a$ with the largest $\rho_t^a(i)$. Let us refer to this set as $\mathcal{L}_t^a$. We then get a proper UCB on the uplift of action a by computing $\tau_t^a = \sum_{i \in \widehat{\mathcal{V}}_t^a \cup \mathcal{L}_t^a} \rho_t^a(i)$. This process is summarized in Algorithm 3 in Appendix A and illustrated in Fig. 2b.

Unknown Baseline Payoffs. Now we focus on the most challenging setting, where also the baseline payoffs are unknown. In this case, neither the sets of identified variables nor the uplifting indices of UPUCB-nAff (bl) can be defined. We also cannot estimate the baseline payoffs using (5) since the sets of affected variables are unknown. To overcome these challenges, we note that for any two actions $a, a' \in \mathcal{A}$, μ^a and $\mu^{a'}$ only differ on $\mathcal{V}^a \cup \mathcal{V}^{a'}$, and $\mathrm{card}(\mathcal{V}^a \cup \mathcal{V}^{a'}) \leq 2L$. Therefore, μ^a and $\mu^{a'}$ differ in at most $2L$ variables, and we recover a similar problem structure by taking the payoffs of any action as the baseline.

Combining this idea with the elements that we have introduced previously, we obtain UPUCB-nAff (Algorithm 2). In each round, UPUCB-nAff starts by picking a most frequently taken action b_t (Line 4) whose payoffs are treated as the baseline during this round. Then, in Line 6, UPUCB-nAff chooses variables that are guaranteed to be either in $\mathcal{V}^a$ or $\mathcal{V}^{b_t}$. This generalizes the identification step of UPUCB-nAff (bl). The individual uplifting indices $\rho_t^a(i) = U_t^a(i) - U_t^{b_t}(i)$ are computed in Line 7. The definition as differences of UCBs is inspired by similar construction in UPUCB. Lines 8 constitutes the padding step, during which variables with the highest uplifting indices are selected, and finally in Line 9 we combine the above to get the uplifting index of the action.

To see why UPUCB-nAff is similar to UPUCB-nAff (bl), suppose that one action has been taken frequently. Then the baseline payoffs are precisely estimated and do not change much between consecutive rounds.

Algorithm 2 UPUCB-nAff

1: **Input:** Error probability δ', Upper bound L on the number of variables that each action affects
2: **Initialization:** Take each action once
3: **for** $t = K + 1, \ldots, T$ **do**
4:     Choose $b_t \in \arg\max_{a \in \mathcal{A}} N_{t-1}^a$ and compute UCBs and confidence intervals using (8)
5:     **for** $a \in \mathcal{A}$ **do**
6:         Set $\widehat{\mathcal{V}}_t^a \leftarrow \{i \in \mathcal{V} : \mathcal{C}_t^a(i) \cap \mathcal{C}_t^{b_t}(i) = \varnothing\}$
7:         For $i \in \mathcal{V}$, compute $\rho_t^a(i) \leftarrow U_t^a(i) - U_t^{b_t}(i)$
8:         Set $L_t^a \leftarrow \max(0, 2L - \mathrm{card}(\widehat{\mathcal{V}}_t^a))$ and $\mathcal{L}_t^a \leftarrow \arg\max_{\mathcal{L} \subseteq \mathcal{V} \setminus \widehat{\mathcal{V}}_t^a, \ \mathrm{card}(\mathcal{L}) \leq L_t^a} \sum_{i \in \mathcal{L}} \rho_t^a(i)$
9:         Compute uplifting index $\tau_t^a \leftarrow \sum_{i \in \widehat{\mathcal{V}}_t^a \cup \mathcal{L}_t^a} \rho_t^a(i)$
10:    Select action $a_t \in \arg\max_{a \in \mathcal{A}} \tau_t^a$

Regret. Both UPUCB-nAff (bl) and UPUCB-nAff choose $\mathcal{O}(L)$ variables for estimating the uplift of an action, and the decisions are made based on these estimates. Therefore, the statistical efficiencies of these algorithms only scale with L and not m. This in turn translates into an improvement of the regret, as demonstrated by the theorem below.

Theorem 2. *Let $\delta' = \delta/(2KmT)$. Then the regret of* UPUCB-nAff *(Algorithm 2) (resp.* UPUCB-nAff *(bl), Algorithm 3), with probability at least $1 - \delta$, satisfies:*

$$\mathrm{Reg}_T \leq \sum_{a \in \mathcal{A} : \Delta^a > 0} \left(\frac{\alpha L^2 \log(2KmT/\delta)}{\Delta^a} + \Delta^a \right), \tag{9}$$

where $\alpha = 512$ (resp. 32) in the above inequality.

The proof of Theorem 2 (Appendix C.3) is notable for two reasons. First, tracking of the identified variables guarantees that the uplifting index τ_t^a does not overestimate the uplift r_{up}^a much. Take UPUCB-nAff (bl) as an example. An alternative to constructing a UCB on r_{up}^a is to choose the L variables with the highest individual uplifting indices $\rho_t^a(i)$. However, this would result in a severe overestimate when a negative individual uplift is present. Second, to prove (9) for UPUCB-nAff, we use that the widths of confidence intervals of the chosen b_t are always smaller than those of the taken action. This is ensured by taking b_t as the most frequent action (Line 4 in Algorithm 2).

7 Contextual Extensions

In this section, we briefly discuss potential contextual extensions of our model; a detailed case study is presented in Appendix F. As in contextual bandits, context is a side information that helps the learner to make a more informed decision, which results in a higher reward. To incorporate context, one possibility is to associate each variable with a feature vector $x_t(i) \in \mathbb{R}^d$. The subscript t indicates that the context can change from one round to another. We also associate each action with a function f^a so that the expected payoff of action a acting on a variable with feature $x_t(i)$ is $f^a(x_t(i))$. The expected reward of choosing a at round t is then $r^a(x_t) = \sum_{i \in \mathcal{V}} f^a(x_t(i))$. The optimal action of round t is $a_t^\star = \arg\max_{a \in \mathcal{A}} r^a(x_t)$ and the regret of a learner that takes the actions $(a_t)_{t \in [T]}$ is given by $\mathrm{Reg}_T = \sum_{t=1}^T \sum_{i \in \mathcal{V}} (f^{a_t^\star}(x_t(i)) - f^{a_t}(x_t(i)))$.

The key structure in our model (Section 2) is there exists a baseline payoff vector μ^0 such that for any given action a, the equality $\mu^a(i) = \mu^0(i)$ holds for most $i \in \mathcal{V}$. Given context, this can be translated into the existence of a baseline function f^0 such that for any given a and t, the equality $f^a(x_t(i)) = f^0(x_t(i))$ holds for most $i \in \mathcal{V}$. The uplift of action a is defined as $r_{\mathrm{up}}^a(x_t) = \sum_{i \in \mathcal{V}} f^a(x_t(i)) - f^0(x_t(i))$.

For concreteness, let us consider a model with linear payoffs. Then, each action is associated with an unknown parameter θ^a and the expected payoff is the scalar product of θ^a and the feature of the variable, i.e., $f^a(x_t(i)) = \langle \theta^a, x_t(i) \rangle$. We also assume the aforementioned equality to hold for the baseline function f^0 and we use $\mathcal{V}_t^a = \{i \in \mathcal{V} : \langle \theta^a, x_t(i) \rangle \neq \langle \theta^0, x_t(i) \rangle\}$ for the variables affected by action a at round t. One sufficient condition for $\mathcal{V}_t^a$ to be small is sparsity in both the parameter difference $\theta_{\mathrm{up}}^a = \theta^a - \theta^0$ and the context vector $x_t(i)$. In fact, $\langle \theta^a, x_t(i) \rangle = \langle \theta^0, x_t(i) \rangle$ as long as the supports of θ_{up}^a and $x_t(i)$ are disjoint. In the sequel, we assume $\mathrm{card}(\mathcal{V}_t^a)$ is uniformly bounded by L.

318 Clearly, our algorithms can be directly applied as long as we can construct an UCB on $\langle \theta^a, x_t(i) \rangle$.
319 This can for example be done using the construction of Linear UCB [1]. In this way, the decision of
320 the learner is again based on the uncertain estimates of at most $\mathcal{O}(L)$ variables, and we thus expect
321 the improvements that we have shown in our theorems would persist. As an example, when both θ^0
322 and $\mathcal{V}_t^a$ are known, UPUCB (bl) adapted to this situation constructs UCB for $\sum_{i \in \mathcal{V}_t^a} \langle \theta_{\mathrm{up}}^a, x_t(i) \rangle$, and
323 it is straightforward to show that the regret of such algorithm can be as small as $\mathcal{O}(Ld\sqrt{KT})$.[4] In
324 contrast, if the learner works directly with the total reward, the regret is in $\mathcal{O}(md\sqrt{KT})$.

8 Numerical Experiments

326 In this section, we present numerical experiments to
327 demonstrate the benefit of estimating uplifts in our model.
328 We compare our methods introduced in Sections 3, 5 and 6
329 against UCB and Thompson sampling with Gaussian prior
330 and Gaussian noise that only use the observed rewards
331 $(r_t)_{t \in [T]}$. To ensure a fair comparison, we tune all the
332 considered algorithms and report the results for the pa-
333 rameters that yield the best averaged performance. The
334 detailed procedure and additional experimental details and
335 results are provided in Appendices G and H. The experi-
336 ments for a contextual extension (mentioned in Section 7)
337 are presented in Appendix F.3.

338 **Gaussian Uplifting Bandit.** We first study our algo-
339 rithms in a Gaussian uplifting bandit with $K = 10$ actions,
340 $m = 100$ variables, and $L^a \equiv 10$ meaning that each action
341 affects 10 variables.[5] The expected payoffs are contained
342 in $[0, 1]$, and the covariance matrix of the noise is taken
343 the same for all the actions. The suboptimality gap of the
344 created problem is around 0.2, and the variance of the total
345 noise $\sum_{i \in \mathcal{V}} \xi^a(i)$ is around 80.

346 **Bernoulli Uplifting Bandit with Criteo Uplift.** We use
347 the Criteo Uplift Prediction Dataset [10] with 'visit' as
348 the outcome variable to build a Bernoulli uplifting bandit,
349 where the payoff of each variable has a Bernoulli distribu-

(a) Gaussian uplifting

(b) Bernoulli uplifting

Figure 3: Experimental results on a synthetic and real-world dataset. All the curves are averaged over 100 runs and the shaded areas represent the standard errors.

350 tion. This dataset is designed for uplift modeling, and has outcomes for both treated and untreated
351 individuals. Thus it is suitable for our simulations. To build the model, we sample 10^5 examples from
352 the dataset, and use K-means to partition these samples into 20 clusters of various sizes. The 10^5
353 examples are taken as our variables. We consider 20 actions that correspond to treating individuals of
354 each cluster, and construct independent Bernoulli payoffs using the visit rates of the treated/untreated
355 individuals of the clusters following a procedure detailed in Appendix G.2. Here, $L = 12654$ and Δ
356 is around 30.

357 **Results.** Fig. 3 confirms that we can effectively achieve much smaller regret by restricting our
358 attention to the uplift. Moreover, when the sets of affected are known, the loss of not knowing the
359 baseline payoffs seems to be minimal. On the other hand, not knowing the affected variables has
360 a more severe effect in the second experiment. In fact, the design of UPUCB-nAff and UPUCB-
361 nAff (bl) heavily rely on the additive structure of the uplifting index, and can thus hardly benefit from
362 the payoff independence which allow the other four algorithms to achieve smaller regret in this case.

363 **Concluding Remarks.** This paper addresses multi-armed bandit problems whose rewards can be
364 written as a sum of some observable variables. We showed that when each of the action only affects a
365 limited number of these variables, much smaller regret can be achieved, and we developed algorithms
366 with such guarantee under different variations of knowledge the learner possesses. While the focus of
367 this paper is on UCBs for stochastic bandits, we believe understanding how similar problem structure
368 can be exploited for other algorithms and problem settings such as Thompson sampling, information
369 directed sampling, or even algorithms for adversarial bandits is also an important question.

---

[4]As in the previous sections, this bounds applies to the case of noises that are not necessarily independent.

[5]By Gaussian uplifting bandit we mean that the noise vectors $(\xi^a)_{a \in \mathcal{A}}$ are Gaussian.

References

[1] Yasin Abbasi-Yadkori, Dávid Pál, and Csaba Szepesvári. Improved algorithms for linear stochastic bandits. *Advances in Neural Information Processing Systems*, 24:2312–2320, 2011.

[2] Yasin Abbasi-Yadkori, David Pal, and Csaba Szepesvari. Online-to-confidence-set conversions and application to sparse stochastic bandits. In *Artificial Intelligence and Statistics*, pages 1–9. PMLR, 2012.

[3] Peter Auer. Using confidence bounds for exploitation-exploration trade-offs. *Journal of Machine Learning Research*, 3(Nov):397–422, 2002.

[4] Hamsa Bastani and Mohsen Bayati. Online decision making with high-dimensional covariates. *Operations Research*, 68(1):276–294, 2020.

[5] Jeroen Berrevoets, Sam Verboven, and Wouter Verbeke. Optimising individual-treatment-effect using bandits. *arXiv preprint arXiv:1910.07265*, 2019.

[6] Sébastien Bubeck and Nicolo Cesa-Bianchi. Regret analysis of stochastic and nonstochastic multi-armed bandit problems. *Machine Learning*, 5(1):1–122, 2012.

[7] Nicolo Cesa-Bianchi and Gábor Lugosi. Combinatorial bandits. *Journal of Computer and System Sciences*, 78(5):1404–1422, 2012.

[8] Varsha Dani, Thomas P Hayes, and Sham M Kakade. Stochastic linear optimization under bandit feedback. In *Conference on Learning Theory*, pages 355–366, 2008.

[9] Rémy Degenne and Vianney Perchet. Combinatorial semi-bandit with known covariance. In *Advances in Neural Information Processing Systems*, pages 2972–2980, 2016.

[10] Eustache Diemert, Artem Betlei, Christophe Renaudin, and Massih-Reza Amini. A large scale benchmark for uplift modeling. In *International Conference on Knowledge Discovery and Data Mining*. ACM, 2018.

[11] Pierre Gutierrez and Jean-Yves Gérardy. Causal inference and uplift modelling: A review of the literature. In *International Conference on Predictive Applications and APIs*, pages 1–13. PMLR, 2017.

[12] Botao Hao, Tor Lattimore, and Wei Deng. Information directed sampling for sparse linear bandits. In *Advances in Neural Information Processing Systems*, 2021.

[13] Joon Kwon, Vianney Perchet, and Claire Vernade. Sparse stochastic bandits. In *Conference on Learning Theory*, volume 65, 2017.

[14] Tze Leung Lai and Herbert Robbins. Asymptotically efficient adaptive allocation rules. *Advances in applied mathematics*, 6(1):4–22, 1985.

[15] Tor Lattimore and Csaba Szepesvári. *Bandit algorithms*. Cambridge University Press, 2020.

[16] Nicholas Radcliffe. Using control groups to target on predicted lift: Building and assessing uplift model. *Direct Marketing Analytics Journal*, pages 14–21, 2007.

[17] Neela Sawant, Chitti Babu Namballa, Narayanan Sadagopan, and Houssam Nassif. Contextual multi-armed bandits for causal marketing. In *International Conference on Machine Learning*, 2018.