Human Label Variation as Stable Signal: Learning Annotator-Specific Explanation Behavior via Cross-Annotator Preference Optimization

Abstract

Free-text explanations extend human label variation (HLV) beyond label disagreement by revealing the reasoning and preferences behind annotators' decisions. We study whether large language models (LLMs) can learn and reproduce such annotator-specific label-explanation behavior. Using two sentence-pair tasks with four annotators each—natural language inference and paraphrase judgment—we first analyze whether annotators exhibit stable individual patterns. We find that such patterns are weak at the single-annotation level due to strong input-content effects, but become detectable after input-content reduction and annotator-level aggregation. We then compare prompting and supervised fine-tuning (SFT) baselines and propose cross-annotator preference optimization (CAPO), which contrasts a target annotator's response with other valid but less target-specific annotations for the same input. Experiments show that prompting is limited and unstable, SFT better captures annotator-specific behavior, and CAPO further improves aggregation-aware imitation and judge-based attribution while preserving target-specific reasoning patterns under human validation. Overall, our results show that HLV can be learned as annotator-specific label-explanation behavior, suggesting a path toward scalable explanation-based annotation grounded in annotator histories rather than labels alone.

1 Introduction

Human label variation (HLV; Plank, 2022) highlights that annotator disagreement often captures meaningful differences in interpretation, rather than noise to be collapsed into a majority label (Aroyo and Welty, 2015; Pavlick and Kwiatkowski, 2019; Plank et al., 2014; Uma et al., 2021; Cabitza et al., 2023). Most work on HLV represents such disagreement as label distributions (Nie et al., 2020; Zhou et al., 2022; Chen et al., 2024; Lu et al., 2026; Chen et al., 2026). However, labels alone provide only a partial view of annotator behavior: they indicate *what* annotators choose, but not *why*. Free-text explanations provide complementary evidence by revealing how annotators interpret an input, which evidence they attend to, and how they justify their decisions (Jiang and de Marneffe, 2022; Jiang et al., 2023; Hong et al., 2025b). Recent work has therefore used explanations to better understand disagreement and annotator reasoning in sentence-pair tasks such as natural language inference (NLI) and paraphrase judgment (Basile et al., 2021; Weber-Genzel et al., 2024; Chen et al., 2025b,a; Hong et al., 2025a). This raises a practical question: how can large language models (LLMs) *simulate annotator-specific label-explanation behavior*, rather than label alone, to produce interpretable, useful, and scalable HLV annotations?

Before modeling such behavior, we first ask whether annotator-specific behavior is observable. We examine two 4-annotator datasets with explanations, covering both NLI and paraphrase judgment settings (Weber-Genzel et al., 2024; Leonardelli et al., 2025). This diagnostic is non-trivial because explanations for the same input are content-dominated: annotators may mention similar semantic relations even when their broader reasoning styles differ. In NLI, for instance, two annotators may both note lexical overlap, but treat it differently—as sufficient evidence for entailment or as compatible with a neutral judgment due to unsupported information. As a result, single explanations provide only weak evidence of annotator-specific patterns. We therefore remove input-content effects and aggregate annotations by annotator, revealing **stable annotator-specific patterns that are better observed in repeated behavior than in isolated responses.**

We then ask whether LLMs can learn such behavior. We compare prompting and supervised fine-tuning (SFT) as simulation baselines, covering in-context and profile prompting, and parameter

adaptation (Brown et al., 2020; Sorensen et al., 2025; Hu et al., 2022). Beyond these baselines, we propose cross-annotator preference optimization (CAPO), which uses variation among annotators on the same input as contrastive supervision. For a target annotator, CAPO treats the target's label-explanation response as preferred and other annotators' responses as valid but less target-specific alternatives, rather than as incorrect outputs. Implemented with direct preference optimization (Rafailov et al., 2023), CAPO learns to **prefer responses that better match the target annotator while still respecting the space of plausible human annotations.**

This simulation setting also requires evaluation beyond decision matching or single-reference explanation similarity. We therefore separate target-label prediction, reference explanation similarity, and recognizable annotator imitation. While ROUGE, BERTScore, and embedding cosine similarity (Lin, 2004; Zhang et al., 2020; Reimers and Gurevych, 2019) capture aspects of explanation overlap, they are difficult to interpret as measures of annotator-specificity and often lack sensitivity when comparing simulation methods. Motivated by our diagnostic analysis, we emphasize aggregation-aware metrics that evaluate groups of outputs for the same target annotator, complemented by LLM-as-judge attribution and human validation. Across Qwen3 (Team, 2025) and Llama3.2 (Team, 2024), prompting is limited and unstable, SFT is a stronger baseline, and CAPO further improves aggregation-aware imitation and judge-based attribution. Overall, our results suggest that HLV can be modeled as annotator-specific label-explanation behavior, but that reliable evaluation of individual annotator style requires grouping outputs across instances.

We make three main contributions:

- We diagnose annotator-specific behavior, which is difficult to characterize at the single-instance level but becomes stable after input-content removal and annotator-level aggregation.
- We propose cross-annotator preference optimization (CAPO), using variation among valid human annotations as contrastive supervision for modeling target-specific label-explanation behavior.
- We evaluate prompting, SFT, and CAPO with decision matching, reference similarity, aggregation-aware imitation, and human validation, showing that CAPO improves pattern-level recognizability of target annotator over baselines.

2 Related Work

Explanation-grounded human label variation. HLV and perspectivist NLP challenge the view of disagreement as annotation noise (Aroyo and Welty, 2015; Plank et al., 2014; Uma et al., 2021; Plank, 2022; Cabitza et al., 2023), motivating label-distribution modeling and annotator-aware learning from disagreement (Nie et al., 2020; Zhou et al., 2022; Wang and Plank, 2023; Leonardelli et al., 2025; Lu et al., 2026; Chen et al., 2026). In sentence-pair tasks such as NLI, such variation often reflects ambiguity, uncertainty, or alternative interpretations that are obscured by majority labels (Pavlick and Kwiatkowski, 2019; Chen et al., 2020). Yet label distributions alone reveal little about why annotators disagree or how they justify their decisions. Free-text explanations address this gap by exposing annotators' reasoning, evidence use, and decision processes (Jiang and de Marneffe, 2022; Jiang et al., 2023; Weber-Genzel et al., 2024; Hong et al., 2025a,b). Recent work has used explanations to analyze disagreement, identify plausible variation, and approximate human label distributions (Chen et al., 2024, 2025b,a; Zuo et al., 2025; Panahi et al., 2026). Our work differs by treating explanations not only as diagnostic evidence or auxiliary rationales, but as part of annotator-specific behavior to be learned and evaluated.

LLM-based annotator simulation. LLMs are increasingly used to generate labels, rationales, and simulated human responses (Gilardi et al., 2023; Park et al., 2023). Existing work often targets aggregate behavior, majority labels, or population-level variation, while persona- and profile-based prompting conditions models on demographic, social, or role descriptions (Deshpande et al., 2023; Santurkar et al., 2023; Argyle et al., 2022). Such approaches can expose perspective sensitivity, but they are often weakly grounded in actual annotation histories and may reduce annotator behavior to coarse-grained or stereotype-prone profiles (Cheng et al., 2023; Orlikowski et al., 2023, 2025; Sorensen et al., 2025). In contrast, we study data-grounded annotator behavior modeling under HLV, where target behavior is inferred from repeated labels and explanations by the same annotator rather than imposed through external personas or optimized only for aggregate agreement. This shifts evaluation from decision matching or surface similarity to whether generated outputs preserve recognizable annotator-specific patterns across instances.

(a) Pairwise label agreement   (b) Label proportions

Figure 1: VariErr label variation across annotators. Annotators differ both in pairwise agreement and in their label priors, suggesting that HLV contains annotator-specific structure rather than only item-level ambiguity.

Figure 2: VariErr explanation-style features averaged by annotator and min-max normalized within each feature. Feature differences provide interpretable evidence of repeated writing habits, such as length, modality, negation, and quotation; feature details are in Appendix C.1.

3 Stability of Annotator Variation

A prerequisite of our simulation is to assess *whether stable annotator-specific behavior exists.* To do so, we here focus on VariErr NLI, the more conservative of our two datasets.[1] R2 paraphrase-judgment results follow the same pattern, with stronger separability, and are reported in Appendix C.4. In VariErr, each input is a premise-hypothesis pair $x_i = (p_i, h_i)$, and each annotator $a \in \{0, 1, 2, 3\}$ provides an NLI label $y_{i,a}$ (for R2 it's a score) and a free-text explanation $e_{i,a}$. An annotation is therefore $z_{i,a} = (y_{i,a}, e_{i,a})$.

---

[1]Dataset details are in Section 4.1 and Appendix B.1

Figure 3: UMAP of VariErr E_1 embeddings. Annotator colors are substantially mixed, indicating that raw semantic embeddings are dominated by item content.

3.1 Annotators Differ in Label Use

We first examine label variation. Figure 1 shows pairwise Cohen's κ (Cohen, 1960) and each annotator's label proportions over all VariErr annotations. Agreement is moderate: off-diagonal κ values range from 0.31 to 0.41. The label marginals also differ. Some global annotator preferences emerge: for example, Annotator 2 assigns NEUTRAL most often and ENTAILMENT least often, while Annotator 3 assigns most CONTRADICTION. Thus, annotators are not interchangeable even before explanations are considered. This label-level structure is the basis of perspectivist and annotator-aware modeling approaches (e.g., Davani et al., 2022; Aroyo and Welty, 2015), but our question is whether such annotator-specific structure also extends to the joint label-explanation behavior.

3.2 Explanation Style Is Visible, But Raw Embeddings Are Content-Dominated

We next ask whether explanations carry annotator-specific signal and propose ways to quantify it. We compute two complementary views over all VariErr annotations. First, we extract handcrafted surface-level features to capture explanation style, including length, sentence count, type-token ratio, and linguistic features. These features are designed to capture how an annotator writes. Second, we embed the input-label-explanation as E_1:[2]

$$E_1 = f(p_i, h_i, y_{i,a}, e_{i,a}). \quad (1)$$

The feature heatmap (Figure 2) reveals small but repeated surface-level tendencies, e.g., Annotator 0 writes the longest explanations on average, and Annotator 2 has the highest modal-word and first-person rates. In contrast, the E_1 UMAP (Figure 3)

---

[2]sentence-transformers/all-mpnet-base-v2 on huggingface.

Figure 4: VariErr group-averaged E_4 for increasing m. Each visualization samples 80 groups per annotator. Averaging annotations by annotator suppresses item-specific content and reveals stable annotator-specific structure.

is heavily mixed across annotators. We hypothesize it is because E_1 contains the input, making explanations for the same or similar inputs semantically similar regardless of annotator-specific habits.

3.3 Single-Annotation Classifiers Are Informative But Insufficient

To quantify whether this variation is learnable, we train annotator 4-way classifiers[3] on an item-level split: 250 items for training and 250 disjoint items for testing, with all annotator rows for an item kept on the same side. The handcrafted features reach 50.2% test accuracy, confirming that explanation style is partially recoverable from a single annotation. However, raw E_1 reaches only 41.9%. This supports the qualitative UMAP result: semantic embeddings of individual explanations are strongly entangled with the question content. To test whether content removal improves annotator recoverability, we construct additional representations that separate the input from the label-explanation response:

$$E_0 = f(p_i, h_i), E_2 = f(y_{i,a}, e_{i,a}), \qquad (2)$$

While E_2 can still reflect the input, we define two residual embeddings after normalizing E_0 and E_2:

$$\begin{aligned} E_3 &= \text{norm}(E_2 - E_0), \\ E_4 &= \text{norm}\left(E_2 - (E_2^\top E_0)E_0\right). \end{aligned} \qquad (3)$$

These residuals are intended as diagnostics, not as perfect content-removal methods. Among single-annotation embeddings, E_4 performs best, reaching 56.5% test accuracy (Appendix C.2), improving over E_1 but still falling short of reliable instance-level identification. This suggests that individual explanations remain mixtures of annotator-specific tendencies and item-specific content, limiting their usefulness as standalone signals for training or evaluation.

3.4 Aggregation Reveals Stable Behavior

We therefore move from individual annotations to groups. The intuition is simple:[4] *if we average many embeddings from the same annotator across different items, item-specific semantic directions should cancel more than repeated annotator-specific tendencies.* For each E_1–E_4 and group size m, we sample groups of m annotations from the same annotator, average their normalized embeddings, and renormalize the group vector. Classifiers are trained on group vectors from train set and evaluated on group vectors from test set. Figure 4 shows group-averaged E_4 embeddings. The clusters become increasingly annotator-specific as m grows. Figure 5 quantifies the same effect: the VariErr E_4 group classifier rises from 57.3% at $m = 1$ to 96.4% at $m = 50$.[5] By contrast, classifiers trained on larger group means are not reliable single-instance classifiers. This gap is the key diagnostic result: target-specific behavioral patterns are much clearer when observed as repeated behavior than as properties of isolated explanations.

---

[3]The feature classifier uses a `StandardScaler` followed by balanced logistic regression (Pedregosa et al., 2011); embedding classifiers use balanced logistic regression on E_1.

[4]This intuition is related to averaging-based directions in activation steering (Arditi et al., 2024; Turner et al., 2023).

[5]Due to random test groups, accuracy at at $m = 1$ slightly differs from single-annotation classifiers.

Figure 5: VariErr annotator-classifier accuracy by representation and group size m (240 train groups and 160 test groups per annotator). Solid lines evaluate grouped test annotations; dashed lines apply the same group-trained classifiers to individual test annotations. Aggregation sharply improves annotator recoverability, especially for content-reduced representations. Detailed group classifier sweep results are in Appendix C.3.

Dataset	Task	Output	Split	Task Metric
VariErr	NLI	label + explanation	300/100/100	Label Acc
R2	paraphrase judgment	score + explanation	300/100/100	Score Acc; MAE

Table 1: Dataset summary. Both datasets contain 4 annotators per item. Details are in Appendix B.1.

We use E_4 as the main diagnostic representation because it is the strongest single-annotation representation and has the clearest content-debiasing interpretation; Appendix C.2.1 further shows that it has the lowest linear recoverability of the input. At larger group sizes, however, E_2–E_4 perform similarly, suggesting that aggregation suppresses much of the item-level variation. Thus, our main claim is not that individual annotations are reliably classifiable, but that repeated label-explanation behavior forms a stable annotator-specific signal, motivating the following aggregation-aware imitation metrics.

4 Annotator Simulation and Evaluation

We next study *whether LLMs can simulate the annotator-specific label-explanation behavior*. We formulate this as conditional generation: given an input question and a target annotator ID, the model outputs both the task decision and an explanation.

4.1 Task and Model

We evaluate on two datasets with annotator-level labels and explanations: VariErr NLI (Weber-Genzel et al., 2024), where outputs are entailment, neutral, or contradiction labels, and R2 paraphrase judgment (Leonardelli et al., 2025), where outputs are integer relatedness scores from -5 to 5. All methods use the same train/dev/test item splits, summa-

Method	Annotator signal	Parameter update	Role
Base	Symbolic ID only	No	format control
ICL	n examples	No	example-only prompting
VP	profile from n examples	No	global summary
VP-ICL	profile + n examples	No	strongest prompt baseline
SFT	target annotations	Yes	learns target behavior
CAPO	cross-annotator preference pairs	Yes	sharpens target contrast

Table 2: Main annotator simulation methods.

rized in Table 1. Experiments are conducted with Qwen3-4B-Instruct-2507 (Qwen3; Team 2025) and Llama-3.2-3B-Instruct (Llama3.2; Team 2024).

4.2 Methods

We compare methods with increasing supervision strength, summarized in Table 2: prompting, supervised fine-tuning (SFT), and cross-annotator preference optimization (CAPO). All methods condition on the same symbolic target annotator ID, but differ in whether and how they ground this ID in the annotator's past behavior; see details in Appendix B.2.

Prompting. The Base setting provides only the input pair and target ID, without annotation history, demonstrations, or profiles; it therefore measures default behavior under the same output schema rather than true annotator conditioning. Prompt-based methods ground the target ID at inference time using n examples from the target annotator. We consider in-context learning (ICL), which provides demonstrations directly; value profiles (VP; Sorensen et al., 2025), which summarize the annotator's label tendencies and explanation style into a natural-language profile; and VP-ICL, which combines both. In the main experiments we use $n = 50$, with prompt in Appendix A, n sweeps in Appendix D.1, and profiles in Appendix H.

SFT. For each annotator a, we train an independent LoRA adapter (Hu et al., 2022) on that annotator's training annotations.[6] Given the base model π_0, the adapted policy is denoted $\pi_{\theta_a}^{\text{SFT}}(z \mid x, a)$, where $z = (y, e)$. We optimize the standard conditional language-modeling objective:

$$\mathcal{L}_{\text{SFT}}(a) = -\sum_{(x_i, z_{i,a}) \in \mathcal{D}_a} \log \pi_{\theta_a}^{\text{SFT}}(z_{i,a} \mid x_i, a).$$
(4)

Thus, SFT stores target-annotator behavior in independent adapted parameters rather than recovering it from a profile string or symbolic annotator ID.

---

[6]We use independent adapters because a shared annotator-ID-conditioned variant showed much weaker annotator separation despite using all annotators' data, suggesting that target behavior is better captured in separate adapted parameters than recovered from symbolic IDs; see Appendix D.2.

4.3 Cross-Annotator Preference Optimization

We propose CAPO that continues training from the corresponding SFT adapter for annotator a and uses cross-annotator variation as contrastive preference supervision. For an input x_i, the chosen response is the target annotator's annotation $z^+ = z_{i,a}$ and the rejected response is another annotator's annotation $z^- = z_{i,b}$ for the same input, with $b \neq a$. The rejected response is not treated as wrong; it is a valid human alternative that is less target-specific under the goal of imitating annotator a.

Let π_{θ_a} be the trainable CAPO policy initialized from $\pi_{\theta_a}^{\text{SFT}}$, and let $\pi_{\text{ref},a} = \pi_{\theta_a}^{\text{SFT}}$ be the frozen reference policy. Define:

$$
\begin{aligned}
r_{\theta_a}(z; x_i, a) = {} & \log \pi_{\theta_a}(z \mid x_i, a) \\
& - \log \pi_{\text{ref},a}(z \mid x_i, a),
\end{aligned} \quad (5)
$$

CAPO optimizes a DPO-style loss (Rafailov et al., 2023):

$$
\begin{aligned}
\mathcal{L}_{\text{CAPO}} = - \log \sigma \Big(\beta \big[& r_{\theta_a}(z^+; x_i, a) \\
& - r_{\theta_a}(z^-; x_i, a) \big] \Big).
\end{aligned} \quad (6)
$$

This turns variation among valid human annotations into supervision for target-specific adaptation, rather than into a quality ranking among annotators.

Pair construction. We use conservative pair policies so that CAPO cannot rely only on large label or score differences. For VariErr, the main policy pairs annotations with the same NLI label, $y_{i,a} = y_{i,b}$, making the preference signal primarily explanation-based. For R2, where exact equality is too sparse over the 11-point scale, we require $|s_{i,a} - s_{i,b}| \leq 1$. Pair counts and policy ablations are reported in Appendices B.3 and E.1.

Checkpoint selection. Because CAPO targets recognizable annotator-specific behavior rather than likelihood alone, we select checkpoints with an aggregation-aware development criterion. For each candidate checkpoint, we generate development outputs for each target annotator and choose the checkpoint whose output groups receive the highest target-annotator confidence from a group classifier trained only on train set, which follows Section 3 that annotator-specific behavior is more reliable at the group level than at the single-output level. The selector does not use test outputs or classifiers trained on test annotations; implementation details and ablations are in Appendix E.2.

View	Evaluates	Main metrics	Main limitation
Decision	task decision agreement	Acc; MAE	ignores reasoning style
Reference	explanation overlap	ROUGE-L; BERTScore; EmbSim	input content can dominate
Imitation	annotator-specific behavior	Feature KL; GC; Judge Acc	single instances are ambiguous

Table 3: Evaluation views. Our main claim concerns annotator imitation, but we interpret it alongside decision matching and reference-based explanation similarity.

4.4 Evaluation Metrics

We evaluate simulation from three complementary views as in Table 3: decision matching, explanation similarity, and annotator recognizability. Following Section 3, we treat annotator-specificity as a repeated behavior, and therefore complement single-output metrics with aggregation-aware metrics.

Decision matching. For VariErr, we report label accuracy against the target annotator. For R2, we report exact score accuracy and score mean absolute error (MAE). These metrics test whether the model matches the annotator's task decision.

Reference-based explanation similarity. Generated explanations are compared with the target annotator's reference explanation by ROUGE-L (Lin, 2004), BERTScore (Zhang et al., 2020), and embedding cosine similarity (Reimers and Gurevych, 2019), following Giulianelli et al. (2023). These metrics capture lexical and semantic overlap, but also reward input content shared across annotators.

Aggregation-aware evaluation. We use group-level metrics motivated by Section 3. First, we compute mean KL divergence between generated and human distributions of handcrafted explanation-style features, measuring whether a method reproduces repeated stylistic tendencies such as length, lexical reuse, and uncertainty marking.

Second, we evaluate whether generated outputs are recognizable as the intended annotator using a held-out group classifier (GC). For each method and target annotator, we form bootstrapped groups of generated outputs, classify their aggregated representations, and report GC confidence: the mean probability assigned to the intended annotator. We also report a normalized imitation score:

$$
\text{ImiScore}(M, a) = \frac{C_a(M_a) - C_a(M_{\neg a})}{C_a(H_a) - C_a(M_{\neg a})}, \quad (7)
$$

where $C_a(\cdot)$ is the classifier probability assigned to annotator a, M_a denotes outputs generated for annotator a, $M_{\neg a}$ denotes outputs from the same method targeting other annotators, and H_a denotes human references from annotator a. ImiScore near

Model	Method	VariErr						R2						
		Label Acc ↑	ROUGE-L ↑	Feature KL ↓	GC Conf ↑	ImiScore ↑	Judge Acc ↑	Score Acc ↑	Score MAE ↓	ROUGE-L ↑	Feature KL ↓	GC Conf ↑	ImiScore ↑	Judge Acc ↑
Qwen3	Base	0.472	0.159	2.394	0.239	-0.034	0.237	0.292	2.453	0.071	5.188	0.248	-0.004	0.237
	ICL	0.535	0.186	0.692	0.344	0.179	0.265	0.407	1.702	0.197	0.587	0.809	0.810	0.463
	VP	0.492	0.131	4.391	0.234	-0.348	0.240	0.278	2.475	0.100	2.740	0.649	0.651	0.360
	VP-ICL	0.545	0.201	0.476	0.494	0.528	0.282	0.415	1.667	0.276	0.246	0.947	0.956	0.510
	SFT	**0.638**	**0.283**	0.084	0.845	0.859	0.300	0.450	**1.478**	0.307	0.130	0.929	0.936	0.512
	CAPO	0.627	0.281	**0.081**	**0.867**	**0.888**	**0.328**	**0.455**	1.490	**0.316**	**0.112**	**0.964**	**0.973**	**0.560**
Llama3.2	Base	0.315	0.153	2.036	0.258	0.023	0.265	0.207	3.188	0.068	1.515	0.255	0.015	0.230
	ICL	0.380	0.214	0.476	0.295	0.375	0.260	0.273	3.333	0.213	0.480	0.871	0.879	0.367
	VP	0.338	0.148	1.907	0.358	0.325	0.253	0.180	4.185	0.098	0.913	0.359	0.175	0.260
	VP-ICL	0.412	0.210	0.539	0.260	0.432	0.275	0.273	3.390	0.230	0.257	0.858	0.865	0.370
	SFT	**0.512**	**0.271**	**0.113**	0.909	0.946	0.282	0.450	1.535	0.290	**0.118**	0.963	0.972	0.512
	CAPO	**0.512**	0.262	0.121	**0.924**	**0.964**	**0.297**	**0.460**	**1.470**	**0.293**	0.187	**0.985**	**0.995**	**0.530**

Table 4: Main results report overall averages across annotators, with ROUGE-L as the representative similarity metric since BERTScore and EmbSim show the same pattern. We interpret higher GC Conf and Judge Acc as stronger preservation of annotator-specific reasoning patterns. CAPO generally improves imitation metrics while maintaining competitive decision accuracy; bootstrap significance tests in Appendix D.3 further show higher mean ImiScore than SFT in all settings. Complete metrics and setting results are provided in Appendix D.

0 indicates no gain over non-target generated outputs, near 1 indicates human-level recognizability, and above 1 indicates amplified recognizability. See details and robustness checks in Appendix B.4.

LLM-as-judge. As an item-level complement to GC, we use DeepSeek V4 Pro as a single-instance attribution judge (DeepSeek-AI, 2026). Given a generated decision and explanation, together with four shuffled human annotator candidates for the same item, the judge selects the candidate the output most resembles. We report accuracy against the intended annotator, with details in Appendix B.5.

5 Results and Analyses

5.1 Main Results

Table 4 reports results on VariErr and R2. Across both datasets and models, performance improves from frozen prompting to parameter-based simulation. Prompting recovers limited annotator signal when demonstrations are included, with VP-ICL generally the strongest; profile-only prompting is less reliable, suggesting that compact summaries miss fine-grained label-explanation behavior.

SFT substantially outperforms prompting, showing that annotator-specific behavior is learnable from repeated histories. CAPO further improves imitation-oriented metrics while maintaining competitive decision accuracy. Since its preference pairs control for label or score differences, these gains are unlikely to come from decisions alone, but instead reflect sharper explanation-grounded target specificity. The divergence across decision, reference-similarity, and imitation metrics shows that annotator simulation requires behavior-level evaluation beyond label matching or single-reference explanation overlap.

Figure 6: CAPO policy and checkpoint effects. Panels (a) and (b) show how pair-policy looseness affects the accuracy-imitation trade-off. Panels (c) and (d) compare checkpoint-selection strategies using judge-based imitation, which is not the selection criterion.

5.2 Policy and Selection Effects

Figure 6 summarizes CAPO pair-policy and checkpoint-selection ablations, with full results in Appendix E. CAPO constructs preference pairs within each input instance, using the target annotator's label-explanation pair as chosen and another annotator's pair as rejected. Pair policies control decision similarity: VariErr uses same-label pairs under the strict policy, while looser variants allow near-label or unrestricted pairs; R2 uses same-score pairs under the strict policy and tolerance-k pairs otherwise. Although looser policies may improve recognizability by creating stronger contrasts, they can introduce label or score confounds. We therefore adopt conservative settings in the main experiments: strict same-label pairs for VariErr and tolerance-1 pairs for R2, emphasizing explanation framing and target-specific reasoning.

Checkpoint-selection results provide a sanity

Case	Premise	Hypothesis	Gold Explanation	SFT Explanation	CAPO Explanation
1	I guess history repeats itself, Jane.	I truly think the prior situation shows history repeats itself.	The context doesn't specify what shows that history repeats itself.	Both the context and the statement suggest that history repeats itself.	The context doesn't mention what the speaker truly thinks.

Observation: SFT mainly follows lexical overlap between the premise and hypothesis, whereas CAPO moves closer to the gold rationale by identifying unsupported information introduced by the hypothesis.

| 2 | He's a bad lot. | He's a dishonest person. | Bad people can be both honest and dishonest. | He can be a dishonest person, but he can also be a good person. | He's a bad lot, but he can be honest or dishonest. |

Observation: Both systems produce neutral-style explanations, but CAPO preserves the relevant distinction between being "bad" and being specifically dishonest, while SFT introduces the irrelevant alternative of being good.

Table 5: Case study comparing SFT and CAPO on VariErr. Case study for R2 is in Appendix G.1.

Setting	Feature	SFT KL	CAPO KL
Qwen-VariErr	`avg_sent_len`	0.1127	0.0233
Qwen-VariErr	`modal_rate`	0.1795	0.1274
Qwen-R2	`len_chars`	0.1691	0.0256
Qwen-R2	`type_token_ratio`	0.1394	0.1111

Table 6: Representative feature-wise KL.

check. Although CAPO selects checkpoints using a group classifier trained only on human training annotations, the selected checkpoints remain competitive under Judge Acc, which is not used for selection. This suggests that CAPO's gains are not merely artifacts of optimizing the group-classifier-style metric. The ablations also show that CAPO moves models along an accuracy–imitation frontier rather than uniformly improving all metrics.

5.3 Feature Shifts

To interpret what changes under CAPO, we report representative feature-wise KL shifts in Table 6, with full results in Appendix F. CAPO reduces distribution shift across several interpretable dimensions, including length, sentence structure, modal expressions, and lexical diversity. This suggests that CAPO improves alignment with multiple aspects of annotator-specific style rather than amplifying a single marker. Because the effect is not uniform across all settings, we treat Feature KL as a diagnostic rather than an optimization target.

5.4 Human Validation

We validate whether aggregation-aware gains correspond to human-recognizable explanation quality on 50 VariErr samples. Two annotators evaluate coherence, input grounding, gold-explanation compatibility, and similarity to the target annotator's style and perspective. Both produce the same system ranking, CAPO > SFT > prompting, with 82.8% agreement; see Appendix G. This suggests that CAPO improves not only automatic imitation metrics, but also perceived explanation validity and target specificity.

Case study. Table 5 illustrates how these gains arise. CAPO better preserves the gold annotator's reasoning focus, while SFT more often relies on shallow lexical overlap or introduces irrelevant contrasts. Thus, CAPO's higher GC Conf and ImiScore reflect more recognizable target-annotator behavior, rather than merely higher surface similarity.

Profile study. To interpret what annotator-level variation captures, we compare LLM-generated profiles in Appendix H with manual behavioral characterizations in Appendix G.2. We do not attribute these differences to demographics, education, or psychological traits. Instead, the profiles reveal recurring task interpretations and explanation strategies, such as evidence checking, uncertainty handling, underspecification sensitivity, aspect-level comparison, and answer-equivalence reasoning. This helps explain why features such as length, modality, first-person use, and input reuse form stable signals rather than random noise.

6 Conclusion

We studied whether human label variation can be learned as annotator-specific label-explanation behavior rather than only as label disagreement. We showed that such behavior is weak and content-entangled at the single-instance level, but becomes a stable and recoverable signal when aggregated across items. Building on this finding, we proposed CAPO, which improves aggregation-aware annotator-specific modeling and attribution metrics while maintaining competitive decision accuracy across two sentence-pair tasks, showing that variation among annotators can be used as supervision for scalable, explanation-based HLV generation. More broadly, our results call for annotator simulation to move beyond single-reference matching toward behavior-level modeling and evaluation, while guarding against over-amplifying recognizable annotator markers.

Limitations

Sensitivity to annotator-pool size. CAPO's effectiveness may depend on the size and composition of the annotator pool. Our experiments use four annotators per item, where each rejected candidate is a valid alternative annotation from a small pool and the contrastive signal remains relatively clean. In larger crowdsourcing settings, the pair distribution may change substantially: easy negatives can dilute fine-grained explanation-style learning, while near-duplicate same-label negatives can incorrectly penalize reasonable variants of the target annotator's behavior. Thus, CAPO may not scale monotonically with the number of annotators. Extending CAPO to large annotator pools likely requires difficulty-aware rejected-candidate sampling, such as selecting same-label negatives at an intermediate explanation-embedding distance from the target annotation. We leave this direction for future work.

Data-regime and scaling analysis. Our experiments are conducted with hundreds of training annotations per annotator, providing a useful setting for testing whether annotator-specific label-explanation behavior can be learned from repeated histories. An important next step is to explore how this behavior emerges under different data regimes. For example, low-resource ablations with 50, 100, or 200 annotations per annotator could test whether CAPO is especially helpful when direct target-annotator supervision is limited, since cross-annotator comparisons may provide additional relative signal beyond likelihood-based SFT. Conversely, larger-scale studies could examine how SFT and CAPO change as the number of target examples, annotators, domains, or valid cross-annotator pairs increases. Such experiments would make it possible to characterize when SFT is sufficient, when CAPO provides the largest gains, and how pair construction should evolve as more contrastive supervision becomes available.

Generalization to new annotators. Our current setup assumes that each target annotator has enough label-explanation history to support an independent adapter. In practical annotation workflows, however, new annotators may enter the pool with only a small number of examples. This creates a promising cold-start and few-shot adaptation problem: given a few annotations from a new annotator, can the model infer an effective annotator representation, initialize an adapter from similar existing annotators, or compose a new adapter from previously learned behavioral directions? Future work could study adapter retrieval, adapter interpolation, meta-learned initializations, or hybrid approaches that combine profile prompting with lightweight parameter updates. These extensions would make annotator-specific explanation generation more applicable to evolving annotation pools.

Ethical Considerations

Our goal is to preserve and model human label variation for analysis, not to impersonate individual annotators. Annotator IDs should remain anonymized, and models trained to imitate annotators should only be used under appropriate consent and data-governance conditions. Because annotator-specific behavior may encode demographic, cultural, ideological, or other sensitive patterns, such models should not be used to infer private attributes or to replace human judgment in high-stakes settings. Preference optimization over annotator differences can also amplify artifacts; imitation scores above the human-reference scale should therefore be interpreted as increased recognizability, not as better or more authentic human behavior.

Reproducibility and responsible release. We will release all code, prompts, evaluation scripts, and model-training configurations at publication time to support reproducibility. Any released artifacts will preserve annotator anonymity and exclude private or non-redistributable annotation content.

Use of AI Assistants. The authors acknowledge the use of ChatGPT solely for correcting grammatical errors, enhancing the coherence of the final manuscript.

References

Andy Arditi, Oscar Obeso, Aaquib Syed, Daniel Paleka, Nina Panickssery, Wes Gurnee, and Neel Nanda. 2024. Refusal in language models is mediated by a single direction. In *Advances in Neural Information Processing Systems 38: Annual Conference on Neural Information Processing Systems 2024, NeurIPS 2024, Vancouver, BC, Canada, December 10 - 15, 2024.*

Shlomo Argamon, Moshe Koppel, James W. Pennebaker, and Jonathan Schler. 2009. Automatically

profiling the author of an anonymous text. *Commun. ACM*, 52(2):119–123.

Lisa P. Argyle, Ethan C. Busby, Nancy Fulda, Joshua Gubler, Christopher Michael Rytting, and David Wingate. 2022. Out of one, many: Using language models to simulate human samples. *CoRR*, abs/2209.06899.

Lora Aroyo and Chris Welty. 2015. Truth is a lie: Crowd truth and the seven myths of human annotation. *AI Mag.*, 36(1):15–24.

Valerio Basile, Michael Fell, Tommaso Fornaciari, Dirk Hovy, Silviu Paun, Barbara Plank, Massimo Poesio, and Alexandra Uma. 2021. We need to consider disagreement in evaluation. In *Proceedings of the 1st Workshop on Benchmarking: Past, Present and Future*, pages 15–21, Online. Association for Computational Linguistics.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, and 12 others. 2020. Language models are few-shot learners. In *Advances in Neural Information Processing Systems 33: Annual Conference on Neural Information Processing Systems 2020, NeurIPS 2020, December 6-12, 2020, virtual*.

Federico Cabitza, Andrea Campagner, and Valerio Basile. 2023. Toward a perspectivist turn in ground truthing for predictive computing. In *Thirty-Seventh AAAI Conference on Artificial Intelligence, AAAI 2023, Thirty-Fifth Conference on Innovative Applications of Artificial Intelligence, IAAI 2023, Thirteenth Symposium on Educational Advances in Artificial Intelligence, EAAI 2023, Washington, DC, USA, February 7-14, 2023*, pages 6860–6868. AAAI Press.

Beiduo Chen, Tiancheng Hu, Caiqi Zhang, Robert Litschko, Anna Korhonen, and Barbara Plank. 2026. Decoupling the effect of chain-of-thought reasoning: A human label variation perspective. *CoRR*, abs/2601.03154.

Beiduo Chen, Yang Janet Liu, Anna Korhonen, and Barbara Plank. 2025a. Threading the needle: Reweaving chain-of-thought reasoning to explain human label variation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 33111–33135, Suzhou, China. Association for Computational Linguistics.

Beiduo Chen, Siyao Peng, Anna Korhonen, and Barbara Plank. 2025b. A rose by any other name: LLM-generated explanations are good proxies for human explanations to collect label distributions on NLI. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 10777–10802, Vienna, Austria. Association for Computational Linguistics.

Beiduo Chen, Xinpeng Wang, Siyao Peng, Robert Litschko, Anna Korhonen, and Barbara Plank. 2024. "seeing the big through the small": Can LLMs approximate human judgment distributions on NLI from a few explanations? In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pages 14396–14419, Miami, Florida, USA. Association for Computational Linguistics.

Tongfei Chen, Zhengping Jiang, Adam Poliak, Keisuke Sakaguchi, and Benjamin Van Durme. 2020. Uncertain natural language inference. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 8772–8779, Online. Association for Computational Linguistics.

Myra Cheng, Esin Durmus, and Dan Jurafsky. 2023. Marked personas: Using natural language prompts to measure stereotypes in language models. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1504–1532, Toronto, Canada. Association for Computational Linguistics.

Jacob Cohen. 1960. A coefficient of agreement for nominal scales. *Educational and psychological measurement*, 20(1):37–46.

Aida Mostafazadeh Davani, Mark Díaz, and Vinodkumar Prabhakaran. 2022. Dealing with disagreements: Looking beyond the majority vote in subjective annotations. *Trans. Assoc. Comput. Linguistics*, 10:92–110.

DeepSeek-AI. 2026. Deepseek-v4: Towards highly efficient million-token context intelligence.

Ameet Deshpande, Vishvak Murahari, Tanmay Rajpurohit, Ashwin Kalyan, and Karthik Narasimhan. 2023. Toxicity in chatgpt: Analyzing persona-assigned language models. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 1236–1270, Singapore. Association for Computational Linguistics.

Richárd Farkas, Veronika Vincze, György Móra, János Csirik, and György Szarvas. 2010. The CoNLL-2010 shared task: Learning to detect hedges and their scope in natural language text. In *Proceedings of the Fourteenth Conference on Computational Natural Language Learning – Shared Task*, pages 1–12, Uppsala, Sweden. Association for Computational Linguistics.

Fabrizio Gilardi, Meysam Alizadeh, and Maël Kubli. 2023. Chatgpt outperforms crowd-workers for text-annotation tasks. *CoRR*, abs/2303.15056.

Mario Giulianelli, Joris Baan, Wilker Aziz, Raquel Fernández, and Barbara Plank. 2023. What comes next? evaluating uncertainty in neural text generators against human production variability. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 14349–14371, Singapore. Association for Computational Linguistics.

Suchin Gururangan, Swabha Swayamdipta, Omer Levy, Roy Schwartz, Samuel Bowman, and Noah A. Smith. 2018. Annotation artifacts in natural language inference data. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 2 (Short Papers)*, pages 107–112, New Orleans, Louisiana. Association for Computational Linguistics.

Pingjun Hong, Beiduo Chen, Siyao Peng, Marie-Catherine de Marneffe, and Barbara Plank. 2025a. LiTEx: A linguistic taxonomy of explanations for understanding within-label variation in natural language inference. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 34065–34085, Suzhou, China. Association for Computational Linguistics.

Pingjun Hong, Beiduo Chen, Siyao Peng, Marie-Catherine de Marneffe, Benjamin Roth, and Barbara Plank. 2025b. Agree, disagree, explain: Decomposing human label variation in NLI through the lens of explanations. *CoRR*, abs/2510.16458.

Edward J. Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, and Weizhu Chen. 2022. Lora: Low-rank adaptation of large language models. In *The Tenth International Conference on Learning Representations, ICLR 2022, Virtual Event, April 25-29, 2022*. OpenReview.net.

Nan-Jiang Jiang, Chenhao Tan, and Marie-Catherine de Marneffe. 2023. Ecologically valid explanations for label variation in NLI. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 10622–10633, Singapore. Association for Computational Linguistics.

Nanjiang Jiang and Marie-Catherine de Marneffe. 2022. Investigating reasons for disagreement in natural language inference. *Trans. Assoc. Comput. Linguistics*, 10:1357–1374.

Moshe Koppel, Jonathan Schler, and Shlomo Argamon. 2009. Computational methods in authorship attribution. *J. Assoc. Inf. Sci. Technol.*, 60(1):9–26.

Elisa Leonardelli, Silvia Casola, Siyao Peng, Giulia Rizzi, Valerio Basile, Elisabetta Fersini, Diego Frassinelli, Hyewon Jang, Maja Pavlovic, Barbara Plank, and Massimo Poesio. 2025. LeWiDi-2025 at NLPerspectives: Third edition of the learning with disagreements shared task. In *Proceedings of the The 4th Workshop on Perspectivist Approaches to NLP*, pages 182–195, Suzhou, China. Association for Computational Linguistics.

Chin-Yew Lin. 2004. ROUGE: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pages 74–81, Barcelona, Spain. Association for Computational Linguistics.

Junyu Lu, Deyi Ji, Xuanyi Liu, Lanyun Zhu, Bo Xu, Liang Yang, and Hongfei Lin. 2026. Aligning llm uncertainty with human disagreement in subjectivity analysis. *arXiv preprint arXiv:2605.10415*.

R. Thomas McCoy, Ellie Pavlick, and Tal Linzen. 2019. Right for the wrong reasons: Diagnosing syntactic heuristics in natural language inference. In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 3428–3448, Florence, Italy. Association for Computational Linguistics.

Alberto Muñoz-Ortiz, Carlos Gómez-Rodríguez, and David Vilares. 2024. Contrasting linguistic patterns in human and llm-generated news text. *Artif. Intell. Rev.*, 57(9):265.

Yixin Nie, Xiang Zhou, and Mohit Bansal. 2020. What can we learn from collective human opinions on natural language inference data? In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 9131–9143, Online. Association for Computational Linguistics.

Matthias Orlikowski, Jiaxin Pei, Paul Röttger, Philipp Cimiano, David Jurgens, and Dirk Hovy. 2025. Beyond demographics: Fine-tuning large language models to predict individuals' subjective text perceptions. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2092–2111, Vienna, Austria. Association for Computational Linguistics.

Matthias Orlikowski, Paul Röttger, Philipp Cimiano, and Dirk Hovy. 2023. The ecological fallacy in annotation: Modeling human label variation goes beyond sociodemographics. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 1017–1029, Toronto, Canada. Association for Computational Linguistics.

Solmaz Panahi, John Kelleher, and Vasudevan Nedumpozhimana. 2026. When LLMs annotate: Reliability challenges in low-resource NLI. In *Proceedings of the Second Workshop on Language Models for Low-Resource Languages (LoResLM 2026)*, pages 178–188, Rabat, Morocco. Association for Computational Linguistics.

Joon Sung Park, Joseph C. O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S. Bernstein. 2023. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th Annual ACM Symposium on User Interface Software and Technology, UIST 2023, San Francisco, CA, USA, 29 October 2023- 1 November 2023*, pages 2:1–2:22. ACM.

Ellie Pavlick and Tom Kwiatkowski. 2019. Inherent disagreements in human textual inferences. *Transactions of the Association for Computational Linguistics*, 7:677–694.

Fabian Pedregosa, Gaël Varoquaux, Alexandre Gramfort, Vincent Michel, Bertrand Thirion, Olivier Grisel, Mathieu Blondel, Peter Prettenhofer, Ron Weiss, Vincent Dubourg, Jake VanderPlas, Alexandre Passos, David Cournapeau, Matthieu Brucher, Matthieu Perrot, and Edouard Duchesnay. 2011. Scikit-learn:

Machine learning in python. *J. Mach. Learn. Res.*, 12:2825–2830.

Krishna Pillutla, Swabha Swayamdipta, Rowan Zellers, John Thickstun, Sean Welleck, Yejin Choi, and Zaïd Harchaoui. 2021. MAUVE: measuring the gap between neural text and human text using divergence frontiers. In *Advances in Neural Information Processing Systems 34: Annual Conference on Neural Information Processing Systems 2021, NeurIPS 2021, December 6-14, 2021, virtual*, pages 4816–4828.

Barbara Plank. 2022. The "problem" of human label variation: On ground truth in data, modeling and evaluation. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 10671–10682, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Barbara Plank, Dirk Hovy, and Anders Søgaard. 2014. Learning part-of-speech taggers with inter-annotator agreement loss. In *Proceedings of the 14th Conference of the European Chapter of the Association for Computational Linguistics*, pages 742–751, Gothenburg, Sweden. Association for Computational Linguistics.

Daniel Preoţiuc-Pietro, Ye Liu, Daniel Hopkins, and Lyle Ungar. 2017. Beyond binary labels: Political ideology prediction of Twitter users. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 729–740, Vancouver, Canada. Association for Computational Linguistics.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D. Manning, Stefano Ermon, and Chelsea Finn. 2023. Direct preference optimization: Your language model is secretly a reward model. In *Advances in Neural Information Processing Systems 36: Annual Conference on Neural Information Processing Systems 2023, NeurIPS 2023, New Orleans, LA, USA, December 10 - 16, 2023*.

Sara Rajaee, Yadollah Yaghoobzadeh, and Mohammad Taher Pilehvar. 2022. Looking at the overlooked: An analysis on the word-overlap bias in natural language inference. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 10605–10616, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

Nils Reimers and Iryna Gurevych. 2019. Sentence-BERT: Sentence embeddings using Siamese BERT-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 3982–3992, Hong Kong, China. Association for Computational Linguistics.

Pablo Rosillo-Rodes, Maxi San Miguel, and David Sanchez. 2024. Entropy and type-token ratio in gigaword corpora. *CoRR*, abs/2411.10227.

Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. 2023. Whose opinions do language models reflect? In *International Conference on Machine Learning, ICML 2023, 23-29 July 2023, Honolulu, Hawaii, USA*, Proceedings of Machine Learning Research, pages 29971–30004. PMLR.

Taylor Sorensen, Pushkar Mishra, Roma Patel, Michael Henry Tessler, Michiel A. Bakker, Georgina Evans, Iason Gabriel, Noah Goodman, and Verena Rieser. 2025. Value profiles for encoding human variation. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pages 2047–2095, Suzhou, China. Association for Computational Linguistics.

Efstathios Stamatatos. 2009. A survey of modern authorship attribution methods. *J. Assoc. Inf. Sci. Technol.*, 60(3):538–556.

Llama Team. 2024. The llama 3 herd of models. *CoRR*, abs/2407.21783.

Qwen Team. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Juan J Vazquez, Ulisse Mini, and Monte MacDiarmid. 2023. Steering language models with activation engineering. *arXiv preprint arXiv:2308.10248*.

Alexandra Uma, Tommaso Fornaciari, Dirk Hovy, Silviu Paun, Barbara Plank, and Massimo Poesio. 2021. Learning from disagreement: A survey. *J. Artif. Intell. Res.*, 72:1385–1470.

Xinpeng Wang and Barbara Plank. 2023. ACTOR: Active learning with annotator-specific classification heads to embrace human label variation. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pages 2046–2052, Singapore. Association for Computational Linguistics.

Leon Weber-Genzel, Siyao Peng, Marie-Catherine De Marneffe, and Barbara Plank. 2024. VariErr NLI: Separating annotation error from human label variation. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 2256–2269, Bangkok, Thailand. Association for Computational Linguistics.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. Bertscore: Evaluating text generation with BERT. In *8th International Conference on Learning Representations, ICLR 2020, Addis Ababa, Ethiopia, April 26-30, 2020*. OpenReview.net.

Xiang Zhou, Yixin Nie, and Mohit Bansal. 2022. Distributed NLI: Learning to predict human opinion distributions for language reasoning. In *Findings of the Association for Computational Linguistics: ACL 2022*, pages 972–987, Dublin, Ireland. Association for Computational Linguistics.

Longfei Zuo, Barbara Plank, and Siyao Peng. 2025. EVADE: llm-based explanation generation and validation for error detection in NLI. *CoRR*, abs/2511.08949.

A Prompt and Output Formats

This appendix records the prompt templates implemented in the experiment scripts. The prompt-based baselines use the same task templates as the fine-tuned models, with optional demonstrations or profiles prepended. In the base prompt, `Annotator_{a}` is an ungrounded symbolic ID; no examples or profile are provided.

A.1 VariErr Task Prompt

```
VariErr task prompt

You are Annotator_{a}.
Follow this annotator's specific
language style and reasoning habits.

Premise:
{premise}

Hypothesis:
{hypothesis}

Please provide the NLI label and
a concise explanation.

Output format:
Label: Entailment, Neutral, or
Contradiction
Explanation: <concise explanation>
```

For independent SFT and independent CAPO, the target annotator is represented by the adapter rather than by an explicit ID. The corresponding instruction replaces the first sentence with:

```
Adapter-based VariErr instruction

You are a human NLI annotator.
Follow your learned language style
and reasoning habits.
```

A.2 R2 Task Prompt

```
R2 task prompt

You are Annotator_{a}.
Follow this annotator's specific
language style and reasoning habits.

Question 1:
{question1}

Question 2:
{question2}

Assign a Likert score from -5 to 5
indicating how strongly the two
questions are paraphrases of one
another, then provide a concise
explanation.
-5 means definitely not paraphrases,
0 means uncertain or mixed, and
5 means definitely paraphrases.

Output format:
Score: <integer from -5 to 5>
```

```
Explanation: <concise explanation>
```

A.3 ICL Demonstrations

ICL prepends 50 target-annotator examples sampled from the train split. Each example contains the task input without the output-format block, followed by the target annotator's label or score and explanation.

```
ICL demonstration format

Here are examples of this annotator's
previous labels and explanations.

Example k
Input:
...

Annotator_{a} answer:
Label/Score: ...
Explanation: ...

Now annotate the following item.
...
```

A.4 Value Profile Construction

The direct profile baseline asks the same model family to summarize 50 target-annotator training annotations.

```
Value profile construction prompt

Summarize Annotator_{a}'s annotation
behavior from the following examples.
Focus on label/score bias, value
judgment criteria, evidence usage,
explanation style, wording,
strictness, uncertainty, and quirks.
Write a compact profile that can guide
another LLM to imitate this annotator.
Do not predict labels for the samples.
```

At inference time, VP and VP-ICL prepend:

```
Value profile inference prefix

Use the following value/style profile
for this annotator when deciding the
label/score and writing the explanation.

Annotator_{a} profile:
{profile}
```

A.5 CAPO Format

```
CAPO preference-pair format
```

CAPO uses the same task prompt as SFT. For each target annotator a, the chosen response is the target annotator's formatted label/score and explanation. The rejected response is another annotator's formatted label/score and explanation for the same item.

Dataset	Split	Items	Explanations	Complete Items
VariErr	train	300	1,055	194
	dev	100	400	100
	test	100	400	100
R2	train	300	1,200	300
	dev	100	400	100
	test	100	400	100

Table 7: Dataset splits used by all methods. VariErr train contains missing annotator explanations for some items; dev and test are complete four-annotator splits.

B Implementation Details

B.1 Data Splits

Statistics of the two datasets are listed in Table 7. For independent SFT, the number of VariErr train examples per annotator is 257, 265, 251, and 282 for annotators 0–3. R2 has 300 train examples for each annotator. Dev contains 100 examples per annotator for both datasets. VariErr has 1,055 usable training judgments because some train items are missing annotator rows, while dev and test contain four judgments per item. R2 contains 1,200/400/400 train/dev/test judgments. Both datasets are in English.

B.2 Models and Training Hyperparameters

All the hyperparameters are elaborated in Table 8. Training is conducted on a single NVIDIA A100-SXM4-80GB GPU. SFT training takes an average of 30 minutes per setting, while CAPO training takes an average of 50 minutes per setting.

B.3 CAPO Pair Construction and Pair Counts

CAPO pairs are ordered same-item pairs. For a target annotator a, the chosen response is a's annotation and the rejected response is another annotator's annotation for the same input. Pair builders balance the final training set by target annotator. Table 9 reports the number of train pairs after balancing; candidate counts before balancing are included to show how restrictive each policy is.

VariErr strict requires identical NLI labels; near-label adds entailment–neutral and neutral–contradiction pairs; no restriction allows any cross-annotator label pair. R2 strict requires identical scores, while tol1–tol3 require score distance at most 1–3. All the ablation experimental results are in Appendix E.

B.3.1 Theoretical Sensitivity of CAPO to Annotator Pool Size

CAPO constructs preferences from cross-annotator variation on the same input. For a target annotator a, the chosen response is the target annotator's annotation $z^+ = z_{i,a}$, while the rejected response is another annotator's annotation $z^- = z_{i,b}$ for $b \neq a$. Following the DPO-style objective used in the main method, we write the reward difference relative to the SFT reference model as

$$r_{\theta_a}(z; x_i, a) = \log \pi_{\theta_a}(z \mid x_i, a) \\ - \log \pi_{\text{ref},a}(z \mid x_i, a). \tag{8}$$

The CAPO loss for annotator a is then

$$\mathcal{L}_{\text{CAPO}}(a) = -\mathbb{E}_{(x_i, z^+, z^-)}\Big[\log \sigma\big(\beta \Delta r_{\theta_a}\big)\Big], \tag{9}$$

where

$$\Delta r_{\theta_a} = r_{\theta_a}(z^+; x_i, a) \\ - r_{\theta_a}(z^-; x_i, a). \tag{10}$$

When the annotator pool size is N, each input provides $N-1$ possible rejected responses for each target annotator. The empirical CAPO objective can therefore be approximated as

$$\mathcal{L}_{\text{CAPO}}(a) \approx \frac{1}{|\mathcal{D}_a|} \sum_{x_i \in \mathcal{D}_a} \ell_i(a), \tag{11}$$

with the per-input loss

$$\ell_i(a) = -\frac{1}{N-1} \sum_{b \neq a} \log \sigma\Big(\beta\big(r_{\theta_a}(z_{i,a}; x_i, a) \\ - r_{\theta_a}(z_{i,b}; x_i, a)\big)\Big). \tag{12}$$

This formulation exposes three ways in which CAPO depends on the annotator pool size.

Variance and bias of the contrastive signal. When N is very small, each target annotation has only a few possible rejected responses. In the extreme case of $N = 2$, each input provides only one rejected candidate. The resulting training signal may have high variance: if the only available rejected annotator happens to produce an annotation that is very close to the target annotator on a particular item, the pair provides little useful discriminative signal. As N increases, the rejected pool becomes larger and the empirical estimate in Eq. 12 becomes more stable. However, increasing N also changes the distribution of rejected candidates, which affects the strength and type of contrastive signal.

Component	Setting
Base models	`Qwen3-4B-Instruct-2507`; `Llama-3.2-3B-Instruct`
Prompting decode	temperature 0.0, top-p 1.0, max new tokens 180, max input length 8192
SFT decode	temperature 0.0, top-p 1.0, max new tokens 160, max input length 1536
SFT adapters	LoRA rank 32, alpha 64, dropout 0.05, target modules q/k/v/o/gate/up/down projections
SFT optimization	5 epochs, learning rate 2×10^{-5}, batch size 1, gradient accumulation 16, cosine schedule, warmup 0.03
CAPO initialization	Continue training from the corresponding independent SFT adapter
CAPO objective	DPO-style loss with $\beta = 0.1$, one epoch, learning rate 1×10^{-6} for independent adapters
CAPO optimization	batch size 1, gradient accumulation 8, max prompt length 1024, max length 1536, eval/save every 10 steps
Checkpoint selection	Main CAPO results use train-only group-classifier selection; dev-loss and last checkpoints are ablations
Precision	bf16 with gradient checkpointing; 4-bit loading disabled in the selected runs

Table 8: Implementation settings reflected in the training and generation scripts.

Dataset	Policy	Cand.	Train	Min/ann.	Max/ann.
VariErr	strict	1,736	1,700	425	425
VariErr	near-label	2,718	2,668	667	667
VariErr	no restriction	2,816	2,740	685	685
R2	strict	992	840	210	210
R2	tol1	1,874	1,476	369	369
R2	tol2	2,256	1,816	454	454
R2	tol3	2,426	2,000	500	500
R2	no restriction	3,600	3,600	900	900

Table 9: CAPO training pair counts for independent pair files. VariErr strict and R2 tol1 are the main policies.

Annotator similarity and contrastive margin. Let the reward margin for a target annotator a against another annotator b be

$$m_{i,a,b} = r_{\theta_a}(z_{i,a}; x_i, a) \\ - r_{\theta_a}(z_{i,b}; x_i, a). \quad (13)$$

CAPO is most informative when rejected responses are different enough from the target response to create a meaningful preference, but not so different that the comparison becomes trivial. With a small curated annotator pool, such as the $N = 4$ setting used in our experiments, annotators may share substantial task understanding and explanation conventions. This can make the margin smaller, requiring CAPO to learn fine-grained target-specific differences. With a larger pool, the rejected set is more diverse and may contain easier negatives whose style is clearly different from the target annotator. These easy negatives can increase the apparent margin, but they may contribute less to learning subtle explanation behavior. Conversely, a very large pool may also contain near-duplicate annotators whose explanations are almost indistinguishable from the target annotator's explanations. Treating these near-duplicates as rejected responses may introduce noisy or overly strict penalties against reasonable human variants.

These effects suggest a non-monotonic relationship between N and the relative benefit of CAPO over SFT. With extremely small pools, the signal may be too high-variance. With moderately sized pools, CAPO can obtain useful contrasts while still focusing on target-specific behavior. With very large pools, easy negatives and near-duplicate negatives may respectively dilute or corrupt the contrastive signal unless the pair construction strategy is adapted.

Scalability of strict pair construction. For VariErr, our main CAPO setting uses a strict same-label policy:

$$y_{i,a} = y_{i,b}. \quad (14)$$

This policy reduces the risk that CAPO learns only label-level differences, making the contrast more explanation-focused. If label categories are denoted by $c \in \mathcal{Y}$, the expected fraction of same-label annotator pairs is

$$p_{\text{same}} = \sum_{c \in \mathcal{Y}} P(c)^2. \quad (15)$$

Thus, the expected number of same-label pairs for an item is

$$\mathbb{E}[\#\text{pairs}_{\text{same}}] = \binom{N}{2} p_{\text{same}}. \quad (16)$$

Using the approximate VariErr label proportions from Figure 1(b), this fraction is

$$p_{\text{same}} \approx 0.31^2 + 0.52^2 + 0.17^2 \\ \approx 0.40. \quad (17)$$

Therefore, about 40% of cross-annotator pairs satisfy the same-label constraint under this approximation. As N grows, the total number of same-label pairs grows quadratically in N, while the number of available same-label rejected candidates per target annotation grows approximately linearly in N. This means that the strict policy itself is not a scalability bottleneck.

However, larger pools also increase the chance that same-label rejected responses include either overly easy negatives or near-duplicate negatives. A natural extension is therefore to introduce difficulty-aware rejected-candidate sampling. Instead of sampling uniformly from all valid rejected responses, CAPO could prioritize same-label responses whose explanation embeddings are at an intermediate distance from the target response. This would avoid contrasts that are either too easy to be useful or too similar to be treated as reliable negative examples. Such a strategy is analogous to curriculum learning or hard-negative mining, and we leave it to future work.

B.4 Group Classifier Details

Group classifiers are used for two separate purposes: CAPO checkpoint selection and final imitation evaluation. These uses are kept separate to avoid test leakage. For each method and target annotator, we form bootstrapped groups of generated outputs and feed their aggregated representations to the classifier. We report GC confidence, the mean probability assigned to the intended annotator, which captures the strength of the attribution and is more sensitive when several methods already achieve high accuracy.

Checkpoint-selection classifier. For CAPO checkpoint selection, we train the group classifier only on human training annotations. For each candidate CAPO checkpoint, we generate outputs on the development set, construct groups by target annotator, and select the checkpoint with the highest mean target-annotator confidence. This classifier is used only for model selection and never sees test annotations or test generations.

Evaluation classifier. For final reporting, we train a separate group classifier on human annotations from train, development, and test splits. This classifier is used only as an evaluation instrument for generated test outputs. It is not used to select CAPO checkpoints. We report both group classifier accuracy and confidence. Accuracy is the percentage of bootstrapped groups whose predicted annotator matches the intended target annotator. Confidence is the average probability assigned to the intended annotator, regardless of whether it is the top prediction.

Classifier configuration. Unless otherwise stated, group classifiers use group size 20.

We use fixed logistic-regression regularization $C = 21.544347$ so that confidence values are comparable across group sizes and settings. The group-size sweep shows that group size 20 is large enough to make human annotator identity reliably recoverable on both datasets, while remaining small enough to support stable bootstrapping on generated outputs.

Group-size sweep. Table 10 and 11 report the group-size sweep for the train-only and train+dev+test classifiers. The main paper uses group size 20 because it yields near-perfect human group classification on both datasets, supporting the aggregation-aware evaluation protocol.

Dataset	Group	Test Acc	Test Conf	Test Groups
VariErr	5	0.838	0.780	400
	10	0.950	0.834	200
	20	0.990	0.889	100
	30	0.988	0.915	80
R2	5	0.998	0.978	400
	10	1.000	0.985	200
	20	1.000	0.990	100
	30	1.000	0.990	80

Table 10: Train-only group-classifier sweep used for CAPO checkpoint selection. The classifier is trained on human training annotations and evaluated on held-out human test annotations.

Dataset	Group	Test Acc	Test Conf	Test Groups
VariErr	5	0.950	0.871	400
	10	0.985	0.921	200
	20	1.000	0.951	100
	30	1.000	0.961	80
R2	5	1.000	0.982	400
	10	1.000	0.987	200
	20	1.000	0.991	100
	30	1.000	0.992	80

Table 11: Train+dev+test group-classifier sweep. The group-size-20 classifiers from this setting are used only for final reported GC confidence and imitation score.

B.5 LLM-as-Judge Details

The external judge is DeepSeek V4 Pro, called with temperature 0.0 and JSON-object output. For each generated judgment, the judge receives the original item, the generated label/score and explanation, and the four human gold candidates for the same item in a deterministic shuffled order. The main metric is 1-vs-4 attribution accuracy against the intended target annotator. The parse rate is 1.0.

The judge is deliberately instance-level, whereas the group classifier is aggregation-level. This makes the judge a useful but stricter complement: on VariErr, even strong fine-tuned systems remain only moderately above chance because the four candidates often discuss the same premise-hypothesis evidence; on R2, the scoring and explanation habits are more directly recognizable.

LLM-as-Judge Prompt The judge sees the item, four anonymized shuffled human candidates for the same item, and the generated output.

LLM-as-judge prompt

```
Four original gold annotations,
shown in random anonymous order:
Option A:
Label/Score: ...
Explanation: ...
...

Predicted output:
Label/Score: ...
Explanation: ...

Task:
Choose which anonymous gold option the
predicted output is most similar to.
Use label agreement, explanation
meaning, reasoning style, wording,
specificity, and annotation habits.

Return JSON only:
{"choice": "A" | "B" | "C" | "D"}.
```

C Additional Stable Variation Analysis

This appendix gives the full diagnostic details behind Section 3: the feature inventory, single-annotation classifier results with confusion matrices, group-level classifier sweeps, and the parallel R2 analysis. All classifier splits are item-level splits, so no test item appears in classifier training.

C.1 Explanation-Style Feature Inventory

Table 12 lists the handcrafted explanation-style features used in the heatmaps and feature classifiers. These features are intentionally shallow: they are meant to capture repeated writing and justification habits that may be washed out in semantic embeddings.

C.1.1 Literature Grounding for Handcrafted Explanation Features

The handcrafted feature set used in our Feature KL analysis is intended to capture repeated, interpretable aspects of how annotators write explanations, rather than the item content alone. Although the exact combination of features and the Feature KL aggregation are specific to our setting, the individual feature families are grounded in prior work

on distributional text evaluation, stylometry, hedging and uncertainty, NLI artifacts, and explanation-based analyses of human label variation.

At the metric level, Feature KL follows the general idea of distribution-level comparison between generated and human text. MAUVE compares human and machine text distributions using information divergences in a quantized embedding space (Pillutla et al., 2021). Our Feature KL can be viewed as an interpretable counterpart: instead of comparing distributions in a learned embedding space, we compare distributions over linguistically meaningful handcrafted feature bins. This makes the resulting shift easier to inspect feature by feature.

Table 13 summarizes the provenance of each feature. Length and lexical-diversity features are standard stylometric cues (Stamatatos, 2009; Koppel et al., 2009) and have also been used in recent comparisons of human and LLM-generated text, where human text was found to exhibit more scattered sentence length distributions and richer vocabulary (Muñoz-Ortiz et al., 2024). Type-token ratio is further connected to lexical diversity and entropy in large corpora (Rosillo-Rodes et al., 2024). Modal, hedge, certainty, meta-reasoning, and judgment markers are motivated by work on uncertainty and disagreement: the CoNLL-2010 shared task formalized hedge cue detection (Farkas et al., 2010), and NLI disagreement work shows that annotators use uncertainty, presupposition, and pragmatic reasoning to justify different interpretations (Jiang and de Marneffe, 2022). Recent explanation taxonomies for NLI also explicitly model uncertainty-preserving and reasoning-type distinctions (Hong et al., 2025a).

Reasoning-connective and negation features are grounded in NLI-specific work. Negation and vagueness are known annotation artifacts in NLI (Gururangan et al., 2018), and lexical overlap has been shown to induce strong NLI heuristics (McCoy et al., 2019; Rajaee et al., 2022). Explanation datasets such as LiveNLI and VariErr further motivate studying how annotators express causal, conditional, and evidence-based reasoning in free-text explanations (Jiang et al., 2023; Weber-Genzel et al., 2024). Input-word reuse features similarly follow the NLI overlap-bias literature and explanation-based analyses of whether annotators copy or rephrase premise and hypothesis evidence. Finally, punctuation, quotation, parenthesis use, and first-person markers are classic surface-style

Feature family	Feature names	How the feature is computed
Length and structure	`len_chars`, `len_words`, `num_sentences`, `avg_sent_len`, `type_token_ratio`	The explanation is lowercased and tokenized with the regex `\b\w+\b`. Characters are counted on the raw explanation; words are the regex tokens; sentences are non-empty spans split by `[.!?]+`. `avg_sent_len` is tokens divided by sentences, and `type_token_ratio` is unique tokens divided by tokens. Empty denominators are clipped to 1.
Lexical stance markers	`modal_rate`, `hedge_rate`, `certain_rate`, `meta_rate`, `judge_rate`	Each value is a dictionary-hit rate over explanation tokens. Modal words are `must`, `should`, `could`, `would`, `might`, `may`, `can`, `need`, `shall`, `will`; hedge words include `possibly`, `perhaps`, `probably`, `likely`, `seems`, `appears`, `suggests`, `implies`, `unclear`, `ambiguous`; certainty words include `clearly`, `obviously`, `definitely`, `certainly`, `necessarily`, `always`, `never`, `impossible`. `meta_rate` and `judge_rate` use dataset-specific dictionaries: VariErr uses premise/hypothesis/NLI vocabulary, while R2 uses question/paraphrase vocabulary.
Reasoning-connective rates	`has_negation`, `has_because`, `has_conditional`, `uses_first_person`	Binary indicators. `has_negation` checks for `not`, `no`, `never`, `neither`, `nor`; `has_because` checks for any causal word; `has_conditional` checks for `if`, `unless`, `only`; `uses_first_person` checks for `i`, `my`, `me`.
Punctuation and quotation	`quote_count`, `question_mark`, `parentheses`, `has_direct_quote`	`quote_count` is the number of single plus double quote characters in the raw explanation. `question_mark` and `parentheses` are binary indicators for the presence of `?` and either parenthesis. `has_direct_quote` is 1 if any 15-character lowercase substring from the concatenated input texts, sampled every 5 characters, appears in the explanation.
Input reuse	`text_a_overlap`, `text_b_overlap`; these correspond to premise/hypothesis for VariErr and question 1/question 2 for R2	After removing a small stopword list from the input and explanation token sets, each feature is the fraction of non-stopword tokens from the corresponding input side that also appear in the explanation: $|\text{expl} \cap \text{text\_a}| / \max(|\text{text\_a}|, 1)$ and analogously for `text_b`.

Table 12: Handcrafted explanation-style features.

and authorship-profiling cues (Stamatatos, 2009; Koppel et al., 2009; Argamon et al., 2009; Preoţiuc-Pietro et al., 2017). We therefore use these features not as arbitrary correlates, but as a compact set of interpretable cues with precedent in stylometry, NLI bias analysis, and explanation-grounded HLV research.

The table also clarifies the limits of the feature design. Most features have direct precedent as stylometric, uncertainty, NLI-bias, or explanation-analysis cues. The main exception is `has_direct_quote`: while it is motivated by input reuse and quotation behavior, the 15-character matching threshold is a heuristic operationalization. We therefore treat Feature KL as a diagnostic measure rather than a fully validated psycholinguistic scale, and future work could replace the unweighted average with a reliability- or discriminativeness-weighted aggregation, for example using feature-wise annotator-separation statistics.

C.2 Additional VariErr Embedding Figures and Results

Figure 7 shows VariErr UMAPs for E_2, E_3, and E_4 at the individual-annotation level. Compared with E_1 in Figure 3, removing or reducing the input component makes annotator structure more visible, but the clusters remain noisy. Figures 8–10 show the corresponding group-averaged views for E_1–E_3; the main text shows E_4 in Figure 4.

Single-Annotation Classifier Details Tables 14 and 15 report single-annotation annotator classifiers. The split uses 250 train items and 250 test items. VariErr has 927 train annotations and 928 test annotations because the train data has missing annotator rows; R2 has 1,000 train and 1,000 test annotations. Rows in each confusion matrix are true annotators and columns are predicted annota-

Feature group	Features	Literature grounding
Length and lexical diversity	`len_chars`, `len_words`, `num_sentences`, `avg_sent_len`, `type_token_ratio`	Sentence length, text length, and lexical diversity are standard stylometric features (Stamatatos, 2009; Koppel et al., 2009). Human–LLM comparison work reports systematic differences in sentence-length distributions and vocabulary diversity (Muñoz-Ortiz et al., 2024). TTR is also a standard lexical-diversity measure connected to entropy in large corpora (Rosillo-Rodes et al., 2024).
Epistemic stance and judgment markers	`modal_rate`, `hedge_rate`, `certain_rate`, `meta_rate`, `judge_rate`	Hedge and uncertainty cues have a long precedent in hedge detection, including the CoNLL-2010 shared task (Farkas et al., 2010). NLI disagreement analyses show that uncertainty, pragmatic interpretation, and annotator reasoning strategies are central to label variation (Jiang and de Marneffe, 2022). LiTEx further formalizes explanation categories for NLI reasoning variation (Hong et al., 2025a).
Reasoning connectives and negation	`has_because`, `has_conditional`, `has_negation`	Causal and conditional markers capture explicit reasoning structure in explanations, as studied in LiveNLI and explanation-based HLV work (Jiang et al., 2023; Chen et al., 2025a). Negation is a known NLI artifact and surface cue correlated with inference labels (Gururangan et al., 2018); related NLI challenge-set work studies lexical and syntactic heuristics (McCoy et al., 2019).
Input-word reuse and quotation from input	`premise_overlap`, `hypo_overlap`, `has_direct_quote`	Premise–hypothesis word overlap is a central cue in NLI bias and heuristic analyses (McCoy et al., 2019; Rajaee et al., 2022). VariErr motivates studying explanation text together with labels to separate plausible variation from error (Weber-Genzel et al., 2024). The direct-quote feature operationalizes a more literal form of input reuse; its exact 15-character matching rule is heuristic and should be treated as a feature-engineering choice rather than a previously standardized definition.
Punctuation and parenthetical style	`quote_count`, `question_mark`, `parentheses`	Punctuation and symbol-use patterns are classic stylometric and authorship-attribution features (Stamatatos, 2009; Koppel et al., 2009). Human–LLM linguistic comparison work also reports differences in symbol and punctuation-related usage (Muñoz-Ortiz et al., 2024).
First-person use	`uses_first_person`	Pronoun and self-reference features are common in authorship profiling and social-media style analysis (Argamon et al., 2009; Preoţiuc-Pietro et al., 2017). In explanation settings, first-person use can indicate how explicitly an annotator frames the judgment as their own interpretation.

Table 13: Literature grounding for the 20 handcrafted explanation-style features used in Feature KL. The feature set combines standard stylometric cues, NLI-specific overlap and negation cues, and explanation-oriented markers of uncertainty and reasoning style.

tors, ordered 0–3.

C.2.1 Linear Input Recoverability of Residual Representations

Section 3.3 introduces residual representations to reduce the dominance of input content in annotator-style diagnostics. Our main residual representation is

$$E_4 = \text{norm}\left(E_2 - (E_2^\top E_0)E_0\right), \quad (18)$$

where E_0 is the input embedding and E_2 is the label-explanation embedding. This construction removes the component of E_2 that is directly aligned with E_0. However, input content may still be encoded in directions other than the row-wise E_0 direction. We therefore test how much of the original input embedding can be linearly recovered from each representation.

For each representation E_k, we fit a ridge regression probe on the training items:

$$\widehat{E}_0 = W E_k + b, \quad (19)$$

and evaluate on held-out items using the coefficient of determination:

$$R_k^2 = 1 - \frac{\|E_0 - \widehat{E}_0\|^2}{\|E_0 - \bar{E}_0\|^2}. \quad (20)$$

Higher R^2 indicates that more input-level information remains linearly recoverable from the representation.

Table 16 shows that E_4 sharply reduces direct input recoverability. On VariErr, the global R^2 decreases from 0.499 for E_1 and 0.180 for E_2 to 0.045 for E_4. On R2, E_4 similarly gives the lowest recoverability, with a global R^2 of 0.030. E_4 also improves over E_3 in both datasets, suggesting that removing the aligned component of E_2 is more

(a) E_2 (b) E_3 (c) E_4

Figure 7: VariErr individual-annotation UMAPs for content-reduced explanation representations.

Figure 8: VariErr group-averaged E_1 embeddings. Raw context-containing embeddings become more separable with aggregation, but remain weaker than content-reduced representations.

effective than direct subtraction for suppressing recoverable input information.

These results support the use of E_4 as the main diagnostic representation in Section 3.3. We do not interpret E_4 as a perfectly content-free style vector: explanations necessarily refer to the input, and some content information may remain nonlinearly or semantically encoded. Instead, E_4 is a conservative content-reduced representation that substantially weakens direct input recoverability while preserving enough label-explanation information to test whether annotator-specific behavior is detectable. This also reinforces our aggregation-based interpretation: single annotations remain mixtures of item content and annotator behavior, whereas repeated outputs from the same annotator provide a more reliable signal of annotator-specific label-explanation behavior.

C.3 Group-Level Classifier Sweep

Table 17 reports group-level test accuracy for all embedding representations. For each group size m, we bootstrap 240 train groups and 160 test groups per annotator from item-disjoint train/test pools, average the m row embeddings in each group, renormalize, and train a balanced logistic-regression classifier. The corresponding curves, including dashed single-sample evaluations of the same group-trained classifiers, appear in Figures 5 and 16.

Train- and Test-Time Effects of Aggregation Section 3.4 shows that annotator-specific behavior becomes more recoverable when annotations are aggregated into groups. To disentangle whether this gain comes from aggregation during classifier training or during evaluation, we compare three settings. In the standard group setting, classifiers are trained on groups of size m and evaluated on

Figure 9: VariErr group-averaged E_2 embeddings. Removing the input text from the embedded string improves group-level separability.

Representation	Acc.	Confusion matrix			
Features	50.2	104	47	38	41
		38	102	53	40
		35	29	103	57
		23	29	32	157
E_1	41.9	115	35	48	32
		69	54	79	31
		32	30	116	46
		27	36	74	104
E_2	52.9	117	47	47	19
		56	89	59	29
		28	29	130	37
		16	19	51	155
E_3	52.5	116	51	37	26
		59	91	55	28
		24	34	129	37
		20	22	48	151
E_4	56.5	128	44	41	17
		52	103	53	25
		31	27	134	32
		14	20	48	159

Table 14: VariErr single-annotation annotator classification. Accuracies are percentages. Chance is 25% and the majority baseline is 26.0%.

groups of size m (m train $\to m$ test). We also evaluate the same group-trained classifiers on individual annotations (m train $\to 1$ test), and introduce the complementary setting where classifiers are trained on individual annotations but evaluated on groups of size m (1 train $\to m$ test).

Figure 11 disentangles train- and test-time aggregation effects. The results show that aggregation helps at test time as well as at train time. As m increases, the 1 train $\to m$ test setting consistently improves over single-instance evaluation, indicating that averaging test annotations suppresses item-specific content and makes annotator-level patterns more visible. However, this setting generally converges below the full m train $\to m$ test setting, showing that test-time aggregation alone is not sufficient to obtain the strongest separation. Conversely, the m train $\to 1$ test setting often decreases with larger m, suggesting that classifiers trained to recognize group-level behavior do not transfer well to isolated annotations. Together, these results indicate that aggregation is beneficial on both sides: test-time aggregation improves the signal-to-noise ratio of annotator behavior, while train-time aggregation helps the classifier learn the corresponding group-level decision boundaries. The strongest recoverability is therefore achieved when both training and evaluation operate at the aggregated anno-

Figure 10: VariErr group-averaged E_3 embeddings. Directly subtracting the input embedding gives a stronger group-level signal than raw E_1.

Representation	Acc.	Confusion matrix			
Features	76.7	177	28	20	25
		8	177	6	59
		22	3	204	21
		18	14	9	209
E_1	76.6	182	13	9	46
		30	203	7	10
		27	14	200	9
		53	6	10	181
E_2	86.7	201	3	10	36
		7	237	1	5
		23	2	222	3
		38	3	2	207
E_3	85.3	188	3	9	50
		9	236	1	4
		18	5	222	5
		40	1	2	207
E_4	87.5	198	2	9	41
		8	237	0	5
		20	1	225	4
		32	2	1	215

Table 15: R2 single-annotation annotator classification. Accuracies are percentages. Chance and majority baseline are both 25%.

tator level.

C.4 R2 Stable Variation Analysis

R2 shows the same qualitative pattern as VariErr, but with stronger annotator-specific signal. The label side is ordinal rather than nominal, so we plot pairwise score mean absolute error (MAE) and coarse score-bin proportions in Figure 12. Pairwise MAE ranges from 1.52 to 4.17. Annotator 1 assigns low scores much more often (59.2%), while Annotator 2 assigns high scores most often (79.2%). This creates a stronger score-style signal than in VariErr.

The explanation analysis also parallels VariErr. Figure 13 shows clear feature differences,

and Figure 14 shows that raw E_1 embeddings are less mixed than in VariErr but still partly content-shaped. In the single-annotation classifier, features reach 76.7%, E_1 reaches 76.6%, and E_4 reaches 87.5% (Table 15). The higher numbers suggest that R2 annotators have more separable label-explanation habits, likely due to both task format and stronger score tendencies. Figure 17 shows R2 UMAPs for E_2, E_3, and E_4 at the individual-annotation level. Figures 18–20 show the corresponding group-averaged views for E_1–E_3.

At the group level, R2 rapidly becomes separable. The E_4 group classifier reaches 87.8% at $m = 1$, 96.4% at $m = 3$, 98.8% at $m = 5$, and

(a) VariErr

(b) R2

Figure 11: Train- and test-time effects of aggregation on annotator-classifier accuracy. We compare classifiers trained and evaluated on groups of size m (m train $\to m$ test), classifiers trained on groups but evaluated on individual annotations (m train $\to 1$ test), and classifiers trained on individual annotations but evaluated on groups (1 train $\to m$ test). Test-time aggregation alone improves accuracy as m increases, but the strongest annotator recoverability is obtained when aggregation is used at both training and test time.

Dataset	Source	Global R^2	Median dim. R^2
VariErr	E_1	0.499	0.470
VariErr	E_2	0.180	0.163
VariErr	E_3	0.324	0.299
VariErr	E_4	**0.045**	**0.021**
R2	E_1	0.439	0.423
R2	E_2	0.035	0.032
R2	E_3	0.388	0.376
R2	E_4	**0.030**	**0.026**

Table 16: Linear recovery of the input embedding E_0 from each representation. E_4 yields the lowest recoverability in both datasets, indicating that it substantially suppresses linearly recoverable input information.

(a) Pairwise score MAE

(b) Score-bin proportions

Figure 12: R2 score variation across annotators. R2 uses ordinal paraphrase-relatedness scores, so pairwise MAE is more interpretable than nominal kappa.

100.0% by $m = 10$. Figures 15 and 16 visualize this result. Thus, R2 supports the same conclusion as VariErr: annotator-specific label-explanation behavior is a stable group-level signal, but R2's signal is easier to detect from individual annotations.

D Full Results

Tables 18 and 19 expand the main tables with shared SFT, BERTScore, embedding cosine, and train-only group-classifier confidence. The GC Conf column in the main paper corresponds to the "All Conf" column here. Prompt rows use $n = 50$.

D.1 Prompt Size Sweep

Table 20 summarizes the prompt-size sweep for ICL, VP, and VP-ICL. The lists are ordered by $n \in \{3, 5, 10, 15, 20, 30, 40, 50\}$. Task is label accuracy for VariErr and score accuracy for R2. The main text uses $n = 50$ because it is the largest setting that fits both model context windows and

because the sweep over both models and datasets favors the largest prompt budget overall, especially for R2 group confidence.

D.2 Shared vs. Independent SFT

Table 18 includes an additional SFT-shared baseline, where a single LoRA adapter is trained on the annotations from all annotators and conditioned on the symbolic annotator ID. This setting has access to more total training data than each independent SFT adapter, but it produces substantially weaker annotator separation. On VariErr, for example, SFT-shared achieves much lower group-classifier confidence than SFT-ind. for both base models: 0.312 vs. 0.845 for Qwen3 and 0.256 vs. 0.909 for Llama3.2.

This gap suggests that simply providing an annotator ID as a conditioning signal is insufficient for learning fine-grained annotator-specific label-explanation behavior. Since the shared adapter receives gradients from all annotators in the same

m	VariErr				R2			
	E_1	E_2	E_3	E_4	E_1	E_2	E_3	E_4
1	42.5	54.7	52.0	**57.3**	76.6	87.2	85.6	**87.8**
3	55.6	67.7	65.9	**68.4**	93.0	**96.6**	95.9	96.4
5	62.8	78.0	74.8	**78.8**	94.5	98.4	98.6	**98.8**
10	70.9	84.5	84.5	**85.3**	99.4	99.8	99.8	**100.0**
15	73.6	87.8	87.7	**89.1**	99.7	**100.0**	99.5	**100.0**
20	75.6	**93.3**	90.5	92.3	99.8	**100.0**	**100.0**	**100.0**
30	81.7	94.2	93.8	**94.4**	99.8	**100.0**	**100.0**	**100.0**
50	83.9	**97.0**	96.4	96.4	**100.0**	**100.0**	**100.0**	**100.0**

Table 17: Group-level annotator-classifier test accuracy by representation and group size. Values are percentages; chance is 25%. E4 is the strongest or near-strongest representation while retaining the clearest content-removal interpretation.

Figure 13: R2 explanation-style features averaged by annotator and min-max normalized within each feature.

Figure 14: R2 E_1 UMAP. Compared with VariErr, annotator structure is more visible, but aggregation still provides a cleaner signal.

parameter space, the model may learn an averaged annotation policy and use the ID only weakly, especially when the differences among annotators are subtle and entangled with item content. In contrast, independent adapters allocate a separate adapted parameter space to each target annotator, making it easier to preserve repeated label preferences, explanation style, and reasoning habits.

The shared-SFT result therefore strengthens the motivation for our adapter-based design and for CAPO. If a single shared adapter with ID conditioning were sufficient, then cross-annotator contrastive training in annotator-specific parameter spaces would be less necessary. Instead, the weak separation of SFT-shared indicates that annotator-specific behavior is not reliably recovered from a symbolic ID alone; it benefits from being represented in target-specific adapted parameters and further sharpened by cross-annotator preference supervision.

D.3 Statistical Evidence for Aggregation-Aware Imitation

We further assess whether CAPO's gains over SFT are stable under resampling. Since our main imitation claim concerns repeated annotator-specific behavior, we focus on ImiScore, the aggregation-aware metric used in the main results. Unlike decision accuracy or Judge accuracy, ImiScore is not a direct average over independent test instances: it is computed by forming groups of generated outputs, embedding and averaging each group, applying a fixed annotator group classifier, and normalizing the resulting target-annotator confidence. We therefore use a non-parametric item-level bootstrap rather than a standard parametric test.

For each model-dataset pair, we draw $B = 1000$ bootstrap samples by resampling the 100 test items

Model	Setting	Acc ↑	R-L ↑	BERTScore ↑	EmbSim ↑	Feature KL ↓	Train Conf ↑	All Conf ↑	ImiScore ↑	Judge Acc ↑
Qwen3	Base	0.472	0.159	0.866	0.516	2.394	0.240	0.239	-0.034	0.237
	ICL	0.535	0.186	0.873	0.559	0.692	0.335	0.344	0.179	0.265
	VP	0.492	0.131	0.857	0.517	4.391	0.217	0.234	-0.348	0.240
	VP-ICL	0.545	0.201	0.877	0.582	0.476	0.520	0.494	0.528	0.282
	SFT-shared	0.632	0.244	0.887	0.562	0.280	0.296	0.312	0.308	0.263
	SFT-ind.	0.637	0.283	0.892	0.590	0.084	0.805	0.845	0.859	0.300
	CAPO-strict	0.627	0.281	0.891	0.582	0.081	0.823	0.867	0.888	0.328
Llama3.2	Base	0.315	0.153	0.865	0.483	2.036	0.265	0.258	0.023	0.265
	ICL	0.380	0.214	0.876	0.550	0.476	0.291	0.295	0.375	0.260
	VP	0.338	0.148	0.863	0.467	1.907	0.379	0.358	0.325	0.253
	VP-ICL	0.412	0.210	0.877	0.552	0.539	0.260	0.260	0.432	0.275
	SFT-shared	0.575	0.229	0.883	0.554	0.372	0.255	0.256	0.048	0.255
	SFT-ind.	0.512	0.271	0.887	0.549	0.113	0.873	0.909	0.946	0.282
	CAPO-strict	0.512	0.262	0.887	0.540	0.121	0.885	0.924	0.964	0.297

Table 18: Expanded results on VariErr. CAPO uses strict same-label pairs and train-only group-classifier checkpoint selection.

Model	Setting	Acc ↑	MAE ↓	R-L ↑	BERTScore ↑	EmbSim ↑	Feature KL ↓	Train Conf ↑	All Conf ↑	ImiScore ↑	Judge Acc ↑
Qwen3	Base	0.292	2.453	0.071	0.840	0.395	5.188	0.248	0.248	-0.004	0.237
	ICL	0.407	1.702	0.197	0.871	0.535	0.587	0.800	0.809	0.810	0.463
	VP	0.278	2.475	0.100	0.850	0.480	2.740	0.657	0.649	0.651	0.360
	VP-ICL	0.415	1.667	0.276	0.885	0.601	0.246	0.938	0.947	0.956	0.510
	SFT-shared	0.443	1.617	0.304	0.890	0.569	0.220	0.807	0.800	0.806	0.455
	SFT-ind.	0.450	1.478	0.307	0.891	0.582	0.130	0.936	0.929	0.936	0.512
	CAPO-tol1	0.455	1.490	0.316	0.892	0.595	0.112	0.971	0.964	0.973	0.560
Llama3.2	Base	0.207	3.188	0.068	0.835	0.380	1.515	0.251	0.255	0.015	0.230
	ICL	0.273	3.333	0.213	0.875	0.546	0.480	0.875	0.871	0.879	0.367
	VP	0.180	4.185	0.098	0.850	0.401	0.913	0.347	0.359	0.175	0.260
	VP-ICL	0.273	3.390	0.230	0.880	0.558	0.257	0.875	0.858	0.865	0.370
	SFT-shared	0.385	2.050	0.209	0.870	0.425	0.683	0.305	0.305	0.191	0.265
	SFT-ind.	0.450	1.535	0.290	0.889	0.570	0.118	0.969	0.963	0.972	0.512
	CAPO-tol1	0.460	1.470	0.293	0.889	0.582	0.187	0.988	0.985	0.995	0.530

Table 19: Expanded results on R2. CAPO uses tolerance-1 pairs and train-only group-classifier checkpoint selection.

Dataset	Model	Method	Task by n	GC Conf by n	KL@50 ↓	Judge@50 ↑
VariErr	Qwen3	ICL	0.46, 0.53, 0.46, 0.53, 0.55, 0.53, 0.57, 0.54	0.30, 0.34, 0.30, 0.29, 0.29, 0.32, 0.38, 0.34	0.692	0.265
VariErr	Qwen3	VP	0.55, 0.54, 0.54, 0.52, 0.53, 0.51, 0.56, 0.49	0.19, 0.30, 0.38, 0.32, 0.29, 0.31, 0.27, 0.23	4.391	0.240
VariErr	Qwen3	VP-ICL	0.56, 0.54, 0.52, 0.54, 0.56, 0.56, 0.58, 0.55	0.41, 0.61, 0.64, 0.48, 0.32, 0.45, 0.45, 0.49	0.476	0.282
VariErr	Llama3.2	ICL	0.35, 0.35, 0.38, 0.41, 0.48, 0.48, 0.42, 0.38	0.30, 0.30, 0.31, 0.27, 0.26, 0.28, 0.31, 0.30	0.476	0.260
VariErr	Llama3.2	VP	0.38, 0.33, 0.32, 0.36, 0.39, 0.37, 0.32, 0.34	0.26, 0.02, 0.46, 0.26, 0.26, 0.22, 0.34, 0.36	1.907	0.253
VariErr	Llama3.2	VP-ICL	0.47, 0.34, 0.39, 0.49, 0.47, 0.51, 0.42, 0.41	0.61, 0.07, 0.50, 0.28, 0.26, 0.33, 0.32, 0.26	0.539	0.275
R2	Qwen3	ICL	0.38, 0.38, 0.36, 0.41, 0.38, 0.40, 0.37, 0.41	0.55, 0.77, 0.78, 0.74, 0.73, 0.78, 0.78, 0.81	0.587	0.463
R2	Qwen3	VP	0.22, 0.28, 0.32, 0.24, 0.34, 0.30, 0.31, 0.28	0.75, 0.55, 0.63, 0.55, 0.53, 0.62, 0.59, 0.65	2.740	0.360
R2	Qwen3	VP-ICL	0.33, 0.40, 0.36, 0.43, 0.41, 0.44, 0.38, 0.41	0.84, 0.96, 0.91, 0.90, 0.93, 0.89, 0.85, 0.95	0.246	0.510
R2	Llama3.2	ICL	0.23, 0.29, 0.26, 0.38, 0.31, 0.33, 0.34, 0.27	0.53, 0.74, 0.88, 0.91, 0.78, 0.94, 0.80, 0.87	0.480	0.367
R2	Llama3.2	VP	0.21, 0.21, 0.16, 0.22, 0.22, 0.20, 0.22, 0.18	0.23, 0.36, 0.56, 0.46, 0.44, 0.42, 0.43, 0.36	0.913	0.260
R2	Llama3.2	VP-ICL	0.24, 0.23, 0.23, 0.36, 0.29, 0.32, 0.30, 0.27	0.39, 0.90, 0.93, 0.97, 0.89, 0.92, 0.96, 0.86	0.257	0.370

Table 20: Prompt-size sweep. Each list follows $n = 3, 5, 10, 15, 20, 30, 40, 50$. The trends are nonmonotonic on VariErr but generally favor larger prompt budgets for R2 group confidence.

Figure 15: R2 group-averaged E_4 embeddings. Annotator clusters become nearly perfectly separable after modest aggregation.

Figure 16: R2 annotator-classifier accuracy by representation and group size. The group-level signal is stronger than in VariErr and saturates quickly.

0.934 to 0.973. The paired one-sided bootstrap tests provide additional evidence for these R2 improvements, with $p = 0.017$ for Llama3.2 and $p = 0.024$ for Qwen3. The VariErr gains are smaller but directionally consistent, suggesting that CAPO's benefit is most reliable when annotator-specific behavior is more separable at the group level.

Overall, this analysis strengthens the interpretation of the main results: CAPO's advantage over SFT is most visible in aggregation-aware evaluation, where annotator identity is assessed through repeated behavior rather than isolated single-instance judgments.

E   CAPO Ablations

This appendix provides additional details for the CAPO ablations summarized in Figure 6. We study two design choices: the pair policy used to construct CAPO preference pairs and the checkpoint-selection criterion used after preference optimization.

E.1   Pair-Policy Ablations

CAPO constructs preference pairs by comparing responses targeted at different annotators. The pair policy controls how similar the paired examples must be in their task-level labels or scores. This is important because overly permissive pairs provide more contrastive supervision, but may also allow the model to learn coarse label or score preferences

with replacement. For each sample, we rebuild annotator-specific output groups, evaluate them with the same fixed group classifier used in the main evaluation, and recompute the macro-average ImiScore. We report the bootstrap mean and the 95% percentile interval. We also compute a paired one-sided bootstrap p-value, defined as the proportion of bootstrap samples in which CAPO does not exceed SFT.

The bootstrap results support the main conclusion that CAPO improves aggregation-aware annotator imitation. As shown in Table 21, CAPO achieves a higher bootstrap mean ImiScore than SFT in all four model-dataset settings. The gains are especially clear on R2, where CAPO improves Llama3.2 from 0.971 to 0.995 and Qwen3 from

(a) E_2 (b) E_3 (c) E_4

Figure 17: R2 individual-annotation UMAPs for content-reduced explanation representations.

Figure 18: R2 group-averaged E_1 embeddings. Even the raw context-containing representation becomes highly separable after aggregation.

instead of explanation-grounded, annotator-specific behavior.

For VariErr, which uses categorical NLI labels, we consider three policies:

- **strict**: the chosen and rejected responses must have the same task label. This is the main VariErr setting.

- **near-label**: the paired responses may differ by a small label-level discrepancy. This increases the number of available pairs, but introduces a weaker label-matching constraint than strict pairing.

- **no-restriction**: no label-matching constraint is applied when forming pairs. This provides the largest and strongest contrastive signal, but is also the most likely to introduce label-driven confounds.

Table 22 reports the VariErr pair-policy ablation. The strict policy is used in the main experiments because it provides the cleanest test of whether CAPO improves target-specific explanation framing without relying on label differences.

For R2, whose targets are ordinal scores rather than categorical NLI labels, we use tolerance-based policies. Let s_i and s_j denote the two target scores in a candidate pair. A tolerance-k policy allows the pair only if $|s_i - s_j| \leq k$:

- **strict**: only exactly matched scores are paired, i.e., $|s_i - s_j| = 0$.

- **tol1**: scores may differ by at most one point, i.e., $|s_i - s_j| \leq 1$. This is the main R2 setting.

- **tol2**: scores may differ by at most two points, i.e., $|s_i - s_j| \leq 2$.

- **tol3**: scores may differ by at most three points, i.e., $|s_i - s_j| \leq 3$.

Figure 19: R2 group-averaged E_2 embeddings. Label-score and explanation embeddings separate annotators quickly under aggregation.

Model	Dataset	SFT	CAPO	Δ
Llama3.2	R2	0.971 [0.947, 0.991]	0.995 [0.984, 1.010]	+0.024
Qwen3	R2	0.934 [0.902, 0.964]	0.973 [0.949, 0.992]	+0.039
Llama3.2	VariErr	0.951 [0.887, 1.011]	0.969 [0.910, 1.028]	+0.018
Qwen3	VariErr	0.864 [0.795, 0.936]	0.893 [0.823, 0.969]	+0.029

Table 21: Bootstrap confidence intervals for ImiScore in the main SFT and CAPO settings. Each cell reports the bootstrap mean with the 95% percentile interval in brackets. CAPO obtains higher bootstrap mean ImiScore than SFT in all four model-dataset settings.

- **no-restriction**: no score-distance constraint is applied.

Table 23 reports the R2 tolerance-policy ablation. We use CAPO-TOL1 in the main experiments because exact score matching can be too restrictive, while tolerance-1 remains the closest practical analogue to same-label pairing.

Overall, Tables 22 and 23 show the expected accuracy–imitation trade-off: looser policies often increase GC Conf or ImiScore, but their interpretation is less clean because the contrast may include larger task-level differences. We therefore use the conservative policies in the main experiments.

E.2 CAPO Checkpoint-Selection Ablations

CAPO produces multiple candidate checkpoints during preference optimization. For the main protocol, we select checkpoints using a group classifier trained only on human training annotations. For each candidate checkpoint, we generate development outputs, group them by target annotator, and select the checkpoint whose groups receive the highest target-annotator confidence. This follows the aggregation-aware motivation in Section 3: annotator-specific behavior can be weak at the single-output level but more reliable when several outputs are evaluated together. The selector does not use test outputs or any classifier trained on test annotations. Additional details on group classifiers are provided in Appendix B.4.

To check whether this selection criterion overly favors classifier-style evaluation, we compare three checkpoint choices:

- **classifier-selected**: the checkpoint selected by train-only group-classifier confidence. This is the main CAPO protocol.

- **dev-loss-selected**: the checkpoint with the best development loss during CAPO training.

- **last checkpoint**: the final checkpoint after CAPO training, without intermediate selection.

Table 24 reports the checkpoint-selection ablation for VariErr under the main strict pair policy.

Figure 20: R2 group-averaged E_3 embeddings. The residual representation also saturates to near-perfect group-level separability.

Model	Policy	Acc ↑	R-L ↑	Feature KL ↓	GC Conf ↑	ImiScore ↑	Judge Acc ↑
Qwen3	CAPO-strict	0.627	0.281	0.081	0.867	0.888	0.328
	CAPO-near-label	0.580	0.272	0.068	0.907	0.940	0.302
	CAPO-no-restriction	0.575	0.269	0.064	0.918	0.955	0.343
Llama3.2	CAPO-strict	0.512	0.262	0.121	0.924	0.964	0.297
	CAPO-near-label	0.500	0.273	0.149	0.957	1.006	0.297
	CAPO-no-restriction	0.517	0.272	0.102	0.959	1.008	0.310

Table 22: VariErr CAPO pair-policy ablation with train-only group-classifier checkpoint selection. The main setting uses CAPO-STRICT, which restricts pairs to the same task label and therefore minimizes label-driven contrast.

Table 25 reports the corresponding checkpoint-selection ablation for R2 under the main tolerance-1 pair policy.

Tables 24 and 25 show that classifier-selected checkpoints are generally competitive with dev-loss-selected and last checkpoints, including under judge-based evaluation. These results serve as sanity checks for the selection protocol, while the main experiments use classifier-selected checkpoints because the training objective is aggregation-aware annotator-specific imitation.

F Additional Feature Shift Analysis

Feature KL. We use Feature KL as a diagnostic measure of distributional alignment between human and generated explanations. For each feature f, we estimate the human feature distribution p_f and the model feature distribution q_f on the test set, and compute

$$D_{\mathrm{KL}}(p_f \| q_f) = \sum_{b \in \mathcal{B}_f} p_f(b) \log \frac{p_f(b)}{q_f(b)}, \quad (21)$$

where $\mathcal{B}_f$ denotes the bins or support values for feature f. Continuous features, such as explanation length or overlap rate, are discretized into fixed bins, while binary features are computed over their two support values. We apply additive smoothing to avoid zero-probability bins. The reported mean Feature KL is the unweighted average over all features. Lower values indicate that generated explanations are closer to human explanations with respect to the corresponding feature distribution.

Overall results. Table 26 reports mean Feature KL for SFT and CAPO. CAPO improves mean Feature KL in the Qwen settings, especially on R2, but its effect is mixed for Llama. This suggests that CAPO does not simply optimize a generic notion of surface similarity; rather, its effect depends on the

Model	Policy	Acc ↑	MAE ↓	R-L ↑	Feature KL ↓	GC Conf ↑	ImiScore ↑	Judge Acc ↑
Qwen3	CAPO-strict	0.463	1.482	0.308	0.156	0.958	0.967	0.535
	CAPO-tol1	0.455	1.490	0.316	0.112	0.964	0.973	0.560
	CAPO-tol2	0.450	1.490	0.312	0.112	0.974	0.983	0.517
	CAPO-tol3	0.453	1.488	0.309	0.113	0.979	0.988	0.532
	CAPO-no-restriction	0.448	1.532	0.310	0.151	0.992	1.002	0.545
Llama3.2	CAPO-strict	0.450	1.542	0.284	0.136	0.976	0.985	0.502
	CAPO-tol1	0.460	1.470	0.293	0.187	0.985	0.995	0.530
	CAPO-tol2	0.448	1.470	0.294	0.153	0.991	1.001	0.530
	CAPO-tol3	0.438	1.480	0.303	0.150	0.990	1.000	0.527
	CAPO-no-restriction	0.415	1.790	0.283	0.149	0.996	1.006	0.520

Table 23: R2 CAPO tolerance-policy ablation with train-only group-classifier checkpoint selection. CAPO-TOL1 is the main setting: it allows target scores to differ by at most one point and balances pair coverage with a relatively tight score-matching constraint.

Model	Selection	Acc ↑	R-L ↑	Feature KL ↓	GC Conf ↑	ImiScore ↑	Judge Acc ↑
Qwen3	classifier-selected	0.627	0.281	0.081	0.867	0.888	0.328
	dev-loss-selected	0.625	0.282	0.066	0.877	0.902	0.312
	last checkpoint	0.627	0.281	0.081	0.867	0.888	0.320
Llama3.2	classifier-selected	0.512	0.262	0.121	0.924	0.964	0.297
	dev-loss-selected	0.507	0.259	0.098	0.944	0.989	0.273
	last checkpoint	0.507	0.260	0.113	0.942	0.988	0.292

Table 24: VariErr checkpoint-selection ablation for the main strict CAPO policy. The classifier-selected checkpoint is chosen using train-only group-classifier confidence; dev-loss-selected and last checkpoints are included as selection-sanity checks.

base model, dataset, and which annotator-specific properties are easiest to control.

Feature-wise improvements. Table 27 shows representative feature-wise improvements. The improved features span several interpretable groups: verbosity and structure, such as `len_chars` and `avg_sent_len`; annotator or judgment language, such as `modal_rate` and `judge_rate`; and diversity, such as `type_token_ratio`. This supports the claim that CAPO can reduce SFT's feature-level distribution shift along multiple human-interpretable dimensions, rather than only matching length.

Regressions and limitations. Feature KL also reveals that CAPO's feature control is not uniformly positive. For example, Llama-R2 shows a worse mean Feature KL despite improvements on several individual features, because some discourse-marker features, such and `modal_rate`, become less aligned with the human distribution. Similarly, CAPO can over-correct explanation length in some settings, making outputs too short or too long relative to human explanations. These regressions are important because they show that CAPO does not trivially optimize the Feature KL metric itself. Instead, CAPO mainly optimizes a relative preference objective that encourages target-annotator-specific outputs, while Feature KL serves as an external diagnostic of which explanation properties move closer to or farther from human behavior.

Surface-marker concern. A potential concern is that group-level classifier metrics may reward easily detectable markers, such as explanation length, quotation frequency, first-person usage, or modal words, rather than faithful reasoning imitation. Our analysis partially addresses this concern in two ways. First, the feature-wise improvements are distributed across multiple feature families, including sentence structure, modal and causal language, lexical diversity, and input grounding, rather than being concentrated only in length features. Second, the qualitative examples in Table 5 show cases where CAPO better matches the gold annotator's reasoning focus, not merely its surface form.

Nevertheless, we treat GC Conf and ImiScore as diagnostic metrics rather than ground-truth measures of imitation. A stronger future test would retrain the group classifier after removing explicit surface markers such as `len_chars`, `len_words`, first-person indicators, modal words, and direct-quotation features. If CAPO continues to improve classifier confidence under this marker-ablated set-

Model	Selection	Acc ↑	MAE ↓	R-L ↑	Feature KL ↓	GC Conf ↑	ImiScore ↑	Judge Acc ↑
Qwen3	classifier-selected	0.455	1.490	0.316	0.112	0.964	0.973	0.560
	dev-loss-selected	0.453	1.490	0.312	0.134	0.967	0.976	0.520
	last checkpoint	0.455	1.490	0.316	0.112	0.964	0.973	0.530
Llama3.2	classifier-selected	0.460	1.470	0.293	0.187	0.985	0.995	0.530
	dev-loss-selected	0.465	1.438	0.296	0.149	0.981	0.991	0.520
	last checkpoint	0.460	1.470	0.293	0.187	0.985	0.995	0.527

Table 25: R2 checkpoint-selection ablation for the main tolerance-1 CAPO policy. The tolerance-1 policy allows paired target scores to differ by at most one point.

Model	Dataset	SFT	CAPO	Rel. Change
Llama	VariErr	0.1131	0.1214	+7.3%
Qwen	VariErr	0.0839	0.0806	−4.0%
Llama	R2	0.1177	0.1875	+59.3%
Qwen	R2	0.1302	0.1118	−14.2%

Table 26: Mean Feature KL between human and generated explanations. Lower is better. Negative relative change means CAPO reduces the feature distribution gap relative to SFT.

Setting	Feature	SFT KL	CAPO KL	Reduction
Qwen-VariErr	avg_sent_len	0.1127	0.0233	0.0895
Qwen-VariErr	modal_rate	0.1795	0.1274	0.0521
Qwen-VariErr	judge_rate	0.0951	0.0524	0.0428
Qwen-R2	len_chars	0.1691	0.0256	0.1435
Qwen-R2	parentheses	0.1940	0.0572	0.1368
Qwen-R2	avg_sent_len	0.1356	0.0479	0.0877
Qwen-R2	type_token_ratio	0.1394	0.1111	0.0283

Table 27: Representative feature-wise KL reductions from SFT to CAPO. Lower KL means the generated distribution is closer to the human distribution for that feature.

ting, it would provide stronger evidence that the model learns deeper reasoning-style regularities rather than only marker amplification. Another useful extension is label-conditioned Feature KL, where human and generated feature distributions are compared within the same gold label. This would help distinguish explanation-style alignment from indirect improvements caused by matching label priors.

Fluency and diversity. CAPO may also introduce a trade-off between style specificity and generation diversity. Because CAPO strengthens target-specific preferences, it could make outputs more templatic or repetitive. We therefore recommend reporting diversity diagnostics such as type-token ratio, unique-output ratio, repetition rate, or self-BLEU in addition to GC Conf and ImiScore. In our current feature analysis, CAPO improves `type_token_ratio` KL for Qwen-R2, suggesting that the gain in annotator specificity does not

necessarily come from reduced lexical diversity in this setting. However, this pattern is not universal across all model-dataset combinations, so diversity should be treated as a complementary health check for CAPO-generated explanations.

Summary. Overall, Feature KL helps interpret what CAPO changes, while also exposing its failure modes. The main-text results show that CAPO improves group-level recognizability; the feature analysis shows which human-interpretable properties shift toward the gold distribution; and the case study verifies that these shifts can correspond to more faithful reasoning focus. This combination forms a more reliable evaluation loop than any single metric alone.

G Human Validation Protocol

Two annotators participated in the human validation. Both annotators are trained on the task instructions and paid according to national standards. The guideline explicitly instructs annotators not to judge only whether the predicted label matches the gold label. Instead, they are asked to focus on whether the generated explanation is coherent, grounded in the input pair, compatible with the gold explanation, and similar to the original annotator's style and perspective. A generated explanation is marked as making sense when it is plausible for that annotator, even if the predicted label is imperfect; it is left unmarked when it is generic, contradicts the example, ignores key evidence, or fails to match the annotator's reasoning style.

Each annotator independently annotated the same 50-sample subset from VariErr. We aggregate the binary "makes sense" decisions over samples, settings, and annotator profiles to compute the make-sense rate for each setting. On the 50-sample VariErr subset, both annotators produced the same ranking: CAPO > SFT > prompt. The overall raw percent agreement between the two annotators was

Annotator	CAPO	SFT	Prompt	Overall ranking
Annotator 1	45.5%	43.5%	27.0%	CAPO > SFT > Prompt
Annotator 2	46.0%	45.5%	45.0%	CAPO > SFT > Prompt

Table 28: Human validation results on the 50-sample VariErr subset. Each cell reports the make-sense rate, computed over $50 \times 4 = 200$ binary decisions for each setting.

Setting	Agreement/Total decisions	Agreement	Cohen's κ
CAPO	167/200	83.5%	0.668
SFT	174/200	87.0%	0.737
Prompt	156/200	78.0%	0.539
Overall	497/600	82.8%	0.650

Table 29: Inter-annotator agreement for the human validation study. Agreement and Cohen's κ are computed over binary make-sense decisions. The overall score aggregates across 50 samples, three settings, and four original annotators.

0.828, computed over $50 \times 3 \times 4 = 600$ binary decisions.

To assess inter-annotator agreement, we further compute Cohen's κ between the two annotators. Overall agreement is substantial ($\kappa = 0.650$). Per-setting raw agreement and κ values are reported in Table 29.

G.1 Case study on R2

To accompany the VariErr examples shown in the main text, Table 30 presents two additional examples from R2. These examples illustrate the same pattern in a semantic similarity setting. The gold explanations often rely on fine-grained similarity rationales: two questions may share a broad topic or object, while differing in intent, specificity, or the aspect being queried. SFT tends to collapse such cases into generic judgments such as "different questions" or "conceptually unrelated," which misses the partial overlap emphasized by the original annotator. In contrast, CAPO more often preserves both parts of the rationale: it identifies the shared domain (e.g., death-related questions or iPhone-related questions) while also noting the relevant distinction between the two queries.

G.2 Profile Study Details

Table 31 summarizes the behavioral profiles for the eight annotators across the two datasets. These profiles connect closely to the handcrafted explanation-style features shown in Table 6, and the LLM-generated profiles in Appendix H, which help us to better understand and characterize annotator behavior preferences.

It is recognizable that different annotators reuse different levels of detail from the input, different lexical choices, and also different ways of grounding their reasoning. In VariErr for example, annotator 0 gives the longest explanation in average with relatively detailed, context-grounded explanations using vocabulary such as "context," "statement," and "mention." In contrast, annotator 3 is highly compressed, often giving short diagnostic phrases such as "irrelevant," "paraphrases," or "no info about.".

In R2, the four annotator-profiles reflect different ways of explaining similarity and relations between the two given sentences. For instance, annotator 0 often writes explicit comparisons of Q1 and Q2, contrasting what each question asks. Annotator 2, on the other hand, gives more analytic-style explanations, frequently mentioning "domain," "overlap," "specific," or exact shared phrases.

These differences further motivate our use of feature-level diagnostics: a model should not only provide explanations that are reasonable and plausible when imitating human annotators, but also focus on the target annotator's characteristic explanation style and reasoning focus. The stronger alignment of CAPO with these feature profiles suggests that it better captures annotator-specific explanatory behavior, rather than producing simply more fluent or generically "high quality" rationales.

H Value Profiles

This appendix records the value/style profiles used by the VP and VP-ICL baselines. Each profile was generated from 50 target-annotator training examples with seed 42 and the direct profile-construction method described in Appendix A.

H.1 VariErr Value Profiles

H.1.1 Llama3.2 profiles

These profiles correspond to profile model family: `llama32`, sample size: 50, seed: 42.

VariErr Llama3.2 Annotator 0 value profile

```
Based on the provided examples, here is a
    compact profile of Annotator_0's
    annotation behavior:

**Label/Score Bias:**

* Tends to label as "Contradiction" when the
    context and statement have opposing
    meanings.
```

Case	Q1	Q2	Gold Explanation	SFT Explanation	CAPO Explanation
1	How much time it takes to die by hanging?	Can you die by forcing yourself to stay awake for too long?	Both Q deal with reasons for death and are domain specific; syntax differ.	The queries are conceptually unrelated. The first query is a request for a time estimate, the second is a request for a yes/no answer.	Q1 is a specific query, Q2 is a general query. Both are related to death.

Observation: *SFT over-separates the pair by treating the questions as unrelated and focusing on surface question type. CAPO better matches the gold explanation by preserving the shared death-related domain while still noting their different specificity.*

2	How accurate is the iPhone as a pedometer?	How good is the iPhone 6?	Q2 is a more general question. Q1 is more specifically asking about iphone as pedometer.	Two different questions.	Q1 is about the iPhone's pedometer, while Q2 is about the iPhone 6.

Observation: *SFT reduces the comparison to a generic "different questions" judgment. CAPO better captures the gold distinction: both questions concern the iPhone, but Q1 targets a specific function while Q2 asks about the product more generally.*

Table 30: Case study comparing SFT and CAPO on R2. CAPO better preserves the gold annotator's similarity rationale by capturing shared domains and fine-grained differences, while SFT tends to over-separate question pairs or collapse them into generic difference judgments.

```
* Labels as "Entailment" when the context
    implies a logical connection between the
    premise and hypothesis.
* Labels as "Neutral" when the context is
    unclear or lacks sufficient information
    to make a conclusion.

**Value Judgment Criteria:**

* Evaluates statements for implicit value
    judgments, such as "beautiful" or
    "hardworking".
* May not always recognize value judgments,
    especially if they are implicit or
    nuanced.

**Evidence Usage:**

* Requires explicit evidence to support a
    conclusion, such as quotes or specific
    examples.
* May not consider implicit evidence, such as
    tone or context.

**Explanation Style:**

* Provides concise explanations that summarize
    the reasoning behind the label.
* May use phrases like "the context only
    mentions" or "it is unclear if" to
    indicate uncertainty.

**Typical Wording:**

* Uses phrases like "the context only
    mentions" or "it is unclear if" to
    indicate uncertainty.
* May use phrases like "the statement implies"
    or "the context suggests" to indicate
    logical connections.

**Strictness:**

* Can be quite strict in its labeling,
    especially when it comes to
    "Contradiction" and "Entailment".
* May be more lenient when it comes to
    "Neutral" labels.

**Uncertainty:**

* Recognizes uncertainty when the context is
    unclear or lacks sufficient information.
* May use phrases like "it is unclear if" or
    "the context only mentions" to indicate
    uncertainty.

**Quirks:**
```

```
* May not always recognize implicit evidence,
    such as tone or context.
* Can be quite strict in its labeling,
    especially when it comes to
    "Contradiction" and "Entailment".
* May use phrases like "the statement implies"
    or "the context suggests" to indicate
    logical connections.

To imitate Annotator_0, follow these
    guidelines:

1. Be cautious when labeling as
    "Contradiction" or "Entailment", as these
    labels require explicit evidence and
    logical connections.
2. Use phrases like "the context only
    mentions" or "it is unclear if" to
    indicate uncertainty.
3. Provide concise explanations that summarize
    the reasoning behind the label.
4. Be strict in your labeling, especially when
    it comes to "Contradiction" and
    "Entailment".
5. Recognize implicit evidence, such as tone
    or context, when possible.
6. Use phrases like "the statement implies" or
    "the context suggests" to indicate
    logical connections.
```

VariErr Llama3.2 Annotator 1 value profile

```
**Annotation Style Profile: Annotator_1**

**Label/Score Bias:**

* Tends to avoid making definitive judgments,
    often labeling as "Neutral" when the
    context suggests a stronger stance.
* May not always provide a clear label,
    especially when the context is ambiguous
    or open to multiple interpretations.

**Value Judgment Criteria:**

* Focuses on literal meaning and context,
    rather than making value judgments about
    the statements.
* Avoids making assumptions or inferences that
    may not be supported by the text.

**Evidence Usage:**

* Typically provides a concise explanation to
    support the label, but may not always
    provide explicit evidence.
```

Annotator	Behavioral interpretation	Empirical cues	Representative examples
VariErr NLI			
0	Evidence-checking and context-grounded: treats the task as verifying whether the hypothesis is explicitly licensed by the context.	Longer explanations; frequent meta-level NLI terms such as "context," "statement," and "mention."	- Both the *context* and the *statement* suggest that the speaker believes what was said.
- The *context mentions* that activities with a longer time frame than 12 months will be included, so some activities could be shorter than 12 months.
1	Conservative under underspecification: withholds commitment when a specific detail is not stated.	Concise absence-of-evidence formulations, especially "not clear whether" and "does not say anything about."	- *It is not clear whether* the speaker wants the taxes to be lower.
- *The context does not say anything about* lepers or where they could work.
2	Possibility-oriented and ambiguity-preserving: keeps multiple compatible readings open instead of forcing a deterministic inference.	High modal/first-person tendency; frequent use of "could," "maybe," and "we do not know."	- The man *could* be grabbed by Jon, *but also could* slip from him.
- *We do not know* how often a Global Expo is held.
3	Compressed and diagnostic: uses explanations as short decision cues rather than full rationales.	Short explanations; repeated minimal phrases such as "irrelevant," "paraphrases," and "no info about …".	- No info about the murder.
- Irrelevant.
R2			
0	Aspect-level question comparison: contrasts what Q1 and Q2 ask about, especially conditions, degree, or requested information.	Explicit Q1–Q2 contrast, often using "Q1 asks …whereas Q2 asks …".	- *Q1 asks* whether sex is important, *whereas Q2 asks* how important it is.
- *In Q2*, the prerequisite, knowing C and C++, is given, *whereas in Q1* there is no prerequisite.
1	Coarse topic-relation categorization: reduces the comparison to topic sameness, topic difference, or semantic-field overlap.	Shortest and most formulaic explanations; recurrent labels such as "same topic," "different topics," and "same semantic field."	- *Different topics*, although both are in the same semantic field, namely MIT.
- *The same topic*.
2	Analytical query-relevance comparison: weighs phrase overlap, domain, template effects, and fine-grained differences.	Frequent input reuse and quotation; markers such as "common_phrase," "Difference in," and "boilerplate template."	- *common_phrase*: sleep cycle; Difference in: fix–calculate can be neglected.
- Calculation request for both Qs where context is specified for the problem. The problems themselves differ. No penalty since *"boilerplate template"*.
3	Answer-equivalence and keyword-sensitive reasoning: judges whether two questions would lead to the same answer.	Broad semantic judgments such as "similar meaning" or "different meaning," combined with answer-changing keyword contrasts.	- They have a *similar meaning*.
- *Different keywords*, "goherenext.com" and "thedartmouth.com," can lead to entirely different answers.

Table 31: Qualitative characterization of annotator-level explanation behavior. Behavioral interpretations describe recurring annotation strategies, not demographic or psychological attributes. Empirical cues are summarized from feature statistics, value-profile summaries, and manual inspection of human explanations; examples are lightly normalized for readability.

```
* May use paraphrasing or restatement of the
    context to support the label.

**Explanation Style:**

* Uses a formal, objective tone, avoiding
    emotive language or personal opinions.
* Provides a clear and concise explanation,
    but may not always elaborate on the
    reasoning.

**Typical Wording:**

* Uses straightforward language, avoiding
    jargon or technical terms unless
    necessary.
* May use phrases like "it's not clear" or
    "it's not clear whether" to indicate
    uncertainty.

**Strictness:**
```

```
* Tends to be neutral or cautious in their
    labeling, avoiding strong or absolute
    statements.
* May not always provide a clear label,
    especially when the context is ambiguous
    or open to multiple interpretations.

**Uncertainty:**

* Often indicates uncertainty or ambiguity in
    the context, using phrases like "it's not
    clear" or "it's not clear whether".
* May not always provide a clear label,
    especially when the context is ambiguous
    or open to multiple interpretations.

**Quirks:**

* May use phrases like "it's not clear" or
    "it's not clear whether" to indicate
    uncertainty.
* Tends to avoid making value judgments or
    assumptions, focusing on literal meaning
```

and context.
* May not always provide explicit evidence to support the label, relying on paraphrasing or restatement of the context instead.

Imitation Guidelines:

To imitate Annotator_1's style, follow these guidelines:

1. Use a formal, objective tone and avoid emotive language or personal opinions.
2. Focus on literal meaning and context, avoiding value judgments or assumptions.
3. Provide a clear and concise explanation to support the label, but avoid elaborating on the reasoning unless necessary.
4. Use straightforward language and avoid jargon or technical terms unless necessary.
5. Be cautious in labeling, avoiding strong or absolute statements.
6. Indicate uncertainty or ambiguity in the context using phrases like "it's not clear" or "it's not clear whether".
7. Avoid making value judgments or assumptions, focusing on literal meaning and context instead.

VariErr Llama3.2 Annotator 2 value profile

Annotator_2's Annotation Behavior Profile

Label/Score Bias:

* Tends to label as "Contradiction" when the premise and hypothesis are mutually exclusive, but not necessarily contradictory in a strict sense.
* Labels as "Entailment" when the premise implies a logical consequence, but may not be a direct entailment.
* Labels as "Neutral" when the premise and hypothesis are ambiguous or lack clear implications.

Value Judgment Criteria:

* Evaluates the strength of the premise and hypothesis based on logical coherence and implications.
* May consider the context and tone of the text when making judgments.

Evidence Usage:

* Relys on explicit statements and logical implications to support judgments.
* May consider implicit assumptions or unstated premises.

Explanation Style:

* Provides concise and clear explanations for judgments.
* May use phrases like "usually," "typically," or "in context" to clarify reasoning.

Typical Wording:

* Uses phrases like "usually," "typically," or "in context" to clarify reasoning.
* May use simple, direct language to explain judgments.

Strictness:

* May be lenient in cases where the premise and hypothesis are ambiguous or lack clear implications.
* May be more strict in cases where the premise and hypothesis are mutually exclusive.

Uncertainty:

* May indicate uncertainty or ambiguity in judgments, especially when the premise and hypothesis are unclear or lack clear implications.

Quirks:

* May over-interpret or over-analyze text, leading to overly complex or nuanced judgments.
* May be overly cautious in cases where the premise and hypothesis are ambiguous or lack clear implications.

Imitation Guidelines:

To imitate Annotator_2's annotation behavior, follow these guidelines:

1. Evaluate the strength of the premise and hypothesis based on logical coherence and implications.
2. Consider the context and tone of the text when making judgments.
3. Use explicit statements and logical implications to support judgments.
4. Be concise and clear in explanations, using phrases like "usually," "typically," or "in context" to clarify reasoning.
5. Be lenient in cases where the premise and hypothesis are ambiguous or lack clear implications.
6. Indicate uncertainty or ambiguity in judgments when the premise and hypothesis are unclear or lack clear implications.
7. Avoid over-interpreting or over-analyzing text, and be cautious in cases where the premise and hypothesis are ambiguous or lack clear implications.

VariErr Llama3.2 Annotator 3 value profile

Based on the provided examples, here is a compact profile of Annotator_3's annotation behavior:

Label/Score Bias:

* Tends to label as "Entailment" when the context implies a positive relationship between two statements.
* Labels as "Contradiction" when the context implies a direct opposition between two statements.
* Neutral labels are used when the context is unclear or when the annotator is unsure of the relationship between the statements.

Value Judgment Criteria:

* Evaluates statements based on their logical coherence and implied relationships.
* Does not make explicit value judgments, but rather focuses on identifying the relationships between statements.

Evidence Usage:

* Uses context to infer relationships between statements.
* Does not require explicit evidence to support the annotation.

Explanation Style:

* Provides concise explanations that summarize the relationship between the statements.
* Uses simple language and avoids complex explanations.

```
**Typical Wording:**

* Uses phrases like "entails", "contradicts",
    and "neutral" to describe the
    relationships between statements.
* Avoids using technical jargon or complex
    terminology.

**Strictness:**

* Tends to be lenient in its annotation,
    allowing for some ambiguity in the
    context.
* Does not require absolute certainty in the
    relationships between statements.

**Uncertainty:**

* Indicates uncertainty when the context is
    unclear or when the annotator is unsure
    of the relationship between the
    statements.
* Uses phrases like "No info" or "irrelevant"
    to indicate uncertainty.

**Quirks:**

* May misinterpret certain phrases or idioms,
    leading to incorrect annotations.
* Can be overly literal in its interpretation
    of statements, leading to incorrect
    conclusions.
* Does not account for nuances in language,
    such as sarcasm or irony.

By following this profile, another LLM can
    attempt to imitate Annotator_3's
    annotation behavior on new items.
    However, it is essential to note that
    this profile is based on a limited
    dataset and may not capture the full
    complexity of Annotator_3's annotation
    behavior.
```

H.1.2 Qwen3 profiles

These profiles correspond to profile model family:
`qwen3`, sample size: 50, seed: 42.

VariErr Qwen3 Annotator 0 value profile

```
**Annotator_0 Profile (Imitation Guide)**

- **Label/Score Bias**: Strongly avoids
    *Entailment* when evidence is weak or
    indirect; favors *Contradiction* when the
    hypothesis introduces a false or
    incompatible claim (e.g., misreading
    negation, overreach, or false inference).
    *Neutral* is default when information is
    missing, ambiguous, or contextually
    unrelated.

- **Value Judgment Criteria**: Does **not**
    apply value judgments independently.
    Labels are based strictly on **literal
    content**, **semantic consistency**, and
    **explicit or implied factual
    alignment**. No moral, emotional, or
    ideological evaluation is introduced.

- **Evidence Usage**:
  - Requires **explicit or directly implied**
    support for *Entailment* or
    *Contradiction*.
  - Rejects assumptions (e.g., "people might
    say", "it could be", "it seems like").
  - Flags **missing elements** (e.g., "no
    mention of", "not stated", "unclear") as
    grounds for *Neutral*.
  - Uses **semantic precision** (e.g.,
    "interim rules" vs "general notices") to
    detect contradictions.
```

```
- **Explanation Style**:
  - Concise, direct, and **fact-based**.
  - Uses **logical reasoning** to trace from
    premise to label.
  - Often includes **explicit negation** or
    **contrast** (e.g., "not mentioned",
    "means X, not Y").
  - Avoids speculation or hedging beyond
    necessary qualifiers.

- **Typical Wording**:
  - "The context only mentions X, has no
    information about Y."
  - "There is no mention of Z."
  - "It is unclear if A or B."
  - "The context states that X, but the
    statement says Y."
  - "Means X, so Y is false."
  - "The statement suggests Z, but the context
    says W."
  - "It is not clear if A is true."

- **Strictness**:
  - Very strict on **semantic precision**
    (e.g., "interim" vs "general notices",
    "national" vs "regional").
  - Rejects **overgeneralization** or
    **inference beyond the text**.
  - Treats **modalities** (e.g., "might",
    "could", "possibly") as insufficient for
    entailment.

- **Uncertainty Handling**:
  - Uses *Neutral* when:
    - The hypothesis introduces new claims not
      in the premise.
    - The premise lacks sufficient detail to
      support entailment.
    - The meaning is ambiguous (e.g.,
      "protest", "hardworking", "crazy").
  - Avoids *Uncertain* or *Possibly* labels --
    only *Neutral* or
    *Contradiction/Entailment*.

- **Quirks**:
  - Frequently **rephrases the premise** in
    the explanation to highlight mismatch.
  - Uses **self-reflective language** ("I am
    asking myself", "it is unclear") to
    signal hesitation.
  - Treats **questions** or **statements of
    inquiry** as *Neutral* unless clearly
    entailed.
  - Strongly **rejects inference from tone or
    implication** (e.g., "splendid" ->
    excited) unless explicitly tied
```

VariErr Qwen3 Annotator 1 value profile

```
**Annotator_1 Profile (Imitation Guide)**

- **Label/Score Bias**:
  Strongly avoids over-entailment; defaults to
    *Neutral* when meaning is ambiguous,
    incomplete, or requires inference beyond
    direct textual support. *Entailment* is
    only assigned when the hypothesis is a
    clear paraphrase, logical consequence, or
    direct restatement. *Contradiction* is
    used when explicit negation or factual
    incompatibility exists. *Neutral* is the
    default for uncertainty or missing
    information.

- **Value Judgment Criteria**:
  Does **not** assign value judgments based on
    sentiment or moral stance. Instead,
    evaluates logical consistency and textual
    support. If a statement asserts a value
    (e.g., "stealing is bad"), it is only
    labeled *Entailment* if the premise
    explicitly supports it. Otherwise, it is
    *Neutral*.
```

- **Evidence Usage**:
  Relies **strictly** on explicit or directly inferable content. Does **not** introduce external knowledge, assumptions, or interpretive leaps. If a claim is not directly supported or contradicted, it is labeled *Neutral*. Even plausible inferences (e.g., "wallop" ~= "hit with a spoon") are only accepted if the similarity is clearly grounded in the text.

- **Explanation Style**:
  Concise, neutral tone. Uses **factual, observational language**. Avoids emotional or evaluative phrasing. Structure:
  – Label first.
  – Explanation: "It is not clear..." / "The context does not say..." / "That indicates..." / "It is a paraphrase of..."
  – Avoids speculative or hypothetical language.

- **Typical Wording**:
  – "It is not clear whether..."
  – "The context does not say..."
  – "That indicates..." / "It implies..."
  – "It is a paraphrase of..."
  – "It's clearly stated that..."
  – "It's not clear how..."
  – "The speaker says that..."

- **Strictness**:
  High. Rejects entailment when the connection is indirect, inferential, or based on interpretation. Requires **direct textual alignment** or **explicit contradiction**. Even subtle differences (e.g., "best example" vs. "good example") are treated as entailment only if clearly supported.

- **Uncertainty Handling**:
  Explicitly acknowledges uncertainty using phrases like "It is not clear", "It's not clear whether", or "It's not clear how". Never assumes missing information is implied or can be reasonably inferred.

- **Quirks**:
  – Treats **paraphrasing** as *Entailment* if it's a direct rewording.
  – Treats **negation** or **contradiction** as *Contradiction* when explicitly stated.
  – Uses **"it is not clear"** as a default when meaning is ambiguous.
  – Occasionally interprets **intensity** (e.g., "wallop" vs. "hit with spoon") as equivalent if contextually plausible.
  – Avoids over-interpretation of emotional or rhetorical tone.
  – Labels *Neutral* when the premise and hypothesis are unrelated or only partially aligned.

Imitation Rule Summary:
When in doubt, label **Neutral**. Only label

VariErr Qwen3 Annotator 2 value profile

Annotator_2 Profile (Imitation Guide)

- **Label/Score Bias**:
  Strongly favors *Contradiction* when the hypothesis directly conflicts with explicit or implied facts (e.g., mismatched terms like "national" vs. "regional", or logical impossibility). Favors *Entailment* when the hypothesis is a plausible, direct inference (e.g.,

"made beautiful" -> "positive view of violence"). *Neutral* is default when uncertainty, missing context, or multiple interpretations exist.

- **Value Judgment Criteria**:
  Rejects value-laden or emotionally charged inferences (e.g., "crazy", "great", "flawed") unless directly supported. Avoids assuming intent, emotion, or moral stance. Labels like "neutral" are used when the premise doesn't justify a positive/negative evaluation.

- **Evidence Usage**:
  Relies on **literal, contextual, and grammatical alignment**. Prioritizes **explicit terms** (e.g., "national" vs. "regional") and **logical consistency** over implied or metaphorical meanings. Ignores out-of-scope or unmentioned details (e.g., cost, location, actor vs. character).

- **Explanation Style**:
  Concise, direct, and **cautious**. Uses **"we don't know"**, **"maybe"**, **"could be"**, or **"not definitely"** to express uncertainty. Avoids speculative or emotional language. Explains *why* a label is chosen through **logical or factual mismatch**, not emotional or philosophical reasoning.

- **Typical Wording**:
  – "We don't know..."
  – "Maybe it is..." / "could be"
  – "No, because..." / "It is not true because..."
  – "In context, there is nothing about..."
  – "He could be sure of X, or Y"
  – "It is possible, because..."
  – "No, the rules were issued as interim rules."

- **Strictness**:
  High. Rejects entailment when the connection is not direct or unambiguous. Requires **explicit support** or **clear logical necessity**. Even plausible inferences are labeled *Neutral* if the premise doesn't fully justify the conclusion.

- **Uncertainty Handling**:
  Systematically uses *Neutral* when:
  – Context lacks information (e.g., location, cost, intent)
  – Multiple interpretations are possible
  – The hypothesis introduces new elements not in the premise
  – Ambiguity in pronouns, references, or emotional tone

- **Quirks**:
  – Frequently uses **"No"** to reject contradictions, even in neutral contexts.
  – Treats **"only"**, **"best"**, **"must"**, **"flawed"**, or **"crazy"** as red flags for contradiction or neutrality.
  – Misinterprets **character vs. actor** (e.g., "George Clooney" as character -> neutral).
  – Assumes **"positive" or "negative" connotations** only when explicitly stated.
  – Over-uses **"we don't know"** or **"maybe"** even when the premise is clear.
  – Labels **"entailment"**

VariErr Qwen3 Annotator 3 value profile

Annotator_3 Profile (Imitation Guide)

- **Label/Score Bias**:
  Strongly avoids over-entailment or
  over-contradiction. Prefers *Neutral*
  when information is missing, ambiguous,
  or contextually insufficient. Only
  assigns *Entailment* or *Contradiction*
  when clear logical or semantic
  alignment/disagreement exists. Avoids
  assuming intent, emotion, or value
  judgments.

- **Value Judgment Criteria**:
  Does **not** apply value judgments (e.g.,
  "crazy," "flawed," "good," "bad") in
  labels. Labels are strictly based on
  factual, logical, or semantic
  consistency. Any value-laden language in
  explanation is used only to clarify
  meaning, not to justify a label.

- **Evidence Usage**:
  Relies **exclusively** on explicit or
  directly inferable information from the
  premise. Rejects assumptions, inferences
  beyond the text, or external knowledge.
  Flags gaps with "No info," "irrelevant,"
  or "not mentioned."

- **Explanation Style**:
  Concise, direct, and grounded in linguistic
  or logical analysis. Uses plain language,
  avoids jargon. Often includes
  paraphrase recognition
  ("paraphrases"), **semantic
  equivalence**, or **word-level
  reasoning** (e.g., "budge entails that
  the door wouldn't move").
  Frequently includes **explicit negation** or
  contradiction of implication (e.g.,
  "cannot be outlawed" = "cannot be made
  illegal").

- **Typical Wording**:
  - "No info about..."
  - "Not mentioned"
  - "It is not known"
  - "Paraphrases"
  - "Entails X because Y"
  - "Contradiction because Z"
  - "No info about where he is hardworking or
    not"
  - "Can not conclude that..."
  - "The context is talking about..."

- **Strictness**:
  Very strict. Rejects entailment when the
  hypothesis introduces new claims not
  supported by the premise. Requires
  **direct logical or semantic
  connection**. Even subtle mismatches
  (e.g., "only" vs. "also") trigger
  Contradiction or *Neutral*.

- **Uncertainty Handling**:
  Explicitly acknowledges uncertainty with
  phrases like:
  - "No info"
  - "Not sure"
  - "Can not conclude"
  - "The context is talking about..."
  Never uses vague or probabilistic language
  (e.g., "possibly," "might").

- **Quirks & Idiosyncrasies**:
  - **High sensitivity to word precision**:
    e.g., "only" vs. "also," "best way" vs.
    "the only way."
  - **Strong rejection of
    over-interpretation**: e.g., "crazy" ->
    "no info about beauty," "excited" ->
    "entails excitement" only if clearly
    implied.

- **Frequent use of synonym mapping** (e.g.,
  "generally accepted" = "large
  acknowledged").
- **Rejects emotional or subjective
  inferences** (e.g., "he is hardworking"
  -> no info).
- **Treats questions as neutral** (e.g., "is
  it true?" -> neutral).
- **

H.2 R2 Value Profiles

H.2.1 Llama3.2 profiles

These profiles correspond to profile model family:
llama32, sample size: 50, seed: 42.

R2 Llama3.2 Annotator 0 value profile

Label/Score Bias:
Annotator_0 tends to assign high scores (4-5)
  when the questions are paraphrases of
  each other, indicating a strong bias
  towards recognizing similar questions.
  Conversely, when the questions are not
  paraphrases (scores -5), Annotator_0
  tends to assign lower scores, indicating
  a lack of understanding or recognition of
  the similarity between the questions.

Value Judgment Criteria:
Annotator_0's value judgment criteria seem to
  be based on the similarity in wording and
  structure between the questions. They
  tend to prioritize questions that have
  similar phrasing, sentence structure, and
  context.

Evidence Usage:
Annotator_0's evidence usage is limited to
  recognizing the similarity between the
  questions. They do not provide additional
  context or evidence to support their
  answers.

Explanation Style:
Annotator_0's explanation style is concise and
  to the point, often focusing on the
  similarity between the questions. They
  tend to avoid providing additional
  context or background information.

Typical Wording:
Annotator_0's typical wording is
  straightforward and lacks embellishments.
  They tend to use simple language to
  convey their answers.

Strictness:
Annotator_0's strictness is evident in their
  tendency to assign high scores only when
  the questions are paraphrases. They seem
  to be quite strict in their evaluation of
  question similarity.

Uncertainty:
Annotator_0's uncertainty is evident in their
  tendency to assign lower scores when the
  questions are not paraphrases. However,
  they also seem to be uncertain when the
  questions are similar but not identical.

Quirks:
Annotator_0's quirks include:

* A tendency to assign high scores only when
    the questions are paraphrases
* A focus on the similarity in wording and
    structure between the questions
* A lack of evidence usage beyond recognizing
    question similarity
* A concise explanation style that lacks
    additional context or background

```
        information
* A strict evaluation of question similarity
* Uncertainty when questions are similar but
    not identical

**Profile:**
Based on the analysis, Annotator_0's
    annotation behavior can be summarized as
    follows:

* Strong bias towards recognizing paraphrases
    (scores 4-5)
* Focus on similarity in wording and structure
    between questions
* Limited evidence usage beyond recognizing
    question similarity
* Concise explanation style that lacks
    additional context or background
    information
* Strict evaluation of question similarity
* Uncertainty when questions are similar but
    not identical

To imitate Annotator_0's annotation behavior,
    it is recommended to:

* Focus on the similarity in wording and
    structure between questions
* Assign high scores only when the questions
    are paraphrases
* Use a concise explanation style that lacks
    additional context or background
    information
* Evaluate question similarity strictly
* Be uncertain when questions are similar but
    not identical
```

R2 Llama3.2 Annotator 1 value profile

```
Based on the provided examples, here is a
    compact profile of Annotator_1's
    annotation behavior:

**Label/Score Bias:**
Annotator_1 tends to assign high scores (4-5)
    when the questions are paraphrases of
    each other, indicating a strong
    understanding of the topic and a clear
    connection between the questions. They
    also assign low scores (-4 to -5) when
    the questions are not paraphrases,
    indicating a lack of understanding or a
    different topic.

**Value Judgment Criteria:**
Annotator_1's explanations often reflect their
    personal opinions and biases. For
    example, in Sample 4, they mention that
    the two questions are "the same topic and
    subject," which implies a positive bias
    towards the topic.

**Evidence Usage:**
Annotator_1 rarely provides explicit evidence
    to support their answers. Instead, they
    rely on their understanding of the topic
    and make inferences based on the context.

**Explanation Style:**
Annotator_1's explanations are concise and to
    the point, often focusing on the main
    topic or subject. They use simple
    language and avoid complex explanations.

**Typical Wording:**
Annotator_1's typical wording is
    straightforward and lacks jargon. They
    use simple sentences and avoid technical
    terms unless necessary.

**Strictness:**
Annotator_1's annotations are generally
    strict, with a focus on identifying
    paraphrases and distinguishing them from
```

```
        non-paraphrases.

**Uncertainty:**
Annotator_1 rarely expresses uncertainty or
    doubt in their annotations. When they do,
    it's usually in the form of a low score
    (-4 to -5) indicating a lack of
    understanding or a different topic.

**Quirks:**
Annotator_1 has a few quirks in their
    annotation style:

* They often use similar wording in their
    explanations, such as "the same topic" or
    "the same subject."
* They tend to focus on the main topic or
    subject, rather than providing a
    comprehensive explanation.
* They rarely provide explicit evidence to
    support their answers.
* They have a bias towards positive language,
    using words like "good" and "best" to
    describe topics and subjects.

Overall, Annotator_1's annotation style is
    straightforward and focused on
    identifying paraphrases. They have a bias
    towards positive language and rarely
    express uncertainty or doubt in their
    annotations.
```

R2 Llama3.2 Annotator 2 value profile

```
**Label/Score Bias:**
The annotator tends to assign higher scores
    (closer to 5) to questions that are more
    concise, have a clear and specific query,
    and are related to a specific domain or
    entity. Conversely, questions that are
    more open-ended, vague, or unrelated to a
    specific domain are assigned lower scores.

**Value Judgment Criteria:**
The annotator's value judgment criteria seem
    to be based on the clarity and
    specificity of the query, as well as the
    domain or entity being queried. Questions
    that are more direct and concise are
    given higher scores, while questions that
    are more open-ended or vague are given
    lower scores.

**Evidence Usage:**
The annotator tends to rely on the context and
    the specific words used in the query to
    determine the relevance and specificity
    of the question. They also seem to
    consider the domain or entity being
    queried, as well as the presence of any
    qualifiers or modifiers.

**Explanation Style:**
The annotator's explanations are concise and
    to the point, often focusing on the key
    differences between the two questions or
    the specific criteria that led to the
    assigned score.

**Typical Wording:**
The annotator's typical wording is formal and
    objective, avoiding any emotive or
    subjective language. They tend to use
    technical terms and domain-specific
    jargon when relevant.

**Strictness:**
The annotator's strictness seems to be
    moderate, with a focus on clarity and
    specificity in the query. They are
    willing to consider context and
    domain-specific knowledge when assigning
    scores, but are not overly lenient with
    vague or open-ended questions.
```

Uncertainty:
The annotator tends to be uncertain when faced
with questions that are highly ambiguous
or unrelated to a specific domain. In
such cases, they may assign a lower score
or indicate that the question is not
relevant to the task.

Quirks:
Some quirks in the annotator's behavior
include:

* A tendency to overlook minor differences in
wording or phrasing when the overall
meaning and intent are clear.
* A focus on domain-specific knowledge and
context when assigning scores.
* A willingness to consider technical terms
and jargon when relevant.
* A moderate level of strictness, with a focus
on clarity and specificity in the query.
* A tendency to be uncertain when faced with
highly ambiguous or unrelated questions.

Profile:
Based on the provided examples, the
annotator's profile can be summarized as
follows:

* Label/Score Bias: Moderate, with a focus on
clarity and specificity in the query.
* Value Judgment Criteria: Clarity and
specificity of the query, as well as
domain or entity being queried.
* Evidence Usage: Context and specific words
used in the query, as well as domain or
entity being queried.
* Explanation Style: Concise and objective,
focusing on key differences between
questions or specific criteria.
* Typical Wording: Formal and objective, using
technical terms and domain-specific
jargon when relevant.
* Strictness: Moderate, with a focus on
clarity and specificity in the query.
* Uncertainty: Uncertain when faced with
highly ambiguous or unrelated questions.
* Quirks: Tendency to overlook minor
differences in wording or phrasing, focus
on domain-specific knowledge and context,
willingness to consider technical terms
and jargon, moderate level of strictness,
and tendency to be uncertain when faced
with highly ambiguous or unrelated
questions.

This profile can guide another LLM to imitate
the annotator's behavior and assign
scores based on the provided criteria.

R2 Llama3.2 Annotator 3 value profile

Label/Score Bias:
Annotator_3 tends to assign high scores (4-5)
when the questions are paraphrases of
each other, indicating a strong bias
towards recognizing similar meaning.
However, when the questions are not
paraphrases (score -5), the annotator
acknowledges the difference in meaning.

Value Judgment Criteria:
Annotator_3 does not explicitly express value
judgments in their explanations. They
focus on the literal meaning of the
questions and provide concise
explanations.

Evidence Usage:
Annotator_3 does not provide explicit evidence
to support their answers. Their
explanations are based on the literal
meaning of the questions.

Explanation Style:
Annotator_3's explanations are concise and to
the point, providing a clear indication
of whether the questions are paraphrases
or not.

Typical Wording:
Annotator_3's explanations often use simple
and straightforward language, avoiding
complex sentences or jargon.

Strictness:
Annotator_3 is relatively strict in their
classification of paraphrases, assigning
low scores (-5) when the questions are
not similar in meaning.

Uncertainty:
Annotator_3 does not express uncertainty in
their answers, providing a clear
classification of paraphrases or not.

Quirks:

1. Annotator_3 tends to emphasize specific
keywords or phrases in the questions,
which can lead to different answers.
2. They do not provide explicit explanations
for their answers, relying on the literal
meaning of the questions.
3. Annotator_3's explanations are often brief,
providing only a concise indication of
whether the questions are paraphrases or
not.
4. They do not acknowledge the context or
nuances of the questions, focusing solely
on the literal meaning.

Profile:
To imitate Annotator_3, follow these
guidelines:

1. Focus on the literal meaning of the
questions.
2. Emphasize specific keywords or phrases in
the questions.
3. Provide concise explanations, avoiding
complex sentences or jargon.
4. Classify questions as paraphrases or not
based on their similarity in meaning.
5. Avoid expressing value judgments or
providing explicit evidence.
6. Be strict in your classification of
paraphrases, assigning low scores (-5)
when the questions are not similar in
meaning.
7. Do not express uncertainty in your answers.
8. Use simple and straightforward language in
your explanations.

H.2.2 Qwen3 profiles

These profiles correspond to profile model family:
qwen3, sample size: 50, seed: 42.

R2 Qwen3 Annotator 0 value profile

Annotator_0 Profile (Imitation Guide)

- **Label/Score Bias**:
Strongly penalizes minor differences (e.g.,
word order, quantifiers like "some" vs.
"a few") unless they alter core meaning.
Assigns **-5** for completely unrelated
topics, **-3 to -1** for subtle
mismatches (e.g., scope, specificity,
context), **0** only when ambiguity
remains unresolved. **5** is given only
when meaning is identical or trivially
different (e.g., synonyms, rephrasing,
minor syntax).

- **Value Judgment Criteria**:
  Prioritizes **semantic precision** over
    surface similarity. Rejects paraphrases
    that differ in:
  – Subject (e.g., "all questions" vs. "some
    questions")
  – Object (e.g., "steak" vs. "tomahawk steak")
  – Scope (e.g., country, time, field, entity)
  – Intent (e.g., definition vs. background,
    action vs. condition)
  – Detail (e.g., "why" vs. "what", "how" with
    or without reasons)

- **Evidence Usage**:
  Relies **exclusively on explicit content**
    in the questions. Does **not** infer
    meaning from context, assumptions, or
    external knowledge. Compares **literal
    content** and **core intent**. Ignores
    extraneous details (e.g., URLs, names,
    dates) unless they change the subject or
    scope.

- **Explanation Style**:
  Concise, direct, and **diagnostic**. Uses
    clear comparative language ("Q1 asks
    for X, Q2 asks for Y") to highlight
    differences. Avoids speculation. Uses
    neutral, factual phrasing without
    emotional tone.

- **Typical Wording**:
  – "Q1 asks for X. Q2 asks for Y."
  – "The words to be translated are different."
  – "Time is different."
  – "Two different questions."
  – "Q2 adds a reason..."
  – "Scope is different."
  – "The field of professorship is different."
  – "They could be different trailer."
  – "The issues on the webpage are different."

- **Strictness**:
  Highly strict on semantic fidelity. Even
    slight shifts in focus (e.g., "after 20"
    vs. "after 20 years") or entity (e.g.,
    country, type of steak) lead to negative
    scores. Requires **exact alignment** in
    subject, object, and intent.

- **Uncertainty Handling**:
  Assigns **0 only when ambiguity is genuine**
    (e.g., unclear reference, missing
    context). Otherwise, defaults to **-1 or
    higher** if differences are detectable.
    Avoids neutral scores unless truly
    uncertain.

- **Quirks**:
  – **Sensitive to quantifiers and scope**:
    "some" vs. "all", "best" vs. "reliable"
    (assumes implied meaning).
  – **Rejects implied or contextual
    inferences** (e.g., "why" implies reasons
    -> not equivalent to "what").
  – **Finds differences in specificity**
    (e.g., "Dwarf DPS" vs. "Blood Elf DPS").
  – **Ignores

R2 Qwen3 Annotator 1 value profile

Annotator_1 Profile (Imitation Guide)

- **Label/Score Bias**:
  Tends to assign **high scores (4–5)** when
    questions share the **same core topic,
    object, and intent**, even with minor
    differences in phrasing or condition.
    Assigns **-4 or -5** when topics diverge,
    even if semantically related (e.g., same
    field but different focus, object, or
    condition). Avoids 0 unless ambiguity is
    clear.

- **Value Judgment Criteria**:
  Does **not** evaluate the correctness or
    quality of content. Focuses solely on
    semantic alignment and **topic
    coherence**. Does not judge tone,
    sentiment, or personal opinion.

- **Evidence Usage**:
  Uses **only explicit linguistic features**
    (topic, object, condition, subject,
    phrasing) to determine paraphrase status.
    Does **not** rely on external knowledge,
    context, or implied meaning.

- **Explanation Style**:
  Concise, direct, and **structured**. Always
    begins with a clear statement of the
    score, followed by a brief justification
    using phrases like:
  – "the same topic", "same topic and object",
    "similar topic but in different
    conditions", "different topics",
    "although refer to the same thing"
  – Avoids vague or emotional language.

- **Typical Wording**:
  – "the same topic and object of discussion"
  – "similar topic but in different conditions"
  – "different topics, although refer to the
    same thing"
  – "the same topic, subject and object..."
  – "different topics" (used as a strong
    negative signal)
  – "similar topic, although s2 is more
    specific" or "s1 refers to personal
    opinion"

- **Strictness**:
  Highly strict about topic boundaries.
    Even slight shifts in object (e.g.,
    "maids" vs. "maids office"), condition
    (e.g., time, location), or focus (e.g.,
    feeling vs. action) lead to negative
    scores.

- **Uncertainty**:
  Rarely assigns 0. When uncertainty exists,
    it is explicitly stated (e.g., "uncertain
    or mixed") only in edge cases, and even
    then, the explanation justifies the
    choice.

- **Quirks**:
  – **Sensitive to object specificity**: A
    shift in object (e.g., "Dwarf DPS" vs.
    "Blood Elf DPS") is treated as a
    condition change, not a topic shift.
  – **Ignores minor syntactic differences**
    (e.g., "what is" vs. "how is") if the
    core topic remains.
  – **Downgrades questions with added
    conditions or personal context** (e.g.,
    "I'm worried about my boards") unless the
    core topic is identical.
  – **Fails to treat semantic overlap as
    sufficient**––e.g., "what is the best"
    vs. "what are the best" is not enough to
    justify a 5.
  – **Consistently penalizes location/time
    shifts** (e.g., August 2014 vs. September
    2016) as "different conditions" rather
    than topic differences.

Imitation Rules for New Items:
1. Compare core topic, object, and intent.
2.

R2 Qwen3 Annotator 2 value profile

Annotator_2 Profile (Imitation Guide)

- **Label/Score Bias**:
  Tends to assign **high scores (4–5)** when
    questions share core domain, key phrase,

and intent, even with minor differences (e.g., word order, redundancy, or minor qualifiers). **Low scores (-3 to -5)** only when concepts are unrelated or domains diverge significantly. **Score 0** is used for "unrelated" or "folklore" queries with shared style but no semantic overlap.

- **Value Judgment Criteria**:
  Prioritizes **semantic similarity over syntactic form**. Ignores trivial differences like capitalization, "some" vs. "the", or "you" vs. "people" if the core intent and domain match. Values **domain specificity** and **shared entity/attribute** (e.g., "mount kailash", "gaming PC", "Wuthering Heights") as primary anchors.

- **Evidence Usage**:
  Relies on **lexical overlap**, **shared domain**, and **core query structure**. Explicitly notes **omitted or redundant phrases** (e.g., "and strong", "second trailer") as negligible. Uses **contextual cues** (e.g., "context-rich", "colloquial") to assess similarity, especially when one query is more specific or structured.

- **Explanation Style**:
  Concise, direct, and **diagnostic**. Uses **structured reasoning** with clear justifications:
  - Identifies overlap (e.g., "common_phrase", "domain specific")
  - Notes differences (e.g., "penalty for different entities", "redundancy", "contextual richness")
  - Explicitly states what is **neglected** or **ignored**
  - Avoids emotional or speculative language

- **Typical Wording**:
  - "Overlap: X; penalty: Y"
  - "Q1 and Q2 share domain, but differ in Z"
  - "Redundancy can be neglected"
  - "Key term overlap: X"
  - "Conceptually unrelated"
  - "Colloquial, low signal"
  - "Query context differs"
  - "Omission of X can be neglected"

- **Strictness**:
  Moderately strict -- allows minor syntactic or lexical variation if semantic intent and domain match. **Strict** when domains or concepts differ (e.g., "gym" vs. "hacking", "cancer" vs. "asthma"). Rejects paraphrase claims when the **core object or concept** is different.

- **Uncertainty**:
  Uses **score 0** only when queries are **conceptually unrelated** or **stylistically similar but semantically distinct** (e.g., "folklore", "humorous", "context-rich"). Avoids vague or ambiguous explanations.

- **Quirks**:
  - **Ignores grammatical errors** as long as domain and intent align (e.g., "I like to learn rhetoric is their any institute" -> scored -3 due to conceptual mismatch, not grammar).
  - **Values colloquialism** as a signal of shared context (e.g., "like a maniac", "plz help").
  - **Pen

R2 Qwen3 Annotator 3 value profile

Annotator_3 Profile (Imitation Guide)

- **Label/Score Bias**:
  Tends to assign **high scores (4-5)** when questions are structurally and semantically similar, especially when core intent, topic, and phrasing align closely. **Low scores (-3 to -5)** when key differences in focus, subject, or implied context create distinct meanings. Avoids assigning 0 unless there's a clear, significant divergence in intent or scope.

- **Value Judgment Criteria**:
  Prioritizes **semantic precision** over surface similarity. Judges based on whether the questions target the same concept, object, or outcome. Values **specificity** (e.g., "Dwarf DPS" vs. "Blood Elf DPS") and **contextual nuance** (e.g., "UK" vs. "global", "in Mexico" vs. "in Germany") as decisive differentiators.

- **Evidence Usage**:
  Relies **exclusively on textual content** and **explicit differences in keywords, focus, or implied scope**. Does not use external knowledge or assumptions. Uses **contrastive analysis** (e.g., "emphasizes X", "focuses on Y") to justify scores.

- **Explanation Style**:
  Concise, direct, and **diagnostic**. Always includes a **specific observation** about what differs (e.g., "emphasizes X", "different keywords", "different time/place", "entirely different answers"). Avoids vague or interpretive language.

- **Typical Wording**:
  - "They have the same meaning."
  - "They have a similar meaning."
  - "They have almost the same meaning."
  - "Different keywords that are asked can lead to entirely different answers."
  - "The second question emphasises X."
  - "They do not mean the same thing, even though both are about Y."
  - "The focus of the questions is completely different."
  - "These two sentences express very different things."

- **Strictness**:
  Highly strict. Requires **near-identical semantic intent** for a score of 5. Minor differences in phrasing, focus, or context (e.g., "UK" vs. "global", "Dwarf" vs. "Blood Elf") are sufficient to reduce the score. Rejects overlap without semantic alignment.

- **Uncertainty**:
  Only assigns **0 or 1** when the difference is subtle but meaningful (e.g., "emphasises 'at home'") or when intent is ambiguous. Avoids uncertainty unless clearly warranted by divergent focus or context.

- **Quirks**:
  - **Sensitive to specific terms** (e.g., "Dwarf DPS", "Tomahawk steak", "apple cider vinegar" vs. "apple cider").
  - **Highlights contextual differences** (time, location, object, scope) as primary reasons for scoring.
  - **Consistently uses "emphasises" or "focuses on"** to describe differences.

- **Avoids overgeneralization**; never assumes similarity without explicit textual alignment.
- **Scores −5 only when topics are fundamentally unrelated** (e.g., hacking vs. business names, health vs. history).

Imitation Rule Summary:
When two