# Thinking at the Right Size:
# Amortized Distillation Across Post-Trained LLMs

## Abstract

Practical deployment of large language models (LLMs) requires families of post-trained variants—instruction-tuned, reasoning-tuned, and chat-style models—each at multiple sizes to meet diverse latency and memory budgets. Producing each (variant, size) pair independently is prohibitive, so model families typically span only a handful of coarse-grained sizes per post-trained variant. Boomerang distillation (Kangaslahti et al., 2026) reduces this cost along the size axis for base models through model size interpolation by constructing models of intermediate sizes from a single teacher-student pair without additional training, but still treats each post-trained variant as a separate object of optimization. We introduce **ADAPT**—Amortized Distillation Across Post-Trained LLMs—a framework for amortizing distillation across both axes of a model family: size and post-training variant, producing $L \times K$ models for $L$ interpolated sizes across $K$ post-trained variants with a *single* distillation run. ADAPT combines two components. First, a two-phase distillation procedure constructs post-trained students through pre-training alignment and supervised fine-tuning distillation, enabling smooth size–performance interpolation on generation and reasoning tasks. Second, weight-delta initialization approximates this construction across post-trained variants by transferring the distillation-induced weight change from the base model to students initialized from different post-trained variants. The resulting continuum of interpolated models also enables adaptive model-size selection at inference time, improving the compute–accuracy trade-off for long-form reasoning tasks.

## 1 Introduction

Deployed LLM applications rely overwhelmingly on post-trained models—instruction-tuned, reasoning-tuned, and chat-style variants—rather than base pre-trained ones. They also span a wide range of compute environments, from mobile devices to personal laptops to on-premise servers with multi-GPU clusters, with correspondingly diverse latency and memory constraints (Huyen, 2022; Narayan et al., 2025). Practical use thus requires families of models that vary along two axes: size, to meet deployment compute constraints, and post-trained variants, to support different downstream capabilities. Training each (variant, size) combination from scratch is computationally infeasible, so model families are typically released only at a few coarse-grained sizes per variant, and only at a few variants per base model (Team, 2026).

Existing approaches address one of these axes but not both. Layer pruning (Men et al., 2025; Chen et al., 2025) removes transformer layers from a fixed model to produce smaller variants, but generation and reasoning performance collapse. Knowledge distillation (Hinton et al., 2015; Sanh et al., 2019) transfers capability from a teacher to a smaller student model but requires a separate run per target size. More recently, boomerang distillation (Kangaslahti et al., 2026) removes this per-size cost by distilling a single student with an alignment loss objective and then patching the teacher layers back in to produce intermediate model sizes without additional training. It thus efficiently covers the size axis, though only in the pre-trained setting and evaluated primarily on classification tasks. Whether this strategy extends to post-trained models, where instruction-following and reasoning are central, is the key question this paper investigates.

A natural first approach is to apply the boomerang distillation recipe directly to a post-trained teacher: initialize a student from the teacher, distill, and patch. We find that this does not work: generation and reasoning performance collapses across most intermediate sizes for both in-domain and out-of-domain tasks, despite the post-trained teacher itself achieving strong performance on these tasks (Figure 2). This

Figure 1: **ADAPT: Amortized Distillation Across Post-Trained LLMs.** We distill a base student once, yielding $L$ interpolated model sizes from a single teacher–student pair. We then compute the distillation-induced weight delta and add it to the initialized students from multiple post-trained teachers. This amortizes distillation for post-trained LLMs: one distillation run can now produce $L \times K$ models across $K$ post-trained variants.

asymmetry suggests that instruction-following depends on properties of the distillation process that the original recipe does not provide.

In response, we introduce **ADAPT**—Amortized Distillation Across Post-Trained LLMs—a framework for constructing post-trained model families across both model size and post-training variant axes. ADAPT combines two-phase distillation with weight-delta initialization. First, two-phase distillation distills a student for each post-trained variant, using both pre-training alignment and supervised fine-tuning distillation for instruction following and reasoning, enabling smooth model size interpolation without any additional training. We then provide weight-delta initialization as an approximate construction that avoids separate distillation runs by transferring the distillation-induced weight change from the base model to students initialized from different post-trained variants of the same base model. This allows a single base-model distillation run to produce $L \times K$ models: $L$ interpolated model sizes for each of $K$ post-trained variants.

Our experiments show that ADAPT recovers smooth size-performance interpolation on generation and reasoning benchmarks and outperforms standard boomerang distillation and layer pruning baselines at equal compute. The resulting family of intermediate-sized models supports adaptive inference: routing easier inputs to smaller models traces an empirical compute–accuracy Pareto frontier that dominates any single fixed model. To understand why a single base-model distillation transfers to multiple post-trained variants, we examine the un-

derlying weight-space geometry. Empirically, base and post-trained models—and their corresponding distilled students—are connected by low-loss linear interpolation paths, a form of smooth weight interpolation that is preserved through distillation. The distillation update thus operates within a connected region of weight space shared by base and post-trained models, providing a geometric explanation of why weight-arithmetic transfer succeeds in this setting.

In summary, our contributions are:

- We introduce ADAPT, a framework for amortizing distillation runs to create interpolated post-trained model families across sizes and post-training variants.

- We show that ADAPT outperforms strong baselines, including boomerang distillation and layer pruning approaches, while enabling improved performance–compute trade-offs through adaptive model-size selection.

- We provide an empirical analysis of size-agnostic smooth weight interpolation, showing that the weight-space structure connecting base and post-trained models is preserved after distillation and helps explain the success of weight-delta initialization.

## 2 Related Work

**Knowledge distillation.** Knowledge distillation is an effective technique for training a smaller model using a larger teacher model (Hinton

et al., 2015; Sanh et al., 2019). Several LLM families, including Qwen (Yang et al., 2025), DeepSeek (Guo et al., 2025a), and Gemma (Team et al., 2025), distill their larger pre-trained models into smaller models. These smaller LLMs show improved performance when compared to naive training, but require individual distillation runs. In this work, we introduce a two-phase distillation pipeline and a weight-arithmetic procedure that produces a family of post-trained models using a single distillation run.

**Post-training LLMs.** Post-training is a critical step in the language model training pipeline, in which pre-trained LLMs are trained to follow instructions (Olmo et al., 2025; Guo et al., 2025b; Bercovich et al., 2025). Because post-training is expensive, recent work aims to reduce its compute cost (Ye et al., 2025; Nayak et al., 2026), but often requires training models at every size. Here, we distill a single post-trained student LLM and then create interpolated post-trained LLMs of varying sizes without training additional models, thereby dramatically reducing compute cost.

**Model Arithmetic.** Model arithmetic enables practitioners to combine the skills of multiple models into a single unified model by simply adding or subtracting model weights (Ilharco et al., 2023). Prior work has used model arithmetic for instruction following (Ilharco et al., 2023), creating multitask models (Yadav et al., 2024), and machine unlearning (Liu et al., 2025). In this work, we use model arithmetic to amortize student distillation by transferring the distillation-induced weight delta from a base student to students initialized from multiple post-trained variants.

**Adaptive compute.** Adapting LLM compute to input difficulty significantly reduces latency requirements during inference (Taghibakhshi et al., 2026). While recent work has shown promising results for test-time scaling (Muennighoff et al., 2025), many of these approaches require training fine-grained models from scratch (Kusupati et al., 2022) or rely on heuristics such as appending thinking tokens (Muennighoff et al., 2025). In this work, we dynamically adjust inference compute by adapting the model size based on the input difficulty for reasoning and generation tasks.

**Layer pruning.** Layer pruning removes transformer layers from a trained LLM under an importance criterion, sometimes followed by a healing step (Men et al., 2025; Chen et al., 2025). While effective at preserving classification accuracy, recent analyses show that pruning collapses open-ended generation (Shrestha et al., 2026). ADAPT instead recovers generation capability through a targeted two-phase distillation step, and substantially outperforms layer pruning approaches such as ShortGPT and LLM-Streamline (Section 4.4).

# 3 ADAPT: Amortizing Distillation Across Post-Trained LLMs

We begin by summarizing boomerang distillation (Kangaslahti et al., 2026), a recently proposed method for zero-shot model size interpolation. We then introduce the two versions of ADAPT: ADAPT (distilled), a two-phase distillation framework for constructing interpolated post-trained models, and ADAPT (weight-delta), a weight-delta initialization method that approximates the two-phase distillation process across model variants and constructs multiple post-trained model families from a single distillation run.

## 3.1 Boomerang Distillation

Boomerang distillation (Kangaslahti et al., 2026) distills a small student from a teacher in such a way that intermediate models can be constructed by combining student and teacher layers without additional training. We now discuss its three stages.

**Student initialization.** Let $\boldsymbol{T}$ be the teacher with $N$ layers denoted by $\boldsymbol{\theta}_T$, and $\boldsymbol{S}$ with parameters $\boldsymbol{\theta}_S$ and $M$ layers be the student, where $M < N$. The student is initialized by partitioning the $N$ teacher layers into $M$ blocks of consecutive layers. From each of these blocks, the first layer is used to initialize the corresponding student layer. The student's embedding and LM head are initialized from $\boldsymbol{T}$.

**Knowledge distillation.** The initialized student is trained on a pre-training corpus such as the Pile (Gao et al., 2020) on a combined loss involving a logit-level knowledge distillation loss, such as KL, and a block-wise alignment loss, such as cosine distance, that pushes each student layer's output towards the outputs of the corresponding block of teacher layers. Specifically, given a training corpus $\mathcal{D}$ and a sample $x = (x_1, ..., x_L) \in \mathcal{D}$, an index $j$, and denoting the next-token distributions by $p(\cdot \mid x_{<j})$, the per-token loss $\mathcal{L}_{\boldsymbol{\theta}_S}(x_j)$ is:

$$\mathcal{L}_{\boldsymbol{\theta_S}}(x_j) = \text{CE}(x_j \mid x_{<j}; \boldsymbol{\theta_S})$$
$$+ \lambda_{\text{KL}} \, \text{KL}\big(p_{\boldsymbol{T}}(\cdot \mid x_{<j}) \,\big\|\, p_{\boldsymbol{S}}(\cdot \mid x_{<j})\big)$$
$$+ \lambda_{\cos} \sum_{i=1}^{M} \mathcal{L}_{\cos}^{(i)}(x_{<j}; \boldsymbol{\theta_T}, \boldsymbol{\theta_S}).$$

$$(1)$$

Here, CE denotes the next-token cross-entropy loss and $\mathcal{L}_{\cos}^{(i)}$ is the cosine distance between the outputs of the $i$th student layer and the $i$th teacher block. $\lambda_{\text{KL}} > 0$ and $\lambda_{\cos} > 0$ are hyperparameters that weight the three loss terms.

**Student patching.** After the distillation stage, boomerang distillation constructs intermediate models by *patching*—i.e., replacing student layers with their corresponding sets of teacher layers. We treat student patching as an important but complementary design choice and use simple front-to-back and back-to-front patching in the main experiments, selecting the better-performing of the two orders for each model (see Appendix H for details).

### 3.2 ADAPT

In this section, we present ADAPT for efficiently constructing post-trained model families.

#### 3.2.1 ADAPT (Distilled): Two-Phase Post-Trained Distillation

We propose a unified two-phase distillation procedure for model size interpolation in post-trained models. This consists of a *pre-training phase* followed by a *supervised fine-tuning phase*. The pre-training phase ensures that we recover the general language modeling capability in the initialized student model before restoring the instruction following and reasoning capabilities. In Section 4.2, we find that the two-phase distillation prevents overfitting and shows better out-of-domain performance.

**Pre-training phase.** We follow the standard knowledge distillation setup over a pre-training corpus $\mathcal{D}_{\text{pre}}$. Given a training sequence $x = (x_1, \ldots, x_L) \in \mathcal{D}_{\text{pre}}$, the loss from Equation 1 is summed over all positions $x_2, \ldots, x_L$. Training on pre-training data not only mitigates catastrophic forgetting, but has even been shown to improve downstream performance (Kotha and Liang, 2026).

**Supervised fine-tuning phase.** In this phase, we transition to instruction-following data $\mathcal{D}_{\text{SFT}}$, where each sequence $(x, y) \in \mathcal{D}_{\text{SFT}}$ consists of

a prompt $x = (x_1, \ldots, x_L)$ and a response $y = (y_1, \ldots, y_{L'})$. We use the same distillation objective, but loss (Equation 1) is computed only over all the response tokens. This stage allows the student to adopt instruction-following capabilities and adapt to downstream generation tasks, while preserving alignment to the teacher.

For simplicity, we dedicate half of training to pre-training and half to supervised fine-tuning. We also use a continuous LR schedule for both phases as we found in initial experiments that two separate schedulers can hurt final performance.

#### 3.2.2 ADAPT (Weight-Delta): Weight-Delta Initialization

Although the two-phase distillation produces strong interpolated model families for generation and reasoning tasks, applying it independently to each post-trained variant still requires a separate distillation run. We propose **weight-delta initialization**, a simple weight-arithmetic procedure that transfers a base-model distillation run to a post-trained variant without additional training, approximately constructing distilled post-trained student models and amortizing the cost of constructing multiple post-trained model families.

Let $\boldsymbol{\theta}_{S,\text{init}}^{\text{base}}$ denote the student initialized from the base teacher, and let $\boldsymbol{\theta}_{S,\text{distill}}^{\text{base}}$ denote the corresponding student after distillation. We define the distillation delta as:

$$\Delta_{S,\text{distill}}^{\text{base}} = \boldsymbol{\theta}_{S,\text{distill}}^{\text{base}} - \boldsymbol{\theta}_{S,\text{init}}^{\text{base}}.$$

Given a student $\boldsymbol{\theta}_{S,\text{init}}^{\text{PT}}$ initialized from a post-trained teacher using the same layer-selection rule and parameter shapes as $\boldsymbol{\theta}_{S,\text{init}}^{\text{base}}$, we construct the weight-delta-initialized student $\boldsymbol{\theta}_{S,\Delta}^{\text{PT}}$ as:

$$\boldsymbol{\theta}_{S,\Delta}^{\text{PT}} = \boldsymbol{\theta}_{S,\text{init}}^{\text{PT}} + \Delta_{S,\text{distill}}^{\text{base}}.$$

The resulting model $\boldsymbol{\theta}_{S,\Delta}^{\text{PT}}$ is intended to approximate the directly distilled post-trained student $\boldsymbol{\theta}_{S,\text{distill}}^{\text{PT}}$ in downstream performance, while avoiding the cost of an additional distillation run.

## 4 Experiments

Here we study the creation of post-trained model families using ADAPT. We show the benefits of ADAPT over strong baselines (Section 4.2 and 4.3) and layer pruning approaches (Section 4.4). Then, we show ADAPT offers a better performance–compute trade-off than a single model (Section 4.5). Finally, we analyze the loss landscape to understand weight-delta initialization (Section 4.6).

Figure 2: **ADAPT improves generation performance significantly over boomerang distillation.** For generation tasks that are both in-domain (math reasoning) and out-of-domain (instruction following and general knowledge) relative to our SFT dataset, SFT training is necessary to recover generation performance, especially for smaller models. For OOD tasks, two-phase distillation stabilizes performance compared to SFT-only training. We observe similar results for Olmo-3-7B-Instruct and Llama-3.1-8B-Instruct in Appendices L.1 and L.2.

## 4.1 Setup

In our experiments, we primarily use Qwen3-4B-Instruct-2507 (Yang et al., 2025) as the teacher model. We also study Qwen3-4B-Thinking-2507 and Qwen3-4B in Section 4.3. We initialize the student models with 2.7B inference-time parameters by removing every other layer from the teacher (excluding the final layer). We train on a total budget of 1B tokens. For more training details, see Appendices A and B. We also reproduce experiments with Olmo (Olmo et al., 2025) and Llama (Grattafiori et al., 2024) families in Appendices L.1 and L.2. We train on the deduplicated Pile (Gao et al., 2020) during the pre-training stage, and the math split of the Llama Nemotron Post-Training Dataset (Bercovich et al., 2025) during the SFT stage. We primarily evaluate our models on a set of five generation benchmarks measuring instruction-following and mathematical reasoning. For more implementation details, see Appendix C. We include error bars of one standard deviation in all the figures.

## 4.2 Two-Phase Distillation for Reasoning

We begin by showing that a two-phase distillation pipeline is key to model size interpolation for generation tasks, yielding substantially stronger interpolation performance than boomerang distillation.

**Setup.** We compare five setups on an equal training budget. The baseline follows standard boomerang distillation on the base model. Post-trained model patching (PT-patch (1 phase)) uses the same base model distilled on the pre-training phase only, but instead patches from the post-trained teacher (Qwen3-4B-Instruct-2507). The pre-training-only setup performs distillation on general language modeling data only, while SFT-only performs distillation only on the math SFT data. Finally, our two-phase pipeline ADAPT (distilled) first performs pre-training distillation to align the student with the teacher, then performs math SFT distillation to recover generation and reasoning capabilities. We evaluate on three in-domain (ID) math reasoning tasks and two out-of-domain (OOD) tasks focused on instruction-following and general understanding capabilities.

**Results.** Figure 2 shows a sharp separation between methods on generation tasks. Standard base-model boomerang distillation performs poorly, indicating that base-model interpolation does not directly transfer to post-trained generation. Pre-training-only distillation improves at larger model sizes but remains weak for smaller models, while PT-patch (1 phase) recovers nontrivial performance as more post-trained teacher layers are inserted. This suggests that base and post-trained models remain partially compatible, motivating our weight-delta transfer experiments in Section 4.3.

Overall, ADAPT (distilled) achieves the strongest interpolation performance on both ID and OOD tasks by combining pre-training alignment with SFT capability recovery. Unlike SFT-only, it preserves stronger OOD performance and classification performance (Appendix D.2), while also improving last-layer activation alignment with the teacher (Appendix D.1). We observe similar trends for Olmo and Llama in Appendix L.

Figure 3: **ADAPT (weight-delta) enables reusable base-model distillation across post-trained variants.** ADAPT (weight-delta) and PT-patch (2 phase) use the same two-phase-distilled base student and training compute. ADAPT (weight-delta) matches ADAPT (distilled) on ID tasks while substantially outperforming PT-patch (2 phase), showing that one base-model distillation run can transfer to multiple post-trained variants without additional training. We report OOD performance in Appendix E.1.

## 4.3 Weight-Delta Initialization Enables Reusable Base Distillation

We demonstrate that ADAPT (weight-delta) can reuse a single base-model distillation run across multiple post-trained variants, recovering much of the interpolation behavior of directly distilled post-trained students without additional distillation.

**Setup.** We construct the student models for Qwen3-4B-Instruct-2507, Qwen3-4B-Thinking-2507, and Qwen3-4B using ADAPT (weight-delta). Specifically, we first perform two-phase distillation on the Qwen3-4B-Base student to obtain the base distillation delta, then add this delta to students initialized from each post-trained variant. We compare against ADAPT (distilled), a higher-compute upper bound that runs a separate two-phase distillation for each post-trained student, and PT-patch (2 phase), which patches post-trained teacher layers into the same two-phase-distilled base student without applying the weight delta. PT-patch (2 phase) serves as a baseline, as it requires the same training compute as ADAPT (weight-delta). All methods use the same student architecture, layer-selection rule, patching order, and evaluation protocol.

**Results.** Figure 3 shows that ADAPT (weight-delta) achieves interpolation performance comparable to ADAPT (distilled) on ID tasks across the evaluated Qwen variants, while requiring no additional distillation on the post-trained teachers. On OOD tasks (Appendix E.1), we observe slight degradation, but this is largely due to formatting and parsing issues for thinking-style outputs rather than broad degradation in generation quality. ADAPT (weight-delta) also substantially

outperforms PT-patch (2 phase) across post-trained variants, suggesting that the base-model distillation delta transfers useful instruction-following capability and enables stronger interpolation than patching alone.

Results for Olmo and Llama models (Appendix L) suggest that ADAPT (weight-delta) generally falls between ADAPT (distilled) and PT-patch (2 phase), and is comparable to ADAPT (distilled) in many cases. It also achieves higher interpolation AUC than PT-patch (2 phase) in all ID settings, making it a cheaper but still strong-performing alternative to separately distilling each post-trained variant.

We experimented with continued training from the weight-delta initialized model, $\theta_{S,\Delta}^{\text{PT}}$, but found that it did not improve interpolation performance; we include these results in Appendix E.2. We also report results for one-phase weight-delta initialization in Appendix E.3, where the transferred distillation delta is computed from a base student distilled on the pre-training phase only. This setting still demonstrates strong cross-model distillation transfer, but generally underperforms the two-phase weight-delta initialization used in ADAPT.

Overall, these results demonstrate the amortization benefit of ADAPT: a single base-model distillation run can produce interpolated families for multiple post-trained variants, rather than only multiple sizes of one model.

## 4.4 Comparison to Layer Pruning Methods

We compare ADAPT against layer pruning methods on generation benchmarks to show that it produces substantially stronger intermediate models.

Figure 4: **ADAPT significantly outperforms layer pruning baselines on generation tasks.** We compare ADAPT (distilled) and ADAPT (weight-delta) to two popular layer pruning methods for generation tasks, ShortGPT (Men et al., 2025) and LLM-Streamline (Chen et al., 2025), and show that our method performs substantially better across all sizes.

**Setup.** We consider two popular layer pruning methods: ShortGPT (Men et al., 2025) and LLM-Streamline (Chen et al., 2025). ShortGPT prunes the least influential layers, as determined by the block influence score, which is the cosine distance between the layer's input and output activations. LLM-Streamline identifies the block of layers with the lowest block influence score, replaces it with a lightweight network, and trains it to recover the input and output activations of the pruned block. For more details, see Appendix F.

**Results.** Figure 4 shows that across all model sizes, ADAPT (distilled) and ADAPT (weight-delta) models consistently outperform ShortGPT and LLM-Streamline, which struggle to recover meaningful generation capability, especially at smaller sizes.

### 4.5 Adaptive Model-Size Selection

In this section, we show that ADAPT allows us to dynamically choose from the suite of interpolated models at inference time, enabling a Pareto-optimal trade-off between downstream performance and computational efficiency. Dynamically adapting compute to input difficulty improves compute utilization while preserving performance, a practical requirement for deployment.

**Setup.** We use the MATH dataset (Hendrycks et al., 2021b), which contains competition-style problems with varying difficulty levels. We estimate each problem's difficulty using a single forward pass with the teacher model, Qwen3-4B-Instruct-2507, and provide details in Appendix G. For each interpolated model $m$ over difficulty level $d \in \{1, \ldots, 5\}$, we estimate accuracy $A(m, d)$ on a training split. Given a target threshold $\tau$, we route each difficulty level to the smallest model $m_d$ satisfying $A(m_d, d) \geq \tau$.

We consider two selection criteria: average accuracy, $A_{\text{avg}}(m, d)$, and minimum accuracy, $A_{\min}(m, d)$, the latter yielding a more conservative policy. At inference time, we select the model $m_d$ corresponding to the predicted difficulty $d$. Sweeping over $\tau$ produces routing policies with different accuracy–compute trade-offs, which we compare against fixed single-model baselines.

**Results.** Figure 5 shows that the adaptive model-size selection approach outperforms the single-model baseline, tracing out a superior Pareto frontier across both average and minimum accuracy metrics for both ADAPT (distilled) and ADAPT (weight-delta) models. This improvement arises from assigning smaller models to easier questions while reserving larger models for harder ones, thereby using compute more efficiently. Across all thresholds, the adaptive approach consistently achieves higher accuracy at comparable or lower FLOPs per token, showing that a continuum of interpolated models whose performance increases smoothly with size offers a superior performance-compute trade-off over a single model.

### 4.6 Size-Agnostic Smooth Weight Interpolation

The weight-delta initialization results suggest that base-model distillation remains compatible with post-trained variants. To better understand this, we study whether interpolation between base and post-trained models is preserved after distillation. We call this property **size-agnostic smooth weight interpolation**: the low-loss linear path between a base model and its post-trained variant is preserved in the corresponding student models after distillation. For models $\boldsymbol{\theta}^{(a)}$ and $\boldsymbol{\theta}^{(b)}$, we evaluate models $\boldsymbol{\theta}(\alpha) = (1 - \alpha)\boldsymbol{\theta}^{(a)} + \alpha\boldsymbol{\theta}^{(b)}$ where $\alpha \in [0, 1]$.

Figure 6 shows that interpolation paths between base and post-trained models do not exhibit sharp loss barriers for either teachers or students. The

Figure 5: **ADAPT enables adaptive model-size selection based on input difficulty for more compute-efficient inference.** By producing a continuum of interpolated models with smoothly varying performance, ADAPT allows for more fine-grained matching between model capacity and task difficulty. This approach achieves a Pareto-optimal trade-off between average and worst-case accuracy and computational efficiency.

Figure 6: **Smooth weight interpolation is preserved after distillation.** Across post-trained variants, both teacher and distilled student models exhibit smooth interpolation paths between base and post-trained endpoints, suggesting that the relevant weight-space structure is preserved after distillation.

Figure 7: **Weight-delta initialization produces a student in a connected region of high generation performance.** We report AUC for generation accuracy between student and teacher models on the plane intersecting base, instruct, and weight-delta students. The weight-delta student has improved AUC compared to the base student and lies in a high-performance region connected to both the base and instruct students.

loss increases toward the post-trained endpoints because they are evaluated on the Pile, which is better matched to base models than post-trained variants. Importantly, students retain similar interpolation behavior after distillation, suggesting that distillation preserves much of the weight-space structure connecting base and post-trained models. We observe similar trends for generation accuracy and SFT loss in Appendix I. We further examine this geometry using a two-dimensional generation-accuracy AUC landscape over the plane spanned by the base, instruct, and weight-delta students. Here, AUC denotes the area under the generation-accuracy curve, measured between the smaller student and the corresponding teacher model. Figure 7 shows that the weight-delta initialized student lies in a high-performing region connected to both the base and distilled instruct students. These results suggest that distillation preserves smooth weight interpolation across model sizes, suggesting a possible connection to linear-mode connectivity (Garipov et al., 2018).

## 5 Conclusion

We introduce ADAPT, a framework for amortizing distillation across both the size and post-training-variant axes of a model family. ADAPT substantially outperforms boomerang distillation and layer pruning baselines on reasoning and instruction-following benchmarks under matched compute, and the resulting continuum of interpolated models enables adaptive model-size selection at inference time. Crucially, we find that smooth linear weight interpolation between base and post-trained models is preserved across model sizes after distillation, providing a plausible mechanism for the success of weight-arithmetic transfer in our setting. This connection between size interpolation and linear mode connectivity points to a broader principle—that distillation can be reused across related models, not just sizes—and we view its further investigation as a promising direction.

## Limitations

ADAPT is effective across the model families and benchmarks we study, but several aspects warrant further investigation. We highlight open questions about the underlying mechanism, assumptions implicit in our procedure, and the empirical scope of our evaluation.

**Interpolation dips at specific sizes.** As also observed by Kangaslahti et al. (2026), some interpolation curves show sharp drops at particular intermediate sizes. A plausible explanation is that the inserted teacher layers are locally misaligned with the surrounding student layers at those configurations, but the precise mechanism remains unclear. Characterizing and predicting these failure modes remain open directions. We also observe that the weight-delta transfer is not uniformly reliable across Olmo and Llama (Figures 14 and 15), especially in some OOD settings and intermediate sizes. This suggests that weight-delta effectiveness depends on model-family compatibility and post-training details, and should be validated beyond the settings studied here.

**Model and data scope.** Our experiments cover three model families (Qwen, Olmo, Llama) at the 4B–8B scale and use the math split of the Llama Nemotron post-training dataset for the SFT phase. It remains to be verified whether ADAPT retains its size-amortization benefits at larger model scales (e.g., 10B+ teachers) and across broader instruction-tuning mixtures (e.g., code, multilingual).

**Weight-delta assumptions.** Weight-delta initialization requires access to the base model used to produce each post-trained variant. For some open-weight releases (and most closed-weight releases) the corresponding base checkpoint is unavailable or not exactly identifiable, restricting which model families ADAPT (weight-delta) can target without additional approximation.

**Adaptive inference depends on a difficulty signal.** The compute–accuracy gains from adaptive model-size selection (Section 4.5) rely on a per-input difficulty estimate. Our MATH experiments use teacher-predicted difficulty, which is cheap but task-specific; we have not characterized how well this approach generalizes to settings where difficulty is not well-defined or where a separate difficulty predictor would be expensive to obtain.

**Hyperparameter sensitivity.** We fix the pre-training/SFT split at 50/50 and use a single layer-selection and patching order per model. Both are likely improvable, and we have not measured how robust ADAPT is to substantially different choices.

## Ethical Considerations

Our experiments use publicly available datasets and evaluation benchmarks, primarily focused on mathematical reasoning, instruction following, and general model evaluation. We also use publicly available model checkpoints as teachers and base models. We do not collect new human-subject data. However, because pre-training and post-training datasets may contain web-derived text, they may inherit biases, harmful content, or privacy concerns from their source corpora. Similarly, the models used in this work may inherit biases or unsafe behaviors from their original training pipelines or the datasets we use. Our work does not attempt to remove these risks, and downstream users should evaluate generated outputs for safety, bias, and reliability before deployment.

## References

AI-MO. 2025. Aimo validation aime dataset. https://huggingface.co/datasets/AI-MO/aimo-validation-aime. Accessed: 2026-03-29.

Art of Problem Solving. n.d. Aops wiki: Competition ratings. https://artofproblemsolving.com/wiki/index.php/AoPS_Wiki:Competition_ratings. Accessed: 2026-03-23.

Akhiad Bercovich, Itay Levy, Izik Golan, Mohammad Dabbah, Ran El-Yaniv, Omri Puny, Ido Galil, Zach Moshe, Tomer Ronen, Najeeb Nabwani, Ido Shahaf, Oren Tropp, Ehud Karpas, Ran Zilberstein, Jiaqi Zeng, Soumye Singhal, Alexander Bukharin, Yian Zhang, Tugrul Konuk, and 114 others. 2025. Llama-nemotron: Efficient reasoning models. *Preprint*, arXiv:2505.00949.

Yonatan Bisk, Rowan Zellers, Ronan Le Bras, Jianfeng Gao, and Yejin Choi. 2020. Piqa: Reasoning about physical commonsense in natural language. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 7432–7439.

Xiaodong Chen, Yuxuan Hu, Jing Zhang, Yanling Wang, Cuiping Li, and Hong Chen. 2025. Streamlining redundant layers to compress large language models. *Preprint*, arXiv:2403.19135.

Christopher Clark, Kenton Lee, Ming-Wei Chang, Tom Kwiatkowski, Michael Collins, and Kristina Toutanova. 2019. BoolQ: Exploring the surprising

difficulty of natural yes/no questions. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 2924–2936, Minneapolis, Minnesota. Association for Computational Linguistics.

Peter Clark, Isaac Cowhey, Oren Etzioni, Tushar Khot, Ashish Sabharwal, Carissa Schoenick, and Oyvind Tafjord. 2018. Think you have solved question answering? try arc, the ai2 reasoning challenge. *Preprint*, arXiv:1803.05457.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, Christopher Hesse, and John Schulman. 2021. Training verifiers to solve math word problems. *Preprint*, arXiv:2110.14168.

Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, Shawn Presser, and Connor Leahy. 2020. The pile: An 800gb dataset of diverse text for language modeling. *Preprint*, arXiv:2101.00027.

Leo Gao, Jonathan Tow, Baber Abbasi, Stella Biderman, Sid Black, Anthony DiPofi, Charles Foster, Laurence Golding, Jeffrey Hsu, Alain Le Noac'h, Haonan Li, Kyle McDonell, Niklas Muennighoff, Chris Ociepa, Jason Phang, Laria Reynolds, Hailey Schoelkopf, Aviya Skowron, Lintang Sutawika, and 5 others. 2023. A framework for few-shot language model evaluation.

Timur Garipov, Pavel Izmailov, Dmitrii Podoprikhin, Dmitry Vetrov, and Andrew Gordon Wilson. 2018. Loss surfaces, mode connectivity, and fast ensembling of dnns. *Preprint*, arXiv:1802.10026.

Aryo Pradipta Gema, Joshua Ong Jun Leang, Giwon Hong, Alessio Devoto, Alberto Carlo Maria Mancino, Rohit Saxena, Xuanli He, Yu Zhao, Xiaotang Du, Mohammad Reza Ghasemi Madani, Claire Barale, Robert McHardy, Joshua Harris, Jean Kaddour, Emile van Krieken, and Pasquale Minervini. 2025. Are we done with mmlu? *Preprint*, arXiv:2406.04127.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, Xiaokang Zhang, Xingkai Yu, Yu Wu, Z. F. Wu, Zhibin Gou, Zhihong Shao, Zhuoshu Li, Ziyi Gao, Aixin Liu, and 175 others. 2025a. Deepseek-r1 incentivizes reasoning in llms through reinforcement learning. *Nature*, 645(8081):633–638.

Daya Guo, Dejian Yang, Haowei Zhang, Junxiao Song, Peiyi Wang, Qihao Zhu, Runxin Xu, Ruoyu Zhang, Shirong Ma, Xiao Bi, and 1 others. 2025b. Deepseek-r1: Incentivizing reasoning capability in llms via reinforcement learning. *arXiv preprint arXiv:2501.12948*.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. 2021a. Measuring massive multitask language understanding. In *International Conference on Learning Representations*.

Dan Hendrycks, Collin Burns, Saurav Kadavath, Akul Arora, Steven Basart, Eric Tang, Dawn Song, and Jacob Steinhardt. 2021b. Measuring mathematical problem solving with the math dataset. *Preprint*, arXiv:2103.03874.

Geoffrey Hinton, Oriol Vinyals, and Jeff Dean. 2015. Distilling the knowledge in a neural network. *Preprint*, arXiv:1503.02531.

Jordan Hoffmann, Sebastian Borgeaud, Arthur Mensch, Elena Buchatskaya, Trevor Cai, Eliza Rutherford, Diego de Las Casas, Lisa Anne Hendricks, Johannes Welbl, Aidan Clark, Tom Hennigan, Eric Noland, Katie Millican, George van den Driessche, Bogdan Damoc, Aurelia Guy, Simon Osindero, Karen Simonyan, Erich Elsen, and 3 others. 2022. Training compute-optimal large language models. *Preprint*, arXiv:2203.15556.

Chip Huyen. 2022. *Designing machine learning systems*. O'Reilly Media, Inc.

Gabriel Ilharco, Marco Tulio Ribeiro, Mitchell Wortsman, Suchin Gururangan, Ludwig Schmidt, Hannaneh Hajishirzi, and Ali Farhadi. 2023. Editing models with task arithmetic. *Preprint*, arXiv:2212.04089.

Sara Kangaslahti, Nihal V. Nayak, Jonathan Geuter, Marco Fumero, Francesco Locatello, and David Alvarez-Melis. 2026. Boomerang distillation enables zero-shot model size interpolation. In *The Fourteenth International Conference on Learning Representations*.

Yeganeh Kordi, Nihal V. Nayak, Max Zuo, Ilana Nguyen, and Stephen H. Bach. 2025. Revisiting generalization across difficulty levels: It's not so easy. *Preprint*, arXiv:2511.21692.

Suhas Kotha and Percy Liang. 2026. Replaying pre-training data improves fine-tuning. *Preprint*, arXiv:2603.04964.

Aditya Kusupati, Gantavya Bhatt, Aniket Rege, Matthew Wallingford, Aditya Sinha, Vivek Ramanujan, William Howard-Snyder, Kaifeng Chen, Sham M. Kakade, Prateek Jain, and Ali Farhadi. 2022. Matryoshka representation learning. In *Advances in Neural Information Processing Systems 35: Annual Conference on Neural Information Processing Systems 2022, NeurIPS 2022, New Orleans, LA, USA, November 28 - December 9, 2022*.

Guokun Lai, Qizhe Xie, Hanxiao Liu, Yiming Yang, and Eduard Hovy. 2017. RACE: Large-scale ReAding comprehension dataset from examinations. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pages 785–794, Copenhagen, Denmark. Association for Computational Linguistics.

Sijia Liu, Yuanshun Yao, Jinghan Jia, Stephen Casper, Nathalie Baracaldo, Peter Hase, Yuguang Yao, Chris Yuhao Liu, Xiaojun Xu, Hang Li, and 1 others. 2025. Rethinking machine unlearning for large language models. *Nature Machine Intelligence*, 7(2):181–194.

Xin Men, Mingyu Xu, Qingyu Zhang, Qianhao Yuan, Bingning Wang, Hongyu Lin, Yaojie Lu, Xianpei Han, and Weipeng Chen. 2025. ShortGPT: Layers in large language models are more redundant than you expect. In *Findings of the Association for Computational Linguistics: ACL 2025*, pages 20192–20204, Vienna, Austria. Association for Computational Linguistics.

Todor Mihaylov, Peter Clark, Tushar Khot, and Ashish Sabharwal. 2018. Can a suit of armor conduct electricity? a new dataset for open book question answering. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 2381–2391, Brussels, Belgium. Association for Computational Linguistics.

Niklas Muennighoff, Zitong Yang, Weijia Shi, Xiang Lisa Li, Li Fei-Fei, Hannaneh Hajishirzi, Luke Zettlemoyer, Percy Liang, Emmanuel Candès, and Tatsunori Hashimoto. 2025. s1: Simple test-time scaling. *ArXiv preprint*, abs/2501.19393.

Avanika Narayan, Dan Biderman, Sabri Eyuboglu, Avner May, Scott Linderman, James Zou, and Christopher Re. 2025. Cost-efficient collaboration between on-device and cloud language models. In *Forty-second International Conference on Machine Learning*.

Nihal V Nayak, Paula Rodriguez-Diaz, Neha Hulkund, Sara Beery, and David Alvarez-Melis. 2026. A critical look at targeted instruction selection: Disentangling what matters (and what doesn't). *arXiv preprint arXiv:2602.14696*.

Team Olmo, Allyson Ettinger, Amanda Bertsch, Bailey Kuehl, David Graham, David Heineman, Dirk Groeneveld, Faeze Brahman, Finbarr Timbers, Hamish Ivison, Jacob Morrison, Jake Poznanski, Kyle Lo, Luca Soldaini, Matt Jordan, Mayee Chen, Michael Noukhovitch, Nathan Lambert, Pete Walsh, and 49 others. 2025. Olmo 3. *Preprint*, arXiv:2512.13961.

Keisuke Sakaguchi, Ronan Le Bras, Chandra Bhagavatula, and Yejin Choi. 2020. Winogrande: An adversarial winograd schema challenge at scale. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 34, pages 8732–8740.

Victor Sanh, Lysandre Debut, Julien Chaumond, and Thomas Wolf. 2019. Distilbert, a distilled version of bert: smaller, faster, cheaper and lighter. *ArXiv preprint*, abs/1910.01108.

Safal Shrestha, Anubhav Shrestha, Aadim Nepal, Minwu Kim, and Keith Ross. 2026. On the limits of layer pruning for generative reasoning in llms. *Preprint*, arXiv:2602.01997.

Ali Taghibakhshi, Ruisi Cai, Saurav Muralidharan, Sharath Turuvekere Sreenivas, Aditya Vavre, Ameya Sunil Mahabaleshwarkar, Bilal Kartal, Sheldon Liang, Marcin Chochowski, Zijia Chen, and 1 others. 2026. Star elastic: Many-in-one reasoning llms with efficient budget control. *arXiv preprint arXiv:2605.07182*.

Gemma Team, Aishwarya Kamath, Johan Ferret, Shreya Pathak, Nino Vieillard, Ramona Merhej, Sarah Perrin, Tatiana Matejovicova, Alexandre Ramé, Morgane Rivière, Louis Rouillard, Thomas Mesnard, Geoffrey Cideron, Jean bastien Grill, Sabela Ramos, Edouard Yvinec, Michelle Casbon, Etienne Pot, Ivo Penchev, and 197 others. 2025. Gemma 3 technical report. *Preprint*, arXiv:2503.19786.

Qwen Team. 2026. Qwen3.5: Accelerating productivity with native multimodal agents.

Abdul Waheed, Chancharik Mitra, Laurie Z. Wang, Deva Ramanan, and Bhiksha Raj. 2025. Less is more tokens: Efficient math reasoning via difficulty-aware chain-of-thought distillation. *Preprint*, arXiv:2509.05226.

Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R. Bowman. 2019. GLUE: A multi-task benchmark and analysis platform for natural language understanding. In *International Conference on Learning Representations*.

Prateek Yadav, Tu Vu, Jonathan Lai, Alexandra Chronopoulou, Manaal Faruqui, Mohit Bansal, and Tsendsuren Munkhdalai. 2024. What matters for model merging at scale? *arXiv preprint arXiv:2410.03617*.

An Yang, Anfeng Li, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chang Gao, Chengen Huang, Chenxu Lv, Chujie Zheng, Dayiheng Liu, Fan Zhou, Fei Huang, Feng Hu, Hao Ge, Haoran Wei, Huan Lin, Jialong Tang, and 41 others. 2025. Qwen3 technical report. *Preprint*, arXiv:2505.09388.

Yixin Ye, Zhen Huang, Yang Xiao, Ethan Chern, Shijie Xia, and Pengfei Liu. 2025. Limo: Less is more for reasoning. *arXiv preprint arXiv:2502.03387*.

Rowan Zellers, Ari Holtzman, Yonatan Bisk, Ali Farhadi, and Yejin Choi. 2019. HellaSwag: Can a machine really finish your sentence? In *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pages 4791–4800, Florence, Italy. Association for Computational Linguistics.

Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. 2023. Instruction-following evaluation for large language models. *Preprint*, arXiv:2311.07911.

## A   Training Implementation Details

We use a mixture of non-thinking and thinking models in this paper. Non-thinking models include Qwen3-4B-Instruct-2507, Qwen3-4B, Olmo-3-7B-Instruct, and Llama-3.1-8B-Instruct. Thinking models include Qwen3-4B-Thinking-2507, Qwen3-4B, and Olmo-3-7B-Think. Note that Qwen3-4B can toggle between thinking and non-thinking modes.

For model training, we use a total token budget of 1B for the Qwen family models. For the larger models (Olmo and Llama), we scale up the total budget proportionally, to 2B tokens (Hoffmann et al., 2022). Across different configurations of the same model, we choose hyperparameters such that the number of tokens per update remains approximately constant between the pre-training phase and SFT phase. The hyperparameters reported in Table 3 correspond to using the deduplicated Pile (Gao et al., 2020) for pre-training and the Llama Nemotron Post-Training Dataset (Bercovich et al., 2025) for the SFT phase. For Nemotron, we use the math split for all models. For non-thinking models, we use examples with non-thinking ground truths (i.e., responses not enclosed in <think> and </think>), while for thinking models we use examples with thinking ground truths (version 1.1).

Each Qwen-family training run takes approximately 12 hours on 4 NVIDIA H100 GPUs. The Olmo and Llama models are trained using 4 NVIDIA H200 GPUs, each taking approximately 24 hours. We will release the distilled models under an Apache 2.0 license.

## B   Hyperparameters

We choose the majority of the hyperparameters (Table 1) following Kangaslahti et al. (2026). We determine the KL and cosine loss weights such that cross entropy, KL, and cosine loss are approximately equal in magnitude early in training. M denotes the number of student layers. When doing two-phase distillation, we use a single LR scheduler across the two phases.

## C   Evaluation Implementation Details

For generation, we use a custom evaluation pipeline for more fine-grained control over chat template and system prompt settings. Table 4 shows the system prompts used for each benchmark. We report the average accuracy on 5 benchmarks: AIME (AIMO, 2025), GSM8K (Cobbe et al., 2021), IFEval

| Hyperparameters | Values |
|---|---|
| Learning rate | 3e-4 |
| LR scheduler | cosine |
| Warmup ratio | 0.01 |
| Optimizer | AdamW |
| Adam betas | (0.9, 0.95) |
| Adam epsilon | 1e-8 |
| Weight decay | 0.1 |
| Max gradient norm | 1.0 |
| Mixed precision | bf16 |
| KL weight $\lambda_{KL}$ | 0.1 |
| Cosine weight $\lambda_{cos}$ | 10.0 / (M+1) |

Table 1: **Hyperparameters for distillation training.**

(Zhou et al., 2023), MATH500 (Hendrycks et al., 2021b), MMLU-REDUX (Gema et al., 2025). We consider AIME, GSM8K, and MATH500 to be in-domain (ID) math reasoning tasks and IFEval and MMLU-REDUX to be out-of-domain (OOD) tasks. For Section 4.5, we use the MATH dataset (Hendrycks et al., 2021b), which contains ground truth question difficulty labels. We elaborate on this further in Appendix G.

For classification tasks, we use `lm-evaluation-harness` (Gao et al., 2023) and report the average accuracy on 10 benchmarks: ARC-easy and ARC-challenge (Clark et al., 2018), BoolQ (Clark et al., 2019), HellaSwag (Zellers et al., 2019), MMLU (Hendrycks et al., 2021a), OpenBookQA (Mihaylov et al., 2018), PIQA (Bisk et al., 2020), RACE (Lai et al., 2017), RTE (Wang et al., 2019), and WinoGrande (Sakaguchi et al., 2020).

Table 2 shows the sampling parameters used for non-thinking and thinking models, which follow the recommended values by Yang et al. (2025).

| Models | Non-thinking | Thinking |
|---|---|---|
| Max output len. | 16384 | 32768 |
| Temperature | 0.7 | 0.6 |
| Top p | 0.8 | 0.95 |
| Top k | 20 | 20 |
| Min. p | 0.0 | 0.0 |
| Presence penalty | 0.5 | 0.5 |
| Min. tokens | 32 | 32 |

Table 2: **Sampling parameters for non-thinking and thinking models.**

| Model Type | Setup | Pre-training Phase | | | SFT Phase | | |
|---|---|---|---|---|---|---|---|
| | | Steps | Effective BS | Seq. len. | Steps | Effective BS | Seq. len. |
| Small (Non-think) | Pile only | 480 | 2048 | 1024 | – | – | – |
| | Nemotron only | – | – | – | 585 | 4096 | 1024 |
| | Pile+Nemotron | 240 | 2048 | 1024 | 293 | 4096 | 1024 |
| Small (Think) | Pile only | 500 | 512 | 4096 | – | – | – |
| | Nemotron only | – | – | – | 400 | 1024 | 4096 |
| | Pile+Nemotron | 250 | 512 | 4096 | 200 | 1024 | 4096 |
| Large (Non-think) | Pile only | 960 | 2048 | 1024 | – | – | – |
| | Nemotron only | – | – | – | 1170 | 4096 | 1024 |
| | Pile+Nemotron | 480 | 2048 | 1024 | 585 | 4096 | 1024 |
| Large (Think) | Pile only | 1000 | 512 | 4096 | – | – | – |
| | Nemotron only | – | – | – | 800 | 1024 | 4096 |
| | Pile+Nemotron | 500 | 512 | 4096 | 400 | 1024 | 4096 |

Table 3: **Training hyperparameters across model families.** We report the number of steps, effective batch size, and sequence length for the pre-training and SFT phases across all distillation setups. Small models refer to the 4B parameter Qwen family models. Large models refer to the 7B/8B Olmo and Llama models.

| Benchmarks | System Prompts |
|---|---|
| AIME, GSM8K, MATH500, MATH | Please reason step by step, and put your final answer within \boxed{}. |
| IFEval | None |
| MMLU-REDUX | Please reason step by step, and select the answer from the given choices A, B, C, or D. Respond only with the letter of the correct answer. Put the index within \boxed{}. |

Table 4: **System prompts for generation tasks.**

Figure 8: **Final layer activation cosine similarity between student and teacher models.** The two-phase distillation setup yields the best student-teacher alignment, further motivating our approach.

# D  Additional Evaluation Results for ADAPT (Distilled)

Here, we provide additional results for the models in Figure 2. We first study final-layer cosine similarity to the teacher in Section D.1, then show results on classification tasks in Section D.2.

## D.1  Cosine Similarity Analysis

In this section, we report the final-layer activation cosine similarity between each interpolated model and the corresponding teacher for PT-patch (1-phase), pre-training-only, SFT-only, and ADAPT (distilled). We compute activations by averaging over all downstream tasks.

As shown in Figure 8, ADAPT (distilled) achieves the highest cosine similarity across nearly the entire interpolation curve. SFT-only also maintains strong alignment, but is consistently below ADAPT (distilled). PT-patch (1-phase) has the

Figure 9: **Classification accuracy is relatively insensitive to the distillation strategy.** Across Qwen, Olmo, and Llama, most setups exhibit similar interpolation behavior on classification benchmarks. The main exception is SFT-only, which underperforms across much of the interpolation curve, suggesting that task-specific distillation alone can degrade broader alignment with the teacher.

Figure 10: **OOD performance of weight-delta initialization on Qwen models.** Weight-delta initialization remains competitive with direct distillation and outperforms patching-only across Qwen variants. Degradation in thinking-style settings is mainly due to `<think>` formatting and parsing issues, rather than broad loss of generation quality.

weakest alignment, especially at smaller model sizes, indicating that patching alone does not sufficiently align the student with the post-trained teacher. These results provide additional motivation for the two-phase distillation approach.

## D.2 Classification Performance

Figure 9 shows that classification benchmarks are relatively insensitive to the distillation strategy. Most variants achieve similar interpolation performance, indicating that classification tasks do not fully expose the alignment challenges that arise in post-trained generation. The main exception is the SFT-only setup, which underperforms across much of the interpolation curve for all three model families, suggesting that task-specific distillation alone can degrade broader alignment with the teacher.

## E Additional Evaluation Results for ADAPT (Weight-Delta)

In this section, we provide additional results for the setting in Figure 3. We show OOD performance in

Section E.1, then explore continued training from ADAPT (weight-delta) models in Section E.2, and finally study pre-training-only ADAPT (weight-delta) in Section E.3.

## E.1 Qwen: OOD Performance for ADAPT (Weight-Delta)

We further evaluate ADAPT (weight-delta) on OOD tasks for Qwen models, which include IFEval and MMLU-Redux. Figure 10 compares ADAPT (weight-delta), ADAPT (distilled), and PT-patch (2-phase) across Qwen3-4B-Instruct-2507, Qwen3-4B-Thinking-2507, and Qwen3-4B.

Overall, ADAPT (weight-delta) remains competitive with direct distillation and substantially outperforms patching-only across most model sizes. The main degradation comes from thinking-style models at smaller and intermediate sizes. Inspecting outputs shows that this is largely due to formatting and parsing issues on IFEval: weight-delta models are initialized from a base distillation run without thinking-style `<think>` tags, so they can

Figure 11: **Continued training from weight-delta initialization does not improve interpolation performance.** We initialize the instruct student using either a one-phase weight delta, computed from base distillation on pre-training data only, or a two-phase weight delta, computed from base distillation on both pre-training and SFT data. We then continue training for 0.5B or 1B tokens. Continued training does not improve over the weight-delta initialization and converges to similar, suboptimal interpolation behavior.

produce malformed or missing delimiters. Since IFEval parses only the response after `</think>`, these errors reduce measured accuracy even when the generated content is otherwise reasonable.

This issue is specific to strict thinking-tag parsing rather than a broad loss of OOD capability. In particular, performance of ADAPT (weight-delta) remains strong on MMLU-Redux, where evaluation does not depend on parsing `</think>`. We provide individual benchmark breakdowns in Appendix M.

### E.2 Continued Training from Weight-Delta Initialization

We investigate whether weight-delta initialization can serve as a stronger initialization for additional distillation. Specifically, we ask whether continued training from a weight-delta-initialized student can outperform ADAPT (distilled). Figure 11 compares continued training from both one-phase and two-phase weight-delta initializations.

**Setup.** In the left panel, we initialize the instruct student by adding the distillation delta from a base model distilled only on the pre-training phase (1-phase). In the right panel, we instead use the delta from a base model distilled with both pre-training and SFT phases (2-phase). Starting from each initialization, we continue training for either 0.5B or 1B tokens using the same distillation setup described in Appendix B. We also sweep learning rates and find that 3e−4, the value used in Appendix B, performs the best.

**Results.** Continued training from weight-delta initialization does not improve interpolation performance beyond the weight-delta initialization itself. Training for 0.5B or 1B tokens converges to similar interpolation curves, regardless of whether the initialization comes from a one-phase (left panel) or two-phase (right panel) weight delta. This suggests that continued distillation largely washes out the difference between the two initializations rather than improving the final interpolated family.

Overall, these results indicate that the main benefit of weight-delta initialization comes from its zero-training transferability, not from providing a better starting point for further training.

### E.3 Weight-Delta Initialization with Pre-training-only Distillation

We evaluate whether weight-delta initialization works when the base distillation delta is computed from a one-phase distillation run using only pre-training data. This setting tests whether the transferable component of distillation can be obtained without the SFT phase.

**Setup.** We compute a one-phase distillation delta from a base student distilled only on pre-training data, and add this delta to initialized post-trained students across model families. We compare the resulting one-phase weight-delta initialized models against directly distilled pre-training-only students and the corresponding PT-patch (1-phase) baseline. We report the results for Qwen (Figure 12 and 13), Olmo (Figure 14), and Llama (Figure 15) families.

Figure 12: **One-phase weight-delta initialization ID performance for Qwen models.**

Figure 13: **One-phase weight-delta initialization OOD performance for post-trained Qwen models.**

Figure 14: **One-phase weight-delta initialization performance for post-trained Olmo models.**

Figure 15: **One-phase weight-delta initialization performance for post-trained Llama models.**

**Results.** Across model families, one-phase weight-delta initialization performs comparably to, and in some cases better than, direct pre-training-only distillation. This indicates that the alignment

| Hyperparameters | Values |
|---|---|
| Learning rate | 2e-4 |
| LR scheduler | cosine |
| Warmup ratio | 0.01 |
| Optimizer | AdamW |
| Adam betas | (0.9, 0.999) |
| Adam epsilon | 1e-8 |
| Weight decay | 1e-3 |
| Max gradient norm | 5.0 |
| Mixed precision | bf16 |

Table 5: **Hyperparameters for LLM-Streamline MSE replacement-layer training.**

| Hyperparameters | Values |
|---|---|
| Learning rate | 5e-5 |
| LR scheduler | cosine |
| Warmup ratio | 0.01 |
| Optimizer | AdamW |
| Adam betas | (0.9, 0.999) |
| Adam epsilon | 1e-8 |
| Weight decay | 1e-3 |
| Max gradient norm | 5.0 |
| Mixed precision | bf16 |

Table 6: **Hyperparameters for LLM-Streamline LM-loss post-training.**

learned during base-model pre-training distillation can transfer across post-trained variants.

However, one-phase weight-delta initialization remains weaker than the corresponding two-phase methods. Both two-phase weight-delta initialization (ADAPT (weight-delta)) and direct two-phase distillation (ADAPT (distilled)) achieve stronger interpolation performance, reflecting the importance of the SFT phase for recovering downstream generation and reasoning capability. Thus, one-phase weight-delta initialization is effective at transferring broad alignment, but two-phase distillation is still needed for the best post-trained interpolation performance.

## F  Layer Pruning Methods Details

### F.1  ShortGPT

For ShortGPT (Men et al., 2025), we first calculate the Block Influence score (BI), which is the cosine distance between the input and output activations. A higher BI score indicates higher importance of a specific layer. The BI score of the $\ell^{\text{th}}$ layer can be calculated as follows:

$$BI_\ell = 1 - \mathbb{E}_{X,t} \left[ \frac{\boldsymbol{x}_t^{(\ell)} \cdot \boldsymbol{x}_t^{(\ell+1)}}{\|\boldsymbol{x}_t^{(\ell)}\| \|\boldsymbol{x}_t^{(\ell+1)}\|} \right]$$

where $\boldsymbol{x}_t^{(\ell)}$ is the $t^{\text{th}}$ row of hidden states of the $\ell^{\text{th}}$ layer. When pruning, we sequentially remove layers with the lowest BI score. We compute BI using a held-out set of 128 calibration samples from Nemotron.

### F.2  LLM-Streamline

For LLM-Streamline (Chen et al., 2025), we identify the block of $n$ layers $(\ell^*, \ell^* + n)$ with the lowest BI score (using the same calibration set from

Nemotron as ShortGPT) and replace it with a single lightweight network. We then train the replacement network to imitate the pruned block using mean squared error (MSE):

$$\min_h \mathbb{E}_{(\boldsymbol{x}^{(\ell^*)}, \boldsymbol{x}^{(\ell^*+n)}) \in \mathcal{D}} \text{MSE}\left(h(\boldsymbol{x}_i^{(\ell^*)}), \boldsymbol{x}_i^{(\ell^*+n)}\right)$$

where $h$ denotes the lightweight network, $\mathcal{D}$ denotes the recorded hidden states of samples, and $\boldsymbol{x}^{(i)}$ is the hidden state of the $i^{\text{th}}$ layer.

Following Chen et al. (2025), we further post-train the replaced layer on language modeling loss in order to have a fairer comparison with our method.

In our implementation, we use a transformer block from the original Qwen3-4B-Instruct-2507 model as the lightweight layer and train it on the same data and token budget as ADAPT (distilled). We allocate 80% of the total training budget to lightweight network training and the remaining 20% to post-training. The MSE stage runs for 192 Pile steps and 234 Nemotron steps, while the LM-loss stage runs for 48 Pile steps and 59 Nemotron steps. All stages use sequence length of 1024, with effective batch size of 2048 for Pile and 4096 for Nemotron. We use the training hyperparameters shown in Tables 5 and 6. We perform evaluation following the same sampling strategy as discussed in Appendix C, using the non-thinking sampling parameters.

## G  Input Difficulty Classification for Adaptive Model Selection

As described in Section 4.5, we use the MATH dataset (Hendrycks et al., 2021b), which contains competition-style math problems with ground truth

Figure 16: **Interpolation performance of Qwen3-4B-Instruct-2507 for different difficulty levels.** We find that the teacher-defined difficulty score produces similar interpolation curves to the ground truth difficulty scores, but student-defined difficulty is unreliable.

difficulty labels according to the Art of Problem Solving (AoPS) competition ratings (Art of Problem Solving, n.d.). For our task, we sample 2 separate subsets of 1050 problems from the original dataset, each with 210 problems for each difficulty level. We use one as the training set to determine the optimal model routing policy, and the other as a test set to measure the efficiency gains of our method.

To create the model routing policy, we require a lightweight and reliable method for estimating input difficulty. We test both the student and teacher models as classifiers by prompting them to assign a difficulty rating to each question. Specifically, each input question is paired with a prompt describing the AoPS difficulty scale (Figure 17), and the model is asked to output a rating from 1 to 10. We merge all levels above 5 into level 5, since we know a priori that the MATH dataset contains problems of at most level 5 difficulty. To obtain predictions efficiently, we perform a single forward pass and extract the predicted class directly from the output logits.

To evaluate classification performance, we use the mean absolute error (MAE):

$$\text{MAE}_{\mathcal{D}_{\text{train}}}(\hat{\boldsymbol{y}}, \boldsymbol{y}) = \frac{1}{|\mathcal{D}_{\text{train}}|} \sum_{i \in \mathcal{D}_{\text{train}}} |\hat{y}_i - y_i|$$

where $\mathcal{D}_{\text{train}}$ denotes the training set, $\hat{y}_i$ is the predicted difficulty for the $i^{\text{th}}$ problem, and $y_i$ is the corresponding ground-truth difficulty.

On our training set, the teacher achieves an MAE of 0.970, while the student has an MAE of 1.995. This indicates that the teacher's predictions are typically within one difficulty level of the ground truth,

| Levels | Teacher | Student |
|--------|---------|---------|
| 1 | 184 | 1035 |
| 2 | 282 | 9 |
| 3 | 149 | 2 |
| 4 | 195 | 0 |
| 5 | 240 | 4 |

Table 7: **Breakdown of input-difficulty classification results from teacher and student models.** The student is unreliable for difficulty classification, as it chooses the lowest difficulty level for the vast majority of examples.

whereas the student's predictions deviate by approximately two levels on average. This suggests that the teacher provides substantially more accurate estimates for adaptive model selection. The class breakdown of the teacher and student predictions is shown in Table 7.

While the MATH dataset provides human-annotated difficulty labels, prior work has shown that human difficulty does not always align with model-perceived difficulty (Kordi et al., 2025). Figure 16 verifies that teacher-predicted labels produce well-separated and consistently ordered performance curves, closely matching the trends from ground-truth labels, whereas student-predicted labels are noisy and do not yield clear separation. This further supports using the teacher for difficulty estimation in adaptive model selection.

We omit the cost of difficulty classification from the results in Figure 5, as it requires only a single teacher forward pass and is negligible relative to the average response length of 3770.5 tokens.

**Difficulty Grading Prompt**

You will be given a math problem. Your job is to grade the difficulty level from 1-10 according to the AoPS standard.

Here is the standard:

All levels are estimated and refer to averages. The following is a rough standard based on the USA tier system AMC 8 - AMC 10 - AMC 12 - AIME - USAMO/USAJMO - IMO, representing Middle School - Junior High - High School - Challenging High School - Olympiad levels. Other contests can be interpolated against this.

Notes:

- Multiple choice tests like AMC are rated as though they are free-response.

- Some Olympiads are taken in 2 sessions, with similarly difficult sets of questions.

Scale

1: Problems strictly for beginners (e.g., AMC 8 1-20, AMC 10 1-10).

2: For motivated beginners (e.g., AMC 8 21-25, AMC 10 11-20).

3: Advanced beginner problems (e.g., AMC 10 21-25, AIME 4-6).

4: Intermediate-level problems (e.g., AMC 12 21-25, AIME 7-9).

5: More difficult AIME problems (10-12), simple Olympiad problems.

6: High-level AIME (13-15), introductory Olympiad questions.

7: Tougher Olympiad questions requiring technical knowledge.

8: High-level Olympiad questions.

9: Expert Olympiad questions.

10: Extremely difficult problems unsuitable for standard competitions.

Examples

<1: Counting edges/corners/faces of a cube (2003 AMC 8 Problem 1).

1: How many integers satisfy $|x| < 3\pi$? (2021 AMC 10B Problem 1).

2: Probability problem with die rolls (2021 AMC 10B Problem 18).

3: Geometry problem with area calculation (2018 AMC 10A Problem 24).

4: Recursive sequence problem (2019 AMC 10B Problem 24).

5: System of equations (JBMO 2020/1).

6: Complex geometry problem (2020 AMC I Problem 15).

7: IMO 2015 Problem 1 about balanced sets.

8: IMO 2014 Problem 5 about coin denominations.

9: IMO 2022 Problem 3 about prime arrangements.

10: IMO 2020 Problem 6 about point separation.

Task:

Problem to be labeled: {problem}.

Please put your estimation of the difficulty as a single number from 1-10.

Important: You MUST respond with only a single number between 1-10 indicating the difficulty of problem, not the solution of the problem.

Output: <difficulty level from 1-10>

Figure 17: **Prompt for difficulty classification (Waheed et al., 2025).**

Figure 18: **Comparison of interpolation performance for different patching orders.** We test patching from the front and patching from the back. We find that the optimal patching order is model-specific and use the better of patching from the front versus patching from the back in our experiments.

Figure 19: **Smooth weight interpolation results for generation accuracy.** Base and post-trained students display smooth interpolation behavior in downstream generation accuracy.

Figure 20: **Smooth weight interpolation results for loss on non-thinking Nemotron data.** Base and post-trained students display smooth interpolation behavior in loss evaluated on non-thinking Nemotron data.

Figure 21: **Smooth weight interpolation results for loss on thinking Nemotron data.** Base and post-trained students display smooth interpolation behavior in loss evaluated on thinking Nemotron data.

## H   Patching Order Experiment Results

Figure 18 shows the full interpolation curves for all three model families when testing front-to-back and back-to-front patching orders. These plots provide a more detailed view of how patching order affects interpolation behavior across model sizes.

We observe that the effect of patching order varies substantially across models. For Qwen3-4B-Instruct-2507, patching from the back has the best performance, but for Olmo-3-7B-Instruct and Llama-3.1-8B-Instruct, patching from the front yields the best performance. This suggests that the optimal patching depends on how different layers contribute to downstream generation performance in each model and architecture. In our experiments, we use the better-performing patching order.

## I   Additional Smooth Weight Interpolation Results

In this section, we report the smooth weight interpolation results for generation accuracy (Figure 19) and loss on SFT data (Figures 20 and 21). We observe that the same smooth weight interpolation be-

Figure 22: **Training dynamics study of two-phase distillation.** We find that two-phase distillation converges to two distinct interpolation curves during the pre-training and SFT stages, which allows the model to retain general-purpose and in-domain interpolation performance.

havior between the base and post-trained students holds across all three setups, providing additional evidence that distilled students mirror teacher-level connectivity in the weight space.

## J Training Dynamics

In Figure 22, we study how the interpolation performance behaves during the two-phase training. During the pre-training phase, the model converges to a lower interpolation performance curve very similar to the pre-training-only line in Figure 2. The SFT phase on Nemotron data initially produces improved student model performance but has a dip in interpolation performance at higher model sizes, then converges to a solution with both improved student model performance and smooth interpolation behavior. Taken together, this indicates that both phases converge to distinct solutions with general-purpose versus in-domain alignment to the teacher model.

## K Distillation with Cosine Loss Only

Figure 23 shows that distilling with cosine loss alone can yield performance comparable to the full objective combining cross-entropy, KL, and cosine losses. This suggests that intermediate representation alignment may be a key driver of interpolation behavior, and points to an orthogonal direction for improving distillation efficiency by simplifying the training objective.

## L ADAPT for Other Models

In this section, we show the performance of ADAPT for Olmo and Llama models.

### L.1 Replication Results for Olmo

We replicate the experiments from Sections 4.2 and 4.3 for Olmo-3-7B-Instruct and Olmo-3-7B-Think in Figures 24 and 25.

### L.2 Replication Results for Llama

We replicate the experiments from Sections 4.2 and 4.3 for Llama-3.1-8B-Instruct in Figures 26 and 27.

## M Individual Benchmark Results

### M.1 Two-phase Post-trained Distillation Results

The interpolation performance of Qwen3-4B-Instruct-2507 on individual benchmarks is shown in Figure 28.

### M.2 Weight-delta Initialization Results

The results from the weight-delta initialization experiments for Qwen model family on individual benchmarks are shown in Figure 29.

## N Use of Large Language Models

We utilized generative AI tools for code completion, debugging, and minor grammatical corrections in the manuscript. The authors carried out all the substantive research contributions, analyses, and interpretations.

Figure 23: **Distilling with cosine loss only yields interpolation performance comparable to the full objective.** We compare training with cosine alignment loss only to training with all of the loss terms in Equation 1 and find that cosine only training has similar performance, indicating that the efficiency of interpolation training can potentially be improved by using only alignment loss.

Figure 24: **Replication of Figure 2 for Olmo models.** Two-phase distillation produces the highest and most stable performance over both ID and OOD tasks.

Figure 25: **Replication of Figure 3 for Olmo models.** ADAPT (weight-delta) remains competitive with ADAPT (distilled) across both ID and OOD settings, while consistently outperforming PT-patch (2-phase) (with the exception of OOD performance for Olmo-3-7B-Think).

Figure 26: **Replication of Figure 2 for Llama models.** Two-phase distillation produces the highest and most stable performance over both ID and OOD tasks.

Figure 27: **Replication of Figure 3 for Llama models.** ADAPT (weight-delta) remains comparable with ADAPT (distilled) across both ID and OOD settings.

Figure 28: **Interpolation results for Qwen3-4B-Instruct-2507 on individual benchmarks.**

Figure 29: **Weight-delta initialization experiment results for Qwen model family on individual benchmarks.**