HeteroFL: Computation and Communication Efficient Federated Learning for Heterogeneous Clients

Abstract

Federated Learning (FL) is a method of training machine learning models on private data distributed over a large number of possibly heterogeneous clients such as mobile phones and IoT devices. In this work, we propose a new federated learning framework named *HeteroFL* to address heterogeneous clients equipped with very different computation and communication capabilities. Our solution can enable the training of heterogeneous local models with varying computation complexities and still produce a single global inference model. For the first time, our method challenges the underlying assumption of existing work that local models have to share the same architecture as the global model. We demonstrate several strategies to enhance FL training and conduct extensive empirical evaluations, including five computation complexity levels of three model architecture on three datasets. We show that adaptively distributing subnetworks according to clients' capabilities is both computation and communication efficient.

1 Introduction

Mobile devices and the Internet of Things (IoT) devices are becoming the primary computing resource for billions of users worldwide (Lim et al., 2020). These devices generate a significant amount of data that can be used to improve numerous existing applications (Hard et al., 2018). From the privacy and economic point of view, due to these devices' growing computational capabilities, it becomes increasingly attractive to store data and train models locally. Federated learning (FL) (Konečnỳ et al., 2016; McMahan et al., 2017) is a distributed machine learning framework that enables a number of clients to produce a global inference model without sharing local data by aggregating locally trained model parameters. A widely accepted assumption is that local models have to share the same architecture as the global model (Li et al., 2020b) to produce a single global inference model. With this underlying assumption, we have to limit the global model complexity for the most indigent client to train its data. In practice, the computation and communication capabilities of each client may vary significantly and even dynamically. It is crucial to address heterogeneous clients equipped with very different computation and communication capabilities.

In this work, we propose a new federated learning framework called *HeteroFL* to train heterogeneous local models with varying computation complexities and still produce a single global inference model. This **model heterogeneity** differs significantly from the classical distributed machine learning framework where local data are trained with the same model architecture (Li et al., 2020b; Ben-Nun & Hoefler, 2019). It is natural to adaptively distribute subnetworks according to clients' capabilities. However, to stably aggregate heterogeneous local models to a single global model under various heterogeneous settings is not apparent. Addressing these issues is thus a key component of our work. Our main contributions of this work are three-fold.

- We identify the possibility of model heterogeneity and propose an easy-to-implement framework *HeteroFL* that can train heterogeneous local models and aggregate them stably and effectively into a single global inference model. Our approach outperforms state-of-the-art results without introducing additional computation overhead.

- Our proposed solution addresses various heterogeneous settings where different proportions of clients have distinct capabilities. Our results demonstrate that even when the model

heterogeneity changes dynamically, the learning result from our framework is still stable and effective.

- We introduce several strategies for improving FL training and demonstrate that our method is robust against the non-IID statistical heterogeneity. Also, the proposed method can reduce the number of communication rounds needed to obtain state-of-the-art results. Experimental studies have been performed to evaluate the proposed approach.

2 RELATED WORK

Federated Learning aims to train massively distributed models at a large scale (Bonawitz et al., 2019). FedAvg proposed by McMahan et al. (2017) is currently the most widely adopted FL baseline, which reduces communication cost by allowing clients to train multiple iterations locally. Major challenges involved in FL include communication efficiency, system heterogeneity, statistical heterogeneity, and privacy (Li et al., 2020b). To reduce communication costs in FL, some studies propose to use data compression techniques such as quantization and sketching (Konečný et al., 2016; Alistarh et al., 2017; Ivkin et al., 2019). To tackle system heterogeneity, techniques of asynchronous communication and active sampling of clients have been developed (Bonawitz et al., 2019; Nishio & Yonetani, 2019). Statistical heterogeneity is the major battleground for current FL research. A research trend is to adapt the global model to accommodate personalized local models for non-IID data (Liang et al., 2020), e.g., by integrating FL with other frameworks such as assisted learning (Xian et al., 2020), meta-learning (Jiang et al., 2019; Khodak et al., 2019), multi-task learning (Smith et al., 2017), transfer learning (Wang et al., 2019; Mansour et al., 2020), knowledge distillation (Li & Wang, 2019) and lottery ticket hypothesis (Li et al., 2020a). Nevertheless, these personalization methods often introduce additional computation and communication overhead that may not be necessary. Another major concern of FL is data privacy (Lyu et al., 2020), as model gradient updates can reveal sensitive information (Melis et al., 2019) and even local training data (Zhu et al., 2019; Zhao et al., 2020).

To our best knowledge, what we present is the first work that allows local models to have different architectures from the global model. Heterogeneous local models can allow local clients to adaptively contribute to the training of global models. System heterogeneity and communication efficiency can be well addressed by our approach, where local clients can optimize low computation complexity models and therefore communicate a small number of model parameters. To address statistical heterogeneity, we propose a "Masking Trick" and demonstrate that personalization is unnecessary for non-IID data in classification problems. We also propose a modification of Batch Normalization (BN) (Ioffe & Szegedy, 2015) as privacy concern of running estimates hinders the usage of advanced deep learning models.

3 HETEROGENEOUS FEDERATED LEARNING

Federated Learning aims to train a global inference model from locally distributed data $\{X_1, \ldots, X_m\}$ across m clients. The local models are parameterized by model parameters $\{W_1, \ldots, W_m\}$. The server will receive local model parameters and aggregate them into a global model W_g through model averaging. This process iterates multiple communication rounds and can be formulated as $W_g^t = \frac{1}{m} \sum_{i=1}^{m} W_i^t$ at iteration t. At the next iteration, W_g^t is transmitted to a subset of local clients and update their local models as $W_i^{t+1} = W_g^t$.

In this work, we focus on the relaxation of the assumption that local models need to share the same architecture as the global model. Since our primary motivation is to reduce the computation and communication complexity of local clients, we consider local models to have similar architecture but can shrink their complexity within the same model class. To simplify global aggregation and local update, it is tempting to propose local model parameters to be a subset of global model parameters $W_i^{t+1} \subseteq W_g^t$. However, this raises several new challenges like the optimal way to select subsets of global model parameters, compatibility of the-state-of-art model architecture, and minimum modification from the existing FL framework. We develop Heterogeneous Federated Learning (HeteroFL) to address these issues in the context of deep learning models.

Global model parameters W_g

Local parameters W_l^3

Local parameters W_l^2

Local parameters W_l^1

Figure 1: Global model parameters W_g are distributed to $m = 6$ local clients with $p = 3$ computation complexity levels.

A variety of works show that we can modulate the size of deep neural networks by varying the width and depth of networks (Zagoruyko & Komodakis, 2016; Tan & Le, 2019). Because we aim to reduce the computation complexity of local models, we choose to vary the width of hidden channels. In this way, we can significantly reduce the number of local model parameters, while the local and global model architectures are also within the same model class, which stabilizes global model aggregation.

We demonstrate our method of selecting subsets of global model parameters W_l for a single hidden layer parameterized by $W_g \in \mathbf{R}^{d_g \times k_g}$ in Fig. 1, where d_g and k_g are the output and input channel size of this layer. It is possible to have multiple computation complexity levels $W_l^p \subset W_l^{p-1} \cdots \subset W_l^1$ as illustrated in Fig. 1. Let r be the hidden channel shrinkage ratio such that $d_l^p = r^{p-1} d_g$ and $k_l^p = r^{p-1} k_g$. It follows that the size of local model parameters $|W_l^p| = r^{2(p-1)} |W_g|$ and the model shrinkage ratio $R = \frac{|W_l^p|}{|W_g|} = r^{2(p-1)}$. With this construction, we can adaptively allocate subsets of global model parameters according to the corresponding capabilities of local clients. Suppose that number of clients in each computation complexity level is $\{m_1, \ldots, m_p\}$. Specifically, we perform global aggregation in the following way.

$$W_l^p = \frac{1}{m} \sum_{i=1}^m W_i^p, \quad W_l^{p-1} \setminus W_l^p = \frac{1}{m - m_p} \sum_{i=1}^{m-m_p} W_i^{p-1} \setminus W_i^p, \ldots \quad (1)$$

$$W_l^1 \setminus W_l^2 = \frac{1}{m - m_{2:p}} \sum_{i=1}^{m-m_{2:p}} W_i^1 \setminus W_i^2 \quad (2)$$

$$W_g = W_l^1 = W_l^p \cup (W_l^{p-1} \setminus W_l^p) \cup \cdots \cup (W_l^1 \setminus W_l^2) \quad (3)$$

For notational convenience, we have dropped the iteration index t. We exemplify the above equations using Fig. 1. The first part of Equation (1) shows that the smallest part of model parameters (blue, $p = 3$) is aggregated from all the local clients that contain it. In the second part of Equation (1), the set difference between part $p-1$ (orange) and p (blue) of model parameters is aggregated from local clients with computation complexity level smaller than $p - 1$. In Equation (2), the red part of model parameters can be similarly aggregated from $m - m_{2:p} = m_1$ clients. In Equation (3), the global model parameters W_g^t is constructed from the union of all disjoint sets of the partition.

Several works show that wide neural networks can drop a tremendous number of parameters per layer and still produce acceptable results (Han et al., 2015; Frankle & Carbin, 2018). The intuition is thus to perform global aggregation across all local models, at least on one subnetwork. To stabilize global model aggregation, we also allocate a fixed subnetwork for every computation complexity level. Our proposed inclusive subsets of global model parameters also guarantee that smaller local

models will aggregate with more local models. Thus, small local models can benefit more from global aggregation by performing less global aggregation for part of larger local model parameters. We empirically found that this approach produces better results than uniformly sampled subnetworks for each client or computation complexity level.

After global model parameters are distributed to active local clients, we can optimize local model parameters with private data. It is well-known that the latest deep learning models usually adopt Batch Normalization (BN) to facilitate and stabilize optimization. However, classical FedAvg and most recent works avoid BN. A major concern of BN is that it requires running estimates of representations at every hidden layer. Uploading these statistics to the server will have higher communication costs. Besides, because BN is usually attached before the activation layer, the server will have access to a linear transformed representation of local data. We believe that private data can be readily reconstructed with these running estimates. However, BN facilitates optimization and achieve the same performance with less number of communication rounds. Therefore, we propose **static Batch Normaliztion** (sBN) for optimizing privacy constrained deep neural networks. During the training phase, sBN does not track running estimates and simply normalize batch data. We only calculate statistics of hidden representations from local data after the model converges and is ready for inference. This method is suitable for the FL framework as local models do not need to upload running estimates during training. Local models only upload their statistics for once after optimization is completed. Thus, this method greatly reduces the risk of leaking private data. We also empirically found this trick can greatly facilitate optimization and produce comparable results as vanilla BN. Meanwhile, it is worth noting that vanilla BN is not compatible with our HeteroFL framework because the running estimates of subnetworks at different computation complexity levels significantly vary. Thus, the aggregation of those statistics severely deteriorates the performance.

There still exists another cornerstone of our HeteroFL framework. Because we need to optimize local models for multiple epochs, local model parameters at different computation complexity levels will digress to various scales. This known phenomenon was initially discussed the dropout (Srivastava et al., 2014). To directly use the full model during the inference phase, inverted dropout with dropout rate q scales representations with $\frac{1}{q}$ during the training phase. In practice, dropout is usually attached after the activation layer as the selection of subnetworks is performed with masking. Our method directly selects subnetworks from the subsets of global model parameters. Therefore, we append a **Scaler** module right after the parametric layer and before the sBN and activation layers. The Scaler module scales representations by $\frac{1}{r^{p-1}}$ during the training phase. After the global aggregation, the global model can be directly used for inference without scaling. A typical linear hidden layer used in our HeteroFL framework can be formulated as

$$y = \phi(\text{sBN}(\text{Scaler}(X_m W_m^p + b_m^p)))$$ (4)

where y is the output, $\phi(\cdot)$ is activation layer, and W_m^p, b_m^p are the weight and bias for local model m at computation complexity level p. With all the practical methods mentioned above, we propose the complete pseudo-code for our HeteroFL framework in Algorithm 1. We can also optionally update learning rates to facilitate optimization and local capabilities information if changing dynamically.

4 EXPERIMENTAL RESULTS

We trained over 600 individual models for exploring and demonstrating the effectiveness of our method. We experimented with MNIST and CIFAR10 image classification tasks and the WikiText2 language modeling task (LeCun et al., 1998; Krizhevsky et al., 2009; Merity et al., 2016; Devlin et al., 2018).

Our experiments are performed with three different models including a CNN for MNIST, a preactivated ResNet (PreResNet18) (He et al., 2016) for CIFAR10 and a Transformer (Vaswani et al., 2017) for WikiText2. We replace BN in CNN and PreResNet18 with our proposed sBN, and attach the Scaler module after each convolution layer. To study federated optimization, we adopt data partition the same as McMahan et al. (2017) and Liang et al. (2020). We have 100 clients, and the fraction C of active clients per communication round is 0.1 throughout our experiments. For IID data partition, we uniformly assign the same number of data examples for each client. For non-IID data partition, clients will only have examples at most from two classes. We conduct a masked language modeling task with a 15% masking rate and uniformly assign balanced data examples for each client. It needs

---

Algorithm 1: HeteroFL: Heterogeneous Federated Learning

Input: Data X_i distributed on M local clients, the fraction C of active clients per
communication round, the number of local epochs E, the local minibatch size B, the
learning rate η, the global model parameterized by W_g, the channel shrinkage ratio r,
and the number of computation complexity levels P.

System executes:

    Initialize W_g^0 and local capabilities information $L_{1:K}$

    for each communication round $t = 0, 1, 2, \ldots$ **do**

        $M_t \leftarrow \max(C \cdot M, 1)$

        $S_t \leftarrow$ random set of M_t clients

        for each client $m \in S_t$ **in parallel do**

            Determine computation complexity level p based on L_m

            $r_m \leftarrow r^{(p-1)}, d_m \leftarrow r_m d_g, k_m \leftarrow r_m k_g$

            $W_m^t \leftarrow W_g^t[: d_m, : k_m]$

            $W_m^{t+1} \leftarrow \text{ClientUpdate}(m, r_m, W_m^t)$

        end

        for each computation complexity level p **do**

            $W_g^{p-1,t+1} \setminus W_g^{p,t+1} \leftarrow \frac{1}{M_t - M_{p:P,t}} \sum_{i=1}^{M_t - M_{p:P,t}} W_i^{p-1,t+1} \setminus W_i^{p,t+1}$

        end

        $W_g^{t+1} \leftarrow \bigcup_{p=1}^{P} W_g^{p-1,t+1} \setminus W_g^{p,t+1}$

        Update $L_{1:K}, \eta$ (Optional)

    end

    Query representation statistics from local clients (Optional)

ClientUpdate (m, r_m, W_m)**:**

    $\mathcal{B}_m \leftarrow$ split local data X_m into batches of size B

    for each local epoch e from 1 to E **do**

        for batch $b_m \in \mathcal{B}_m$ **do**

            $W_m \leftarrow W_m - \eta \nabla \ell(W_m, r_m; b_m)$

        end

    end

    Return W_m to server

---

to point out that each client will roughly have 3000 different words in their local dataset, while the total vocabulary size is 33278. The details regarding hyperparameters and model architecture can be found in Table 4 of the Appendix.

To study the effectiveness of our proposed HeteroFL framework, we construct five different computation complexity levels $\{a, b, c, d, e\}$ with the hidden channel shrinkage ratio $r = 0.5$. Within the same model class like CNN and PreResNet18, model e has approximately 0.4% of parameters compared to model a. As for the Transformer model e, the embedding layer and the last layer for classification take up 99% of parameters (1.09 M over 1.1 M). In practice, each local client can query partial embeddings as not all words are present in a local dataset. Each local client is assigned an initial computation complexity level. We annotate *Fix* for experiments with a fixed assignment of computation complexity levels, and *Dynamic* for local clients uniformly sampling computation complexity levels at each communication round. We perform distinct experiments for *Fix* and *Dynamic* assignments.

To demonstrate the effect of proportionality of clients with various computation complexity levels, we interpolate from 10% to 100% with step size 10% of global model proportionality. For example, $a - b$ means to interpolate between a and b models starting from 10% of clients assigned level a and 90% of clients assigned level b to 100% level a clients. As illustrated in Fig. 2, the performance of clients with smaller models can be boosted by those with larger models. As shown in Table 2, 100% model e achieves 77.09% accuracy. By introducing 50% model a, the result can be boosted up to 89% for *Fix* and 90% for *Dynamic* assignments. The results show that HeteroFL can boost clients' performance with low computation and communication capabilities by allowing the training of heterogeneous models with larger computation complexities. With our method, *the clients*

Figure 2: Interpolation experimental results for CIFAR10 (IID) dataset between global model complexity ((a) a, (b) b, (c) c, (d) d) and various smaller model complexities.

with the lowest capabilities will not be the bottleneck of FL's performance. Results of MNIST and WikiText2 can be found in appendix in Fig. 3 and 4. These results also validate our statements.

To demonstrate the effect of dynamically varying computation and communication capabilities, we uniformly sample from various combinations of computation complexity levels. For example, $a - b - c - d - e$ means that we uniformly sample from all possible available levels for every active client at each communication round. We show the results regarding *Dynamic* assignments in Table 1-3. Note that single-letter model like model e has *Fix* levels. We show the number of model parameters, FLOPs, and Space (MB) to indicate the computation and communication requirements of our methods. For example, since we uniformly sample levels, model $a - e$ calculates these metrics by averaging those of model a and e. The ratio is calculated between the number of parameters of a given model with respect to its 100% global model. We compare our results to other baseline methods like Standalone, FedAvg, and LG-FedAvg (McMahan et al., 2017; Liang et al., 2020). Our method outperforms existing methods from several aspects. First, we can safely adopt more complex backbone deep learning models with sBN. A strong backbone model makes it possible to outperform existing results with even the simplest model e. Second, HeteroFL provides much more flexible options for clients with various capabilities to fully exploit their computation power. Full results including other possible combinations can be found in appendix in Table 5-7. Finally, our method is robust to dynamically varying model complexities. Thus HeteroFL is more reliable in practical applications. It is worth noting that our method does not incur any additional computation overhead and can be readily migrated from FedAvg framework.

We also perform experiments for non-IID data partition and provide a simple trick to achieve comparable results. As mentioned earlier, most state-of-the-art results of non-IID datasets suggest the personalization of local models to achieve better local results (Smith et al., 2017; Liang et al., 2020; Li et al., 2020a). Here *Local* results assume that the training data distribution and test data distribution for each local client are the same. In an image classification task, it means that local clients will not test with labels that are not trained locally. Meanwhile, *Global* results are obtained from the

Model	Ratio	Parameters	FLOPs	Space (MB)	Accuracy		
					IID	Non-IID	
						Local	Global
a	1.00	1.6 M	80.5 M	5.94	99.53	99.85	98.92
a-e	0.50	782 K	40.5 M	2.98	99.46	99.89	98.96
a-b-c-d-e	0.27	416 K	21.6 M	1.59	99.46	99.85	98.29
b	1.00	391 K	20.5 M	1.49	99.53	99.87	99.10
b-e	0.51	199 K	10.4 M	0.76	99.51	99.67	98.51
b-c-d-e	0.33	131 K	6.9 M	0.50	99.52	99.88	98.99
c	1.00	99 K	5.3 M	0.38	99.35	99.56	96.34
c-e	0.53	53 K	2.9 M	0.20	99.39	99.79	97.27
c-d-e	0.44	44 K	2.4 M	0.17	99.31	99.76	97.85
d	1.00	25 K	1.4 M	0.10	99.17	99.86	97.86
d-e	0.63	16 K	909 K	0.06	99.19	99.63	97.70
e	1.00	7 K	400 K	0.03	98.66	99.07	92.84
Standalone	1.00	633 K	1.3 M	2.42	86.24	98.72	30.41
FedAvg	1.00	633 K	1.3 M	2.42	97.93	98.20	98.20
LG-FedAvg	1.00	633 K	1.3 M	2.42	97.93	98.54	98.17

Table 1: Results of combination of various computation complexity levels for MNIST dataset. Full results can be found in Table 5.

overall test data. Zhao et al. (2018) shows that the failure of non-IID FL is related to the weight divergence among local model parameters trained locally for many iterations. The weight divergence mostly occurs in the last classification layer of networks. Thus, instead of a full Cross-Entropy Loss for all classes, we are motivated to train each local model only with their corresponding classes. In this way, each local model will train a subtask given locally available label information. Specifically, we mask out the output of the model before passing it Cross-Entropy Loss, which we named as **Masked Cross-Entropy Loss**. When aggregating local model parameters, we do not aggregate the untrained parameters in the last classification layers. Either the server can infer this information implicitly, or the local clients can report which classes they have to the server explicitly. We experimented with several different ways of masking, including replacing the last layer parameters that are not associated with local labels with zero, $-\infty$, or simply detach the corresponding parameters. We find only the first approach achieves both stable and comparable local and global results. The second approach, although stable, produces worse results. The last approach does not produce stable results when aggregated. Since our primary focus is to address model heterogeneity, we leave the analysis of this trick to future work. We show the results of interpolation experiments in appendix in Fig. 5-8. The results of non-IID data are less coherent than IID data, probably because our data partition does not set random seed and some clients with small models are partitioned with a single class data. *Dynamic* non-IID results are also included in Table 1-3. The results show that our method performs comparably to those with personalized local models. Our method is readily adaptable, free of computation overhead, and only rely on the single global model for testing local and global results. It allows local clients to switch to another subtask simply by changing its mask without querying the server for others' personalized models.

We show the learning curves of 50% *Fix* and *Dynamic* assignments in appendix in Fig. 9-11. The learning curves show that the optimization of HeteroFL for the IID dataset is stable and efficient. We empirically discover gradient clipping stabilizes the optimization of HeteroFL as it prevents small models from gradient explosion. We can therefore adopt a universal learning rate for heterogeneous local models. It is also perceivable that aggregation of model parameters trained with non-IID data makes the optimization less stable. Results of *Dynamic* show that aggregation of *Dynamic* assignments is stable. They are also slightly better than *Fix*, because clients are possible to train at the global model complexity level.

Model	Ratio	Parameters	FLOPs	Space (MB)	Accuracy		
					IID	Non-IID	
						Local	Global
a	1.00	9.6 M	330.2 M	36.71	91.19	92.38	56.88
a-e	0.50	4.8 M	165.9 M	18.43	90.29	92.10	59.11
a-b-c-d-e	0.27	2.6 M	88.4 M	9.78	88.83	92.49	61.64
b	1.00	2.4 M	83.3 M	9.19	89.82	93.83	55.45
b-e	0.51	1.2 M	42.4 M	4.67	89.10	90.68	59.81
b-c-d-e	0.33	801 K	27.9 M	3.05	87.92	91.90	59.10
c	1.00	604 K	21.2 M	2.30	87.55	91.09	55.12
c-e	0.53	321 K	11.3 M	1.22	86.88	91.83	63.47
c-d-e	0.44	265 K	9.4 M	1.01	85.79	91.49	55.42
d	1.00	152 K	5.5 M	0.58	84.21	90.77	61.13
d-e	0.63	95 K	3.5 M	0.36	82.93	90.89	56.16
e	1.00	38 K	1.5 M	0.15	77.09	89.62	54.16
Standalone	1.00	1.8 M	3.6 M	6.88	16.90	87.93	10.03
FedAvg	1.00	1.8 M	3.6 M	6.88	67.74	58.99	58.99
LG-FedAvg	1.00	1.8 M	3.6 M	6.88	69.76	91.77	60.79

Table 2: Results of combination of various computation complexity levels for CIFAR10 dataset. Full results can be found in Table 6.

Model	Ratio	Parameters	FLOPs	Space (MB)	Perplexity
a	1.00	19.3 M	1.4 B	73.49	3.37
a-e	0.53	10.2 M	718.6 M	38.86	3.75
a-b-c-d-e	0.37	7.2 M	496.6 M	27.55	3.55
b	1.00	9.1 M	614.8 M	34.74	3.46
b-e	0.56	5.1 M	342.0 M	19.49	3.90
b-c-d-e	0.46	4.2 M	278.7 M	16.07	3.64
c	1.00	4.4 M	290.1 M	16.92	3.62
c-e	0.62	2.8 M	179.7 M	10.57	3.89
c-d-e	0.58	2.6 M	166.7 M	9.85	3.66
d	1.00	2.2 M	140.7 M	8.39	3.83
d-e	0.75	1.7 M	105.0 M	6.31	3.90
e	1.00	1.1 M	69.3 M	4.23	7.41

Table 3: Results of combination of various computation complexity levels for WikiText2 dataset. Full results can be found in Table 7.

5 CONCLUSIONS AND FUTURE WORK

We propose Heterogeneous Federated Learning (HeteroFL), which shows the possibility of coordinatively training local models much smaller than a global model to produce a single global inference model. Our experiments show that FL can be made more practical by introducing HeteroFL and sBN and Mased Cross-Entropy Loss, as HeteroFL fully exploits local clients' capabilities and achieves better results with a fewer number of communication rounds. We demonstrate our results with various model architectures, including CNN, PreResNet18, and Transformer, and show that our method is robust to statistical heterogeneity and dynamically varying local capabilities. A future direction is to distinct model classes as well as model heterogeneity. Also, the proposed methods may be emulated to address heterogeneous few-shot learning, multi-modal learning, and multi-task learning.

REFERENCES

Dan Alistarh, Demjan Grubic, Jerry Li, Ryota Tomioka, and Milan Vojnovic. Qsgd: Communication-efficient sgd via gradient quantization and encoding. In *Advances in Neural Information Processing Systems*, pp. 1709–1720, 2017.

Tal Ben-Nun and Torsten Hoefler. Demystifying parallel and distributed deep learning: An in-depth concurrency analysis. *ACM Computing Surveys (CSUR)*, 52(4):1–43, 2019.

Keith Bonawitz, Hubert Eichner, Wolfgang Grieskamp, Dzmitry Huba, Alex Ingerman, Vladimir Ivanov, Chloe Kiddon, Jakub Konečnỳ, Stefano Mazzocchi, H Brendan McMahan, et al. Towards federated learning at scale: System design. *arXiv preprint arXiv:1902.01046*, 2019.

Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. *arXiv preprint arXiv:1810.04805*, 2018.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *arXiv preprint arXiv:1803.03635*, 2018.

Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *arXiv preprint arXiv:1510.00149*, 2015.

Andrew Hard, Kanishka Rao, Rajiv Mathews, Swaroop Ramaswamy, Françoise Beaufays, Sean Augenstein, Hubert Eichner, Chloé Kiddon, and Daniel Ramage. Federated learning for mobile keyboard prediction. *arXiv preprint arXiv:1811.03604*, 2018.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Identity mappings in deep residual networks. In *European conference on computer vision*, pp. 630–645. Springer, 2016.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. *arXiv preprint arXiv:1502.03167*, 2015.

Nikita Ivkin, Daniel Rothchild, Enayat Ullah, Ion Stoica, Raman Arora, et al. Communication-efficient distributed sgd with sketching. In *Advances in Neural Information Processing Systems*, pp. 13144–13154, 2019.

Yihan Jiang, Jakub Konečnỳ, Keith Rush, and Sreeram Kannan. Improving federated learning personalization via model agnostic meta learning. *arXiv preprint arXiv:1909.12488*, 2019.

Mikhail Khodak, Maria-Florina F Balcan, and Ameet S Talwalkar. Adaptive gradient-based meta-learning methods. In *Advances in Neural Information Processing Systems*, pp. 5917–5928, 2019.

Jakub Konečnỳ, H Brendan McMahan, Felix X Yu, Peter Richtárik, Ananda Theertha Suresh, and Dave Bacon. Federated learning: Strategies for improving communication efficiency. *arXiv preprint arXiv:1610.05492*, 2016.

Alex Krizhevsky et al. Learning multiple layers of features from tiny images. 2009.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Ang Li, Jingwei Sun, Binghui Wang, Lin Duan, Sicheng Li, Yiran Chen, and Hai Li. Lotteryfl: Personalized and communication-efficient federated learning with lottery ticket hypothesis on non-iid datasets. *arXiv preprint arXiv:2008.03371*, 2020a.

Daliang Li and Junpu Wang. Fedmd: Heterogenous federated learning via model distillation. *arXiv preprint arXiv:1910.03581*, 2019.

Tian Li, Anit Kumar Sahu, Ameet Talwalkar, and Virginia Smith. Federated learning: Challenges, methods, and future directions. *IEEE Signal Processing Magazine*, 37(3):50–60, 2020b.

Paul Pu Liang, Terrance Liu, Liu Ziyin, Ruslan Salakhutdinov, and Louis-Philippe Morency. Think locally, act globally: Federated learning with local and global representations. *arXiv preprint arXiv:2001.01523*, 2020.

Wei Yang Bryan Lim, Nguyen Cong Luong, Dinh Thai Hoang, Yutao Jiao, Ying-Chang Liang, Qiang Yang, Dusit Niyato, and Chunyan Miao. Federated learning in mobile edge networks: A comprehensive survey. *IEEE Communications Surveys & Tutorials*, 2020.

Lingjuan Lyu, Han Yu, and Qiang Yang. Threats to federated learning: A survey. *arXiv preprint arXiv:2003.02133*, 2020.

Yishay Mansour, Mehryar Mohri, Jae Ro, and Ananda Theertha Suresh. Three approaches for personalization with applications to federated learning. *arXiv preprint arXiv:2002.10619*, 2020.

Brendan McMahan, Eider Moore, Daniel Ramage, Seth Hampson, and Blaise Aguera y Arcas. Communication-efficient learning of deep networks from decentralized data. In *Artificial Intelligence and Statistics*, pp. 1273–1282. PMLR, 2017.

Luca Melis, Congzheng Song, Emiliano De Cristofaro, and Vitaly Shmatikov. Exploiting unintended feature leakage in collaborative learning. In *2019 IEEE Symposium on Security and Privacy (SP)*, pp. 691–706. IEEE, 2019.

Stephen Merity, Caiming Xiong, James Bradbury, and Richard Socher. Pointer sentinel mixture models. *arXiv preprint arXiv:1609.07843*, 2016.

Takayuki Nishio and Ryo Yonetani. Client selection for federated learning with heterogeneous resources in mobile edge. In *ICC 2019-2019 IEEE International Conference on Communications (ICC)*, pp. 1–7. IEEE, 2019.

Virginia Smith, Chao-Kai Chiang, Maziar Sanjabi, and Ameet S Talwalkar. Federated multi-task learning. In *Advances in Neural Information Processing Systems*, pp. 4424–4434, 2017.

Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. Dropout: a simple way to prevent neural networks from overfitting. *The journal of machine learning research*, 15(1):1929–1958, 2014.

Mingxing Tan and Quoc V Le. Efficientnet: Rethinking model scaling for convolutional neural networks. *arXiv preprint arXiv:1905.11946*, 2019.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Kangkang Wang, Rajiv Mathews, Chloé Kiddon, Hubert Eichner, Françoise Beaufays, and Daniel Ramage. Federated evaluation of on-device personalization. *arXiv preprint arXiv:1910.10252*, 2019.

Xun Xian, Xinran Wang, Jie Ding, and Reza Ghanadan. Assisted learning: A framework for multiple organizations' learning. *NeurIPS 2020 (spotlight)*, 2020.

Sergey Zagoruyko and Nikos Komodakis. Wide residual networks. *arXiv preprint arXiv:1605.07146*, 2016.

Bo Zhao, Konda Reddy Mopuri, and Hakan Bilen. idlg: Improved deep leakage from gradients. *arXiv preprint arXiv:2001.02610*, 2020.

Yue Zhao, Meng Li, Liangzhen Lai, Naveen Suda, Damon Civin, and Vikas Chandra. Federated learning with non-iid data. *arXiv preprint arXiv:1806.00582*, 2018.

Ligeng Zhu, Zhijian Liu, and Song Han. Deep leakage from gradients. In *Advances in Neural Information Processing Systems*, pp. 14774–14784, 2019.

A APPENDIX

Figure 3: Interpolation experimental results for MNIST (IID) dataset between global model complexity ((a) a, (b) b, (c) c, (d) d) and various smaller model complexities.

Data		MNIST	CIFAR10	WikiText2
Model		CNN	PreResNet18	Transformer
Hidden size		[64, 128, 256, 512]	[64, 128, 256, 512]	[512, 512, 512, 512]
E		5	5	1
B		10	10	100
Optimizer			SGD	
Momentum			0.9	
Weight decay			5.00E-04	
η		0.01	0.1	0.1
Communication rounds	IID	200	400	100
	non-IID	400	800	200
Decay schedule (0.1)	IID	[100]	[150, 250]	[25, 50]
	non-IID	[200]	[300, 500]	[50, 100]
Embedding Size				256
Number of heads			N/A	8
Dropout				0.2
Sequence length				64

Table 4: Hyperparameters and model architecture used in our experiments.

Figure 4: Interpolation experimental results for WikiText2 (IID) dataset between global model complexity ((a) a, (b) b, (c) c, (d) d) and various smaller model complexities.

Figure 5: Interpolation experimental results for MNIST (non-IID, Local) dataset between global model complexity ((a) a, (b) b, (c) c, (d) d) and various smaller model complexities.

Figure 6: Interpolation experimental results for CIFAR10 (non-IID, Local) dataset between global model complexity ((a) a, (b) b, (c) c, (d) d) and various smaller model complexities.

Figure 7: Interpolation experimental results for MNIST (non-IID, Global) dataset between global model complexity ((a) a, (b) b, (c) c, (d) d) and various smaller model complexities.

Figure 8: Interpolation experimental results for CIFAR10 (non-IID, Global) dataset between global model complexity ((a) a, (b) b, (c) c, (d) d) and various smaller model complexities.

Figure 9: Learning curves of MNIST datasets with 50% Fix and Dynamic computation complexity assignments.

Figure 10: Learning curves of CIFAR10 datasets with 50% Fix and Dynamic computation complexity assignments.

Figure 11: Learning curves of WikiText2 datasets with 50% Fix and Dynamic computation complexity assignments.

Model	Ratio	Parameters	FLOPs	Space (MB)	Accuracy		
					IID	Non-IID	
						Local	Global
a	1.00	1.6 M	80.5 M	5.94	99.53	99.85	98.92
a-b	0.63	974.1 K	50.5 M	3.72	99.54	99.96	99.10
a-c	0.53	827.9 K	42.9 M	3.16	99.52	99.89	99.12
a-d	0.51	791.1 K	41.0 M	3.02	99.54	99.81	98.37
a-e	0.50	781.7 K	40.5 M	2.98	99.46	99.89	98.96
a-b-c	0.44	682.4 K	35.4 M	2.60	99.53	99.90	98.72
a-b-d	0.42	657.8 K	34.1 M	2.51	99.52	99.78	98.02
a-b-e	0.42	651.6 K	33.8 M	2.49	99.54	99.95	98.92
a-c-d	0.36	560.4 K	29.1 M	2.14	99.57	99.95	99.34
a-c-e	0.36	554.1 K	28.7 M	2.11	99.52	99.94	98.43
a-d-e	0.34	529.6 K	27.4 M	2.02	99.57	99.80	98.92
a-b-c-d	0.33	518.1 K	26.9 M	1.98	99.54	99.80	99.03
a-b-c-e	0.33	513.4 K	26.7 M	1.96	99.46	99.69	97.53
a-b-d-e	0.32	495.0 K	25.7 M	1.89	99.49	99.85	98.66
a-c-d-e	0.27	421.9 K	21.9 M	1.61	99.54	99.84	98.80
a-b-c-d-e	0.27	415.8 K	21.6 M	1.59	99.46	99.85	98.29
b	1.00	391.4 K	20.5 M	1.49	99.53	99.87	99.10
b-c	0.63	245.1 K	12.9 M	0.94	99.49	99.87	99.05
b-d	0.53	208.3 K	11.0 M	0.79	99.44	99.85	98.95
b-e	0.51	199.0 K	10.4 M	0.76	99.51	99.67	98.51
b-c-d	0.44	171.9 K	9.1 M	0.66	99.54	99.84	98.98
b-c-e	0.42	165.6 K	8.7 M	0.63	99.51	99.85	98.20
b-d-e	0.36	141.1 K	7.4 M	0.54	99.48	99.89	98.72
b-c-d-e	0.33	130.5 K	6.9 M	0.50	99.52	99.88	98.99
c	1.00	98.9 K	5.3 M	0.38	99.35	99.56	96.34
c-d	0.63	62.1 K	3.4 M	0.24	99.38	99.92	99.05
c-e	0.53	52.8 K	2.9 M	0.20	99.39	99.79	97.27
c-d-e	0.44	43.6 K	2.4 M	0.17	99.31	99.76	97.85
d	1.00	25.3 K	1.4 M	0.10	99.17	99.86	97.86
d-e	0.63	15.9 K	909.5 K	0.06	99.19	99.63	97.70
e	1.00	6.6 K	400.5 K	0.03	98.66	99.07	92.84
Standalone	1.00	633.2 K	1.3 M	2.42	86.24	98.72	30.41
FedAvg	1.00	633.2 K	1.3 M	2.42	97.93	98.20	98.20
LG-FedAvg	1.00	633.2 K	1.3 M	2.42	97.93	98.54	98.17

Table 5: Results of combination of various computation complexity levels for MNIST dataset.

Model	Ratio	Parameters	FLOPs	Space (MB)	Accuracy		
					IID	Non-IID	
						Local	Global
a	1.00	9.6 M	330.2 M	36.71	91.19	92.38	56.88
a-b	0.63	6.0 M	206.8 M	22.95	90.60	91.35	59.93
a-c	0.53	5.1 M	175.7 M	19.50	90.59	92.83	60.25
a-d	0.51	4.9 M	167.9 M	18.64	90.28	91.78	56.54
a-e	0.50	4.8 M	165.9 M	18.43	90.29	92.10	59.11
a-b-c	0.44	4.2 M	144.9 M	16.07	89.70	90.41	54.16
a-b-d	0.42	4.1 M	139.7 M	15.49	89.98	90.29	51.79
a-b-e	0.42	4.0 M	138.4 M	15.35	89.79	90.79	62.17
a-c-d	0.36	3.5 M	119.0 M	13.20	89.47	89.82	53.13
a-c-e	0.36	3.4 M	117.6 M	13.05	89.35	93.59	57.30
a-d-e	0.34	3.3 M	112.4 M	12.48	88.75	91.11	56.74
a-b-c-d	0.33	3.2 M	110.1 M	12.19	89.33	91.32	54.50
a-b-c-e	0.33	3.2 M	109.1 M	12.09	89.37	92.52	61.56
a-b-d-e	0.32	3.1 M	105.1 M	11.65	89.40	91.80	56.78
a-c-d-e	0.27	2.6 M	89.6 M	9.93	88.42	91.50	62.15
a-b-c-d-e	0.27	2.6 M	88.4 M	9.78	88.83	92.49	61.64
b	1.00	2.4 M	83.3 M	9.19	89.82	93.83	55.45
b-c	0.63	1.5 M	52.3 M	5.75	89.00	89.96	52.29
b-d	0.53	1.3 M	44.4 M	4.88	89.18	91.78	51.07
b-e	0.51	1.2 M	42.4 M	4.67	89.10	90.68	59.81
b-c-d	0.44	1.1 M	36.7 M	4.02	88.35	92.79	58.09
b-c-e	0.42	1.0 M	35.3 M	3.88	87.98	91.98	58.28
b-d-e	0.36	866.3 K	30.1 M	3.30	88.06	91.94	54.02
b-c-d-e	0.33	800.7 K	27.9 M	3.05	87.92	91.90	59.10
c	1.00	603.8 K	21.2 M	2.30	87.55	91.09	55.12
c-d	0.63	377.8 K	13.4 M	1.44	86.75	91.58	54.61
c-e	0.53	321.1 K	11.3 M	1.22	86.88	91.83	63.47
c-d-e	0.44	264.6 K	9.4 M	1.01	85.79	91.49	55.42
d	1.00	151.8 K	5.5 M	0.58	84.21	90.77	61.13
d-e	0.63	95.1 K	3.5 M	0.36	82.93	90.89	56.16
e	1.00	38.4 K	1.5 M	0.15	77.09	89.62	54.16
Standalone	1.00	1.8 M	3.6 M	6.88	16.90	87.93	10.03
FedAvg	1.00	1.8 M	3.6 M	6.88	67.74	58.99	58.99
LG-FedAvg	1.00	1.8 M	3.6 M	6.88	69.76	91.77	60.79

Table 6: Results of combination of various computation complexity levels for CIFAR10 dataset.

Model	Ratio	Parameters	FLOPs	Space (MB)	Perplexity
a	1.00	19.3 M	1.4 B	73.49	3.37
a-b	0.74	14.2 M	991.4 M	54.12	3.31
a-c	0.62	11.8 M	829.0 M	45.20	3.71
a-b-c	0.57	10.9 M	757.6 M	41.72	3.42
a-d	0.56	10.7 M	754.3 M	40.94	3.74
a-b-d	0.53	10.2 M	707.8 M	38.87	3.53
a-e	0.53	10.2 M	718.6 M	38.86	3.75
a-b-e	0.51	9.8 M	684.0 M	37.49	3.47
b	1.00	9.1 M	614.8 M	34.74	3.46
a-b-c-d	0.45	8.8 M	603.4 M	33.39	3.61
a-c-d	0.45	8.6 M	599.6 M	32.93	4.08
a-b-c-e	0.44	8.5 M	585.5 M	32.34	3.50
a-c-e	0.43	8.3 M	575.8 M	31.54	3.65
a-b-d-e	0.41	7.9 M	548.2 M	30.21	3.64
a-d-e	0.39	7.5 M	526.0 M	28.70	4.02
a-b-c-d-e	0.37	7.2 M	496.6 M	27.55	3.55
b-c	0.74	6.8 M	452.4 M	25.83	3.45
a-c-d-e	0.35	6.8 M	467.0 M	25.76	3.92
b-d	0.62	5.7 M	377.7 M	21.57	3.70
b-c-d	0.58	5.2 M	348.5 M	20.02	3.47
b-e	0.56	5.1 M	342.0 M	19.49	3.90
b-c-e	0.54	4.9 M	324.7 M	18.63	3.46
c	1.00	4.4 M	290.1 M	16.92	3.62
b-c-d-e	0.46	4.2 M	278.7 M	16.07	3.64
b-d-e	0.45	4.1 M	274.9 M	15.79	3.92
c-d	0.75	3.3 M	215.4 M	12.66	3.46
c-e	0.62	2.8 M	179.7 M	10.57	3.89
c-d-e	0.58	2.6 M	166.7 M	9.85	3.66
d	1.00	2.2 M	140.7 M	8.39	3.83
d-e	0.75	1.7 M	105.0 M	6.31	3.90
e	1.00	1.1 M	69.3 M	4.23	7.41

Table 7: Results of combination of various computation complexity levels for WikiText2 dataset.