Encoding Without Influence: Dissociating Demographic Representation from Causal Effect in Large Language Models

Abstract

Large language models are increasingly deployed in settings that require normative judgment, yet the internal pathway by which demographic context shapes their outputs remains uncharacterized. We apply sparse autoencoder feature extraction and causal interventions (activation patching, feature steering, and targeted ablation) to Gemma 2 9B, Qwen 2.5 7B, and Llama 3.1 8B, tracing how demographic information is represented and used during survey responses across five policy domains. We find that demographic representations and demographic influence are localized in different parts of the network: early layers encode demographic identity but exert no measurable effect on outputs, while interventions on late-layer features recover 68.7–75.8% of behavioral effects across architectures. Variance-matched null baselines confirm that these effects are specific to demographic features rather than a generic consequence of perturbation. We further show that demographic influence is domain-modulated, with the ranking of influential demographics shifting across policy areas. The dissociation generalizes across three architectures with different encoding profiles and alignment procedures. These results suggest that representational detection alone is insufficient for bias auditing, as the most detectable demographic encodings are not the ones driving outputs, and that fairness evaluation must be both causally validated and domain-specific.

1 Introduction

Large language models produce outputs that vary systematically with demographic context provided in the prompt (Santurkar et al., 2023; Durmus et al., 2024; Argyle et al., 2023). Understanding how this sensitivity arises requires tracing the computational pathway by which demographic information, encoded in model activations, comes to influence token-level predictions for normative content. A natural hypothesis is that encoding strength predicts causal influence: the layers and features that most strongly represent demographic attributes should also be the primary mediators of their effect on outputs. Prior work on factual recall has established that different types of stored knowledge exhibit distinct depth profiles, with early layers enriching subject representations and later stages extracting task-relevant attributes (Meng et al., 2023; Geva et al., 2023), but the depth profile of demographic influence on normative outputs has not been characterized. We test the encoding-influence relationship in Gemma 2 9B, Qwen 2.5 7B, and Llama 3.1 8B using sparse autoencoder (SAE) features and three causal interventions across multiple layers. In all architectures, encoding and causal influence are dissociated: early and middle layers strongly encode demographic attributes but contribute negligibly to output variation, while late-layer features with weak demographic encoding recover the majority of behavioral effects. The resulting pattern, which we term encoding–causal dissociation, indicates that representational prominence and causal influence over normative outputs are governed by distinct mechanisms operating at different network depths.

Prior work has established that LLM outputs are systematically misaligned with the expressed opinions of many demographic groups (Santurkar et al., 2023; Durmus et al., 2024), and that demographic conditioning can produce subgroup-faithful response distributions (Argyle et al., 2023). Persona assignment degrades

reasoning performance along stereotype-consistent lines (Gupta et al., 2024), and value-aligned models that pass explicit bias benchmarks exhibit implicit biases detectable through psychology-adapted measures (Bai et al., 2025). At the representational level, LLMs form linear encodings of inferred user demographics that causally shape downstream outputs (Bouchaud & Ramaciotti, 2025), and activation patching can localize and manipulate demographic representations in clinical tasks (Ahsan et al., 2025). These results establish that demographic information is both linearly encoded and causally active in transformer models, but do not address whether encoding and causal influence are co-located across layers, or how the thematic content of a query modulates the relationship between demographic context and model output.

We address both questions using contrastive prompt pairs derived from the European Social Survey (ESS), covering normative questions across five policy domains. For each model, we extract sparse autoencoder features at multiple layers, identify features with significant activation differences across demographic conditions, and assess their causal role through activation patching, feature steering, and ablation, each with variance-matched null and random controls. The central result is that encoding detectability and causal influence follow divergent depth profiles in all three architectures, with causal effects concentrating in the final third of network depth and early-layer encodings contributing nothing beyond what matched controls produce. This dissociation is further modulated by policy domain: the ranking of which demographics most shape outputs shifts across thematic areas, with effect magnitudes varying substantially.

These findings bear on how bias is evaluated in practice. Representational approaches that detect demographic encodings without causal validation risk targeting the wrong model components, since the layers with the strongest encodings are not the layers where demographic information shapes outputs. The problem is compounded by the nature of the causally active features themselves: at late layers, demographic information is encoded polysemantically as composite social axes rather than as clean single-attribute representations, meaning that standard single-demographic probes may fail to isolate the relevant features even at the correct depth. The domain dependence of demographic effects further implies that fairness evaluations must be disaggregated by thematic content. We provide our experimental framework alongside this submission to support replication and extension to additional architectures.

2 Related Work and Contributions

2.1 Demographic Conditioning and LLM Opinions

Models exhibit systematic demographic biases in their default outputs, aligning more closely with liberal, highly-educated, and higher-income respondents (Santurkar et al., 2023), with disproportionate representation of Western perspectives globally (Durmus et al., 2024). When conditioned on sociodemographic backstories, LLMs can approximate the response distributions of matching human subgroups (Argyle et al., 2023), though this sensitivity cuts both ways: persona assignment degrades reasoning in stereotype-consistent ways (Gupta et al., 2024), and models passing explicit bias tests still harbor implicit biases detectable through psychology-adapted measures (Bai et al., 2025). At the representational level, LLMs infer user demographics from contextual signals rather than explicit statements, forming linear encodings that causally shape downstream outputs (Bouchaud & Ramaciotti, 2025). Collectively, these results show that demographic information is encoded, influences outputs, and persists despite alignment, but existing work has not examined how this processing is distributed across model depth, whether the most detectable representations are the ones driving output variation, or how the thematic content of a query modulates demographic influence.

2.2 Sparse Autoencoders and Causal Interpretability

Sparse autoencoders decompose dense activations into sparse, interpretable features (Cunningham et al., 2023; Bricken et al., 2023), with recent work scaling to comprehensive model suites (Lieberum et al., 2024; Gao et al., 2024). Causal methods complement feature identification through activation patching (Meng et al., 2023), circuit discovery (Conmy et al., 2023; Marks et al., 2025), and activation steering (Turner et al., 2024). Closest to our work, Ahsan et al. (2025) applied activation patching to localize gender information in MLP (Multi-layer perceptron) layers of healthcare LLMs. Their analysis is restricted to a single domain

and architecture, operates on full MLP layers rather than SAE features, and does not examine how encoding strength relates to causal influence across depth.

Prior work has established in principle that probing accuracy need not imply causal relevance (Ravichander et al., 2021; Elazar et al., 2021). We provide a mechanistic demonstration of this dissociation for demographic information in normative contexts, quantify the depth profile at which it occurs across architectures, and show that it is modulated by policy domain.

2.3 Contributions

We trace the path from demographic representation to normative output in Gemma 2 9B, Qwen 2.5 7B, and Llama 3.1 8B, applying SAE-based feature extraction and three causal interventions across eight layers (12–88% depth) in Gemma, five layers (26–100% depth) in Qwen, and three layers in Llama. Our contributions are:

1. **Encoding–causal dissociation.** Cross-architecture evidence that encoding detectability does not predict causal influence for demographic information, confirmed by null baselines with specificity gaps of 61.8 (Gemma) and 55.3 (Qwen) percentage points.

2. **Converging causal evidence.** Patching, steering, and ablation interventions that respectively recover, amplify, and reduce demographic effects, each validated against matched controls in Gemma and Qwen. Llama replicates patching and steering but shows non-significant ablation, consistent with redundant encoding.

3. **Domain-modulated influence.** The ranking of influential demographics varies across policy areas, with recovery spanning a wide range across demographic×domain combinations (Gemma IQR: 59–89%), arguing for domain-sensitive rather than aggregate bias evaluation.

4. **Cross-architecture methodology.** A replicable pipeline combining unsupervised SAE feature discovery with multi-method causal validation, demonstrated across three architectures (Gemma 2 9B, Qwen 2.5 7B, Llama 3.1 8B) with different SAE training regimes.

3 Data

We construct contrastive prompt pairs from the European Social Survey CRONOS-3 Wave 4 (European Social Survey European Research Infrastructure (ESS ERIC), 2026), a cross-national self-completion panel survey fielded in 2024–2025 across 11 European countries.[1] Questions span five thematic domains representing distinct dimensions of normative reasoning: climate policy (25 questions), health regulation (15), digital governance (35), economic policy (17), and personal values (18). We retain 110 questions after excluding items that elicit factual self-reports rather than normative judgments. Response formats include 5-point Likert scales, 11-point agreement scales (0–10), 4-point categorical items, and binary choices.

From the stratified panel, we select 150 respondents with complete demographic information across five attributes (gender, age, education, subjective income, and voting behavior), partitioned into 120 for feature selection and 30 for held-out validation. This yields 66,000 contrastive pairs for feature selection and 16,500 for validation. All three models are evaluated on identical prompt pairs.

We define five demographic contrasts using extreme values to maximize activation differences: income (wealthy vs. poor), age (75 vs. 22), gender (man vs. woman), education (PhD vs. no secondary), and voting (regular voter vs. non-voter). For each respondent, question, and demographic dimension, we construct a pair of prompts identical in all respects except the target demographic. We use extreme demographic contrasts by design: the goal is to maximize activation differences for feature discovery, not to estimate realistic effect sizes. This follows standard practice in causal tracing, where unambiguous stimuli are used to identify

---

[1]Experiments were conducted using edition 1.0 of the dataset. Edition 1.1, released February 2026, corrected a reversed scale coding for one variable (`w4eq1`). This correction does not affect our analyses, which use respondent demographic variables and question text only, not respondent-level response data.

Prompt A (income = wealthy)

You are a woman. You are 47 years old, in middle age. You live in France. You have a bachelor's degree from university. **You are financially wealthy. You own multiple properties, have substantial savings and diverse investments, and never worry about money. You can afford luxuries and expensive experiences without thinking twice about the cost.** You voted in the last national election.

To what extent are you in favor or against the following policy? Imposing higher taxes on gas and electricity generated by fossil fuels. (1 = Strongly in favor, 5 = Strongly against)

RESPOND WITH ONLY A SINGLE NUMBER.

Prompt B (income = poor)

You are a woman. You are 47 years old, in middle age. You live in France. You have a bachelor's degree from university. **You are financially poor. You struggle to afford rent, have accumulated significant debt, and constantly worry about paying for basic necessities. Money is a persistent source of stress and limits your daily choices.** You voted in the last national election.

To what extent are you in favor or against the following policy? Imposing higher taxes on gas and electricity generated by fossil fuels. (1 = Strongly in favor, 5 = Strongly against)

RESPOND WITH ONLY A SINGLE NUMBER.

Figure 1: Contrastive prompt pair for the income dimension. Bold text is the manipulated demographic; all other attributes are held at the respondent's real ESS values.

mediating components (Meng et al., 2023). The gender contrast is constrained to binary categories by the ESS panel variable; whether the identified features generalize to subtler demographic cues or non-binary identities is left to future work.

Non-tested attributes use the respondent's real ESS values converted to natural language (e.g., ESS education code 6 becomes *"You have a bachelor's degree from university"*). Paraphrase robustness testing on a held-out subsample (30 respondents × 20 questions) confirmed that identified features track demographic content rather than specific phrasing (mean $\rho = 0.79$ across wordings).

Figure 1 shows a complete contrastive pair.

Prompts instruct the model to respond with a single numeric value on the question's scale. We format prompts using each model's chat template (Gemma 2 and Qwen 2.5) and extract the probability distribution over valid response tokens to compute expected values as our behavioral measure (§4.2).

4 Methods

Our methodology proceeds in four stages (Figure 2): we measure how demographic conditioning shifts model outputs (§4.2), identify SAE features that encode these shifts (§4.3), intervene on those features to test causal mediation (§4.4), and compare against matched controls to rule out perturbation artifacts (§4.5).

4.1 Models and Sparse Autoencoders

We experiment on two primary architectures: Gemma 2 9B IT paired with pretrained Gemma Scope sparse autoencoders (16K features; Lieberum et al., 2024), and Qwen 2.5 7B IT paired with instruction-tuned SAEs (131K features) from the SAELens library (Bloom et al., 2024), trained on Qwen 2.5 7B Instruct residual stream activations following the methodology of Gao et al. (2024). We additionally replicate core analyses on Llama 3.1 8B Instruct as a cross-architecture test. An SAE decomposes a dense model activation $\mathbf{h} \in \mathbb{R}^d$ into a sparse set of interpretable features (Cunningham et al., 2023; Bricken et al., 2023):

$$\mathbf{z} = \text{JumpReLU}(\mathbf{W}_{\text{enc}} \cdot \mathbf{h} + \mathbf{b}_{\text{enc}}) \tag{1}$$

$$\hat{\mathbf{h}} = \mathbf{W}_{\text{dec}} \cdot \mathbf{z} + \mathbf{b}_{\text{dec}} \tag{2}$$

Figure 2: Methodological pipeline. Stage 1 measures behavioral effects of demographic conditioning via contrastive prompt pairs (§4.2). Stage 2 identifies SAE features with significant activation differences across demographic conditions (§4.3). Stage 3 applies three causal interventions to test whether identified features mediate demographic effects (§4.4). Stage 4 compares intervention effects against four control conditions at increasing stringency to establish specificity (§4.5).

where $\mathbf{W}_{\text{enc}} \in \mathbb{R}^{m \times d}$ and $\mathbf{W}_{\text{dec}} \in \mathbb{R}^{d \times m}$ are encoder and decoder weights, and $m \gg d$ is the dictionary size ($m = 16{,}384$ for Gemma; $m = 131{,}072$ for Qwen). JumpReLU zeroes values below a learned threshold to enforce sparsity (Rajamanoharan et al., 2024). Each nonzero z_i represents the activation strength of feature i, with associated unit-norm decoder direction $\mathbf{d}_i \in \mathbb{R}^d$ (the i-th column of $\mathbf{W}_{\text{dec}}$). Because the residual stream decomposes linearly, we can intervene on specific features by adding or subtracting their weighted decoder directions (§4.4).

For Gemma, we apply pretrained SAEs to the instruction-tuned model across eight layers (L5–L36, 12–88% depth), with dense coverage in the 44–88% range where the encoding-to-causal transition occurs. Applying pretrained SAEs to instruction-tuned activations introduces a distribution mismatch that degrades reconstruction (Lieberum et al., 2024). We address this by omitting the standard $\mathbf{b}_{\text{dec}}$ subtraction during encoding, which improves reconstruction substantially (NMSE (normalized mean squared error), defined as the ratio of reconstruction error variance to activation variance : 0.17 vs. 0.50 at L5; full statistics in Appendix D.1). Reconstruction degrades modestly at late layers (NMSE up to 0.32 at L32; 0.28 at the peak causal layer L36), but remains acceptable across all layers (cosine similarity 0.82–0.91). Our contrastive design (comparing matched persona pairs) means shared reconstruction error cancels to first order, and the specificity controls confirm that late-layer effects are not attributable to reconstruction artifacts, since variance-matched non-demographic features at the same layers produce substantially weaker NPE. L20 uses an instruction-tuned SAE variant and shows no discontinuity in encoding strength or causal effects relative to adjacent PT layers, further suggesting the mismatch does not systematically bias results. For Qwen, we

use natively instruction-tuned SAEs across five layers (L7–L27, 26–100% depth), where this concern does not arise; consistent findings across both SAE regimes rule out PT-IT (pretrained–instruction-tuned)mismatch as an explanation.

4.2 Behavioral Measurement

For each prompt, we extract logits for all valid response tokens at the final token position and compute the expected value over the normalized probability distribution:

$$\text{EV} = \sum_{v=s_{\min}}^{s_{\max}} v \cdot P(v) \tag{3}$$

$$P(v) = \text{softmax}(\text{logits}_{[s_{\min}:s_{\max}]})_v$$

where v indexes valid response values on the question's scale (e.g., $v \in \{1, 2, 3, 4, 5\}$ for a 5-point Likert item), $s_{\min}$ and $s_{\max}$ are the minimum and maximum scale values, and $P(v)$ is the probability assigned to response value v after restricting the softmax to valid response tokens only. This continuous measure captures the model's full response distribution rather than the argmax prediction alone, providing greater sensitivity for detecting subtle shifts from causal interventions. For 11-point scales (0 to 10), the value "10" tokenises as two tokens. Because the first token ("1") is shared between values 1 and 10, we split its probability mass equally between the two, a conservative choice that avoids biasing estimates toward either end of the scale. Details and token handling for other edge cases are reported in Appendix D.2.

The behavioral effect for each contrastive pair is:

$$\Delta_{\text{EV}} = \text{EV}_a - \text{EV}_b \tag{4}$$

where EV_a and EV_b are the expected values under demographic conditions a and b respectively. Significance is assessed via paired t-tests with Cohen's d_z as the effect size.

4.3 Feature Identification

For each contrastive pair, we extract SAE feature activations at the final token position under both demographic conditions, yielding activation vectors $\mathbf{f}^a, \mathbf{f}^b \in \mathbb{R}^m$, and compute the element-wise difference $\mathbf{f}^a - \mathbf{f}^b$ across all m features. We aggregate them within each demographic×domain group (e.g., income×climate) and apply a three-stage filtering pipeline: noise filtering for sign consistency and stability, statistical testing (one-sample t-tests on mean activation differences, BH-corrected (Benjamini–Hochberg) at $\alpha = 0.05$), and effect size thresholding ($|\text{Cohen's } d_z| \geq 0.3$). From features passing all stages, we select the top $K = 50$ by mean absolute activation difference. Threshold details and feature yield statistics are reported in Appendix C. All effect sizes for feature identification are computed as d_z (mean of paired differences divided by their standard deviation). We use the shorthand $|d_{\text{enc}}|$ when referring to encoding strength to distinguish it from the d_z values reported for causal specificity comparisons, though both are computed from paired data.

4.4 Causal Interventions

The features identified in §4.3 provide correlational evidence of demographic encoding but do not establish causal mediation. To test whether these features drive demographic effects on outputs, we apply three complementary interventions that modify the residual stream at the final token position. Each constructs a perturbation vector from the top-K selected features:

$$\mathbf{v} = \sum_{i \in \text{top-}K} \delta_i \cdot \mathbf{d}_i \tag{5}$$

where $\delta_i = f_i^a - f_i^b$ is the signed activation difference for feature i, with f_i^a and f_i^b denoting the SAE activations under conditions a and b respectively (§4.3). The vector $\mathbf{v} \in \mathbb{R}^d$ thus represents the combined contribution of the selected features to the difference between the two demographic conditions in the model's

residual stream space. All three interventions below are reported on a common scale as percentages of the original behavioral effect (Δ_{EV}), where 0% indicates no change from the control condition and 100% indicates exact reproduction (for NPE), complete elimination (for NAE), or doubling (for NSE) of the demographic effect. Values may exceed 100% or fall below 0%.

Patching tests causal sufficiency: can transplanting the demographic feature pattern from condition a into condition b reproduce the behavioral effect? Following the causal tracing framework (Meng et al., 2023) and the denoising paradigm described by Heimersheim & Nanda (2024), we add $\mathbf{v}$ to condition b's residual stream at the final token position. We adapt standard patching metrics, which typically operate on token probabilities (Meng et al., 2023) or logit differences (Wang et al., 2022; Zhang & Nanda, 2024), to our expected-value setting. We define the normalized patching effect (NPE):

$$\mathrm{NPE} = \frac{\mathrm{EV}'_b - \mathrm{EV}_b}{\Delta_{\mathrm{EV}}} \tag{6}$$

where EV_b is the baseline expected value for condition b, EV'_b is the post-intervention expected value, and $\Delta_{\mathrm{EV}} = \mathrm{EV}_a - \mathrm{EV}_b$ is the baseline behavioral difference (Equation 4). NPE = 0 indicates no effect and NPE = 1.0 indicates exact reproduction of the behavioral gap, with values exceeding 1.0 indicating overshoot. We additionally define signed and absolute transfer errors that measure deviation from exact transfer in original scale units (Appendix A).

Ablation tests causal necessity: does removing the demographic feature pattern from condition a eliminate the behavioral effect? We subtract $\mathbf{v}$ from condition a's residual stream and measure the normalized ablation effect (NAE):

$$\mathrm{NAE} = 1 - \frac{\mathrm{EV}_a^- - \mathrm{EV}_b}{\Delta_{\mathrm{EV}}} \tag{7}$$

where EV_a^- is the expected value for condition a after subtracting $\mathbf{v}$ from its residual stream. NAE = 0 indicates no effect; 1.0 indicates complete elimination of the demographic effect.

Steering tests whether the effect can be pushed beyond its natural magnitude. We add a scaled perturbation $\alpha\mathbf{v}$ (with $\alpha = 2.0$) to condition a's residual stream (Turner et al., 2024) and measure the normalized steering effect (NSE):

$$\mathrm{NSE} = \frac{\mathrm{EV}_a^+ - \mathrm{EV}_b}{\Delta_{\mathrm{EV}}} - 1 \tag{8}$$

where EV_a^+ is the expected value for condition a after adding $\alpha\mathbf{v}$. NSE = 0 indicates no change beyond the natural effect; positive values indicate NSE. We Winsorize this metric at $\pm 200\%$ to limit the influence of outlier pairs with small baseline effects.

For all three interventions, we additionally report signed and absolute transfer errors in original scale units (Appendix A). We apply each intervention using two feature selection strategies. The *per-pair* strategy selects the top-K features by $|\delta_i|$ for each individual contrastive pair, providing an upper bound on what the identified feature space can achieve. The *aggregate* strategy uses the population-level top-K features from §4.3, testing whether features generalize beyond the pairs from which they were selected; this addresses the circularity inherent in per-pair selection, where the same data are used to identify and evaluate features. We vary $K \in \{5, 10, 20, 50\}$ to examine dose-response relationships and exclude pairs with baseline $|\Delta_{\mathrm{EV}}|$ below a scale-normalized threshold (0.3 scale points, normalized by the ratio of the question's scale range to a 10-point reference) to prevent floor effects from inflating effect estimates. Unless otherwise noted, reported results use the per-pair strategy.

4.5 Control Conditions

Establishing that demographic features produce causal effects is insufficient; we must show these effects are specific to the selected features rather than a generic consequence of perturbing the residual stream. Four controls address this at increasing stringency.

Random-A samples K features uniformly from features active in the current pair (activation > 0) along with their real activation differences, testing whether any set of active features with comparable magnitudes produces similar effects. *Random-B* takes the top-K $|\delta_i|$ magnitudes from the demographic features but applies them to K randomly selected active features in shuffled order, controlling for the possibility that the delta magnitudes alone drive NPE regardless of which features carry them. *Cross-condition* applies features selected for one demographic×domain group to pairs from a different group (e.g., income×climate features applied to age×health pairs), testing whether causal effects are specific to their source condition. *Null baseline* provides the most stringent control: we select features not among the top-K demographic features for any group, whose activation variance across all pairs falls within $0.5\times$ to $1.5\times$ of the demographic features' variance range, with progressive fallback to wider windows (up to $0.1\times$–$5.0\times$) when the primary window yields fewer than K candidates. Patching with these variance-matched non-demographic features directly tests whether any set of high-variance features would show causal influence.

Significance for individual intervention effects is assessed via one-sample t-tests against zero. For specificity comparisons (same-pair vs. matched random), interventions on each pair share the same prompt and baseline expected value, making the comparison naturally paired. We therefore use paired t-tests and report Cohen's $d_z = \bar{d}/s_d$, where $\bar{d}$ is the mean within-pair difference and s_d its standard deviation. Within-pair analyses in earlier stages (behavioral effects, feature selection) similarly use paired t-tests with d_z. All p-values are BH-corrected.

5 Results

Steering means are capped at $\pm 200\%$ before averaging to limit the influence of extreme outliers (consistent with the $2\times$ steering multiplier); medians are provided in parentheses where mean–median divergence is substantial.

5.1 Behavioral Baseline

Both models show demographic sensitivity, though with different breadth. In Gemma, 24 of 25 demographic×domain cells produce significant behavioral effects (paired t-tests, $p < 0.05$), with gender×digital as the sole non-significant cell ($\Delta EV = 0.007$, $p = 0.07$). The largest absolute effects are income×economy ($\Delta EV = +0.594$), education×health (-0.522), and vote×health (-0.517).

Qwen shows narrower sensitivity: 17 of 25 cells reach significance (paired t-tests, $p < 0.05$), with non-significant cells concentrated in age (3 cells) and education (2 cells). Among significant cells, the largest effect is income×economy ($\Delta EV = +0.139$). Effect magnitudes are substantially smaller across all cells (Qwen max $|\Delta EV| = 0.139$ vs. Gemma's 0.594). After applying the floor-effect exclusion threshold (§4.4), 384 valid pairs remain for Gemma at Layer 36 and 364 for Qwen at Layer 27.

5.2 Encoding–Causal Dissociation

The central finding is that encoding strength does not predict causal influence: features that strongly encode demographic information are not necessarily the features that shape normative outputs. We define the *specificity gap* as the difference in NPE between same-pair demographic features and Random-A controls; a positive gap indicates that the intervention effect is specific to demographically identified features rather than a generic property of perturbing active features at that depth

In Gemma, the dissociation is stark. Encoding peaks at early layers (mean $|d_{\text{enc}}| = 2.02$ at L9) and declines monotonically to $|d_{\text{enc}}| = 0.99$ at L36, yet early-layer features have zero causal specificity (all gaps ≤ 0.3 pp, $|d_z| \leq 0.07$), while late-layer features with weaker encoding drive nearly all normative influence ($d_z = 0.99$ at L36). A purely proximity-to-output account would still predict some early-layer specificity given encoding strengths above $|d_{\text{enc}}| = 2.0$; the complete absence of such specificity suggests that demographic information is representationally reorganised between encoding and causal deployment. In Qwen, encoding is uniformly weak across depth (mean $|d_{\text{enc}}| \approx 0.19$ across all selected features at each layer; the higher values in Table 8 reflect within-group top-50 averages rather than layer-wide means). This limits the strength of

Figure 3: Encoding–causal dissociation across model depth. Bars show the specificity gap (same-pair minus Random-A patching NPE, in percentage points); the green line shows mean encoding strength (Cohen's $|d_{\mathrm{enc}}|$) of significant features. **(A)** Gemma 2 9B IT shows opposing depth gradients: encoding peaks early (L9, $|d_{\mathrm{enc}}| = 2.02$) while causal influence peaks late (L36, 49.1 pp gap). **(B)** Qwen 2.5 7B IT shows flat encoding with late-concentrated causal influence (L27, 79.8 pp gap). The invariant across both models is late-layer causal concentration, not the early-layer encoding peak.

this dissociation argument, but causal effects nonetheless concentrate exclusively at late layers (Figure 3), consistent with the same architectural pattern. The fact that late-layer causal concentration holds regardless of encoding profile, whether a steep decline in Gemma or flat in Qwen, indicates that this is an architectural property rather than a consequence of encoding reorganisation across depth.

Specifically, in Gemma, patching at layers L5–L20 (12–49% depth) produces negligible specificity (gaps ≤ 0.3 pp; all $|d_z| \leq 0.07$, $p > 0.15$). Causal effects emerge at L27 (66% depth; NPE 53.0%, gap 35.0 pp, $d_z = 0.83$, $p < 10^{-44}$) and peak at L36 (88% depth; NPE 75.8%, gap 49.1 pp, $d_z = 0.99$, $p < 10^{-58}$). In Qwen, the same pattern holds: L7 and L15 show negligible specificity (gaps ≤ 0.7 pp; all $|d_z| \leq 0.02$, $p > 0.65$), effects emerge at L19 (70% depth; NPE 83.1%, gap 12.8 pp, $d_z = 0.29$, $p < 10^{-7}$), and peak at L27 (100% depth; NPE 132.9%, gap 79.8 pp, $d_z = 0.63$, $p < 10^{-27}$). NPE above 100% at L27 indicates that patching the top-50 demographic features overshoots the target expected value, consistent with features that encode amplified rather than merely sufficient demographic signal at late layers. Figure 4 summarises both models' intervention results at each layer.

Three interventions converge at the best layer in both architectures. In Gemma at L36: patching recovers 75.8%, steering amplifies by 65.1% (median 40.6%), and ablation reduces by 74.5%, each significantly exceeding matched random controls ($d_z = 0.99$, 0.44, 1.27 respectively; all $p < 10^{-15}$). In Qwen at L27: patching recovers 132.9%, steering amplifies by 75.3% (median 69.6%), and ablation reduces by 62.5% ($d_z = 0.63$, 0.67, 0.56; all $p < 10^{-22}$). The three-way convergence across architectures provides strong evidence for causal mediation through the identified features.

The dissociation is thus asymmetric across architectures: in Gemma, encoding and causal influence show opposing depth gradients, while in Qwen, encoding remains flat across depth as causal influence emerges only at late layers. The invariant across both models is the late-layer concentration of causal effects, not the early-layer encoding peak.

5.3 Specificity: Null Baseline and Control Hierarchy

We verify that causal effects are specific to demographically relevant features using variance-matched null baselines and four control conditions (Figure 5).

Null baseline. The null baseline compares per-pair demographic features against variance-matched null features selected at the population level, applied to the subset of pairs for which matched null features could be identified ($N = 384$ in Gemma; $N = 237$ in Qwen). At early layers, demographic and null features

Figure 4: Intervention effects across layers and conditions ($K = 50$). Cells show mean effect size (%): patching NPE, steering NSE (capped at $\pm 200\%$), and ablation reduction. **Spec. gap** = same-pair patching minus Random-A. **(A)** Gemma 2 9B IT: early layers (L5–L20) show zero specificity; late layers (L27–L36) show large, significant effects across all three interventions. Cell values are rounded to the nearest integer; exact values are reported in §5.2 **(B)** Qwen 2.5 7B IT: the same late-layer concentration pattern, with specificity emerging at L19 and peaking at L27.

Figure 5: Specificity controls and dose-response. **(A)** Gemma null baseline: demographic features (blue) and variance-matched null features (grey) produce indistinguishable NPE at early layers but diverge sharply at late layers (L36: 75.8% vs. 14.0%, $p < 10^{-52}$). **(B)** Qwen null baseline: the same pattern, with separation emerging at L19 and widening through L27 (116.8% vs. 61.5%, $p < 10^{-5}$). **(C)** Dose-response: patching NPE at the best layer increases monotonically with K in both models, saturating near $K = 50$.

produce indistinguishable recovery in both models (Gemma L5: demographic -4.1%, null -4.2%, $p = 0.92$; Qwen L7: 20.4% vs. 20.8%, $p = 0.98$). At late layers, demographic features substantially exceed null controls: Gemma L36 recovers 75.8% vs. null 14.0%, a 61.8 pp gap ($p < 10^{-52}$, two-sided Mann–Whitney); Qwen L27 recovers 116.8% vs. null 61.5%, a 55.3 pp gap ($p < 10^{-5}$). Qwen's lower recovery here relative to the 132.9% per-pair result in §5.2 reflects the smaller pair subset ($N = 237$ vs. 364), not a change in feature selection method; both use per-pair demographic features.

Control hierarchy. In Gemma at L36, the expected ordering holds cleanly: same-pair patching (75.8%) substantially exceeds Random-A (26.7%), which in turn exceeds cross-condition (-3.7%) and Random-B (-2.6%). In Qwen at L27, same-pair (132.9%) exceeds Random-A (53.2%) and Random-B (43.0%), but

the cross-condition control (56.9%) is comparable to Random-A rather than near zero. This elevated cross-condition transfer in Qwen suggests that demographic features are less domain-specific than in Gemma, a difference we return to in §6. Despite this, the core finding holds: same-pair features significantly outperform all controls in both models at late layers, confirming that the identified features carry information specific to their source demographic condition.

Dose-response. NPE increases monotonically with the number of features K in both models: Gemma at L36 rises from 39.8% ($K = 5$) to 75.8% ($K = 50$); Qwen at L27 rises from 75.8% ($K = 5$) to 132.9% ($K = 50$). We use $K = 50$ for all primary analyses. For Qwen, where NPE exceeds 100%, we additionally tested $K = 100$ to verify saturation rather than unbounded growth. NPE at $K = 100$ (132.7%) is unchanged from $K = 50$, confirming that 50 features capture the recoverable demographic signal. NPE at early layers remains flat regardless of K (Gemma L5: -4.3% to -4.1%; Qwen L7: 42.9% to 44.0%), confirming that the null result at those depths is not due to insufficient feature count.

5.4 Domain Modulation

NPE is not uniform across policy domains. In Gemma at L36, the interquartile range of NPE across the 25 demographic×domain cell means spans 59–89%, and in Qwen at L27 it spans 79–157%, indicating that demographic features exert domain-modulated rather than blanket influence on normative outputs. The model's deployment of demographic context is topic-sensitive: the same demographic dimension may be strongly causally mediated for one policy area and weakly mediated for another.

In Gemma, this domain modulation is accompanied by increasing feature specialization across depth: the mean Jaccard similarity between feature sets selected for different domains declines monotonically from 0.920 at L5 to 0.392 at L36 ($\rho = -1.00$, $p < 0.0001$), with the fraction of features shared across all five domains dropping from 83.8% to 11.9%. Early layers thus represent demographic identity through a shared feature vocabulary regardless of topic, while late layers recruit distinct features depending on the policy domain in which demographic context is being deployed. This specialization gradient parallels the encoding–causal dissociation: the same layers that become causally active (§5.2) are also those at which features differentiate by domain, suggesting that causal influence and domain specificity emerge together as the model transitions from generic encoding to context-sensitive deployment. This gradient is not observed in Qwen, where Jaccard similarity shows no consistent depth trend, indicating that the specialization pattern may be architecture-dependent.

5.5 Architecture-Dependent Variation

While the core findings generalize across architectures, several quantitative differences merit discussion. First, Qwen's NPE exceeds 100% at late layers (132.9% at L27 vs. Gemma's 75.8% at L36), meaning the intervention overshoots condition a's baseline. This likely reflects polysemantic features that carry correlated non-demographic signal alongside demographic content; transplanting them transfers both. Consistent with this, Qwen's Random-B baseline is itself elevated (43.0% vs. Gemma's -2.6%), indicating that even non-demographically-matched perturbations produce substantial NPE in Qwen. The demographic breakdown further supports a polysemanticity account: gender pairs show the most extreme overshoot (mean 209.3%, median 109.7%), with the large mean–median divergence indicating a tail of high-overshoot pairs. After subtracting the Random-B baseline, which controls for transplantation magnitude without demographic matching, Qwen's corrected NPE is 90.0%, closer to Gemma's baseline-corrected 78.4%. Second, Qwen's early-layer patching reveals a perturbation artifact: NPE at L7 is 44.0%, but the specificity gap (same-pair minus Random-A) is 0.3 pp, indicating that *any* perturbation of comparable magnitude shifts outputs regardless of demographic content. This artifact is absent in Gemma (L5 NPE -4.1%), suggesting greater sensitivity to residual-stream perturbation at early depths in Qwen. This reinforces the importance of reporting specificity gaps rather than raw NPE when comparing across architectures. Third, aggregate features perform substantially worse in Qwen (ratio 0.27) than Gemma (ratio 0.73), indicating more pair-specific demographic encoding that generalizes less across the population. Fourth, steering directionality shows a parallel pattern: at early layers, forward and reverse steering produce equivalent effects ($\sim$98% in Gemma, $\sim$88% in Qwen), consistent with non-directional perturbation. At late layers, forward steering

preserves direction (96.6% in Gemma, 94.0% in Qwen) while reverse steering collapses (17.7% and 29.1% respectively), confirming that late-layer features encode directional demographic information rather than merely perturbing the residual stream.

5.6 Cross-Architecture Replication: Llama

We replicate the core analyses on Llama 3.1 8B Instruct across three layers (L15, L23, L27) to test generalizability beyond the primary models. All 25 demographic×domain cells show significant behavioral effects, and 479 pairs remain after floor-effect exclusion. Llama replicates the encoding–causal dissociation: mean $|d_{enc}|$ of selected features declines from 4.73 (L15) to 1.98 (L23) to 1.19 (L27), yet causal specificity emerges only at L27. Patching NPE is numerically highest at L15 (153.2%), but ablation at that depth is pathological (-226.5%), indicating that the identified features play a compensatory rather than straightforwardly mediating role at early layers. At L27, where encoding is weakest, patching recovers 68.7% of baseline effects versus 22.8% for Random-A controls ($d_z = 0.52$, $p < 10^{-26}$), and steering amplifies by 62.3% versus 25.8% ($d_z = 0.36$, $p < 10^{-13}$). Ablation reduces by 29.9% versus 24.3%, but this difference is not statistically significant ($d_z = 0.08$, $p = 0.07$). One possible explanation is redundant encoding across parallel pathways that prevents removal of a single feature set from eliminating the behavioral effect, though we do not test this directly. Gender shows the strongest patching (88.6%) and steering (102.8%); age shows negligible ablation (1.0%). Demographic breakdowns and the full encoding profile are reported in Appendix D.4.

6 Discussion

The encoding–causal dissociation demonstrates that demographic information undergoes a functional transformation across model depth, and that representational prominence is not a reliable indicator of causal influence on normative outputs.

6.1 Representation Versus Deployment

In both architectures, early and middle layers construct representations of demographic identity that are causally inert: intervention effects are indistinguishable from random controls, and variance-matched null baselines confirm the early-layer null is genuine rather than an artifact of feature selection. Causal influence emerges only at late layers, but with a different representational signature: greater domain specialization and sensitivity to the specific demographic contrast rather than to perturbation in general.

The two models achieve this separation through different encoding strategies. Gemma shows opposing depth gradients: encoding peaks early ($|d_{enc}| = 2.02$ at L9) and declines as causal influence rises ($|d_{enc}| = 0.99$ at L36). Qwen shows uniformly weak encoding ($|d_{enc}| \approx 0.19$) across all selected features with causal influence concentrated at the final layer. The invariant is not the encoding profile but the late-layer concentration of causal effects, suggesting that transformers separate demographic representation from its deployment in normative judgment regardless of how the encoding itself is organized.

Characterizing the late-layer causal features reveals why this dissociation poses a practical detection problem. Rather than encoding individual demographic attributes cleanly, these features are polysemantic: in Gemma, top causal features at L36 consistently encode multiple demographics simultaneously, typically with opposite-direction encoding across demographics (e.g., younger/wealthier/educated loading together as a composite social axis). Single-demographic probes applied at these layers would fail to isolate features that encode demographics as correlated bundles rather than independent dimensions (Appendix D.5).

One alternative explanation is that instruction tuning or RLHF (Reinforcement learning from human feedback) pushes demographic processing to later layers rather than this being an architectural property. Three observations weigh against this. First, for Gemma we apply pretrained SAEs learned on base model activations (Lieberum et al., 2024); the fact that these features show late-layer causal effects on instruction-tuned activations suggests the relevant structure is not purely an alignment artifact. Second, the three models (Gemma, Qwen, Llama) likely underwent different alignment procedures, yet all exhibit late-layer causal concentration, consistent with the view that alignment primarily shapes surface behavior rather than deep

representational structure (Zhou et al., 2023).Third, encoding strength in Gemma peaks at early layers regardless of the SAE regime (the IT SAE at L20 shows no discontinuity relative to adjacent PT layers), paralleling findings that fine-tuning amplifies pre-existing computational pathways rather than introducing novel ones (Prakash et al., 2024). These observations are suggestive but not conclusive; a direct comparison of base and instruction-tuned variants at matched scale would settle the question and is a natural direction for future work.

One might expect late-layer causal effects to reflect generic response generation rather than demographic processing specifically. Three lines of evidence argue against this. First, same-pair demographic features substantially outperform active random features at late layers (Gemma: 75.8% vs. 26.7%; Qwen: 132.9% vs. 53.2%), demonstrating that the effect is specific to contrastively identified features, not any features active at that depth.

Second, the variance-matched null baseline shows that features selected to match the activation variance of demographic features but without demographic significance recover far less (Gemma: 14.0%; Qwen: 61.5%), ruling out the possibility that any high-variance late-layer perturbation would produce the same result. Qwen's elevated null NPE is consistent with the broader pattern of high non-specific perturbation sensitivity in that architecture (§5.5), but demographic features still substantially exceed the null in both models.

Third, late-layer features are increasingly domain-specialised in Gemma: cross-domain Jaccard similarity drops from 0.920 at L5 to 0.392 at L36, with shared features declining from 83.8% to 11.9%. Generic response-generation features would be domain-invariant; these are not. Together, these results indicate that late-layer features encode how demographic context shapes normative judgment in specific domains, not simply how to produce a well-formatted response.

6.2   Implications for Bias Auditing

These findings expose a structural blind spot in representational approaches to bias detection. Current methods typically identify demographic features by probing for representations that differ across demographic conditions (Ravfogel et al., 2020), then intervene on those with the strongest detected signal. Our results show that this selection criterion is misleading when applied without depth awareness: the layers with the strongest demographic encoding are causally inert, while the features that actually mediate demographic effects reside at late layers where encoding is substantially weaker. Furthermore, the causally important features at late layers encode demographics polysemantically as composite social axes rather than clean single-attribute detectors (Appendix D.5) suggesting that standard single-demographic probes may fail to identify the relevant features even at the correct depth, though we do not test this directly.

The domain-contingency of demographic influence compounds this problem. NPE varies substantially across demographic×domain combinations (Gemma IQR (interquartile range):59% to 89%; Qwen IQR (interquartile range): 79% to 157%), meaning that aggregate fairness evaluations would miss the heterogeneous structure of demographic influence.

For value-sensitive deployments, audits must therefore be both causally validated and domain-specific. These conclusions extend recent findings that models passing explicit bias benchmarks still harbor implicit biases (Bai et al., 2025) and that demographic representations are linear and causal (Bouchaud & Ramaciotti, 2025), by adding that the strength of encoding does not predict causal influence, and that the distribution of influence is uneven across policy areas.

6.3   Limitations

Three models in the 7–9B range do not establish that the dissociation holds at larger scales, though consistency across Gemma, Qwen, and Llama with different alignment procedures and SAE regimes suggests it is not idiosyncratic to a single model family. Quantitative details are architecture-dependent: Qwen shows higher random baselines and elevated cross-condition transfer, while Llama shows non-significant ablation ($d_z = 0.08$, $p = 0.07$), consistent with redundant encoding (§5.6). The qualitative pattern, late-layer causal concentration with early-layer encoding, holds across all three.

Our contrastive design uses extreme demographic values to maximise feature identification sensitivity (§3), which is appropriate for the discovery question we address but does not establish that the same features mediate effects under naturalistic demographic variation, non-Western contexts, or open-ended generation.

All models studied are instruction-tuned, leaving open whether the dissociation reflects architectural properties or is induced by alignment training. Base-versus-instruction-tuned comparisons would address this directly.

Finally, most causally important features lack clear semantic labels, limiting interpretation beyond the causal-functional level.

7 Conclusion

We presented a mechanistic analysis of how demographic context causally influences normative reasoning in large language models. Using sparse autoencoders and three causal interventions across Gemma 2 9B, Qwen 2.5 7B, and Llama 3.1 8B, we traced the path from demographic encoding to demographic influence and found that these are distinct phenomena occurring at different network depths. Early layers construct representations of demographic identity (Gemma: mean $|d_{\text{enc}}| > 1.7$; Llama: $|d_{\text{enc}}| = 4.73$) that contribute minimally to outputs, while late layers, where encoding is weaker ($|d_{\text{enc}}| < 1.2$ across all three models), carry the causal leverage that shapes normative judgments, recovering 68.7–75.8% of baseline effects across architectures through targeted patching. Variance-matched null baselines confirm specificity, with gaps of 61.8 (Gemma) and 55.3 (Qwen) percentage points between demographic and non-demographic features at the best layer.

This dissociation generalises across three architectures with different encoding profiles and alignment procedures. Gemma shows opposing depth gradients; Qwen shows flat encoding with late-concentrated causal influence; Llama shows steep encoding decline with the same late-layer causal concentration. The invariant is the late-layer concentration of causal effects, not the encoding structure. The dissociation is further modulated by domain: NPE varies substantially across demographic×domain combinations (Gemma IQR: 59–89%; Qwen IQR: 79–157%), and features become increasingly domain-specialized with depth in Gemma (cross-domain Jaccard: $0.920 \rightarrow 0.392$), indicating that models learn to deploy different aspects of demographic identity depending on what is being reasoned about.

The practical implication is that bias auditing strategies relying on representational detection will surface the wrong model components, targeting features that are visible but causally inert while missing the late-layer, domain-specific features that actually drive outputs. Effective governance of language models in value-sensitive applications requires causal validation of representational findings, conducted separately for each deployment domain.

Broader Impact Statement

Our methods are designed for bias auditing, but the same pipeline could in principle be used to amplify rather than mitigate demographic influence; for example, by identifying late-layer causal features and steering them to increase demographic sensitivity in targeted domains. We believe the transparency value of publishing the methodology outweighs this risk, as effective bias mitigation requires the research community to understand the mechanisms it seeks to govern, and because the interventions we describe require white-box access to model weights, limiting misuse by external actors.

The European Social Survey data used in this study are collected under established ethical protocols with informed consent from participants, governed by ESS ERIC's data protection framework in compliance with GDPR, and made available for scientific research under a registered user agreement. We use only aggregate response patterns and do not attempt to identify individual respondents. The binary gender contrast in our experimental design is constrained by the ESS panel variable and does not reflect the full spectrum of gender identities; we flag this as a limitation and note that extending the framework to non-binary identities is an important direction for future work.

References

Hiba Ahsan, Arnab Sen Sharma, Silvio Amir, David Bau, and Byron C Wallace. Elucidating mechanisms of demographic bias in LLMs for healthcare. In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 14614–14631, Suzhou, China, November 2025. Association for Computational Linguistics. ISBN 979-8-89176-335-7. doi: 10.18653/v1/2025.findings-emnlp.789. URL https://aclanthology.org/2025.findings-emnlp.789/.

Lisa P. Argyle, Ethan C. Busby, Nancy Fulda, Joshua R. Gubler, Christopher Rytting, and David Wingate. Out of one, many: Using language models to simulate human samples. *Political Analysis*, 31(3):337–351, 2023. doi: 10.1017/pan.2023.2.

Xuechunzi Bai, Angelina Wang, Ilia Sucholutsky, and Thomas Griffiths. Explicitly unbiased large language models still form biased associations. *Proceedings of the National Academy of Sciences*, 122, 02 2025. doi: https://doi.org/10.1073/pnas.2416228122.

Joseph Bloom, Curt Tigges, Anthony Duong, and David Chanin. Saelens. https://github.com/decoderesearch/SAELens, 2024.

Paul Bouchaud and Pedro Ramaciotti. Linear socio-demographic representations emerge in large language models from indirect cues. 2025. URL https://arxiv.org/abs/2512.10065.

Trenton Bricken, Adly Templeton, Joshua Batson, Brian Chen, Adam Jermyn, Tom Conerly, Nick Turner, Cem Anil, Carson Denison, Amanda Askell, et al. Towards monosemanticity: Decomposing language models with dictionary learning. *Transformer Circuits Thread*, 2(5):6, 2023. URL https://transformer-circuits.pub/2023/monosemantic-features.

Arthur Conmy, Augustine N. Mavor-Parker, Aengus Lynch, Stefan Heimersheim, and Adrià Garriga-Alonso. Towards automated circuit discovery for mechanistic interpretability. 2023. URL https://arxiv.org/abs/2304.14997.

Hoagy Cunningham, Aidan Ewart, Logan Riggs, Robert Huben, and Lee Sharkey. Sparse autoencoders find highly interpretable features in language models. 2023. URL https://arxiv.org/abs/2309.08600.

Esin Durmus, Karina Nguyen, Thomas I. Liao, Nicholas Schiefer, Amanda Askell, Anton Bakhtin, Carol Chen, Zac Hatfield-Dodds, Danny Hernandez, Nicholas Joseph, Liane Lovitt, Sam McCandlish, Orowa Sikder, Alex Tamkin, Janel Thamkul, Jared Kaplan, Jack Clark, and Deep Ganguli. Towards measuring the representation of subjective global opinions in language models. 2024. URL https://arxiv.org/abs/2306.16388.

Yanai Elazar, Shauli Ravfogel, Alon Jacovi, and Yoav Goldberg. Amnesic probing: Behavioral explanation with amnesic counterfactuals. *Transactions of the Association for Computational Linguistics*, 9:160–175, 2021. doi: 10.1162/tacl_a_00359. URL https://aclanthology.org/2021.tacl-1.10/.

European Social Survey European Research Infrastructure (ESS ERIC). CRONOS3 Wave 4, edition 1.1 [Data set], 2026. URL https://doi.org/10.21338/cron3w4e01_1.

Leo Gao, Tom Dupré la Tour, Henk Tillman, Gabriel Goh, Rajan Troll, Alec Radford, Ilya Sutskever, Jan Leike, and Jeffrey Wu. Scaling and evaluating sparse autoencoders. 2024. URL https://arxiv.org/abs/2406.04093.

Mor Geva, Jasmijn Bastings, Katja Filippova, and Amir Globerson. Dissecting recall of factual associations in auto-regressive language models, 2023. URL https://arxiv.org/abs/2304.14767.

Shashank Gupta, Vaishnavi Shrivastava, Ameet Deshpande, Ashwin Kalyan, Peter Clark, Ashish Sabharwal, and Tushar Khot. Bias runs deep: Implicit reasoning biases in persona-assigned llms. 2024. URL https://arxiv.org/abs/2311.04892.

Stefan Heimersheim and Neel Nanda. How to use and interpret activation patching, 2024. URL `https://arxiv.org/abs/2404.15255`.

Tom Lieberum, Senthooran Rajamanoharan, Arthur Conmy, Lewis Smith, Nicolas Sonnerat, Vikrant Varma, János Kramár, Anca Dragan, Rohin Shah, and Neel Nanda. Gemma scope: Open sparse autoencoders everywhere all at once on gemma 2. 2024. URL `https://arxiv.org/abs/2408.05147`.

Samuel Marks, Can Rager, Eric J. Michaud, Yonatan Belinkov, David Bau, and Aaron Mueller. Sparse feature circuits: Discovering and editing interpretable causal graphs in language models. 2025. URL `https://arxiv.org/abs/2403.19647`.

Kevin Meng, David Bau, Alex Andonian, and Yonatan Belinkov. Locating and editing factual associations in gpt. 2023. URL `https://arxiv.org/abs/2202.05262`.

Nikhil Prakash, Tamar Rott Shaham, Tal Haklay, Yonatan Belinkov, and David Bau. Fine-tuning enhances existing mechanisms: A case study on entity tracking, 2024. URL `https://arxiv.org/abs/2402.14811`.

Senthooran Rajamanoharan, Tom Lieberum, Nicolas Sonnerat, Arthur Conmy, Vikrant Varma, János Kramár, and Neel Nanda. Jumping ahead: Improving reconstruction fidelity with jumprelu sparse autoencoders, 2024. URL `https://arxiv.org/abs/2407.14435`.

Shauli Ravfogel, Yanai Elazar, Hila Gonen, Michael Twiton, and Yoav Goldberg. Null it out: Guarding protected attributes by iterative nullspace projection, 2020. URL `https://arxiv.org/abs/2004.07667`.

Abhilasha Ravichander, Yonatan Belinkov, and Eduard Hovy. Probing the probing paradigm: Does probing accuracy entail task relevance? In Paola Merlo, Jorg Tiedemann, and Reut Tsarfaty (eds.), *Proceedings of the 16th Conference of the European Chapter of the Association for Computational Linguistics: Main Volume*, pp. 3363–3377, Online, April 2021. Association for Computational Linguistics. doi: 10.18653/v1/ 2021.eacl-main.295. URL `https://aclanthology.org/2021.eacl-main.295/`.

Shibani Santurkar, Esin Durmus, Faisal Ladhak, Cinoo Lee, Percy Liang, and Tatsunori Hashimoto. Whose opinions do language models reflect? 2023. URL `https://arxiv.org/abs/2303.17548`.

Alexander Matt Turner, Lisa Thiergart, Gavin Leech, David Udell, Ulisse Mini, and Monte MacDiarmid. Activation addition: Steering language models without optimization. June 2024. URL `https://arxiv.org/html/2308.10248v4`.

Kevin Wang, Alexandre Variengien, Arthur Conmy, Buck Shlegeris, and Jacob Steinhardt. Interpretability in the wild: a circuit for indirect object identification in gpt-2 small. 2022. URL `https://arxiv.org/abs/2211.00593`.

Fred Zhang and Neel Nanda. Towards best practices of activation patching in language models: Metrics and methods. 2024. URL `https://arxiv.org/abs/2309.16042`.

Chunting Zhou, Pengfei Liu, Puxin Xu, Srini Iyer, Jiao Sun, Yuning Mao, Xuezhe Ma, Avia Efrat, Ping Yu, LILI YU, Susan Zhang, Gargi Ghosh, Mike Lewis, Luke Zettlemoyer, and Omer Levy. LIMA: Less is more for alignment. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=KBMOKmX2he`.

A Transfer Error Definitions

The main text defines three normalized intervention metrics: NPE for patching (Equation 6), NAE for ablation (Equation 7), and NSE for steering (Equation 8), each expressing effect size relative to Δ_{EV}. Normalization enables comparison across scales but can obscure interpretation when baseline effects are small or when interventions overshoot their targets. We therefore report signed and absolute transfer errors for all three interventions, expressed in original scale units.

Each intervention has a target outcome. The signed transfer error (STE) is the difference between the observed post-intervention behavioral gap and this target; |STE| is its magnitude.

Patching. The target is exact reproduction of condition a's baseline output, i.e., $\mathrm{EV}'_b = \mathrm{EV}_a$, yielding a post-intervention gap of Δ_{EV}:

$$\mathrm{STE}_{\mathrm{patch}} = (\mathrm{EV}'_b - \mathrm{EV}_b) - \Delta_{\mathrm{EV}} \tag{9}$$

Ablation. The target is complete elimination of the demographic effect, i.e., $\mathrm{EV}'_a = \mathrm{EV}_b$, yielding a post-intervention gap of zero:

$$\mathrm{STE}_{\mathrm{ablation}} = \mathrm{EV}'_a - \mathrm{EV}_b \tag{10}$$

Steering. The target is NSE by factor α ($= 2.0$), i.e., a post-intervention gap of $\alpha\Delta_{\mathrm{EV}}$:

$$\mathrm{STE}_{\mathrm{steer}} = (\mathrm{EV}'_a - \mathrm{EV}_b) - \alpha\Delta_{\mathrm{EV}} \tag{11}$$

For all three, STE $= 0$ indicates the intervention achieved its target exactly. Negative values indicate undershoot and positive values indicate overshoot. |STE| treats both directions symmetrically. Table 1 summarises the metrics.

Table 1: normalized metrics and transfer errors for each intervention. Perfect transfer corresponds to STE $= 0$ and the normalized metric equalling 1.0.

Intervention	normalized metric	Target gap	STE definition	Perfect transfer
Patching	NPE (Eq. 6)	Δ_{EV}	$(\mathrm{EV}'_b - \mathrm{EV}_b) - \Delta_{\mathrm{EV}}$	STE $= 0$, NPE $= 1$
Ablation	NAE (Eq. 7)	0	$\mathrm{EV}'_a - \mathrm{EV}_b$	STE $= 0$, NAE $= 1$
Steering	NSE (Eq. 8)	$\alpha\Delta_{\mathrm{EV}}$	$(\mathrm{EV}'_a - \mathrm{EV}_b) - \alpha\Delta_{\mathrm{EV}}$	STE $= 0$, NSE $= 1$

B Causal Validation Details

This appendix provides detailed results supporting the causal intervention analyses in §5. All means use 1st/99th percentile Winsorization; steering means use a $\pm200\%$ cap (§4.4).

B.1 Main Intervention Results

Tables 2 and 3 report metrics at the best layer ($K = 50$, per-pair). All interventions significantly exceed Random-A controls ($p < 0.001$).

Table 2: Gemma 2 9B IT at L36 ($K = 50$, per-pair).

	Mean	Med.	Rnd-A	d_z	N
NPE	75.8	90.7	26.7	0.99	384
NSE	65.1	40.6	42.8	0.44	384
NAE	74.5	85.1	26.6	1.27	384

Table 3: Qwen 2.5 7B IT at L27 ($K\!=\!50$, per-pair).

	Mean	Med.	Rnd-A	d_z	N
NPE	132.9	102.3	53.2	0.63	364
NSE	75.3	69.6	13.2	0.67	364
NAE	62.5	96.3	-23.3	0.56	364

B.2 Aggregate vs. Per-Pair Selection

Per-pair selection chooses the K most active features per contrastive pair (upper bound). Aggregate selection uses population-level top-K features (§4.3), testing generalisation. In Gemma ($N_{\mathrm{agg}}=97$), aggregate features retain most of the per-pair effect (ratio ≥ 0.70). In Qwen ($N_{\mathrm{agg}}=260$), aggregate features perform substantially worse (patching ratio 0.27), indicating more pair-specific features.

Table 4: Gemma: agg. vs. per-pair, L36. $N_{\mathrm{agg}}=97$.

	Per-Pair	Agg.	Ratio
NPE	75.8	55.4	0.73
NSE	65.1	70.1	1.08
NAE	74.5	52.2	0.70

Table 5: Qwen: agg. vs. per-pair, L27. $N_{\mathrm{agg}}=260$.

	Per-Pair	Agg.	Ratio
NPE	132.9	36.3	0.27
NSE	75.3	13.6	0.18
NAE	62.5	-5.3	-0.08

B.3 Demographic Breakdown

Tables 6 and 7 disaggregate results by demographic (mean / median). In Gemma, education shows the highest NPE (90.3) and gender the lowest (62.7). In Qwen, gender shows the largest mean–median divergence for patching (209.3 vs. 109.7), reflecting overshoot on a subset of pairs.

B.4 Dose-Response

Figures 6 and 7 show intervention effects as a function of K at the best layer. In Gemma at L36, all three interventions increase monotonically: NPE from 39.8 ($K\!=\!5$) to 75.8 ($K\!=\!50$); NSE from 47.9 to 65.1; NAE from 40.8 to 74.5. In Qwen at L27, NPE rises from 75.8 ($K\!=\!5$) to 132.9 ($K\!=\!50$), saturating by $K\!=\!100$ (132.7). NSE rises from 40.5 to 75.3; NAE from 5.5 to 62.5 (both saturating at $K\!=\!100$). We tested $K\!=\!100$ only for Qwen. In both models, the specificity gap widens with K.

B.5 Floor-Effect Exclusion

We exclude pairs with $|\Delta_{\mathrm{EV}}|$ below a scale-normalized threshold (0.3 scale points for range $=10$, scaled proportionally: 0.03 for range $=1$, 0.09 for range $=3$, 0.12 for range $=4$). After exclusion, 384 pairs remain for Gemma (L36) and 364 for Qwen (L27).

Table 6: Gemma: by demographic, L36. Mean / med.

	N	NPE	NSE	NAE
Inc.	102	76.7/94.3	49.1/24.8	80.9/96.1
Age	42	81.3/88.1	68.6/42.3	89.1/92.2
Gen.	67	62.7/76.8	79.4/49.9	58.2/69.2
Edu.	81	90.3/98.8	74.5/75.2	71.4/81.9
Vote	92	69.1/90.2	62.3/23.4	75.3/77.1

Table 7: Qwen: by demographic, L27. Mean / med.

	N	NPE	NSE	NAE
Inc.	105	114.0/101.4	77.1/52.9	61.4/100.0
Age	62	108.5/93.0	79.3/80.6	55.4/93.8
Gen.	42	209.3/109.7	94.6/113.0	15.5/82.6
Edu.	75	167.0/111.6	81.3/77.6	44.7/92.7
Vote	80	104.8/95.2	54.2/34.4	110.5/96.2

Figure 6: Gemma 2 9B IT: dose-response at Layer 36. All three interventions increase monotonically with K, with specificity gaps widening at each step.

Figure 7: Qwen 2.5 7B IT: dose-response at Layer 27. All three interventions saturate by $K = 50$; $K = 100$ confirms no additional gains.

Figure 8: Gemma: pairs excluded by scale range.

Figure 9: Qwen: pairs excluded by scale range.

C   Feature Identification Details

C.1   Filter Pipeline

From the full set of $m = 16{,}384$ SAE features at each layer, we select demographic-relevant features through a three-stage pipeline applied independently to each demographic×domain group (25 groups per layer).

Stage 1: Noise filtering.   We exclude features with inconsistent activation differences across contrastive pairs. A feature passes if it shows consistent sign direction (sign agreement ≥ 0.6)) and is not flagged as noisy based on coefficient of variation and outlier ratio thresholds.

Stage 2: Statistical testing.   We apply one-sample t-tests on mean activation differences within each group, with Benjamini-Hochberg correction at $\alpha = 0.05$.

Stage 3: Effect size thresholding.   We retain features with $|\text{Cohen's } d_z| \geq 0.3$. From the features passing all three stages, we select the top $K = 50$ by mean absolute activation difference.

C.2   Feature Yield

Table 8 reports the number of features passing all filter stages at each layer, averaged across the 25 demographic×domain groups. In Gemma, feature yield peaks at middle layers (L14, L18) and declines at late layers where causal effects concentrate. In Qwen, yield increases with depth, with the most features at L27 (the causally important layer). This pattern is consistent with the dissociation: layers with many detectable features are not necessarily the layers where those features causally matter. Some Qwen demographic×domain groups yield as few as 1 feature after filtering, reflecting the uniformly weak encoding in that model. Causal validation uses per pair feature selection, which is not constrained by population-level yield. The mean $|d_{\text{enc}}|$ of selected features declines with depth in Gemma (2.02 at L9 to 0.99 at L36),

Table 8: Feature yield per layer. Mean (min–max) selected features per demographic×domain group, and mean $|d_{\text{enc}}|$ of all selected features at each layer.

Layer	Mean/group	Range	$|d_{\text{enc}}|$
Gemma 2 9B IT			
L5 (12%)	37.9	30–48	1.78
L9 (22%)	30.8	24–37	2.02
L14 (34%)	47.5	36–50	2.00
L18 (44%)	48.0	38–50	1.96
L20 (49%)	25.8	15–34	1.42
L27 (66%)	46.3	31–50	1.15
L32 (78%)	34.4	17–50	1.02
L36 (88%)	32.8	12–50	0.99
Qwen 2.5 7B IT			
L7 (26%)	52.8	1–100	0.41
L15 (56%)	29.4	1–100	0.52
L19 (70%)	41.7	1–100	0.43
L23 (85%)	60.6	1–100	0.32
L27 (100%)	72.4	1–100	0.31

consistent with the encoding gradient reported in §5.2. In Qwen, encoding is weaker overall ($|d_{\text{enc}}| \leq 0.52$) and relatively flat across layers. Figures 10 and 11 show the full encoding strength profile disaggregated by demographic×domain.

Figure 10: Gemma 2 9B IT: mean $|d_{\mathrm{enc}}|$ of selected features by domain×demographic at each layer. Encoding peaks at early-to-middle layers and declines with depth across all cells.

C.3 Encoding by Domain and Demographic

Figures 10 and 11 show mean |Cohen's d| of selected features for each demographic×domain cell at every layer. Several patterns are notable.

In Gemma, encoding is strongest for age×health (peaking at $|d_{\mathrm{enc}}| = 4.04$ at L18) and gender across most domains. Encoding declines monotonically with depth for all cells, but the rate varies: health-related cells retain stronger encoding at late layers than digital governance or economy cells. At L36, health cells still show $|d_{\mathrm{enc}}| > 1.0$ while most other cells fall below 1.0.

In Qwen, encoding is substantially weaker across the board ($|d_{\mathrm{enc}}|$ rarely exceeds 1.0). Vote×climate shows the strongest early encoding ($|d_{\mathrm{enc}}| = 1.27$ at L7). Gender shows relatively high encoding at middle layers across domains (e.g., gender×values: 0.60 at L27). The flatter encoding profile in Qwen contrasts with Gemma's steep decline but, as shown in §5.2, both models exhibit the same late-layer concentration of causal effects.

Figure 11: Qwen 2.5 7B IT: mean $|d_{\text{enc}}|$ by domain×demographic at each layer. Encoding is weaker overall and relatively flat across depth.

D Technical Validation and behavioral Baseline

This appendix reports SAE reconstruction quality (§D.1), tokenizer handling (§D.2), and full behavioral baseline results (§D.3).

D.1 SAE Reconstruction Quality

We use width-16K Gemma Scope SAEs (Lieberum et al., 2024) for Gemma 2 9B and width-131K SAEs from Gao et al. (2024) for Qwen 2.5 7B. Table 9 reports reconstruction quality for Gemma across all eight analyzed layers; Table 10 reports the same for Qwen across five layers.

For Gemma, cosine similarity ranges from 0.82 (L32) to 0.91 (L5), with NMSE between 0.17 and 0.32. Reconstruction quality degrades modestly at late layers (L27–L36), coinciding with higher observed L0 sparsity which refers to the number of active features per input, (97–112 active features vs. the canonical 61–77). All layers pass standard quality thresholds (cosine > 0.80).

For Qwen, cosine similarity ranges from 0.82 (L27) to 0.96 (L3) on demographic prompts. Reconstruction is weaker at L23 and L27 (cosine < 0.85). However, for our differential analysis (contrastive activation differences), reconstruction errors cancel to first order if they are consistent across conditions. Per-prompt cosine similarity exceeds 0.90 for most individual prompts even at L15 (Table 11), suggesting that the SAE captures condition-relevant variation well despite moderate aggregate error.

L20 for Gemma uses the instruction-tuned (IT) SAE variant; all other Gemma layers use pretrained (PT) SAEs. All Qwen SAEs are IT variants.

Per-prompt reconstruction (Qwen L15). Table 11 shows that individual demographic prompts achieve cosine ≥ 0.86 at L15, confirming adequate reconstruction on the prompts used in our pipeline. Tables 9 and 10 report different reconstruction metrics because the two SAE frameworks (Gemma Scope and SAELens) expose different default diagnostics. Cosine similarity and sparsity (L0) are directly comparable across both.

Table 9: Gemma SAE reconstruction quality per layer. R^2 denotes explained variance $(1 - \text{NMSE})$, distinct from the expected value EV defined in Equation 3.

Layer	SAE	NMSE	Cos	R^2	L0	Alive
L5	PT	0.17	0.91	0.83	64	0.5%
L9	PT	0.23	0.88	0.77	44	0.4%
L14	PT	0.24	0.87	0.76	70	0.8%
L18	PT	0.22	0.89	0.78	65	0.9%
L20	IT	0.20	0.89	0.80	38	0.6%
L27	PT	0.27	0.85	0.73	112	3.8%
L32	PT	0.32	0.82	0.68	97	3.4%
L36	PT	0.28	0.85	0.72	104	4.2%

PT = pretrained SAE; IT = instruction-tuned SAE.

Table 10: Qwen SAE reconstruction quality per layer (demographic prompts only).

Layer	Cos	RelErr	L0	L1
L3 (11%)	0.96	27.0%	50	79.8
L7 (26%)	0.91	41.0%	64	154.0
L11 (41%)	0.91	41.7%	58	190.3
L15 (56%)	0.90	42.9%	56	225.4
L19 (70%)	0.88	47.4%	51	298.4
L23 (85%)	0.85	52.7%	54	629.8
L27 (100%)	0.82	57.5%	52	1601.3

D.2 Tokenizer Handling

Our experimental design requires models to select responses from a fixed set of numerical options presented on Likert-type and categorical scales. Scale endpoints vary across ESS items (e.g., 0–10 for agreement, 1–4 for categorical). Two tokenization issues arise.

Multi-token numbers. The value "10" tokenizes to two tokens in both Gemma and Qwen tokenizers ("1" + "0"). Since the model predicts one token at a time, the first-token probability $P(\text{"1"})$ conflates two response values: 1 and the first digit of 10. For 11-point scales (0–10), we split $P(\text{"1"})$ equally between value 1 and value 10 (i.e., $P(1) = P(10) = \frac{1}{2}P(\text{"1"})$).

Expected value computation. For each item, we extract logits over the full vocabulary at the response position, restrict to valid scale tokens (including multi-token handling as described above), renormalize via softmax to obtain a probability distribution over valid responses, and compute the expected value EV $= \sum_v v \cdot P(v)$.

D.3 Behavioral Baseline

Tables 12 and 13 report the full behavioral effect for each demographic×domain cell. Effects are computed as the mean EV difference between contrastive persona pairs (condition a minus condition b), averaged across all items within each domain. We report significance at $p < 0.05$ (paired t-test).

Gemma shows significant effects in 24 of 25 cells, with the non-significant cell being gender×digital ($\Delta\text{EV} = 0.007$, $p > 0.05$). Qwen shows significant effects in 17 of 25 cells, with substantially smaller effects across all cells (max $|\Delta\text{EV}| = 0.139$ vs. Gemma's 0.594).

Table 11: Qwen per-prompt reconstruction at L15.

Prompt	Cos	RelErr	L0
wealthy/F/FR/climate	0.92	40.0%	54
poor+old/M/DE/health	0.90	43.4%	47
young+poor/F/PL/econ	0.89	44.7%	53
wealthy(A)/M/UK/health	0.91	40.4%	49
poor(B)/M/UK/health	0.91	40.4%	51
old+nonvote/F/SE/values	0.94	34.0%	23
young+edu/M/NL/digital	0.87	49.3%	76
mid+lowed/F/ES/econ	0.86	51.1%	91

Table 12: Gemma 2 9B IT: behavioral effects (ΔEV) by demographic$\times$domain. Bold indicates $p < 0.05$.

	Inc.	Age	Gen.	Edu.	Vote
Clim.	**−.476**	**.163**	**.172**	**−.480**	**−.352**
Heal.	**−.361**	−.043	**.301**	**−.522**	**−.517**
Digi.	**.420**	**.073**	.007	**.084**	**.156**
Econ.	**.594**	**.182**	**−.146**	**.153**	**.052**
Valu.	**.287**	**−.272**	**−.079**	**.250**	**.158**

Table 13: Qwen 2.5 7B IT: behavioral effects (ΔEV) by demographic$\times$domain. Bold indicates $p < 0.05$.

	Inc.	Age	Gen.	Edu.	Vote
Clim.	.000	**−.040**	**−.047**	.008	**−.049**
Heal.	**.040**	**.040**	**.029**	−.021	−.003
Digi.	**−.023**	−.001	**−.007**	**−.055**	**.009**
Econ.	**.139**	.024	.001	**−.057**	**−.072**
Valu.	**.052**	−.015	**−.080**	**.069**	**.031**

Scale effects. The magnitude of behavioral effects correlates with scale range: 11-point scales (0–10) tend to show larger absolute ΔEV than 5-point Likert scales (1–5). This motivates the scale-normalized floor-effect exclusion threshold used in the causal analysis (Appendix B.5).

D.4 Cross-Architecture Replication: Llama 3.1 8B

We replicate the core analyses on Llama 3.1 8B Instruct (three layers: L15, L23, L27) to test cross-model generalizability. All 25 demographic$\times$domain cells show significant behavioral effects; $N = 479$ pairs remain after floor-effect exclusion.

Llama replicates the encoding-causal dissociation: mean $|d_{\mathrm{enc}}|$ of selected features declines from 4.73 (L15) to 1.98 (L23) to 1.19 (L27), yet causal effects concentrate at L27 where encoding is weakest.

Table 14 reports causal validation at L27 ($K = 50$, per-pair). Patching and steering exceed Random-A controls (NPE 68.7% vs. 22.8%; NSE 62.3% vs. 25.8%). Ablation is weaker (NAE 29.9% vs. 24.3%, $d_z = 0.08$), consistent with redundant encoding. Gender shows

the strongest patching (88.6%) and steering (102.8%); age shows negligible ablation (1.0%).

Table 14: Llama at L27 ($K = 50$, $N = 479$). Top: aggregate. Bottom: by demographic (mean / med.).

	Mean	Med.	Rnd-A	d_z
NPE	68.7	73.5	22.8	0.52
NSE	62.3	65.6	25.8	0.36
NAE	29.9	50.2	24.3	0.08

	N	NPE	NSE	NAE
Inc.	127	59.3/69.3	43.4/52.1	41.2/63.8
Age	71	76.7/69.8	61.4/76.1	1.0/8.1
Gen.	60	88.6/85.2	102.8/109.4	34.9/45.5
Edu.	96	56.6/63.2	67.3/72.0	26.0/43.7
Vote	125	73.2/85.8	58.6/54.7	35.5/53.6

D.5 Feature Interpretability

To characterize what late-layer causal features encode, we analyze the 10 features with highest mean causal effect at the best layer in each model (Gemma L36, Qwen L27). For each feature, we test encoding of all five demographic dimensions using paired t-tests on 30 held-out contrastive pairs per dimension, with Benjamini-Hochberg correction at $\alpha = 0.05$. We report Cohen's d_z as the effect size. Figures 12 and 13 show the full encoding matrices.

Polysemantic demographic encoding. In both models, causally important features encode multiple demographics simultaneously rather than acting as single-demographic detectors. In Gemma, all 10 features encode two or more demographics significantly (mean 3.3 per feature); in Qwen, 7 of 10 do (mean 3.1). This polysemanticity explains why single-demographic probes applied at late layers would fail to identify these features: they do not cleanly separate along any one demographic axis.

Composite social axes. In Gemma, 9 of 10 multi-demographic features show opposite-direction encoding across demographics. For example, feature 11066 activates positively for age ($d_z = +0.6$) but negatively for income ($d_z = -1.4$), gender ($d_z = -1.1$), education ($d_z = -1.2$), and vote ($d_z = -1.4$). This pattern indicates encoding of composite social axes where correlated demographic attributes (e.g., younger/wealthier/female/educated/voter) load together, rather than encoding independent demographic dimensions. In Qwen, the pattern is present but weaker: 4 of 7 multi-demographic features show opposite-direction encoding, with 3 showing same-direction encoding, consistent with the less domain-specific feature structure reported in §5.5.

Response-position concentration. In both models, feature activations concentrate at the final (response) token position rather than being distributed across the prompt span. In the majority of feature×demographic cells, span activation is zero, yielding an undefined ratio; among the cells with non-zero span activation, the mean ratio of last-token to span activation magnitude is 82.3× in Gemma (6 of 50 cells) and 56.4× in Qwen. This is consistent with demographic information being integrated at the point of output generation, not during initial prompt processing, though the small number of cells with finite ratios warrants caution.

Weak per-feature encoding at causal layers. Mean encoding strength across all 50 feature×demographic cells (10 features × 5 demographics) is $|d| = 0.62$ in Gemma and $|d| = 0.54$ in Qwen, substantially below the early-layer encoding peaks reported in §5.2 (Gemma L9: $|d| = 2.02$; Qwen L15: $|d| = 0.52$, Table 8). Individual features show strong encoding for specific demographics (e.g., Qwen feature 44474: gender $d = -2.6$; Gemma feature 15398: gender $d = +1.6$), but these are exceptions. The typical pattern is moderate, distributed encoding across multiple demographics, reinforcing the central finding that the features most causally important for normative outputs are not the features most detectable by standard encoding measures.

Figure 12: Gemma 2 9B IT: encoding matrix for the 10 most causally important features at L36. Cells show signed Cohen's d_z; significance after BH-FDR (False Discovery Rate) correction: $^*p < 0.05$, $^{**}p < 0.01$, $^{***}p < 0.001$.

Figure 13: Qwen 2.5 7B IT: encoding matrix for the 10 most causally important features at L27. Conventions as in Figure 12. Encoding is sparser (48% vs. 66% significant cells) and effect sizes are smaller on average, consistent with Qwen's weaker overall demographic sensitivity.