RECURSIVE REASONING WITH NEURAL NETWORKS

ABSTRACT

Many problems can naturally be thought about recursively. However, neural networks fundamentally cannot reason this way on arbitrarily large problems. This is because they do not have the memory to maintain state for the maximum recursion depth required. Solving this issue would enable neural networks to reason like a wide range of classical recursive algorithms (e.g., tree search in model-based RL). To address this, we propose a neural architecture augmented with a stack that learns to save and recall state as needed. We empirically demonstrate the utility of this method on a recursive neural algorithmic reasoning task (learning depth-first search) and show that our architecture leads to improved generalization.

1 INTRODUCTION & BACKGROUND

Reasoning recursively requires memory at least large enough to store as many states as the maximum recursion depth of the problem. Since neural networks have a fixed size, they cannot reason this way on arbitrarily large problems. This is problematic in Neural Algorithmic Reasoning (NAR) where networks learn to execute algorithms by mimicking steps of algorithmic computation (Veličković & Blundell, 2021; Ibarz et al., 2022).

To address this fundamental issue, we introduce a neural architecture that incorporates a stack. Inspired by call stacks in computer programs, it is used by the network to save or recall state. This enables the network to execute algorithms with arbitrary recursion depth. We demonstrate empirically that our approach is beneficial for neural algorithmic reasoning on depth-first search—a classic example of a recursive problem. Our architecture allows neural networks to reason like classical recursive algorithms used across a wide range of applications such as state-space searches. Therefore, our work is a step towards one of the goals of NAR: building generalist algorithmic learners (Ibarz et al., 2022) that can compose basic algorithms into pragmatic solutions.

2 METHOD & EXPERIMENTS

We implement a stack to store and recall state from a neural network as described in Figure 1. The *hints* (see Veličković et al. (2022) for a complete description) describe the algorithmic computation state (e.g., the state of the pointers in quicksort).

As the prototypical recursive algorithm, we choose depth-first search (DFS) to demonstrate our method. We modify the CLRS algorithmic reasoning benchmark (Veličković et al., 2022) to implement DFS with hints based exactly on the variables of the algorithm defined in Cormen et al. (2009). We append the stack operation to these hints. Our train, validation, and test sets consist of a mix of Erdős–Rényi (E-R) graphs and random binary trees generated with particularly long chains to evaluate high recursion depth. We use a Graph Neural Network (GNN) as the network component of our method. For complete experimental details, see Appendix A and our implementation.[1]

Results. After training to completion, we achieved a mean accuracy of $60.7\% \pm 4.0$ without a stack (but including the stack operation hint) and a mean accuracy of $89.1\% \pm 3.0$ with a stack. Our uncertainty is given as one standard deviation.

---

[1]Our implementation will be provided in the camera-ready version.

Figure 1: **Augmenting a neural network with a stack.** The input to the network is the state at the top of the stack and the algorithm's computation state (a set of hints). **Inference.** The network predicts the next stack element, stack operation, and next algorithm computation state. If the operation is a push, the predicted next stack element is placed on the stack; if it is a pop, the current top stack element is discarded and so is the next stack element prediction. **Training.** We supervise the stack operation selection (and the rest of the algorithmic computation state) by sampling at steps in the computation of the recursive algorithm. This forms the algorithmic computation state (hints) that are predicted by the network and input to the next step.

3   DISCUSSION

We hypothesize that our network is learning to use the stack similarly to a call stack by saving and restoring state across time. This enables reasoning recursively. With this method, we avoid the well-known memory bottleneck seen in Recurrent Neural Networks (RNNs) caused by the fixed size of the hidden state in the network (Jurafsky & Martin, 2022).

Our method resembles that of an RNN or Long Short-Term Memory (LSTM). However, it is important to note the difference. We are able to store the exact past hidden state for an arbitrarily long time and learn to recall it when required. To do so, we must supervise the network's predictions of stack operations which is simple for classical recursive algorithms since call stack usage is well-defined.

4   CONCLUSION & FUTURE WORK

We proposed augmenting a neural network with a stack based on the hypothesis that it allows the network to generalize better on recursive reasoning tasks. We showed that this is indeed the case for neural algorithmic reasoning with depth-first search. This method could be further generalized beyond recursive reasoning to general recursive problems by learning to use a stack without intermediate supervision (e.g., using reinforcement learning). Nevertheless, our solution can currently be used to reason like classical algorithms for backtracking-style search such as path planning. By enlarging the class of algorithms we can precisely reason about, this work is a step towards generalist algorithmic learners (Ibarz et al., 2022).

ACKNOWLEDGEMENTS

Acknowledgements will be included in the camera-ready version.

URM STATEMENT

The authors acknowledge that at least one key author of this work meets the URM criteria of ICLR 2023 Tiny Papers Track.

REFERENCES

Thomas H. Cormen, Charles E. Leiserson, Ronald L. Rivest, and Clifford Stein. *Introduction to algorithms*. MIT Press, 3rd edition, 2009. ISBN 978-0-262-03384-8.

Borja Ibarz, Vitaly Kurin, George Papamakarios, Kyriacos Nikiforou, Mehdi Bennani, Róbert Csordás, Andrew Joseph Dudzik, Matko Bošnjak, Alex Vitvitskyi, Yulia Rubanova, Andreea Deac, Beatrice Bevilacqua, Yaroslav Ganin, Charles Blundell, and Petar Veličković. A generalist neural algorithmic learner. In *Proceedings of the First Learning on Graphs Conference*, volume 198 of *Proceedings of Machine Learning Research*, pp. 2:1–2:23. PMLR, Dec 2022. URL `https://proceedings.mlr.press/v198/ibarz22a.html`.

Dan Jurafsky and James H. Martin. *Speech & language processing*. 3rd edition, 2022. URL `https://web.stanford.edu/~jurafsky/slp3/`.

Petar Veličković, Adrià Puigdomènech Badia, David Budden, Razvan Pascanu, Andrea Banino, Misha Dashevskiy, Raia Hadsell, and Charles Blundell. The CLRS algorithmic reasoning benchmark. In *Proceedings of the 39th International Conference on Machine Learning*, volume 162 of *Proceedings of Machine Learning Research*, pp. 22084–22102. PMLR, Jul 2022. URL `https://proceedings.mlr.press/v162/velickovic22a.html`.

Petar Veličković and Charles Blundell. Neural algorithmic reasoning. *Patterns*, 2(7):100273, July 2021. ISSN 2666-3899. doi: 10.1016/j.patter.2021.100273. URL `https://www.sciencedirect.com/science/article/pii/S2666389921000994`.

A   EXPERIMENT SETUP

We follow the general training setup employed by Ibarz et al. (2022) in their single task experiments. Like Veličković et al. (2022), we apply *teacher forcing* by replacing the predicted computation state of the last time step with the ground truth with 50% probability during training. Crucially, in contrast to the mentioned previous work on NAR, we do not pass a regular hidden state. As compute limits us to relatively small training graphs, it is otherwise easy to overfit to these graphs using this hidden state instead of the stack. Whereas the hidden state would not be able to capture sufficient information for larger graphs, it is easier to learn its usage at the start of training when the stack operations have not yet been learned and we cannot rely on the correct stack element to be present at each time step.

A.1   DFS IMPLEMENTATION

Note that the original specification of DFS for NAR by Veličković et al. (2022) requires prediction of all node-level features (e.g., the parents of all nodes) at once. This inevitably leads to the memory bottleneck issue described in Section 3. Therefore, we collect the output over different time steps, similar to what an RNN would do. We collect the mapping from all nodes to their parents by taking the predicted current node at each time step and overwriting its parent with the predicted parent. Previous work did not exhibit this memory issue as they passed node-level computation states between the time steps. The reason this works in this particular case is that the specific representation of the hints (in terms of nodes) bounds the depth of the call stack in the case of DFS. However, this does not allow learning recursive reasoning. In order to avoid this issue, we modified most of these computation states to be graph-level so that we did not have global information that avoids the need for a call stack.

A.2   GRAPH GENERATION

Following Ibarz et al. (2022), we generate graphs on the fly. However, we observe that their random E-R graphs often only require a low recursion depth. Therefore, we substitute 15% of the generated graphs with random binary trees. We use graphs of size 4, 8, 16, 24, and 32 for training whereas only graphs of size 32 are used for validation (with early stopping) and testing.

A.3 GRAPH-LEVEL CALLSTACK

In our concrete implementation of the general method in Section 2, we employ a Message-Passing Neural Network (MPNN). To utilize a graph-level call stack, we construct a stack element by max-pooling node embeddings.

B ABLATION

Figure 2: **A call stack is advantageous for learning DFS.** We show the means of three runs with different random seeds. The shaded area shows the standard deviation. "with call stack" describes our contribution which is the incorporation of a call stack with a stack operation hint as described in Figure 1. "only stack operation hint" is the same but without inputting the stack elements to the network (i.e., we still predict the stack operations, but do not make use of the stack itself). "neither" removes both the stack and the stack operation hint, leaving only the hints based on the variables of the algorithm.

In Figure 2, we perform an ablation where we compare the training curves of three configurations. Adding a hint for the stack operation and allowing the network to learn a stack as described in Section 2 leads to a significant improvement in test accuracy. Only learning the additional stack operation hint but not using a stack does not yield a similar improvement. This indicates that the crucial element is the stack memory itself rather than an inductive bias induced by the new hint.