DO NOT TRAIN IT: A LINEAR NEURAL ARCHITECTURE SEARCH OF GRAPH NEURAL NETWORKS

ABSTRACT

Neural architecture search (NAS) for Graph neural networks (GNNs), called NAS-GNNs, has achieved significant performance over manually designed GNN architectures. However, these methods inherit issues from the conventional NAS methods, such as high computational cost and optimization difficulty. More importantly, previous NAS methods have ignored the uniqueness of GNNs, where the non-linearity has limited effect. Based on this, we are the first to theoretically prove that a GNN fixed with random weights can obtain optimal outputs under mild conditions. With the randomly-initialized weights, we can then seek the optimal architecture parameters via the sparse coding objective and derive a novel NAS-GNNs method, namely neural architecture coding (NAC). Consequently, our NAC holds a no-update scheme on GNNs and can efficiently compute in linear time. Empirical evaluations on multiple GNN benchmark datasets demonstrate that our approach leads to state-of-the-art performance, which is up to $200\times$ faster and 18.8% more accurate than the strong baselines.

1 INTRODUCTION

Remarkable progress of graph neural networks (GNNs) has boosted research in various domains, such as traffic prediction, recommender systems, etc., as summarized in (Wu et al., 2021). The central paradigm of GNNs is to generate node embeddings through the message-passing mechanism (Hamilton, 2020), including passing, transforming, and aggregating node features across the input graph. Despite its effectiveness, designing GNNs requires laborious efforts to choose and tune neural architectures for different tasks and datasets (You et al., 2020), which limits the usability of GNNs. To automate the process, researchers have made efforts to leverage neural architecture search (NAS) (Liu et al., 2019a; Zhang et al., 2021b) for GNNs, including GraphNAS (Gao et al., 2020), Auto-GNN (Zhou et al., 2019), and SANE (Zhao et al., 2021b). In this work, we refer the problem of NAS for GNNs as *NAS-GNNs*.

While NAS-GNNs have shown promising results, they inherit issues from general NAS methods and fail to account for the unique properties of GNN operators. It is important to understand the difficulty in general NAS training (e.g., architecture searching and weight evaluation). Based on the searching strategy, NAS methods can be categorized into three types: reinforcement learning-based methods (Zoph & Le, 2017), evolutionary algorithms-based methods (Jozefowicz et al., 2015), and differential-based methods (Liu et al., 2019a; Wu et al., 2019a) Both reinforcement learning-based and evolutionary algorithm-based methods suffer from high computational costs due to the need to re-train sampled architectures from scratch. On the contrary, the weight-sharing differential-based paradigm reuses the neural weights to reduce the search effort and produces the optimal sub-architecture directly without excessive processes, such as sampling, leading to significant computational cost reduction and becoming the new frontier of NAS.

However, the weight sharing paradigm requires the neural weights to reach optimality so as to obtain the optimal sub-architecture based on its bi-level optimization (BLO) strategy (Liu et al., 2019a), which alternately optimizes the network weights (outputs of operators) and architecture parameters (importance of operators). First, it is hard to achieve the optimal neural weights in general due to the curse of dimensionality in deep learning, leading to unstable searching results, also called the optimization gap (Xie et al., 2022). Second, this paradigm often shows a sloppy gradient estimation (Bi et al., 2020a;b; Guo et al., 2020b) due to the alternating optimization, softmax-based

estimation, and unfairness in architecture updating. This type of work suffers from slow convergence during training and is sensitive to initialization due to the wide use of early termination. If not worse, it is unclear why inheriting weights for a specific architecture is still efficient—the weight updating and sharing lack interpretability.

Is updating the GNN weights necessary? Or, does updating weights contribute to optimal GNN architecture searching? Existing NAS-GNN methods rely on updating the weights, and in fact, all these issues raised are due to the need to update weights to the optimum. Unlike other deep learning structures, graph neural networks behave almost linearly, so they can be simplified as linear networks while maintaining superior performance (Wu et al., 2019b). Inspired by this, we find that the untrained GNN model is nearly optimal in theory. Note that the first paper on modern GNNs, i.e., GCN (Kipf & Welling, 2017a), already spotted this striking phenomenon in the experiment, but gained lit-

Figure 1: Accuracy vs. running time on Cora. NAC (ours) outperforms the leading methods significantly in both accuracy and speed (in minutes).

tle attention. To the best of our knowledge, our work is the first to unveil this and provide theoretical proof. The issues mentioned before may not be as much of a concern given no weight update is needed, making NAS-GNN much simpler.

In this paper, we formulate the NAS-GNN problem as a sparse coding problem by leveraging the untrained GNNs, called neural architecture coding (NAC). We prove that untrained GNNs have built-in orthogonality, making the output dependent on the linear output layer. With no-update scheme, we only need to optimize the architecture parameters, resulting in a single-level optimization strategy as opposed to the bi-level optimization in the weight-sharing paradigm, which reduces the computational cost significantly and improves the optimization stability. Much like the sparse coding problem (Zhang et al., 2015), our goal is also to learn a set of sparse coefficients for selecting operators when treating these weights collectively as a dictionary, making sharing weights straightforward and understandable. Through extensive experiments on multiple challenging benchmarks, we demonstrate that our approach is competitive with the state-of-the-art baselines, while decreasing the computational cost significantly, as shown in Fig. 1.

In summary, our main contributions are:

- **Problem Formulation**: We present (to our best knowledge) the first linear complexity NAS algorithm for GNNs, namely NAC, which is solved by sparse coding.
- **Theoretical Analysis**: Our NAC holds a no-update scheme, which is theoretically justified by the built-in model linearity in GNNs and orthogonality in the model weights.
- **Effectiveness and Efficiency**: We compare NAC with state-of-the-art baselines and show superior performance in both accuracy and speed. Especially, NAC brings up to 18.8% improvement in terms of accuracy and is $200\times$ faster than baselines.

2 RELATED WORK AND PRELIMINARIES

Graph Neural Networks (GNNs) are powerful representation learning techniques (Xu et al., 2019) with many key applications (Hamilton et al., 2017). Early GNNs are motivated from the spectral perspective, such as Spectral GNN (Bruna et al., 2014) that applies the Laplacian operators directly. ChebNet (Defferrard et al., 2016) approximates these operators using summation instead to avoid a high computational cost. GCN (Kipf & Welling, 2017b) further simplifies ChebNet by using its first order, and reaches the balance between efficiency and effectiveness, revealing the message-passing mechanism of modern GNNs. Concretely, recent GNNs aggregate node features from neighbors and stack multiple layers to capture long-range dependencies. For instance, GraphSAGE (Hamilton et al., 2017) concatenates nodes features with mean/max/LSTM pooled neighbouring information. GAT (Velickovic et al., 2018) aggregates neighbor information using learnable attention weights. GIN (Xu et al., 2019) converts the aggregation as a learnable function based on the Weisfeiler-Lehman test instead of prefixed ones as other GNNs, aiming to maximize the power of GNNs.

GNNs consist of two major components, where the *aggregation* step aggregates node features of target nodes' neighbors and the *combination* step passes previous aggregated features to networks to generate node embeddings. Mathematically, we can update node v's embedding at the l-th layer by

$$\boldsymbol{h}_v^l = \phi\left(\boldsymbol{W}^l \cdot o\left(\left\{\boldsymbol{h}_v^{l-1}, \forall u \in N(v)\right\}\right)\right), \tag{1}$$

where $N(v)$ denotes the neighbours of v. $\boldsymbol{W}^l$ denotes the trainable weight shared by all nodes at the l-layer. ϕ is an activation function (with ReLU as default). A main difference of different GNNs lies in the design of the the aggregation functions, $o(\cdot)$. As GNNs have a large design space (You et al., 2020), this makes it challenging for the architecture search.

Neural Architecture Search (Xie & Yuille, 2017) generally includes three major parts, i.e., search spaces, search strategies, and evaluation methods. Recent advances adopt weight-sharing (Xie et al., 2022) to avoid (re-)training from scratch as in previous methods, where any architecture can share the weights directly for evaluation without re-training. In particular, making the weights and architectural parameters differentiable (Liu et al., 2019a; Luo et al., 2018) further improves the training efficiency. Although efficient, weight-sharing NAS has genetic issues that are caused by its bi-level optimization, including over-fitting and inaccurate gradient estimation (Xie et al., 2022), making these methods collapse unexpectedly. A variety of methods are proposed to address this from different perspectives, while mainly adding regularization towards weights, such as using k-shot (Su et al., 2021), paths dropout (Bender et al., 2018), sampling paths (Guo et al., 2020a), sparsity (Zhang et al., 2021a). However, these cures are still within the bi-level optimization framework, which can at best alleviate the problem but not directly tackle it. In this work, we propose NAC, a linear (i.e., single-level) optimization paradigm, to address the issues in weight-sharing NAS.

Concretely, consider WS-NAS defined by $\{\mathcal{A}, \mathcal{W}\}$, where $\mathcal{A}$ and $\mathcal{W}$ denote the search space and weights of neural networks, respectively. WS-NAS addresses two subproblems of these two space alternatively using a bi-level optimization framework (Liu et al., 2019a), including weight optimization and architecture optimization as shown in the following.

$$\boldsymbol{\alpha}^* = \underset{\boldsymbol{\alpha}}{\arg\max}\, \mathcal{M}_{val}\left(w^*(\boldsymbol{\alpha}), \boldsymbol{\alpha}\right); \quad \text{s.t.} \quad \boldsymbol{w}^*(\boldsymbol{\alpha}) = \underset{\boldsymbol{w}}{\arg\min}\, \mathcal{L}_{\text{train}}\left(\boldsymbol{\alpha}, \boldsymbol{w}\right), \tag{2}$$

where $\mathcal{L}$ denotes a loss function in the training set. $\mathcal{M}$ denotes an evaluation metric, such as accuracy, in the validation set. Optimizing separately, WS-NAS avoids the potential biased caused by imbalance dimensionality between w and $\boldsymbol{\alpha}$, i.e., the neural weights and the architecture parameters. DARTS (Liu et al., 2019a) further converts the discrete search space into a differentiable one with the help of the softmax function that is writing as $\dfrac{\exp\left(\alpha_o^{(i,j)}\right)}{\sum_{o' \in \mathcal{O}} \exp\left(\alpha_{o'}^{(i,j)}\right)}$, where $\mathcal{O}$ represents the search space consisting of all operators. Thus, we can get the importance of each operator in the format of probability. However, it is difficult to reach the optimal state for the objectives defined in Eq. (2) simultaneously, because achieving optimality in deep neural networks is still an open question, and the gradient w.r.t. $\boldsymbol{\alpha}$ is intractable (Xie et al., 2022). In practice, researchers often apply early stopping to tackle it, which leads to unexpected model collapse (Zela et al., 2020) and initialization sensitivity (Xie et al., 2022).

NAS for Graph Neural Networks: Many NAS methods have been proposed and adapted for GNNs, such as GraphNAS (Gao et al., 2020), Auto-GNN (Zhou et al., 2019), and SANE (Zhao et al., 2021b), and thus enable learning an adaptive GNN architecture with less human effort. Methods like Auto-GNN and GraphNAS adopt reinforcement learning (RL) for searching, and thus suffer from the expensive computational cost. Thanks to the weight-sharing policy, SANE (Zhao et al., 2021b) avoids heavy retraining processes in RL methods, which leads to superior performance in general. However, this type of work also faces issues from the weight-sharing differential framework, such as bias optimization and instability due to bi-level optimization. In this work, our proposed method NAC focuses on the NAS for GNNs, and we use GraphNAS and SANE as our main baselines.

Sparse Coding (Zhang et al., 2015) is a well-studied topic, and its goal is to learn an informative representation as a linear combination from a collection of basis or atom, which is called a *dictionary* collectively. The standard SC formulation is written as follows:

$$\underset{\mathcal{D}, \boldsymbol{\Gamma}}{\min}\, \mathcal{L}(\mathcal{V}, \mathcal{D}, \boldsymbol{\Gamma}) = \|\mathcal{V} - \mathcal{D}\boldsymbol{\Gamma}\|_F^2, \quad \text{s.t.} \quad \forall i, \|\boldsymbol{\Gamma}_{\cdot i}\|_0 \le \tau_0; \forall j, \|\mathcal{D}_{\cdot j}\|_2 = 1, \tag{3}$$

where $\boldsymbol{\Gamma}$ is the sparse coefficient vector, $\mathcal{D}$ is the dictionary, τ_0 is a value to control the sparsity. The first constraint is to encourage a sparse representation on $\boldsymbol{\Gamma}$ and the second constraint is to normalize

the atoms in the dictionary. NAS aims to find a small portion of operators from a large set of operators, making it a sparse coding problem in nature. We, therefore, reformulate the NAS-GNN problem as a sparse coding problem.

3 NETWORK ARCHITECTURE CODING (NAC) FOR NAS-GNN

To find the best-performing architecture, we introduce a novel NAS-GNN paradigm, Neural Architecture Coding (NAC), based on sparse Coding, which requires no update on the neural weights during training. Technical motivation for NAC stems from the observation that an untrained GNN performs well, and training it might not provide extra benefit. In the remainder of this section, we provide a theoretical analysis of why no-update is preferred (Section. 3.1) and how to address the NAS-GNN problem by leveraging untrained GNNs as a sparse coding problem (Section. 3.2).

3.1 ANALYSIS OF NO-UPDATE SCHEME IN GNNS

In the performance analysis of GNNs, the nonlinear activation function ϕ defined in Eq. (1) is often skipped. Following (Wu et al., 2019b), we simplify a GNN as $\boldsymbol{F} = \boldsymbol{A} \ldots \boldsymbol{A}(\boldsymbol{A}\boldsymbol{X}\boldsymbol{W}_1)\boldsymbol{W}_2 \ldots \boldsymbol{W}_L = \boldsymbol{A}^L \boldsymbol{X} \prod_{l=1}^{L} \boldsymbol{W}_l$, where $\boldsymbol{A}$ is the adjacency matrix, $\boldsymbol{W}_l$ is the neural weight at the l-th layer from a total number of layers, L. We then obtain the final output as $Out = \boldsymbol{F}\boldsymbol{W}_o$ by passing a linear layer $\boldsymbol{W}_o$. At the t-th iteration, we denote the GNN weight at the l-th layer as $\boldsymbol{W}_l(t)$ and the theoretical output layer weight as $\tilde{\boldsymbol{W}}_o(t)$. By initializing the network for all layers, i.e., $[\boldsymbol{W}_{1:L}, \boldsymbol{W}_o]$, we aim to train the network to get the optimal weights, denoted as $[\boldsymbol{W}_{1:L}^*, \boldsymbol{W}_o^*]$, where we assume the optimal weight can be obtained at $+\infty$-th iteration: $\boldsymbol{W}_l^* = \boldsymbol{W}_l(+\infty)$. We use gradient descent as the default optimizer in GNNs.

We now provide our first main theorem to investigate why an untrained GNN model can attain the same performance as the optimal one.

Theorem 3.1. Assume $\boldsymbol{W}_l(0)$ is randomly initialized for all $l \in [1, L]$, if $\prod_{l=1}^{L} \boldsymbol{W}_l(0)$ is full rank, there must exist a weight matrix for the output layer, i.e., $\tilde{\boldsymbol{W}}_o$, that makes the final output the same as the one from a well-trained network:

$$\boldsymbol{A}^L \boldsymbol{X} \prod_{l=1}^{L} \boldsymbol{W}_l^* \boldsymbol{W}_o^* = \boldsymbol{A}^L \boldsymbol{X} \prod_{l=1}^{L} \boldsymbol{W}_l(0)\tilde{\boldsymbol{W}}_o. \tag{4}$$

Proof. Because $\prod_{l=1}^{L} \boldsymbol{W}_l(0)$ is a full-rank matrix, $\prod_{l=1}^{L} \boldsymbol{W}_l(0)$ is invertible. We can define $\tilde{\boldsymbol{W}}_o$ by

$$\tilde{\boldsymbol{W}}_o \stackrel{\text{def}}{=\!=} (\prod_{l=1}^{L} \boldsymbol{W}_l(0))^{-1} \prod_{l=1}^{L} \boldsymbol{W}_l^* \boldsymbol{W}_o^*, \tag{5}$$

Hence, by multiplying $\prod_{l=1}^{L} \boldsymbol{W}_l(0)$ and $\boldsymbol{A}^L \boldsymbol{X}$ on both sides in Eq. (5), we can attain Eq. (4). □

This theorem implies that the output layer alone can ensure the optimality of the network even when all previous layers have no updates. Next, we show that training in the standard setting of GNNs is guaranteed to reach the desired weight of the output layer, i.e. $\tilde{\boldsymbol{W}}_o$, under mild conditions. We begin by providing the theorem from (Gunasekar et al., 2018).

Theorem 3.2 (From (Gunasekar et al., 2018))**.** Assume we have the following main conditions: 1) the loss function is either the exponential loss or the log-loss; 2) gradient descent is employed to seek the optimal solution; and 3) data is linearly separable. When defining a linear neural network as $\boldsymbol{Y} = \boldsymbol{X}\boldsymbol{W}_1\boldsymbol{W}_2.....\boldsymbol{W}_L = \boldsymbol{X} \prod_{l=1}^{L} \boldsymbol{W}_l = \boldsymbol{X}\boldsymbol{\beta}$, we always have the same optimal weight regardless of the number of layers when using gradient descent,

$$\boldsymbol{\beta}^* = \underset{\boldsymbol{\beta}}{\operatorname{argmin}} \|\boldsymbol{\beta}\|^2, \quad \text{s.t.} \quad \boldsymbol{X}\boldsymbol{\beta} \odot \boldsymbol{s} \geq \mathbf{1}, \tag{6}$$

where $\boldsymbol{s}$ is the ground-truth label vectors with elements as 1 or -1; $\mathbf{1}$ denotes a vector of all ones; $\odot$ denotes the element-wise product.

This theorem suggests that the optimal weights obtained by the gradient descent are the same regardless of how many layers are in the network, which is equivalent to finding a max-margin separating hyperplane. Following this, we prove that $\tilde{\boldsymbol{W}}_o$ can be obtained based on the above conditions:

Theorem 3.3. Assume a GNN model has either the exponential loss or the log-loss, the desired weight $\tilde{W}_o$ is secured when updating with gradient descent and initializing $\prod_{l=1}^{L} W_l(0)$ as an orthogonal matrix. Mathematically, we have $\hat{W}_o(+\infty) = \hat{W}_o^{\;*} = \tilde{W}_o$.

Proof. We first frame the simplified GNNs as $A^L X \prod_{l=1}^{L} W_l = (A^L X)(\prod_{l=1}^{L} W_l)$. According to Theorem. 3.2, we define the corresponding β as $\beta = \prod_{l=1}^{L} W_l$. When using the gradient descent to optimize W_l and W_o, we have the optimized β as $\beta^* = \prod_{l=1}^{L} W_l^* \cdot W_o^*$. The obtained β^* can be viewed as the max-margin hyperplane to separate data $A^L X$ according to Theorem. 3.2.

Omitting the output layer, we let the untrained GNN model as $A^L X \prod_{l=1}^{L} W_l(0) = A^L X O$ and assume $O = \prod_{l=1}^{L} W_l(0)$ is an orthogonal square matrix. Denoting a complete GNN model as $A^L X O W_o$, the optimized output weight, i.e. $\hat{W}_o^*$, becomes the max-margin separating hyperplane of $A^L X O$ because it is also trained by gradient descent. Here, we fix the $W_l(0)$ during training to maintain its orthogonality.

We know that the max-margin hyperplane of any data remains the same if and only if it takes orthogonal transformations, resulting in the following equivalence: $O \hat{W}_o^{\;*} = \beta^* = \prod_{l=1}^{L} W_l^* \cdot W_o^*$. Finally, we get $\hat{W}_o^{\;*} = O^{-1} \prod_{l=1}^{L} W_l^* W_o^* = (\prod_{l=1}^{L} W_l(0))^{-1} \prod_{l=1}^{L} W_l^* W_o^* = \tilde{W}_o$. $\qquad\square$

In summary, our proposed theorems prove that a GNN with randomly initialized weights can make the final output as good as a well-trained network, where one needs to update the overall network with gradient descent and initialize networks with orthogonal weights. Apart from the optimality, another immediate benefit of this no-update scheme is that the computational cost will be significantly reduced. This is of particular importance when the budget is limited, as the main computational cost of NAS comes from this update.

In this work, we treat the entire NAS supernet as a general GNN model where each layer is a mixture of multiple operators. The above theorems show that one can approximate the optimal output by using the network without training, where we only need to update the final linear layer of the supernet. This finding motivates us to learn architectures by taking advantage of randomly initialized networks.

We want to emphasize that real-world scenarios can break the optimal conditions, such as the high complexity of data and the early stopping of the training. Even though, our strategy still provides near-optimal performance, if not the best, in experiments.

3.2 ARCHITECTURE SEARCHING VIA SPARSE CODING

Now, we prove that an untrained GNN model can also yield optimal outputs under mild conditions. This optimality allows us to waive the effort to design complicated models for updating weights and makes us focus on architecture updates. At a high level, the ultimate goal of NAS is to assign the coefficients of unimportant operators as zeros and the important ones as non-zeros. Towards this, searching the optimal architecture is equivalent to finding the optimal sparse combination of GNN operators, i.e., α. Notably, one of the most successful algorithms for this purpose is sparse coding (Olshausen & Field, 1997), which has strong performance guarantees.

What matters most when we reformulate the NAS problem as a sparse coding problem over a dictionary defined on GNN operators? According to the research in sparse coding (Aharon et al., 2006; Tropp, 2004; Candes et al., 2006), its performance depends on the quality of the dictionary. In particular, the most desirable property is mutual coherence or orthogonality. High incoherence in the dictionary tends to avoid ambiguity in the solution and improve optimization stability, resulting in optimal or at least sub-optimal solutions. We prove a dictionary that is defined on deep neural networks has built-in orthogonality, as shown in the theorem below.

Theorem 3.4. Let the neural weights of each operator in a deep neural network be an atom and stack them column-wisely, we can guarantee the existence of an orthogonal dictionary.

Please see Appendix A.2 for more details. This theorem implies that the obtained weights are qualified to be a dictionary due to the built-in high dimensionality in deep neural networks. Taking

inspiration from this, we propose a new NAS paradigm called *neural architecture coding* as follows:

$$\min_{\boldsymbol{\alpha}} \quad \mathcal{L}_{CE}\left(\boldsymbol{y}, f(\mathbf{z})\right) + \|\mathbf{z} - \mathbf{h}^L\|_F^2 + \rho\|\boldsymbol{\alpha}\|_1,$$

$$\text{where} \begin{cases} \mathbf{h}_v^l = \phi\left[\boldsymbol{W}^l \cdot \bar{o}^l\left(\{\mathbf{h}_u^{l-1}, \forall u \in N(v)\}\right)\right] \\ \bar{o}^l(x) = \boldsymbol{o}^l\hat{\boldsymbol{\alpha}}_l = \sum_{k=1}^{K} \frac{\alpha_{lk}}{\|\boldsymbol{\alpha}_l\|_2}o^{lk}(x) \\ \boldsymbol{o}^l = [o^{l1}(x), o^{l2}(x), \ldots, o^{lK}(x)] \end{cases} \tag{7}$$

where ρ is the sparsity hyperparameter, $f(\cdot)$ is a linear function as the final output layer, e.g., MLP, $\mathbf{h}$ represents all nodes' embeddings, and $\mathcal{L}_{CE}$ defines the Cross-Entropy loss function. Here, we set the number of GNN operators to K and the number of hidden layers to L. o^{lk} and α_{lk} denote the neural weight of the k-th operator at the l-th layer and its corresponding coefficient, respectively. $\mathbf{h}_v^l$ denotes the embedding of the node v at the l-th layer, where its neighborhood aggregation process is performed as the weighted summation of the outputs from all operators as $\bar{o}^l(x)$.

Algorithm 1 The NAC algorithm

Require: The search space $\mathcal{A}$;
Ensure: The architecture $\boldsymbol{\alpha}$
 1: Randomly initializing $\boldsymbol{W}^l$, for $l = 1, \ldots, L$; set $\boldsymbol{\alpha} = \mathbf{1}$;
 2: **while** $t = 1, \ldots, T$ **do**
 3:     Performing the feature aggregation at each layer as $\bar{o}^l(x) = \boldsymbol{o}^l\hat{\boldsymbol{\alpha}}_l = \sum_{k=1}^{K} \frac{\alpha_{lk}}{\|\boldsymbol{\alpha}_l\|_2}o^{lk}(x)$;
 4:     Computing $\mathbf{h}_v^l = \phi\left[\boldsymbol{W}^l \cdot \bar{o}^l\left(\{\mathbf{h}_u^{l-1}, \forall u \in N(v)\}\right)\right]$;
 5:     Optimizing $\boldsymbol{\alpha}$ based on the objective function in Eq. (7) w.r.t. $\boldsymbol{\alpha}$ under the fixed dictionary $\boldsymbol{o}$;
 6:     Updating $\boldsymbol{W}_o$ based on the objective function in Eq. (7) w.r.t. $\boldsymbol{W}_o$ under fixed $\boldsymbol{\alpha}$;
 7: **end while**
 8: Obtain the final architecture $\{\boldsymbol{\alpha}^*\}$ from the trained $\boldsymbol{\alpha}$ via an argmax operation at each layer;

It is important to note that, rather than computing the optimal neural weight o^{lk} like previous NAS methods explicitly, we use randomly initialized weights instead and focus on optimizing the combination coefficient $\boldsymbol{\alpha}$, i.e. architecture parameters. The desired optimal embedding $\mathbf{z}$ is then used for downstream applications, such as node classification. In practice, we often let $\mathbf{z} = \mathbf{h}^L$ for computational convenience, which makes the loss of the second term to be zero.

The sparsity regularization $\|\boldsymbol{\alpha}\|_1$ allows us to rank the importance of the operator directly, alleviating inaccurate gradient estimation such as softmax (Garg et al., 2021). We want to emphasize that this regularization does not break the requirement of using gradient descent. Since the architecture, i.e., $\boldsymbol{\alpha}$, is fixed when updating the output layer weights, we can use gradient descent for updating as required, so the theorems in Section. 3.1 hold.

3.3 Implementation Details and Complexity Analysis

The overall algorithm is presented at Algorithm 1. Computing NAC consists of two major parts: the forward pass and the backward pass. Given the search space, the computation of the forward is then fixed and regarded as a constant. Therefore, the computational complexity mainly focuses on the backward pass in the NAC algorithm. In summary, the algorithmic complexity of NAC is $O(T * |\boldsymbol{\alpha}|)$, where $|\boldsymbol{\alpha}|$ is the size of $\boldsymbol{\alpha}$. Please refer to Appendix A.3 for more details about the implementation.

4 Experiments

We conduct experiments to address the following issues: **(1)** *How does NAC perform in comparison to the leading baselines?* **(2)** *How does the no-update scheme affect other methods?* **(3)** *Is NAC robust?* Sec. 4.2-Sec. 4.5 answer the above questions accordingly.

4.1 Experiment Setup

Datasets. We performed experiments on transductive learning for node classification (Zhao et al., 2021b). For this setting, we use four benchmark datasets: CiteSeer (Giles et al., 1998), Cora (Kipf & Welling, 2016), PubMed (Sen et al., 2008), and Computers (McAuley et al., 2015). Also, we follow the data partition setting (training/validation/testing) as in (Zhao et al., 2021b). For more details

about transductive learning task and introduction of each dataset, please refer to Appendix A.1 for more details.

Methods. Following (Zhao et al., 2021b), we compare our NAC with the following strong baselines: 1) Random Search (RS) (Bergstra & Bengio, 2012) and 2) Bayesian Optimization (BO) (Jones et al., 1998), 3) GraphNAS (Gao et al., 2020): a popular reinforcement learning-based (RL) method, 4) GraphNAS-WS (Zhao et al., 2021b): a variant of GraphNAS with weight sharing, and 5) SANE (Zhao et al., 2021b). Among all baselines, the first two are hyperparameter optimization (HPO) methods (Yu & Zhu, 2020). GraphNAS and GraphNAS-WS are two popular methods following the weight sharing paradigm while SANE is the most recent work on automated GNNs using the weight-sharing differential paradigm, which is the closest one to our work. We also evaluate NAC-updating, i.e., NAC with weight updates, to compare it with the proposed one with no-update scheme.

Search space. We select a list of node aggregators (i.e., operators) in GNNs to form the search space. More specifically, they include the following seven aggregators: multi-layer perceptrons (MLP), GCN (Kipf & Welling, 2017b), GAT (Velickovic et al., 2018), GIN (Xu et al., 2019), Geniepath (Liu et al., 2019b), Graphsage (Hamilton et al., 2017), and ChebNet (Defferrard et al., 2016). Note that MLP is a special aggregator with fixed frequency when viewing GNNs from a spectrum perspective (Balcilar et al., 2020). Besides, Graphsage and GAT contain different aggregation functions, i.e., maximum and LSTM. We apply all these variations as operators in the experiments. Note that we do not include the layer aggregators like skip-connection in our search space. The underlying rationale is that recent research (Zela et al., 2020; Chen & Hsieh, 2020; Liang et al., 2019) finds that NAS models converge to skip-connection much faster than other operators due to its parameter-free nature. This introduces biased searching and yields poor generalization.

We do not include layer-wise aggregators like JKNets (Xu et al., 2018) in the main experiment. As we show in Sec. 3.1, our theory is built upon the classical GNN framework, which equals matrix multiplication. JKNets cannot be represented in this framework, which contradicts our assumptions.

Evaluation Metrics. The proposed approaches aim to boost the ability to learn efficacious architecture for downstream tasks. The classification accuracy and the runtime (i.e., wall-clock time) are two widely used metrics in NAS research to measure the model performance and efficiency, respectively (Zhang et al., 2021a). The reported results are the average of the best results in 4 runs from different random seeds.

We set the runtime of NAC, SANE, and GraphNAS as the time they take to obtain the final architectures with 100 epochs[1]. The runtime of RS and Bayesian is fixed to the time of 100 times trial-and-error processes.

Table 1: Experimental results on the compared methods: our NAC attains superior performance in both accuracy (%) and efficiency (in minutes).

	CiteSeer		Cora		PubMed		Computers	
	Accuracy	Time	Accuracy	Time	Accuracy	Time	Accuracy	Time
RS	$70.12_{\pm 2.36}$	14.4	$71.26_{\pm 4.68}$	30.6	$86.75_{\pm 0.82}$	187.8	$77.84_{\pm 1.35}$	8.75
BO	$70.95_{\pm 1.62}$	18	$68.59_{\pm 6.66}$	31.2	$87.42_{\pm 0.68}$	189.6	$77.46_{\pm 2.02}$	17.65
GraphNAS	$68.69_{\pm 1.30}$	253.8	$71.26_{\pm 4.90}$	245.4	$86.07_{\pm 0.51}$	1363.8	$73.97_{\pm 1.79}$	86.37
GraphNAS-WS	$65.35_{\pm 5.13}$	80.4	$72.14_{\pm 2.59}$	161.4	$85.71_{\pm 1.05}$	965.4	$72.99_{\pm 3.44}$	42.47
SANE	$71.84_{\pm 1.33}$	4.2	$84.58_{\pm 0.53}$	10.2	$87.55_{\pm 0.78}$	107.4	$90.70_{\pm 0.89}$	0.72
NAC	$\mathbf{74.62}_{\pm 0.38}$	**1.2**	$\mathbf{87.41}_{\pm 0.92}$	**1.2**	$88.04_{\pm 1.06}$	**9.0**	$\mathbf{91.64}_{\pm 0.14}$	**0.23**
NAC-updating	$74.17_{\pm 1.18}$	4.2	$86.62_{\pm 1.14}$	3.6	$\mathbf{88.10}_{\pm 0.86}$	25.8	$90.89_{\pm 1.10}$	0.70

4.2 COMPARISON RESULTS

Results in Table 1 and Fig. 1 show that NAC attains superior performance than all baselines regarding both *accuracy* and *efficiency*. More specifically, we observe the following.

- In terms of model performance, our NAC beats all baselines and attains up to 2.83% improvement over the best baseline, i.e., SANE, while attaining up to 18.8% improvement over the Bayesian method, the best HPO method. Thanks to our non-updating scheme, it prompts the outputs near the optimal to make the selection of the best-performing architecture reliable, as opposed to biased optimization in others. We notice that in one case, NAC is slightly worse than NAC-updating,

---

[1]The running time for the Computers dataset is measured on a single GPU, which is different from all other three datasets.

about 0.06%. This case reminds us that the optimal condition can get compromised due to the high complexity of the data. Still, NAC holds for near-best performance, demonstrating its robustness. Empirical results corroborate our theories in Section. 3.1 that non-updating scheme is preferred. The underlying assumption of RL-based and BO-based methods is to obtain an accurate estimation of the distribution of the search space. However, these methods rely on random sampling to perform the estimation, thus have no guarantee of the search quality due to the high complexity in the search space. For instance, RL-based methods are sometimes even worse than RS-based methods, pure randomly sampled, implying the unreliability of such estimation under a limited budget. WS-based methods couple the architecture search and the weight training, so they struggle to train the network to be optimal and obtain a biased network due to oscillations between the two components.

- In terms of model efficiency, our NAC achieves superior performance, around $10\times$ faster than SANE and up to $200\times$ time faster than GraphNAS. Our non-updating scheme requires nearly no weight update, thus giving NAC an incomparable advantage in reducing the computation cost. All previous NAS methods need to update neural weights, for example, RL-based costs the most due to retraining the network from scratch at each time step, and WS-based costs the least by reusing neural weights.

4.3 NO-UPDATE SCHEME AT WORK

To further validate our no-update scheme, we evaluate its effect on other weight-sharing methods. Since SANE attains the best performance among all baselines, we test the no-update scheme on SANE as SANE*, i.e., SANE with fixed neural weights. Results in Table 3 show that SANE* outperforms the one with updates. This result implies that we can improve the performance of NAS-GNN methods by simply fixing the weights with random initialization. This yields a much lower computational cost in the training.

Table 2: Performance comparison between SANE, NAC$^+$ and NAC.

	CiteSeer Acc(%)	Cora Acc(%)	PubMed Acc(%)	Computers Acc(%)
SANE	$71.84_{\pm 1.33}$	$84.58_{\pm 0.53}$	$87.55_{\pm 0.78}$	$90.70_{\pm 0.89}$
NAC$^+$	$71.76_{\pm 2.08}$	$87.27_{\pm 1.20}$	$87.59_{\pm 0.22}$	$91.07_{\pm 0.71}$
NAC	$\mathbf{74.62}_{\pm 0.38}$	$\mathbf{87.41}_{\pm 0.92}$	$\mathbf{88.04}_{\pm 1.06}$	$\mathbf{91.64}_{\pm 0.14}$

Figure 2: Visualization of the sorted eigenvalues of weights of NAC with different initialization.

4.4 ABLATION STUDIES

Initialization: Recall that in Sec. 3.1, a prerequisite is the orthogonality on the neural weights matrix. This makes the initialization critical to the final performance. To investigate the effect of initialization, we try three types of initialization methods, including normal, uniform, and orthogonal. Table 4 shows that NAC with orthogonal initialization outperforms other two cases of initialization. The results again confirm our theory.

To get a better understanding of the reason, we visualize the eigenvalues of $\prod_{l=1}^{L} \boldsymbol{W}_l$ on different initialization cases in Figure 2. The results show that the eigenvalues of NACs with normal and uniform initialization decay accordingly. This makes the input feature tends to project to the subspace spanned by the top-ranked eigenvectors, which results in feature distortion and leads to performance degeneration. In contrast, when NAC with orthogonal initialization, the eigenvalues are distributed uniformly, which ensures the spanned space does not bias toward any particular eigenvectors.

In summary, NAC with orthogonal initialization attains the best performance and confirms our theory. In addition, results from non-orthogonal initializations are still better than other baselines, demonstrating the robustness of NAC.

The linear output layer: Recall that for a given linear output layer, there exists the optimal weight, i.e. $\tilde{W}_o$, to secure the optimal output according to Theorem. 3.1. Nevertheless, obtaining optimal weights in a deep learning algorithm is an open question due to its high dimensionality. Often, in practice, we train the network with early stopping, especially in NAS methods. Therefore, obtaining the optimal weights for the output layer is not possible. *Is training the output layer necessary?* This experiment attempts to answer this by comparing NAC with and without training the output layer.

Table 3: Comparison between SANE and SANE* (w/o. weight updates).

	CiteSeer Acc(%)	Cora Acc(%)	Pubmed Acc(%)	Computers Acc(%)
SANE	$71.84_{\pm 1.33}$	$84.58_{\pm 0.53}$	$87.55_{\pm 0.78}$	$90.70_{\pm 0.89}$
SANE*	$\mathbf{71.95}_{\pm 1.32}$	$\mathbf{85.46}_{\pm 0.76}$	$\mathbf{88.12}_{\pm 0.35}$	$\mathbf{90.86}_{\pm 0.80}$

Table 4: Comparison of NAC with different initializations.

	CiteSeer Acc(%)	Cora Acc(%)	PubMed Acc(%)	Computers Acc(%)
Kaiming Normal	$71.12_{\pm 2.45}$	$86.85_{\pm 0.78}$	$87.52_{\pm 0.72}$	$91.05_{\pm 0.80}$
Kaiming Uniform	$72.06_{\pm 2.24}$	$86.99_{\pm 1.03}$	$87.68_{\pm 0.97}$	$88.52_{\pm 3.01}$
Orthogonal	$\mathbf{74.62}_{\pm 0.38}$	$\mathbf{87.41}_{\pm 0.92}$	$\mathbf{88.04}_{\pm 1.06}$	$\mathbf{91.64}_{\pm 0.14}$

Figure 3: Convergence for SANE and NAC in terms of accuracy. NAC converges much faster than SNAE in only around 20 epochs.

Note that we fix all other layers with random weights. By default, NAC is the one without training any layers in the whole paper, including the output layer. On the contrary, NAC$^+$ is the one with training the output layer. Here, we set the number of epochs as 100. In Table. 2, we can find that the performance of NAC$^+$ is in the middle between SANE and NAC. On the one hand, training the linear layer may not be worthwhile because it is impossible to get the desired optimal weights. On the other hand, results with and without training the output layer are always better than SANE, suggesting the superiority of the no-update scheme in general. To further demonstrate this, we implement multiple experiments by training the last layer with different epochs, as shown in Appendix. A.4.3.

Sparsity effect: We also conduct experiments to test how sparsity affect the search quality of NAC. The hyperparameter ρ is to control the sparsity of the architecture parameter α. We test the effect by varying its value in a considerably large range, i.e., $[0.001, 10]$. The results show that the performance varies little w.r.t. ρ. This indicates that NAC is insensitive to the sparsity hyperparameter.

Random seeds: By default, researchers report the average or the best result from different random seeds, this often lead to poor reproducibility. We now present the effect of random seeds on this topic. In particular, we implement the experiment on multiple random seeds and observe a stable performance of NAC.

The experimental results show that NAC is robust to both sparse hyperparameter selection and random seeds. Please refer to Appendix A.4 for more details.

4.5 Analysis of Convergence

A notable benefit of the NAC framework is its guaranteed convergence from the sparse coding perspective. To verify this, Fig. 3 offers a convergence comparison between NAC and SANE from the Pubmed dataset by showing the accuracy on the retrained network acquired at each training epoch. NAC shows substantially faster convergence than SANE, which take around 20 and 80 epochs, respectively. Due to the BLO strategy, SANE suffers strong oscillation when optimizing two variables, i.e., the architecture and neural weights, which consumes more epochs to converge.

5 Conclusion

We present the first linear complexity NAS algorithm for GNNs, namely NAC. Our NAC is solved by sparse coding and holds no-update scheme for model weights in GNNs because GNNs embed the built-in model linearity and orthogonality for the model weights. Extensive experiments demonstrate that our NAC can achieve higher accuracy (up to 18.8%) and much faster convergence (up to $200\times$) than SOTA NAS-GNNs baselines.

Several promising directions can be considered. We can further explore more deep neural networks that satisfy the mild condition of our NAC to extent its usability. We can investigate more on the efficiency of different subgradient methods for solving the sparse coding objective. We also intend to investigate how to jointly learn the search space and architectural representation to further enhance the expressive ability of searched architectures.

REPRODUCIBILITY STATEMENT

The supplemental material includes the code for our experiments. An detailed description of the datasets used in the experiments is provided in Appendix A.1.

REFERENCES

M. Aharon, M. Elad, and A. Bruckstein. K-svd: An algorithm for designing overcomplete dictionaries for sparse representation. *IEEE Transactions on Signal Processing*, 54(11):4311–4322, 2006.

Muhammet Balcilar, Guillaume Renton, Pierre Héroux, Benoit Gaüzère, Sébastien Adam, and Paul Honeine. Analyzing the expressive power of graph neural networks in a spectral perspective. In *ICLR*, 2020.

Gabriel Bender, Pieter-Jan Kindermans, Barret Zoph, Vijay Vasudevan, and Quoc Le. Understanding and simplifying one-shot architecture search. In *ICML*, 2018.

James Bergstra and Yoshua Bengio. Random search for hyper-parameter optimization. *J. Mach. Learn. Res.*, 13:281–305, feb 2012. ISSN 1532-4435.

Kaifeng Bi, Changping Hu, Lingxi Xie, Xin Chen, Longhui Wei, and Qi Tian. Stabilizing darts with amended gradient estimation on architectural parameters. *CoRR*, abs/1910.11831, 2020a.

Kaifeng Bi, Lingxi Xie, Xin Chen, Longhui Wei, and Qi Tian. Gold-nas: Gradual, one-level, differentiable. *CoRR*, abs/2007.03331, 2020b.

Joan Bruna, Wojciech Zaremba, Arthur Szlam, and Yann LeCun. Spectral networks and locally connected networks on graphs. In *ICLR*, 2014.

E.J. Candes, J. Romberg, and T. Tao. Robust uncertainty principles: exact signal reconstruction from highly incomplete frequency information. *IEEE Transactions on Information Theory*, 52(2): 489–509, 2006.

Xiangning Chen and Cho-Jui Hsieh. Stabilizing differentiable architecture search via perturbation-based regularization. In *ICML*, 2020.

Michaël Defferrard, Xavier Bresson, and Pierre Vandergheynst. Convolutional neural networks on graphs with fast localized spectral filtering. In *NeurIPS*, 2016.

Matthias Fey and Jan E. Lenssen. Fast graph representation learning with PyTorch Geometric. In *ICLR Workshop*, 2019.

Hans Fischer. *A history of the central limit theorem: from classical to modern probability theory.* Springer, 2011.

Wenjiang J Fu. Penalized regressions: the bridge versus the lasso. *Journal of computational and graphical statistics*, 7(3):397–416, 1998.

Yang Gao, Hong Yang, Peng Zhang, Chuan Zhou, and Yue Hu. Graph neural architecture search. In *IJCAI*, 2020.

Shivam Garg, Samuele Tosatto, Yangchen Pan, Martha White, and A Rupam Mahmood. An alternate policy gradient estimator for softmax policies. *arXiv preprint arXiv:2112.11622*, 2021.

C. Lee Giles, Kurt D. Bollacker, and Steve Lawrence. Citeseer: An automatic citation indexing system. *Proceedings of the Third ACM Conference on Digital Libraries*, pp. 89–98, 1998.

Suriya Gunasekar, Jason D Lee, Daniel Soudry, and Nati Srebro. Implicit bias of gradient descent on linear convolutional networks. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Ronghao Guo, Chen Lin, Chuming Li, Keyu Tian, Ming Sun, Lu Sheng, and Junjie Yan. Powering one-shot topological NAS with stabilized share-parameter proxy. In *ECCV*, 2020a.

Zichao Guo, Xiangyu Zhang, Haoyuan Mu, Wen Heng, Zechun Liu, Yichen Wei, and Jian Sun. Single path one-shot neural architecture search with uniform sampling. In *ECCV*, 2020b.

William L. Hamilton. Graph representation learning. *Synthesis Lectures on Artificial Intelligence and Machine Learning*, 14(3):1–159, 2020.

William L. Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *NeurIPS*, 2017.

Donald R. Jones, Matthias Schonlau, and William J. Welch. Efficient global optimization of expensive black-box functions. *Journal of Global Optimization*, 13(4), 1998.

Rafal Jozefowicz, Wojciech Zaremba, and Ilya Sutskever. An empirical exploration of recurrent network architectures. In *ICML*, 2015.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *5th International Conference on Learning Representations, ICLR 2017, Toulon, France, April 24-26, 2017, Conference Track Proceedings*, 2017a.

Thomas N. Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2017b.

Hanwen Liang, Shifeng Zhang, Jiacheng Sun, Xingqiu He, Weiran Huang, Kechen Zhuang, and Zhenguo Li. DARTS+: improved differentiable architecture search with early stopping. *CoRR*, abs/1909.06035, 2019.

Hanxiao Liu, Karen Simonyan, and Yiming Yang. DARTS: differentiable architecture search. In *ICLR*, 2019a.

Ziqi Liu, Chaochao Chen, Longfei Li, Jun Zhou, Xiaolong Li, Le Song, and Yuan Qi. Geniepath: Graph neural networks with adaptive receptive paths. In *AAAI*, 2019b.

Renqian Luo, Fei Tian, Tao Qin, Enhong Chen, and Tie-Yan Liu. Neural architecture optimization. In *NeurIPS*, 2018.

Julian McAuley, Christopher Targett, Qinfeng Shi, and Anton Van Den Hengel. Image-based recommendations on styles and substitutes. In *Proceedings of the 38th international ACM SIGIR conference on research and development in information retrieval*, pp. 43–52, 2015.

Bruno A. Olshausen and David J. Field. Sparse coding with an overcomplete basis set: A strategy employed by v1? *Vision Research*, 37(23):3311–3325, 1997. ISSN 0042-6989.

Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. *Advances in neural information processing systems*, 32, 2019.

J Ranstam and JA Cook. Lasso regression. *Journal of British Surgery*, 105(10):1348–1348, 2018.

Mark Schmidt, Glenn Fung, and Romer Rosales. Optimization methods for l1-regularization. *University of British Columbia, Technical Report TR-2009-19*, 2009.

Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. Collective classification in network data. *AI Magazine*, 29(3):93, Sep. 2008. doi: 10.1609/aimag. v29i3.2157.

Shirish Krishnaj Shevade and S Sathiya Keerthi. A simple and efficient algorithm for gene selection using sparse logistic regression. *Bioinformatics*, 19(17):2246–2253, 2003.

Xiu Su, Shan You, Mingkai Zheng, Fei Wang, Chen Qian, Changshui Zhang, and Chang Xu. K-shot NAS: learnable weight-sharing for NAS with k-shot supernets. In *ICML*, 2021.

D. ter Haar. Mathematical foundations of statistical mechanics. a. i. khinchin. *Science*, 110(2865): 570–570, 1949.

J.A. Tropp. Greed is good: algorithmic results for sparse approximation. *IEEE Transactions on Information Theory*, 50(10):2231–2242, 2004.

Petar Velickovic, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Liò, and Yoshua Bengio. Graph attention networks. In *ICLR*, 2018.

Bichen Wu, Xiaoliang Dai, Peizhao Zhang, Yanghan Wang, Fei Sun, Yiming Wu, Yuandong Tian, Peter Vajda, Yangqing Jia, and Kurt Keutzer. Fbnet: Hardware-aware efficient convnet design via differentiable neural architecture search. In *CVPR*, 2019a.

Felix Wu, Amauri Souza, Tianyi Zhang, Christopher Fifty, Tao Yu, and Kilian Weinberger. Simplifying graph convolutional networks. In *International conference on machine learning*, pp. 6861–6871. PMLR, 2019b.

Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and Philip S. Yu. A comprehensive survey on graph neural networks. *IEEE Transactions on Neural Networks and Learning Systems*, 32(1):4–24, Jan 2021. ISSN 2162-2388.

Lingxi Xie and Alan L. Yuille. Genetic CNN. In *ICCV*, 2017.

Lingxi Xie, Xin Chen, Kaifeng Bi, Longhui Wei, Yuhui Xu, Lanfei Wang, Zhengsu Chen, An Xiao, Jianlong Chang, Xiaopeng Zhang, and Qi Tian. Weight-sharing neural architecture search: A battle to shrink the optimization gap. *ACM Comput. Surv.*, 54(9):183:1–183:37, 2022.

Keyulu Xu, Chengtao Li, Yonglong Tian, Tomohiro Sonobe, Ken-ichi Kawarabayashi, and Stefanie Jegelka. Representation learning on graphs with jumping knowledge networks. In Jennifer Dy and Andreas Krause (eds.), *Proceedings of the 35th International Conference on Machine Learning*, volume 80 of *Proceedings of Machine Learning Research*, pp. 5453–5462. PMLR, 10–15 Jul 2018.

Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? In *ICML*, 2019.

Jiaxuan You, Zhitao Ying, and Jure Leskovec. Design space for graph neural networks. *Advances in Neural Information Processing Systems*, 33, 2020.

Tong Yu and Hong Zhu. Hyper-parameter optimization: A review of algorithms and applications. *CoRR*, abs/2003.05689, 2020.

Arber Zela, Thomas Elsken, Tonmoy Saikia, Yassine Marrakchi, Thomas Brox, and Frank Hutter. Understanding and robustifying differentiable architecture search. In *ICLR*, 2020.

Xinbang Zhang, Zehao Huang, Naiyan Wang, Shiming Xiang, and Chunhong Pan. You only search once: Single shot neural architecture search via direct sparse optimization. *IEEE Trans. Pattern Anal. Mach. Intell.*, 43(9):2891–2904, 2021a.

Zheng Zhang, Yong Xu, Jian Yang, Xuelong Li, and David Zhang. A survey of sparse representation: algorithms and applications. *IEEE access*, 3:490–530, 2015.

Ziwei Zhang, Xin Wang, and Wenwu Zhu. Automated machine learning on graphs: A survey. In *IJCAI*, 2021b.

Huan Zhao, Lanning Wei, quanming yao, and Zhiqiang He. Efficient graph neural architecture search, 2021a. URL https://openreview.net/forum?id=IjIzIOkK2D6.

Huan Zhao, Quanming Yao, and Weiwei Tu. Search to aggregate neighborhood for graph neural network. In *ICDE*, 2021b.

Kaixiong Zhou, Qingquan Song, Xiao Huang, and Xia Hu. Auto-gnn: Neural architecture search of graph neural networks. *CoRR*, abs/1909.03184, 2019.

Barret Zoph and Quoc V. Le. Neural architecture search with reinforcement learning. In *ICLR*, 2017.