Constrained Predictive Coding as a Biologically Plausible Model of the Cortical Hierarchy

Abstract

Predictive coding (PC) has emerged as an influential normative model of neural computation, with numerous extensions and applications. As such, much effort has been put into mapping PC faithfully onto the cortex, but there are issues that remain unresolved or controversial. In particular, current implementations often involve separate value and error neurons and require symmetric forward and backward weights across different brain regions. These features have not been experimentally confirmed. In this work, we show that the PC framework in the linear regime can be modified to map faithfully onto the cortical hierarchy in a manner compatible with empirical observations. By employing a disentangling-inspired constraint on hidden-layer neural activities, we derive an upper bound for the PC objective. Optimization of this upper bound leads to an algorithm that shows the same performance as the original objective and maps onto a biologically plausible network. The units of this network can be interpreted as multi-compartmental neurons with non-Hebbian learning rules, with a remarkable resemblance to recent experimental findings. There exist prior models which also capture these features, but they are phenomenological, while our work is a normative derivation. Notably, the network we derive does not involve one-to-one connectivity or signal multiplexing, which the phenomenological models required, indicating that these features are not necessary for learning in the cortex. The normative nature of our algorithm in the simplified linear case allows us to prove interesting properties of the framework and analytically understand the computational role of our network's components. The parameters of our network have natural interpretations as physiological quantities in a multi-compartmental model of pyramidal neurons, providing a concrete link between PC and experimental measurements carried out in the cortex.

1   Introduction

Over the past decades, predictive coding (PC), a normative framework for learning representations that maximize predictive power, has played an important role in computational neuroscience [1, 2]. Initially proposed as an unsupervised learning paradigm in the retina [3], it has since been expanded to the supervised regime [4] with arbitrary graph topologies [5, 6]. The PC framework has been analyzed in many contexts [7, 8] and has found many applications, from clinical neuroscience [9, 10] to memory storage and retrieval [11]. We refer the reader to [12, 13] for recent reviews.

Predictive coding is viewed as a possible theory of cortical computation, and many parallels have been drawn with the known neurophysiology of cortex [12]. While the initial works proposed a

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: Schematic architecture of the predictive coding network (PCN) and our covariance-constrained network (BioCCPC). (a) PCN from [4], figure adapted from [13]. The intra-layer connectivity is to be one-to-one, while the inter-layer connectivity is symmetric. (b) Our BioCCPC network. There is no requirement for symmetric weights across layers, and the connectivity within layers can be diffuse.

biologically plausible network [1, 2], the connection with cortex was more closely examined in [14], where the PC module was mapped onto a cortical-column microcircuit. However, there are aspects of this mapping that have proved controversial. Among these are the requirement of multiple redundant cortical operations, the symmetric connectivity pattern, the one-to-one connectivity of value and error neurons, and also the requirement that feedback connections be inhibitory [12, 15, 16], as sketched in Fig. 1a . The presence of separate error and value neurons has itself been called into question [15].

The PC-based neural circuits also do not account for more recent experimental findings highlighting the details of computation in the cortex [17–26]. For example, the learning dynamics of multi-compartmental pyramidal neurons has been closely investigated. In particular, it was observed that the plasticity of the synapses of the basal compartment is driven by the activity in the apical tuft of the neuron by so-called calcium plateau potentials [19, 20, 24], leading to non-Hebbian learning rules [25]. These experiments have motivated the development of several models of microcircuits with multi-compartmental neurons [27–33]. In a number of cases, it has been shown that these models can replicate learning similar to the backpropagation algorithm under specific assumptions [30, 34, 35]. However, because of their rather phenomenological nature, detailed analysis of these models is in many cases challenging and one must resort to numerical simulations, rendering the task of understanding the role of various neurophysiological quantities difficult. To this date, a normative framework (PC or otherwise) that can explain these experimental findings is still lacking.

In this work, we show how the PC framework can be made compatible with the aforementioned experimental observations. Inspired by prior work which explored the effects of finding decorrelated representations [36–41], we add a decorrelating inequality constraint to the covariance of the latent representations of PC. Using this constraint, we derive an upper bound for the PC objective. By working in the linear regime, we can prove interesting properties of our algorithm. We show that the learning algorithm derived from this upper bound does not suffer from the issues of prior implementations and naturally maps onto the hierarchical structure of the cortical pyramidal neurons.

Contributions

- By imposing a decorrelation-inspired inequality constraint on the latent space, we find an analytic upper bound to the PC objective.
- We introduce BioCCPC, a novel biologically plausible algorithm derived from this upper bound and show that it closely matches the known physiology of the cortical hierarchy.
- We interpret the different parameters of the algorithm in terms of the conductances and leaks of the separate compartments of the pyramidal neuron. We find that the neural compartmental conductances encode the varainces of the PC framework, and the somatic leak maps onto a thresholding mechanism of the associated eigenvalue problem.

2 Related work and review of predictive coding

The backpropagation algorithm [34, 42] is the predominant tool in the training of deep neural networks but is generally not considered biologically plausible [43]. Over the years, many authors have explored biologically plausible approximations or alternatives to backpropagation [30, 31, 44–58]

(for a more complete review see [59]). These approaches generally fall into two categories. First are normative approaches, such as Predictive Coding [1–3], Target Propagation and variations [44,45,47], Equilibrium Propagation [49,53] and others [51,54–56], where one starts from a mathematically motivated optimization objective. These methods, by virtue of their normative derivation, have a firm grounding in theory; however, they do not fully conform to the experimental observations in the brain (see below and Sec. 4). The second approach is driven by biology, with network structures and learning rules inspired by experimental findings [28,30,31,48,60]. While these works mostly conform to the experimentally observed findings, they are more challenging to analyze because of their conjectured phenomenological nature.

The goal of the present paper is *not* to propose yet another biologically plausible alternative to backpropagation. It is rather to demonstrate that the normative framework of predictive coding, when combined with a constraint, can indeed closely match experimental observations. For this reason, in this work, we focus on comparing our method with previous implementations of predictive coding and do not concern ourselves with other biologically plausible alternatives to backpropagation. The relationship between the PC framework and backpropagation was explored in [4,61–64]. The advantages of PC over backpropagation were highlighted in [13].

Notation. Bold upper case $\mathbf{M}$ and lower case variables $\mathbf{v}$ denote matrices and vectors, respectively. By upper case letter $\mathbf{X}, \mathbf{Y}, \mathbf{Z}$, we denote data matrices in $\mathbb{R}^{d \times T}$, where d and T are the dimensions of the relevant variable and the number of samples. Lower case $\mathbf{x}, \mathbf{y}, \mathbf{z}$, denote the relevant quantities of a single sample, and $\mathbf{x}_t, \mathbf{y}_t, \mathbf{z}_t$, denote the t^{th} sample. $\|\mathbf{M}\|_F^2$ denotes the Frobenius norm of $\mathbf{M}$.

2.1 Review of predictive coding

Probabilistic model. In this section, we review the supervised predictive coding algorithm [4]. The derivation starts from a probabilistic model for supervised learning, which parallels the architecture of an artificial neural network (ANN) with $n + 1$ layers. In this model, the neurons of each layer are random variables $\mathbf{z}^{(l)}$ (denoting the vector of activations in the l^{th} layer) with layers 0 and n, respectively, denoting the input and output layers of the network. We assume that the joint probability of the latent variables factorizes in a Markovian structure

$$p(\mathbf{z}^{(0)}, \mathbf{z}^{(1)}, \cdots, \mathbf{z}^{(n)}) = p(\mathbf{z}^{(n)}|\mathbf{z}^{(n-1)}) \times p(\mathbf{z}^{(n-1)}|\mathbf{z}^{(n-2)}) \times \cdots \times p(\mathbf{z}^{(0)})$$

with the relationship between the random variables of adjacent layers given by:

$$p(\mathbf{z}^{(l)}|\mathbf{z}^{(l-1)}) = \mathcal{N}(\mathbf{z}^{(l)}; \boldsymbol{\mu}^{(l)}, \boldsymbol{\Sigma}^{(l)}), \qquad \text{with} \quad \boldsymbol{\mu}^{(l)} = \mathbf{W}^{(l-1)}f(\mathbf{z}^{(l-1)}), \quad \boldsymbol{\Sigma}^{(l)} = \sigma^{(l)2}\mathbf{I}. \quad (1)$$

The mean of the probability density on layer l mirrors the activity of the analogous ANN given by $\boldsymbol{\mu}^{(l)} = \mathbf{W}^{(l-1)}f(\mathbf{z}^{(l-1)})$, where $\mathbf{W}^{(l-1)}$ are the weights connecting layers $l-1$ and l. The objective function is then given by the negative log-likelihood of the joint distribution function:

$$L = -\sum_t \log p(\mathbf{z}_t^{(0)}, \dots, \mathbf{z}_t^{(n)}) = \frac{1}{2} \sum_l \frac{\left\|\mathbf{Z}^{(l)} - \mathbf{W}^{(l-1)}f(\mathbf{Z}^{(l-1)})\right\|_F^2}{\sigma^{(l)2}} + \text{const}, \qquad (2)$$

where we have switched to the data matrix notation for brevity and assumed the variances $\sigma^{(l)2}$ are fixed hyperparameters. In the following, we refer to L, Eq. (2), without the constant term.

Learning. Learning takes place in two steps. First, the values of the random variables are determined by finding the most probable configuration of the joint distribution function when both the input and output layers are conditioned on the given input and output ($\mathbf{z}^{(0)} = \mathbf{x}$ and $\mathbf{z}^{(n)} = \mathbf{y}$):

$$\mathbf{z}^{*(1)}, \dots, \mathbf{z}^{*(n-1)} = \underset{\mathbf{z}^{(1)}, \dots, \mathbf{z}^{(n-1)}}{\arg \min} L(\mathbf{z}^{(0)} = \mathbf{x}, \mathbf{z}^{(n)} = \mathbf{y}). \qquad (3)$$

The solution to this minimization problem can be found via gradient descent, which we evaluate component-wise for clarity as:

$$\dot{z}_j^{(l)} = -\eta \partial_{z_j} L = \eta\left(-\varepsilon_j^{(l)} + \sum_i \varepsilon_i^{(l+1)} W_{ij}^{(l)} f'(z_j^{(l)})\right), \quad \text{with} \quad \varepsilon_i^{(l)} = \frac{z_i^{(l)} - \mu_i^{(l)}}{\sigma^{(l)2}}, \qquad (4)$$

where η is the gradient descent step size. The second step is then to minimize the objective with respect to the weights while keeping the previously obtained neuron values fixed. This corresponds to optimizing the value of the loss at the MAP estimate and can also be carried out by gradient descent, leading to:

$$\delta W_{ij}^{(l)} \propto -\frac{\partial L}{\partial W_{ij}^{(l)}} = \varepsilon_i^{*(l+1)} f\big(z_j^{*(l)}\big), \tag{5}$$

where $\cdot^*$ denotes equilibrium values of the latent variable dynamics obtained in the first step (Eq. (3)). This algorithm can be implemented by a biologically plausible network as described in [4]; see Figure 1a. However, as discussed in Section 1, its mapping onto the cortex has proved controversial. For further details regarding these steps see [4].

3 A constrained predictive coding framework

In this section, we introduce and discuss our novel, covariance-constrained predictive coding (CCPC) model within the supervised PC paradigm of [4]. Our model also straightforwardly extends to the unsupervised learning paradigm discussed in [1,2]. For simplicity we work in the linear regime ($f(x) = x$) which allows us to prove different properties of our framework.

3.1 Derivation of upper bound objective

Reduction to a sum of objectives. We start by reducing the optimization problem, Eq. (2), into a set of overlapping sub-problems, which will allow us to break the symmetry between feedforward and feedback weights. To do so, we first introduce a copy of the terms containing the weights $\mathbf{W}^{(1)}$ to $\mathbf{W}^{(n-2)}$, denoted by $\mathbf{W}_a^{(l)}$ and $\mathbf{W}_b^{(l)}$ respectively, as

$$\min_{\mathbf{Z},\mathbf{W}} L = \min_{\mathbf{Z},\mathbf{W}} \frac{1}{2} \sum_{l=1}^{n} \frac{\left\|\mathbf{Z}^{(l)} - \mathbf{W}^{(l-1)}\mathbf{Z}^{(l-1)}\right\|_F^2}{\sigma^{(l)2}} = \min_{\mathbf{Z},\mathbf{W}_a,\mathbf{W}_b} \hat{L}$$

$$\hat{L} = \min_{\mathbf{Z},\mathbf{W}_a,\mathbf{W}_b} \frac{1}{2} \frac{\left\|\mathbf{Z}^{(1)} - \mathbf{W}_b^{(0)}\mathbf{Z}^{(0)}\right\|_F^2}{\sigma^{(1)2}} + \frac{1}{2} \frac{\left\|\mathbf{Z}^{(n)} - \mathbf{W}_a^{(n-1)}\mathbf{Z}^{(n-1)}\right\|_F^2}{\sigma^{(n)2}} \tag{6}$$

$$+ \frac{1}{4} \sum_{l=2}^{n-1} \left[\frac{\left\|\mathbf{Z}^{(l)} - \mathbf{W}_b^{(l-1)}\mathbf{Z}^{(l-1)})\right\|_F^2}{\sigma^{(l)2}} + \frac{\left\|\mathbf{Z}^{(l)} - \mathbf{W}_a^{(l-1)}\mathbf{Z}^{(l-1)})\right\|_F^2}{\sigma^{(l)2}} \right].$$

For consistency, we rename $\mathbf{W}^{(0)}, \mathbf{W}^{(n-1)}$ to $\mathbf{W}_b^{(0)}, \mathbf{W}_a^{(n-1)}$, respectively. Introducing these copies does not change the optimization[1] but will help us avoid weight sharing in the steps below. We now pair the terms two by two as

$$\min_{\mathbf{Z},\mathbf{W}_a,\mathbf{W}_b} \hat{L} = \frac{1}{2} \sum_{l=1}^{n-1} \left[g_b^{(l)} \left\|\mathbf{Z}^{(l)} - \mathbf{W}_b^{(l-1)}\mathbf{Z}^{(l-1)}\right\|_F^2 + g_a^{(l)} \left\|\mathbf{Z}^{(l+1)} - \mathbf{W}_a^{(l)}\mathbf{Z}^{(l)}\right\|_F^2 \right], \tag{7}$$

with $g_a^{(n-1)} = 1/\sigma^{(n)2}$, $g_b^{(1)} = 1/\sigma^{(1)2}$, and $g_a^{(l-1)} = g_b^{(l)} = 1/(2\sigma^{(l)2})$ for $l = 2, \ldots, n-1$.

Weight sharing occurs here from terms like $\mathbf{z}^{(l+1)\top}\mathbf{W}\mathbf{z}^{(l)}$, obtained from expanding the squared norms in Eq. (7). Indeed, the gradient descent dynamics with respect to $\mathbf{z}^{(l+1)}$ (resp. $\mathbf{z}^{(l)}$) leads to terms of the form $\mathbf{W}\mathbf{z}^{(l)}$ in $\dot{\mathbf{z}}^{(l+1)}$ (resp. $\mathbf{W}^\top\mathbf{z}^{(l+1)}$ in $\dot{\mathbf{z}}^{(l)}$), which use the same weights $\mathbf{W}$. Thanks to the doubling of the weights, we can avoid this problem by optimizing each term in the sum in

---

[1]This can be directly verified by finding the optima for $\mathbf{W}$'s before and after the change. We have $\mathbf{W}^{(l)} = \mathbf{W}_a^{(l)} = \mathbf{W}_b^{(l)} = \mathbf{Z}^{(l+1)}\mathbf{Z}^{(l)\top}(\mathbf{Z}^{(l+1)}\mathbf{Z}^{(l)\top})^{-1}$. Plugging these back into Eq. (6) we see that the equality holds. However, in the next step, since we treat $\mathbf{W}_a$'s and $\mathbf{W}_b$'s differently, $\mathbf{W}_a = \mathbf{W}_B$ will no longer hold.

Eq. (7) separately. In other words,

$$\min_{\mathbf{Z},\mathbf{W}_a,\mathbf{W}_b}\hat{L} \leq \sum_{l=1}^{n-1}\min_{\mathbf{Z}^{(l)},\mathbf{W}_a^{(l)},\mathbf{W}_b^{(l-1)}}\hat{L}^{(l)}, \tag{8}$$

$$\text{where } \hat{L}^{(l)} \equiv \frac{1}{2}\sum_{l=0}^{n}\left[g_b^{(l)}\left\|\mathbf{Z}^{(l)}-\mathbf{W}_b^{(l-1)}\mathbf{Z}^{(l-1)}\right\|_F^2 + g_a^{(l)}\left\|\mathbf{Z}^{(l+1)}-\mathbf{W}_a^{(l)}\mathbf{Z}^{(l)}\right\|_F^2\right].$$

This inequality holds simply because we are no longer finding the minimum of the full objective $\hat{L}$. We are instead finding the minimum of each component separately, and then evaluating $\sum_l \hat{L}^{(l)} = \hat{L}$. This splits the $(n+1)$-layer optimization problem into a set of 3-layer optimizations, in each of which only the middle layer is being optimized. Note, however, that these are overlapping, so the different optimization problems need to be solved self-consistently. We make this precise in the supplementary materials section and show that it provides an upper bound for our objective L (SM Sec. A). Separating the objective function in this manner eliminates the weight sharing problem for $\mathbf{W}_b$, but the problem remains for $\mathbf{W}_a$. We address this problem in the following.

Whitening constraint. The idea of decorrelating internal representation has been widely used for unsupervised tasks, often motivated by neuroscience [36–38]. In the case of deep learning, the main motivations were improved convergence speed and generalization [39–41]. Decorrelation has also been used to circumvent the weight transport problem [55]. Inspired by these observations, we introduce the constraint $\frac{1}{T}\mathbf{Z}^{(l)}\mathbf{Z}^{(l)\top} \preceq \mathbf{I}$, imposing an upper bound on the eigenvalues of the covariance matrix:

$$\min_{\substack{\mathbf{Z}^{(l)},\mathbf{W}_a^{(l)},\mathbf{W}_b^{(l)}}}\hat{L}^{(l)} \leq \min_{\substack{\mathbf{Z}^{(l)},\mathbf{W}_a^{(l)},\mathbf{W}_b^{(l)}\\\mathbf{Z}^{(l)}\mathbf{Z}^{(l)\top}\preceq T\times\mathbf{I}}}\hat{L}^{(l)}$$

$$\leq \min_{\substack{\mathbf{Z}^{(l)},\mathbf{W}_a^{(l)},\mathbf{W}_b^{(l)}\\\mathbf{Z}^{(l)}\mathbf{Z}^{(l)\top}\preceq T\times\mathbf{I}}}\frac{1}{2}\left[g_b^{(l)}\left\|\mathbf{Z}^{(l)}-\mathbf{W}_b^{(l-1)}\mathbf{Z}^{(l-1)}\right\|_F^2 + c^{(l)}\left\|\mathbf{Z}^{(l)}\right\|_F^2\right.$$

$$\left. + g_a^{(l)}\,\mathrm{Tr}\left(-2\mathbf{Z}^{(l+1)\top}\mathbf{W}_a^{(l)}\mathbf{Z}^{(l)}\right) + g_a^{(l)}T\,\mathbf{W}_a^{(l)\top}\mathbf{W}_a^{(l)}\right]$$

The first inequality results from the fact that the parameters of the new optimization problem are a subset of the parameters of the original optimization problem. In the second inequality we have expanded the second term of $\hat{L}^{(l)}$ and used the constraint $\frac{1}{T}\mathbf{Z}^{(l)}\mathbf{Z}^{(l)\top} \preceq \mathbf{I}$ to replace $\mathbf{Z}^{(l)}\mathbf{Z}^{(l)\top}$ with T, making the term larger, resulting again in an upper bound.

The inequality can be implemented by using a positive-definite Lagrange multiplier $\mathbf{Q}^{(l)\top}\mathbf{Q}^{(l)}$:

$$\min_{\mathbf{Z}^{(l)},\mathbf{W}_a^{(l)},\mathbf{W}_b^{(l-1)}}\max_{\mathbf{Q}^{(l)}}\frac{1}{2}\left[g_b^{(l)}\left\|\mathbf{Z}^{(l)}-\mathbf{W}_b^{(l-1)}\mathbf{Z}^{(l-1)}\right\|_F^2 + c^{(l)}\left\|\mathbf{Z}^{(l)}\right\|_F^2\right.$$

$$+ g_a^{(l)}\,\mathrm{Tr}\left(-2\mathbf{Z}^{(l+1)\top}\mathbf{W}_a^{(l)}\mathbf{Z}^{(l)}\right) + g_a^{(l)}T\,\mathbf{W}_a^{(l)\top}\mathbf{W}_a^{(l)}$$

$$\left. + \mathrm{Tr}\,\mathbf{Q}^{(l)\top}\mathbf{Q}^{(l)}\left(\mathbf{Z}^{(l)}\mathbf{Z}^{(l)\top}-T\mathbf{I}\right) + \text{const}\right], \tag{9}$$

where we have added an additional quadratic term in $\mathbf{Z}$ as a regularizer. This can also be interpreted as an extra term in the prior of the latent space. Equation (9) is the final form of the objective which we then optimize using gradient descent/ascent.

3.2 Neural dynamics and learning rules.

Similar to the PCN of [4], the dynamics of our network during learning proceeds in two steps. First the neural dynamics is derived by taking gradient steps of $\hat{L}^{(l)}$ from Eq. (9) with respect to $\mathbf{z}^{(l)}$:

$$\dot{\mathbf{z}}^{(l)} = g_b^{(l)}\mathbf{W}_b^{(l-1)}\mathbf{z}^{(l-1)} + g_a^{(l)}\mathbf{W}_a^{(l)\top}\mathbf{z}^{(l+1)} - \left(g_b^{(l)}+c^{(l)}\right)\mathbf{z}^{(l)} - g_a^{(l)}\mathbf{Q}^{(l)\top}\mathbf{n}^{(l)}, \tag{10}$$

162   where we have defined the variables $\mathbf{n}^{(l)} = (1/g_a^{(l)})\mathbf{Q}^{(l)}\mathbf{z}^{(l)}$ for each layer of the network.

163   The weight updates are derived via stochastic gradient descent of the loss given in Eq. (9) after the
164   neural dynamics have reached equilibrium. These are given by

$$\delta\mathbf{W}_b^{(l)} \propto \left[g_a^{(l+1)}\left(\mathbf{W}_a^{(l+1)\top}\mathbf{z}^{(l+2)} - \mathbf{Q}^{(l+1)\top}\mathbf{n}^{(l+1)}\right) - c^{(l+1)}\mathbf{z}^{(l+1)}\right]\mathbf{z}^{(l)\top}, \tag{11a}$$

$$\delta\mathbf{W}_a^{(l)} \propto \mathbf{z}^{(l+1)}\mathbf{z}^{(l)\top} - \mathbf{W}_a^{(l)}, \tag{11b}$$

$$\delta\mathbf{Q}^{(l)} \propto \mathbf{n}^{(l)}\mathbf{z}^{(l)\top} - \mathbf{Q}^{(l)}. \tag{11c}$$

165   We used the neural dynamics equilibrium equation for $\mathbf{z}^{(l)}$ to simplify the weight update for $\mathbf{W}_b^{(l)}$.
166   This yields our online algorithm (Alg. 1 in SM Sec. E), with the architecture shown in Fig. 1b. The
167   algorithm can be implemented in a biologically plausible neural network as in Fig. 2; see Sec. 4.

4   Biological implementation and comparison with experimental observations

169   In this section, we introduce a biologically plausible neural circuit that implements the CCPC
170   algorithm, denoted by BioCCPC. We also demonstrate that the details of this circuit resemble the
171   neurophysiological properties of pyramidal cells in the neocortex and the hippocampus.

172   **Neural architecture.**   The algorithm for BioCCPC (Alg. 1) summarized by the neural dynamics
173   from Eq. (10) and weight update rules from Eqs. (11) can be implemented by a neural circuit with
174   schematic shown in Fig. 2.

175   The activity of the $n-1$ hidden layers, $\{\mathbf{z}^{(l)}\}_{l=1}^{n-1}$, is encoded as the outputs of $n-1$ sets of neurons,
176   representing pyramidal neurons of different cortical regions. The matrices $\mathbf{W}_a^{(l)}$ and $\mathbf{W}_b^{(l)}$ are
177   encoded as the weights of synapses between the pyramidal neurons of adjacent layers. Explicitly,
178   the matrix $\mathbf{W}_a^{(l)}$ (resp. $\mathbf{W}_b^{(l-1)}$) is the efficacy of the synapse connecting $\mathbf{z}^{(l+1)}$ (resp. $\mathbf{z}^{(l-1)}$) to
179   the pyramidal neurons $\mathbf{z}^{(l)}$. Because of the disjoint nature of these two inputs, we model these
180   as synapsing respectively onto the distal (apical tuft) and proximal (mostly basal) dendrites of the
181   pyramidal neurons, respectively; see Fig. 2. This is reminiscent of cortical pyramidal neurons, which
182   also have two integration sites, the proximal compartment comprised of the basal and proximal apical
183   dendrites providing inputs to the soma, and the distal compartment comprised of the apical dendritic
184   tuft [22, 65]. These two compartments receive excitatory inputs from two separate sources [18, 66].

185   Similarly, the auxiliary variables $\mathbf{n}^{(l)}$ are represented by the activity of interneurons in each cortical
186   region.[2] The $\mathbf{Q}^{(l)}$ synaptic weights are encoded in the weights of synapses connecting $\mathbf{n}^{(l)}$ to $\mathbf{z}^{(l)}$,
187   while $\mathbf{Q}^{(l)\top}$ models the weights of synapses from $\mathbf{z}^{(l)}$ to $\mathbf{n}^{(l)}$. In a biological setting, the implied
188   equality of weights of synapses from $\mathbf{z}^{(l)}$ to $\mathbf{n}^{(l)}$ and the transpose of those from $\mathbf{n}^{(l)}$ to $\mathbf{z}^{(l)}$ can be
189   guaranteed by applying the same Hebbian learning rule [55]. However, unlike previous work, we do
190   not require interneurons of one layer to be connected to the pyramidal neurons of another layer.

191   **Neural dynamics and canonical components.**   The neural dynamics of the pyramidal neurons of
192   our circuit given by Eq. (10) can be recast as the dynamics of a three compartment neuron:

$$\tau\dot{\mathbf{z}}^{(l)} = -g_{\text{lk}}^{(l)}\mathbf{z}^{(l)} + g_a^{(l)}(\mathbf{v}_a^{(l)} - \mathbf{z}^{(l)}) + g_b^{(l)}(\mathbf{v}_b^{(l)} - \mathbf{z}^{(l)}), \tag{12}$$

193   where we have defined the apical and basal compartmental membrane potentials

$$\mathbf{v}_a^{(l)} = \mathbf{W}_a^{(l)\top}\mathbf{z}^{(l+1)} - \mathbf{Q}^{(l)\top}\mathbf{n}^{(l)}, \qquad \mathbf{v}_b^{(l)} = \mathbf{W}_b^{(l-1)}\mathbf{z}^{(l-1)}. \tag{13}$$

194   Here we defined the leak conductance $g_{\text{lk}}^{(l)} = c^{(l)} - g_a^{(l)}$. Interestingly, this is the same neural
195   dynamics of a three-compartment neuron posited previously in [28, 30], which we derived in a
196   normative way. Here, g_a (resp. g_b) are conductances between the apical (resp. basal) compartments

---

[2]There are multiple types of interneurons targeting pyramidal cells [67,68]. The interneurons of BioCCPC
most closely resemble the somatostatin-expressing interneurons, which preferentially inhibit the apical dendrites.

Figure 2: Schematic of the biological implementation of the BioCCPC algorithm. Left: overall connectivity pattern, showing all-to-all connections between pyramidal neurons in consecutive layers, and between pyramidal and interneurons in the same layer. Right: zoom in on one neuron and its immediate neighbors, showing the membrane potentials and synaptic weights that are relevant for our algorithm.

and the soma, and g_{lk} is the somatic leak. Our derivation clarifies the relationship between the physiological quantities and the objective function. Indeed, the basal and apical conductances play the role of the inverse variances in the predictive coding objective. These inverse variances, generally referred to as 'precisions' in the PC literature, have previously been argued to be encoded in lateral inhibitions [2] or top-down attention [69, 70]. In our model, they are simply encoded in the compartmental conductances. In Sec. 5 we show that the leak term also has a functional role and determines a threshold for dynamically learning more diverse variables [71, 72].

Synaptic weight updates. Matching observations in the cortex, in our circuit [18, 22, 65, 73, 74], the basal and apical weights ($\mathbf{W}_b$ and $\mathbf{W}_a$) of our algorithm are updated differently. The basal synaptic weights of the pyramidal neurons, given by the elements of $\mathbf{W}_b^{(l)}$, are updated by the product of two factors represented in the corresponding post- and pre-synaptic neurons (Eq. 11a):

$$\delta \mathbf{W}_b^{(l-1)} \propto \left[g_a^{(l)} \mathbf{v}_a^{(l)} - c^{(l)} \mathbf{z}^{(l)} \right] \mathbf{z}^{(l-1)\top} . \tag{14}$$

The first term in parentheses, $g_a^{(l)} \mathbf{v}_a^{(l)}$, is proportional to the total apical current, given by the difference between the excitatory synaptic current in the apical tuft, $\mathbf{W}_a^{(l)\top} \mathbf{z}^{(l+1)}$, and the inhibitory current induced by interneurons synapsing onto the distal compartment, $\mathbf{Q}^{(l)\top} \mathbf{n}^{(l)}$. Biologically, this factor can be approximated by the calcium plateau potential traveling down the apical shaft. The calcium plateau potential has been experimentally seen to drive plasticity of the basal synapses matching the derived update rule of our circuit [18, 20, 23–25]. The second factor is simply the neural output. Because the total update is not purely dependent on the action potentials of the pre- and post-synaptic neurons, such plasticity is called non-Hebbian [25]. The synaptic learning rule for the apical weights $\mathbf{W}_a^{(l)}$ (Eq. 11b) and the synapses connecting the interneurons and the pyramidal neurons $\mathbf{Q}^{(l)}$ (Eq. 11c) are simply Hebbian, also matching experimental observations in the cortex [19, 75].

Features and limitations. Here we summarize the main differences between the biological implementations of CCPC and PC. In PC, the forward and backward weights (in our notation $\mathbf{W}_b$ and $\mathbf{W}_a^\top$) are symmetric, whereas in CCPC, they are not constrained to be symmetric and are generically not so (see Sec. 6). Another difference is that in PC, the connection between value neurons and error neurons is one-to-one and fixed; this constraint does not exist between the pyramidal and interneurons of our model, which are no longer one-to-one, and have plastic connectivity.

224 While we have shown the improvement in biological realism of our model over the traditional PC
225 network, this was done in the linear case. However, recent work on deep linear networks [76],
226 has provided many insights into the learning dynamics of deep networks. Some of the properties
227 discovered in the deep linear network, like "balancedness" of weights [77, 78], generalize for certain
228 nonlinear networks [78]. We believe several of our observations will generalize in a similar fashion.

229 There are other aspects that can also be improved. For example, the connectivity between pyramidal
230 neurons and interneurons of CCPC is required to be symmetric. This symmetry can be achieved
231 via Hebbian learning [55]; however, it would be interesting to explore if such symmetry is indeed
232 required. In CCPC, symmetric connectivity is only required between neurons of the *same* cortical
233 region, which is a much less stringent biological requirement than the that of symmetric weights
234 between *different* cortical regions, as in PC. Another shortcoming of our model is that while the
235 teaching signal for the basal synapses in CCPC is signed and graded, in the cortex these signals are
236 generally believed to be stereotypical [18].

5 Theoretical arguments

238 In this section, we summarize some of the salient theoretical features of our framework. Further
239 details and proofs are given in SM Sec. B.

240 **The errors are implicitly computed in $\mathbf{v}_a^{(l)}$.** In backpropagation as well as in PC, the learning
241 algorithm computes a loss (or a local error) which is then used to compute updates to the weights. In
242 CCPC, no error or loss is explicitly computed. So how does CCPC learn? In the following proposition,
243 we show that in the $g_a \to 0$ limit, the algorithm implicitly computes an error in its weight updates.
244 This quasi feed-forward or weak nudging limit, has been used to explore the learning dynamics of
245 biologically plausible networks [30] and is related to the 'fixed prediction' assumption [4, 61, 62].

246 **Proposition 1.** *Assume that the learning rules (Eqs. 11) are at equilibrium and we receive a new*
247 *datapoint given by $\mathbf{x}_{T+1}, \mathbf{y}_{T+1}$. For $c^{(l)} = 0$ and in the limit of $\epsilon \equiv g_a/g_b \to 0$, the leading term in*
248 *ϵ for the forward weight updates $\delta\mathbf{W}_b^{(l-1)}$ for this new sample is given by*

$$\delta\mathbf{W}_b^{(l-1)} \propto \mathbf{v}_{a,T+1}^{(l)}\mathbf{z}_{T+1}^{(l-1)\top} = \epsilon^{n-l}\left[\mathbf{W}_a^{(l)\top}\cdots\mathbf{W}_a^{(n-1)\top}(\mathbf{y}_{T+1} - \tilde{\mathbf{y}}_{T+1})\right]\mathbf{z}_{T+1}^{(l-1)\top} + \mathcal{O}(\epsilon^{n-l+1}),$$

249 *where $\tilde{\mathbf{y}}_{T+1} = \mathbf{YZ}^{(l-1)\top}\left(\mathbf{Z}^{(l-1)}\mathbf{Z}^{(l-1)\top}\right)^{-1}\mathbf{z}_{T+1}^{(l-1)}$ is the optimal linear inferred value for $\mathbf{y}_{T+1}$.*

250 This implies that $\mathbf{v}_a^{(l)}$, which we argued can be implemented as the calcium plateau potential,
251 implicitly encodes an error signal. This is in spirit similar to difference target propagation [47], where
252 the difference between the forward pass and the target is explicitly computed and backpropagated.

253 **Adaptive latent dimension discovery for a single module.** For optimization within a single
254 hidden layer, we show that the system performs adaptive latent dimension discovery by thresholding
255 eigenvalues of a Gramian including contributions from both adjacent layers. If we take the loss
256 function in (9), setting $g_a = 1, g_b = \epsilon$, and optimizing over $\mathbf{W}_a, \mathbf{W}_b$, we get the objective $\mathrm{Tr}[(c +$
257 $\epsilon)\mathbf{Z}^\top\mathbf{Z} - \mathbf{Z}^\top\mathbf{Z}\left[\epsilon\mathbf{X}^\top(\mathbf{XX}^\top)^{-1}\mathbf{X} + \mathbf{Y}^\top\mathbf{Y}\right]$ for $\mathbf{Z}$. The next theorem indicates the solution:

258 **Theorem 1.** *Let the concatenated matrix $\mathbf{\Xi} = [\epsilon^{1/2}\mathbf{C}_x^{-1/2}\mathbf{X}, \mathbf{Y}] \in \mathbb{R}^{(d_X+d_Y)\times T}$ have SVD $\mathbf{\Xi} =$*
259 *$\sum_{\alpha=1}^{(d_X+d_Y)} \mathbf{u}_\alpha\lambda_\alpha\mathbf{v}_\alpha^\top$ with $\{\mathbf{u}_\alpha \in \mathbb{R}^{(d_X+d_Y)}\}$ and $\{\mathbf{v}_\alpha \in \mathbb{R}^T\}$ both being sets of orthonormal vectors,*
260 *with the convention that (λ_α) are sorted in decreasing order. We consider the minimization*

$$\min_{\mathbf{Z}\in\mathbb{R}^{d\times T}, \mathbf{ZZ}^\top\preccurlyeq I_d} \mathrm{Tr}\left[(c+\epsilon)\mathbf{Z}^\top\mathbf{Z} - \mathbf{Z}^\top\mathbf{Z}\left[\epsilon\mathbf{X}^\top(\mathbf{XX}^\top)^{-1}\mathbf{X} + \mathbf{Y}^\top\mathbf{Y}\right]\right]. \tag{15}$$

261 *Then one of the optimal solutions is given by $\hat{\mathbf{Z}} = \sum_{\alpha=1}^D \mathbf{w}_\alpha\mathbb{1}(\lambda_\alpha > c + \epsilon)\mathbf{v}_\alpha^\top$ where $\{\mathbf{w}_\alpha \in \mathbb{R}^d\}$ is*
262 *an arbitrary set of orthonormal vectors, with $D = \min(d, d_X + d_Y)$.*

263 Thus, the latent modes are found by thresholding the eigenvalues [72] of the sum of Gramians [71] in
264 Eq. (15). This implies that the quantity $c^{(l)}$ that we showed is encoded in the somatic compartment leak
265 conductance, biologically sets an adaptive threshold for the dimensionality of the latent representation.

266 From this theorem, we derive the computational limits of $\epsilon \to \infty$ and $\epsilon \to 0$ in the supplementary
267 materials. We also show that the neurons of the narrowest layer get whitened and the other layers
268 become low-rank. For further details of these statements and all proofs see SM Sec. B.

6 Numerical experiments

Figure 3: Our algorithm (BioCCPC) compares well to less biologically plausible predictive-coding (PC) imple-
mentations, while enforcing an inequality constraint on the covariance of hidden-layer activations. Simulations
run on the MNIST dataset, using a network with two hidden layers, sizes 50 and 5. Shaded area represents the
95% range out of 40 runs. (a) Evolution of the predictive-coding loss, Eq. (6), on a validation set during learning.
(b), (c) Evolution of the eigenvalues of the covariance matrix of hidden-layer activations in the two hidden layers.
The dashed lines show the scale of the constraint; see SM Sec. A. Inset: covariance matrix at end of training.
Note how activity is whitened in the second hidden layer (c), and low-rank in the first hidden layer (b).

270 We tested our BioCCPC algorithm on the MNIST [79] as well as other datasets. We compared our
271 results with a standard predictive coding network [4] with linear activation (PC) and with a version
272 that includes a covariance constraint (PC+cons; Sec. C). We used unit variances, $\sigma^{(l)2} = 1$, in the PC
273 networks, and matching conductances in our algorithm, $g_b^{(1)} = g_a^{(n)} = 1$, $g_a^{(l)} = g^{(l)} = \frac{1}{2}$ for other l.

274 Our method finds solutions that are almost optimal in terms of predictive-coding loss (see Fig. 3a)
275 and are generally better than the solutions obtained from simply adding the covariance constraint to a
276 predictive-coding network. Learning is slower in our network than in unconstrained PCN, as it takes
277 time for the covariance constraint to be enforced. It is possible that different initialization schemes
278 could improve the learning speed, but we leave this for future work.

279 The covariance constraint is saturated in the narrowest layer—in our example, the second hidden layer,
280 of size 5—see Fig. 3c. The activation in the other hidden layer is rank-restricted by the narrowest
281 layer, as described above, and so it is only whitened within a 5D subspace, Fig. 3b. In SM Sec. C, we
282 provide further numerical experiments, exploring the effects of thresholding, the size of the network,
283 and performance on other datasets. In all tested scenarios, BioCCPC achieves the same validation
284 loss as PC (Figs. 5 and 6 of SM Sec. C). We also show that the forward and backward weights, $\mathbf{W}_b$
285 and $\mathbf{W}_a^\top$, are not symmetric, in accordance with biological observations, and explore their relation.

7 Conclusion

287 We have derived a biologically plausible algorithm for covariance-constrained predictive coding and
288 have shown that it avoids the criticisms of PC and has many features in common with recent experi-
289 mental observations. Our algorithm does not have symmetric forward and backward connectivity
290 matrices, and does not need one-to-one connectivity between any neurons. Furthermore, we showed
291 that the learning rules of our algorithm closely match experimental observations, and we connected
292 our parameters to neurophysiological quantities. Using the simplicity afforded to us because of the
293 linearity, we showed a number of interesting properties of our algorithm, including the effect of the
294 somatic leak term, which acts as an adaptive thresholding mechanism. We also showed how our
295 algorithm implicitly computes a difference term that it uses for learning. We argued that this term
296 could be encoded in the calcium plateau potential, which is known to affect the learning of basal
297 synapses. We hope that this concrete connection between our normative model and observation can
298 further our understanding of cortical computation by guiding future experiments.

Broader impact

We do not foresee any potential societal harm caused by our work. We hope our contribution moves forward the discussion on the relationship between multi-layer networks and cortical structure.

References

[1] Rajesh P.N. Rao and Dana H. Ballard. Predictive coding in the visual cortex: A functional interpretation of some extra-classical receptive-field effects. *Nature Neuroscience*, 1999.

[2] Karl Friston. A theory of cortical responses. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 2005.

[3] Mandyam Veerambudi Srinivasan, Simon Barry Laughlin, A. Dubs, and George Adrian Horridge. Predictive coding: a fresh view of inhibition in the retina. *Proceedings of the Royal Society of London. Series B. Biological Sciences*, 216(1205):427–459, 1982.

[4] James C.R. Whittington and Rafal Bogacz. An approximation of the error backpropagation algorithm in a predictive coding network with local hebbian synaptic plasticity. *Neural Computation*, 29(5):1229–1262, may 2017.

[5] Tommaso Salvatori, Luca Pinchetti, Beren Millidge, Yuhang Song, Tianyi Bao, Rafal Bogacz, and Thomas Lukasiewicz. Learning on arbitrary graph topologies via predictive coding, 2022.

[6] André Ofner and Sebastian Stober. Differentiable generalised predictive coding, 2021.

[7] Martin Boerlin, Christian K Machens, and Sophie Denève. Predictive coding of dynamical variables in balanced spiking networks. *PLoS computational biology*, 9(11):e1003258, 2013.

[8] Jonathan Kadmon, Jonathan Timcheck, and Surya Ganguli. Predictive coding in balanced neural networks with noise, chaos and delays. *Advances in neural information processing systems*, 33:16677–16688, 2020.

[9] Ryan Smith, Paul Badcock, and Karl J Friston. Recent advances in the application of predictive coding and active inference models within clinical neuroscience. *Psychiatry and Clinical Neurosciences*, 75(1):3–13, 2021.

[10] Paul F. Kinghorn, Beren Millidge, and Christopher L. Buckley. Habitual and reflective control in hierarchical predictive coding, 2021.

[11] Tommaso Salvatori, Yuhang Song, Yujian Hong, Lei Sha, Simon Frieder, Zhenghua Xu, Rafal Bogacz, and Thomas Lukasiewicz. Associative Memories via Predictive Coding. In M Ranzato, A Beygelzimer, Y Dauphin, P S Liang, and J Wortman Vaughan, editors, *Advances in Neural Information Processing Systems*, volume 34, pages 3874–3886. Curran Associates, Inc., 2021.

[12] Beren Millidge, Anil Seth, and Christopher L Buckley. Predictive coding: a theoretical and experimental review, 2021.

[13] Beren Millidge, Tommaso Salvatori, Yuhang Song, Rafal Bogacz, and Thomas Lukasiewicz. Predictive coding: Towards a future of deep learning beyond backpropagation?, 2022.

[14] André M. Bastos, W. Martin Usrey, Rick A Adams, George R. Mangun, Pascal Fries, and Karl J. Friston. Canonical microcircuits for predictive coding. *Neuron*, 76:695–711, 2012.

[15] Micha Heilbron and Maria Chait. Great Expectations: Is there Evidence for Predictive Coding in Auditory Cortex? *Neuroscience*, 389:54–73, 2018.

[16] Naoki Kogo and Chris Trengove. Is predictive coding theory articulated enough to be testable? *Frontiers in Computational Neuroscience*, 9, 2015.

[17] Nelson Spruston. Pyramidal neurons: dendritic structure and synaptic integration. *Nature Reviews Neuroscience*, 9(3):206–221, 2008.

[18] Matthew Larkum. A cellular mechanism for cortical associations: an organizing principle for the cerebral cortex. *Trends in Neurosciences*, 36(3):141–151, 2013.

[19] Per Jesper Sjöström and Michael Häusser. A cooperative switch determines the sign of synaptic plasticity in distal dendrites of neocortical pyramidal neurons. *Neuron*, 51(2):227–238, 2006.

[20] Nace L Golding, Nathan P Staff, and Nelson Spruston. Dendritic spikes as a mechanism for cooperative long-term potentiation. *Nature*, 418(6895):326–331, 2002.

[21] Frédéric Gambino, Stéphane Pagès, Vassilis Kehayas, Daniela Baptista, Roberta Tatti, Alan Carleton, and Anthony Holtmaat. Sensory-evoked LTP driven by dendritic plateau potentials in vivo. *Nature*, 515(7525):116–119, 2014.

[22] Guy Major, Matthew E. Larkum, and Jackie Schiller. Active properties of neocortical pyramidal neuron dendrites. *Annual Review of Neuroscience*, 36(1):1–24, 2013. PMID: 23841837.

[23] Katie C Bittner, Christine Grienberger, Sachin P Vaidya, Aaron D Milstein, John J Macklin, Junghyup Suh, Susumu Tonegawa, and Jeffrey C Magee. Conjunctive input processing drives feature selectivity in hippocampal ca1 neurons. *Nature neuroscience*, 18(8):1133, 2015.

[24] Katie C Bittner, Aaron D Milstein, Christine Grienberger, Sandro Romani, and Jeffrey C Magee. Behavioral time scale synaptic plasticity underlies ca1 place fields. *Science*, 357(6355):1033–1036, 2017.

[25] Jeffrey C. Magee and Christine Grienberger. Synaptic plasticity forms and functions. *Annual Review of Neuroscience*, 43, 2020.

[26] Jason Hardie and Nelson Spruston. Synaptic depolarization is more effective than back-propagating action potentials during induction of associative long-term potentiation in hippocampal pyramidal neurons. *Journal of Neuroscience*, 29(10):3233–3241, 2009.

[27] Konrad P Körding and Peter König. Supervised and unsupervised learning with two sites of synaptic integration. *Journal of Computational Neuroscience*, 11(3):207–215, 2001.

[28] Robert Urbanczik and Walter Senn. Learning by the Dendritic Prediction of Somatic Spiking. *Neuron*, 81(3):521–528, 2014.

[29] Jordan Guergiuev, Timothy P Lillicrap, and Blake A Richards. Deep learning with segregated dendrites. *arXiv preprint arXiv:1610.00161*, 2016.

[30] João Sacramento, Rui Ponte Costa, Yoshua Bengio, and Walter Senn. Dendritic cortical microcircuits approximate the backpropagation algorithm. *Advances in Neural Information Processing Systems*, 2018-Decem(Nips):8721–8732, oct 2018.

[31] Alexandre Payeur, Jordan Guerguiev, Friedemann Zenke, Blake A Richards, and Richard Naud. Burst-dependent synaptic plasticity can coordinate learning in hierarchical circuits. *bioRxiv*, 2020.

[32] Albert Gidon, Timothy Adam Zolnik, Pawel Fidzinski, Felix Bolduan, Athanasia Papoutsi, Panayiota Poirazi, Martin Holtkamp, Imre Vida, and Matthew Evan Larkum. Dendritic action potentials and computation in human layer 2/3 cortical neurons. *Science*, 367(6473):83–87, jan 2020.

[33] Aaron D. Milstein, Yiding Li, Katie C. Bittner, Christine Grienberger, Ivan Soltesz, Jeffrey C. Magee, and Sandro Romani. Bidirectional synaptic plasticity rapidly modifies hippocampal representations independent of correlated activity. *bioRxiv*, 2020.

[34] David E. Rumelhart, Geoffrey E. Hinton, and Ronald J. Williams. Learning internal representations by error propagation. In David E. Rumelhart and James L. Mcclelland, editors, *Parallel Distributed Processing: Explorations in the Microstructure of Cognition, Volume 1: Foundations*, pages 318–362. MIT Press, Cambridge, MA, 1986.

[35] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT press, 2016.

[36] Seungjin Choi, Andrzej Cichocki, Hyung-Min Park, and Soo-Young Lee. Blind source separation and independent component analysis: A review. *Neural Information Processing-Letters and Reviews*, 6(1):1–57, 2005.

[37] Cengiz Pehlevan and Dmitri B Chklovskii. Neuroscience-inspired online unsupervised learning algorithms: Artificial neural networks. *IEEE Signal Processing Magazine*, 36(6):88–96, 2019.

[38] Adrian A Wanner and Rainer W Friedrich. Whitening of odor representations by the wiring diagram of the olfactory bulb. *Nature neuroscience*, 23(3):433–442, 2020.

[39] Guillaume Desjardins, Karen Simonyan, Razvan Pascanu, and Koray Kavukcuoglu. Natural neural networks, 2015.

[40] Yuki Fujimoto and Toru Ohira. A neural network model with bidirectional whitening. In *Artificial Intelligence and Soft Computing*, pages 47–57. Springer International Publishing, 2018.

[41] Ping Luo. Learning deep architectures via generalized whitened neural networks. In *International Conference on Machine Learning*, pages 2238–2246. PMLR, 2017.

[42] P. J. Werbos. *Beyond Regression: New Tools for Prediction and Analysis in the Behavioral Sciences*. PhD thesis, Harvard University, 1974.

[43] Francis Crick. The recent excitement about neural networks. *Nature*, 337(6203):129–132, 1989.

[44] Yann Le Cun. Learning Process in an Asymmetric Threshold Network. In *Disordered Systems and Biological Organization*, pages 233–240. Springer, 1986.

[45] Y. Le Cun and Franccoise Fogelman-Soulié. Modèles connexionnistes de l'apprentissage. *Intellectica. Revue de l'Association pour la Recherche Cognitive*, 1987.

[46] John F. Kolen and Jordan B. Pollack. Backpropagation without weight transport. *Proceedings of 1994 IEEE International Conference on Neural Networks (ICNN'94)*, 3:1375–1380 vol.3, 1994.

[47] Dong-Hyun Lee, Saizheng Zhang, Antoine Biard, and Yoshua Bengio. Target Propagation. *Iclr 15*, 1(3):1–16, 2014.

[48] Timothy P. Lillicrap, Daniel Cownden, Douglas B. Tweed, and Colin J. Akerman. Random synaptic feedback weights support error backpropagation for deep learning. *Nature Communications*, 7:1–10, 2016.

[49] Benjamin Scellier and Yoshua Bengio. Equilibrium propagation: Bridging the gap between energy-based models and backpropagation. *Frontiers in Computational Neuroscience*, 11(May), 2017.

[50] Dmitry Krotov and John J. Hopfield. Unsupervised learning by competing hidden units. *Proceedings of the National Academy of Sciences*, 116(16):7723–7731, 2019.

[51] Mohamed Akrout, Collin Wilson, Peter C. Humphreys, Timothy Lillicrap, and Douglas Tweed. Deep Learning without Weight Transport. *arXiv*, apr 2019.

[52] Jordan Guerguiev, Konrad Kording, and Blake Richards. Spike-based causal inference for weight alignment. *arXiv preprint arXiv:1910.01689*, 10 2019.

[53] Maxence Ernoult, Julie Grollier, Damien Querlioz, Yoshua Bengio, and Benjamin Scellier. Equilibrium Propagation with Continual Weight Updates. *arXiv preprint arXiv:2005.04168*, pages 1–37, 2020.

[54] Will Xiao, Honglin Chen, Qianli Liao, and Tomaso A. Poggio. Biologically-plausible learning algorithms can scale to large datasets. *CoRR*, abs/1811.03567, 2018.

[55] Siavash Golkar, David Lipshutz, Yanis Bahroun, Anirvan Sengupta, and Dmitri Chklovskii. A simple normative network approximates local non-Hebbian learning in the cortex. In H Larochelle, M Ranzato, R Hadsell, M F Balcan, and H Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 7283–7295. Curran Associates, Inc., 2020.

[56] Siavash Golkar, David Lipshutz, Yanis Bahroun, Anirvan M. Sengupta, and Dmitri B. Chklovskii. A biologically plausible neural network for local supervision in cortical microcircuits, 2020.

[57] Yoshua Bengio. Deriving differential target propagation from iterating approximate inverses, 2020.

[58] Jyotibdha Acharya, Arindam Basu, Robert Legenstein, Thomas Limbacher, Panayiota Poirazi, and Xundong Wu. Dendritic Computing: Branching Deeper into Machine Learning. *Neuroscience*, 489:275–289, 2022.

[59] Timothy P Lillicrap, Adam Santoro, Luke Marris, Colin J Akerman, and Geoffrey Hinton. Backpropagation and the brain. *Nature Reviews Neuroscience*, 21(6):335–346, 2020.

[60] João Sacramento, Rui Ponte Costa, Yoshua Bengio, and Walter Senn. Dendritic error backpropagation in deep cortical microcircuits. *arXiv preprint arXiv:1801.00062*, pages 1–37, 2017.

[61] Beren Millidge, Alexander Tschantz, and Christopher L. Buckley. Predictive coding approximates backprop along arbitrary computation graphs, 2020.

[62] Yuhang Song, Thomas Lukasiewicz, Zhenghua Xu, and Rafal Bogacz. Can the Brain Do Backpropagation? — Exact Implementation of Backpropagation in Predictive Coding Networks. In H Larochelle, M Ranzato, R Hadsell, M F Balcan, and H Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 22566–22579. Curran Associates, Inc., 2020.

[63] Tommaso Salvatori, Yuhang Song, Thomas Lukasiewicz, Rafal Bogacz, and Zhenghua Xu. Predictive coding can do exact backpropagation on convolutional and recurrent neural networks. *CoRR*, abs/2103.03725, 2021.

[64] Robert Rosenbaum. On the relationship between predictive coding and backpropagation, 2021.

[65] Matthew E. Larkum, Thomas Nevian, Maya Sandler, Alon Polsky, and Jackie Schiller. Synaptic integration in tuft dendrites of layer 5 pyramidal neurons: A new unifying principle. *Science*, 325(5941):756–760, 2009.

[66] Hiroto Takahashi and Jeffrey C Magee. Pathway interactions and synaptic plasticity in the dendritic tuft regions of CA1 pyramidal neurons. *Neuron*, 62(1):102–111, 2009.

[67] Thomas Klausberger, Peter J Magill, László F Márton, J David B Roberts, Philip M Cobden, György Buzsáki, and Peter Somogyi. Brain-state-and cell-type-specific firing of hippocampal interneurons in vivo. *Nature*, 421(6925):844–848, 2003.

[68] Therese Riedemann. Diversity and function of somatostatin-expressing interneurons in the cerebral cortex. *International Journal of Molecular Sciences*, 20(12):2952, 2019.

[69] Karl Friston. The free-energy principle: A unified brain theory?, 2010.

[70] Ryota Kanai, Yutaka Komura, Stewart Shipp, and Karl Friston. Cerebral hierarchies: predictive processing, precision and the pulvinar. *Philosophical Transactions of the Royal Society B: Biological Sciences*, 370(1668):20140169, 2015.

[71] David Lipshutz, Yanis Bahroun, Siavash Golkar, Anirvan M. Sengupta, and Dmitri B. Chklovskii. A Biologically Plausible Neural Network for Multichannel Canonical Correlation Analysis. *Neural Computation*, 33(9):2309–2352, 08 2021.

[72] Cengiz Pehlevan and Dmitri Chklovskii. A Normative Theory of Adaptive Dimensionality Reduction in Neural Networks. In C Cortes, N Lawrence, D Lee, M Sugiyama, and R Garnett, editors, *Advances in Neural Information Processing Systems*, volume 28. Curran Associates, Inc., 2015.

[73] Charles D Gilbert and Wu Li. Top-down influences on visual processing. *Nature Reviews Neuroscience*, 14(5):350–363, 2013.

[74] Georg B Keller and Thomas D Mrsic-Flogel. Predictive processing: a canonical cortical computation. *Neuron*, 100(2):424–435, 2018.

[75] Björn M. Kampa, Johannes J. Letzkus, and Greg J. Stuart. Dendritic mechanisms controlling spike-timing-dependent synaptic plasticity. *Trends in Neurosciences*, 30(9):456–463, 2007.

[76] Andrew M Saxe, James L McClelland, and Surya Ganguli. Exact solutions to the nonlinear dynamics of learning in deep linear neural networks. *arXiv preprint arXiv:1312.6120*, 2013.

[77] Sanjeev Arora, Nadav Cohen, and Elad Hazan. On the optimization of deep networks: Implicit acceleration by overparameterization. In *International Conference on Machine Learning*, pages 244–253. PMLR, 2018.

[78] Simon S Du, Wei Hu, and Jason D Lee. Algorithmic regularization in learning deep homogeneous models: Layers are automatically balanced. *Advances in Neural Information Processing Systems*, 31, 2018.

[79] Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.