MISSINGNESS BIAS IN MODEL DEBUGGING

ABSTRACT

Missingness, or the absence of features from an input, is a concept fundamental to many model debugging tools. However, in computer vision, pixels cannot simply be removed from an image. One thus tends to resort to heuristics such as blacking out pixels, which may in turn introduce bias into the debugging process. We study such biases and, in particular, show how transformer-based architectures can enable a more natural implementation of missingness, which side-steps these issues and improves the reliability of model debugging in practice.

1 INTRODUCTION

Model debugging aims to diagnose a model's failures. For example, researchers can identify global biases of models via the extraction of human-aligned concepts (Bau et al., 2017; Wong et al., 2021), or understand the texture bias by analyzing the models performance on synthetic datasets (Geirhos et al., 2019; Leclerc et al., 2021). Other approaches aim to highlight local features to debug individual model predictions (Simonyan et al., 2013; Dhurandhar et al., 2018; Ribeiro et al., 2016a; Goyal et al., 2019).

A common theme in these methods is to compare the behavior of the model *with and without* certain individual features (Ribeiro et al., 2016a; Goyal et al., 2019; Fong & Vedaldi, 2017; Dabkowski & Gal, 2017; Zintgraf et al., 2017; Dhurandhar et al., 2018; Chang et al., 2019). For example, interpretability methods such as LIME (Ribeiro et al., 2016b) and integrated gradients (Sundararajan et al., 2017) use the predictions when certain features are removed from the input to attribute different regions of the input to the decision of the model. Dhurandhar et al. (2018) find minimal regions in radiology images that are necessary for classifying a person as having autism. Fong & Vedaldi (2017) propose learning image masks that minimize a class score to achieve interpretable explanations. Similarly, in natural language processing, model designers often remove individual words to understand their importance to the output (Mardaoui & Garreau, 2021; Li et al., 2016). The absence of features from an input, a concept sometimes referred to as *missingness* (Sturmfels et al., 2020), is thus fundamental to many debugging tools.

However, there is a problem: while we can easily remove words from sentences, removing objects from images is not as straightforward. Indeed, removing a feature from an image usually requires approximating missingness by replacing those pixel values with something else, e.g., black color. However, these approximations tend to not be perfect (Sturmfels et al., 2020). Our goal is thus to give a holistic understanding of missingness and, specifically, to answer the question:

How do missingness approximations affect our ability to debug ML models?

OUR CONTRIBUTIONS

In this paper, we investigate how current missingness approximations, such as blacking out pixels, can result in what we call *missingness bias*. This bias turns out to hinder our ability to debug models. We then show how transformer-based architectures can enable a more natural implementation of missingness, allowing us to side-step this bias. More specifically, our contributions include:

Pinpointing the missingness bias. We demonstrate at multiple granularities how simple approximations, such as blacking out pixels, can lead to missingness bias. This bias skews the overall output distribution toward unrelated classes, disrupts individual predictions, and hinders the model's use of the remaining (unmasked) parts of the image.

| (a) Original image | (b) Masking the human | (c) Masking the dog's face |

Figure 1: Consider an image of a dog being held by its owner. By removing the owner from the image, we can study how much our model's prediction depends on the presence of a human. In a similar vein, we can identify which aspects of the dog (head, body, paws) are most critical for classifying the image by ablating these parts.

Studying the impact of missingness bias on model debugging. We show that missingness bias negatively impacts the performance of debugging tools. Using LIME—a common feature attribution method that relies on missingness—as a case study, we find that this bias causes the corresponding explanations to be inconsistent and indistinguishable from random explanations.

Using vision transformers to implement a more natural form of missingness. The token-centric nature of vision transformers (ViT) (Dosovitskiy et al., 2021) facilitates a more natural implementation of missingness: simply drop the corresponding tokens of the image subregion we want to remove. We show that this simple property substantially mitigates missingness bias and thus enables better model debugging.

2 MISSINGNESS

Removing features from the input is an intuitive way to understand how a system behaves (Sturmfels et al., 2020). Indeed, by comparing the system's output with and without specific features, we can infer what parts of the input led to a specific outcome (Sundararajan et al., 2017)—see Figure 1. The absence of features from an input is sometimes referred to as *missingness* (Sturmfels et al., 2020).

The concept of missingness is commonly leveraged in machine learning, especially for tasks such as model debugging. For example, several methods for feature attribution quantify feature importance by studying how the model behaves when those features are removed (Sturmfels et al., 2020; Sundararajan et al., 2017; Ancona et al., 2017). One commonly used method, LIME (Ribeiro et al., 2016a), iteratively turns image subregions on and off in order to highlight its important parts. Similarly, integrated gradients (Sundararajan et al., 2017), a typical method for generating saliency maps, leverages a "baseline image" to represent the "absence" of features in the input. Missingness-based tools are also often used in domains such as natural language processing (Mardaoui & Garreau, 2021; Li et al., 2016) and radiology (Dhurandhar et al., 2018).

Challenges of approximating missingness in computer vision. While ignoring parts of an image is simple for humans, removing image features is far more challenging for computer vision models (Sturmfels et al., 2020). After all, convolutional networks require a structurally contiguous image as an input. We thus cannot leave a "hole" in the image where the model should ignore the input. Consequently, practitioners typically resort to approximating missingness by replacing these pixels with other, intended to be "meaningless", pixels.

Common *missingness approximations* include replacing the region of the image with black color, a random color, random noise, a blurred version of the region, and so forth (Sturmfels et al., 2020; Ancona et al., 2017; Smilkov et al., 2017; Fong & Vedaldi, 2017; Zeiler & Fergus, 2014; Sundararajan et al., 2017). However, there is no clear justification for why any of these choices is a good approximation of missingness. For example, blacked out pixels are an especially popular baseline, motivated by the implicit heuristic that near zero inputs are somehow neutral for a simple model (Ancona et al., 2017). However, if only part of the input is masked or the model includes additive bias terms, the choice of black is still quite arbitrary. In (Sturmfels et al., 2020), the authors found that

Original	Random	Least Salient	Most Salient
ResNet-50: flatworm	ResNet-50: crossword	ResNet-50: jigsaw puzzle	ResNet-50: cliff dwelling
ViT-S: flatworm	ViT-S: flatworm	ViT-S: flatworm	ViT-S: sea slug

GT: flatworm

Figure 2: Given an image of a `flatworm`, we remove various regions of the original image; masking for ResNet, and dropping tokens for ViT. **(Section 2.1):** Irrespective of what subregions of the image are removed (least salient, most salient, or random), a ResNet-50 outputs the wrong class (`crossword`, `jigsaw puzzle`, `cliff dwelling`). Taking a closer look at the randomly masked image of Figure 2, we notice that the predicted class (`crossword puzzle`) is not totally unreasonable given the masking pattern. The model seems to be relying on the masking pattern to make the prediction, rather than the remaining (unmasked) portions of the image. **(Section 2.2):** The ViT-S on the other hand either maintains its original prediction or predicts a reasonable label given remaining image subregions.

saliency maps generated with integrated gradients are quite sensitive to the chosen baseline color, and thus can change significantly based on the (arbitrary) choice of missingness approximation.

2.1 MISSINGNESS BIAS

What impact do these various missingness approximations have on our models? We find that current approximations can cause significant bias in the model's predictions. This causes the model to make errors based on the "missing" regions rather than the remaining image features, rendering the masked image out-of-distribution.

Figure 2 depicts an example of these problems. If we mask a small portion of the image, irrespective of which part of the image that is, convolutional networks (CNNs) output the wrong class. In fact, CNNs seem to be relying on the masking pattern to make the prediction, rather than the remaining (unmasked) portions of the image. This type of behavior can be especially problematic for model debugging techniques, such as LIME, that rely on removing image subregions to assign importance to input features. Further examples can be found in Appendix C.1.

There seems to be an inherent bias accompanying missingness approximations, which we refer to as the *missingness bias*. In Section 3, we systematically study how missingness bias can affect model predictions at multiple granularities. Then in Section 4, we find that missingness bias can cause undesirable effects when using LIME by causing its explanations to be inconsistent and indistinguishable from random explanations.

2.2 A MORE NATURAL FORM OF MISSINGNESS VIA VISION TRANSFORMERS

The challenges of missingness bias raises an important question: what constitutes a correct notion of missingness? Since masking pixels creates biases in our predictions, we would ideally like to remove those regions from consideration entirely. Because convolutional networks slide filters across the image, they require spatially contiguous input images. We are thus limited to replacing pixels with some baseline value (such as blacking out the pixes), which leads to missingness bias.

Unlike CNNs, vision transformers (ViTs) (Dosovitskiy et al., 2021) operate on sets of *image tokens*, each of which correspond to a positionally encoded region of the image. ViTs thus enable a far more natural implementation of missingness: *simply drop the tokens that correspond to the regions of the image we want to "remove."* Instead of replacing the masked region with other pixel values, we can modify a forward pass of the ViT to directly remove the region entirely.

We will refer to this implementation of missingness as *dropping tokens* throughout the paper (see Appendix B for further details). As we will see, using ViTs to drop image subregions will allow us to side-step missingness bias, and thus enable better model debugging.

Figure 3: We measure the shift in output class distribution after applying missingness approximations. **Left**: Fraction of images predicted as each class (*on a log scale*) before and after randomly removing 50% of the image. We display the most frequently predicted 30 classes after applying the missingness approximations. **Right**: Degradation in overall class entropy as subregions are removed. As patches are blacked out, the ResNet's predictions skew from a uniform distribution toward a few unrelated classes such as maze, crossword puzzle, and carton. On the other hand, the ViT maintains a uniform class distribution with high class entropy.

3 THE IMPACTS OF MISSINGNESS BIAS

Section 2.1 featured several qualitative examples where missingness approximations affect the model's predictions. Can we get a precise grasp on the impacts of such missingness bias? In this section, we pinpoint how missingness bias can manifest at several levels of granularity. We further demonstrate how, by enabling a more natural implementation of missingness through dropping tokens, ViTs can avoid these biases.

To systematically measure the impacts of missingness bias, we iteratively remove subregions from the input and analyze the types of mistakes that our models make [1]. Our assessment of missingness bias, from the overall class distribution to individual examples, is guided by the following questions:

To what extent do missingness approximations skew the model's overall class distribution?
We find that missingness bias affect the model's overall class distribution (i.e the probability of predicting any one class). In Figure 3, we measure the shift in the model's output class distribution before and after image subregions are randomly removed. The overall entropy of output class distribution degrades severely. In contrast, this bias is eliminated when dropping tokens with the ViT. The ViT thus maintains a high class entropy corresponding to a roughly uniform class distribution. These findings hold regardless of what order we remove the image patches (see Appendix C.2).

Does removing random or unimportant regions flip the model's predictions? We now take closer look at how missingness approximations can affect individual predictions. In Figure 4, we plot the fraction of examples where removing a portion of the image flips the model's prediction. We find that the ResNet rapidly flips its predictions even when the less relevant regions are removed first. This degradation is thus more likely due to missingness bias rather than the removal of individual regions. In contrast, the ViT maintains its original predictions even when large parts of the image are removed.

---

[1]See Appendix A for experimental details. We perform an extensive study across various missingness approximations, architectures, and subregion sizes. Here we present the findings on a single representative setting: removing 16×16 patches from an image through blacking out (ResNet-50) and dropping tokens (ViT-S). We defer the remaining experiments, which lead to similar conclusions, to Appendix C.

Figure 4: We plot the fraction of images where the prediction does not change as image regions are removed. The ResNet flips its predictions even when unrelated patches are removed, while the ViT maintains its original prediction.

Figure 5: We repeat the experiment in Figure 4 with models retrained with missingness augmentations. Applying missingness approximations during training mitigates missingness bias for ResNets.

Figure 6: We iteratively remove image regions in the order of random, most salient, and least salient. We then plot the average WordNet similarity between the original prediction and the new prediction if the predictions differ. We find that ViT-S, even when the prediction changes, continues to predict something relevant to the original image.

Do remaining unmasked regions produce reasonable predictions? When removing regions of the image with missingness, we would hope that the model makes a "best-effort" prediction given the remaining image features. This assumption is critical for interpretability methods such as LIME (Ribeiro et al., 2016a), where crucial features are identified by iteratively masking out image subregions and tracking the model's predictions.

Are our models actually using the remaining uncovered features after missingness approximations are applied though? To answer this question, we measure how semantically related the model's predictions are after masking its original prediction using a similarity metric on the WordNet Hierarchy (Miller, 1995) as shown in Figure 6. By the time we mask out 25% of the image, the predictions of the ResNet largely become irrelevant to the input. ViTs on the other hand continue to predict classes that are related to the original prediction. This indicates that ViTs successfully leverage the remaining features in the image to provide a reasonable prediction.

Can we remove missingness bias by augmenting with missingness approximations? One way to remove missingness bias could be to apply missingness approximations during training. For example, in RemOve and Retrain (ROAR), Hooker et al. (2018) suggest retraining multiple copies of the model by randomly blacking out pixels during training (see Appendix E for an overview on ROAR).

To check if this indeed helps side-step the missingness bias, we retrain our models by randomly removing 50% of the patches during training, and again measure the fraction of examples where removing image patches flips the model's prediction (see Figure 5). While there is a significant gap in behavior between the standard and retrained CNNs, the ViT behaves largely the same. This result

Figure 7: Examples of generated LIME explanations and masking the top 20 features. Since LIME requires removing image features, it can be subject to missingness bias. We note that LIME explanations generated for standard ResNets seem to be less aligned with human intuition than ViTs or ResNets retrained with missingness augmentations (See Appendix D.1 for more examples).

indicates that, while retraining is important when analyzing CNNs, it is unnecessary for ViTs when dropping the removed tokens: we can instead perform missingness approximations directly on the original model while avoiding missingness bias for free. See Appendix E for more details.

4 MISSINGNESS BIAS IN PRACTICE: A CASE STUDY ON LIME

Missingness approximations play a key role in several feature attribution methods. One attribution method that fundamentally relies on missingness is the local interpretable model-agnostic explanations (LIME) method (Ribeiro et al., 2016a). LIME assigns a score to each image subregion based on its relevance to the model's prediction. Subregions of the image with the top scores are referred to as *LIME explanations*. A crucial step of LIME is "turning off" image subregions, usually by replacing them with some baseline pixel color. However, as we found in Section 2, missingness approximations can cause missingness bias, which can impact the generated LIME explanations.

We thus study how this bias impacts model debugging with LIME. To this end, we first show that missingness bias can create inconsistencies in LIME explanations, and further cause them to be indistinguishable from random explanations. In contrast, by dropping tokens with ViTs, we can side-step missingness bias in order to avoid these issues, enabling better model debugging.

Figure 7 depicts an example of LIME explanations. Qualitatively, we note that explanations generated for standard ResNets seem to be less aligned with human intuition than ViTs or ResNets retrained with missingness augmentations[2].

Missingness bias creates inconsistent explanations. Since LIME uses missingness approximations while scoring each image subregion, the generated explanations can change depending on which approximation is used. How consistent are the resulting explanations? We generate such explanations for a ViT and a CNN using 8 different baseline colors. Then, for each pair of colors, we measure how much their top-k features agree (see Figure 8). We find that the ResNet produces explanations that are almost as inconsistent as randomly generated explanations. The explanations of the ViT, however, are always consistent by construction since the ViT drops tokens entirely. For further comparison, we also plot the consistency of the LIME explanations of a ViT-S where we mask out pixels instead of drop the tokens.

---

[2]See Appendix D.1 for more details on this. We also include an overview of LIME and detailed experimental setup for this section in Appendix A, and further experiments using superpixels in Appendix D.2.

Figure 8: We plot the agreement (using Jaccard similarity) of top-k features across LIME explanations of 28 pairs of baseline colors. The result is averaged over the 28 pairs, and we display the 95% confidence interval over the pairs of colors. ResNet-50's explanations are almost as consistent as random explanations. For ViT with dropping tokens, explanations are naturally always consistent.

Figure 9: We evaluate LIME explanations using the top-K ablation test on a ResNet and ViT by measuring the fraction of examples who keep their original prediction after removing the Top-K features. A sharper degradation indicates a more appropriate explanation for that model. While the LIME scores on the ResNet are largely indistinguishable, the ViT shows clear differentiation between the different explanations.

Missingness bias renders different LIME explanations indistinguishable. Do LIME explanations actually reflect the model's predictions? A common approach to answer this is to remove the top-k subregions (by masking using a missingness approximation), and then check if the model's prediction changes (Samek et al., 2016). This is sometimes referred to as the *top-K ablation test* (Sturmfels et al., 2020). Intuitively, an explanation is better if it causes the predictions to flip more rapidly. We apply the top-k ablation test of four different LIME explanations on a ResNet-50 and a ViT-S as shown in Figure 9. Specifically, for each model we evaluate: 1) its own generated explanations, 2) the explanations of an identical architecture trained with a different seed 3) the explanations of the other architecture and 4) randomly generated explanations.

For CNNs (Figure 9-left), all four explanations (even the random one) flip the predictions at roughly an equal rate in the top-K ablation test. In these cases, the bias incurred during evaluation plays a larger role in changing the predictions than the importance of the region being removed, rendering the four explanations indistinguishable. On the ViT however (Figure 9-right), the LIME explanation generated from the original model outperforms all other explanations (followed by an identical model trained with a different seed). As we would expect, the ResNet and the random explanations cause minimal prediction flipping, which indicates that these explanations do not accurately capture

Figure 10: We replicate the experiment in Figure 9, but instead use models where missingness approximations were introduced during training. This procedure fixes evaluation issues for ResNets, but does not substantially change the evaluation picture of ViTs.

the feature importance for the ViT. Thus, unlike for the CNNs, the different LIME explanations for the ViT are distinguishable from random (and quantitatively better) via the top-k ablation test.

What happens if we retrain our models with missingness augmentations? As in Section 3, we repeat the above experiment on models where 50% of the patches are removed during training. The results are reported in Figure 10. We find that the LIME explanations evaluated with the retrained CNN are now distinguishable, and the explanation generated by the same CNN outperforms the other explanations. Thus, retraining with missingness augmentation "fixes" the CNN and makes the top-k ablation test more effective by mitigating missingness bias. On the other hand, since the ViT already side-steps missingness bias by dropping tokens, the top-k ablation test does not substantially change when using the retrained model. We can thus evaluate LIME explanations directly on the original ViT without resorting to surrogate models.

5 RELATED WORK

Interpretability and model debugging. Model debugging is a common goal in interpretability research where researchers try to justify model decisions based on either local features (i.e., specific to a given input) or global ones (i.e., general biases of the model). Global interpretability methods include concept-based explanations (Bau et al., 2017; Kim et al., 2018; Yeh et al., 2020; Wong et al., 2021). They also encompass many of the robustness studies including adversarial (Szegedy et al., 2014; Goodfellow et al., 2015; Madry et al., 2018) or synthetic perturbations (Geirhos et al., 2019; Engstrom et al., 2019; Kang et al., 2019; Hendrycks & Dietterich, 2019; Xiao et al., 2020; Zhu et al., 2017) which can be cast as uncovering global biases of vision models (e.g. the model is biased to textures (Geirhos et al., 2019)). Local explanation methods, also known as *feature attribution methods*, aim to highlight important regions in the image causing the model prediction. Many of these methods use gradients to generate visual explanations, such as saliency maps (Simonyan et al., 2013; Dabkowski & Gal, 2017; Sundararajan et al., 2017). Others explain the model predictions by studying the behavior of models *with and without* certain individual features (Ribeiro et al., 2016a; Goyal et al., 2019; Fong & Vedaldi, 2017; Dabkowski & Gal, 2017; Zintgraf et al., 2017; Dhurandhar et al., 2018; Chang et al., 2019; Hendricks et al., 2018). They focus on the change in classifier outputs with respect to images where some parts are masked and replaced with various references such as random noise, mean pixel values, blur, outputs of generative models, etc.

Evaluating feature attribution methods. It is important for feature attribution methods to truly reflect why the model made a decision. Unfortunately, evaluating this is hard since we lack the ground truth of what parts of the input are important. Several works showed that visual assessment fails to evaluate attribution methods (Adebayo et al., 2018; Hooker et al., 2018; Kindermans et al., 2017; Lin et al., 2019; Yeh et al., 2019; Yang & Kim, 2019; Narayanan et al., 2018), and instead

proposed several qualitative tests as replacements. Samek et al. (2016) proposed the region perturbation method which removes pixels according to the ranking provided by the attribution maps, and measures how the prediction changes i.e., how the class encoded in the image disappears when we progressively remove information from the image. Later on, Hooker et al. (2018) proposed remove and retrain (ROAR) which showed that in order for region perturbation method to be more informative, the model has to be trained with those perturbations. Kindermans et al. (2017) posit that feature attribution methods should fulfill invariance with respect to some set of transformations, e.g. adding a constant shift to the input data. Adebayo et al. (2018) proposed several sanity checks that feature attribution methods should pass. For example, a feature attribution method should produce different attributions when evaluated on a trained model and a randomly initialized model. Zhou et al. (2021) proposed a modifying datasets such that a model must rely on a set of known and well-defined features to achieve high performance, thus offering a ground truth for feature attribution methods.

The notion of missingness. The notion of missingness is commonly used in machine learning, especially for tasks such as feature attribution (Sturmfels et al., 2020; Sundararajan et al., 2017; Hooker et al., 2018; Ancona et al., 2017). Practitioners leverage missingness in order to quantify the importance of specific features, by evaluating the model when removing the feature in the input (Ribeiro et al., 2016a; Goyal et al., 2019; Fong & Vedaldi, 2017; Dabkowski & Gal, 2017; Zintgraf et al., 2017; Dhurandhar et al., 2018; Chang et al., 2019; Sundararajan et al., 2017). For example, natural language processing, model designers often remove tokens to assign importance to individual words (Mardaoui & Garreau, 2021; Li et al., 2016). In computer vision, missingness is foundational to several interpretability methods. For example, LIME (Ribeiro et al., 2016a) iteratively turns image features on and off in order to learn the importance of each image subregion. Similarly, integrated gradients (Sundararajan et al., 2017) requires a "baseline image" that is used to represent "absence" of feature in the input. It is thus important to study missingness and how to properly approximate it for computer vision applications.

Vision transformers. Our work leverages the vision transformer (ViT) architecture, which was first proposed by Dosovitskiy et al. (2021) as a direct adaptation of the popular transformer architecture used in NLP applications (Vaswani et al., 2017) for computer vision. In particular, ViTs do not include any convolutions, instead they tokenize the image into patches which are then passed through several full layers of multi-headed self-attention. These help the transformer *globally share* information between all image regions at every layer. While convolutions must iteratively expand their receptive fields, vision transformers can immediately share information between patches throughout the entire network. ViTs recently got a lot of attention in the research community from works ranging from efficient methods for training ViTs (Touvron et al., 2020) to studying the properties of ViTs (Shao et al., 2021; Mahmood et al., 2021; Naseer et al., 2021). The work of Naseer et al. (2021) is especially related to our work as it studies the robustness of ViTs to a number of input modifications including occlusions. They find that the overall accuracy of CNNs degrades more quickly than ViTs when large regions of the input is masked. These findings complement our intuition that ResNets can experience bias when pixels are replaced with a variety of missingness approximations.

6 CONCLUSION

In this paper, we investigate how current missingness approximations result in missingness bias. We also study how this bias interferes with our ability to debug models. We demonstrate how transformer-based architectures are one possible solution, as they enable a more natural (and thus less biasing) implementation of missingness. Such architectures can indeed side-step missingness bias and are more reliable to debug in practice.

REFERENCES

Radhakrishna Achanta, Appu Shaji, Kevin Smith, Aurelien Lucchi, Pascal Fua, and Sabine Süsstrunk. Slic superpixels. Technical report, 2010.

Julius Adebayo, Justin Gilmer, Michael Muelly, Ian Goodfellow, Moritz Hardt, and Been Kim. Sanity checks for saliency maps. In *Neural Information Processing Systems (NeurIPS)*, 2018.

Marco Ancona, Enea Ceolini, Cengiz Öztireli, and Markus Gross. Towards better understanding of gradient-based attribution methods for deep neural networks. *arXiv preprint arXiv:1711.06104*, 2017.

David Bau, Bolei Zhou, Aditya Khosla, Aude Oliva, and Antonio Torralba. Network dissection: Quantifying interpretability of deep visual representations. In *Computer Vision and Pattern Recognition (CVPR)*, 2017.

Chun-Hao Chang, Elliot Creager, Anna Goldenberg, and David Duvenaud. Explaining image classifiers by counterfactual generation. In *International Conference on Learning Representations (ICLR)*, 2019.

Piotr Dabkowski and Yarin Gal. Real time image saliency for black box classifiers. In *Neural Information Processing Systems (NeurIPS)*, 2017.

Amit Dhurandhar, Pin-Yu Chen, Ronny Luss, Chun-Chen Tu, Paishun Ting, Karthikeyan Shanmugam, and Payel Das. Explanations based on the missing: Towards contrastive explanations with pertinent negatives. *arXiv preprint arXiv:1802.07623*, 2018.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, et al. An image is worth 16x16 words: Transformers for image recognition at scale. In *International Conference on Learning Representations (ICLR)*, 2021.

Logan Engstrom, Brandon Tran, Dimitris Tsipras, Ludwig Schmidt, and Aleksander Madry. Exploring the landscape of spatial robustness. In *International Conference on Machine Learning (ICML)*, 2019.

Ruth C Fong and Andrea Vedaldi. Interpretable explanations of black boxes by meaningful perturbation. In *International Conference on Computer Vision (ICCV)*, 2017.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A. Wichmann, and Wieland Brendel. Imagenet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. In *International Conference on Learning Representations (ICLR)*, 2019.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations (ICLR)*, 2015.

Yash Goyal, Ziyan Wu, Jan Ernst, Dhruv Batra, Devi Parikh, and Stefan Lee. Counterfactual visual explanations. *arXiv preprint arXiv:1904.07451*, 2019.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Lisa Anne Hendricks, Ronghang Hu, Trevor Darrell, and Zeynep Akata. Grounding visual explanations. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 264–279, 2018.

Dan Hendrycks and Thomas G. Dietterich. Benchmarking neural network robustness to common corruptions and surface variations. In *International Conference on Learning Representations (ICLR)*, 2019.

Sara Hooker, Dumitru Erhan, Pieter-Jan Kindermans, and Been Kim. A benchmark for interpretability methods in deep neural networks. *arXiv preprint arXiv:1806.10758*, 2018.

Daniel Kang, Yi Sun, Dan Hendrycks, Tom Brown, and Jacob Steinhardt. Testing robustness against unforeseen adversaries. In *ArXiv preprint arxiv:1908.08016*, 2019.

Been Kim, Martin Wattenberg, Justin Gilmer, Carrie Cai, James Wexler, Fernanda Viegas, et al. Interpretability beyond feature attribution: Quantitative testing with concept activation vectors (tcav). In *International conference on machine learning (ICML)*, 2018.

Pieter-Jan Kindermans, Sara Hooker, Julius Adebayo, Maximilian Alber, Kristof T Schütt, Sven Dähne, Dumitru Erhan, and Been Kim. The (un) reliability of saliency methods. In *arXiv preprint arXiv:1711.00867*, 2017.

Guillaume Leclerc, Hadi Salman, Andrew Ilyas, Sai Vemprala, Logan Engstrom, Vibhav Vineet, Kai Xiao, Pengchuan Zhang, Shibani Santurkar, Greg Yang, et al. 3db: A framework for debugging computer vision models. In *arXiv preprint arXiv:2106.03805*, 2021.

Jiwei Li, Xinlei Chen, Eduard Hovy, and Dan Jurafsky. Visualizing and understanding neural models in nlp. In *Proceedings of NAACL-HLT*, pp. 681–691, 2016.

Zhong Qiu Lin, Mohammad Javad Shafiee, Stanislav Bochkarev, Michael St Jules, Xiao Yu Wang, and Alexander Wong. Do explanations reflect decisions? a machine-centric strategy to quantify the performance of explainability algorithms. *arXiv preprint arXiv:1910.07387*, 2019.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations (ICLR)*, 2018.

Kaleel Mahmood, Rigel Mahmood, and Marten Van Dijk. On the robustness of vision transformers to adversarial examples. 2021.

Dina Mardaoui and Damien Garreau. An analysis of lime for text data. In *International Conference on Artificial Intelligence and Statistics*, 2021.

George A Miller. Wordnet: a lexical database for english. *Communications of the ACM*, 1995.

Menaka Narayanan, Emily Chen, Jeffrey He, Been Kim, Sam Gershman, and Finale Doshi-Velez. How do humans understand explanations from machine learning systems? an evaluation of the human-interpretability of explanation. *arXiv preprint arXiv:1802.00682*, 2018.

Muzammal Naseer, Kanchana Ranasinghe, Salman Khan, Munawar Hayat, Fahad Shahbaz Khan, and Ming-Hsuan Yang. Intriguing properties of vision transformers. *arXiv preprint arXiv:2105.10497*, 2021.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. " why should i trust you?" explaining the predictions of any classifier. In *International Conference on Knowledge Discovery and Data Mining (KDD)*, 2016a.

Marco Tulio Ribeiro, Sameer Singh, and Carlos Guestrin. "why should i trust you?": Explaining the predictions of any classifier. In *International Conference on Knowledge Discovery and Data Mining (KDD)*, 2016b.

Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, Alexander C. Berg, and Li Fei-Fei. ImageNet Large Scale Visual Recognition Challenge. In *International Journal of Computer Vision (IJCV)*, 2015.

Wojciech Samek, Alexander Binder, Grégoire Montavon, Sebastian Lapuschkin, and Klaus-Robert Müller. Evaluating the visualization of what a deep neural network has learned. *IEEE transactions on neural networks and learning systems*, 28(11):2660–2673, 2016.

Rulin Shao, Zhouxing Shi, Jinfeng Yi, Pin-Yu Chen, and Cho-Jui Hsieh. On the adversarial robustness of visual transformers. 2021.

Karen Simonyan, Andrea Vedaldi, and Andrew Zisserman. Deep inside convolutional networks: Visualising image classification models and saliency maps. *arXiv preprint arXiv:1312.6034*, 2013.

D. Smilkov, N. Thorat, B. Kim, F. Viégas, and M. Wattenberg. SmoothGrad: removing noise by adding noise. In *ICML workshop on visualization for deep learning*, 2017.

Pascal Sturmfels, Scott Lundberg, and Su-In Lee. Visualizing the impact of feature attribution baselines. *Distill*, 2020. doi: 10.23915/distill.00022. https://distill.pub/2020/attribution-baselines.

Mukund Sundararajan, Ankur Taly, and Qiqi Yan. Axiomatic attribution for deep networks. In *International Conference on Machine Learning (ICML)*, 2017.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. In *International Conference on Learning Representations (ICLR)*, 2014.

Hugo Touvron, Matthieu Cord, Matthijs Douze, Francisco Massa, Alexandre Sablayrolles, and Hervé Jégou. Training data-efficient image transformers & distillation through attention. *arXiv preprint arXiv:2012.12877*, 2020.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in Neural Information Processing Systems*, 2017.

Ross Wightman. Pytorch image models. https://github.com/rwightman/pytorch-image-models, 2019.

Eric Wong, Shibani Santurkar, and Aleksander Madry. Leveraging sparse linear layers for debuggable deep networks. In *Arxiv preprint arXiv:2105.04857*, 2021.

Kai Xiao, Logan Engstrom, Andrew Ilyas, and Aleksander Madry. Noise or signal: The role of image backgrounds in object recognition. *arXiv preprint arXiv:2006.09994*, 2020.

Mengjiao Yang and Been Kim. Benchmarking attribution methods with relative feature importance. *arXiv preprint arXiv:1907.09701*, 2019.

Chih-Kuan Yeh, Cheng-Yu Hsieh, Arun Suggala, David I Inouye, and Pradeep K Ravikumar. On the (in) fidelity and sensitivity of explanations. *Advances in Neural Information Processing Systems*, 32:10967–10978, 2019.

Chih-Kuan Yeh, Been Kim, Sercan Arik, Chun-Liang Li, Tomas Pfister, and Pradeep Ravikumar. On completeness-aware concept-based explanations in deep neural networks. *Advances in Neural Information Processing Systems (NeurIPS)*, 2020.

Matthew D Zeiler and Rob Fergus. Visualizing and understanding convolutional networks. In *European conference on computer vision*, pp. 818–833. Springer, 2014.

Yilun Zhou, Serena Booth, Marco Tulio Ribeiro, and Julie Shah. Do feature attribution methods correctly attribute features? *arXiv preprint arXiv:2104.14403*, 2021.

Zhuotun Zhu, Lingxi Xie, and Alan Yuille. Object recognition without and without objects. In *International Joint Conference on Artificial Intelligence*, 2017.

Luisa M Zintgraf, Taco S Cohen, Tameem Adel, and Max Welling. Visualizing deep neural network decisions: Prediction difference analysis. *arXiv preprint arXiv:1702.04595*, 2017.

A   EXPERIMENTAL DETAILS.

A.1   MODELS AND ARCHITECTURES

We use two sizes of vision transformers: ViT-Tiny (ViT-T) and ViT-Small (ViT-S) (Wightman, 2019; Dosovitskiy et al., 2021). We compare to residual networks of similar size: ResNet-18 and ResNet-50 (He et al., 2016), respectively. These architectures and their corresponding number of parameters are summarized in Table 1.

Table 1: A collection of neural network architectures we use in our paper.

Architecture	ViT-T	ResNet-18	ViT-S	ResNet-50
Params	5M	12M	22M	26M

A.2   TRAINING DETAILS

We train our models on ImageNet (Russakovsky et al., 2015), with a custom (research, non-commercial) license, as found here `https://paperswithcode.com/dataset/imagenet`. For all experiments in this paper, we consider 10,000 image subset of the original ImageNet validation set (we take every 5th image).

1. For ResNets, we train using SGD with batch size of 512, momentum of 0.9, and weight decay of 1e-4. We train for 90 epochs with an initial learning rate of 0.1 that drops by a factor of 10 every 30 epochs.
2. For ViTs, we use the same training scheme as used in Wightman (2019).

Note that we use the same (basic) data-augmentation techniques for both ResNets and ViTs. Specifically, we only use random resized crop and random horizontal flip (no RandAug, CutMix, MixUp, etc.).

We attach all our model weights to the submission.

Models trained with missingness augmentations.   In Sections 3 and 4, we also consider models that were augmented with missingness approximations during training (inspired by ROAR (Hooker et al., 2018), see Appendix E for further discussion). We retrain our models by randomly removing 50% of the patches (by blacking out for ResNet and dropping the respective tokens for ViT). The other training hyperparameters are maintained the same as the standard models above.

Infrastructure.   We use an internal cluster containing NVIDIA 1080-TI, 2080-TI, V100, and A100 GPUs for all our training and analysis.

A.3   EXPERIMENTAL DETAILS FOR SECTION 3

For the experiments in Section 3, we iteratively remove subregions from the input. In the main paper, we consider removing 16×16 patches: we black out patches for the ResNet-50 and drop the corresponding token for the ViT-S. We consider other patch sizes as well as superpixels in Appendix C.

We consider removing patches in three orders: random, most salient, and least salient. We use saliency as a rough heuristic for relevance to the image (typically, more salient regions tend to be in the foreground and less salient regions in the background). For all models, we determine the salience of an image subregion as the mean value of that subregion for a standard ResNet-50's saliency map (the order of patches removed is thus the same for both the ResNet and the ViT).

A.4   EXPERIMENTAL DETAILS FOR SECTION 4

Overview on LIME.   Local interpretable model-agnostic explanations (LIME) Ribeiro et al. (2016b) is a common method for feature attribution. Specifically, LIME proceeds by generating

perturbations of the image, where in each perturbation the subregions are randomly turned on or off. For ResNets, we turn off subregions by masking them with some baseline color, while for ViTs we drop the associated tokens. After evaluating these perturbations with the model, we fit classifier using Ridge Regression to predict the value of the logit of the original predicted class given the presence of each subregion. The LIME explanation is then the weight of each subregion in the ridge classifier (these are often referred to as LIME scores). We perform LIME with 1000 perturbations, and include an implementation of LIME in our attached code.

Implementation details for LIME consistency plots. For the experiment in Figure 8, we evaluate LIME using 8 different baseline colors (the colors are generated by setting the R, G, and B values as either 0 or 1). Then, for each pair of colors, we measure the similarity of their top-k feature sets according to their LIME scores for varying k (using Jaccard similarity) averaged over 10,000 examples. We plot the average over the 28 pairs of colors.

B IMPLEMENTING MISSINGNESS BY DROPPING TOKENS IN VISION TRANSFORMERS

As described in Section 2.2, the token-centric nature of vision transformers enables a more natural implementation of missingness: simply drop the tokens that correspond to the removed image sub-regions. In this section, we provide a more detailed description of dropping tokens, as well as a few implementation considerations.

Recall that a ViT has two stages when processing an input image **x**.

- **Tokenization:** **x** is split into 16×16 patches and positionally encoded into tokens.
- **Self-Attention:** The set of tokens is passed through several self-attention layers and produces a class label.

After the initial tokenization step, the self-attention layers of the transformer deal solely with sets of tokens, rather than a constructed image. This set is not constrained to a specific size. Thus, after the patches have all be tokenized, we can remove the tokens that correspond to removed regions of the input before passing the reduced set to the self-attention layers. The remaining tokens retain their original positional encodings.

Our attached code includes an implementation of the vision transformer which takes in an optional argument of the indices of tokens to drop. Our implementation can also handle varying token lengths in a batch (we use dummy tokens and then mask the self-attention layers appropriately).

Dropping tokens for superpixels and other patch sizes   In the main body of the paper, we deal with 16×16 image subregions, which aligns nicely with the tokenization of vision transformers. In Appendix C, we consider other patch sizes that do not align along the token boundaries, as well as irregularly shaped superpixels. In these cases, we conservatively drop the token if any portion of the token was supposed to be removed (we thus remove a slightly larger subregion).

C ADDITIONAL EXPERIMENTS (SECTION 3)

C.1 ADDITIONAL EXAMPLES OF THE BIAS (SIMILAR TO FIGURE 2).

In Figure 11, we display more examples that qualitatively demonstrate the missingness bias.

Figure 11: Further examples of removing 75 16×16 patches from ImageNet images. The images are blacked out for ResNet-50, and the corresponding tokens are dropped for ViT-S. While ResNet-50 skews toward classes that are unrelated to the remaining image features (i.e crossword, jigsaw puzzle), the ViT-S either maintains its original prediction or predicts a reasonable label given remaining image features.

C.2 Bias for removing patches in various orders

In this section, we display results for the experiments in Section 3 where we remove patches in 1) random order 2) most salient first and 3) least salient first (Figure 12). We find that missingness approximations skew the output distribution for ResNets regardless of what order we remove the patches. Similarly, we find that the ResNet's predictions flip rapidly in all three cases (though to varying extents). Finally, the ViT mitigates the impact of missingness bias in all three cases.

(a) The shift in the output class distribution after applying missingness approximations in different orders.

(b) Degradation in class entropy (left), the fraction of predictions that change (middle), and the average Word-Net similarity if the prediction changes after masking (right) as we remove patches from the image in different orders.

Figure 12: Full experiments for removing 16×16 patches by blacking out (ResNet-50) or dropping tokens (ViT-S).

C.3 COMPARISON OF DROPPING TOKENS VS BLACKING OUT PIXELS FOR VITS

We compare dropping tokens for ViTs to blacking out pixels. Here, we present a condensed version of the experiments in Section 3, and include the ViT-S with blacking out pixels instead of dropping tokens (Figure 13). We find that using a ViT instead of a ResNet significant mitigates missingness bias on all three metrics. However, dropping tokens for ViTs mitigates missingness bias more effectively than simply blacking out pixels.

Figure 13: We compare dropping tokens vs blacking out pixels for ViTs.

C.4 RESULTS FOR DIFFERENT ARCHITECTURE SIZES

In Figure 14, we repeat the experiments in Section 3, but with a ViT-T and ResNet-18. These results parallel our findings in the main paper.

Figure 14: We repeat the setup in Section 3, with a ViT-T and ResNet-18.

C.5 RESULTS FOR DIFFERENT MISSINGNESS APPROXIMATIONS

In this section, we consider missingness approximations other than blacking out pixels. In Figure 15, we use three baselines: a) the mean RGB value of the dataset, b) a randomly selected baseline color for each image, and c) a randomly selected color for each pixel Sturmfels et al. (2020); Sundararajan et al. (2017). Since we drop tokens for the vision transformers, changing the baseline color does not change the behavior for the ViTs. Our findings in the main paper for blacking out patches closely mirror the findings for other baselines.

(a) Using the mean ImageNet RGB value for the baseline color

(b) Picking a random baseline color for each image.

(c) Picking a random baseline color for each pixel.

Figure 15: Using different baseline colors for masking pixels.

We also consider blurring the removed features, as suggested in Fong & Vedaldi (2017). We use a gaussian blur with kernel size 21 and $\sigma = 10$. Examples of blurred images can be found in Figure 16a. Unlike the previous missingness approximations, *this method does not fully remove subregions of the input*; thus, blurring the pixels can still leak information from the removed regions, which can then influence the model's prediction. Indeed, we find that, by visual inspection, we can still roughly distinguish the label of images that are entirely blurred (as in Figure 16a).

For completeness, we repeat the experiments in Section 3 using the blurred image as the missingness approximation (Figure 16b). We find that ResNets still experience missingness bias, though the bias is reduced compared to using an image-independent baseline color.

(a) Examples of blurring ImageNet images.

(b) Repeating the experiments in Section 3 using the blurred ImageNet image.

Figure 16: Using the blurred image for the missingness approximation.

C.6 USING DIFFERENTLY SIZED PATCHES

In the main body of the paper, we consider image subregions of 16×16. In this section, we consider subregions of other patch size: 14×14, 28×28, 32×32, and 56×56. As mentioned in Appendix Section B, when dropping tokens for the ViT, we conservatively drop the token if *any* part of the corresponding image subregion is being removed. Thus, the ViT removes slightly more area than the ResNet for patch sizes that are not multiples of 16. We find that the ResNet is impacted by missingness bias regardless of the patch size, though the effects of the bias is reduced for very large patch sizes (see Figure 17).

Figure 17: Using different baseline colors for masking pixels.

C.7 USING SUPERPIXELS INSTEAD OF PATCHES

Thus far, we have used square patches. What if we instead use superpixels? In this section, we compute the SLIC segmentation of superpixels (Achanta et al., 2010). In order to keep the superpixels roughly the same size (and of a more similar size as the patches in the paper), we consider the images having more than 130 superpixels. We display examples of the superpixels in Figure 18a.

We then repeat our experiments from Section 3, and analyze our models' predictions after removing 50 superpixels in different orders (blacking out for ResNets and dropping tokens for ViTs). As described in Section B, we conservatively drop all tokens for ViTs that contain any pixels that should have been removed. We find that ResNets are significantly impacted by missingness bias when masking out superpixels. As in the case of patches, dropping tokens through the ViT substantially mitigates the missingness bias.

(a) Examples of superpixel segmentations.

(b) Measuring the impact of removing superpixels through missingness approximations.

Figure 18: Using SLIC superpixels instead of patches

D ADDITIONAL EXPERIMENTS (SECTION 4)

D.1 EXAMPLES OF LIME

In this section, we display further examples of LIME explanations for ViT-S, ResNet-50, and a ResNet-50 retrained with missingness augmentations (Figure 19). As we explain in Section 4, LIME relies heavily on the notion of missingness, and can be subject to missingness bias. We note that the ViT-S and retrained ResNets qualitatively have more human-aligned LIME explanations (by highlighting patches in the foreground over patches in the background) compared to a standard ResNet. While human-alignment does not a guarantee that the LIME explanation is good (the model might be relying on non-aligned features), we do see a substantial difference in the explanations of models robust to the missingness bias (ViTs and retrained ResNet) and models suffering from this bias (standard ResNet).

Figure 19: Examples of LIME explanations

Figure 20: Top K ablation test using superpixels instead of patches.

D.2 TOP-K ABLATION TEST WITH SUPERPIXELS.

We repeat the top-k ablation test in Section 4, using superpixels instead of patches (Figure 20). The setup for superpixels is that same as that described in Appendix C.7. After generating LIME explanations for a ViT and ResNet-50, we evaluate these explanations using the top-k ablation test. As we found for 16×16 patches, the explanations when evaluating with a ResNet are less distinguishable than when evaluating for a ViT: even masking features according to the random explanations rapidly flips the predictions. We do find that masking random superpixels seems to have a greater effect on ViTs than masking random 16×16 patches: this is likely because the superpixels are on average larger.

E RELATIONSHIP TO ROAR

Here, we present more details about the ROAR experiment of Section 3.

E.1 OVERVIEW ON ROAR

Evaluating feature attribution methods requires the ability to remove features from the input to assess how important these features are to the model's predictions. To do so properly, Hooker et al. (2018) argue that re-training (with removing pixels) is required so that images with removed features stay in-distribution. Their argument holds since machine learning models typically assume that the train and the test data comes from a similar distribution.

So, they propose *RemOve and Retrain (ROAR)* where new models (of the exact same architecture) are *retrained* such that random pixels are blacked out during training. The intuition is that this way, removing pixels do not render images out-of-distribution. Overall, they were able to better assess how much removing information from the image affects the predictions of the model using those retrained surrogate models.

The authors of ROAR list several downsides for their approach though. In particular, retraining models can be computationally expensive. More pressingly, the retrained model is *not* the same model that they analyze, but instead a surrogate with a substantially different training procedure: any feature attribution or model debugging result inferred from the retrained model might not hold for the original model. Given these downsides, is retraining always necessary?

E.2 VITS DO NOT REQUIRE RETRAINING

Here, we show that retraining is not always necessary: indeed for ViTs, we do not need to retraining to be able to properly evaluate feature attribution methods. While ROAR in (Hooker et al., 2018) dealt with blacking out features on a per-pixel level, we adapt their approach for masking out larger contiguous regions (like patches). If we apply missingness approximations during training as in ROAR, missingness approximations are now in-distribution, and thus would likely mitigate the observed biases.

We retrain a ResNet-50 and a ViT-S by randomly removing 50% of patches during training (through blacking out pixels for the ResNet-50 and dropping tokens for the ViT-S). Our goal is to compare the behavior of each model to its retrained counterpart. If retraining does not change the model's behavior when missingness approximations are applied, retraining would be unnecessary, and we can instead confidently use the original model. In Figure 5, we measure the fraction of images where the model changes its prediction as we remove image features for both the standard and retrained models. We find that, while there is a significant gap in behavior between the standard and retrained CNNs, the standard and retrained ViTs behave largely the same..

This result indicates that, while retraining is important when analyzing CNNs, it is unnecessary for ViTs: we can instead intervene on the original model. We thus avoid the expense of training the augmented models, and can perform feature attribution on the actual model instead of a proxy.