Transition to Linearity of General Neural Networks with Directed Acyclic Graph Architecture

Abstract

In this paper we show that feedforward neural networks corresponding to arbitrary directed acyclic graphs undergo transition to linearity as their "width" approaches infinity. The width of these general networks is characterized by the minimum in-degree of their neurons, except for the input and first layers. Our results identify the mathematical structure underlying transition to linearity and generalize a number of recent works aimed at characterizing transition to linearity or constancy of the Neural Tangent Kernel for standard architectures.

1 Introduction

A remarkable property of wide neural networks, first discovered in [10] in terms of the constancy of the Neural Tangent Kernel along the optimization path, is that they transition to linearity (using the terminology from [14]), i.e., are approximately linear in a ball of a fixed radius. There has been an extensive study of this phenomenon for different types of standard neural networks architectures including fully-connected neural networks (FCNs), convolutional neural networks (CNNs), ResNets [12, 4, 3, 7]. Yet the scope of the transition to linearity and the underlying mathematical structure has not been made completely clear.

In this paper, we show that the property of transition to linearity holds for a much broader class of neural networks, feedforward neural networks. The architecture of a feedforward neural network can generically be described by a DAG [26, 25, 16]: the vertices and the edges correspond to the neurons and the trainable weight parameters of a neural network, respectively. This DAG structure includes standard network architectures e.g., FCNs, CNNs, ResNets, as well as DenseNets [9] and networks with dropout [20], whose property of transition to linearity has not been studied in literature. This generalization shows that the transition to linearity, or the constant Neural Tangent Kernel, does not depend on the specific designs of the networks, and is a more fundamental and universal property.

We define the width of a feedforward neural network as the minimum in-degree of all neurons except for the input and first layers, which is a natural generalization of the the minimum number of neurons in hidden layers which is how the width is defined for standard architectures. For a feedforward neural network, we show it transitions to linearity if its width goes to infinity as long as the in-degrees of individual neurons are bounded by a polynomial of the network width. Specifically, we control the deviation of the network function from its linear approximation by the spectral norm of the Hessian of the network function, which, as we show vanishes in a ball of fixed radius, in the infinite width limit. Interestingly, we observe that not only the output neurons, but any pre-activated neuron in the hidden layers of a feedforward neural network can be regarded as a function with respect to its parameters, which will also transition to linearity as the width goes to infinity.

The key technical difficulty is that all existing analyses for transition to linearity or constant NTK do not apply to this general DAG setting. Specifically, those analyses assume in-degrees of neurons are

either the same or proportional to each other up to a constant ratio [5, 12, 3, 27, 14, 2]. However, the general DAG setting allows different scales of neuron in-degrees, for example, the largest in-degree can be polynomially large in the smallest in-degree. In such scenarios, the $(2, 2, 1)$-norm in [14] and the norm of parameter change in [5, 12] scales with the maximum of in-degrees which causes a trivial bound on the NTK change. Instead, we introduce a different set of tools based on the tail bound for the norm of matrix Gaussian series [23]. Specifically, we show that the Hessian of the network function takes the form of matrix Gaussian series, whose matrix variance relies on the Hessian of connected neurons. Therefore, we reconcile the in-degree difference by building a recursive relation between the Hessian of neurons, which exactly cancels out the in-degree with the scaling factor.

Transition to linearity helps understand the training dynamics of wide neural networks and plays an important role in developing the optimization theory for them, as has been shown for certain particular wide neural networks [6, 5, 4, 12, 28, 27]. While transition to linearity is not a necessary condition for successful optimization, it provides a powerful tool for analyzing optimization for many different architectures. Specifically, transition to linearity in a ball of sufficient radius combined with a lower bound on the norm of the gradient at its center is sufficient to demonstrate the PL^* condition [13] (a version of the Polyak-Łojasiewicz condition [19, 15]) which ensures convergence of optimization. We discuss this connection and provide one such lower bound in Section 4.

Summary of contributions. We show the phenomenon of transition to linearity in general feedforward neural networks corresponding to a DAG with large in-degree. Specifically, under the assumption that the maximum in-degree of its neurons is bounded by a polynomial of the width m (the minimum in-degree), we prove that the spectral norm of the Hessian of a feedforward neural network is bounded by $\tilde{O}(1\sqrt{m})$ in an $O(1)$ ball. Our results generalize the existing literature on the linearity of wide feedforward neural networks. We discuss connections to optimization. Under additional assumptions we show that the norm of the gradient of a feedforward neural network is bounded away from zero at initialization. Together with the Hessian bound this implies convergence of gradient descent for the loss function.

1.1 Notations

We use bold lowercase letters, e.g., $\mathbf{w}$, to denote vectors, capital letters, e.g., A, to denote matrices, and bold capital letters, e.g., $\mathbf{H}$, to denote higher order tensors or matrix tuples. For a matrix A, we use $A_{[i,:]}$ to denote its i-th row and $A_{[:,i]}$ to denote its j-th column.

We use $\nabla_{\mathbf{w}} f(\mathbf{w}_0)$ to denote the gradient of f with respect to $\mathbf{w}$ at $\mathbf{w}_0$, and $H_f(\mathbf{w})$ to denote Hessian matrix (second derivative) of f with respect to $\mathbf{w}$. For vectors, we use $\|\cdot\|$ to denote Euclidean norm. For matrices, we use $\|\cdot\|$ to denote spectral norm and $\|\cdot\|_F$ to denote Frobenius norm. We use $\|\cdot\|_\infty$ to denote function L_∞ norm. For a set $\mathcal{S}$, we use $|\mathcal{S}|$ to denote the cardinality of the set. For $n > 0$, $[n]$ denotes the set $\{1, 2, ..., n\}$.

We use big-O notation to hide constant factors, and use big-$\tilde{O}$ notation to additionally hide logarithmic factors. In this paper, the argument of $O/\tilde{O}(\cdot)$ is always with respect to the network width.

Given a vector $\mathbf{w}$ and a constant $R > 0$, we define a Euclidean ball $\mathsf{B}(\mathbf{w}, R)$ as:

$$\mathsf{B}(\mathbf{w}, R) := \{\mathbf{v} : \|\mathbf{v} - \mathbf{w}\| \leq R\}. \tag{1}$$

2 Neural networks with acyclic graph architecture

In this section, we provide a definition and notation for general feedforward neural networks with an arbitrary DAG structure. This definition includes standard feedforward neural network architectures, such as FCNs, DenseNet and CNNs.

2.1 Defining feedforward neural networks

Graph Structure. Consider a directed acyclic graph (DAG) $\mathcal{G} = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V}$ and $\mathcal{E}$ denote the sets of vertices and edges, respectively. See the left panel of Figure 1, for an illustrative example. For a directed edge $e \in \mathcal{E}$, we may also use the notation $e = (v_1, v_2)$ to explicitly write out the start vertex v_1 and end vertex v_2.

Figure 1: **Left panel: An example of directed acyclic graph.** v_1, v_2 and v_3 are three vertices and e_1, e_2 are two edges of the graph. v_3 has two incoming edges e_1 and e_2 which connects to v_1 and v_2 respectively. **Right panel: Organizing the vertices into layers.** The vertices with 0 in-degree are in 0-th layer (or input layer), and last layer are called output layer in which the vertices have 0 out-degree. Note that the layer index is determined by the longest path from the inputs $\mathcal{V}_{\text{input}}$, for example, the neuron in layer 3.

For a vertex $v \in \mathcal{V}$, we denote its in-degree, $\text{in}(v)$, by the number of incoming edges (edges that end with it):

$$\text{in}(v) = |\mathcal{S}_{\text{in}}(v)|, \quad \text{with } \mathcal{S}_{\text{in}}(v) := \{u \in \mathcal{V} : (u, v) \in \mathcal{E}\}.$$

Similarly, for a vertex $v \in \mathcal{V}$, we denote its out-degree $\text{out}(v)$ by the number of outgoing edges (edges that start from it):

$$\text{out}(v) = |\mathcal{S}_{\text{out}}(v)|, \quad \text{with } \mathcal{S}_{\text{out}}(v) := \{u \in \mathcal{V} : (v, u) \in \mathcal{E}\}.$$

We call the set of vertices with zero in-degrees *input*: $\mathcal{V}_{\text{input}} = \{v \in \mathcal{V} : \text{in}(v) = 0\}$, and the set of vertices with zero out-degrees *output* $\mathcal{V}_{\text{output}} = \{v \in \mathcal{V} : \text{out}(v) = 0\}$.

Definition 2.1. For each vertex $v \in \mathcal{V}\backslash\mathcal{V}_{\text{input}}$, its distance $p(v)$, to the input $\mathcal{V}_{\text{input}}$, is defined to be the maximum length of all paths that start from a vertex within $\mathcal{V}_{\text{input}}$ and end with v.

It is easy to check that $p(v) = 0$ if $v \in \mathcal{V}_{\text{input}}$.

Feedforward neural network. Based on a given DAG architecture, we define the feedforward neural network. Each individual vertex corresponds to a neuron additionally equipped with a scalar function (also called activation function). Each edge is associated with a real-valued weight, a trainable parameter. Each neuron is defined as a function of the weight parameters and the adjacent neurons connected by its incoming edges. The feedforward neural network is considered as the output neurons, corresponding to the output $\mathcal{V}_{\text{output}}$, of all weight parameters and input neurons which correspond to the input $\mathcal{V}_{\text{input}}$. Formally, we define the feedforward neural network as follows.

Definition 2.2 (Feedforward neural network). Consider a DAG $\mathcal{G} = (\mathcal{V}, \mathcal{E})$. For each vertex $v \in \mathcal{V}\backslash\mathcal{V}_{\text{input}}$, we associate it with an activation function $\sigma_v(\cdot) : \mathbb{R} \to \mathbb{R}$ and each of its incoming edges $e = (u, v) \in \mathcal{E}$ with a weight variable $w_e = w_{(u,v)}$. Then we define the following functions:

$$f_v = \sigma_v(\tilde{f}_v), \quad \tilde{f}_v = \frac{1}{\sqrt{\text{in}(v)}} \sum_{u \in \mathcal{S}_{\text{in}}(v)} w_{(u,v)} f_u. \tag{2}$$

When $v \in \mathcal{V}_{\text{input}}$, f_v is prefixed as the input data, and we denote $f_{\text{input}} := \{f_v : v \in \mathcal{V}_{\text{input}}\}$. For $v \notin \mathcal{V}_{\text{input}}$, we call f_v *neurons* and $\tilde{f}_v$ *pre-activations*. With necessary composition of functions, each f_v, and $\tilde{f}_v$, can be regarded as a function of all related weight variables and inputs f_{input}. The *feedforward neural network* is defined to be the function corresponding to the output $\mathcal{V}_{\text{output}}$:

$$f(\mathcal{W}; f_{\text{input}}) := f_{\text{output}} = \{f_v : v \in \mathcal{V}_{\text{output}}\}, \tag{3}$$

where $\mathcal{W} := \{w_e : e \in \mathcal{E}\}$ denotes the set of all the weight variables.

Remark 2.3. The validity of the definition is guaranteed by the fact that the DAG is acyclic. It makes sure that the dependence of each function f_v on other neurons can pass all the way down to the input f_{input}, through Eq. (2).

Remark 2.4. For $v \in \mathcal{V}_{\text{input}} \bigcup \mathcal{V}_{\text{output}}$, we use the identity function $\mathbb{I}(\cdot)$ as the activation functions.

Weight initialization and inputs. Each weight parameter $w_e \in \mathcal{W}$ is initialized i.i.d. following the standard normal distribution i.e., $\mathcal{N}(0, 1)$. The inputs are considered given, usually determined by datasets. Under this initialization, we introduce the scaling factor $1/\sqrt{\text{in}(v)}$ in Eq. (5) to control the value of neurons to be of order $O(1)$. Note that this initialization is an extension of the NTK initialization [10], which was defined for FCNs therein.

Generality of DAG architecture. The feedforward neural networks include FCNs, CNNs, DenseNets [9] as special examples. Notably, neural networks with dropout layers [20], whose property of transition to linearity has not been studied in literature, also fit into our definition. Please see detailed discussions in Appendix A. We note that our definition of feedforward neural networks does not directly include networks with skip connection, e.g., ResNets. However, as shown in Appendix D, our main results still apply with skip connections present. Therefore, architectures that are the combination of FCNs, CNNs, ResNets, etc., are included within our framework [11, 21, 8, 22].

2.2 Organizing feedforward networks into layers

The architecture of the feedforward neural network is determined by the DAG $\mathcal{G}$. The complex structures of DAGs often lead to complicated neural networks, which are hard to analyze.

For the ease of analysis, we organize the neurons of the feedforward neural network into *layers*, which are sets of neurons.

Definition 2.5 (Layers). Consider a feedforward neural network f and its corresponding graph structure $\mathcal{G}$. A layer of the network is defined to be the set of neurons which have the same distance p to the inputs. Specifically, the ℓ-th layer, denoted by $f^{(\ell)}$, is

$$f^{(\ell)} = \{f_v : p(v) = \ell, v \in \mathcal{V}, \ell \in \mathbb{N}\}. \tag{4}$$

It is easy to see that the layers are mutually exclusive, and the layer index ℓ is labeled from 0 to ℓ, where $L + 1$ is the total number of layers in the network. As $p(v) = 0$ if and only if $v \in \mathcal{V}_{\text{input}}$, the 0-th layer $f^{(0)}$ is exactly the input layer f_{input}. The right panel of Figure 1 provides an illustrative example of the layer structures.

In general, the output neurons f_{output} (defined in Eq. (3)) do not have to be in the same layer. For the convenience of presentation and analysis, we assume that all the output neurons are in the last layer, i.e., layer ℓ, which is the case for most of commonly used neural networks, e.g., FCNs and CNNs. Indeed, our analysis applies to every output neuron (see Theorem 3.8), even if they are not in the same layer.

With the notion of network layers, we rewrite the neuron functions Eq. (2), as well as related notations, to reflect the layer information.

For ℓ-layer, $\ell = 0, 1, \cdots, L$, we denote the total number of neurons as d_ℓ, and rewrite the layer function $f^{(\ell)}$ into a form of vector-valued function

$$f^{(\ell)} = \left(f_1^{(\ell)}, f_2^{(\ell)}, ..., f_{d_\ell}^{(\ell)} \right)^T,$$

where we use $f_i^{(\ell)}$ with index $i = 1, 2, \cdots, d_\ell$ to denote each individual neuron. Correspondingly, we denote its vertex as $v_i^{(\ell)}$, and $\mathcal{S}_i^{(\ell)} := \mathcal{S}_{\text{in}}(v_i^{(\ell)})$. Hence, the in-degree $\text{in}(v_i^{(\ell)})$, denoted as $m_i^{(\ell)}$ here, is equivalent to the cardinality of the set $\mathcal{S}_i^{(\ell)}$.

Remark 2.6. Note that $m_i^{(\ell)}$, with the superscript ℓ, denotes an in-degree, i.e., the number of neurons that serve as direct inputs to the current neuron in ℓ-th layer. In the context of FCNs, $m_i^{(\ell)}$ is equivalent to the size of its previous layer, i.e., $(\ell - 1)$-th layer, and is often denoted as $m^{(\ell-1)}$ in literature.

To write the summation in Eq. (2) as a matrix multiplication, we further introduce the following two vectors: (a), $f_{\mathcal{S}_i^{(\ell)}}$ represents the vector that consists of neuron components f_v with $v \in \mathcal{S}_i^{(\ell)}$; (b), $\mathbf{w}_i^{(\ell)}$ represents the vector that consists of weight parameters $w_{(u, v_i^{(\ell)})}$ with $u \in \mathcal{S}_i^{(\ell)}$. Note that both vectors $f_{\mathcal{S}_i^{(\ell)}}$ and $\mathbf{w}_i^{(\ell)}$ have the same dimension $m_i^{(\ell)}$.

With the above notation, the neuron functions Eq. (2) can be equivalently rewritten as:

$$f_i^{(\ell)} = \sigma_i^{(\ell)}(\tilde{f}_i^{(\ell)}), \quad \tilde{f}_i^{(\ell)} = \frac{1}{\sqrt{m_i^{(\ell)}}} \left(\mathbf{w}_i^{(\ell)}\right)^T f_{\mathcal{S}_i^{(\ell)}}. \tag{5}$$

For any $\ell \in [L]$, we denote the weight parameters corresponding to all incoming edges toward neurons at layer ℓ by

$$\mathbf{w}^{(\ell)} := \left((\mathbf{w}_1^{(\ell)})^T, ..., (\mathbf{w}_{d_\ell}^{(\ell)})^T\right)^T \quad \ell \in [L]. \tag{6}$$

Through the way we define the feedforward neural network, the output of the neural network is a function of all the weight parameters and the input data, hence we denote it by

$$f(\mathbf{w}; \boldsymbol{x}) := f^{(\ell)} = \left(f_1^{(\ell)}, ..., f_{d_\ell}^{(\ell)}\right)^T, \tag{7}$$

where $\mathbf{w}$ is the collection of all the weight parameters, i.e., $\mathbf{w} := \left((\mathbf{w}^{(1)})^T, ..., (\mathbf{w}^{(\ell)})^T\right)^T \in \mathbb{R}^{\sum_\ell \sum_i m_i^{(\ell)}}$.

With all the notations, for a feedforward neural network, we formally define the width of it:

Definition 2.7 (Network width). The width m of a feedforward neural network is the minimum in-degree of all the neurons except those in the input and first layers:

$$m := \inf_{\ell \in \{2, ..., L-1\}, i \in [d_\ell]} m_i^{(\ell)}. \tag{8}$$

Remark 2.8. Note that, the network width m is determined by the in-degrees of neurons except for the input and first layers, and not necessarily relates the number of neurons in hidden layers. But for certain architectures e.g., FCNs, these two coincide that the minimum in-degree after the first layer is the same as the minimum hidden layer size.

We say a feedforward neural network is *wide* if its width m is large enough. In this paper, we consider wide feedforward neural networks with a fixed number of layers.

3 Transition to linearity of feedforward neural networks

In this section, we show that the feedforward neural networks exhibit the phenomenon of transition to linearity, which was previously observed in specific types of neural networks.

Specifically, we prove that a feedforward neural network $f(\mathbf{w}; \boldsymbol{x})$, when considered as a function of its weight parameters $\mathbf{w}$, is arbitrarily close to a *linear* function in the ball $B(\mathbf{w}_0, R)$ given constant $R > 0$, where $\mathbf{w}_0$ is randomly initialized, as long as the width of the network is sufficiently large.

First, we make the following assumptions on the input $\boldsymbol{x}$ and the activation functions:

Assumption 3.1. The input is uniformly upper bounded, i.e., $\|\boldsymbol{x}\|_\infty \leq C_{\boldsymbol{x}}$ for some constant $C_{\boldsymbol{x}} > 0$.

Assumption 3.2. All the activation functions $\sigma(\cdot)$ are twice differentiable, and there exist constants $\gamma_0, \gamma_1, \gamma_2 > 0$ such that, for all activation functions, $|\sigma(0)| \leq \gamma_0$ and the following Lipschitz continuity and smoothness conditions are satisfied

$$|\sigma'(z_1) - \sigma'(z_2)| \leq \gamma_1 |z_1 - z_2|,$$
$$|\sigma''(z_1) - \sigma''(z_2)| \leq \gamma_2 |z_1 - z_2|,$$

for any $z_1, z_2 \in \mathbb{R}$.

We note that the above two assumptions are very common in literature. Although ReLU does not satisfy Assumption 3.2 due to non-differentiability at point 0, we believe our main claims still hold as ReLU can be approximated arbitrarily closely by some differentiable function which satisfies our assumption.

Remark 3.3. By assuming all the activation functions are twice differentiable, it is not hard to see that the feedforward neural network i.e., Eq. (7) is also twice differentiable.

Taylor expansion. To study the linearity of a general feedforward neural network, we consider its Taylor expansion with second order Lagrange remainder term. Given a point $\mathbf{w}_0$, we can write the network function $f(\mathbf{w})$ (omitting the input argument for simplicity) as

$$f(\mathbf{w}) = \underbrace{f(\mathbf{w}_0) + (\mathbf{w} - \mathbf{w}_0)^T \nabla_{\mathbf{w}} f(\mathbf{w}_0)}_{f_{\mathrm{lin}}(\mathbf{w})} + \underbrace{\frac{1}{2}(\mathbf{w} - \mathbf{w}_0)^T H_f(\xi)(\mathbf{w} - \mathbf{w}_0)}_{\mathcal{R}(\mathbf{w})}, \qquad (9)$$

where ξ is a point on the line segment between $\mathbf{w}_0$ and $\mathbf{w}$. Above, $f_{\mathrm{lin}}(\mathbf{w})$ is a linear function and $\mathcal{R}(\mathbf{w})$ is the Lagrange remainder term. Here we assume the output dimension of the network function is one. The same analysis can be applied to multiple outputs (see Corollary C.1).

In the rest of the section, we will show that in a ball $\mathsf{B}(\mathbf{w}_0, R)$ of any constant radius $R > 0$,

$$|\mathcal{R}(\mathbf{w})| = \tilde{O}\left(\frac{1}{\sqrt{m}}\right) \qquad (10)$$

where m is the network width (see Definition 2.7). Hence, $f(\mathbf{w})$ can be arbitrarily close to its linear approximation $f_{\mathrm{lin}}(\mathbf{w})$ with sufficiently large m.

Remark 3.4. For a general function, the remainder term $\mathcal{R}(\mathbf{w})$ is not expected to vanish at a finite distance from $\mathbf{w}_0$. Hence, the transition to linearity in the ball $\mathsf{B}(\mathbf{w}_0, R)$ is a non-trivial property. On the other hand, the radius R can be set to be large enough to contain the whole optimization path of GD/SGD for various types of wide neural networks (see [13, 28], also indicated in [6, 5, 27, 12]). In Section 4, we will see that such a ball is also large enough to cover the whole optimization path of GD/SGD for the general feedforward neural networks. Hence, to study the optimization dynamics of wide feedforward neural networks, this ball is large enough.

To prove Eq. (10), we make an assumption on the width m:

Assumption 3.5. The maximum in-degree of any neuron is at most polynomial in the network width m:

$$\sup_{\ell \in \{2,...,L-1\}, i \in [d_\ell]} m_i^{(\ell)} = O(m^c),$$

where $c > 0$ is a constant.

This assumption puts a constraint on the neurons with large in-degrees such that the in-degrees cannot be super-polynomially large compared to m. A natural question is whether this constraint is necessary, for example, do our main results still hold in cases some in-degrees are exponentially large in m? While we believe the answer is positive, we need this assumption to apply the proof techniques. Specifically, we apply the tail bound for the norm of matrix Gaussian series [23], where there is a dimension factor equivalent to the number of weight parameters. Thus an exponentially large dimension factor would result in useless bounds. It is still an open question whether the dimension factor in the bound can be removed or moderated (see the discussion after Theorem 4.1.1 in [23]).

With these assumptions, we are ready to present our main result:

Theorem 3.6 (Scaling of the Hessian norm). *Suppose Assumption 3.1, 3.2 and 3.5 hold. Given a fixed $R > 0$, for all $\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)$, with probability at least $1 - \exp(-\Omega(\log^2 m))$ over the random initialization $\mathbf{w}_0$, each output neuron f_k of a feedforward neural network satisfies*

$$\|H_{f_k}(\mathbf{w})\| = \tilde{O}\left(\frac{1}{\sqrt{m}}\right), \quad k \in [d_\ell]. \qquad (11)$$

This theorem states that the Hessian matrix, as the second derivative with respect to weight parameters $\mathbf{w}$, of any output neuron can be arbitrarily small, if the network width is sufficient large.

Note that Eq. (11) holds for all $\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)$ with high probability over the random initialization $\mathbf{w}_0$. The basic idea is that, the spectral norm of Hessian can be bounded at the center of the ball, i.e., $\mathbf{w}_0$, though probability bounds due to the randomness of $\mathbf{w}_0$. For all other points $\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)$, the distance $\|\mathbf{w} - \mathbf{w}_0\|$, being no greater than R, controls $\|H(\mathbf{w}) - H(\mathbf{w}_0)\|$ such that it is no larger than the order of $\|H(\mathbf{w}_0)\|$, hence $\|H(\mathbf{w})\|$ keeps the same order. See the proof details in Subsection 3.1.

Using the Taylor expansion Eq. (9), we can bound the Lagrange remainder and have transition to linearity of the network:

Corollary 3.7 (Transition to linearity). *Suppose Assumption 3.1, 3.2 and 3.5 hold. Given a fixed $R > 0$, for all $\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)$, with probability at least $1 - \exp(-\Omega(\log^2 m))$ over the random initialization $\mathbf{w}_0$, each f_k will be closely approximated by a linear model:*

$$|f_k(\mathbf{w}) - (f_k)_{\mathrm{lin}}(\mathbf{w})| \leq \frac{1}{2} \sup_{\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)} \|H_{f_k}(\mathbf{w})\| R^2 = \tilde{O}\left(\frac{1}{\sqrt{m}}\right).$$

For feedforward neural networks with multiple output neurons, the property of transition to linearity holds with high probability, if the number of output neurons is bounded, i.e., $d_\ell = O(1)$. See the result in Appendix C.

Furthermore, as defined in Definition 2.2, each pre-activation, as a function of all related weight parameters and inputs, can be viewed as a feedforward neural network. Therefore, we can apply the same techniques used for Theorem 3.6 to show that each pre-activation can transition to linearity:

Theorem 3.8. *Suppose Assumption 3.1, 3.2 and 3.5 hold. Given a fixed radius $R > 0$, for all $\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)$, with probability at least $1 - \exp(-\Omega(\log^2 m))$ over the random initliazation of $\mathbf{w}_0$, any pre-activation in a feedforward neural network i.e., $\tilde{f}_k^{(\ell)}(\mathbf{w})$ satisfies*

$$\left\| H_{\tilde{f}_k^{(\ell)}}(\mathbf{w}) \right\| = \tilde{O}\left(\frac{1}{\sqrt{m}}\right), \quad \ell \in [L], \quad k \in [d_\ell]. \tag{12}$$

Remark 3.9. Note that pre-activations in the input layer i.e., the input data and in the first layer are constant and linear functions respectively, hence the spectral norm of their Hessian is zero.

Non-linear activation on output neurons breaks transition to linearity. In the above discussions, the transition to linearity of networks are under the assumption of identity activation function on every output neuron. In fact, the activation function on output neurons is critical to the linearity of neural networks. Simply, composing a non-linear function with a linear function will break the linearity. Consistently, as shown in [13] for FCNs, with non-linear activation function on the output, transition to linearity does not hold any more.

3.1 Proof sketch of Theorem 3.6

By Lemma I.1, the spectral norm of H_{f_k} can be bounded by the summation of the spectral norm of all the Hessian blocks, i.e., $\|H_{f_k}\| \leq \sum_{\ell_1, \ell_2} \|H_{f_k}^{(\ell_1, \ell_2)}\|$, where $H_{f_k}^{(\ell_1, \ell_2)} := \frac{\partial^2 f_k}{\partial \mathbf{w}^{(\ell_1)} \partial \mathbf{w}^{(\ell_2)}}$. Therefore, it suffices to bound the spectral norm of each block. Without lose of generality, we consider the block with $1 \leq \ell_1 \leq \ell_2 \leq L$.

By the chain rule of derivatives, we can write the Hessian block into:

$$\frac{\partial^2 f_k}{\partial \mathbf{w}^{(\ell_1)} \partial \mathbf{w}^{(\ell_2)}} = \sum_{\ell'=\ell_2}^{L} \sum_{i=1}^{d_{\ell'}} \frac{\partial^2 f_i^{(\ell')}}{\partial \mathbf{w}^{(\ell_1)} \partial \mathbf{w}^{(\ell_2)}} \frac{\partial f_k}{\partial f_i^{(\ell')}} := \sum_{\ell'=\ell_2}^{L} G_k^{L, \ell'}. \tag{13}$$

For each $G_k^{L, \ell'}$, since $f_i^{(\ell')} = \sigma\left(\tilde{f}_i^{(\ell')}\right)$, again by the chain rule of derivatives, we have

$$G_k^{L, \ell'} = \sum_{i=1}^{d_{\ell'}} \frac{\partial^2 \tilde{f}_i^{(\ell')}}{\partial \mathbf{w}^{(\ell_1)} \partial \mathbf{w}^{(\ell_2)}} \frac{\partial f_k}{\partial \tilde{f}_i^{(\ell')}} + \frac{1}{\sqrt{m_k^{(L)}}} \sum_{i: f_i^{(\ell')} \in \mathcal{F}_{\mathcal{S}_k^{(L)}}} \left(\mathbf{w}_k^{(L)}\right)_i \sigma''\left(\tilde{f}_i^{(\ell')}\right) \frac{\partial \tilde{f}_i^{(\ell')}}{\partial \mathbf{w}^{(\ell_1)}} \left(\frac{\partial \tilde{f}_i^{(\ell')}}{\partial \mathbf{w}^{(\ell_2)}}\right)^T$$

$$= \frac{1}{\sqrt{m_k^{(L)}}} \sum_{r=\ell'}^{L-1} \sum_{s: f_s^{(r)} \in \mathcal{F}_{\mathcal{S}_k^{(L)}}} \left(\mathbf{w}_k^{(L)}\right)_s \sigma'\left(\tilde{f}_s^{(r)}\right) G_s^{r, \ell'}$$

$$+ \frac{1}{\sqrt{m_k^{(L)}}} \sum_{i: f_i^{(\ell')} \in \mathcal{F}_{\mathcal{S}_k^{(L)}}} \left(\mathbf{w}_k^{(L)}\right)_i \sigma''\left(\tilde{f}_i^{(\ell')}\right) \frac{\partial \tilde{f}_i^{(\ell')}}{\partial \mathbf{w}^{(\ell_1)}} \left(\frac{\partial \tilde{f}_i^{(\ell')}}{\partial \mathbf{w}^{(\ell_2)}}\right)^T,$$

where $\mathcal{F}_{\mathcal{S}_k^{(L)}} := \{f : f \in f_{\mathcal{S}_k^{(L)}}\}$.

The first quantity on the RHS of the above equation, $\sum \left(\mathbf{w}_k^{(L)}\right)_s \sigma'\left(\tilde{f}_s^{(r)}\right) G_s^{r,\ell'}$, is a matrix Gaussian series with respect to random variables $\mathbf{w}_k^{(L)}$, conditioned on fixed $\sigma'\left(\tilde{f}_s^{(r)}\right) G_s^{r,\ell'}$ for all s such that $f_s^{(r)} \in \mathcal{F}_{\mathcal{S}_k^{(\ell)}}$. We apply the tail bound for matrix Gaussian series, Theorem 4.1.1 from [23], to bound this quantity. To that end, we need to bound its matrix variance, which suffices to bound the spectral norm of $\sum_s G_s^{r,\ell'}$ since $\sigma'(\cdot)$ is assumed to be uniformly bounded by Assumption 3.2. Note that there is a recursive relation that the norm bound of $G_k^{L,\ell'}$ depends on the norm bound of $G_s^{r,\ell'}$ which appears in the matrix variance. Therefore, we can recursively apply the argument to bound each G.

Similarly, the second quantity on the RHS of the above equation is also a matrix Gaussian series with respect to $\mathbf{w}_k^{(L)}$, conditioned on fixed $\sigma''\left(\tilde{f}_i^{(\ell')}\right) \frac{\partial \tilde{f}_i^{(\ell')}}{\partial \mathbf{w}^{(\ell_1)}} \left(\frac{\partial \tilde{f}_i^{(\ell')}}{\partial \mathbf{w}^{(\ell_2)}}\right)^T$ for all i such that $f_i^{(\ell')} \in \mathcal{F}_{\mathcal{S}_k^{(L)}}$. We use Lemma B.1 to bound its matrix variance, hence the matrix Gaussian series can be bounded.

Note that such tail bound does not scale with the largest in-degree of the networks, since the in-degree of f_k, i.e., $m_k^{(L)}$, will be cancelled out with the scaling factor $1/\sqrt{m_k^{(L)}}$ in the bound of matrix variance. See the complete proof in Appendix B.

4 Relation to optimization

While transition to linearity is a significant and surprising property of wide networks in its own right, it also plays an important role in building the optimization theory of wide feedforward neural networks. Specifically, transition to linearity provides a path toward showing that the corresponding loss function satisfies the PL* condition in a ball of a certain radius, which is sufficient for exponential convergence of optimization to a global minimum by gradient descent or SGD [13].

Consider a supervised learning task. Given training inputs and labels $\{(\boldsymbol{x}_i, y_i)\}_{i=1}^n$, we use GD/SGD to minimize the square loss:

$$\mathcal{L}(\mathbf{w}) = \frac{1}{2}\sum_{i=1}^n (f(\mathbf{w}; \boldsymbol{x}_i) - y_i)^2, \tag{14}$$

where $f(\mathbf{w}; \cdot)$ is a feedforward neural network.

The loss $\mathcal{L}(\mathbf{w})$ is said to satisfy μ-PL* condition, a variant of the well-known Polyak-Łojasiewicz condition [19, 15], at point $\mathbf{w}$, if

$$\|\nabla_{\mathbf{w}}\mathcal{L}(\mathbf{w})\|^2 \geq 2\mu\mathcal{L}(\mathbf{w}), \quad \mu > 0.$$

Satisfaction of this μ-PL* condition in a ball $\mathsf{B}(\mathbf{w}_0, R)$ with $R = O(1/\mu)$ around the starting point $\mathbf{w}_0$ of GD/SGD guarantees a fast converge of the algorithm to a global minimum in this ball [13].

In the following, we use the transition to linearity of wide feedforward networks to establish the PL* condition for $\mathcal{L}(\mathbf{w})$. Taking derivative on Eq. (14), we get

$$\|\nabla_{\mathbf{w}}\mathcal{L}(\mathbf{w})\|^2 \geq 2\lambda_{\min}(K(\mathbf{w}))\mathcal{L}(\mathbf{w}), \tag{15}$$

where matrix $K(\mathbf{w})$, with elements $K_{i,j}(\mathbf{w}) = \nabla_{\mathbf{w}}f(\mathbf{w}; \boldsymbol{x}_i)^T\nabla_{\mathbf{w}}f(\mathbf{w}; \boldsymbol{x}_j)$ for $i, j \in [n]$, is called Neural Tangent Kernel (NTK) [10], and $\lambda_{\min}(\cdot)$ denotes the smallest eigenvalue of a matrix. Note that, by definition, the NTK matrix is always positive semi-definite, i.e., $\lambda_{\min}(K(\mathbf{w})) \geq 0$.

Directly by the definition of PL* condition, at a given point $\mathbf{w}$, if $\lambda_{\min}(K(\mathbf{w}))$ is strictly positive, then the loss function $\mathcal{L}(\mathbf{w})$ satisfies PL* condition.

To establish convergence of GD/SGD, it is sufficient to verify that PL* condition is satisfied in a ball $\mathsf{B}(\mathbf{w}_0, R)$ with $R = O(1/\mu)$. Assuming that $\lambda_{\min}(K(\mathbf{w}_0))$ is bounded away from zero, transition to linearity extends the satisfaction of the PL* condition from one point $\mathbf{w}_0$ to all points in $\mathsf{B}(\mathbf{w}_0, R)$.

PL* condition at $\mathbf{w}_0$. For certain neural networks, e.g., FCNs, CNNs and ResNets, strict positiveness of $\lambda_{\min}(K(\mathbf{w}_0))$ can be shown, see for example, [6, 5]. We expect same holds more generally, in the case of general feedforward neural networks. Here we show that $\lambda_{\min}(K(\mathbf{w}_0))$ can be bounded

from 0 for one data point under certain additional assumptions. Since there is only one data point, $\lambda_{\min}(K(\mathbf{w}_0)) = K(\mathbf{w}_0) = \|\nabla_{\mathbf{w}} f(\mathbf{w}_0)\|^2$. We also assume the following on activation functions and the input.

Assumption 4.1. The input $\mathbf{x}$ satisfies $\mathbf{x} \sim \mathcal{N}(I_{d_0}, 0)$.

Assumption 4.2. The activation function is homogeneous, i.e. $\sigma_i^{(\ell)}(az) = a^r \sigma_i^{(\ell)}(z), r > 0$ for any constant a. And $\inf_{\ell \in [L-1], i \in [d_\ell]} \mathbb{E}_{z \sim \mathcal{N}(0,1)}\left[\sigma_i^{(\ell)}(z)^2\right] = C_\sigma > 0$.

Remark 4.3. Here for simplicity we assume the activation functions are homogeneous with the same r. It is not hard to extend the result to the case that each activation function has different r.

Proposition 4.4. *With Assumption 4.1 and 4.2, we have for any $k \in [d_\ell]$,*

$$\mathbb{E}_{\mathbf{x}, \mathbf{w}_0}[\|\nabla_{\mathbf{w}} f_k(\mathbf{w}_0)\|] \geq \sqrt{\min\left(1, \min_{1 \leq j \leq L} C_\sigma^{\sum_{l'=0}^{j-1} r^{\ell'}}\right)} = \Omega(1). \tag{16}$$

The proof can be found in Appendix E.

The above proposition establishes a positive lower bound on $\|\nabla_{\mathbf{w}} f(\mathbf{w}_0)\|$, hence also on $\lambda_{\min}(K(\mathbf{w}_0))$. Using Eq. (15), we get that the loss function $\mathcal{L}(\mathbf{w})$ satisfies PL* at $\mathbf{w}_0$.

Extending PL* condition to $\mathsf{B}(\mathbf{w}_0, R)$. Now we use transition to linearity to extend the satisfaction of PL* condition to the ball $\mathsf{B}(\mathbf{w}_0, R)$. In Theorem 3.6, we see that, a feedforward neural network $f(\mathbf{w})$ transitions to linearity, i.e., $\|H_f(\mathbf{w})\| = \tilde{O}(1/\sqrt{m})$ in this ball. An immediate consequence is that, for any $\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)$,

$$|\lambda_{\min}(K(\mathbf{w})) - \lambda_{\min}(K(\mathbf{w}_0))| \leq O\left(\sup_{\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)} \|H_f(\mathbf{w})\|\right).$$

Since $\lambda_{\min}(K(\mathbf{w}_0))$ is bound from 0 and $\|H_f(\mathbf{w})\|$ can be arbitrarily small as long as m is large enough, we have $\lambda_{\min}(K(\mathbf{w}))$ is lower bounded from 0 in the whole ball. Specifically, there is a $\mu > 0$ such that

$$\inf_{\mathbf{w} \in \mathsf{B}(\mathbf{w}_0, R)} \lambda_{\min}(K(\mathbf{w})) \geq \mu.$$

Moreover, the radius R can be set to be $O(1/\mu)$, while keeping the above inequality hold. Then, applying the theory in [13], existence of global minima of $\mathcal{L}(\mathbf{w})$ and convergence of GD/SGD can be established.

For the case of multiple data points, extra techniques are needed to lower bound the minimum eigenvalue of the tangent kernel. Since we focus more on the transition to linearity of feedforward neural networks in this paper, we leave it as a future work.

Non-linear activation function on outputs and transition to linearity. In this paper, we mainly discussed feedforward neural networks with linear activation function on output neurons. In most of the literature also considers this setting [10, 17, 18, 6, 5, 28, 27]. In fact, as pointed out in [13] for FCNs, while this linearity of activation function on the outputs is necessary for transition to linearity, it is not required for successful optimization. Specifically, simply adding a nonlinear activation function on the output layer causes the Hessian norm to be $O(1)$, independently of the network width. Thus transition to linearity does not occur. However, the corresponding square loss can still satisfy the PL* condition and the existence of global minimuma and efficient optimization can still be established.

5 Discussion and future directions

In this work, we showed that transition to linearity arises in general feedforward neural networks with arbitrary DAG architectures, extending previous results for standard architectures [10, 12, 14]. For non-feedforward networks, such as RNN, recent work [1] showed they also have a constant NTK. For this reason, we expect transition to linearity also to occur for of non-feedforward networks. Another direction of future work is better understanding of optimization that requires a more delicate analysis of the NTK at initialization.

References

[1] Sina Alemohammad, Zichao Wang, Randall Balestriero, and Richard Baraniuk. "The Recurrent Neural Tangent Kernel". In: *International Conference on Learning Representations*. 2020.

[2] Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. "A convergence theory for deep learning via over-parameterization". In: *International Conference on Machine Learning*. PMLR. 2019, pp. 242–252.

[3] Sanjeev Arora, Simon S Du, Wei Hu, Zhiyuan Li, Russ R Salakhutdinov, and Ruosong Wang. "On Exact Computation with an Infinitely Wide Neural Net". In: *Advances in Neural Information Processing Systems* 32 (2019), pp. 8141–8150.

[4] Lenaic Chizat, Edouard Oyallon, and Francis Bach. "On lazy training in differentiable programming". In: *Advances in Neural Information Processing Systems* 32 (2019).

[5] Simon Du, Jason Lee, Haochuan Li, Liwei Wang, and Xiyu Zhai. "Gradient Descent Finds Global Minima of Deep Neural Networks". In: *International Conference on Machine Learning*. 2019, pp. 1675–1685.

[6] Simon S Du, Xiyu Zhai, Barnabas Poczos, and Aarti Singh. "Gradient Descent Provably Optimizes Over-parameterized Neural Networks". In: *International Conference on Learning Representations*. 2018.

[7] Boris Hanin and Mihai Nica. "Finite Depth and Width Corrections to the Neural Tangent Kernel". In: *International Conference on Learning Representations*. 2019.

[8] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. "Deep residual learning for image recognition". In: *Proceedings of the IEEE conference on computer vision and pattern recognition*. 2016, pp. 770–778.

[9] Gao Huang, Zhuang Liu, Laurens Van Der Maaten, and Kilian Q Weinberger. "Densely connected convolutional networks". In: *Proceedings of the IEEE conference on computer vision and pattern recognition*. 2017, pp. 4700–4708.

[10] Arthur Jacot, Franck Gabriel, and Clément Hongler. "Neural tangent kernel: Convergence and generalization in neural networks". In: *Advances in neural information processing systems*. 2018, pp. 8571–8580.

[11] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. "Imagenet classification with deep convolutional neural networks". In: *Advances in neural information processing systems* 25 (2012).

[12] Jaehoon Lee, Lechao Xiao, Samuel Schoenholz, Yasaman Bahri, Roman Novak, Jascha Sohl-Dickstein, and Jeffrey Pennington. "Wide neural networks of any depth evolve as linear models under gradient descent". In: *Advances in neural information processing systems* 32 (2019), pp. 8572–8583.

[13] Chaoyue Liu, Libin Zhu, and Mikhail Belkin. "Loss landscapes and optimization in over-parameterized non-linear systems and neural networks". In: *Applied and Computational Harmonic Analysis* (2022).

[14] Chaoyue Liu, Libin Zhu, and Mikhail Belkin. "On the linearity of large non-linear models: when and why the tangent kernel is constant". In: *Advances in Neural Information Processing Systems* 33 (2020).

[15] Stanislaw Lojasiewicz. "A topological property of real analytic subsets". In: *Coll. du CNRS, Les équations aux dérivées partielles* 117 (1963), pp. 87–89.

[16] James L McClelland, David E Rumelhart, PDP Research Group, et al. *Parallel Distributed Processing, Volume 2: Explorations in the Microstructure of Cognition: Psychological and Biological Models*. Vol. 2. MIT press, 1987.

[17] Andrea Montanari and Yiqiao Zhong. "The interpolation phase transition in neural networks: Memorization and generalization under lazy training". In: *arXiv preprint arXiv:2007.12826* (2020).

[18] Quynh Nguyen, Marco Mondelli, and Guido F Montufar. "Tight bounds on the smallest eigenvalue of the neural tangent kernel for deep relu networks". In: *International Conference on Machine Learning*. PMLR. 2021, pp. 8119–8129.

[19] Boris Teodorovich Polyak. "Gradient methods for minimizing functionals". In: *Zhurnal Vychislitel'noi Matematiki i Matematicheskoi Fiziki* 3.4 (1963), pp. 643–653.

[20] Nitish Srivastava, Geoffrey Hinton, Alex Krizhevsky, Ilya Sutskever, and Ruslan Salakhutdinov. "Dropout: a simple way to prevent neural networks from overfitting". In: *The journal of machine learning research* 15.1 (2014), pp. 1929–1958.

[21] Christian Szegedy, Wei Liu, Yangqing Jia, Pierre Sermanet, Scott Reed, Dragomir Anguelov, Dumitru Erhan, Vincent Vanhoucke, and Andrew Rabinovich. "Going deeper with convolutions". In: *Proceedings of the IEEE conference on computer vision and pattern recognition*. 2015, pp. 1–9.

[22] Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jon Shlens, and Zbigniew Wojna. "Rethinking the inception architecture for computer vision". In: *Proceedings of the IEEE conference on computer vision and pattern recognition*. 2016, pp. 2818–2826.

[23] Joel A Tropp et al. "An Introduction to Matrix Concentration Inequalities". In: *Foundations and Trends® in Machine Learning* 8.1-2 (2015), pp. 1–230.

[24] Roman Vershynin. *High-dimensional probability: An introduction with applications in data science*. Vol. 47. Cambridge university press, 2018.

[25] Mitchell Wortsman, Ali Farhadi, and Mohammad Rastegari. "Discovering neural wirings". In: *Advances in Neural Information Processing Systems* 32 (2019).

[26] Jiaxuan You, Jure Leskovec, Kaiming He, and Saining Xie. "Graph structure of neural networks". In: *International Conference on Machine Learning*. PMLR. 2020, pp. 10881–10891.

[27] Difan Zou, Yuan Cao, Dongruo Zhou, and Quanquan Gu. "Gradient descent optimizes overparameterized deep ReLU networks". In: *Machine Learning* 109.3 (2020), pp. 467–492.

[28] Difan Zou and Quanquan Gu. "An improved analysis of training over-parameterized deep neural networks". In: *Advances in Neural Information Processing Systems*. 2019, pp. 2053–2062.