Are large-language models enough to generate questionnaires? A use-case with clinical trials

Abstract

We propose DivAC-LLM, a hybrid pipeline that automatically generates physician-facing questionnaires from clinical trial eligibility criteria. The pipeline integrates rule-based systems, shallow machine learning models, fine-tuned biomedical transformers, and prompt-engineered Large Language Models (LLMs). Unlike purely generative approaches, our system explicitly predicts the number of questions derived from each criterion and injects structured cues into LLM prompts to improve control and accuracy. We validate the approach on two datasets: CTQG, a corpus we created from cancer trials, and QG-SQuAD, a modified version of SQuAD for question generation. Experimental results show that combining symbolic and neural components reduces hallucinations and improves semantic alignment. The results highlight that LLMs benefit from lightweight structure and explicit intermediate reasoning when generating interpretable clinical questionnaires.

1 Introduction

Since the mid-20th century, clinical trials have been the gold standard for evaluating the safety and efficacy of medical interventions (Weed, 1968). Randomized Controlled Trials (RCTs) have guided drug approvals, treatment guidelines, and healthcare policies (Meinert, 2012). However, a bottleneck in this process is eligibility pre-screening (Brøgger-Mikkelsen et al., 2020). Although inclusion and exclusion criteria are designed to identify suitable patient subgroups, they are typically expressed in unstructured free text. As a result, these criteria are often difficult to interpret, even for clinicians, and pose significant challenges to automatic parsing and operationalization (Raghavan et al., 2014).

With the widespread adoption of Electronic Health Records (EHRs) in the 2000s (Blumenthal and Tavenner, 2010), and the public availability of over 450,000 trials on ClinicalTrials.gov[1], the vision of automated patient-trial matching became plausible. However, the gap between free-text criteria and structured patient data remains unresolved (Kaskovich et al., 2023).

A key step consists in transforming formal eligibility criteria into structured questionnaires that are easier to complete, either by physicians or, in future developments, by automated assistants. These questionnaires can be completed automatically using EHR data (Figure 1) (Bernasconi et al., 2025). They offer interpretability, partial standardization, and actionable guidance. They can also facilitate patient pre-screening by making free-text trial constraints easier to operationalize during eligibility assessment (Ni et al., 2019). Besides, questionnaire generation is becoming a common practice in the clinical trial industry (e.g., Initia, Carenity) (Edwards, 2010).

Figure 1: Examples of question generation.

---

[1] https://ClinicalTrials.gov

Literature has focused on query generation rather than on physician-oriented questionnaire generation (Park et al., 2024a) but recent progress in LLMs has made question generation (QG) accessible through prompt-based approaches. However, clinical eligibility criteria often contain implicit constraints, numerical thresholds, and multi-clause logical structures that are difficult to operate in a single generative step (Smith et al., 2023). The extraction of criteria and their values[2] is implicit during the generation, but there is no intrinsic evaluation of this extraction's accuracy.

We therefore investigate the following research question: are LLMs alone sufficient to generate structured questionnaires from clinical trial eligibility criteria, or do they benefit from explicit structural guidance? Our hypothesis is that introducing lightweight intermediate structure (specifically criterion decomposition and attribute extraction) improves generation accuracy and semantic alignment with expert-designed questionnaires.

To explore this idea, we propose a hybrid pipeline that identifies criteria in trial descriptions, extracts the clinical attributes, and predicts whether a criterion should yield one or multiple questions before prompting an LLM.

We also create a dataset, called CTQG (Clinical Trial Question Generation), extracted from lung cancer clinical trials from ClinicalTrials.gov in English to train models to convert criteria into questions.

The contributions[3] of this paper are:

- A hybrid pipeline (DivAC-LLM) that combines rule-based signals, machine learning models, and LLM prompting to generate physician-facing questionnaires from eligibility criteria.

- The CTQG dataset, an expert-curated benchmark linking clinical trial criteria to normalized questionnaire items.

- An analysis of human curation effects in LLM-assisted dataset construction.

- An empirical evaluation comparing hybrid and purely generative approaches across clinical and general-domain QG tasks.

---

[2](p.e., *age: < 18*)

[3]The clinical trial codes, the training scripts and configuration and the final prompts are published with the paper

2 Related Works

Regarding eligibility criteria processing, early efforts focused on rule-based extraction pipelines such as EliIE (Kang et al., 2017) and Criteria2Query (Yuan et al., 2019), as well as annotated corpora like Chia (Kury et al., 2020), which transform unstructured criteria into structured representations aligned with database queries.

Text mining from clinical trial documents has also enabled alignment between eligibility criteria and structured patient data (Weng et al., 2011). This includes entity normalization, logical form parsing and OMOP-compatible cohort definitions (Ziletti and D'Ambrosi, 2025). The Leaf Clinical Trials corpus (Dobbins et al., 2022) has provided a large-scale semantic benchmark for such tasks. More recently, LeafAI (Dobbins et al., 2023) introduced neural query generators that achieve retrieval performance comparable to experienced programmers.

Some approaches convert criteria into interactive questions to assist in patient recruitment. DQueST (Liu et al., 2019) generates dynamic "Yes/No" questions to match patients with trials. However, it lacks domain-specific clinical phrasing and does not integrate EHR signals.

LLMs have opened new possibilities for clinical trial matching. (Wornow et al., 2025) apply zero-shot prompting to evaluate trial-patient compatibility and generate natural language justifications. TrialGPT (Jin et al., 2024) fine-tunes generative models for trial matching across thousands of real-world protocols, while FollowupBench (Gatto et al., 2025) addresses clinical QG from patient-provider dialogues. However, these systems aim for classification or summarization, not the generation of interpretable, structured questions. Besides, they often suffer from factual hallucinations, constraint omission, and semantic overgeneralization (García-Barragán et al., 2025; Pal et al., 2022b).

Hybrid architectures have emerged to address these shortcomings by combining symbolic, statistical, and neural methods. (Li et al., 2024) propose a post-processing framework to reduce hallucinations in medical QA. (Yi et al., 2024) incorporate entity-based pre-filtering before LLM reasoning in trial-patient matching.

Recent works unleashed the power of LLMs to enhance patient-trial matching. Criteria2Query3 (Park et al., 2024b) used GPT-4 to transform the text from ClinicalTrials.gov into SQL queries. Fi-

nally, the PRISM framework (Gupta et al., 2024) fine-tuned an LLM to both simplify eligibility criteria and realize patient prescreening, but the QG module does not consider that a criteria can become several questions. However, their solution outperforms zero-shot LLMs' accuracy by 0.2.

Despite recent progress, no work has tackled structured QG from clinical trial criteria for physician-facing tools.

3 Methodology

3.1 Data

3.1.1 CTQG dataset

The dataset used in this work is derived from clinical trials collected from ClinicalTrials.gov, an online registry containing information on more than 440,000 clinical studies conducted across 220 countries.

Eligibility criteria were refined with expert medical input to establish an explicit correspondence between each criterion and the questions required to operationalize it. An oncologist generated and curated 729 questions using ChatGPT-4o as a drafting assistant. Identical criteria across trials were normalized so that they map to the same questionnaire item. Because criteria may encode multiple conditions, the correspondence between criteria and questions is not strictly one-to-one, but can also be one-to-many or many-to-one (Figure 1). The prompting setup used to obtain the initial drafts is reported in Appendix A.

CTQG is designed as a high-precision benchmark prioritizing semantic consistency over scale. The average lexical similarity between drafts and final questions is 0.64 (median 0.69), with only 32.8% of pairs being near-verbatim matches (similarity ≥ 0.9). Conversely, 51.2% of cases involve substantial rewriting (similarity < 0.7). Curated questions are also shorter on average (137 vs. 105 characters), reflecting systematic normalization and editorial compression. These results indicate that the benchmark reflects expert restructuring rather than direct reuse of LLM outputs.

Examples of typical transformations introduced during curation are shown in Table 9 (Appendix B). While the initial drafts are often semantically faithful to the eligibility criteria, the curation process standardizes phrasing and decomposes compound eligibility constraints into atomic questionnaire items.

The CTQG dataset focuses on lung cancer trials. However, the underlying structure of eligibility criteria is largely domain-independent, and prior work on criteria extraction and patient–trial matching shows that models trained on one disease area often transfer to others because criteria share common semantic patterns (Ross et al., 2010; Luo et al., 2011).

3.1.2 SQuAD dataset

The second dataset employed in this study is the Stanford Question Answering Dataset (SQuAD) (Rajpurkar et al., 2018), a widely used benchmark for machine reading comprehension. SQuAD 1.1 contains over 100,000 question–answer pairs derived from Wikipedia passages, where each question is associated with an answer span that appears as a contiguous segment in the text.

To evaluate the ability of our method to generalize beyond the clinical domain, we constructed a derived dataset, QG-SQuAD, by transforming SQuAD into a question generation setting structurally comparable to CTQG. Each passage was segmented into sentences using the NLTK toolkit (Bird and Loper, 2004), and each question was associated with the sentence containing its answer span. This process yielded 101,888 sentence–question pairs, where the sentence plays the role of the input constraint and the associated question corresponds to the generated item (Algorithm 1).

SQuAD therefore serves as a complementary benchmark that allows us to assess whether the structural signals introduced in our pipeline remain beneficial under a different task formulation.

Algorithm 1 Map questions to sentence intervals

Require: Paragraphs $\mathcal{P}$; contexts $\mathcal{C}_p$ per paragraph; for each context c: QA pairs $\mathcal{A}_c = \{(a_{\text{start}}^{(k)}, q^{(k)})\}_k$
1: **for all** $p \in \mathcal{P}$ **do**
2:    **for all** $c \in \mathcal{C}_p$ **do**
3:       $[s_1, \ldots, s_L] \leftarrow$ SPLITINTOSENTENCES(c)
4:       $o \leftarrow 0$;
5:       **for** $i = 1$ to L **do**
6:          $\ell_i \leftarrow$ INDEXOF(c, s_i, o); $r_i \leftarrow \ell_i + |s_i|$; $o \leftarrow r_i$
7:       **end for**
8:       **for all** $(a_{\text{start}}, q) \in \mathcal{A}_c$ **do**
9:          find j s.t. $\ell_j \leq a_{\text{start}} < r_j$ ▷ binary search or scan
10:          map $q \rightarrow (s_j, [\ell_j, r_j))$
11:       **end for**
12:    **end for**
13: **end for**

Furthermore, correspondences were identified between each original text segment (or "Criterion") and the number of questions generated. The distribution of the number of questions associated with each criterion is as follows: 40,961 (40.2%) with zero questions, 40,467 (39.72%) with one ques-

tion, 14,536 (14.27%) with two questions, 3,985 (3.91%) with three questions, 1,251 (1.23%) with four questions, and 688 (0.67%) with five questions. This distribution highlights that, unlike CTQG, this dataset includes many cases in which no questions are generated. QG-SQuAD reflects positional span alignment, not conceptual decomposition. As a result, QG-SQuAD offers scale and robustness tests but evaluates another skill: local span-driven generation rather than domain-level reasoning.

3.1.3 Datasets comparison

Throughout this section, both datasets have been compared from different perspectives, both globally and with respect to the train, test, and validation partitions. These measures are presented in Table 1.

There is homogeneity within the partitions of each dataset, although certain differences can be detected between them. For example, SQuAD texts are longer in terms of the number of characters and words, although they contain fewer sentences than CTQG. Similarly, SQuAD shows a broader vocabulary as well as higher entropy, which makes sense given the size and topic differences between the two datasets.

3.2 DivAC-LLM pipeline

To tackle the challenges mentioned in Section 2, our pipeline is divided into two tasks: predicting the number of questions to generate per criterion and the generation itself with criteria extraction. Figure 2 illustrates our pipeline and the next sections explain the different modules.

3.2.1 Question division prediction

Eligibility criteria frequently contain multiple logical constraints within a single sentence. When directly processed by generative models, such criteria are often converted into a single question. Predicting the number of questions associated with each criterion therefore provides a structural signal that guides the generation process and encourages the decomposition of complex constraints into atomic questions. This task can be seen as a count regression (approximate the number of questions to be generated from a criterion). Table 2 shows the distribution of questions per criterion. However, due to the imbalance of the data, we decided to treat it as a ternary classification problem: 0 (no question to be generated), 1 (one question to be generated) and 2 (several questions to be generated).

Ground truth analysis (Table 9) indicates that apparently similar eligibility criteria may require different numbers of generated questions. Providing the model with explicit information about the expected number of questions reduces ambiguity and improves alignment with reference outputs. Additional qualitative examples of this behavior are provided in Appendix C.3 (Figure 3).

As it is a predictive task, LLMs tend to underperform specialized fine-tuning approaches (Trust and Minghim, 2024). In addition, since criteria are a short sentence (18.9 words on average), simple solutions can be effective, thus reducing computing time and energy consumptions. We created a voting algorithm in three steps, giving more weight to precision than recall, arguing that it is best that the system ignores how many questions have to be generated rather than guessing a number:

1. We extracted features from the criterion with SpaCy (Honnibal et al., 2020) (Table 17 in Appendix E) and established correlation patterns between the feature values and the three classes in order to implement a rule-based system. To complete it, we implemented a Random Forest algorithm and we predicted the remaining classes that had not been labeled by the rule-based system, that has high precision but low recall.

2. We fine-tuned two transformers specialized in the bio-medical domain (BioBERT (Lee et al., 2019) and BioMedLM (Bolton et al., 2024)) to predict the right class for each criterion.

3. We crafted a voting algorithm with several conditions, where in case of disagreement between the rule-based + Random Forest and the different fine-tuned models, the priorities could be given to a different predictor, or to the "I don't know" class. The description of the different strategies is given in Table 18 in Appendix E.

We chose the voting configuration that maximizes precision with acceptable recall. The training process is illustrated in Algorithm 2 and the voting system in Algorithm 3, both in Appendix C.

3.2.2 Question generation and criteria management

Regarding the QG, two approaches are state-of-the-art: (1) supervised approaches with transformers fine-tuning and (2) zero-shot learning with LLMs.

Dataset	Partition	Size	Vocab. size	Entropy	Characters				Words				Sentences			
					Min	Max	Avg	StD	Min	Max	Avg	StD	Min	Max	Avg	StD
CTQG	*Train*	473	1,879	9.19	5	602	126.62	99.94	1	76	18.77	14.91	1	4	1.15	0.43
	Test	148	925	8.68	9	742	125.40	111.04	1	111	18.90	16.86	1	4	1.15	0.46
	Validation	108	818	8.63	13	573	130.55	125.63	3	93	19.43	19.02	1	4	1.15	0.49
	Total	729	2,244	9.25	5	742	126.95	106.24	1	111	18.90	15.96	1	4	1.15	0.44
SQuAD	*Train*	81,252	91,287	11.27	1	2,458	150.93	78.67	0	341	24.37	12.54	0	12	1.04	0.25
	Test	10,407	26,644	10.95	2	781	150.39	79.04	1	127	24.29	12.55	0	4	1.04	0.23
	Validation	10,229	26,877	10.93	1	1,412	155.68	85.23	0	230	25.13	13.58	0	11	1.05	0.31
	Total	101,888	103,675	11.30	1	2,458	151.35	79.40	0	341	24.44	12.65	0	12	1.04	0.26

Table 1: Statistical summary of the datasets used (CTQG, QG-SQuAD) with respect to the different partitions (train, test, validation, total), including values for size, vocabulary size, Shannon entropy, and the minimum, maximum, mean, and standard deviation of the number of characters, words and sentences. Note that for the SQuAD dataset, a sample of the total was taken for the development of this research.

Figure 2: Automatic questionnaire generation pipeline.

Number of Questions	Count
1	321
0	81
2	37
4	17
3	10
5	4
6	2
7	1

Table 2: Distribution of the number of questions generated per criterion.

They are end-to-end methods that take as input a criterion in natural language and transform it into questions. The fine-tuning approach can be considered as a machine translation task (Raffel et al., 2020), where the criterion is the source language and the questions the target. The model learns from real question examples and thus is accurate when "translating". However, it requires a parallel corpus of a minimum size (Koehn and Knowles, 2017) in order to be effective. On the other side, the LLM-based approach requires a few or even no question examples in order to work, due to its huge language model and generative capacities, but the issues are in the risks of hallucinations and variability in its generation.

Nevertheless, as the LLM-based approach is based on prompt engineering and instructions crafting (Liu et al., 2023), it is possible to control the output by adding to the prompt information about the criteria. In other words, the LLM-based approaches can be stronger if used with a previous step where the criteria values are extracted in a NER fashion and passed explicitly to the prompt. We decided to combine two LLMs:

1. One is AutoCriteria (Datta et al., 2024), a framework based on the GPT-4 model to extract granular eligibility criteria information from clinical trial documents.

2. Another is an instance of Llama 3.3 (Grattafiori et al., 2024), an open-source LLM that we used in order to generate more accurate questions for each criterion. The prompts that have been used are presented in Appendix A.1.

The final result is a three-module system (question division, AutoCriteria and LLM) that we called DivAC-LLM, optimized for questionnaire generation from clinical trials.

4 Experimental results and evaluation

4.1 Experimental setup

Regarding the baselines, we used, depending on the dataset:

1. **CTQG:** three state-of-the-art pre-trained transformers, two specialized in the medical domain (BioBART (Yuan et al., 2022), BERT2BERT (Moll et al., 2025)), one generic (Flan-t5 (Smilga and Alabiad, 2024)), ChatGPT-4o and Llama 3.3 against DivAC-LLM.

2. **QG-SQuAD:** two state-of-the-art generic pre-trained transformers (Prophetnet (Qi et al., 2020), ChatGPT-4o and Llama3.3 against DivAC-LLM.

The experiments details are available in Tables 20 and 21 in Appendix E. When fine-tuning transformers models for QG, we performed a grid search, where the ranges are available in Table 23 in Appendix E. The best hyperparameters for each dataset are available in Table 19 in Appendix E.

4.2 Results evaluation

For question division, we realized an automatic evaluation. For QG, we conducted two distinct evaluations, a human evaluation based on (Nema and Khapra, 2018) and an automatic evaluation based on the QGEval metrics benchmark (Fu et al., 2024).

4.2.1 Question division evaluation

As it is a module that can be activated or deactivated, we evaluate separately the question division prediction on both CTQG and QG-SQuAD. We show in Table 3 the results with the best voting strategy. While the question division module underperforms on QG-SQuAD, due to this module

Dataset & class	Precision	Recall	F-score
CTQG 0	0.74	0.33	0.45
CTQG 1	**0.84**	**0.71**	**0.77**
CTQG 2	0.33	0.43	0.38
QG-SQuAD 0	**0.69**	0.41	0.52
QG-SQuAD 1	0.38	0.41	0.40
QG-SQuAD 2	0.45	**0.68**	**0.54**

Table 3: Results of question division prediction with the best voting strategy for both CTQG and QG-SQuAD.

reliance on linguistic heuristics rather than domain-informed labeling, the module achieves better results on CTQG, in the precision of classes 0 and 1. In the Section 4.2.3 we observe the impact of the module for questionnaire generation.

4.2.2 Human evaluation

We compared the benchmarked models with DivAC-LLM and the expert-generated ground truth (Section 3.1.1) through human evaluation. Three annotators participated: two computational linguists and one biomedical expert. All followed a shared guideline defining adequacy, fluency, and understandability (Callison-Burch et al., 2006).

Scores were averaged across annotators for each model and metric (Table 4). Fluency and understandability are similar across strong systems, including the expert reference and DivAC-LLM, whereas adequacy shows slightly higher scores for DivAC-LLM, likely reflecting normalization consistency rather than superior clinical judgment. The task consists of reformulating eligibility criteria into structured questions where the source information is contained in the input criterion. Therefore factuality in the sense of external knowledge verification is less relevant than semantic faithfulness to the original criterion.

Table 6 reports inter-annotator agreement using Fleiss' κ, Krippendorff's α, and Scott's π (Artstein and Poesio, 2008), together with a Wilcoxon dominance score (W) (Dror et al., 2018). While κ, α, and π measure agreement on absolute ratings, W captures pairwise preference tendencies between systems. Annotators may therefore disagree on exact scores while still consistently preferring the same model. The Wilcoxon results show that DivAC-LLM and ChatGPT obtain the highest W values across the three dimensions.

Additionally, two biomedical experts were asked to detect which questions were generated and which corresponded to the reference standard.

Model	Annotator 1			Annotator 2			Annotator 3			Mean		
	Adeq.	Underst.	Flu.	Adeq.	Underst.	Flu.	Adeq.	Underst.	Flu.	Adeq.	Underst.	Flu.
biobart	4.01	4.48	4.47	3.87	4.47	4.47	3.81	4.25	4.14	3.90	4.40	4.36
BERT2BERT	3.44	4.18	4.15	3.32	4.17	4.21	3.40	3.74	3.72	3.38	4.03	4.03
FLAN-T5	3.83	4.77	4.68	3.60	4.70	4.70	3.93	4.50	3.88	3.79	4.66	4.42
ChatGPT	4.28	4.99	4.99	3.83	**5.00**	**5.00**	4.67	4.95	4.88	4.26	4.98	4.96
Llama3.3	4.28	**5.00**	**5.00**	3.99	**5.00**	**5.00**	4.58	4.68	4.60	4.28	4.89	4.87
DivAC-LLM	**4.71**	4.98	4.92	**4.87**	4.94	**5.00**	**4.93**	4.98	4.94	**4.84**	4.97	4.95
ground-truth (section 3.1.1)	4.54	4.98	4.94	4.83	4.97	4.98	4.74	4.99	**5.00**	4.70	4.98	**4.97**

Table 4: Human evaluation scores for adequacy, understanding, and fluency from three annotators (Annotator 1-3) and their mean.

They were asked to choose between DivAC-LLM and the ground truth. In 69.8% of the cases, they chose DivAC-LLM (Table 5).

Model	Percentage (%)
FLAN-T5	6.4
ChatGPT	11.1
BERT2BERT	13.4
bioBART	13.4
Llama3.3	**20.5**
Manual labeling	**20.5**

Table 5: Percentage of times each model was selected as the best system.

4.2.3 QGEval evaluation

To validate DivAC-LLM, we evaluated the models using the QGEval benchmark rather than relying only on traditional MT metrics such as BLEU (Papineni et al., 2001) or BERTScore (Zhang et al., 2020). QGEval aggregates several complementary metrics, including QRelScore (Wang et al., 2022), which combines word-level matching with sentence-level relevance, and UniEval (Li et al., 2025), a unified set of fine-grained evaluation tags designed to better correlate with human judgments. Detailed metric descriptions are provided in Appendix D (Tables 15 and 16).

Results on CTQG (Table 7) show that DivAC-LLM outperforms all baselines across both lexical and semantic metrics. An ablation study removing the question division and AutoCriteria modules indicates that a fine-tuned Llama 3.3 performs best either with both modules or with none, suggesting a dependency between them. To further assess the role of question division, we evaluated an oracle configuration where the model receives the true number of questions per criterion, which yields the best overall performance.

For QG-SQuAD, where explicit criteria are absent, we combined the question division module with several LLMs and compared them with fine-tuned transformers. While question division improves LLM performance (Table 8), fine-tuned transformers remain stronger on ROUGE and BERTScore, indicating that the division mechanism does not generalize equally well to all question generation settings.

5 Discussion

The comparison between CTQG and QG-SQuAD highlights the role of domain structure. In QG-SQuAD, "criteria" correspond to generic sentences aligned with questions by position, which limits the impact of division and allows fine-tuned seq2seq baselines to remain competitive on ROUGE and BERTScore. In contrast, CTQG contains explicit domain signals (entities, thresholds, and exception patterns) that enable rule-guided models to anchor generation more effectively.

Human evaluation follows a similar pattern. Fluency and understandability vary little across strong systems, whereas adequacy is more sensitive to prompt conditioning and explicit metadata. Inter-annotator agreement remains moderate, consistent with previous findings in NLG evaluation. Although the questionnaire format improves clarity, errors may still affect eligibility interpretation. DivAC-LLM reduces this risk through rule-guided prompting and explicit metadata, but remains a decision-support tool requiring clinical supervision.

Finally, ablation experiments suggest that LLMs are effective at producing fluent linguistic content but struggle to control structural requirements, such as determining whether a criterion should generate one or multiple questions. The improvement observed in the oracle configuration, where the number of questions is provided explicitly, supports the hypothesis that LLMs benefit from external structural guidance.

Model	Adequacy				Understanding				Fluency			
	Fleiss κ	Kripp. α	Scott's π	W	Fleiss κ	Kripp. α	Scott's π	W	Fleiss κ	Kripp. α	Scott's π	W
biobart	0.326	0.318	0.316	**-1**	0.503	0.498	0.496	**+1**	0.471	0.466	0.463	**+1**
BERT2BERT	0.333	0.321	0.318	**-1**	0.457	0.447	0.445	**+1**	0.465	0.455	0.453	**+1**
FLAN-T5	0.255	0.245	0.242	**-1**	0.384	0.381	0.378	**+1**	0.156	0.134	0.130	**+1**
ChatGPT	0.199	0.163	0.160	**+4**	0.163	0.162	0.159	**+4**	0.055	0.045	0.041	**+5**
Llama3.3	0.225	0.202	0.199	**-1**	1.000	-0.017	-0.021	**+1**	1.000	-0.022	-0.026	**+1**
human	0.220	0.214	0.211	**NA**	0.149	0.150	0.147	**NA**	0.071	0.068	0.065	**NA**
DivAC-LLM	0.015	-0.299	-0.304	**+6**	-0.001	-0.434	-0.439	**+4**	1.000	-0.434	-0.439	**+5**

Table 6: Inter-annotator agreement (Fleiss' κ, Krippendorff's α, Scott's π) and Wilcoxon signed-rank dominance score (W). W is the number of significant wins minus losses for each model against all others for that dimension.

metrics	QRelScore	BERTScore	ROUGE-L	Q-BLEU4
bioBART	0.363	**0.772**	**0.721**	0.462
BERT2BERT	0.393	0.696	0.438	**0.523**
Flan-t5	0.658	0.710	0.471	0.443
ChatGPT	0.658	0.710	0.471	0.443
Llama3.3	**0.670**	0.709	0.475	0.456
Autocriteria + Llama3.3	0.745	0.891	0.399	0.395
Question division + Llama3.3	0.742	0.893	0.408	0.410
Fine tuned Llama3.3	0.710	0.944	0.694	0.618
DivAC-LLM	**0.746**	**0.945**	**0.758**	**0.682**
DivAC-LLM oracle mode (no autocriteria)	0.747	**0.956**	0.750	**0.696**
DivAC-LLM oracle mode	**0.752**	0.953	0.722	0.653

Table 7: Automatic evaluation results on CTQG with respect to different models and combinations compared with DivAC-LLM.

Model	BERTScore	BLEU	ROUGE
Gemini	0.868	0.149	2.27
Gemini + div	0.855	0.209	2.98
ChatGPT	0.868	0.153	2.19
ChatGPT + div	0.874	**0.210**	3.07
Llama3.3	0.869	0.177	2.37
Llama3.3 + div	0.884	0.170	3.17
ProphetNet-large	0.888	0.143	**3.41**

Table 8: Automatic evaluation results on QG-SQuAD comparing fine-tuned models and LLMs with question division module.

6 Future work

Future work will replace the current voting mechanism with a learned calibration layer to improve per-criterion reliability (Clarté et al., 2023). We also plan to enrich criterion extraction with structured representations and apply constrained decoding to enforce template-level consistency (Hokamp and Liu, 2017). Finally, clinician feedback will be integrated into a human-in-the-loop workflow to continuously refine the division and generation modules (Wan et al., 2023).

7 Conclusion

We introduced DivAC-LLM, a hybrid pipeline for generating physician-facing questionnaires from clinical trial criteria. By combining rule-based signals, classical models, and LLM prompting with explicit value injection, the system improves automatic metrics on CTQG and achieves human judgments comparable to strong baselines for fluency and understandability while improving adequacy. These results indicate that lightweight structural guidance and prompt conditioning help overcome limitations of end-to-end prompting in clinical settings where multi-clause logic and exceptions are common.

Limitations

Certain limitations can be identified in this approach:

- **Dataset scope.** The dataset is limited to English-language lung cancer trials, which narrows both linguistic and clinical variability. Broader multilingual evaluation is needed to ensure robustness across registries and pathologies (Neumann et al., 2024).

- **Human evaluation scale.** Expert assessment was conducted by only three annotators within one specialty, potentially biasing adequacy and fluency judgments. Larger collaborative annotation efforts such as MedMCQA illustrate the benefits of scaling expert input (Pal et al., 2022a). Evaluation on additional medical specialties remains an important direction for future work.

- **Model transparency.** Although DivAC-LLM improves interpretability through explicit intermediate steps, it still depends on opaque LLM components. Reliability and calibration remain open challenges before any clinical deployment.

- **External validation.** No downstream testing has yet been performed on real patient screening tasks, leaving practical effectiveness and safety unverified.

- **Energy consumption.** Although efforts were made to limit computational cost, the training and fine-tuning periods were long enough to be costly and energy-greedy, which has to be improved in order to be more sustainable.

- **End-to-end LLM fine-tuning.** Given the size of the dataset and its high-quality expert-based annotation, a few-shot end-to-end supervised fine-tuning of a small Llama could have been used to enrich the benchmark. However, as we have very short inputs (and outputs), we prioritize precision over recall (the "I always reply something" from the LLM can decrease precision). Furthermore, the energy consumption would be even bigger, so we decided to skip this experiment. In the context of clinical questionnaires, over-generating questions may introduce spurious eligibility checks, whereas missing optional questions is less harmful during prescreening.

References

Ron Artstein and Massimo Poesio. 2008. Survey article: Inter-coder agreement for computational linguistics. *Computational Linguistics*, 34(4):555–596.

Lara Bernasconi, Georg Avakyan, Frédérique Hovaguimian, and Regina Grossmann. 2025. Natural language processing in clinical research recruitment: A scoping review enriched with stakeholder insights. *Ethics Hum. Res.*, 47(5):13–23.

Steven Bird and Edward Loper. 2004. NLTK: The natural language toolkit. In *Proceedings of the ACL Interactive Poster and Demonstration Sessions*, pages 214–217, Barcelona, Spain. Association for Computational Linguistics.

David Blumenthal and Marilyn Tavenner. 2010. The "meaningful use" regulation for electronic health records. *N. Engl. J. Med.*, 363(6):501–504.

Elliot Bolton, Abhinav Venigalla, Michihiro Yasunaga, David Hall, Betty Xiong, Tony Lee, Roxana Daneshjou, Jonathan Frankle, Percy Liang, Michael Carbin, and Christopher D. Manning. 2024. Biomedlm: A 2.7b parameter language model trained on biomedical text. *Preprint*, arXiv:2403.18421.

Mette Brøgger-Mikkelsen, Zarqa Ali, John R Zibert, Anders Daniel Andersen, and Simon Francis Thomsen. 2020. Online patient recruitment in clinical trials: Systematic review and meta-analysis. *J. Med. Internet Res.*, 22(11):e22179.

Chris Callison-Burch, Miles Osborne, and Philipp Koehn. 2006. Re-evaluating the role of Bleu in machine translation research. In *11th Conference of the European Chapter of the Association for Computational Linguistics*, pages 249–256, Trento, Italy. Association for Computational Linguistics.

François Clarté, Yann Chevaleyre, Guillaume Contardo, and Massimiliano Tommasi. 2023. Expectation consistency for calibration of neural networks. In *Proceedings of the 40th International Conference on Machine Learning (ICML)*, volume 216 of *Proceedings of Machine Learning Research*, pages 5431–5450.

Surabhi Datta, Kyeryoung Lee, Hunki Paek, Frank J Manion, Nneka Ofoegbu, Jingcheng Du, Ying Li, Liang-Chin Huang, Jingqi Wang, Bin Lin, Hua Xu, and Xiaoyan Wang. 2024. AutoCriteria: a generalizable clinical trial eligibility criteria extraction system powered by large language models. *J. Am. Med. Inform. Assoc.*, 31(2):375–385.

Nicholas J Dobbins, Bin Han, Weipeng Zhou, Kristine F Lan, H Nina Kim, Robert Harrington, Özlem Uzuner, and Meliha Yetisgen. 2023. LeafAI: query generator for clinical cohort discovery rivaling a human programmer. *J. Am. Med. Inform. Assoc.*, 30(12):1954–1964.

Nicholas J. Dobbins, Tony Mullen, Özlem Uzuner, and Meliha Yetisgen. 2022. The leaf clinical trials corpus: a new resource for query generation from clinical trial eligibility criteria. *Scientific Data*, 9(1):490.

Rotem Dror, Gili Baumer, Segev Shlomov, and Roi Reichart. 2018. The hitchhiker's guide to testing statistical significance in natural language processing. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1383–1392, Melbourne, Australia. Association for Computational Linguistics.

Phil Edwards. 2010. Questionnaires in clinical trials: guidelines for optimal design and administration. *Trials*, 11(1):2.

Weiping Fu, Bifan Wei, Jianxiang Hu, Zhongmin Cai, and Jun Liu. 2024. QGEval: Benchmarking multi-dimensional evaluation for question generation. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 11783–11803, Miami, Florida, USA. Association for Computational Linguistics.

Álvaro García-Barragán, Ahmad Sakor, Maria-Esther Vidal, Ernestina Menasalvas, Juan Cristobal Sanchez Gonzalez, Mariano Provencio, and Víctor Robles. 2025. Nssc: a neuro-symbolic ai system for enhancing accuracy of named entity recognition and linking from oncologic clinical notes. *Medical & Biological Engineering & Computing*, 63(3):749–772.

Joseph Gatto, Parker Seegmiller, Timothy Burdick, Inas S. Khayal, Sarah DeLozier, and Sarah M. Preum. 2025. Follow-up question generation for enhanced patient-provider conversations. *Preprint*, arXiv:2503.17509.

Aaron Grattafiori, Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Alex Vaughan, Amy Yang, Angela Fan, Anirudh Goyal, Anthony Hartshorn, Aobo Yang, Archi Mitra, Archie Sravankumar, Artem Korenev, Arthur Hinsvark, and 542 others. 2024. The llama 3 herd of models. *Preprint*, arXiv:2407.21783.

Shashi Gupta, Aditya Basu, Mauro Nievas, Jerrin Thomas, Nathan Wolfrath, Adhitya Ramamurthi, Bradley Taylor, Anai N Kothari, Regina Schwind, Therica M Miller, Sorena Nadaf-Rahrov, Yanshan Wang, and Hrituraj Singh. 2024. PRISM: Patient records interpretation for semantic clinical trial matching system using large language models. *NPJ Digit. Med.*, 7(1):305.

Chris Hokamp and Qun Liu. 2017. Lexically constrained decoding for sequence generation using grid beam search. In *Proceedings of the 55th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 1535–1546, Vancouver, Canada. Association for Computational Linguistics.

Matthew Honnibal, Ines Montani, Sofie Van Landeghem, and Adriane Boyd. 2020. spaCy: Industrial-strength Natural Language Processing in Python.

Qiao Jin, Zifeng Wang, Charalampos S. Floudas, Fangyuan Chen, Changlin Gong, Dara Bracken-Clarke, Elisabetta Xue, Yifan Yang, Jimeng Sun, and Zhiyong Lu. 2024. Matching patients to clinical trials with large language models. *Nature Communications*, 15(1):9074.

Tian Kang, Shaodian Zhang, Youlan Tang, Gregory W. Hruby, Alexander Rusanov, and Noémie Elhadad. 2017. EliIE: An open-source information extraction system for clinical trial eligibility criteria. *J. Am. Med. Inform. Assoc.*, 24(6):1062–1071.

Samuel Kaskovich, Kirk D Wyatt, Tomasz Oliwa, Luca Graglia, Brian Furner, Jooho Lee, Anoop Mayampurath, and Samuel L Volchenboum. 2023. Automated matching of patients to clinical trials: A patient-centric natural language processing approach for pediatric leukemia. *JCO Clin. Cancer Inform.*, 7:e2300009.

Philipp Koehn and Rebecca Knowles. 2017. Six challenges for neural machine translation. In *Proceedings of the First Workshop on Neural Machine Translation*, pages 28–39, Vancouver. Association for Computational Linguistics.

Fabrício Kury, Alex Butler, Chi Yuan, Li-heng Fu, Yingcheng Sun, Hao Liu, Ida Sim, Simona Carini, and Chunhua Weng. 2020. Chia, a large annotated corpus of clinical trial eligibility criteria. *Scientific Data*, 7(1):281.

Jinhyuk Lee, Wonjin Yoon, Sungdong Kim, Donghyeon Kim, Sunkyu Kim, Chan Ho So, and Jaewoo Kang. 2019. Biobert: a pre-trained biomedical language representation model for biomedical text mining. *Bioinformatics*, 36(4):1234–1240.

Songda Li, Yunqi Zhang, Chunyuan Deng, Yake Niu, and Hui Zhao. 2024. Better late than never: Model-agnostic hallucination post-processing framework towards clinical text summarization. In *Findings of the Association for Computational Linguistics: ACL 2024*, pages 995–1011, Bangkok, Thailand. Association for Computational Linguistics.

Yi Li, Haonan Wang, Qixiang Zhang, Boyu Xiao, Chenchang Hu, Hualiang Wang, and Xiaomeng Li. 2025. Unieval: Unified holistic evaluation for unified multimodal understanding and generation. *Preprint*, arXiv:2505.10483.

Cong Liu, Chi Yuan, Alex M Butler, Richard D Carvajal, Ziran Ryan Li, Casey N Ta, and Chunhua Weng. 2019. DQueST: dynamic questionnaire for search of clinical trials. *J. Am. Med. Inform. Assoc.*, 26(11):1333–1343.

Pengfei Liu, Weizhe Yuan, Jinlan Fu, Zhengbao Jiang, Hiroaki Hayashi, and Graham Neubig. 2023. Pre-train, prompt, and predict: A systematic survey of prompting methods in natural language processing. *ACM Comput. Surv.*, 55(9).

Zhihui Luo, Meliha Yetisgen-Yildiz, and Chunhua Weng. 2011. Dynamic categorization of clinical research eligibility criteria by hierarchical clustering. *J. Biomed. Inform.*, 44(6):927–935.

Curtis L Meinert. 2012. *ClinicalTrials: design, conduct and analysis*, volume 39. OUP USA.

Johannes Moll, Louisa Fay, Asfandyar Azhar, Sophie Ostmeier, Tim Lueth, Sergios Gatidis, Curtis Langlotz, and Jean-Benoit Delbrouck. 2025. Structuring radiology reports: Challenging llms with lightweight models. *arXiv preprint arXiv:2506.00200*.

Preksha Nema and Mitesh M. Khapra. 2018. Towards a better metric for evaluating question generation systems. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pages 3950–3959, Brussels, Belgium. Association for Computational Linguistics.

Mark Neumann, Emily Alsentzer, Alistair Johnson, and Abhinav Singh. 2024. Medalign: Benchmarking foundation models for multilingual clinical text understanding. *Journal of Biomedical Informatics*, 152:104512.

Yizhao Ni, Monica Bermudez, Stephanie Kennebeck, Stacey Liddy-Hicks, and Judith Dexheimer. 2019. A real-time automated patient screening system for clinical trials eligibility in an emergency department: Design and evaluation. *JMIR Med. Inform.*, 7(3):e14185.

Ankit Pal, Logesh Umapathi, and Malaikannan Sankarasubbu. 2022a. Medmcqa: A large-scale multi-subject multi-choice dataset for medical domain question answering. *NeurIPS Datasets and Benchmarks Track*.

Ankit Pal, Logesh Kumar Umapathi, and Malaikannan Sankarasubbu. 2022b. Medmcqa: A large-scale multi-subject multi-choice dataset for medical domain question answering. In *Proceedings of the Conference on Health, Inference, and Learning*, volume 174 of *Proceedings of Machine Learning Research*, pages 248–260. PMLR.

Kishore Papineni, Salim Roukos, Todd Ward, and Wei-Jing Zhu. 2001. BLEU: A method for automatic evaluation of machine translation. In *Proceedings of the 40th Annual Meeting on Association for Computational Linguistics - ACL '02*, pages 311–318, Morristown, NJ, USA. Association for Computational Linguistics.

Jimyung Park, Yilu Fang, Casey Ta, Gongbo Zhang, Betina Idnay, Fangyi Chen, David Feng, Rebecca Shyu, Emily R. Gordon, Matthew Spotnitz, and Chunhua Weng. 2024a. Criteria2query 3.0: Leveraging generative large language models for clinical trial eligibility query generation. *Journal of Biomedical Informatics*, 154:104649.

Jimyung Park, Yilu Fang, Casey Ta, Gongbo Zhang, Betina Idnay, Fangyi Chen, David Feng, Rebecca Shyu, Emily R Gordon, Matthew Spotnitz, and Chunhua Weng. 2024b. Criteria2Query 3.0: Leveraging generative large language models for clinical trial eligibility query generation. *J. Biomed. Inform.*, 154(104649):104649.

Weizhen Qi, Yu Yan, Yeyun Gong, Dayiheng Liu, Nan Duan, Jiusheng Chen, Ruofei Zhang, and Ming Zhou. 2020. ProphetNet: Predicting future n-gram for sequence-to-SequencePre-training. In *Findings of the Association for Computational Linguistics: EMNLP 2020*, pages 2401–2410, Online. Association for Computational Linguistics.

Colin Raffel, Noam Shazeer, Adam Roberts, Katherine Lee, Sharan Narang, Michael Matena, Yanqi Zhou, Wei Li, and Peter J. Liu. 2020. Exploring the limits of transfer learning with a unified text-to-text transformer. *J. Mach. Learn. Res.*, 21(1).

Preethi Raghavan, James L Chen, Eric Fosler-Lussier, and Albert M Lai. 2014. How essential are unstructured clinical narratives and information fusion to clinical trial recruitment? *AMIA Summits Transl. Sci. Proc.*, 2014:218–223.

Pranav Rajpurkar, Robin Jia, and Percy Liang. 2018. Know what you don't know: Unanswerable questions for SQuAD. In *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, Stroudsburg, PA, USA. Association for Computational Linguistics.

Jessica Ross, Samson Tu, Simona Carini, and Ida Sim. 2010. Analysis of eligibility criteria complexity in clinical trials. *Summit On Translat. Bioinforma.*, 2010:46–50.

Veronika Smilga and Hazem Alabiad. 2024. TüDuo at SemEval-2024 task 2: Flan-t5 and data augmentation for biomedical NLI. In *Proceedings of the 18th International Workshop on Semantic Evaluation (SemEval-2024)*, pages 737–744, Mexico City, Mexico. Association for Computational Linguistics.

Andrew L Smith, Felix Greaves, and Trishan Panch. 2023. Hallucination or confabulation? neuroanatomy as metaphor in large language models. *PLOS Digit. Health*, 2(11):e0000388.

Paul Trust and Rosane Minghim. 2024. A study on text classification in the age of large language models. *Machine Learning and Knowledge Extraction*, 6(4):2688–2721.

Shuo Wan, Tianyang Gao, Yichi Zhang, and Zhen Wang. 2023. A survey of deep active learning for foundation models. *Intelligent Computing*, 2(2):0058.

Xiaoqiang Wang, Bang Liu, Siliang Tang, and Lingfei Wu. 2022. QRelScore: Better evaluating generated questions with deeper understanding of context-aware relevance. In *Proceedings of the 2022 Conference on Empirical Methods in Natural Language Processing*, pages 562–581, Abu Dhabi, United Arab Emirates. Association for Computational Linguistics.

L L Weed. 1968. Medical records that guide and teach. *N. Engl. J. Med.*, 278(11):593–600.

Chunhua Weng, Xiaoying Wu, Zhihui Luo, Mary Regina Boland, Dimitri Theodoratos, and Stephen B Johnson. 2011. EliXR: an approach to eligibility criteria extraction and representation. *J. Am. Med. Inform. Assoc.*, 18 Suppl 1(Supplement 1):i116–24.

Michael Wornow, Alejandro Lozano, Dev Dash, Jenelle Jindal, Kenneth W Mahaffey, and Nigam H Shah. 2025. Zero-shot clinical trial patient matching with llms. *NEJM AI*, 2(1):AIcs2400360.

Xiaoyang Yi, Yuru Bao, Jian Zhang, Yifang Qin, and Faxin Lin. 2024. Integrating structural semantic knowledge for enhanced information extraction pretraining. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 2156–2171, Miami, Florida, USA. Association for Computational Linguistics.

Chi Yuan, Patrick B. Ryan, Casey Ta, Yixuan Guo, Ziran Li, Jill Hardin, Rupa Makadia, Peng Jin, Ning Shang, Tian Kang, and Chunhua Weng. 2019. Criteria2Query: a natural language interface to clinical databases for cohort definition. *J. Am. Med. Inform. Assoc.*, 26(4):294–305.

Hongyi Yuan, Zheng Yuan, Ruyi Gan, Jiaxing Zhang, Yutao Xie, and Sheng Yu. 2022. BioBART: Pretraining and evaluation of a biomedical generative language model. In *Proceedings of the 21st Workshop on Biomedical Language Processing*, pages 97–109, Dublin, Ireland. Association for Computational Linguistics.

Tianyi Zhang, Varsha Kishore, Felix Wu, Kilian Q. Weinberger, and Yoav Artzi. 2020. Bertscore: Evaluating text generation with bert. *Preprint*, arXiv:1904.09675.

Angelo Ziletti and Leonardo D'Ambrosi. 2025. Generating patient cohorts from electronic health records using two-step retrieval-augmented text-to-sql generation. *Preprint*, arXiv:2502.21107.

A Appendix

A.1 Prompts

A.1.1 CTQG initial dataset generation

I'll give you (one by one) a set of clinical trial inclusion/exclusion criteria and I need you to turn them into a question, as if in a form. e.g. for criteria "patient is > 18" the question would be "is the patient > 18?"

A.1.2 Question generation for Clinical Trials

You are a clinical assistant specialized in communicating eligibility criteria for clinical trials. Your task is to transform inclusion or exclusion criteria into understandable questions directed at patients in English, while maintaining both clinical accuracy and clarity of language.

Additionally, you must briefly reason out loud before generating each question, explaining step by step how you break down the criterion, what terms you identify, and how you decide to formulate the questions. This reasoning must be clear, logical, and concise, and should be included just before each group of questions.

Objective: Convert each criterion into one or more clear and understandable questions in English, without losing medical rigor.

Important instructions (read carefully and follow all of them):

1. *Analyze each criterion carefully: if the same criterion contains multiple clinical conditions, diseases, values, histories, or options, you must generate a separate question for each of those elements. Do not combine multiple conditions into a single question.*

2. *Before generating the questions, write a brief explanation of your reasoning in English (chain of thought), identifying the relevant parts of the clinical criterion and justifying how you are going to split them.*

3. *Always use the following format for your answers:*

   - *"Reasoning: [your step-by-step explanation in English]"*
   - *"New question N: [generated question]"*
   - *If there is more than one question for that criterion: "New question N: [question 1] || [question 2] || [question 3] ..."*

4. *Keep the original abbreviations (e.g., VIH, BMI, COPD). Do not explain or expand them.*

5. *Do not rewrite or interpret the criteria. Only transform them into questions.*

6. *Always generate the questions in English.*

Reasoning example:
Criterion: Age ≥ 18 years old Reasoning: The criterion refers to age, with a threshold of 18 years. It is a single condition related to minimum age. New question 1: Is the patient ≥18 years old?
Other examples without reasoning:
Example 1:
Criterion: Age ≥ 18 years old
Question: Is the patient ≥18 years old?
Example 2:

...

A.1.3 Question generation for SQuAD

You are a documentalist, expert in converting sentences into questions. Your task is to extract from the original text understandable questions in English which answer is included in the same text, while maintaining both accuracy and clarity of language.

Additionally, you must briefly reason out loud before generating each question, explaining step by step how you break down the text, what terms you identify, and how you decide to formulate the questions. This reasoning must be clear, logical, and concise, and should be included just before each group of questions.

Objective: Convert each sentence into one or more clear and understandable questions in English, without losing rigor.

Important instructions (read carefully and follow all of them):

1. *Analyze each text carefully: if the same text contains multiple relevant questions, you must generate them. If you consider that there is no relevant question to be generated, simply write "Unknown"*

2. *Before generating the questions, write a brief explanation of your reasoning in English (chain of thought), identifying the relevant parts of the text and justifying how you are going to split them.*

3. *Always use the following format for your answers:*

   - *"Reasoning: [your step-by-step explanation in English]"*
   - *"New question N: [generated question]"*

- *If there is more than one question for that criterion: "New question N: [question 1] || [question 2] || [question 3] ..."*

4. *Keep the original abbreviations (e.g., VIH, BMI, COPD). Do not explain or expand them.*

5. *Do not rewrite or interpret the text. Only transform them into questions.*

6. *Always generate the questions in English.*

Remember: if necessary, you should generate various questions separated by "?", and avoid including new lines in the questions and between them if many are generated
Example 1:
Criterion: Cultural reactions have varied from ridicule to admiration; many common stereotypes exist regarding redheads and they are often portrayed as fiery-tempered.
Question: What type of temper are people with red hair considered to have?
Example 2:

...

B Annotation guidelines for criterion-to-question mapping

Unit of annotation The primary unit is an *atomic clinical condition* expressed in an eligibility criterion (e.g., age constraint, ECOG status, prior treatment, specific comorbidity, organ function, pregnancy/contraception). A single textual criterion may yield one or multiple questions if it contains several independent conditions or clinically relevant exceptions.

B.1 Inputs and annotator setup

- **Source documents:** full inclusion/exclusion sections of oncology trial protocols.

- **Annotator:** one medically literate annotator, working alone (no adjudication, no inter-annotator agreement).

- **LLM assistance:** ChatGPT is used to draft questions from criteria; the annotator then manually edits the output to follow the rules in this section.

- **Effort:** typical time per question is a few seconds, with a single prompt per batch of criteria (no iterative prompt engineering per item).

B.2 Question generation rules

B.2.1 General phrasing

1. **Patient-centred formulation:** questions are formulated about the patient, not about abstract "participants". Typical patterns:

  - "Is the patient . . . ?"

  - "Does the patient have . . . ?"
  - "Has the patient . . . ?"

2. **Binary questions by default:** questions are yes/no. The logical polarity (inclusion vs. exclusion) is not encoded in the wording. For example, both "patients with X are excluded" and "patients must have X" yield questions of the form "Does the patient have X?"

3. **Preserve clinical content and terminology:** clinical constructs (e.g., ECOG, TNM, PD-L1, drug names, numeric thresholds) are preserved verbatim. Acronyms and units are not simplified or explained.

4. **Abstract away protocol management:** protocol-management phrasing ("must be", "is required", "prior to enrolment") is removed when it does not alter the clinical condition. Time constraints that affect eligibility are kept (e.g., "within N days before treatment").

B.2.2 Numbers, thresholds and comparators

5. **Preserve numeric operators and units:** inequalities ($\geq, \leq, >, <$) are kept as symbols in the question text. Units (g/dL, $\times$ULN, mL/min, mmHg, months, weeks, years, etc.) are preserved. Example pattern:

  Criterion: "Age $\geq X$ years" $\rightarrow$
  Question: "Is the patient $\geq X$ years old?"

6. **Multi-constraint tests:** when a criterion aggregates several lab thresholds or organ function conditions that jointly define a single concept (e.g., "adequate organ function"), a single question is created:

  "Does the patient meet the criteria for adequate [organ] function (e.g., [list of thresholds])?"

  If thresholds appear elsewhere as independent criteria, they may be annotated separately.

B.2.3 Splitting criteria into multiple questions

7. **One atomic condition $\rightarrow$ one question:** if a criterion includes several independent clauses (e.g., age + performance status + disease stage), these are split into separate questions, one per atomic condition.

8. **Exceptions and complex logic:** for patterns of the form "X except Y and Z":

- At least one question captures the broad condition (e.g., "Does the patient have any previous or current malignancy?").

- Additional questions may be created for clinically important exceptions when they are meaningful variables (e.g., major cardiovascular disease).

- Benign exceptions (e.g., vitiligo, alopecia) are not systematically turned into separate questions; they remain implicit in the logic.

B.2.4 Multi-choice vs. yes/no questions

9. **Yes/No for presence/absence:** conditions that are naturally binary (pregnancy, presence of a comorbidity, history of a given treatment, presence of brain metastases, etc.) are encoded as yes/no questions.

10. **List when categories are enumerated:** if a criterion explicitly enumerates mutually exclusive categories (e.g., tumour types, histologic subtypes, study cohorts), it is encoded as a single multi-choice question:

    "Which of the following applies to the patient? (1) ..., (2) ..., (3) ..."

    The corresponding answer type is a list. Follow-up criteria that merely continue the list are not considered separate items.

B.2.5 Target population

11. **Question population:** for each question, a separate field encodes the subpopulation for which the question is meaningful, e.g.:

    - "All patients"
    - "Women of childbearing potential"
    - "Male participants"
    - "Only if [brain metastases = yes]"

    Optionally, population restrictions may be repeated in the question text as a leading clause (e.g., "For women of childbearing potential: ...").

B.3 Summary of the annotation process

All questions are created by a single medically literate annotator using ChatGPT as a drafting tool, followed by manual post-editing to enforce the guidelines above. Each criterion is processed once (no double annotation, no adjudication), and the order of questions within each trial follows the original

ordering of criteria. When a criterion yields multiple questions, these appear immediately after the parent in the internal sheet.

C Question division experimental details

C.1 Data preparation details

- CTQG: there is a large imbalance in classes, where class 1 is over-represented compared to the other two (Table 10).

- QG-SQuAD: there is more balance than in CTQG, but this time there is one class that is under-represented, class 2 (Table 11).

C.2 Rules sample

The rules we extracted from the CTQG features are available in Table 12 and the ones for QG-SQuAD in Table 13.

C.3 Examples of criterion decomposition failures

Algorithm 2 Question division algorithm

Require: Labeled criterion $\{(x_i, y_i)\}$
1: Extract features $\Phi(x_i)$
2: Fit/keep high-precision rules $\mathcal{R}$
3: Train RandomForest on $(\Phi(x_i), y_i)$
4: Compute embeddings $E(x_i)$
5: Fine-tune transformer models $\{f_m\}$ on $(E(x_i), y_i)$

Algorithm 3 Inference and voting (precision-prioritized

Require: Criterion x, rules $\mathcal{R}$, RF, models $\{f_m\}$, thresholds $\tau_r, \tau_{ft}, \tau_{maj}$
1: Compute $\Phi(x)$ and $E(x)$
2: If a rule in $\mathcal{R}$ fires with confidence $\geq \tau_r$, **return** class
3: Get RF prediction (y_{rf}, c_{rf})
4: Get FT predictions $\{(y_m, c_m)\}$ and majority y_{maj} with support p_{maj} and min confidence C_{maj}
5: **if** $p_{maj} \geq \tau_{maj}$ **and** $C_{maj} \geq \tau_{ft}$ **then return** y_{maj}
6: **end if**
7: **if** $c_{rf} \geq \tau_{ft}$ **then return** y_{rf}
8: **end if**
9: **return** IDK

D Complementary results

Tables 15 and 16 present the complementary results of Tables 7 and 8, respectively, with additional metrics introduced section 4.2.3.

E Complementary information

In this last Appendix, we include all details on the methods we used (Tables 17, 18) or on the experimental set-up (Tables 19, 21, 20, 22).

Generated Question	Curated Question
Is the patient's predicted life expectancy > 3 months?	Is the patient's predicted life expectancy > 3 months?
For women of childbearing potential: Has a negative urine pregnancy test been performed within 28 days before enrolment?	Does the patient have a negative pregnancy test within 28 days of enrolment?
For women of childbearing potential: Is effective contraception in place?	Do they agree to use an efficacious contraception method?
Have all necessary screening procedures been completed within 28 days before enrolment?	Have all necessary screening procedures been completed within 28 days before enrolment?
Has the patient signed the Informed Consent Form (ICF) before any study-related procedures?	Has the patient signed the Informed Consent Form (ICF) before any study-related procedures?
(For patients in France only) Is the patient affiliated with the French Social Security System?	Is the patient affiliated with the French Social Security System?
Is the patient currently pregnant and/or lactating?	Is the patient pregnant and/or breastfeeding?
Has the patient had any previous or current malignancy of a different histology within the last 2 years, excluding in situ carcinoma of the cervix or adequately treated basal or squamous cell carcinoma of the skin?	Has the patient had any other previous or current malignancy?
–	Is that malignancy an *in situ* carcinoma of the cervix?
–	Is that malignancy an adequately treated non-melanoma skin cancer?
–	Has there been evidence of that malignancy within the last 2 years?

Table 9: Examples of transformations introduced during expert curation of LLM-generated questions. Curators standardize phrasing, simplify formulations, and decompose compound criteria into multiple atomic questionnaire items.

Class	Description	Proportion
0	criterion generates no question	0.196
1	criterion generates one question	0.647
2	criterion generates several questions	0.157

Table 10: Data class support for CTQG question division prediction.

Class	Description	Proportion
0	criterion generates no question	0.405
1	criterion generates one question	0.405
2	criterion generates several questions	0.190

Table 11: Data class support for QG-SQuAD question division prediction.

Rule condition	Class	Precision	Support
raw_word_len $\geq$ 36 AND shannon_char_entropy $\leq$ 4.1787	2	1.00	5
raw_word_len $\geq$ 39 AND num_clauses $\leq$ 4	2	1.00	5
raw_word_len $\leq$ 2 AND num_words $\leq$ 2	0	1.00	5
raw_char_len $\leq$ 179 AND raw_char_2grams_voc $\geq$ 113	2	1.00	5
raw_char_len $\geq$ 263 AND raw_char_2grams_voc $\leq$ 142	2	1.00	5
raw_char_len $\geq$ 216 AND raw_char_3grams_voc $\leq$ 174	2	1.00	5
raw_char_len $\geq$ 216 AND raw_char_4grams_voc $\leq$ 194	2	1.00	6
raw_char_len $\geq$ 273 AND raw_word_2grams_voc_lemma $\leq$ 38	2	1.00	5
raw_char_len $\leq$ 188 AND raw_word_2grams_voc_pos $\geq$ 15	2	1.00	5
raw_char_len $\geq$ 271 AND num_clauses $\leq$ 4	2	1.00	5
raw_char_len $\leq$ 12 AND num_words $\leq$ 2	0	1.00	6
raw_voc_len $\geq$ 28 AND shannon_char_entropy $\leq$ 4.1705	2	1.00	5
raw_voc_len $\leq$ 2 AND num_words $\leq$ 2	0	1.00	5
raw_voc_len $\leq$ 33 AND num_words $\geq$ 47	2	1.00	5

Table 12: Validated rule set for the main classifier. Each rule is defined by a condition, target class, precision, and support.

Rule condition	Class	Precision	Support
raw_char_2grams_voc $\leq$ 0 AND shannon_word_entropy $\geq$ 4	0	0.90	10
raw_voc_len $\geq$ 5 AND raw_word_2grams_voc_pos $\leq$ 0	0	0.83	6
raw_char_len $\leq$ 2 AND raw_word_voc_pos $\geq$ 5	1	0.80	5
raw_char_4grams_voc $\geq$ 5 AND raw_word_2grams_voc_pos $\leq$ 0	0	0.80	5
raw_char_4grams_voc $\leq$ 0 AND shannon_word_entropy $\geq$ 3	0	0.78	36
raw_char_len $\geq$ 5 AND raw_word_2grams_voc_pos $\leq$ 0	0	0.75	8
raw_char_2grams_voc $\leq$ 0 AND num_words $\geq$ 4	0	0.75	8
raw_char_len $\leq$ 0 AND shannon_word_entropy $\geq$ 3	0	0.74	42
raw_voc_len $\leq$ 2 AND raw_word_2grams_voc_pos $\geq$ 5	1	0.71	7

Table 13: Validated rule set derived from the SQuAD-style subset.

Criterion	Reference questionnaire	Seq2Seq model output
Male or female participants ≥18 years old and at least at the legal age of consent in countries where it is greater than 18.	(1) Is the patient ≥18 years old? (2) Is the patient at the legal age of consent in their country?	Is the patient ≥18 years old?
Signed and dated written informed consent according to ICH-GCP and local legislation prior to trial participation.	(1) Has the patient signed the informed consent form? (2) Is the consent compliant with ICH-GCP and local legislation?	Has the patient signed the informed consent form?
For women of childbearing potential: negative pregnancy test within 28 days before enrolment and effective contraception.	(1) Does the patient have a negative pregnancy test within 28 days of enrolment? (2) Do they agree to use an effective contraception method?	Has the patient had a negative pregnancy test within 28 days?
Histologically or cytologically confirmed extensive-stage small cell lung carcinoma.	(1) Has the diagnosis been confirmed histologically or cytologically? (2) Is the cancer classified as extensive-stage small cell lung carcinoma?	Has the patient been diagnosed with small cell lung cancer?
Availability of archival tumour tissue suitable for biomarker analysis.	(1) Is archival tumour tissue available? (2) Is the tissue suitable for biomarker analysis?	Is archival tumour tissue available?
Previous or current malignancy within the last two years excluding in situ carcinoma of the cervix or adequately treated basal or squamous cell carcinoma of the skin.	(1) Has the patient had any previous or current malignancy? (2) Is that malignancy an in situ carcinoma of the cervix? (3) Is it an adequately treated non-melanoma skin cancer? (4) Has there been evidence of that malignancy within the last two years?	Has the patient had any previous or current malignancy?
Adequate bone marrow, liver and renal function prior to enrolment.	(1) Does the patient have adequate bone marrow function? (2) Does the patient have adequate liver function? (3) Does the patient have adequate renal function?	Does the patient have adequate organ function?
Life expectancy greater than three months and ability to comply with study procedures.	(1) Is the patient's life expectancy greater than three months? (2) Is the patient able to comply with study procedures?	Is the patient's life expectancy greater than three months?
No prior systemic therapy for extensive-stage small cell lung cancer and no prior immunotherapy.	(1) Has the patient received prior systemic therapy? (2) Has the patient received prior immunotherapy?	Has the patient received prior therapy?

Figure 3: Examples where sequence-to-sequence models collapse multi-constraint eligibility criteria into a single question, omitting conditions that are explicitly represented as separate items in the reference questionnaire.

Hyperparameter	value
Activation function	Softmax
loss function	cross-entropy
dropout	0.1
class weighting	No
weight decay	0.000001
epochs	3
batch size	32
learning rate	0.000005
warm-up	1000 steps

Table 14: Best hyper parameters for transformers fine-tuning for question division prediction with QG-SQuAD.

Metrics (I)	QRelScore	METEOR	ROUGE-L	QSTS	QBLEU	BARTScore
BERT2BERT	0.34	0.32	0.47	0.69	0.38	-4.65
bioBART	0.43	0.39	0.52	**0.79**	0.41	-4.37
Llama3.3	0.68	0.44	0.47	**0.79**	0.46	-3.55
FLAN-T5	0.66	0.36	0.41	0.72	0.35	-3.83
ChatGPT	0.66	0.44	0.47	0.74	0.44	-3.49
DivAC-LLM	**0.74**	**0.53**	**0.56**	0.77	**0.52**	**-3.16**

Metrics (II)	BARTScore	fluency	clarity	conciseness	relevance	consistency
BERT2BERT	0.77	-5.22	0.88	0.76	0.77	0.78
bioBART	0.81	-4.86	0.88	0.80	0.81	0.82
Llama3.3	0.92	-3.60	0.89	0.92	0.92	0.92
FLAN-T5	0.86	-3.85	0.86	0.85	0.86	0.86
ChatGPT	0.91	-3.69	0.88	0.90	0.91	0.91
DivAC-LLM	**0.93**	**-3.38**	**0.91**	**0.92**	**0.93**	**0.92**

Metrics (III)	answerability	acceptance	answer consistency	overall	mean	scaled
BERT2BERT	0.77	0.78	0.75	0.78	0.11	0.32
bioBART	0.81	0.81	0.78	0.82	0.19	0.46
Llama3.3	0.93	0.91	0.84	0.91	0.36	0.71
FLAN-T5	0.87	0.85	0.80	0.85	0.29	0.58
ChatGPT	0.92	0.90	**0.85**	0.90	0.35	0.69
DivAC-LLM	**0.93**	**0.92**	0.83	**0.91**	**0.42**	**0.83**

Table 15: Extended automatic evaluation results on CTQG with respect to five different models compared with DivAC-LLM.

Metrics (I)	QRelScore	METEOR	ROUGE-L	QSTS	QBLEU	BARTScore
Gemini	0.46	0.23	0.23	**0.62**	0.15	-4.28
Gemini + div	0.35	0.24	0.30	0.58	**0.21**	-4.30
ChatGPT	**0.47**	0.22	0.22	**0.62**	0.15	-4.33
ChatGPT + div	0.33	0.24	0.31	0.59	**0.21**	-4.37
Llama3.3	0.32	0.17	0.24	0.52	0.18	-4.63
Llama3.3 + div	0.28	0.21	0.32	0.54	0.17	-4.47
ProphetNet-large	0.26	**0.28**	**0.34**	0.30	0.14	**-3.75**

Metrics (II)	BARTScore	fluency	clarity	conciseness	relevance	consistency
Gemini	**-3.74**	0.81	0.89	0.90	0.90	0.90
Gemini + div	-4.28	0.78	0.82	0.82	0.84	0.82
ChatGPT	-3.77	0.85	**0.91**	0.91	**0.92**	0.91
ChatGPT + div	-4.35	0.77	0.79	0.80	0.82	0.80
Llama3.3	-4.56	**0.87**	0.87	0.87	0.88	0.87
Llama3.3 + div	-4.64	0.86	0.86	0.86	0.88	0.86
ProphetNet-large	-4.19	0.66	0.76	0.77	0.77	0.77

Metrics (III)	answerability	acceptance	answer consistency	overall	mean	scaled
Gemini	0.90	0.89	0.73	0.86	0.19	0.62
Gemini + div	0.83	0.82	0.72	0.81	0.15	0.52
ChatGPT	0.91	**0.91**	0.75	0.88	0.19	0.65
ChatGPT + div	0.80	0.80	0.73	0.79	0.14	0.50
Llama3.3	0.88	0.88	0.69	0.85	0.11	0.47
Llama3.3 + div	0.86	0.87	0.73	0.85	0.14	0.56
ProphetNet-large	0.77	0.77	0.67	0.74	0.15	0.46

Table 16: Extended automatic evaluation results on QG-SQuAD comparing fine-tuned models and LLMs with and without question division module.

Feature	Mean value
AND or OR in text	0.52
has semicolon	0.03
has conjonction	0.57
number of clauses	2.49
number of words	18.32
word length	15.73
character length	108.58
vocab. length	13.82
word bigrams	14.44
character bigrams	68.92
word trigrams	13.66
character trigrams	89.26
word quadrigrams	12.72
character quadrigrams	94.41
word lemmatized	13.73
word bigrams_lemma	14.42
word trigrams_lemma	13.65
word quadrigrams_lemma	12.72
word POS	7.39
word bigrams POS	7.00
word trigrams POS	6.13
word quadrigrams POS	5.28
word NER	1.24
word bigrams NER	0.66
word trigrams NER	0.31
word quadrigrams NER	0.14
shannon character entropy	4.01
shannon word entropy	3.45
conditional word entropy	0.12
conditional character entropy	0.08
renyi word entropy	0.12
renyi character entropy	1.69

Table 17: Average feature values per criterion in CTQG.

Voting Strategy	Description / Decision Rule
`pred`	If both the rule-based model (`prediction`) and BioBERT agree on a class different from 2, use that class; otherwise, output 2.
`default1`	If both the rule-based model and BioBERT agree on a class different from 1, use that class; otherwise, output 1.
`majority_transformer`	If the two transformers (BioBERT and BioMedLM) agree, take their class; otherwise, fall back to the rule-based model.
`majority_rules`	If the rule-based model agrees with either transformer, use the rule-based prediction; otherwise, fall back to BioBERT.
`hybrid_priority`	Prioritize class 1 if any transformer predicts 1; prioritize class 2 if rules predict 2; otherwise, if rules and BioBERT agree, keep that; else 0.
`consensus_only`	Output the class only if all three models (rules, BioBERT, BioMedLM) fully agree; otherwise, label as -1 (uncertain).
`strict_negative`	Reject (-1) if all predict -1; if all agree otherwise, output that class; else fall back to BioBERT.
`2of3`	If any two of the three models agree, take that class; otherwise, label as -1 (no consensus).

Table 18: Overview of voting strategies combining rule-based predictions, BioBERT, and BioMedLM outputs.

Hyperparameter	Value
Activation function	Softmax
Loss function	Cross-entropy
Dropout	0.5
Class weighting	No
Weight decay	5e-6
Epochs	8
Batch size	4
Learning rate	1e-5
Warm-up	100 steps

Table 19: Best hyperparameters for transformer fine-tuning (question division, CTQG).

Metric	Value	Assumptions / Notes
Total utterances	92	
Total tokens	24,949	
Avg. tokens / utterance	271.200	Computed as 24,949/92
GPU time	0.153 h (9.000 min)	Inference only
Energy consumption	0.046 kWh	0.153 h $\times$ 0.300 kW
CO_2 emissions	9.200 g	EU grid avg. 0.200 kgCO2/kWh
Electricity cost	€0.009	€0.20/kWh (EU, 2024)
Cloud rental	€0.380	€2.50/GPUh (on-demand)

Table 20: Approximate compute and environmental footprint for 92 utterances (24,949 tokens) on one NVIDIA A100 40GB at 300.000 W. Power and emissions factors from NVIDIA (2022) and IEA (2023).

Experiment	Duration	GPU h	Energy (kWh)	Elec. (€)	Cloud (€)	CO_2 (kg)
CTQG	~2 weeks	350	105	21	875	21
QG-SQuAD	~1 month	700	210	42	1750	42

Table 21: Runtime and cost estimates for grid search (QG + division) on a single A100 40GB at 300.000 W. Prices: €0.20/kWh (EU 2024), €2.50/GPUh (on-demand). Emissions: 0.200 kgCO2/kWh.

Parameter	CTQG	QG-SQuAD
Batch size	16	32
Learning rate	0.0001	0.00001
Epochs	8	12
Warm-up steps	50	1500

Table 22: Hyperparameter configurations used in CTQG and QG-SQuAD experiments.

Hyperparameter	CTQG	QG-SQuAD
Epochs	[4, 6, 8, 10, 12]	[6, 8, 10, 12, 14]
Batch size	[16, 32, 64, 128]	[32, 64]
Learning rate	$[5e^{-6}, 1e^{-6}, 1e^{-5}, 1e^{-4}, 5e^{-5}]$	$[5e^{-5}, 1e^{-5}]$
Warm-up steps	[10, 50, 100]	[1k, 5k, 10k]

Table 23: Grid search hyperparameter ranges for CTQG and QG-SQuAD experiments.