META-LEARNING WITH NEURAL TANGENT KERNELS

ABSTRACT

Model Agnostic Meta-Learning (MAML) has emerged as a standard framework for meta-learning, where a *meta-model* is learned with the ability of fast adapting to new tasks. However, as a double-looped optimization problem, MAML needs to differentiate through the whole inner-loop optimization path for every outer-loop training step, which may lead to both computational inefficiency and sub-optimal solutions. In this paper, we generalize MAML to allow meta-learning to be defined in function spaces, and propose the first meta-learning paradigm in the Reproducing Kernel Hilbert Space (RKHS) induced by the meta-model's Neural Tangent Kernel (NTK). Within this paradigm, we introduce two meta-learning algorithms in the RKHS, which no longer need a sub-optimal iterative inner-loop adaptation as in the MAML framework. We achieve this goal by 1) replacing the adaptation with a fast-adaptive regularizer in the RKHS; and 2) solving the adaptation analytically based on the NTK theory. Extensive experimental studies demonstrate advantages of our paradigm in both efficiency and quality of solutions compared to related meta-learning algorithms. Another interesting feature of our proposed methods is that they are demonstrated to be more robust to adversarial attacks and out-of-distribution adaptation than popular baselines, as demonstrated in our experiments.

1 INTRODUCTION

Meta-learning (Schmidhuber, 1987) has made tremendous progresses in the last few years. It aims to learn abstract knowledge from many related tasks so that fast adaption to new and unseen tasks becomes possible. For example, in few-shot learning, meta-learning corresponds to learning a meta-model or meta-parameters so that they can fast adapt to new tasks with a limited number of data samples. Among all existing meta-learning methods, Model Agnostic Meta-Learning (MAML) (Finn et al., 2017) is perhaps one of the most popular and flexible ones, with a number of follow-up works such as (Nichol et al., 2018; Finn et al., 2018; Yao et al., 2019; Khodak et al., 2019a;b; Denevi et al., 2019; Fallah et al., 2020; Lee et al., 2020; Tripuraneni et al., 2020). MAML adopts a double-looped optimization framework, where adaptation is achieved by one or several gradient-descent steps in the inner-loop optimization. Such a framework could lead to some undesirable issues related to computational inefficiency and sub-optimal solutions. The main reasons are that 1) it is computationally expensive to back-propagate through a stochastic-gradient-descent chain, and 2) it is hard to tune the number of adaptation steps in the inner-loop as it can be different for both training and testing. Several previous works tried to address these issues, but they can only alleviate them to certain extents. For example, first order MAML (FOMAML) (Finn et al., 2017) ignores the high-order terms of the standard MAML, which can speed up the training but may lead to deteriorated performance; MAML with Implicit Gradient (iMAML) (Rajeswaran et al., 2019) directly minimizes the objective of the outer-loop without performing the inner-loop optimization. But it still needs an iterative solver to estimate the meta-gradient.

To better address these issues, we propose two algorithms that generalize meta-learning to the Reproducing Kernel Hilbert Space (RKHS) induced by the meta-model's Neural Tangent Kernel (NTK) (Jacot et al., 2018). In this RKHS, instead of using parameter adaptation, we propose to perform an implicit function adaptation. To this end, we introduce two algorithms to avoid explicit function adaptation: one replaces the function adaptation step in the inner-loop with a new meta-objective with a fast-adaptive regularizer inspired by MAML; the other solves the adaptation problem analytically based on tools from NTK so that the meta-objective can be directly evaluated on samples in a closed-form. When restricting the function space to be RKHS, the solutions to the proposed

two algorithms become conveniently solvable. In addition, we provide theoretical analysis on our proposed algorithms in the cases of using fully-connected neural networks and convolutional neural networks as the meta-model. Our analysis shows close connections between our methods and the existing ones. Particularly, we prove that one of our algorithms is closely related to MAML with some high-order terms ignored in the meta-objective function, thus endowing effective optimization. In summary, our main contributions are:

- We re-analyze the meta-learning problem and introduce two new algorithms for meta-learning in RKHS. Different from all existing meta-learning algorithms, our proposed methods can be solved efficiently without cumbersome chain-based adaptations.

- We conduct theoretically analysis on the proposed algorithms, which suggests that our proposed algorithms are closely related to the existing MAML methods when fully-connected neural networks and convolutional neural networks are used as the meta-model.

- We conduct extensive experiments to validate our algorithms. Experimental results indicate the effectiveness of our proposed methods, through standard few-shot learning, robustness to adversarial attacks and out-of-distribution adaptation.

2 PRELIMINARIES

2.1 META-LEARNING

Meta-learning can be roughly categorized as black-box adaptation methods (Andrychowicz et al., 2016; Graves et al., 2014; Mishra et al., 2018), optimization-based methods (Finn et al., 2017), non-parametric methods (Vinyals et al., 2016; Snell et al., 2017; Triantafillou et al., 2020) and Bayesian meta-learning methods (Finn et al., 2018; Yoon et al., 2018; Ravi & Beatson, 2019). In this paper, we focus on the framework of Model Agnostic Meta-Learning (MAML) (Finn et al., 2017), which has two key components, meta initialization and fast adaptation. Specifically, MAML solves the meta-learning problem through a double-looped optimization procedure. In the inner-loop, MAML runs a task-specific adaptation procedure to transform a meta-parameter, $\boldsymbol{\theta}$, to a task-specific parameter, $\{\boldsymbol{\phi}_m\}_{m=1}^B$, for a total of B different tasks. In the outer-loop, MAML minimizes a total loss of $\sum_{m=1}^B \mathcal{L}(f_{\boldsymbol{\phi}_m})$ with respect to meta-parameter $\boldsymbol{\theta}$, where $f_{\boldsymbol{\phi}_m}$ is the model adapted on task m that is typically represented by a deep neural network. It is worth noting that in MAML, one potential problem is to compute the meta-gradient $\nabla_{\boldsymbol{\theta}} \sum_{m=1}^B \mathcal{L}(f_{\boldsymbol{\phi}_m})$. It requires one to differentiate through the whole inner-loop optimization path, which could be very inefficient.

2.2 GRADIENT FLOW

Our proposed method relies on the concept of gradient flow. Generally speaking, gradient flow is a continuous-time version of gradient descent. In the finite-dimensional parameter space, a gradient flow is defined by an ordinary differential equation (ODE), $\mathrm{d}\boldsymbol{\theta}^t/\mathrm{d}t = -\nabla_{\boldsymbol{\theta}^t} F(\boldsymbol{\theta}^t)$, with a starting point $\boldsymbol{\theta}^0$ and function $F : R^d \to R$. Gradient flow is also known as steepest descent curve.

One can generalize gradient flows to infinite-dimensional function spaces. Specifically, given a function space $\mathcal{H}$, a functional $\mathcal{F} : \mathcal{H} \to R$, and a starting point $f^0 \in \mathcal{H}$, a gradient flow is similarly defined as the solution of $\mathrm{d}f^t/\mathrm{d}t = -\nabla_{f^t}\mathcal{F}(f^t)$. This is a curve in the function space $\mathcal{H}$. In this paper, we use notation $\nabla_{f^t}\mathcal{F}(f^t)$, instead of $\nabla_{\mathcal{H}}\mathcal{F}(f^t)$, to denote the general function derivative of the energy functional $\mathcal{F}$ with respect to function f^t (Villani, 2008).

2.3 THE NEURAL TANGENT KERNEL

Neural Tangent Kernel (NTK) is a recently proposed technique for characterizing the dynamics of a neural network under gradient descent (Jacot et al., 2018; Arora et al., 2019; Lee et al., 2019). NTK allows one to analyze deep neural networks (DNNs) in RKHS induced by NTK. One immediate benefit of this is that the loss functional in the function space is often convex, even when it is highly non-convex in the parameter space (Jacot et al., 2018) [*]. This property allows one to better understand the property of DNNs. Specifically, let $f_{\boldsymbol{\theta}}$ be a DNN parameterized by $\boldsymbol{\theta}$. The corresponding NTK Θ

---

[*]Let $\mathcal{H}$ be the function space, F be the realization function for neural network defined in Section 3.2. Note even if a functional loss (*e.g.*, L2 loss) $\mathcal{E} : \mathcal{H} \to R$ is convex on $\mathcal{H}$, the composition $\mathcal{E} \circ F$ is in general not.

is defined as: $\boldsymbol{\Theta}(\mathbf{x}_1, \mathbf{x}_2) = \frac{\partial f_{\boldsymbol{\theta}}(\mathbf{x}_1)}{\partial \boldsymbol{\theta}} \frac{\partial f_{\boldsymbol{\theta}}(\mathbf{x}_2)}{\partial \boldsymbol{\theta}}^{\mathsf{T}}$, where $\mathbf{x}_1, \mathbf{x}_2$ are two data points. In our paper, we will define meta-learning on an RKHS induced by such a kernel.

3 META-LEARNING IN RKHS

We first define the meta-learning problem in a general function space, and then restrict the function space to be an RKHS, where two frameworks will be proposed to make meta-learning feasible in RKHS, along with some theoretical analysis. For simplicity, in the following we will hide the superscript time t unless necessary, *e.g.*, when the analysis involves time-changing.

3.1 META-LEARNING IN FUNCTION SPACE

Given a function space $\mathcal{H}$, a distribution of tasks $P(\mathcal{T})$, and a loss function $\mathcal{L}$, the goal of meta-learning is to find a *meta function* $f^* \in \mathcal{H}$, so that it performs well after simple adaptation on a specific task. Let $\mathcal{D}_m^{tr}$ and $\mathcal{D}_m^{test}$ be the training and testing sets, respectively, sampled from a data distribution of task $\mathcal{T}_m$. The meta-learning problem on function space $\mathcal{H}$ is defined as:

$$f^* = \arg\min_{f \in \mathcal{H}} \mathcal{E}(f), \text{ with } \mathcal{E}(f) = \mathbb{E}_{\mathcal{T}_m} \left[\mathcal{L} \left(\mathsf{Adapt}(f, \mathcal{D}_m^{tr}), \mathcal{D}_m^{test} \right) \right] \tag{1}$$

where Adapt denotes some adaptation algorithms, *e.g.*, several steps of gradient descent; $\mathcal{E} : \mathcal{H} \to R$ is called energy functional, which is used to evaluate the model represented by the function f.

In theory, solving equation 1 is equivalent to solving the gradient flow equation $\mathrm{d}f^t/\mathrm{d}t = -\nabla_{f^t}\mathcal{E}(f^t)$. However, solving the gradient flow equation is generally infeasible, since i) it is hard to directly apply optimization methods in function space and ii) the energy functional $\mathcal{E}$ contains an adaptation algorithm Adapt, making the functional gradient infeasible. Thus, a better way is to design a special energy functional so that it can be directly optimized without running the specific adaptation algorithm. In the following, we first specify the functional meta-learning problem in RKHS, and then propose two methods to derive efficient solutions for the problem.

3.2 META-LEARNING IN RKHS

We consider a function f that is parameterized by $\boldsymbol{\theta} \in \mathbb{R}^P$, denoted as $f_{\boldsymbol{\theta}}$, with P being the number of parameters. Define a realization function $F : \mathbb{R}^P \to \mathcal{H}$ that maps parameters to a function. With these, we can then define an energy function in the parameter space as $E \triangleq \mathcal{E} \circ F : R^P \to R$ with $\circ$ being the composition operator. Consequently, with an initialized $\boldsymbol{\theta}^0$, we can define the gradient flow of $E(\boldsymbol{\theta}^t)$ in parameter space as: $\mathrm{d}\boldsymbol{\theta}^t/\mathrm{d}t = -\nabla_{\boldsymbol{\theta}^t}E(\boldsymbol{\theta}^t)$. In the following, we first establish an equivalence between the gradient flow in RKHS and the gradient flow in the parameter space. We then propose two algorithms for meta-learning in the RKHS induced by NTK.

Theorem 1 *Let $\mathcal{H}$ be an RKHS induced by the NTK $\boldsymbol{\Theta}$ of $f_{\boldsymbol{\theta}}$. With $f^0 = f_{\boldsymbol{\theta}^0}$, the gradient flow of $\mathcal{E}(f^t)$ coincides with the function evolution of $f_{\boldsymbol{\theta}^t}$ driven by the gradient flow of $E(\boldsymbol{\theta}^t)$.*

The proof of Theorem 1 relies on the property of NTK (Jacot et al., 2018), and is provided in the Appendix. Theorem 1 serves as a foundation of our proposed methods, which indicates that solving the meta-learning problem in RKHS can be done by some appropriate manipulations. In the following, we describe two different approaches termed Meta-RKHS-I and Meta-RKHS-II, respectively.

3.3 META-RKHS-I: META-LEARNING IN RKHS WITHOUT ADAPTATION

Our goal is to design an energy functional that has no adaptation component, but is capable of achieving fast adaptation. For this purpose, we first introduce two definitions: empirical loss function $\mathcal{L}(f_{\boldsymbol{\theta}}, \mathcal{D}_m)$ and expected loss function $\mathcal{L}(f_{\boldsymbol{\theta}})$. Let $\mathcal{D}_m = \{\mathbf{x}_{m,i}, \mathbf{y}_{m,i}\}_{i=1}^n$ be a set containing the data of a regression task $\mathcal{T}_m$. The empirical loss function $\mathcal{L}(f_{\boldsymbol{\theta}}, \mathcal{D}_m)$ and the expected loss function $\mathcal{L}_m(f_{\boldsymbol{\theta}})$ are defined as:

$$\mathcal{L}(f_{\boldsymbol{\theta}}, \mathcal{D}_m) = \frac{1}{2n} \sum_{i=1}^n \left\| f(\mathbf{x}_{m,i}) - \mathbf{y}_{m,i} \right\|^2, \quad \mathcal{L}_m(f_{\boldsymbol{\theta}}) = \mathbb{E}_{\mathbf{x}_m, \mathbf{y}_m} \left[\frac{1}{2} \left\| f(\mathbf{x}_m) - \mathbf{y}_m \right\|^2 \right].$$

Our idea is to define a regularized functional such that it endows the ability of fast adaptation in RKHS. Our solution is based on some property of the standard MAML. We start from analyzing the meta-objective of MAML with a k-step gradient-descent adaptation, *i.e.*, applying k gradient-descent steps in the inner-loop. The objective can be formulated as

$$\boldsymbol{\theta}^* = \arg\min_{\boldsymbol{\theta}} \mathbb{E}_{\mathcal{T}_m} \left[\mathcal{L}(f_{\boldsymbol{\phi}}, \mathcal{D}_m^{test}) \right], \text{ with } \boldsymbol{\phi} = \boldsymbol{\theta} - \alpha \sum_{i=0}^{k-1} \nabla_{\boldsymbol{\theta}_i} \mathcal{L}(f_{\boldsymbol{\theta}_i}, \mathcal{D}_m^{tr}),$$

where α is the learning rate of the inner-loop, $\boldsymbol{\theta}_0 = \boldsymbol{\theta}$, and $\boldsymbol{\theta}_{i+1} = \boldsymbol{\theta}_i - \alpha \nabla_{\boldsymbol{\theta}_i} \mathcal{L}(f_{\boldsymbol{\theta}_i}, \mathcal{D}_m^{tr})^{\dagger}$. By Taylor expansion, we have

$$\mathbb{E}_{\mathcal{T}_m} \left[\mathcal{L}(f_{\boldsymbol{\phi}}, \mathcal{D}_m^{test}) \right] \approx \mathbb{E}_{\mathcal{T}_m} \left[\mathcal{L}(f_{\boldsymbol{\theta}}, \mathcal{D}_m^{test}) - \alpha \sum_{i=0}^{k-1} \nabla_{\boldsymbol{\theta}_i} \mathcal{L}(f_{\boldsymbol{\theta}_i}, \mathcal{D}_m^{tr}) \nabla_{\boldsymbol{\theta}} \mathcal{L}(f_{\boldsymbol{\theta}}, \mathcal{D}_m^{test})^{\intercal} \right]. \quad (2)$$

Since $\mathcal{D}_m^{tr}$ and $\mathcal{D}_m^{test}$ come from the same distribution, equation 2 is an unbiased estimator of

$$\mathcal{M}_k = \mathbb{E}_{\mathcal{T}_m}[\mathcal{L}_m(f_{\boldsymbol{\theta}}) - \sum_{i=0}^{k-1} \beta_i], \text{ where } \beta_i = \alpha \nabla_{\boldsymbol{\theta}_i} \mathcal{L}_m(f_{\boldsymbol{\theta}_i}) \nabla_{\boldsymbol{\theta}} \mathcal{L}_m(f_{\boldsymbol{\theta}})^{\intercal}. \quad (3)$$

We focus on the case of $k = 1$, which is $\mathcal{M}_1 = \mathbb{E}_{\mathcal{T}_m}[\mathcal{L}_m(f_{\boldsymbol{\theta}})] - \alpha \mathbb{E}_{\mathcal{T}_m}\left[\|\nabla_{\boldsymbol{\theta}} \mathcal{L}_m(f_{\boldsymbol{\theta}})\|^2\right]$. The first term on the RHS is the traditional multi-task loss evaluated at $\boldsymbol{\theta}$ for all tasks. The second term corresponds to the negative gradient norm; minimizing it means choosing a $\boldsymbol{\theta}$ with the maximum gradient norm. Intuitively, when $\boldsymbol{\theta}$ is not a stationary point of a task, one should choose the steepest descent direction to reduce the loss maximally for a specific task, thus leading to *fast adaptation*.

The above understanding suggests us to propose the following regularized energy functional, $\widetilde{\mathcal{E}}_{\alpha}$, for meta-learning in the RKHS induced with the NTK for *fast function adaptation*:

$$\widetilde{\mathcal{E}}(\alpha, f_{\boldsymbol{\theta}}) = \mathbb{E}_{\mathcal{T}_m} \left[\mathcal{L}_m(f_{\boldsymbol{\theta}}) - \alpha \|\nabla_{f_{\boldsymbol{\theta}}} \mathcal{L}_m(f_{\boldsymbol{\theta}})\|_{\mathcal{H}}^2 \right], \quad (4)$$

where $\|\cdot\|_{\mathcal{H}}$ denotes the functional norm in $\mathcal{H}$, and α is a hyper-parameter. The above objective is inspired by the Taylor expansion of the MAML objective, but is defined in the RKHS induced by the NTK. Its connection with MAML and some functional-space properties will be discussed later.

Solving the Function Optimization Problem   To minimize equation 4, we first derive Theorem 2 to reduce the function optimization problem to a parameter optimization problem.

Theorem 2 *Let $f_{\boldsymbol{\theta}}$ be a neural network with parameter $\boldsymbol{\theta}$ and $\mathcal{H}$ be the RKHS induced by the NTK Θ of $f_{\boldsymbol{\theta}}$. Then, the following are equivalent*

$$\widetilde{\mathcal{E}}(\alpha, f_{\boldsymbol{\theta}}) = \mathcal{M}_1, \text{ and } \|\nabla_{f_{\boldsymbol{\theta}}} \mathcal{L}_m(f_{\boldsymbol{\theta}})\|_{\mathcal{H}}^2 = \|\nabla_{\boldsymbol{\theta}} \mathcal{L}_m(f_{\boldsymbol{\theta}})\|^2.$$

Theorem 2 is crucial to our approach as it indicates that solving problem equation 4 is no more difficult than the original parameter-based MAML, although it only considers one-step adaptation case. Next, we will show that multi-step adaptation in the parameter space can also be well-approximated by our objective equation 4 but with a scaled regularized parameter α. In the following, we consider the squared loss $\mathcal{L}$. The case with the cross-entropy loss is discussed in the Appendix. We assume that $f_{\boldsymbol{\theta}}$ is parameterized by either fully-connected or convolutional neural networks, and only consider the impact of number of hidden layers L in our theoretical results.

Theorem 3 *Let $f_{\boldsymbol{\theta}}$ be a fully-connected neural network with L hidden layers and ReLU activation function, $s_1, ..., s_{L+1}$ be the spectral norm of the weight matrices, $s = \max_h s_h$, and α be the learning rate of gradient descent. If $\alpha \leq O(qr)$ with $q = \min(1/(Ls^L), L^{-1/(L+1)})$ and $r = \min(s^{-L}, s)$, then the following holds*
$$|\mathcal{M}_k - \widetilde{\mathcal{E}}(k\alpha, f_{\boldsymbol{\theta}})| \leq O\left(\frac{1}{L}\right).$$

Theorem 4 *Let $f_{\boldsymbol{\theta}}$ be a convolutional neural network with $L - l$ convolutional layers and l fully-connected layers and with ReLU activation function, and d_x be the input dimension. Denote by W^h the parameter **vector** of the convolutional layer for $h \leq L - l$, and the weight **matrices** of the fully connected layers for $L - l + 1 \leq h \leq L + 1$. $\|\cdot\|_2$ means both the spectral norm of a matrix*

---

†For ease of our later notation, we write the gradient $\nabla_{\boldsymbol{\theta}_i} \mathcal{L}$ (thus the parameter as well) as a row vector.

and the Euclidean norm of a vector. Define $s_h = \sqrt{d_x}\|W^h\|_2$ if $h = 1, ..., L - l$, and $\|W^h\|_2$ if $L - l + 1 \le h \le L + 1$. Let $s = \max_h s_h$ and α be the learning rate of gradient descent. If $\alpha \le O(qr)$ with $q = \min(1/(Ls^L), L^{-1/(L+1)})$ and $r = \min(s^{-L}, s)$, the following holds

$$|\mathcal{M}_k - \widetilde{\mathcal{E}}(k\alpha, f_{\boldsymbol{\theta}})| \le O\Big(\frac{1}{L}\Big).$$

The above Theorems indicate that, for a meta-model with fully-connected and convolutional layers, the proposed Meta-RKHS-I can be an efficient approximation of MAML with a bounded error.

Comparisons with Reptile and MAML   Similar to Reptile and MAML, the testing stage of Meta-RKHS-I also requires gradient-based adaptation on meta-test tasks. By Theorem 1, we known that gradient flow of an energy functional can be approximated by gradient descent in a parameter space. Reptile with 1-step adaptation (Nichol et al., 2018) is equivalent to the approximation of the gradient flow of $\widetilde{\mathcal{E}}(\alpha, f_{\boldsymbol{\theta}})$ with $\alpha = 0$, which does not include the fast-adaptation regularization as in our method. For a fairer comparison on the efficiency, we will discuss the computational complexity later.

From the equivalent parameter-optimization form indicated in Theorem 2, we know that our energy functional $\widetilde{\mathcal{E}}(\alpha, f_{\boldsymbol{\theta}})$ is closely related to MAML. However, with this form, our method does not need the explicit adaptation steps in training (*i.e.*, the inner-loop of MAML), leading to a simpler optimization problem. We will show that our proposed method leads to better results.

3.4 META-RKHS-II: META-LEARNING IN RKHS WITH A CLOSED-FORM ADAPTATION

In this section, we present our second solution for meta-learning in RKHS by deriving a closed-form adaptation function, *i.e.*, we focus on a case where $\mathsf{Adapt}(f, \mathcal{D}_m^{tr})$ is analytically solvable using the theory of NTK. Specifically, we are given a loss function $\mathcal{L}$, tasks $\mathcal{T}_m$ with randomly split training set $\mathcal{D}_m^{tr} = \{\mathbf{x}_{m,i}^{tr}, \mathbf{y}_{m,i}^{tr}\}_{i=1}^n$, and testing set $\mathcal{D}_m^{test}$. Let $\boldsymbol{\theta}_m^t$ and $f_{m,\boldsymbol{\theta}}^t$ denote the parameters and the corresponding function at time t adapted by task $\mathcal{T}_m$ from the meta parameter $\boldsymbol{\theta}$ and meta function $f_{\boldsymbol{\theta}}$, respectively. From the NTK theory (Jacot et al., 2018; Arora et al., 2019; Lee et al., 2019), we can write the function/parameter evolution as:

$$\frac{\mathrm{d}\boldsymbol{\theta}_m^t}{\mathrm{d}t} = -\nabla_{\boldsymbol{\theta}_m^t}\mathcal{L}(f_{m,\boldsymbol{\theta}}^t, \mathcal{D}_m^{tr}), \quad \text{and} \quad \frac{\mathrm{d}f_{m,\boldsymbol{\theta}}^t}{\mathrm{d}t} = \frac{\mathrm{d}\boldsymbol{\theta}_m^t}{\mathrm{d}t}\frac{\partial f_{m,\boldsymbol{\theta}}^t}{\partial \boldsymbol{\theta}_m^t}^{\mathsf{T}} = \sum_{i=1}^n \frac{\partial \mathcal{L}(f_{m,\boldsymbol{\theta}}^t, \mathcal{D}_m^{tr})}{\partial f_{m,\boldsymbol{\theta}}^t(\mathbf{x}_{m,i}^{tr})}\boldsymbol{\Theta}(\mathbf{x}_{m,i}^{tr}, \cdot).$$

The above differential equation corresponds to the adaptation step, *i.e.*, how to adapt the meta parameter/function for task m. By the NTK theory, we can show that this admits closed-form solutions. In our meta-learning settings, this indicates that no explicit adaptation steps are necessary.

To see why this is the case, we first investigate the regression case, where the loss function $\mathcal{L}$ is the squared loss. Let $\mathbf{x} \in \mathcal{D}_m^{test}$ be a test data point. As shown in Arora et al. (2019); Lee et al. (2019), with a large enough neural network we can safely assume that NTK will not change too much during the training. In this case, we can have a closed-form solution for $f_{m,\boldsymbol{\theta}}^t$ as

$$f_{m,\boldsymbol{\theta}}^t(\mathbf{x}) = f_{\boldsymbol{\theta}}(\mathbf{x}) + H(\mathbf{x}, \mathbf{X}_m^{tr})H^{-1}(\mathbf{X}_m^{tr}, \mathbf{X}_m^{tr})\left(e^{-tH(\mathbf{X}_m^{tr}, \mathbf{X}_m^{tr})} - \mathbf{I}\right)\left(f_{\boldsymbol{\theta}}(\mathbf{X}_m^{tr}) - Y^{tr}\right), \quad (5)$$

where e is the matrix exponential map, which can be approximated by $Pad\acute{e}$ approximation (M.Arioli et al., 1996). $H(\mathbf{X}_m^{tr}, \mathbf{X}_m^{tr})$ is an $n \times n$ kernel matrix with its (i, j) element being $\boldsymbol{\Theta}(\mathbf{x}_{m,i}, \mathbf{x}_{m,j})$, $H(\mathbf{x}, \mathbf{X}_m^{tr})$ is a $1 \times n$ vector with its i-th element being $\boldsymbol{\Theta}(\mathbf{x}, \mathbf{x}_{m,i})$, $f_{\boldsymbol{\theta}}(\mathbf{X}_m^{tr}) \in R^n$ is the predictions of all training data at the initialization, and $Y^{tr} \in R^n$ is the target value of the training data. Specifically, at time $t = \infty$, we have

$$f_{m,\boldsymbol{\theta}}^\infty(\mathbf{x}) = f_{\boldsymbol{\theta}}(\mathbf{x}) + H(x, \mathbf{X}_m^{tr})H^{-1}(\mathbf{X}_m^{tr}, \mathbf{X}_m^{tr})\left(Y^{tr} - f_{\boldsymbol{\theta}}(\mathbf{X}_m^{tr})\right). \quad (6)$$

The above results allow us to directly define an energy functional by substituting $\mathsf{Adapt}(f, \mathcal{D}_m^{tr})$ in equation 1 with its closed-form solution $f_{m,\boldsymbol{\theta}}^t$. In other words, our new energy functional is

$$\overline{\mathcal{E}}(t, f_{\boldsymbol{\theta}}) = \mathbb{E}_{\mathcal{T}_m}\left[\mathcal{L}_m(f_{m,\boldsymbol{\theta}}^t)\right], \quad (7)$$

where $f_{m,\boldsymbol{\theta}}^t$ is defined in equation 5, and $\mathcal{L}_m(f_{m,\boldsymbol{\theta}}^t)$ is the expectation of $\mathcal{L}\left(f_{m,\boldsymbol{\theta}}^t, \mathcal{D}_m^{test}\right)$. For classification problems, we follow the same strategy as in Arora et al. (2019) to extend regression to classification. Mores details can be found in the Appendix, including the algorithm in Appendix A.

Table 1: Running time comparison per iteration with $C_1 = d_x p + L p^2$ and $C_2 = d_x p + L d_x p^2$.

	FOMAML	Reptile	Meta-RKHS-I	Meta-RKHS-II
Fully-connected	$O(n(k+1)C_1)$	$O(nkC_1)$	$O(nC_1)$	$O(nC_1 + n^3)$
Convolutional	$O(n(k+1)C_2)$	$O(nkC_2)$	$O(nC_2)$	$O(nC_2 + n^3)$

On Potential Robustness of Meta-RKHS-II   Our extensive empirical studies show that Meta-RKHS-II is a more robust model than related baselines. We provide an intuitive explanation on the potential robustness of Meta-RKHS-II, as we find current theories of both robustness machine learning and NTK are insufficient for a formal explanation. Our explanation is based on some properties of both the meta-learning framework and NTK: 1) Strong initialization (meta model): For NTK to generalize well, we argue that it is necessary to start the model with a good initialization. This is automatically achieved in our meta-learning setting, where the meta model serves as the initialization for NTK predictions. Actually, this has been supported by recent research (Fort et al., 2020), which shows that there is a chaotic stage in the NTK prediction with finite neural networks, and the NTK regime can be reachable with a good initialization. 2) Low complex classification boundary: It is known that NTK is a linear model in the NTK regime. Intuitively, generating adversarial samples with a lower complex model should be relatively harder because there is less data in the vicinity of the decision boundary compared to a more complex model, making the probability of the model being attacked smaller. Thus we argue that our model can be more robust than standard meta learning models. 3) Our NTK-based model is robust enough to adapt with different time steps. And these finite time steps can be more robust to adversarial attacks than that of the infinite-time limit partly due to the complexity of back-propagating gradients. We note each of the individual factors might not be enough to ensure robustness. Instead, we argue it is the combination effect of these factors that lead to robustness of our model. Formal analysis is out of the scope of this paper and left for future work.

Connection with Meta-RKHS-I   The proposed two methods choose different strategies to avoid explicit adaptation in meta-learning, which seem to be two very different algorithms. We prove below theorem, which indicates that the difference of the underlying gradient flows of the two algorithms indeed increases w.r.t. both T and the depth L of a DNN (we only consider impacts of T and L).

Theorem 5 *Let $f_{\boldsymbol{\theta}}$ be a neural network with L hidden layers, with each layer being either fully-connected or convolutional. Assume that $\|\mathcal{L}\|_\infty < \infty$. Then, $error(T) = |\widetilde{\mathcal{E}}(T, f_{\boldsymbol{\theta}}) - \overline{\mathcal{E}}(T, f_{\boldsymbol{\theta}})|$ is a non-decreasing function of T. Furthermore, for arbitrary $T > 0$ we have $error(T) \leq O(T^{2L+3})$.*

Actually, Meta-RKHS-II implicitly contains a term of functional gradient norm because $\overline{\mathcal{E}}(T, f_{\boldsymbol{\theta}}) = \mathbb{E}_{\mathcal{T}_m}\left[\mathcal{L}_m(f_{\boldsymbol{\theta}}) - \int_0^T \left\|\nabla_{\boldsymbol{\theta}^t}\mathcal{L}_m(f_{m,\boldsymbol{\theta}}^t)\right\|^2 dt\right]$. The difference compared to Meta-RKHS-I mainly comes from the fact that Meta-RKHS-I can be regarded as an approximation of time-discrete adaptation, while Meta-RKHS-II is based on time-continuous adaptation. In our experiments, we observe that Meta-RKHS-I is as fast as FOMAML, which means that it is more computationally efficient than the standard MAML. Meanwhile Meta-RKHS-II is the more robust model in tasks of adversarial attack and out-of-distribution adaptation.

Connection with iMAML   Our proposed method is similar to the iMAML algorithm (Finn & Levine, 2019) in the sense that both methods try to solve meta-learning without executing the optimization path. Different from iMAML, which still relies on an iterative solver, our method only needs to solve a simpler optimization problem due to the closed-form adaptation.

3.5 TIME COMPLEXITY ANALYSIS

We compare the time complexity of our proposed methods with other first-order meta-learning methods. Without loss of generality, we analyze the complexity in the case of a L-layer MLP or L-layer convolutional neural networks. Recall that d_x is the input dimension. Assume each layer has width (filter number) $O(p)$. Let n be the data batch size, k the adaptation steps of inner-loop optimization. We summarize the time complexity in Table 1, where we simply assume the complexity of multiplying matrices with sizes $a \times b$ and $b \times c$ to be $O(abc)$. Note in the meta-learning setting, n is typically small, indicating the efficiency of our proposed methods.

(a) Random Initialized   (b) Meta-RKHS-I   (c) Meta-RKHS-II

Figure 1: Performance of random initialized network and our methods. The models before/after adaptation are shown in dotted/dashed lines, samples used for adaptation are also shown in the figure.

4 EXPERIMENTS

We conduct a set of experiments to evaluate the effectiveness of our proposed methods, including a sine wave regression toy experiment, few-shot classification, robustness to adversarial attacks, out-of-distribution generalization and ablation study. Due to space limit, more results are provided in the Appendix. We compare our models with related baselines including MAML (Finn et al., 2017), the first order MAML (FOMAML) (Finn et al., 2017), Reptile (Nichol et al., 2018) and iMAML (Rajeswaran et al., 2019). Results are reported as mean and variance over three independent runs.

4.1 REGRESSION

Following Finn et al. (2017); Nichol et al. (2018), we first test our proposed methods on the 1-dimensional sine wave regression problem. This problem is instructive, where a model is trained on many different sine waves with different amplitudes and phases, and tested by adapting the trained model to new sine waves with only a few data points using a fixed number of gradient-descent steps. Following Finn et al. (2017); Nichol et al. (2018), we use a fully-connected neural network with 2 hidden layers and the ReLU activation function. The results are shown in Figure 1.

4.2 FEW-SHOT IMAGE CLASSIFICATION

For this experiment, we choose two popular datasets adopted for meta-learning: Mini-ImageNet and FC-100 (Oreshkin et al., 2018). The cross-entropy loss is adopted for Meta-RKHS-I; while the squared loss is used for Meta-RKHS-II following Arora et al. (2019); Novak et al. (2019). Similar to Finn et al. (2017), the model architecture is set to be a four-layer convolutional neural network with ReLU activation. The filter number is set to be 32. The Adam optimizer (Kingma & Ba, 2015) is used to minimize the energy functional. Meta batch size is set to be 16 and learning rates are set to be 0.01 for Meta-RKHS-II.

The results are shown in Table 2. Note the results of Reptile is different from those in Nichol et al. (2018), because we re-evaluate it under the same setting as Finn et al. (2017), i.e., 10 steps of adaptation is applied during testing. Our results of iMAML is based on the implementation of Spigler (2019). It is observed that our proposed methods

Table 2: Few-shot classification results on Mini-ImageNet and FC-100.

	MINI-IMAGENET		FC-100	
ALGORITHM	5 WAY 1 SHOT	5 WAY 5 SHOTS	5 WAY 1 SHOT	5 WAY 5 SHOTS
MAML	$48.70 \pm 1.84\%$	$63.11 \pm 0.93\%$	$38.00 \pm 1.95\%$	$49.34 \pm 0.97\%$
FOMAML	$48.07 \pm 1.75\%$	$63.15 \pm 0.91\%$	$37.73 \pm 1.93\%$	$49.05 \pm 0.99\%$
IMAML	$49.30 \pm 1.88\%$	$64.89 \pm 0.95\%$	$38.38 \pm 1.70\%$	$49.41 \pm 0.80\%$
REPTILE	$49.70 \pm 1.83\%$	$65.91 \pm 0.84\%$	$38.40 \pm 1.94\%$	$50.50 \pm 0.87\%$
META-RKHS-I	$\mathbf{51.10 \pm 1.82}\%$	$\mathbf{66.19 \pm 0.80}\%$	$38.90 \pm 1.90\%$	$\mathbf{51.47 \pm 0.86}\%$
META-RKHS-II	$50.53 \pm 2.09\%$	$65.40 \pm 0.91\%$	$\mathbf{41.20 \pm 2.17}\%$	51.36 ± 0.96

achieve better accuracy than different baselines. Interestingly, our Meta-RKHS-I performs better than FOMAML (this is also the case in other experiments), although they share a similar objective. We conjecture the reason is because our Meta-RKHS-I restricts the function to be in an RKHS, making the functional space smaller thus easier to optimize compared to the unrestricted version of FOMAML. In terms of our two algorithms, there is not always a winner on all the tasks. We note that Meta-RKHS-I is more efficient in training. However, we show below that Meta-RKHS-II is better in terms of robustness to adversarial attacks and out-of-distribution generalization.

4.3 ROBUSTNESS TO ADVERSARIAL ATTACKS

We now compare the adversarial robustness of our methods with other popular baselines. We adopt both white-box and black-box attacks in this experiment. For the white-box attacks, we adopt strong attacks including the PGD Attack (Madry et al., 2017), BPDA attack (Athalye et al., 2018) and

Figure 2: Black-box attack on Mini-ImageNet and FC-100. Mini-ImageNet 5-way 1-shot (left), FC-100 5-way 1-shot (middle) and Mini-ImageNet 5-way 5-shot (right).

Figure 3: BPDA attack on Mini-ImageNet 5-way 5-shot (left) and FC-100 5-way 5-shot (right).

Figure 4: SPSA attack on Mini-ImageNet 5-way 5-shot (left) and FC-100 5-way 5-shot (right).

SPSA attack (Uesato et al., 2018). For PGD attack, we use ℓ_∞ norm and compare the results on Mini-imagenet and FC-100. We compare the robust accuracy with different magnitude with 20-step attack with a step size of $2/255$. For BPDA attack, we apply median smoothing, JPEGFilter and BitSqueezing as input transformation adapted from (Guo et al., 2018) as defense strategies. For SPSA attack, we follow (Uesato et al., 2018) and set the Adam learning rate 0.01, perturbation size $\delta = 0.01$. For Black-box attack, we adopt the strong query efficient attack method (Guo et al., 2019). Follow the setting of Guo et al. (2019), we use a fixed step size of 0.2.

We consider both finite-time and infinite-time adaptation in this experiment. For finite-time adaptation, the Padé approximation with $P = Q = 1$ and $P = Q = 2$ to approximate the matrix exponential are considered (Butcher & Chipman, 1992). We use Meta-RKHS-II_t100_PQ1 and Meta-RKHS-II_t100_PQ2 to denote methods using finite time $t = 100$, $P = Q = 1$ or $P = Q = 2$, respectively. We observe other finite time t makes similar predictions, thus we only consider $t = 100$. The results from the black-box attack in Figure 2 indicate the robustness of our Meta-RKHS-II. In fact, the gaps are significantly large, making it the only useful robust model in the adversarial-attack setting. Our Meta-RKHS-I is not as robust as Meta-RKHS-II, but still slightly outperforms other baselines. Regarding the white-box attack, results in Figure 3, 4 and 5 again show that our proposed Meta-RKHS-II is significantly more robust than baselines under the three strong attacks. It is also interesting to see that our Meta-RKHS-I performs slightly better than Meta-RKHS-II in some rare cases, e.g., in the Mini-ImageNet 5-way 1-shot case when the attack magnitude is not too small. More results are presented in the Appendix.

Figure 5: ℓ_∞ norm PGD attack on Mini-ImageNet and FC-100. Mini-ImageNet 5-way 5-shot (left), Mini-ImageNet 5-way 1-shot (middle) and FC-100 5-way 5-shot (right).

Table 4: Meta-RKHS-II with different time t.

	TIME t	$t = 0.1$	$t = 1$	$t = 10$	$t = 100$	$t = \infty$
MINI-IMAGENET	5 WAY 1 SHOT	$49.67 \pm 2.23\%$	$48.27 \pm 2.23\%$	$\mathbf{50.53 \pm 2.09}\%$	$49.13 \pm 2.19\%$	$48.70 \pm 2.28\%$
	5 WAY 5 SHOTS	$64.51 \pm 0.93\%$	$64.28 \pm 0.98\%$	$\mathbf{65.40 \pm 0.91}\%$	$64.24 \pm 1.06\%$	$64.95 \pm 0.96\%$
FC-100	5 WAY 1 SHOT	$36.50 \pm 2.10\%$	$38.80 \pm 2.32\%$	$\mathbf{41.20 \pm 2.17}\%$	$38.80 \pm 2.21\%$	$37.60 \pm 2.13\%$
	5 WAY 5 SHOTS	$48.35 \pm 1.02\%$	$49.79 \pm 1.04\%$	$\mathbf{51.36 \pm 0.96}\%$	$48.59 \pm 1.09\%$	$49.48 \pm 0.98\%$

4.4 OUT-OF-DISTRIBUTION GENERALIZATION

We adopt similar strategy in (Lee et al., 2020) to test a model's ability of generalizing to out-of-distribution datasets. In this setting, the state of arts are achieved by Bayesian TAML (Lee et al., 2020). Different from their setting that considers any-shot learning with maximum number of examples for each class being as large as 50, we only focus on the standard 1 or 5 shot learning. We thus modify their code to accommodate our standard setting. The CUB (Wah et al., 2011) and VGG Flower Nilsback & Zisserman (2008) are fine-grained datasets used in this experiment, where all images are resized to 84×84. We follow Lee et al. (2020) to split these datasets into meta training/validation/testing sets. We first train all the methods on Mini-ImageNet or FC-100 datasets, then conduct meta-testing on CUB and VGG Flower datasets. The results are shown in Table 3. Again, our methods achieve the best results, outperforming the state-of-art method with our Meta-RKHS-II, indicating the robustness of our proposed methods. More results are presented in the Appendix.

4.5 ABLATION STUDY

We conduct several ablation studies, including: comparing Reptile with Meta-RKHS-I under different adaptation steps (results shown in the Appendix), testing the impact of choosing different time t in Meta-RKHS-II (results shown in Table 4) and the impact of network architecture with dif-

Table 3: Meta testing on different out-of-distribution datasets with model trained on Mini-ImageNet.

	5 WAY 1 SHOT		5 WAY 5 SHOT	
ALGORITHM	CUB	VGG FLOWER	CUB	VGG FLOWER
MAML	$34.23 \pm 1.52\%$	$52.98 \pm 1.76\%$	$52.36 \pm 0.94\%$	$67.52 \pm 1.30\%$
FOMAML	$35.32 \pm 1.69\%$	$53.86 \pm 1.64\%$	$52.02 \pm 0.71\%$	$68.83 \pm 1.16\%$
REPTILE	$35.61 \pm 1.38\%$	$53.57 \pm 1.58\%$	$51.93 \pm 0.89\%$	$71.62 \pm 1.25\%$
IMAML	$40.55 \pm 0.61\%$	$54.97 \pm 0.80\%$	$46.31 \pm 2.03\%$	$60.67 \pm 1.91\%$
BAYESIAN TAML(SOTA)	$41.57 \pm 0.60\%$	$58.56 \pm 0.66\%$	$61.78 \pm 0.56\%$	$77.95 \pm 0.46\%$
META-RKHS-I	$36.73 \pm 1.26\%$	$54.79 \pm 1.61\%$	$54.19 \pm 0.73\%$	$72.76 \pm 1.08\%$
META-RKHS-II	$\mathbf{45.36 \pm 0.87}\%$	$\mathbf{60.80 \pm 1.02}\%$	$\mathbf{65.21 \pm 0.64}\%$	$\mathbf{78.25 \pm 0.49}\%$

ferent number of CNN feature channels (results shown in the Appendix). It is interesting to see that a finite-time (around $t = 10$) achieves the best accuracy, although the infinite-time case guarantees a stationary point. This indicates that a stationary point achieved by limited training data in the adaptation step is not always the best choice, because the limited training data might easily overfit the model, thus achieving worse test results.

5 CONCLUSION

We develop meta-learning in RKHS, and propose two practical algorithms allowing efficient adaptation in the function space by avoiding some complicated adaptations as in traditional methods. We show connections between our proposed methods and existing ones. Extensive experiments suggest that our methods are more effective, achieve better generalization and are more robust against adversarial attacks and out-of-distribution generalization, compared to popular strong baselines.

REFERENCES

Zeyuan Allen-Zhu, Yuanzhi Li, and Zhao Song. A convergence theory for deep learning via over-parameterization. volume 97 of *Proceedings of Machine Learning Research*, pp. 242–252, Long Beach, California, USA, 09–15 Jun 2019. PMLR. URL http://proceedings.mlr.press/v97/allen-zhu19a.html.

Marcin Andrychowicz, Misha Denil, Sergio Gómez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando de Freitas. Learning to learn by gradient descent by gradient descent. In D. D. Lee, M. Sugiyama, U. V. Luxburg, I. Guyon, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, pp. 3981–3989. 2016.

Sanjeev Arora, Simon S. Du, Wei Hu, Zhiyuan Li, Ruslan Salakhutdinov, and Ruosong Wang. On exact computation with an infinitely wide neural net. In *Advances in Neural Information Processing Systems*, 2019.

Anish Athalye, Nicholas Carlini, and David Wagner. Obfuscated gradients give a false sense of security: Circumventing defenses to adversarial examples. In *International Conference on Machine Learning*, 2018.

J. C. Butcher and F. H. Chipman. Generalized padé approximations to the exponential function. *BIT Numerical Mathematics*, 32:118–130, 1992.

Giulia Denevi, Carlo Ciliberto, Riccardo Grazzi, and Massimiliano Pontil. Learning-to-learn stochastic gradient descent with biased regularization. In *https://arxiv.org/abs/1903.10399*, 2019.

Alireza Fallah, Aryan Mokhtari, and Asuman Ozdaglar. On the convergence theory of gradient-based model-agnostic meta-learning algorithms. In *International Conference on Artificial Intelligence and Statistics*, 2020.

Chelsea Finn and Sergey Levine. Meta-learning: from few-shot learning to rapid reinforcement learning. In *ICML 2019 Meta-Learning Tutorial*, 2019.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. In *International Conference on Machine Learning*, 2017.

Chelsea Finn, Kelvin Xu, and Sergey Levine. Probabilistic model-agnostic meta-learning. In *Advances in Neural Information Processing Systems*. 2018.

Stanislav Fort, Gintare Karolina Dziugaite, Mansheej Paul, Sepideh Kharaghani, Daniel M. Roy, and Surya Ganguli. Deep learning versus kernel learning: an empirical study of loss landscape geometry and the time evolution of the neural tangent kernel. In *Advances in Neural Information Processing Systems*, 2020.

Alex Graves, Greg Wayne, and Ivo Danihelka. Neural turing machines. In *https://arxiv.org/abs/1410.5401*, 2014.

Chuan Guo, Mayank Rana, Moustapha Cisse, and Laurens van der Maaten. Countering adversarial images using input transformations. In *International Conference on Learning Representations*, 2018.

Chuan Guo, Jacob R. Gardner, Yurong You, Andrew Gordon Wilson, and Kilian Q. Weinberger. Simple black-box adversarial attacks. In *International Conference on Machine Learning*, 2019.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: Convergence and generalization in neural networks. In *Advances in neural information processing systems*, pp. 8571–8580, 2018.

Mikhail Khodak, Maria-Florina Balcan, and Ameet Talwalkar. Provable guarantees for gradient-based meta-learning. In *International Conference on Machine Learning*, 2019a.

Mikhail Khodak, Maria-Florina Balcan, and Ameet Talwalkar. Adaptive gradient-based meta-learning methods. In *Advances in Neural Information Processing Systems*, 2019b.

Diederik P. Kingma and Jimmy Ba. Adam: A method for stochastic optimization. In *International Conference on Learning Representations*, 2015.

Hae Beom Lee, Hayeon Lee, Donghyun Na, Saehoon Kim, Minseop Park, Eunho Yang, and Sung Ju Hwang. Learning to balance: Bayesian meta-learning for imbalanced and out-of-distribution tasks. In *International Conference on Learning Representations*, 2020.

Jaehoon Lee, Lechao Xiao, Samuel Schoenholz, Yasaman Bahri, Roman Novak, Jascha Sohl-Dickstein, and Jeffrey Pennington. Wide neural networks of any depth evolve as linear models under gradient descent. In *Advances in Neural Information Processing Systems 32*, pp. 8572–8583. Curran Associates, Inc., 2019.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. *ArXiv*, abs/1706.06083, 2017.

M.Arioli, B.Codenotti, and C.Fassino. The $Pad\acute{e}$ method for computing the matrix exponential. *Linear Algebra and its Applications*, June 1996.

Nikhil Mishra, Mostafa Rohaninejad, Xi Chen, and Pieter Abbeel. A simple neural attentive meta-learner. In *International Conference on Learning Representations*, 2018.

Alex Nichol, Joshua Achiam, and John Schulman. On first-order meta-learning algorithms. In *https://arxiv.org/abs/1803.02999*, 2018.

Maria-Elena Nilsback and Andrew Zisserman. Automated flower classification over a large number of classes. In *Sixth Indian Conference on Computer Vision, Graphics and Image Processing*, 2008.

Roman Novak, Lechao Xiao, Yasaman Bahri, Jaehoon Lee, Greg Yang, Jiri Hron, Daniel A. Abolafia, Jeffrey Pennington, and Jascha Sohl-dickstein. Bayesian deep convolutional networks with many channels are gaussian processes. In *International Conference on Learning Representations*, 2019.

Boris N. Oreshkin, Pau Rodriguez, and Alexandre Lacoste. Tadam: Task dependent adaptive metric for improved few-shot learning. In *Advances in Neural Information Processing Systems*, 2018.

Aravind Rajeswaran, Chelsea Finn, Sham Kakade, and Sergey Levine. Meta-learning with implicit gradients. In *Advances in Neural Information Processing Systems*. 2019.

Sachin Ravi and Alex Beatson. Amortized bayesian meta-learning. In *International Conference on Learning Representations*, 2019.

Filippo Santambrogio. Euclidean, Metric, and Wasserstein gradient flows: an overview, 2016.

Jurgen Schmidhuber. Evolutionary principles in self-referential learning. Diploma thesis, Technische Universitat Munchen, Germany, 14 May 1987.

Jake Snell, Kevin Swersky, and Richard S. Zemel. Prototypical networks for few-shot learning. In *Advances in Neural Information Processing Systems*, 2017.

Giacomo Spigler. Meta-learnt priors slow down catastrophic forgetting in neural networks. *arXiv e-prints*, art. arXiv:1909.04170, Sep 2019.

Eleni Triantafillou, Tyler Zhu, Vincent Dumoulin, Pascal Lamblin, Utku Evci, Kelvin Xu, Ross Goroshin, Carles Gelada, Kevin Swersky, Pierre-Antoine Manzagol, and Hugo Larochelle. Meta-dataset: A dataset of datasets for learning to learn from few examples. In *International Conference on Learning Representations*, 2020.

Nilesh Tripuraneni, Chi Jin, and Michael I. Jordan. Provable meta-learning of linear representations. In *https://arxiv.org/abs/2002.11684*, 2020.

Jonathan Uesato, Brendan O'Donoghue, Aaron van den Oord, and Pushmeet Kohli. Adversarial risk and the dangers of evaluating against weak attacks, 2018.

C Villani. *Optimal transport – Old and new*, volume 338, pp. xxii+973. 01 2008. doi: 10.1007/978-3-540-71050-9.

Oriol Vinyals, Charles Blundell, Timothy Lillicrap, Koray Kavukcuoglu, and Daan Wierstra. Matching networks for one shot learning. In *https://arxiv.org/pdf/1606.04080.pdf*, 2016.

Catherine Wah, Steve Branson, Peter Welinder, Pietro Perona, and Serge Belongie. The caltech-ucsd birds-200-2011 dataset. In *Technical Report CNS-TR-2011-001, California Institute of Technology*, 2011.

Huaxiu Yao, Ying Wei, Junzhou Huang, and Zhenhui Li. Hierarchically structured meta-learning. In *International Conference on Machine Learning*, 2019.

Jaesik Yoon, Taesup Kim, Ousmane Dia, Sungwoong Kim, Yoshua Bengio, and Sungjin Ahn. Bayesian model-agnostic meta-learning. In *Advances in Neural Information Processing Systems*. 2018.