DEEP ENSEMBLE KERNEL LEARNING

ABSTRACT

Gaussian processes (GPs) are nonparametric Bayesian models that are both flexible and robust to overfitting. One of the main challenges of GP methods is selecting the kernel. In the deep kernel learning (DKL) paradigm, a deep neural network or "feature network" is used to map inputs into a latent feature space, where a GP with a "base kernel" acts; the resulting model is then trained in an end-to-end fashion. In this work, we introduce the "deep ensemble kernel learning" (DEKL) model– a simple and efficient special case of DKL with two defining properties: First, we use a linear base kernel, which allows for the exact optimization of the base kernel hyperparameters and allows us to derive a scalable inference method that doesn't require approximation by inducing points. Second, we represent the feature network as a linear combination of an ensemble of basis functions having common network architecture, allowing for easy model parallelism. We show that DEKL is able to approximate any kernel if the number of learners in the ensemble may be arbitrarily large. We compare the DEKL model to DKL and deep ensemble (DE) baselines on both regression and classification tasks, finding that DEKL often outperforms both baselines in terms of predictive performance.

1 INTRODUCTION

In recent years, there has been a growing interest in Bayesian deep learning (DL), where the point predictions of traditional deep neural network (DNN) models are replaced with full predictive distributions using Bayes' Rule (Neal, 2012; Wilson, 2020). The advantages of Bayesian DL over traditional DL are numerous and include greater robustness to overfitting and better calibrated uncertainty quantification (Guo et al., 2017; Kendall & Gal, 2017). Furthermore, the success of traditional DL already rests on a number of probabilistic elements such as stochastic gradient descent (SGD), dropout, and weight initialization– all of which have been given Bayesian interpretations (Smith & Le, 2018; Gal & Ghahramani, 2016; Kingma et al., 2015; Schoenholz et al., 2016; Jacot et al., 2018).

Gaussian processes (GPs) are nonparametric Bayesian models with appealing properties, as they admit exact inference for regression and allow for a natural functional perspective suitable for predictive modeling (Rasmussen & Williams, 2005). While at first glance GPs appear unrelated to DL models, a number of interesting connections between GPs and DNNs exist in the literature, suggesting that GPs can constitute a valid approach to Bayesian DL (Neal, 1996; Lee et al., 2018; de Matthews et al., 2018; Jacot et al., 2018; Damianou & Lawrence, 2013; Salimbeni & Deisenroth, 2017; Agrawal et al., 2020). A GP prior is typically characterized by its covariance function or "kernel", which determines the class of functions that the GP can model, as well as its generalization properties outside training data. Kernel selection is the primary problem in GP modeling, and unfortunately traditional kernels such as the radial basis function (RBF) kernel are not sufficiently expressive for complex problems where more flexible models such as DNNs generally perform well. This is the key motivation for kernel learning, which refers to the selection of an optimal kernel out of a family of kernels in a data-driven way.

A number of approaches to kernel learning exist in the literature, including some that parameterize kernels using DNNs (Zhou et al., 2019; Li et al., 2019; Bullins et al., 2018; Sinha & Duchi, 2016). However, these approaches are not specific to GPs and do not take advantage of a robust Bayesian framework. In contrast, the deep kernel learning (DKL) paradigm does exactly this; In DKL, a DNN is used as a feature extractor that maps data inputs into a latent feature space, where GP inference with some "base kernel" is then performed (Wilson et al., 2016b;a; Jean et al., 2016; Al-Shedivat et al., 2017; Bradshaw et al., 2017; Izmailov et al., 2018; Xuan et al., 2018). The

(a) Deep Ensembles (DE) (b) Deep Kernel Learning (DKL) (c) Deep Ensemble Kernel Learning (DEKL)

Figure 1: Training various neural architectures considered in this work. Deep ensembles (a) use identical prediction networks with independent initialization and training. Deep kernel learning (b) uses a neural feature extraction network with an expressive kernel such as an RBF. Our model, deep ensemble kernel learning (c) uses an ensemble of feature networks trained jointly through a linear kernel that enables exact inference via minimization of variational free energy for regression.

resulting model is then trained end-to-end using standard gradient-based optimization, usually in a variational framework. We note that the DKL model is just a GP with a highly flexible kernel parameterized by a DNN. By optimizing all hyperparameters (including the DNN weights) with type II maximum likelihood estimation, the DKL model is able to learn an optimal kernel in a manner directly informed by the data, while also taking advantage of the robustness granted by the Bayesian framework. A special case of DKL that is worthy of note was considered in Dasgupta et al. (2018), who use a linear base kernel and impose a soft orthogonality constraint to learn the eigenfunctions of a kernel. Although similar in spirit to the approach in this paper, their method does not make use of an efficient variational method, nor is distributed training made possible since all of the basis functions are derived from the same feature network.

In this work, we introduce the "deep ensemble kernel learning" (DEKL) model– a simpler and more efficient special case of DKL with two specifications– the base kernel is linear, and the feature network is partitioned into an "ensemble" of "learners" with common network architecture. In contrast to nonlinear kernels, the linear kernel allows us to derive an efficient training and inference method for DEKL that circumvents the inducing points approximation commonly used in traditional DKL. The hyperparameters of the linear kernel can also be optimized in closed form, allowing us to simplify the loss function considerably. Convenience aside, we show that DEKL remains highly expressive, proving that it is universal in the sense that it can approximate any continuous kernel so long as its feature network is arbitrarily wide. In other words, we may keep the base kernel simple if we are willing to let the feature network be more complex. The second specification of DEKL lets us handle the complexity of the feature network; because the feature network is partitioned, it admits easy model parallelism, where the learners in the ensemble are distributed. Moreover, our universality result only requires the number of learners to be arbitrarily large; the learners themselves need not grow (meaning fixed-capacity learners are sufficient), avoiding additional model parallelism.

From a different perspective, DEKL may be regarded as an extension of traditional ensembling methods for DNNs where the learners are usually trained independently (Lakshminarayanan et al., 2017). In DEKL, the learners are trained jointly via a shared linear GP layer. We surmise this may help to promote diversity among the learners, in contrast to other non-Bayesian joint ensemble training methods such as that of Webb et al. (2019). We therefore expect DEKL to be more efficient than DKL and more robust than ensembles, by drawing on the strengths of both (see Fig. 1 for a comparison of model architectures).

2 DEEP ENSEMBLE KERNEL LEARNING

A DKL model is a GP whose kernel encapsulates a DNN for feature extraction (Wilson et al., 2016b;a). A deep kernel is defined as

$$K_{\text{deep}}(x_1, x_2; \theta, \gamma) = K(\varphi(x_1; \theta), \varphi(x_2; \theta); \gamma),$$

where $\varphi(\cdot; \theta)$ is a DNN with weight parameters θ and $K(\cdot, \cdot; \gamma)$ is any chosen kernel—called the "base kernel"—with hyperparameters γ. Note that the kernel hyperparameters of K_{deep} include all hyperparameters γ of the base kernel K as well as the DNN weight parameters θ. Given the expressive power of DNNs, the deep kernel is also highly expressive and may be viewed as a method to automatically select a GP model.

Our proposed method, DEKL, is a special case of DKL. Whereas RBF and Matern kernels are typically used as base kernels in DKL, in DEKL we take the base kernel to be the linear kernel:

$$K_{\text{lin}}(x_1, x_2; V) = x_1^\top V x_2,$$

where V is a symmetric positive-semidefinite matrix. In order to enable parallel computation, in DEKL, we use a feature network $\varphi(\cdot; \theta)$ that is partitioned into an "ensemble" of subnetworks $\varphi_i(\cdot; \theta_i)$ called "learners", having identical network architectures; i.e., $\varphi(\cdot; \theta)$ is the concatenation of the outputs of the $\varphi_i(\cdot; \theta_i)$. DEKL offers a number of advantages over general DKL:

1. Unlike the hyperparameters of the RBF kernel, in DEKL, we can optimize the hyperparameters of the linear base kernel in closed form.

2. The linear base kernel allows us to think of a DEKL model not just as a GP but as a finite-dimensional Bayesian linear model (BLM), conditional on the feature networks; this lets us derive an efficient inference method that is much simpler than the inducing points method used in general DKL.

3. Finally, the partitioned architecture of the feature network makes it much more amenable to model parallelism.

A potential drawback to partitioning the feature network as we do in DEKL is that, compared to general DKL, the network is less expressive. However, the following universal approximation theorem for DKL implies that this effect can be compensated by adding parallel learners:

Theorem 1 (Universal kernel approximation theorem). *Let $\mathcal{X} \subset \mathbb{R}^D$ be some compact Euclidean domain, and let $\sigma : \mathbb{R} \to \mathbb{R}$ be a non-polynomial activation function (Pinkus, 1999). Then, given a continuous, symmetric, positive-definite kernel $\kappa : \mathcal{X} \times \mathcal{X} \mapsto \mathbb{R}$ and any $\epsilon > 0$, there exist a finite number H of affine functions $\beta_i : \mathcal{X} \xrightarrow{aff.} \mathbb{R}$ and a symmetric positive semi-definite matrix $V \in \mathbb{R}^{H \times H}$ such that for any $x_1, x_2 \in \mathcal{X}$,*

$$\left| \sum_{i,j=1}^{H} v_{ij} \sigma(\beta_i(x_1)) \sigma(\beta_j(x_2)) - \kappa(x_1, x_2) \right| < \epsilon. \tag{1}$$

The proof, found in Appendix A, contains a straightforward combination of Mercer's Theorem (Mercer, 1909) and the Universal Approximation Theorem, attributed to Cybenko, Hornik, Leshno, and Pinkus (Cybenko, 1989; Hornik et al., 1989; Leshno et al., 1993; Pinkus, 1999). Although for clarity only scalar kernels are considered in this work, multivariate versions of Thm. 1 are easily obtained with minor modifications to the proof. Note that the approximation in Thm. 1 requires a possibly large number H of affine functions β_i, but that in DEKL we replace the functions $x \to \sigma(\beta_i(x))$ with a distributed collection of strictly more flexible deep neural networks.

Theorem 1 defines a meaningful notion of universality that is distinct from and should not be confused with the existing notion of a "universal kernel". A kernel is called universal if it can be used to approximate under the sup-norm any continuous function as a kernel-weighted sum of values assigned at points in the domain (Micchelli et al., 2006). In contrast, Thm. 1 defines *universality of a class of kernels*, $\mathcal{K}$, to mean that $\mathcal{K}$ is a dense set in the space of all continuous kernels (including those that are universal kernels), under the sup-norm on a compact domain.

Drawing an analogy with deep ensembles (Lakshminarayanan et al., 2017), we refer to the H neural networks $\varphi(\cdot; \theta_i)$ for $i = 1, \ldots, H$ as "learners" and collectively as an "ensemble". The learners $\varphi(\cdot; \theta_i)$ differ from the simpler functions $x \to \sigma(\beta_i(x))$ in Thm. 1 in two key respects: First, the learners $\varphi(\cdot; \theta_i)$ may be significantly more flexible than the simple learners, which can help to reduce the number H of learners required to approximate a target kernel within a given error ϵ. In the proof of Thm. 1, we approximate each eigenfunction of the target kernel κ with a linear combination of the learners; if the learners are sufficiently expressive, then it may take only one learner per eigenfunction to approximate the target kernel. Second, each learner $\varphi(\cdot; \theta_i)$ may have multiple outputs M. In the case of the simple learners $x \to \sigma(\beta_i(x))$, a learner with M outputs is simply a concatenation of M single-output learners, suggesting that multi-output learners may help to further reduce the number H of required learners.

2.1 EXACT INFERENCE

Consider a dataset $\{(x_i, y_i) \in \mathbb{R}^D \times \mathbb{R}\}_{i=1}^N$. In DEKL, we model this data with likelihood $p(y \mid f)$ and GP prior $\mathcal{GP}(0, \mathcal{K}_{\mathrm{DE}}(\cdot, \cdot; \theta, V))$, where the kernel $\mathcal{K}_{\mathrm{DE}}(\cdot, \cdot; \theta, V) : \mathbb{R}^D \times \mathbb{R}^D \mapsto \mathbb{R}$ is defined as

$$\mathcal{K}_{\mathrm{DE}}(x_1, x_2; \theta, V) = \Phi(x_1; \theta)^\top V \Phi(x_2; \theta), \qquad (2)$$

where V is an $H \times H$ symmetric positive semidefinite matrix and $\Phi(x; \theta) = \{\varphi(x; \theta_i)\}_{i=1}^H$ is the concatenation of H DNN learners $\varphi(\cdot; \theta_i) : \mathbb{R}^D \mapsto \mathbb{R}$ with common network architecture. The DEKL model is thus a standard GP but with a special kernel, and thus one may proceed following standard practices for GP inference. However, in contrast to other popular GP kernels such as the RBF kernel, the kernel in Eq. 2 has rank at most H, and we can leverage this property to derive a more efficient GP inference method by regarding it as a Bayesian linear model (BLM) where the learners act as the BLM basis functions. More precisely, our GP prior is equivalent to taking the latent function $f : \mathbb{R}^D \mapsto \mathbb{R}$ to be a generative model of the form

$$f(x) = \Phi(x; \theta)^\top a, \quad a \sim \mathcal{N}(0, V).$$

Now formulated as a BLM, we may perform Bayesian inference by inferring the posterior on a; when the number of training points N is large, this approach is significantly more efficient than direct GP inference, which requires a Cholesky decomposition of complexity $O(N^3)$.

In the case of regression with a Gaussian likelihood, the posterior on a admits a closed form. Moreover, the evidence of the above model given the training data also admits a closed form, allowing us to obtain maximum evidence estimates of the DEKL hyperparameters V and θ as is standard practice in GP methods. However, the dependence of the evidence on θ is in general complex, so that the maximum evidence estimates must be approximated. Moreover, the evidence is not separable across the training data, so that optimization is not amenable to SGD with minibatching and is thus not scalable to large datasets. Finally, in the case of non-conjugate likelihoods such as in classification problems, exact inference on A is intractable as well. We therefore perform approximate inference and maximum evidence estimation in a variational framework, discussed in the next section. We reiterate that DEKL admits exact inference on small datasets and that maximum evidence estimation can be performed through non-stochastic gradient-based optimization methods; however, we consider the variational framework as it can handle a larger class of problems.

2.2 VARIATIONAL INFERENCE

In variational inference, we approximate the posterior distribution on the vector a with a variational distribution by solving an optimization problem. In the GP literature, it is standard to take the variational distribution to itself be a GP. In our DEKL model formulated as a BLM, this corresponds to a normal variational distribution $\mathcal{N}(\mu, \Sigma)$ on a, where $\mu \in \mathbb{R}^H$ and $\Sigma \in \mathbb{R}^{H \times H}$. We now minimize the KL divergence between the variational and posterior distributions on a, which is equivalent to minimizing the variational free energy loss function:

$$\mathcal{L}_{\mathrm{VFE}}(\mu, \Sigma, \theta, V) = \sum_{i=1}^N \mathrm{NELL}_i(\mu, \Sigma, \theta) + \mathrm{KL}(\mu, \Sigma, V) \qquad (3)$$

$$\mathrm{NELL}_i(\mu, \Sigma, \theta) = -\mathbb{E}_{a_i \sim \mathcal{N}(\mu, \Sigma)}\left[\log p(y_i \mid \Phi(x_i; \theta)^\top a_i)\right] \qquad (4)$$

$$\mathrm{KL}(\mu, \Sigma, V) = \mathrm{D}_{\mathrm{KL}}(\mathcal{N}(\mu, \Sigma) \mid \mathcal{N}(0, V))$$

$$= \frac{1}{2}\mu^\top V^{-1}\mu + \frac{1}{2}\mathrm{tr}(\Sigma V^{-1}) - \frac{1}{2}\log\det(\Sigma V^{-1}) - \frac{H}{2}. \qquad (5)$$

Observe that we optimize both the variational parameters μ and Σ as well as the kernel hyperparameters θ and V as is standard in GP inference. Note also that this loss function is separable over the training data and is thus amenable to optimization with SGD and minibatching; using a minibatch size B, we define the loss on one minibatch as the variational free energy over the batch normalized by the minibatch size:

$$\mathcal{L}_{\mathrm{batch}}(\mu, \Sigma, \theta, V) = \frac{1}{B}\sum_{i=1}^B \mathrm{NELL}_i(\mu, \Sigma, \theta) + \frac{1}{N}\mathrm{KL}(\mu, \Sigma, V).$$

In this paper, we focus on regression tasks with Gaussian likelihood $p(y \mid f) = \mathcal{N}(y; f, \tau^{-1})$ with precision τ. The corresponding NELL admits a closed form and is given by

$$\text{NELL}_i(\mu, \Sigma, \theta) = \frac{\tau}{2} \|\Phi(x_i; \theta)^\top \mu - y_i\|^2 + \frac{\tau}{2} \Phi(x_i; \theta)^\top \Sigma \Phi(x_i; \theta) - \frac{1}{2} \log \tau + \frac{1}{2} \log(2\pi). \quad (6)$$

Note that in practice, we parameterize Σ with its positive-definite lower-triangular Cholesky factor in order to guarantee the symmetric positive-definiteness of Σ.

For scalability to large training sets, DKL inference is usually performed using the inducing points approximation in a sparse variational framework (Titsias, 2009; Hensman et al., 2013). In the case of DEKL, due to using a linear base kernel, the inducing point approximation is not necessary, as seen above. Instead, our parameters μ and Σ take the place of the inducing parameters in the sparse variational GP framework, and we are able to maintain an exact model for the posterior GP.

2.3 OPTIMAL PRIOR COVARIANCE

The variational free energy depends on the prior covariance V only through the KL term, which has a tractable form. This allows us to optimize V in closed form; we find the optimal prior covariance to be

$$V_*(\mu, \Sigma) = \Sigma + \mu\mu^\top. \quad (7)$$

Next, we substitute this optimal prior covariance back into the KL term, thereby eliminating the prior covariance from the variational free energy altogether. After some simplification, the KL term takes the following form:

$$\text{KL}_O(\mu, \Sigma) = \text{KL}(\mu, \Sigma, V_*(\mu, \Sigma)) = \frac{1}{2} \log(1 + \mu^\top \Sigma^{-1} \mu). \quad (8)$$

(See Appendix B for derivations of Eqs. 7-8). During training, this term drives down the signal-to-noise ratio (SNR) $\mu\Sigma^{-1}\mu$, encouraging the model to learn a more robust fit to the data.

We contrast the form of Eq. 8 with the KL term obtained by fixing the prior covariance to the identity $V = I$:

$$\text{KL}_I(\mu, \Sigma) = \text{KL}(\mu, \Sigma, I) = \frac{1}{2} \|\mu\|^2 + \frac{1}{2} \text{tr}(\Sigma) - \frac{1}{2} \log \det(\Sigma) - \frac{H}{2}. \quad (9)$$

We note that while Eq. 9 includes a quadratic penalty on μ, Eq. 8 includes only a logarithmic penalty; optimizing the prior covariance therefore results in weaker regularization of μ. The same is true with respect to Σ; both Eqs. 8-9 include roughly logarithmic penalties on Σ^{-1} that encourage larger Σ, but Eq. 9 additionally includes a linear penalty on Σ, resulting in stronger regularization of Σ. We note that in regression, the NELL term already favors small Σ (see Eq. 6), so that the KL term is the only thing preventing Σ from degenerating. By weakening the regularization on Σ, we suspect the KL term with optimal prior covariance to be beneficial in practice.

3 EXPERIMENTS

In our experiments, we evaluate DEKL on various regression datasets, comparing it to two key baselines– DKL (with linear base kernel) and deep ensembles (DE) introduced in Lakshminarayanan et al. (2017). For both DKL and DEKL, we also compare using a KL regularizer with the optimal prior covariance, KL_O, to that with an identity prior covariance, KL_I.

3.1 SYNTHETIC DATA

For our first experiment, we consider a simple regression problem with one-dimensional inputs and outputs, as it allows for easy visualization of the posterior predictive distribution. For this purpose, we generate data via $y = x^3 + \epsilon$ where $\epsilon \sim \mathcal{N}(0, 3^2)$ as in Lakshminarayanan et al. (2017). We sample twenty (x, y) pairs with $x \sim \text{Unif}(-4, 4)$. As already stated, we compare the DEKL model to the DKL and DE baselines. For DE, we follow the implementation of Lakshminarayanan et al. (2017), except that we do not use adversarial samples, which the authors say is optional. For the DEKL and DE models, we use five learners, where each learner is a shallow MLP with rectified linear unit (ReLU) activation and 50 hidden neurons. For the DKL model, we use a shallow MLP

Figure 2: Synthetic cubic dataset. A deep ensemble of five learners is compared to a comparable DEKL architecture with five parallel feature networks and a DKL network of the same architecture and five times the width of an individual feature network. Predictive mean function (blue) with three units of standard deviation of each model trained on the cubic dataset (red), with ground truth (black).

feature network with ReLU activation and 250 hidden and five output neurons, so that all models have the same total hidden width. Note that the only difference between the DEKL and DKL models is that—compared to the DKL model—the DEKL model is missing some connections in its second layer. We set the prior covariance V of DKL and DEKL to $V = I$, using the KL term in Eq. 9.

We train all models on the training set using the Adam optimizer with learning rate 10^{-3} and full batches for 1000 epochs. For the DEKL and DKL models, we set the noise precision to its true value $\tau = \frac{1}{9}$.

The predictive distributions of all models on their input domain are visualized in Fig. 2. DKL and DEKL exhibit better uncertainty quantification than DE, as they both have lower variance than DE inside the training domain (interpolation) and higher variance than DE outside the training domain (extrapolation). Moreover, the predictive distribution of DEKL is very similar to that of DKL, suggesting that partitioning the feature network for efficiency does not hurt predictive performance.

We also evaluate DEKL and DKL with the prior covariance V optimized, using the KL term in Eq. 8. Additionally, we investigate the effect of one vs. five learners for the DE and DEKL models; these results may be found in Appendix C. Briefly, optimizing the prior covariance leads to over-confidence; we believe this is because the cubic dataset is small, and a fixed prior provides stronger regularization than an optimized one. The effect of using a single learner is reduced flexibility of the model. More interestingly, however, with one learner, DE becomes more confident while the DEKL models become less confident, highlighting the difference in their uncertainty quantification mechanisms.

3.2 UCI DATA

We test our DEKL model on a set of regression tasks from the UCI repository that has become a popular benchmark in the Bayesian DL literature, starting with the work of Hernández-Lobato & Adams (2015). We compare the same DE, DKL and DEKL models discussed in Sec. 3.1, and we use the same experimental setup as in Lakshminarayanan et al. (2017). Each learner in the DEKL and DE models has 50 hidden neurons, except on the Protein dataset, where we use 100 hidden neurons (and correspondingly, 500 hidden neurons in the DKL models). In addition, we test the DKL and DEKL models both with a fixed prior covariance $V = I$ (DKL-I and DEKL-I) and an optimized prior covariance (DKL-O and DEKL-O).

Table 1: Test-RMSE (mean and std. dev. across 20 train-test splits) on UCI datasets, using deep ensembles (DE), deep kernel learning (DKL) and deep ensemble kernel learning (DEKL). Suffices -I and -O indicate using KL_I and KL_O, respectively.

Dataset	DE	DKL-I	DKL-O	DEKL-I	DEKL-O
Boston housing	3.29 ± 1.01	3.13 ± 0.77	3.43 ± 1.68	3.03 ± 0.87	3.03 ± 0.86
Concrete	5.79 ± 0.82	4.93 ± 0.80	4.79 ± 0.67	4.52 ± 0.59	4.57 ± 0.64
Energy	2.04 ± 0.31	0.61 ± 0.22	0.94 ± 0.96	0.48 ± 0.06	0.47 ± 0.05
Kin8nm	0.08 ± 0.00	0.08 ± 0.00	0.08 ± 0.01	0.07 ± 0.00	0.07 ± 0.00
Naval Propulsion	0.00 ± 0.00	0.00 ± 0.00	0.00 ± 0.00	0.00 ± 0.00	0.00 ± 0.00
Power plant	3.95 ± 0.16	3.83 ± 0.25	3.85 ± 0.23	3.91 ± 0.20	3.91 ± 0.18
Protein	4.40 ± 0.12	4.06 ± 0.10	3.94 ± 0.07	3.99 ± 0.11	3.95 ± 0.02
Wine	0.63 ± 0.03	0.68 ± 0.14	0.67 ± 0.06	0.63 ± 0.05	0.64 ± 0.05
Yacht	0.72 ± 0.24	2.92 ± 3.06	2.52 ± 2.78	0.61 ± 0.22	0.62 ± 0.22

Table 2: Test-NLL (mean and std. dev. across 20 train-test splits) on UCI datasets, using deep ensembles (DE), deep kernel learning (DKL) and deep ensemble kernel learning (DEKL). Suffices -I and -O indicate using KL_I and KL_O, respectively.

Dataset	DE	DKL-I	DKL-O	DEKL-I	DEKL-O
Boston housing	2.51 ± 0.23	2.59 ± 0.19	2.66 ± 0.40	2.54 ± 0.21	2.54 ± 0.21
Concrete	3.08 ± 0.28	3.01 ± 0.14	2.99 ± 0.13	2.94 ± 0.11	2.95 ± 0.12
Energy	1.66 ± 1.38	1.13 ± 0.55	1.24 ± 0.66	0.68 ± 0.09	0.67 ± 0.07
Kin8nm	-1.26 ± 0.02	-1.13 ± 0.04	-1.12 ± 0.05	-1.16 ± 0.02	-1.16 ± 0.02
Naval Propulsion	-6.69 ± 0.13	-5.65 ± 4.24	-6.28 ± 1.01	-6.52 ± 0.96	-6.78 ± 0.60
Power plant	2.77 ± 0.05	2.76 ± 0.07	2.77 ± 0.06	2.78 ± 0.06	2.78 ± 0.05
Protein	2.75 ± 0.05	2.82 ± 0.03	2.79 ± 0.02	2.81 ± 0.03	2.79 ± 0.01
Wine	0.96 ± 0.10	1.03 ± 0.23	1.01 ± 0.09	0.96 ± 0.07	0.97 ± 0.07
Yacht	0.21 ± 0.17	2.06 ± 1.33	1.78 ± 0.81	1.07 ± 0.06	1.08 ± 0.07

We consider 20 random train-test splits of each dataset except Protein, where we use only 5 train-test splits. For each split, we use 20% of the training set for validation. We train all models on the training sets using the Adam optimizer with learning rate 10^{-3} and minibatch size 128 for 1000 epochs. For the DEKL and DKL models, we set the noise precision τ by performing a grid search and selecting the value that results in the lowest negative log-likelihood (NLL) on the validation set. For all models, we find the epoch where NLL is minimized on the validation set, then retrain all models on the full dataset up to that number of epochs, and finally evaluate the models on the test sets.

We report the test root mean square error (RMSE) and test NLL averaged over all train-test splits, as is standard for the UCI benchmarks in Bayesian DL (Tables 1-2). Given a test set with N_* data points, if y_i is the true output of the ith point and μ_i and σ_i^2 are a model's predictive mean and variance (including the noise), then the RMSE and NLL of the model are given by

$$\text{RMSE} = \sqrt{\frac{1}{N_*} \sum_{i=1}^{N_*} (y_i - \mu_i)^2}, \qquad \text{NLL} = \frac{1}{N_*} \sum_{i=1}^{N_*} \left[\frac{(y_i - \mu_i)^2}{2\sigma_i^2} + \frac{1}{2} \log \sigma_i^2 \right] + \frac{1}{2} \log(2\pi),$$

where we note that the NLL is normalized by the number of data points. We see that DEKL often outperforms DE, especially in terms of RMSE, suggesting that joint ensemble Bayesian training can often be beneficial. A further comparison of DE and DEKL may be found in Appendix C, where we examine predictive performance as a function of number of learners and find that the performance gap between DE and DEKL is largely independent of the number of learners, at least up to five learners. More surprisingly, DEKL often outperforms DKL, indicating that the benefit of DEKL over DKL goes beyond simple efficiency or ease of parallelization; partitioning the feature network can often lead to a significant boost in predictive performance as well.

4 CONCLUSION

We have introduced the DEKL model: a special case of DKL that is more easily parallelizable and thus more efficient than other DKL models of comparable network complexity. DEKL achieves better predictive performance than deep ensembles, which are also highly parallelizable. Even with a linear base kernel, we have shown that DEKL is a universal kernel approximator if the feature network is allowed to be arbitrarily wide, and we handle the complexity of the feature network by partitioning it into an ensemble of learners. In our experiments, we found that DEKL often outperforms DE, suggesting that jointly training learners in a Bayesian framework can be beneficial. Interestingly, we also observed that DEKL often outperforms DKL of the same width, suggesting that partitioning the feature network not only grants computatational efficiency through model parallelism but may also boost performance by reducing parameters compared to a fully-connected DKL.

We are considering several avenues for future work. We plan to study the scalability of DEKL to a very large number of learners in a distributed setting, which may be necessary to approximate a kernel of very high or infinite rank. A key challenge in this endeavor is that the size of the variational covariance Σ grows quadratically with the number of learners; to deal with this, we will consider asymptotic regimes where efficient approximations of Σ are justified, namely the many-simple-learners regime and the complex-learners regime. In the first of these regimes, the dimension R of the span of H learners will be much less than H, which will allows us to assume that Σ is of low rank, specifically R. In the second regime, the learners may be sufficiently flexible to be orthogonal to one another, allowing us to assume Σ is diagonal. This could lead to an approach similar to that of Dasgupta et al. (2018), although with distributed computation and using our variational framework.

Another interesting topic of investigation is the mechanism by which DEKL achieves performance often superior to that of DE. In DE, the learners are trained independently, and thus any diversity among the learners is solely due to random initialization and the nonconvexity of the loss function. In contrast, in DEKL, the learners are able to "communicate" with one another through the common final GP layer, and thus we hypothesize that the learners may "coordinate" with one another to ensure diversity. We believe that diversity in DEKL may be linked to the posterior covariance, which is generally nonzero in this Bayesian setting.

It is also tempting to extend DEKL to deep Gaussian processes (DGPs), which are models defined as compositions of GPs (Damianou & Lawrence, 2013; Cutajar et al., 2017; Salimbeni & Deisenroth, 2017). This will result in a DGP inference method that again does not require an inducing points approximation, similar to the random features expansion approach of Cutajar et al. (2017), except that the features are trainable DNNs that need not be orthogonal. Given that DEKL is a universal kernel approximator, we conjecture that a DGP with DEKL kernels can approximate any DGP with continuous kernels, under some distance metric on stochastic processes. Such a result would suggest a universal model for stochastic processes (or some suitably well-behaved subspace of them), arguably the most general universality theorem we can imagine in predictive modeling.

REFERENCES

Devanshu Agrawal, Theodore Papamarkou, and Jacob Hinkle. Wide neural networks with bottlenecks are deep Gaussian processes. *Journal of Machine Learning Research*, 21(175):1–66, 2020. URL http://jmlr.org/papers/v21/20-017.html.

Maruan Al-Shedivat, Andrew Gordon Wilson, Yunus Saatchi, Zhiting Hu, and Eric P. Xing. Learning scalable deep kernels with recurrent structure. *Journal of Machine Learning Research*, 18 (82):1–37, 2017. URL http://jmlr.org/papers/v18/16-498.html.

John Bradshaw, Alexander G de G Matthews, and Zoubin Ghahramani. Adversarial examples, uncertainty, and transfer testing robustness in Gaussian process hybrid deep networks. *arXiv preprint arXiv:1707.02476*, 2017.

Brian Bullins, Cyril Zhang, and Yi Zhang. Not-so-random features. In *International Conference on Learning Representations*, 2018. URL https://openreview.net/forum?id=Hk8XMWgRb.

Kurt Cutajar, Edwin V Bonilla, Pietro Michiardi, and Maurizio Filippone. Random feature expansions for deep Gaussian processes. In *International Conference on Machine Learning*, pp. 884–893, 2017.

George Cybenko. Approximation by superpositions of a sigmoidal function. *Mathematics of Control, Signals and Systems*, 2(4):303–314, 1989.

Andreas Damianou and Neil Lawrence. Deep Gaussian processes. In *Artificial Intelligence and Statistics*, pp. 207–215, 2013.

Sambarta Dasgupta, Kumar Sricharan, and Ashok Srivastava. Finite rank deep kernel learning. In *Third Workshop on Bayesian Deep Learning, NeurIPS*, 2018.

Alexander G. de Matthews, Jiri Hron, Mark Rowland, Richard E. Turner, and Zoubin Ghahramani. Gaussian process behaviour in wide deep neural networks. *International Conference on Learning Representations*, 2018. accepted as poster.

Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. In *International Conference on Machine Learning*, pp. 1050–1059, 2016.

Chuan Guo, Geoff Pleiss, Yu Sun, and Kilian Q Weinberger. On calibration of modern neural networks. In *International Conference on Machine Learning*, pp. 1321–1330, 2017.

James Hensman, Nicolò Fusi, and Neil D Lawrence. Gaussian processes for big data. In *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence*, pp. 282–290, 2013.

José Miguel Hernández-Lobato and Ryan Adams. Probabilistic backpropagation for scalable learning of Bayesian neural networks. In *International Conference on Machine Learning*, pp. 1861–1869, 2015.

Kurt Hornik, Maxwell Stinchcombe, Halbert White, et al. Multilayer feedforward networks are universal approximators. *Neural Networks*, 2(5):359–366, 1989.

Pavel Izmailov, Alexander Novikov, and Dmitry Kropotov. Scalable Gaussian processes with billions of inducing inputs via tensor train decomposition. In *International Conference on Artificial Intelligence and Statistics*, pp. 726–735, 2018.

Arthur Jacot, Franck Gabriel, and Clément Hongler. Neural tangent kernel: convergence and generalization in neural networks. In *Advances in neural information processing systems*, pp. 8571–8580, 2018.

Neal Jean, Michael Xie, and Stefano Ermon. Semi-supervised deep kernel learning. In *NIPS Bayesian Deep Learning Workshop*, 2016.

Alex Kendall and Yarin Gal. What uncertainties do we need in Bayesian deep learning for computer vision? In *Advances in Neural Information Processing Systems*, pp. 5574–5584, 2017.

Durk P Kingma, Tim Salimans, and Max Welling. Variational dropout and the local reparameterization trick. In *Advances in Neural Information Processing Systems*, pp. 2575–2583, 2015.

Balaji Lakshminarayanan, Alexander Pritzel, and Charles Blundell. Simple and scalable predictive uncertainty estimation using deep ensembles. In *Advances in neural information processing systems*, pp. 6402–6413, 2017.

Jaehoon Lee, Yasaman Bahri, Roman Novak, Samuel S Schoenholz, Jeffrey Pennington, and Jascha Sohl-Dickstein. Deep neural networks as Gaussian processes. In *International Conference on Learning Representations*, 2018.

Moshe Leshno, Vladimir Ya Lin, Allan Pinkus, and Shimon Schocken. Multilayer feedforward networks with a nonpolynomial activation function can approximate any function. *Neural Networks*, 6(6):861–867, 1993.

Chun-Liang Li, Wei-Cheng Chang, Youssef Mroueh, Yiming Yang, and Barnabas Poczos. Implicit kernel learning. In *The 22nd International Conference on Artificial Intelligence and Statistics*, pp. 2007–2016, 2019.

James Mercer. Functions of positive and negative type, and their connection with the theory of integral equations. *Philosophical Transactions of the Royal Society of London. Series A, Containing Papers of a Mathematical or Physical Character*, 209:415–446, 1909.

Charles A Micchelli, Yuesheng Xu, and Haizhang Zhang. Universal kernels. *Journal of Machine Learning Research*, 7(Dec):2651–2667, 2006.

Radford M Neal. Priors for infinite networks. In *Bayesian Learning for Neural Networks*, pp. 29–53. Springer, 1996.

Radford M Neal. *Bayesian learning for neural networks*, volume 118. Springer Science & Business Media, 2012.

Allan Pinkus. Approximation theory of the MLP model in neural networks. *Acta Numerica*, 8: 143–195, 1999. doi: 10.1017/S0962492900002919.

Carl Edward Rasmussen and Christopher K. I. Williams. *Gaussian Processes for Machine Learning (Adaptive Computation and Machine Learning)*. The MIT Press, 2005. ISBN 026218253X.

Hugh Salimbeni and Marc Deisenroth. Doubly stochastic variational inference for deep Gaussian processes. In *Advances in Neural Information Processing Systems*, pp. 4588–4599, 2017.

Samuel S Schoenholz, Justin Gilmer, Surya Ganguli, and Jascha Sohl-Dickstein. Deep information propagation. In *International Conference on Learning Representations*, 2016.

Aman Sinha and John C Duchi. Learning kernels with random features. In *Advances in Neural Information Processing Systems*, pp. 1298–1306, 2016.

Samuel L Smith and Quoc V Le. A Bayesian perspective on generalization and stochastic gradient descent. In *International Conference on Learning Representations*, 2018.

Michalis Titsias. Variational learning of inducing variables in sparse Gaussian processes. In *Artificial Intelligence and Statistics*, pp. 567–574, 2009.

Andrew M. Webb, Charles Reynolds, Wenlin Chen, Henry Reeve, Dan-Andrei Iliescu, Mikel Lujan, and Gavin Brown. To Ensemble or Not Ensemble: When does End-To-End Training Fail? *arXiv preprint arXiv:1902.04422*, February 2019.

Andrew G Wilson, Zhiting Hu, Ruslan R Salakhutdinov, and Eric P Xing. Stochastic variational deep kernel learning. In *Advances in Neural Information Processing Systems*, pp. 2586–2594, 2016a.

Andrew Gordon Wilson. The case for Bayesian deep learning. *arXiv preprint arXiv:2001.10995*, 2020.

Andrew Gordon Wilson, Zhiting Hu, Ruslan Salakhutdinov, and Eric P Xing. Deep kernel learning. In *Artificial Intelligence and Statistics*, pp. 370–378, 2016b.

Junyu Xuan, Jie Lu, Zheng Yan, and Guangquan Zhang. Bayesian deep reinforcement learning via deep kernel learning. *International Journal of Computational Intelligence Systems*, 12(1): 164–171, 2018.

Yufan Zhou, Changyou Chen, and Jinhui Xu. Kernelnet: A data-dependent kernel parameterization for deep generative modeling. *arXiv preprint arXiv:1912.00979*, 2019.

A   PROOF OF UNIVERSAL KERNEL APPROXIMATION THEOREM

Proof of Thm. 1. By Mercer's Theorem (Mercer, 1909, Sec. 29), there exist non-negative scalars $\{\lambda_r\}_{r=1}^{\infty}$ and an orthonormal basis of continuous functions $\{e_r : \mathcal{X} \mapsto \mathbb{R}\}_{r=1}^{\infty}$ called "feature maps" such that the target kernel κ admits the representation

$$\kappa(x_1, x_2) = \sum_{r=1}^{\infty} \lambda_r e_r(x_1) e_r(x_2), \tag{10}$$

where the sum on the righthand side converges absolutely and uniformly on the compact set $\mathcal{X}$. Selecting $0 < \delta < \epsilon$, uniform convergence guarantees the existence of an integer R such that for all $x_1, x_2 \in \mathcal{X}$,

$$\left| \sum_{r=1}^{R} \lambda_r e_r(x_1) e_r(x_2) - \kappa(x_1, x_2) \right| < \delta. \tag{11}$$

By continuity of the feature maps e_r and compactness of X, the feature maps are bounded, so there exists a finite positive $B > \max_{r=1,\dots,R} \sqrt{\lambda_r} \sup_{x \in X} |e_r(x)|$. By the classic Universal Approximation Theorem (Pinkus, 1999), there exists a shallow MLP $\psi : \mathcal{X} \mapsto \mathbb{R}^R$ of width H and parameters $u_{ir} \in \mathbb{R}$ and $\beta_i : \mathcal{X} \mapsto \mathbb{R}$ for $i = 1, \dots, H$ such that for all $x \in \mathcal{X}$,

$$\psi_r(x) = \sum_{i=1}^{H} u_{ir} \sigma(\beta_i(x)) \tag{12}$$

$$\left| \psi_r(x) - \sqrt{\lambda_r} e_r(x) \right| < \gamma < \min\left(B, \frac{\epsilon - \delta}{3NB} \right) \tag{13}$$

$$|\psi_r(x_1)\psi_r(x_2) - \lambda_r e_r(x_1) e_r(x_2)| < \gamma(\gamma + 2B) < 3B\gamma \tag{14}$$

$$\left| \sum_{r=1}^{R} \psi_r(x_1)\psi_r(x_2) - \sum_{r=1}^{R} \lambda_r e_r(x_1) e_r(x_2) \right| < 3NB\gamma < \epsilon - \delta \tag{15}$$

$$\left| \sum_{r=1}^{R} \psi_r(x_1)\psi_r(x_2) - \kappa(x_1, x_2) \right| < (\epsilon - \delta) + \delta = \epsilon. \tag{16}$$

More explicitly, we have the uniform bound

$$\left| \sum_{i,j=1}^{H} \sum_{r=1}^{R} u_{ir} u_{jr} \sigma(\beta_i(x_1)) \sigma(\beta_j(x_2)) - \kappa(x_1, x_2) \right| < \epsilon. \tag{17}$$

Letting $v_{ij} = \sum_{r=1}^{R} u_{ir} u_{jr}$, the bound takes the form claimed in the statement of the theorem. Since this matrix V is of the form UU^T, it is clearly symmetric and positive semi-definite.   □

B   DERIVATION OF THE KL TERM WITH OPTIMAL PRIOR COVARIANCE

Here we derive the optimal prior covariance V_* with respect to the variational free energy in Eq. 3 and use it to eliminate the prior covariance V from the loss function entirely. We note that V appears only in the KL term (Eq. 5) and only through its inverse V^{-1}. Minimizing the KL term with respect to V^{-1}, we obtain Eq. 7 as follows:

$$\frac{\partial}{\partial V^{-1}} \text{KL}(\mu, \Sigma, V) \mid_{V=V_*} = 0$$

$$\mu\mu^\top + \Sigma - (V_*^{-1})^{-1} = 0$$

$$V_* = \mu\mu^\top + \Sigma.$$

Substituting this back into Eq. 5 and applying the Matrix Inversion Lemma, we obtain Eq. 8 as follows:

$$
\begin{aligned}
\mathrm{KL}_O(\mu, \Sigma) &= \mathrm{KL}(\mu, \Sigma, V_*) \\
&= \frac{1}{2}\mu^\top(\mu\mu^\top + \Sigma)^{-1}\mu + \frac{1}{2}\operatorname{tr}[(\mu\mu^\top + \Sigma)^{-1}\Sigma] - \frac{1}{2}\log\det[(\mu\mu^\top + \Sigma)^{-1}\Sigma] - \frac{H}{2} \\
&= \frac{1}{2}\mu^\top\left(\Sigma^{-1} - \frac{\Sigma^{-1}\mu\mu^\top\Sigma^{-1}}{1 + \mu^\top\Sigma^{-1}\mu}\right)\mu \\
&\quad + \frac{1}{2}\operatorname{tr}\left[\left(\Sigma^{-1} - \frac{\Sigma^{-1}\mu\mu^\top\Sigma^{-1}}{1 + \mu^\top\Sigma^{-1}\mu}\right)\Sigma\right] \\
&\quad + \frac{1}{2}\log\left[\frac{\det(\mu\mu^\top + \Sigma)}{\det\Sigma}\right] - \frac{H}{2} \\
&= \frac{1}{2}\mu^\top\Sigma^{-1}\mu - \frac{1}{2}\frac{\mu^\top\Sigma^{-1}\mu\mu^\top\Sigma^{-1}\mu}{1 + \mu^\top\Sigma^{-1}\mu} \\
&\quad + \frac{1}{2}\operatorname{tr}\left(I - \frac{\Sigma^{-1}\mu\mu^\top}{1 + \mu^\top\Sigma^{-1}\mu}\right) \\
&\quad + \frac{1}{2}\log\left[\frac{\det\Sigma(1 + \mu^\top\Sigma^{-1}\mu)}{\det\Sigma}\right] - \frac{H}{2} \\
&= \frac{1}{2}\mu^\top\Sigma^{-1}\mu\left(1 - \frac{\mu^\top\Sigma^{-1}\mu}{1 + \mu^\top\Sigma^{-1}\mu}\right) \\
&\quad + \frac{H}{2} - \frac{1}{2}\frac{\operatorname{tr}(\Sigma^{-1}\mu\mu^\top)}{1 + \mu^\top\Sigma^{-1}\mu} \\
&\quad + \frac{1}{2}\log(1 + \mu^\top\Sigma^{-1}\mu) - \frac{H}{2} \\
&= \frac{1}{2}\frac{\mu^\top\Sigma^{-1}\mu}{1 + \mu^\top\Sigma^{-1}\mu} \\
&\quad - \frac{1}{2}\frac{\mu^\top\Sigma^{-1}\mu}{1 + \mu^\top\Sigma^{-1}\mu} \\
&\quad + \frac{1}{2}\log(1 + \mu^\top\Sigma^{-1}\mu) \\
&= \frac{1}{2}\log(1 + \mu^\top\Sigma^{-1}\mu).
\end{aligned}
$$

C ADDITIONAL EXPERIMENTS

Here we present the results of additional experiments on the toy cubic dataset and UCI datasets. On the cubic dataset, we evaluate DEKL and DKL with both a fixed prior covariance $V = I$ as well as the optimal prior covariance. We also test DE and DEKL for one vs. five learners ($H = 1$ vs. $H = 5$). The predictive distributions of all these models are shown in Fig. 3. We make a number of observations: First, the DKL and DEKL models with fixed prior display better uncertainty quantification than DE, having lower variance within the training domain (interpolation) and higher variance outside the training domain (extrapolation). Second, DE and DEKL with one learner have less flexible means compared to their five-learner counterparts, which we expect due to reduced expressivity. However, DE is more confident with one learner while DEKL is less confident. This highlights the difference in the uncertainty quantification mechanisms of the two models; while DE relies on multiple learners for its predictive variance, DEKL offers some predictive uncertainty even with one learner thanks to Bayesian inference. Third, using the optimal prior covariance instead of the fixed one results in overconfidence. This is reasonable; a fixed prior offers stronger regularization than an optimized one, which can be critical on a dataset as small as the toy cubic dataset. Finally, the DEKL predictive distribution with five learners is similar to that of DKL. DKL is the ideal model, but it may be inefficient when a wide feature network is required. On the other hand, DEKL is more

Figure 3: Synthetic cubic dataset. The first row compares a single deep ensemble learner and a single DEKL learner with linear kernel both with and without optimal prior covariance. In the second row, a deep ensemble of five learners is compared to a comparable DEKL architecture with five parallel feature networks, with and without optimal prior covariance. In the third row are shown DKL models of the same width as the five-learner DEKL models both with and without the closed-form optimal prior covariance. Predictive mean function (blue) with three units of standard deviation of each model trained on the cubic dataset (red), with ground truth (black). Although DEKL has far fewer parameters than DKL due to partitioning into five parallel feature networks, it approximates the full DKL well on this dataset, and improves over the equivalent deep ensemble.

parallelizable thanks to its partitioned feature network. Our results show that we may partition the feature network in this way for efficiency without hurting predictive performance.

On the UCI datasets, we evaluate DE and DEKL (both with and without optimal prior covariance) for a varying number of learners to see its effect on test performance (Figs. 4-5). DEKL often maintains superior performance over DE in terms of RMSE as the number of learners is increased, although any trends in the performance gap itself are unclear. We believe an in-depth study on more complex problems and a much greater number of learners is required to see clearer trends, which we leave for future work.

Figure 4: Mean test RMSE (across all train-test splits) of the DE (red, solid), DEKL-I (green, dotted), and DEKL-O (blue, dashed) models on nine UCI datasets as a function of the number of learners.

Figure 5: Mean test NLL (across all train-test splits) of the DE (red, solid), DEKL-I (green, dotted), and DEKL-O (blue, dashed) models on nine UCI datasets as a function of the number of learners.