When Privacy Meets Partial Information: A Refined Analysis of Differentially Private Bandits

Abstract

We study the problem of multi-armed bandits with ϵ-global Differential Privacy (DP). First, we prove *the minimax and problem-dependent regret lower bounds* for stochastic and linear bandits that quantify the hardness of bandits with ϵ-global DP. These bounds suggest the existence of two hardness regimes depending on the privacy budget ϵ. In the high-privacy regime (small ϵ), the hardness depends on a coupled effect of privacy and partial information about the reward distributions. In the low-privacy regime (large ϵ), bandits with ϵ-global DP are not harder than the bandits without privacy. For stochastic bandits, *we further propose a generic framework to design a near-optimal ϵ-global DP extension of an index-based optimistic bandit algorithm*. The framework consists of three ingredients: the Laplace mechanism, arm-dependent adaptive episodes, and usage of only the rewards collected in the last episode for computing private statistics. Specifically, we instantiate ϵ-global DP extensions of UCB and KL-UCB algorithms, namely AdaP-UCB and AdaP-KLUCB. *AdaP-KLUCB is the first algorithm that both satisfies ϵ-global DP and yields a regret upper bound that matches the problem-dependent lower bound up to multiplicative constants.*

1 Introduction

Multi-armed bandit problems, in short *bandits*, are a model for sequential decision-making with partial information [16]. In bandits, a learner sequentially interacts with an environment, which is a set of unknown distributions (or arms or actions), over $T \in \mathbb{N}$ steps. T is referred to as the horizon. At each step $t \in \{1, \ldots, T\}$, the learner chooses an arm A_t from $\{1, \ldots, K\}$ and the environment reveals a reward r_t from the distribution ν_{A_t}. The learner's objective is to maximise its cumulative reward $\sum_{t=1}^{T} r_t$. An equivalent performance metric for a bandit algorithm π is *regret*. Regret is the difference between the expected cumulative reward collected by pulling the optimal arm a^* for T times and the expected cumulative reward obtained by using π. Regret is the price paid by the bandit algorithm due to partial information about the reward distributions. *The goal of a bandit algorithm is to minimise its regret.* Bandits, introduced in [24] for medical trials, are widely studied and deployed in real-life applications, such as online advertising [21], recommendation systems [23] and investment portfolio design [23]. Sensitive data of individuals, such as health conditions, personal preferences, financial status etc., are utilised in these applications, which raises the concern about privacy.

Example 1. *In bandit-based recommendation systems, the learning algorithm selects an item for each user. The user decides whether or not to click the recommendation. Based on the click feedback, the bandit algorithm improves its subsequent recommendations. Here, an action corresponds to an item and a reward corresponds to whether a user clicks on the item (1) or not (0). A change in a user's preference prompts changes in the algorithm's output. As a result, even if the click feedback is kept private, the user's private information, i.e. their preference over items, is revealed. Privacy protection aims to prevent the algorithm's output from revealing the preferences of any specific user.*

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

This example demonstrates the need for privacy in bandits. In this paper, we use Differential Privacy (DP) [8] as the framework for privacy. DP ensures that an algorithm's output is unaffected by changes in input at a single data point. By limiting the amount of sensitive information that an adversary can deduce from the output, DP renders an individual corresponding to a data point 'indistinguishable'. A calibrated amount of noise is injected into an algorithm to ensure DP. The noise scale is set to be proportional to the algorithm's sensitivity and inversely proportional to the privacy budget ϵ.

To address the privacy issues in bandit applications, the problem of Differentially Private Bandits is coined and studied under different settings, such as stochastic bandits [18, 25, 20, 12], adversarial bandits [26], and linear contextual bandits [22, 19]. Also, multiple adaptations of DP, namely local and global, are proposed for bandits [3]. *Local DP* aims to preserve the privacy of the sequence of rewards obtained by sending noisy rewards to the algorithm [5]. *Global DP* allows the algorithm to access rewards without noise and aims to keep the sequence of rewards private while only the sequence of actions taken by the algorithm is produced to the public [3]. Though local DP provides stronger privacy as the data curator has no access to the original reward stream, it injects too much noise that leads to higher regret. Also, the fundamental hardness of local DP in bandits in terms of regret lower bound and also corresponding optimal algorithms are well-understood [28]. Thus, in this paper, *we focus on the bandit problems with ϵ-global DP*. We aim to address two questions:

1. *What is the fundamental hardness of differentially private bandits with global DP expressed in terms of the regret lower bound?*
2. *How to design an algorithmic framework that converts an optimistic and near-optimal bandit algorithm into a near-optimal bandit algorithm satisfying global DP?*

Our Contributions. These questions have led to the following contributions:

1. *Hardness as Lower Bounds:* We derive both the minimax (worst-case) and problem-dependent lower bounds on the regret of bandits with ϵ-global DP for stochastic bandits (Thm. 2 and 3, Sec. 3). Both the bounds show that the hardness depends on a trade-off between the privacy budget ϵ and the distinguishability gap of a bandit environment. If the ϵ is bigger than the distinguishability gap, a bandit with global DP is not harder than a non-private bandit problem. We also extend our techniques to derive the lower bounds for linear bandits with a finite number of arms (Thm. 4 and 5). These lower bounds also reflect the same transition of hardness depending on ϵ and distinguishability gaps.

2. *Algorithm Design:* Optimistic bandit algorithms used the empirical mean and variance of observed rewards to compute indexes and use them to select an action. We propose three fundamental strategies to design a private bandit algorithm from an optimistic algorithm (Sec. 4)– a) add Laplacian noise to the empirical mean of each arm calibrated by the corresponding sensitivity, b) use adaptive episodes to compute the private empirical mean less number of times, and c) use only the observed rewards of the arm's *last active episode*[1] and forget everything before to keep the sensitivity of the empirical mean low. We deploy these techniques with UCB [2] and KL-UCB [10] algorithms for non-private bandits to propose two near-optimal and ϵ-global DP bandit algorithms, AdaP-UCB and AdaP-KLUCB (Sec. 4). Both of these algorithms achieve near-optimal problem-dependent regret and also reflect a transition in hardness from a low to a high privacy regime (Thm. 7 and 8). Both theoretical (Table 1) and experimental (Sec. 5) results demonstrate optimality of AdaP-KLUCB than existing algorithms.

3. *Technical Tools:* To derive the lower bound, we present a novel sequential information processing lemma under ϵ-global DP that controls the difference between the outcome streams of a differentially private policy when interacting with two different bandit instances. To derive the upper bound, we develop a novel and general analysis of optimistic algorithms with adaptive episodes.

Related Works: Lower Bound. [22] first proposed a problem-dependent lower bound on regret, $\Omega(\max\{\sum_{a \neq a^*} \frac{\log T}{\Delta_a}, \frac{K \log(T)}{\epsilon}\})^2$, for stochastic bandits with ϵ-globally DP. But this bound is restricted to Bernoulli distributions of reward. In this paper, *we provide the first problem-dependent regret lower bound that is valid for any reward distribution. This lower bound shows that the effect of privacy does not only depend on ϵ but also on the total variation distance corresponding to the environment.* Thus, *it explicates the coupled effect of privacy and partial information in a high-privacy regime*, which was not observed before. To derive this tighter lower bound, we extend the Karwa-Vadhan lemma (Lemma 6.1, [13]) to a sequential setting and also propose a generic proof

---

[1]The last active episode of an arm is the last episode in which that arm was played.

[2]Here, a^* is the optimal arm with mean reward μ^* and $\Delta_a \triangleq \mu^* - \mu_a$ is the suboptimality gap of arm a.

Table 1: A comparison of ϵ-global DP algorithms for bandits.

Algorithm	Regret	# Private Means [3]	Anytime	Forgetfulness [4]
DP-UCB[18, 25]	$\mathcal{O}\left(\frac{\log(T)^{2.5}}{\epsilon} + \sum_{a \neq a^*} \frac{\log(T)}{\Delta_a}\right)$	KT	Yes	No
DP-SE[20]	$\mathcal{O}\left(\frac{K\log(T)}{\epsilon} + \sum_{a \neq a^*} \frac{\log(T)}{\Delta_a}\right)$	$\mathcal{O}(\log(T))$	No	Yes
AdaP-UCB	$\mathcal{O}\left(\sum_{a \neq a^*} \frac{\Delta_a \log(T)}{\min(\epsilon\Delta_a, \Delta_a^2)}\right)$	$\mathcal{O}(\log(T))$	Yes	Yes
AdaP-KLUCB	$\mathcal{O}\left(\sum_{a \neq a^*} \frac{\Delta_a \log(T)}{\min(d(\mu_a, \mu^*), \epsilon\Delta_a)}\right)$	$\mathcal{O}(\log(T))$	Yes	Yes

structure leading to *problem-dependent and minimax lower bounds for stochastic and linear bandits. To our knowledge, these are the first regret lower bounds for linear bandits with ϵ-global DP.*

Related Works: Bandit Algorithms with ϵ-global DP. DP-UCB [18, 25] was the first global DP version of UCB. DP-UCB uses the tree-based mechanism [6, 4] to compute the sum of rewards. The tree mechanism maintains a binary tree of depth $\log(T)$ over the T streaming observations, where each node in this tree holds an i.i.d sample from a Laplace distribution with zero mean and scale $(\log(T)/\epsilon)$. At each step t, the mechanism yields the sum of the first t observations and the $\log(T)$ nodes on the root-to-the-leaf path in the binary tree as the private empirical mean. As a result, the noise added to the UCB index per time-step is $\mathcal{O}\left(\log(T)^{2.5}/\epsilon\right)$, which is responsible for the extra multiplicative factor $\log(T)^{1.5}$ in regret compared to the lower bound. DP-SE [20] was the first ϵ-global DP algorithm to eliminate the additional multiplicative factor $\log(T)^{1.5}$. DP-SE is an ϵ-global DP version of the Successive Elimination algorithm [9]. However, the drawbacks were that the algorithm was not anytime, and was optimal only asymptotically, i.e. the horizon should be big enough. On the other hand, a careful analysis of the algorithm suggests that what made the algorithm optimal was the fact that the algorithm was run in doubling episodes, where the private means computed at the end of the episode to decide which arms to eliminate, were only computed using the samples collected from that episode. *We detect these ingredients and generalise them to propose a general framework to make any optimist index-based policy optimal followed by upper bounds matching the lower bounds (Table 1).* Similar techniques have been deployed to design a global DP extension of UCB in [12] but they have an additive factor $\log(T)$ extra in regret than AdaP-UCB and do not match our proposed regret lower bound. *This work leads to the first near-optimal bandit algorithm with ϵ-global DP, namely* AdaP-KLUCB.

2   Background: Differential Privacy and Bandits

Differential Privacy (DP). DP renders an individual corresponding to a datum indistinguishable by constraining the output of an algorithm to be almost the same under a change in one input datum.

Definition 1 ((ϵ, δ)-DP). *A randomised algorithm $\mathcal{A}$ satisfies (ϵ, δ)-Differentially Privacy (DP) if for any two neighbouring datasets[5] $\mathcal{D}$ and $\mathcal{D}'$, and for all sets of output $\mathcal{O} \subseteq \mathrm{Range}(\mathcal{A})$*

$$\Pr[\mathcal{A}(\mathcal{D}) \in \mathcal{O}] \leq e^\epsilon \Pr[\mathcal{A}(\mathcal{D}') \in \mathcal{O}] + \delta, \tag{1}$$

where the probability space is over the coin flips of the mechanism $\mathcal{A}$ and for some $(\epsilon, \delta) \in \mathbb{R}^{\geq 0} \times \mathbb{R}^{\geq 0}$. If $\delta = 0$, we say that $\mathcal{A}$ satisfies ϵ-differential privacy.

The Laplace mechanism [7, 8] ensures ϵ-DP by injecting a random noise to the output of the algorithm that is sampled from a calibrated Laplace distribution (as specified in Theorem 1). We use $Lap(b)$ to denote the Laplace distribution with mean 0 and variance $2b^2$.

Theorem 1 (ϵ-DP of Laplace Mechanism (Theorem 3.6, [8])). *Let us consider an algorithm $f : \mathcal{X} \to \mathbb{R}^d$ with sensitivity $s(f) \triangleq \max_{\mathcal{D}, \mathcal{D}' \text{ s.t } \|\mathcal{D}-\mathcal{D}'\|_{\mathrm{Hamming}}=1} \|f(\mathcal{D}) - f(\mathcal{D}')\|_1$. Here, $\|\cdot\|_1$ is the L_1 norm on $\mathbb{R}^d$. If d noise samples $\{N_i\}_{i=1}^d$ are generated independently from $Lap(\frac{s(f)}{\epsilon})$, the output injected with the noise, i.e. $f(\mathcal{D}) + [N_1, \ldots, N_d]$ satisfies ϵ-DP.*

---

[3] The number of private empirical mean reward statistics computed by the algorithm.

[4] Not using the full history of rewards to compute the private empirical mean reward statistics.

[5] Neighbouring datasets differ only in one entry, i.e $\|\mathcal{D} - \mathcal{D}'\|_{\mathrm{Hamming}} = 1$.

Table 2: Regret lower bounds for bandits with ϵ-global DP

	Minimax	Problem Dependent
Stochastic Multi-armed bandit	$\max\left(\frac{1}{27}\sqrt{T(k-1)}, \frac{1}{131}\frac{k-1}{\epsilon}\right)$	$\sum_{a:\Delta_a>0} \frac{\Delta_a \log(T)}{\min(d_a, 6\epsilon t_a)}$
Stoachastic Linear bandit	$\max\left(\exp(-2), \exp(-6\epsilon\sqrt{T})\right)\frac{d}{8}\sqrt{T}$	$\inf_{\alpha\in[0,\infty)^{\mathcal{A}}} \sum_{a\in\mathcal{A}} \alpha(a)\Delta_a \log(T)$ s.t. $\|a\|_{H_\alpha^{-1}}^2 \leq \Delta_a \min\left(\frac{\Delta_a}{2}, 3\epsilon\rho(\mathcal{A})\right)$

126 The Laplace mechanism is originally proposed to ensure DP when the input database is static. In a
127 sequential setting like bandits, a mechanism must update the published statistics as new data items
128 arrive, and thus DP definitions are extended accordingly [3].

129 **Stochastic Bandits with Global DP.** Now, we describe the general canonical bandit model (Section
130 4.6, [16]) and define global Differential Privacy (global DP) in this setting. A bandit algorithm (or
131 policy) interacts with an environment ν consisting of K arms with reward distributions $\{\nu_a\}_{a=1}^K$ for
132 a given horizon T and produces a history $\mathcal{H}_T \triangleq \{(A_t, R_t)\}_{t=1}^n$. At each step t, the choice of the arm
133 depends on the previous history $\mathcal{H}_{t-1}$. The reward R_t is sampled from the reward distribution ν_{A_t}
134 and is conditionally independent of the previous history $\mathcal{H}_{t-1}$. Thus, a bandit algorithm (or policy) π
135 can be represented by a sequence $(\pi_t)_{t=1}^T$, where $\pi_t : \mathcal{H}_{t-1} \to [K]$ is a probability kernel. Thus, we
136 denote the probability of occurrence of a sequence of actions $a^T \triangleq [a_1, \ldots, a_T]$ given a sequence
137 of rewards $r^n \triangleq [r_1, \ldots, r_T]$ as $\pi(a^T \mid r^T) \triangleq \prod_{t=1}^T \pi_t(a_t \mid a_1, r_1, \ldots, a_{t-1}, r_{t-1})$. *If we consider*
138 a^T *as the output of a bandit algorithm and r^T as the input, $\pi(a^T \mid r^T)$ defines the corresponding*
139 *probability distribution on the output space required for defining DP* (Eq. (1)). In order to define
140 DP in the sequential setup of bandits, the event-level privacy under continuous observations [7]
141 framework is adopted. In this framework, if two data sequences differ on a single entry at a single
142 time-step t and are identical on all other time-steps, they are called neighbouring data sequences. A
143 sequential algorithm is differentially private if its output sequence is not distinguishable from two
144 neighbouring input sequences. This framework leads to the *global DP* definition for bandits [18, 3].

145 **Definition 2** (Global DP for Bandits)**.** *A bandit algorithm $\pi \in \Pi^\epsilon$ satisfies ϵ-global DP, if $\pi(a^T \mid$*
146 *$r^T) \leq e^\epsilon \pi(a^T \mid r'^T)$ for every action sequence $a^T \in [K]^T$ and every two neighbouring reward*
147 *sequences $r^T, r'^T \in \mathbb{R}^T$, which means that $\exists j \in [1, T]$ such that $r_j \neq r'_j$ and $\forall t \neq j \ r_t = r'_t$. The*
148 *set of all bandit algorithms satisfying ϵ-global DP, i.e. Π^ϵ, is called the ϵ-global DP policy class.*

149 Now, we formally define the regret of a bandit algorithm with ϵ-global DP, namely π^ϵ, as

$$\text{Reg}_T(\pi^\epsilon, \nu) \triangleq T\mu^*(\nu) - \mathbb{E}_{\nu\pi}\left[\sum_{t=1}^T R_t\right] \triangleq \sum_{a=1}^K \Delta_a \mathbb{E}_{\nu\pi}[N_a(T)]. \tag{2}$$

150 $N_a(T) \triangleq \sum_{t=1}^T \mathbb{1}\{A_t = a\}$ is the number of times the arm a is played till T. $\Delta_a \triangleq \mu^*(\nu) - \mu_a$ is
151 the suboptimality gap of the arm a. The expectation is taken with respect to the probability measure
152 on action-reward sequences induced by the interaction of π and ν. *The objective of the bandit*
153 *algorithm π^ϵ is to satisfy ϵ-global DP while minimising the regret over horizon T. A regret lower*
154 *bound of any ϵ-global DP bandit algorithm in Π^ϵ quantifies the fundamental hardness of this problem.*
155

3 Regret Lower Bounds for Bandits with ϵ-global DP

157 The first question is how much additional regret we have to endure in bandits with ϵ-global DP than
158 the bandits without privacy. The lower bound on regret provides insight into the intrinsic hardness of
159 the problem and serves as a target for the optimal algorithm design. In this section, *we prove minimax*
160 *and problem-dependent lower bounds for stochastic and linear bandits under ϵ-global DP.* The
161 proposed lower bounds are summarised in Table 2. We defer the proof details to the supplementary.

162 **Stochastic Bandits.** First, we consider the stochastic bandit problem with K-arms (as in Section 2).

163 *Minimax Regret.* We derive the minimax regret lower bound in this bandit setting with ϵ-global DP.
164 Minimax regret is the lowest achievable regret by any bandit algorithm under the worst environment
165 among a family of environments $\mathcal{E}^K$ with K arms under consideration.

$$\text{Reg}_{T,\epsilon}^{\text{minimax}} = \inf_{\pi^\epsilon \in \Pi^\epsilon} \sup_{\nu \in \mathcal{E}^K} \text{Reg}_T(\pi^\epsilon, \nu)$$

Theorem 2 (Minimax lower bound). *For any $K > 1$ and $T \geq K - 1$, and $\epsilon > 0$, the minimax regret of stochastic bandits with ϵ-global DP satisfies*

$$\text{Reg}_{T,\epsilon}^{minimax} \geq \max\left\{ \frac{1}{27}\underbrace{\sqrt{T(K-1)}}_{without\ global\ DP}, \quad \frac{1}{131}\underbrace{\frac{K-1}{\epsilon}}_{with\ \epsilon\text{-}global\ DP} \right\}. \tag{3}$$

Consequences of Theorem 2. Equation (3) shows two regimes of hardness: *high-privacy*, corresponding to lower values of ϵ, and *low-privacy*, corresponding to higher values of ϵ. In the high-privacy regime, specifically for $\epsilon < \frac{131}{27}\sqrt{\frac{(K-1)}{T}}$, the hardness depends only on the number of the arms K and the privacy budget ϵ and is higher than the lower bound for bandits without privacy. In the low-privacy regime, i.e. for $\epsilon \geq \frac{131}{27}\sqrt{\frac{(K-1)}{T}}$, the lower bound coincides with that of the bandits without privacy. This indicates the phenomena that for higher values of ϵ, signifying lower privacy, bandits with global DP is not harder than the bandits without privacy. Specially, for significantly large T, the threshold between low and high privacy regime is smaller than most of the practically used privacy budget values. For example, if $T = 10^6$ and $K = 100$, the bandits with and without global DP are equivalently hard for any privacy budget $\epsilon \geq 0.05$. This shows that for stochastic bandits, we can deploy very low privacy budgets (ϵ) without loosing anything in performance.

Problem-dependent Regret: Similar to the lower bounds specific to the Bernoulli reward distributions [22], the minimax bound indicates a separation between hardness due to global DP and partial information. To understand whether this observation is an artefact of the Bernoulli distribution and the worst-case environment considered in minimax bounds, we derive a lower bound on the problem-dependent regret (Equation (2)) for general reward distributions.

Before deriving the lower bound, we define two information-theoretic terms that quantify the distinguishability of the specific bandit environment ν where the algorithm is operating from all other bandit environments with K arms and finite means. If $\mathcal{M}$ is a set of distributions with finite means, and $\mu(P)$ is the mean of the reward distribution $P \in \mathcal{M}$, we define the *KL-distinguishability gap* as $d_{\inf}(P, \mu^*, \mathcal{M}) \triangleq \inf_{P' \in \mathcal{M}} \{D_{\text{KL}}(P \parallel P') : \mu(P') > \mu^*\}$ and the *TV-distinguishability gap* as $t_{\inf}(P, \mu^*, \mathcal{M}) \triangleq \inf_{P' \in \mathcal{M}} \{\text{TV}(P \parallel P') : \mu(P') > \mu^*\}$. These two quantities indicate the minimum dissimilarity, in terms of KL-divergence and Total Variation (TV) distance, of the reward distribution of the optimal arm a^* with any other distribution with finite mean higher than μ^*. For bandits without DP, inverse of the KL-distinguishability gap quantifies the hardness to identify the optimal arm of the environment ν under partial information [14].

Theorem 3 (Problem-dependent Regret Lower Bound). *Let the environment $\mathcal{E}$ be a set of K reward distributions with finite means and a policy $\pi^\epsilon \in \Pi_{cons}(\mathcal{E}) \cap \Pi^\epsilon$ be a consistent policy[6] over $\mathcal{E}$ satisfying ϵ-global DP . Then, for all $\nu = (P_i)_{i=1}^k \in \mathcal{E}$, it holds that*

$$\liminf_{T \to \infty} \frac{\text{Reg}_T(\pi^\epsilon, \nu)}{\log(T)} \geq \sum_{a:\Delta_a > 0} \frac{\Delta_a}{\min\left(\underbrace{d_{\inf}(P_a, \mu^*, \mathcal{M}_a)}_{without\ global\ DP}, \underbrace{6\,\epsilon\,t_{\inf}(P_a, \mu^*, \mathcal{M}_a)}_{with\ \epsilon\text{-}global\ DP}\right)}. \tag{4}$$

Consequences of Theorem 3. Now, we summarise the interesting observations led by the lower bound.
1. *Universality:* The lower bound of Theorem 3 holds for any environment with K arms and reward distributions with finite means. This is the first general lower bound for bandits with ϵ-global DP.

2. *For Bernoulli distributions of reward:* TV-distinguishability gap $t_{\inf}(P_a, \mu^*, \mathcal{M}_a) = \Delta_a$, i.e. the suboptimality gap of arm a, and the KL-distinguishability gap $d_{\inf}(P_a, \mu^*, \mathcal{M}_a) \geq 2\Delta_a^2$. Thus, our problem-dependent lower bound reduces to $\Omega(\sum_{a \neq a^*} \frac{\log T}{\min\{\Delta_a, \epsilon\}})$. For Bernoulli rewards, our lower bound is able to retrieve the lower bound of [22] with explicit constants.

3. *High- and Low-privacy Regimes:* Like the minimax regret bound, the problem-dependent regret also indicates two clear regimes in regret due to high and low privacy (resp. small and large privacy budgets ϵ). *In the low-privacy regime, i.e. for $\epsilon \geq \frac{d_{\inf}(P_a, \mu^*, \mathcal{M}_a)}{6t_{\inf}(P_a, \mu^*, \mathcal{M}_a)}$, the regret achievable by bandits*

---

[6]A policy π is called consistent over a class of bandits $\mathcal{E}$ if for all $\nu \in \mathcal{E}$ and $p > 0$, it holds that $\lim_{T \to \infty} \frac{R_T(\pi, \nu)}{T^p} = 0$. We denote the class of consistent policies over a set of environments $\mathcal{E}$ as $\Pi_{cons}(\mathcal{E})$.

with global DP and without global DP are same. Thus, there is no loss in performance due to privacy in this regime. *In the high-privacy regime, i.e. for $\epsilon < \frac{d_{\inf}(P_a, \mu^*, \mathcal{M}_a)}{6t_{\inf}(P_a, \mu^*, \mathcal{M}_a)}$, the regret depends on a coupled effect of privacy and partial information.* This effect is quantified by the inverse of the privacy budget times inverse of the TV-distinguishability gap. This interaction between privacy and partial information was not explicated by any of the existing lower bounds. In Section 4, we propose the AdaP-KLUCB algorithm that demonstrates the same interactive effect in its regret upper bound.

Stochastic Linear Bandits. In order to illustrate the generality of our results, and also to investigate how partial information and privacy in structured bandits, we derive minimax and problem-dependent regret lower bounds for stochastic linear bandits [15]. To perform the regret analysis, we consider a simple linear model with parameter $\theta \in \mathbb{R}^d$ and Gaussian noise. It implies that for an action $A_t \in \mathcal{A} \subseteq \mathbb{R}^d$ the reward is $X_t = \langle A_t, \theta \rangle + \eta_t$, where $\eta_t \sim \mathcal{N}(0, 1)$ is a sequence of independent Gaussian noises. The regret of a policy is $\text{Reg}_T(\mathcal{A}, \theta) \triangleq \mathbb{E}_\theta \left[\sum_{t=1}^{T} \Delta_{A_t} \right]$, where suboptimality gap $\Delta_a \triangleq \max_{a' \in \mathcal{A}} \langle a' - a, \theta \rangle$, and $\mathbb{E}_\theta[\cdot]$ is the expectation with respect to the measure on outcomes induced by the interaction of the policy and the linear bandit determined by θ. Given this structure, we state the minimax and problem-dependent regret lower bounds for stochastic linear bandits.

Theorem 4 (Minimax regret lower bound). *Let $\mathcal{A} = [-1, 1]^d$ and $\Theta = \left\{ -T^{-1/2}, T^{-1/2} \right\}^d$. Then, there exists a vector $\theta \in \Theta$ such that the minimax regret of linear bandits with ϵ-global DP satisfies*

$$\text{Reg}_T^{minimax}(\mathcal{A}, \theta) \geq \max \left\{ \underbrace{\exp(-2)}_{\text{without global DP}}, \underbrace{\exp(-6\epsilon\sqrt{T})}_{\text{with } \epsilon\text{-global DP}} \right\} \frac{d}{8} \sqrt{T}. \tag{5}$$

Theorem 5 (Problem-dependent regret lower bound). *Let $\mathcal{A} \subset \mathbb{R}^d$ be a finite set spanning $\mathbb{R}^d$ and $\theta \in \mathbb{R}^d$ be such that there is a unique optimal action. Then, for any consistent and ϵ-global DP bandit algorithm satisfies*

$$\liminf_{T \to \infty} \frac{\text{Reg}_T(\mathcal{A}, \theta)}{\log(T)} \geq c(\mathcal{A}, \theta), \tag{6}$$

where the structural distinguishability gap *is the solution of a constraint optimisation*

$$c(\mathcal{A}, \theta) \triangleq \inf_{\alpha \in [0,\infty)^{\mathcal{A}}} \sum_{a \in \mathcal{A}} \alpha(a) \Delta_a, \text{ such that } \|a\|_{H_\alpha^{-1}}^2 \leq \min \left\{ \underbrace{0.5\Delta_a^2}_{\text{without global DP}}, \underbrace{3\epsilon\rho_a(\mathcal{A})\Delta_a}_{\text{with } \epsilon\text{-global DP}} \right\}$$

for all $a \in \mathcal{A}$ with $\Delta_a > 0$, $H_\alpha = \sum_{a \in \mathcal{A}} \alpha(a) aa^\top$, and an arm-structure dependent constant $\rho_a(\mathcal{A})$.

Remarks. Theorems 4 and 5 are the first minimax and problem-dependent regret lower bounds for linear bandits. The minimax regret bound also shows a clear distinction between high- and low-privacy regimes for $\epsilon < 1/(3\sqrt{T})$ and $\epsilon \geq 1/(3\sqrt{T})$. Interestingly, the threshold between two regimes is independent of the dimension d and allows us to use quite low values of ϵ without losing any performance. The difference between high- and low-privacy regimes is more subtle. The first constraint on $\|a\|_{H_\alpha^{-1}}^2$ is reminiscent of the Graves-Lai bound for structural bandits without privacy. The second constraint, i.e. $3\epsilon\rho(\mathcal{A})\Delta_a$, captures the interaction between privacy and partial information under linear structure and in the high-privacy regime.

Proof Technique. In order to prove the lower bounds, we adopt the general canonical bandit model. The high level idea of proving bandit lower bounds is selecting two *hard* environments, which are hard to be statistically distinguished but are conflicting, i.e. actions that may be optimal in one is suboptimal in other. This is quantified by upper bounding the per-step KL-divergence between action distributions for such hard environments, and then plugging in this upper bound in the Bretagnolle-Huber inequality to obtain a regret lower bound. Though this proof technique works to quantify the hardness due to partial information, we need to upper bound the "confusion" created due to global DP. Existing proofs use the information-processing lemma of Karwa-Vadhan [13]. Though this works for Bernoulli bandits, to proof a general bound, we derive a sequential version of this lemma. The sequential version leads to an upper bound of the KL-divergence dependent on both total-variation distinguishability gap and privacy budget, and enables us to show the coupled effect of privacy and partial-information in the high-privacy regimes. For details of the technical results, we refer to the Supplementary Material.

4 Stochastic Bandit Algorithms with ϵ-global DP: AdaP-UCB & AdaP-KLUCB

In this section, *we present a framework (Algorithm 1) to convert index-based optimistic algorithms into algorithms satisfying ϵ-global DP*. We instantiate this framework by proposing AdaP-UCB and AdaP-KLUCB, and derive corresponding regret upper bounds.

Algorithm 1 A framework for ϵ-global DP extension of an index-based bandit algorithm

---

1: **Input:** Privacy budget ϵ, an environment ν with K arms, parameter $\alpha > 3$
2: **Output:** A sequence of T-actions satisfying ϵ-global DP
3: **Initialisation:** Choose each arm once and assign $t = k$
4: **for** $\ell = 1, 2, \ldots$ **do**   ▷ Adaptive episodes of reward subsequences
5:     Let $t_\ell = t + 1$
6:     Compute $A_\ell = \mathrm{argmax}_a \, \mathrm{I}_a^\epsilon(t_\ell - 1, \alpha)$ ▷ Arm selection with the private indexes
7:     Choose arm A_ℓ until round t such that $T_i(t) = 2T_i(t_\ell - 1)$ ▷ Doubling of episodes
8: **end for**

Index-Based Algorithms and Private Empirical Mean. We focus on index-based bandit algorithms that compute the empirical mean of rewards of each arm at each step. *Using the empirical means, they compute an optimistic index for each arm that serves as a high-probability upper confidence bound on the true mean of the corresponding arm.* Examples of such algorithms with empirical mean-based indexes include UCB [2], MOSS [1], KL-UCB [10], IMED [11] etc. Here, the empirical mean is the main statistics of reward sequences used by the algorithms. Thus, by post-processing lemma, *designing an ϵ-global DP bandit algorithm reduces to computing the empirical means privately.*

By Theorem 1, we know that adding a Laplacian noise with scale $s(\hat{\mu}_t)/\epsilon$ to each empirical mean turns it ϵ-DP, where $s(\hat{\mu}_t)$ is the sensitivity of empirical mean $\hat{\mu}_t$ at step t. For K arms and horizon T, an index-based bandit algorithm computes the empirical mean KT times. Using the naïve composition of ϵ-DP, a first baseline is to make each computed empirical mean $\frac{\epsilon}{KT}$-DP. This needs us to add at each step noise scaled linearly to T. This might lead the corresponding bandit algorithm to yield a linear regret. Thus, we need to add noise less number of times and with lower sensitivity.

Empirical Mean using Reward Sub-sequence. The improvement is invoked by the observation that a bandit algorithm does not need to calculate the empirical mean at each time-step using all the rewards observed till that step. Thus, motivated by the DP-SE [20], we calculate the empirical mean less number of times by exploiting an episodic structure that we will explicit later. Specifically, we use only the rewards of the last episode. We formally express this trick in Lemma 1.

Lemma 1. *Let us define the private empirical mean of the rewards between steps i and j $(i < j)$ as*

$$f^\epsilon\{r_i, \ldots, r_j\} \triangleq \frac{1}{j - i} \sum_{t=i}^{j} r_t + Lap\left(\frac{1}{(j-i)\epsilon}\right).$$

If $1 < t_1 < \cdots < t_\ell < T$ and $r_t \in [0,1]$, the mechanism f^ϵ mapping the sequence of rewards $(r_1, r_2, \ldots, r_{T-1}, r_T)$ to $(\ell + 1)$-private empirical means $(f^\epsilon\{r_1, \ldots, r_{t_1-1}\}, f^\epsilon\{r_{t_1}, \ldots, r_{t_2-1}\}, \ldots, f^\epsilon\{r_{t_{\ell-1}}, \ldots, r_{t_\ell-1}\}, f^\epsilon\{r_{t_\ell}, \ldots, r_T\})$ satisfies ϵ-DP.

Lemma 1 implies that, if we calculate the empirical mean of each arm $\ell + 1$ $(\ll T)$ times on non-overlapping sub-sequences of the reward stream, we only need to ensure that each empirical mean is ϵ-DP with respect to the corresponding reward sub-sequence. These $(\ell + 1)$ private empirical means together ensure that the sequence of $(\ell + 1)$ computed indexes and the resultant action sequence of length T satisfy ϵ-global DP by the post-processing lemma [8]. *Thus, we divide the horizon into $(\ell + 1)$-episodes. This allows us to take T actions only by computing $\ell + 1$ private empirical means with the rewards observed in the last active episode of the arm.* Specifically, for each $t \in [t_i, t_{i+1} - 1]$, we play the same arm that was decided at the beginning of the episode, i.e. at t_i, with the private empirical mean computed from the last active episode of that arm.

Adaptive Episodes with Doubling. In order to set the episode lengths, we focus on the specific structure of the bandit process. Specifically, we know that a sub-optimal arm a should be sampled at least $n_a = \mathcal{O}\left(\frac{\log(T)}{\Delta_a^2}\right)$ times before discarding. Since the empirical means are computed using only rewards of one episode, to yield a near-optimal regret, the length of the episode at any given time should be greater than n_a. *To satisfy this criterion, we deploy adaptive episodes with doubling.*

Figure 1: An illustration of adaptive episodes with per-arm doubling.

Example 2 (Illustration of Algortihm 1.). *To clarify the schematic, we illustrate a few steps of executing Algorithm 1 in Figure 1. After playing each arm once, the first episode begins at t_1. To observe different ingredients, we focus on step $t_4 = 7$. The index of Arm 1 at t_4 uses the private empirical mean $\frac{r_4+r_5}{2} + Lap(\frac{1}{2\epsilon})$ to build a high probability upper bound of the real mean μ_1 with confidence $t_4^{-\alpha}$. The index of Arm 2 uses $r_6 + Lap(\frac{1}{\epsilon})$. If we assume that the index of Arm 1 is higher at t_4, Arm 1 is played for a full episode from t_4 until $t_5 - 1$. The last time, when Arm 1 was played, the length of the episode was 2. Thus, following t_4, the length of the episode is doubled to 4.*

Theorem 6 (ϵ-global DP). *For any index I_a^ϵ computed using the private empirical mean of the rewards collected in the last active episode of arm a, Algorithm 1 satisfies ϵ-global DP.*

Now, to concretise an algorithm, we only need to explicit how the indexes are calculated. In other words, we need to build a high-probability upper confidence bound on the true mean of an arm only using a private empirical mean. We instantiate the design details for AdaP-UCB and AdaP-KLUCB.

AdaP-UCB **and** AdaP-KLUCB. Let $\hat{\mu}_a^\ell$ be the empirical mean reward of arm a computed using the samples collected between $t_{\psi_a(\ell)}$ and $t_{\psi_a(\ell)+1} - 1$.[7] Thus, due to the doubling of episode length, the empirical mean corresponds to $\frac{1}{2} N_a(t_\ell - 1)$ samples of arm a. Since the rewards are in $[0,1]$, the private empirical mean as $\tilde{\mu}_{a,\epsilon}^\ell = \hat{\mu}_a^\ell + Lap\left(\frac{2}{\epsilon N_a(t_\ell-1)}\right)$ satisfies ϵ-DP (Theorem 1). Now, we want to ensure that $I_a^\epsilon(t_\ell - 1, \alpha)$, computed using only $\tilde{\mu}_{a,\epsilon}^\ell$, is a high-probability upper bound on the true mean. Here, we introduce two specific indexes that satisfy this criterion.

For AdaP-UCB:
$$I_a^\epsilon(t_\ell - 1, \alpha) = \tilde{\mu}_{a,\epsilon}^\ell + \sqrt{\frac{\alpha \log(2t_\ell)}{2 \times \frac{1}{2} N_a(t_\ell-1)}} + \frac{\alpha \log(t_\ell)}{\epsilon \times \frac{1}{2} N_a(t_\ell-1)} \tag{7}$$

For AdaP-KLUCB:
$$I_a^\epsilon(t_\ell - 1, \alpha) = \max\left\{ q \in [0,1] : d\left(\breve{\mu}_{a,\epsilon}^{\ell,\alpha}, q\right) \leq \frac{\alpha \log(t_\ell)}{\frac{1}{2} N_a(t_\ell-1)} \right\}, \tag{8}$$

where $\breve{\mu}_{a,\epsilon}^{\ell,\alpha} = \mathrm{Clip}_{0,1}\left(\tilde{\mu}_{a,\epsilon}^\ell + \frac{\alpha \log(t_\ell)}{\epsilon \frac{1}{2} N_a(t_\ell-1)}\right) = \min\{\max\{0, \tilde{\mu}_{a,\epsilon}^\ell + \frac{\alpha \log(t_\ell)}{\epsilon \times \frac{1}{2} N_a(t_\ell-1)}\}, 1\}$ is the private empirical mean clipped between zero and one.

Theorem 7. *For rewards in $[0,1]$,* AdaP-UCB *satisfies ϵ-global DP, and for $\alpha > 3$, it yields a regret*
$$\mathrm{Reg}_T(\text{AdaP-UCB}, \nu) \leq \sum_{a:\Delta_a > 0} \left(\frac{16\alpha}{\min\{\Delta_a, \epsilon\}} \log(T) + \frac{\alpha}{\alpha - 3} \right).$$

Theorem 8. *When the rewards are sampled from Bernoulli distributions,* AdaP-KLUCB *satisfies ϵ-global DP, and for $\alpha > 3$ and constants $C_1(\alpha), C_2 > 0$, it yields a regret*
$$\mathrm{Reg}_T(\text{AdaP-KLUCB}, \nu) \leq \sum_{a:\Delta_a > 0} \left(\frac{C_1(\alpha)\Delta_a}{\min\{d_{\inf}(\mu_a, \mu^*), C_2\epsilon\Delta_a\}} \log(T) + \frac{\alpha}{\alpha - 3} \right).$$

Both the upper bounds show that for low-privacy regime, the regrets of AdaP-UCB and AdaP-KLUCB are independent of ϵ, and in high-privacy regime, they depend on the coupled effect.

Summary of Algorithm Design. We propose three ingredients to design an ϵ-global DP version of a bandit algorithm (Algo. 1). Firstly, add Laplace noise to make the empirical means private (Lemma 1). Secondly, computed the index of an arm using the private empirical mean of rewards collected from the last active episode of that arm and forget all the samples obtained before that. Thirdly, use adaptive episodes with doubling. At the beginning of an episode choose the arm with the highest index and play it double number of times than the length of the last active episode of the arm.

---

[7]For an episode ℓ, $\psi_a(\ell) = \ell_a$ is the last active episode of arm a. In Example 2, $\psi_1(4) = 2$ and $\psi_2(4) = 3$.

Figure 2: Evolution of regret over time for DP-UCB, DP-SE, AdaP-UCB, and AdaP-KLUCB with $\epsilon = 1$. Each algorithm is run 20 times with $T = 10^7$, and Bernoulli distributions with means $\{0.75, 0.625, 0.5, 0.375, 0.25\}$. AdaP-KLUCB achieves the lowest regret.

Figure 3: Dependence of lower bounds and regret of AdaP-KLUCB with respect to the privacy budget ϵ. We run AdaP-KLUCB for 20 runs with $T = 10^7$. Echoing the theoretical analysis, regret of AdaP-KLUCB transits between privacy regimes and is independent of ϵ for low-privacy.

5 Experimental Analysis

In this section, we perform empirical evaluations to test two hypotheses: (i) AdaP-KLUCB is the most optimal algorithm among the existing bandit algorithms with ϵ-global DP, and (ii) the transition between high and low-privacy regimes are reflected in the upper bounds.

Efficiency in Performance. First, we compare performances of AdaP-UCB and AdaP-KLUCB with those of DP-SE and DP-UCB.[8] We set $\alpha = 3.1$ to comply with the regret upper bounds of AdaP-UCB and AdaP-KLUCB. We assign $\gamma = 0.1$ for DP-UCB and $\beta = 1/T$ for DP-SE. We implement all the algorithms in Python (version 3.8) and on an 8 core 64-bits Intel i5@1.6 GHz CPU. We test the algorithms for Bernoulli bandits with 5-arms and means $\{0.75, 0.625, 0.5, 0.375, 0.25\}$ (as in [20]). We run each algorithm 20 times for a horizon $T = 10^7$, and plot corresponding average and standard deviations of regrets in Figure 2. AdaP-KLUCB achieves the lowest regret followed by AdaP-UCB. Both of them attain almost 10 times lower regret than the competing algorithms.

Impact of Privacy Regimes. In Figure 3, we plot regret of AdaP-KLUCB at $T = 10^7$ for a Bernoulli bandit with mean rewards $\{0.8, 0.1, 0.1, 0.1, 0.1\}$. We plot the average regret over 20 runs as a function of the privacy budget ϵ. As indicated by the theoretical regret lower bounds and upper bounds, the experimental performance of AdaP-KLUCB demonstrates two regimes: a high-privacy regime (for $\epsilon < 0.3$), where the regret of AdaP-KLUCB depends on the privacy budget ϵ, and a low privacy regime (for $\epsilon > 0.3$), where the regret of AdaP-KLUCB does not depend on ϵ.

In brief, *our experimental results validate that* AdaP-KLUCB *is the most optimal algorithm for stochastic bandits that satisfies ϵ-global DP, and performance of* AdaP-KLUCB *transits from high- to low-privacy regimes, where its performance turns independent of the privacy budget ϵ.*

6 Conclusion and Future Works

We revisit bandits with ϵ-global DP. We prove the minimax and problem-dependent regret lower bounds for stochastic and linear bandits indicating two regimes of hardness. We propose a framework to design an ϵ-global DP version of an index-based optimistic bandit algorithm in a near-optimal fashion by utilising three ingredients: adding noise with Laplace Mechanism, using the empirical mean of rewards collected in the last active episode of an arm, and adapting episodes with doubling.

One limitation of our analysis that the lower and upper bounds defer by multiplicative constants. It would be a technical challenge to merge this gap. Another future direction is to derive regret lower bounds for other variants of DP, namely (ϵ, δ)-DP and Rényi-DP [17], especially in the structured bandits compatible with Gaussian noise injection, and also to extend the proposed proof techniques in these settings. For the algorithm design, it would be interesting to see how the proposed ingredients generalise to linear and contextual bandits [22], and Markov Decision Processes [27].

---

[8]Source code and additional experimental results are in the Supplementary Material.

References

[1] Jean-Yves Audibert and Sébastien Bubeck. Regret bounds and minimax policies under partial monitoring. *The Journal of Machine Learning Research*, 11:2785–2836, 2010.

[2] Peter Auer, Nicolo Cesa-Bianchi, and Paul Fischer. Finite-time analysis of the multiarmed bandit problem. *Machine learning*, 47(2-3):235–256, 2002.

[3] Debabrota Basu, Christos Dimitrakakis, and Aristide Tossou. Differential privacy for multi-armed bandits: What is it and what is its cost? *arXiv preprint arXiv:1905.12298*, 2019.

[4] T.-H. Hubert Chan, Elaine Shi, and Dawn Song. Private and continual release of statistics. *ACM Trans. Inf. Syst. Secur.*, 14(3), nov 2011. ISSN 1094-9224. doi: 10.1145/2043621.2043626. URL https://doi.org/10.1145/2043621.2043626.

[5] John C Duchi, Michael I Jordan, and Martin J Wainwright. Local privacy, data processing inequalities, and statistical minimax rates. *arXiv preprint arXiv:1302.3203*, 2013.

[6] Cynthia Dwork, Moni Naor, Toniann Pitassi, and Guy N. Rothblum. Differential privacy under continual observation. In *Proceedings of the Forty-Second ACM Symposium on Theory of Computing*, STOC '10, page 715–724, New York, NY, USA, 2010. Association for Computing Machinery. ISBN 9781450300506. doi: 10.1145/1806689.1806787. URL https://doi.org/10.1145/1806689.1806787.

[7] Cynthia Dwork, Moni Naor, Toniann Pitassi, and Guy N Rothblum. Differential privacy under continual observation. In *Proceedings of the forty-second ACM symposium on Theory of computing*, pages 715–724. ACM, 2010.

[8] Cynthia Dwork, Aaron Roth, et al. The algorithmic foundations of differential privacy. *Foundations and Trends® in Theoretical Computer Science*, 9(3–4):211–407, 2014.

[9] Eyal Even-Dar, Shie Mannor, and Yishay Mansour. Pac bounds for multi-armed bandit and markov decision processes. In *Proceedings of the 15th Annual Conference on Computational Learning Theory*, COLT '02, page 255–270, Berlin, Heidelberg, 2002. Springer-Verlag. ISBN 354043836X.

[10] Aurélien Garivier and Olivier Cappé. The kl-ucb algorithm for bounded stochastic bandits and beyond. In *Proceedings of the 24th annual conference on learning theory*, pages 359–376. JMLR Workshop and Conference Proceedings, 2011.

[11] Junya Honda and Akimichi Takemura. Non-asymptotic analysis of a new bandit algorithm for semi-bounded rewards. *J. Mach. Learn. Res.*, 16:3721–3756, 2015.

[12] Bingshan Hu, Zhiming Huang, and Nishant A. Mehta. Optimal algorithms for private online learning in a stochastic environment, 2021. URL https://arxiv.org/abs/2102.07929.

[13] Vishesh Karwa and Salil Vadhan. Finite sample differentially private confidence intervals, 2017. URL https://arxiv.org/abs/1711.03908.

[14] Tze Leung Lai and Herbert Robbins. Asymptotically efficient adaptive allocation rules. *Advances in applied mathematics*, 6(1):4–22, 1985.

[15] Tor Lattimore and Csaba Szepesvari. The end of optimism? an asymptotic analysis of finite-armed linear bandits. In *Artificial Intelligence and Statistics*, pages 728–737. PMLR, 2017.

[16] Tor Lattimore and Csaba Szepesvári. Bandit algorithms. *preprint*, 2018.

[17] Ilya Mironov. Rényi differential privacy. In *2017 IEEE 30th computer security foundations symposium (CSF)*, pages 263–275. IEEE, 2017.

[18] Nikita Mishra and Abhradeep Thakurta. (nearly) optimal differentially private stochastic multi-arm bandits. In *UAI*, 2015.

[19] Seth Neel and Aaron Roth. Mitigating bias in adaptive data gathering via differential privacy. In *International Conference on Machine Learning*, pages 3720–3729. PMLR, 2018.

[20] Touqir Sajed and Or Sheffet. An optimal private stochastic-MAB algorithm based on an optimal private stopping rule, 2019. URL `https://arxiv.org/abs/1905.09383`.

[21] Eric M Schwartz, Eric T Bradlow, and Peter S Fader. Customer acquisition via display advertising using multi-armed bandit experiments. *Marketing Science*, 36(4):500–522, 2017.

[22] Roshan Shariff and Or Sheffet. Differentially private contextual linear bandits. In *Advances in Neural Information Processing Systems*, pages 4296–4306, 2018.

[23] Nícollas Silva, Heitor Werneck, Thiago Silva, Adriano CM Pereira, and Leonardo Rocha. Multi-armed bandits in recommendation systems: A survey of the state-of-the-art and future directions. *Expert Systems with Applications*, 197:116669, 2022.

[24] William R Thompson. On the likelihood that one unknown probability exceeds another in view of the evidence of two samples. *Biometrika*, 25(3-4):285–294, 1933.

[25] Aristide CY Tossou and Christos Dimitrakakis. Algorithms for differentially private multi-armed bandits. In *Thirtieth AAAI Conference on Artificial Intelligence*, 2016.

[26] Aristide CY Tossou and Christos Dimitrakakis. Achieving privacy in the adversarial multi-armed bandit. In *Thirty-First AAAI Conference on Artificial Intelligence*, 2017.

[27] Giuseppe Vietri, Borja Balle, Akshay Krishnamurthy, and Steven Wu. Private reinforcement learning with pac and regret guarantees. In *International Conference on Machine Learning*, pages 9754–9764. PMLR, 2020.

[28] Kai Zheng, Tianle Cai, Weiran Huang, Zhenguo Li, and Liwei Wang. Locally differentially private (contextual) bandits learning, 2020. URL `https://arxiv.org/abs/2006.00701`.