Exploitability Minimization in Games and Beyond

Abstract

Pseudo-games are a natural and well-known generalization of normal-form games, in which the actions taken by each player affect not only the other players' payoffs, as in games, but also the other players' strategy sets. The solution concept par excellence for pseudo-games is the generalized Nash equilibrium (GNE), i.e., a strategy profile at which each player's strategy is feasible and no player can improve their payoffs by unilaterally deviating to another strategy in the strategy set determined by the other players' strategies. The computation of GNE in pseudo-games has long been a problem of interest, due to applications in a wide variety of fields, from environmental protection to logistics to telecommunications. Although the computation of GNE is PPAD-hard in general, it is still of interest to try to compute them in restricted classes of pseudo-games. The literature thus far has focused on asymptotic convergence of search procedures; there are very few, if any, results on the computational complexity of GNE. In this paper, we develop fast exploitability-minimization methods that compute exact or approximate GNE in pseudo-games with jointly convex constraints. We derive convergence guarantees for our methods, and we demonstrate their superiority in experiments over a baseline algorithm for a variety of benchmark pseudo-games.

1 Introduction

Nash equilibrium [1] is the canonical solution concept used to predict the outcome of models of rational agents known as games. A game comprises a set of players, each of whom simultaneously chooses a strategy (or action) from a strategy set, and then receives a payoff based on all the players' choices. A **Nash equilibrium (NE)** is a strategy profile, i.e., a collection of strategies, one per player, from which no player can improve their payoff via a unilateral deviation.

Recently, the literature on NE has expanded beyond classic economic applications to the question of its computation, a problem known as the **Nash equilibrium problem (NEP)** [2, 3]. Unfortunately, it is unlikely that there exists an efficient algorithm to compute NE, as NEP is PPAD-complete, i.e., NEP is equivalent to the problem of computing solutions to a class of fixed-point problems known as PPAD [4], which are believed to be computationally intractable [5, 6, 7]. Nonetheless, there has been a great deal of recent progress developing *efficient* algorithms to compute NE in special classes of games, such as two-player zero-sum [8, 9, 10, 11, 12, 13, 14, 15, 16, 17, 18, 19, 20, 21, 22, 23, 24, 25, 26, 27, 28, 29, 30, 31], potential [32, 33, 34], and monotone (or, more generally, variationally stable) games [35, 36, 37, 38, 39, 40, 41]. Interest in two-player zero-sum games, for example, stems in part from emerging applications in machine learning, e.g., the training of GANs [42, 43].

A natural generalization of games are **pseudo-games**, first introduced by Arrow and Debreu [44] in the context of markets, in which the actions taken by each player affect not only the other players' payoffs, as in games, but also the other players' strategy sets. In other words, players (simultaneously) take actions that can restrict the other players' strategy sets. Such a model is not technically a game, giving rise to the pseudo-game terminology. Pseudo-games generalize

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

games, and hence are even more widely applicable. Some recently studied applications include adversarial classification [45, 46], energy resource allocation [47, 48], environmental protection [49, 50], cloud computing [51, 52], adversarial classification, ride sharing services [53], transportation [54], wireless and network communication [55, 56].

The solution concept par excellence for pseudo-games is the **generalized Nash equilibrium (GNE)** [44, 57, 58], i.e., a strategy profile at which each player's strategy is feasible and no player can improve their payoffs by unilaterally deviating to another strategy in the strategy set determined by the other players' strategies. The **generalized Nash equilibrium problem (GNEP)** generalizes NEP, The aforementioned applications speak to the importance of developing algorithms that can approximate GNEs efficiently in the largest class of pseudo-games possible. Work in this direction is progressing; see, for example, [59, 57, 60, 61, 62, 63, 64, 65, 66, 67, 68, 69, 70, 71, 72, 73, 74, 75, 76, 77]. Nonetheless, there are still few, if any [78], GNE-finding algorithms with guarantees, even for restricted classes of pseudo-games.

Exploitability, or the Nikoida-Isoda potential [79], is defined as the sum of the players' payoff-maximizing unilateral deviations w.r.t. a given strategy profile. Minimizing exploitability is a logical approach, especially in cases where exploitability is convex, such as in the pseudo-games that result from replacing each player's payoff function in a monotone pseudo-game by a second-order Taylor approximation [80]. When the players' payoffs are also Lipschitz-smooth, this approximation can be quite good, because the error in the approximation will be bounded by the Lipschitz-smoothness constant. Minimizing exploitability can thus be an effective way of finding GNEs in pseudo-games; however, to our knowledge, no convergence rates for this approach are known, and few methods have been proposed for pseudo-games whose exploitability is non-convex.

In this paper, we develop efficient exploitability-minimization algorithms that compute GNEs exactly—or approximately, in settings where an exact computation is intractable—in a large class of pseudo-games with jointly convex constraints, which includes, but is not limited to, two-player zero-sum, n-player pairwise zero-sum, and a large class of monotone and bilinear pseudo-games, as well as Cournot oligopoly games. We note that our algorithms also apply to games with continuous action spaces; previous exploitability-minimization algorithms concern only finite games [81, 82].

Our algorithms and their analysis rely on the following key insights: assuming joint constraints, (i.e., symmetric constraint correspondences for all players) the exploitability-minimization problem is equivalent to solving a min-max Stackelberg game, which although non-convex-concave in general can nonetheless be solved by gradient descent ascent (GDA) methods[1] [25, 85] using a parametric variant of Moreau's envelope theorem that we introduce (Theorem 4.1). We apply this logic to develop two algorithms for Lipschitz-smooth pseudo-games with jointly convex constraints. The first (EDA; Algorithm 1) is an extragradient method that converges in average iterates to a GNE in $O(1/\varepsilon)$ iterations, where ε is the exploitability of the game, in pseudo-games with convex-concave cumulative regret (Theorem 3.4). Our second algorithm (ADA; Algorithm 2) is a nested GDA algorithm, whose best iterate converges to a GNE at a slightly slower rate of $O(\log(1/\varepsilon)/\varepsilon)$ in pseudo-games with invex exploitability, i.e., games in which the distance function to the set of GNE is invex, a weaker condition than convex-concave cumulative regret or convex exploitability. Beyond invex exploitability pseudo-games, ADA is also guaranteed to converge to a stationary point of the exploitability at the same rate (Theorem 4.2). *To the best of our knowledge, this makes ours the first exploitability-minimization method with convergence rate guarantees for all Lipschitz-smooth pseudo-games with jointly convex constraints.* Finally, we provide additional conditions under which ADA converges to a GNE in last iterates in $O(\log(1/\varepsilon)^2)$ iterations in strongly-convex exploitability pseudo-games, and in a class of pseudo-games with non-convex exploitability (Theorem 4.3).

Pseudo-games with jointly convex constraints are of interest in decentralized resource allocation problems with feasibility (e.g., supply) constraints. Feasibility constraints are almost always joint, and often also jointly convex. One of the many examples of such pseudo-games is wireless and network communication, where agents communicate packets across a shared network, with limited capacities [55]. The experiments we run in this paper suggest that our algorithms have the potential to yield improved solutions to such pseudo-games as compared to other known approaches, and thus opens up avenues for practical applications of our work in the future.

---

[1] When the objective function is convex-concave, a min-max Stackelberg game reduces to a (simultaneous-move) min-max game, which can be solved using simultaneous-GDA-style algorithms (e.g., [21, 83, 84]).

Related Work Following Arrow and Debreu's introduction of GNE, Rosen [86] initiated the study of the mathematical and computational properties of GNE in pseudo-games with jointly convex constraints, proposing a projected gradient method to compute GNE. Thirty years later, Uryas'ev and Rubinstein [87] developed the first relaxation methods for finding GNEs, which were improved upon in subsequent works [88, 89]. Two other types of algorithms were also introduced to the literature: Newton-style methods [59, 64, 68, 69, 70, 90] and interior-point potential methods [90]. Many of these approaches are based on minimizing the exploitability of the pseudo-game, but others use variational inequality[91, 92] and Lemke methods [93].

More recently, novel methods that transform GNEP to NEP were analyzed. These models take the form of either exact penalization methods, which lift the constraints into the objective function via a penalty term [72, 73, 76, 77, 94], or augmented Lagrangian methods [71, 74, 76, 95], which do the same, augmented by dual Lagrangian variables. Using these methods, Jordan, Lin, and Zampetakis [78] provide the first convergence results to a ε-GNE in monotone (resp. strongly monotone) pseudo-games with jointly affine constraints in $\tilde{O}(1/\varepsilon)$ ($\tilde{O}(1/\sqrt{\varepsilon})$) iterations. These algorithms, despite being highly efficient in theory, are numerically unstable in practice [78]. Nearly all of the aforementioned approaches concerned pseudo-games with jointly convex constraints.

Exploitability minimization has also been a valuable tool in multi-agent reinforcement learning; algorithms in this literature that aim to minimize exploitability are known as exploitability descent algorithms [81]. Lockhart et al. [81] analyzed exploitability descent in two-player, zero-sum, extensive-form games with finite action spaces. More recently, variants of exploitability-descent have been combined with entropic regularization to solve for NE in large games [82].

2 Preliminaries

Notation We use caligraphic uppercase letters to denote sets (e.g., $\mathcal{X}$); bold lowercase letters to denote vectors (e.g., $\boldsymbol{p}, \boldsymbol{\pi}$); bold uppercase letters to denote matrices and vector-valued random variables (e.g., $\boldsymbol{X}, \boldsymbol{\Gamma}$)—which one should be clear from context; lowercase letters to denote scalar quantities (e.g., x, δ); and uppercase letters to denote scalar-valued random variables (e.g., X, Γ). We denote the ith row vector of a matrix (e.g., $\boldsymbol{X}$) by the corresponding bold lowercase letter with subscript i (e.g., $\boldsymbol{x}_i$). Similarly, we denote the jth entry of a vector (e.g., $\boldsymbol{p}$ or $\boldsymbol{x}_i$) by the corresponding Roman lowercase letter with subscript j (e.g., p_j or x_{ij}). We denote functions by a letter determined by the value of the function, e.g., f if the mapping is scalar-valued, $\boldsymbol{f}$ if the mapping is vector-valued, and $\mathcal{F}$ if the mapping is set-valued. We denote the set of integers $\{1, \ldots, n\}$ by $[n]$, the set of natural numbers by $\mathbb{N}$, the set of real numbers by $\mathbb{R}$, and the positive and strictly positive elements of a set by a $+$ and $++$ subscript, respectively, e.g., $\mathbb{R}_+$ and $\mathbb{R}_{++}$. We define the gradient $\nabla_{\boldsymbol{x}} : C^1(\mathcal{X}) \to C^0(\mathcal{X})$ as the operator which takes as input a differentiable functional $f : \mathcal{X} \to \mathbb{R}$, and outputs a vector-valued function consisting of the partial derivatives of f w.r.t. $\boldsymbol{x}$. We denote the orthogonal projection onto a set C by Π_C, i.e., $\Pi_C(\boldsymbol{x}) = \arg\min_{\boldsymbol{y} \in C} \|\boldsymbol{x} - \boldsymbol{y}\|_2^2$.

A **min-max Stackelberg game**, denoted $(\mathcal{X}, \mathcal{Y}, f, \boldsymbol{g})$, is a two-player, zero-sum game, where one player, who we call the $\boldsymbol{x}$-player (resp. the $\boldsymbol{y}$-player), is trying to minimize their loss (resp. maximize their gain), defined by a continuous **objective function** $f : X \times Y \to \mathbb{R}$, by choosing a strategy from a compact **strategy set** $\mathcal{X} \subset \mathbb{R}^n$ (resp. $\mathcal{Y} \subset \mathbb{R}^m$) s.t. $\boldsymbol{g}(\boldsymbol{x}, \boldsymbol{y}) \geq 0$ where $\boldsymbol{g}(\boldsymbol{x}, \boldsymbol{y}) = (g_1(\boldsymbol{x}, \boldsymbol{y}), \ldots, g_d(\boldsymbol{x}, \boldsymbol{y}))^T$ with $g_k : \mathcal{X} \times \mathcal{Y} \to \mathbb{R}$, for all $k \in [d]$. A strategy profile $(\boldsymbol{x}, \boldsymbol{y}) \in \mathcal{X} \times \mathcal{Y}$ is said to be **feasible** iff $g_k(\boldsymbol{x}, \boldsymbol{y}) \geq 0$, for all $k \in [d]$. The function f maps a pair of feasible strategies taken by the players to a real value (i.e., a payoff), which represents the loss (resp. the gain) of the $\boldsymbol{x}$-player (resp. $\boldsymbol{y}$-player). The relevant solution concept for Stackelberg games is the **Stackelberg equilibrium (SE)**. A strategy profile $(\boldsymbol{x}^*, \boldsymbol{y}^*) \in \mathcal{X} \times \mathcal{Y}$ s.t. $\boldsymbol{g}(\boldsymbol{x}^*, \boldsymbol{y}^*) \geq \boldsymbol{0}$ is a **Stackelberg equilibrium** if $\max_{\boldsymbol{y} \in \mathcal{Y}: \boldsymbol{g}(\boldsymbol{x}^*, \boldsymbol{y}) \geq 0} f(\boldsymbol{x}^*, \boldsymbol{y}) \leq f(\boldsymbol{x}^*, \boldsymbol{y}^*) \leq \min_{\boldsymbol{x} \in \mathcal{X}} \max_{\boldsymbol{y} \in \mathcal{Y}: \boldsymbol{g}(\boldsymbol{x}, \boldsymbol{y}) \geq 0} f(\boldsymbol{x}, \boldsymbol{y})$.

A **pseudo-game** [44] $\mathcal{G} \doteq (n, \mathcal{A}, \mathcal{X}, \boldsymbol{h}, \boldsymbol{u})$ comprises $n \in \mathbb{N}_+$ players, each $i \in [n]$ of whom chooses an $\boldsymbol{a}_i$ from an action space $\mathcal{A}_i$. We denote the players' joint action space by $\mathcal{A} = \bigtimes_{i \in [n]} \mathcal{A}_i$. Each player i' aims to maximize their continuous utility $u_i : \mathcal{A} \to \mathbb{R}$, which is concave in $\boldsymbol{a}_i$, by choosing a feasible action from a set of actions $\mathcal{X}_i(\boldsymbol{a}_{-i}) \subseteq \mathcal{A}_i$ determined by the actions $\boldsymbol{a}_{-i} \in \mathcal{A}_{-i} \subset \mathbb{R}^m$ of the other players, where $\mathcal{X}_i : \mathcal{A}_{-i} \rightrightarrows \mathcal{A}_i$ is a non-empty, continuous, compact- and convex-valued action correspondence, which for convenience we represent as $\mathcal{X}_i(\boldsymbol{a}_{-i}) = \{\boldsymbol{a}_i \in \mathcal{A}_i \mid h_{ik}(\boldsymbol{a}_i, \boldsymbol{a}_{-i}) \geq \boldsymbol{0}, \text{ for all } k \in [d]\}$, where for all $i \in [n]$, and $k \in [d]$, h_{ik} is a continuous and

concave function in $\boldsymbol{a}_i$, which defines the constraints. We denote the product of the feasible action correspondences of all players by $\mathcal{X}(\boldsymbol{a}) = \bigtimes_{i \in [n]} \mathcal{X}_i(\boldsymbol{a}_{-i})$, which we note is guaranteed to be non-empty, continuous, and compact-valued, but not necessarily convex-valued. A pseudo-game is said to be **monotone** if for all $\boldsymbol{a}, \boldsymbol{b} \in \mathcal{A} \sum_{i \in [n]} \left(\nabla_{\boldsymbol{a}_i} u_i(\boldsymbol{a}) - \nabla_{\boldsymbol{a}_i} u_i(\boldsymbol{b}) \right)^T (\boldsymbol{a} - \boldsymbol{b}) \leq 0$. A pseudo-game is said to have **joint constraints** if there exists a function $\boldsymbol{g} : \mathcal{A} \to \mathbb{R}^d$ s.t. $\boldsymbol{g} = \boldsymbol{h}_1 = \ldots = \boldsymbol{h}_d$, in which case the joint action correspondence is simply a set, i.e., $\mathcal{X} = \{\boldsymbol{a} \in \mathcal{A} \mid \boldsymbol{g}(\boldsymbol{a}) \geq \boldsymbol{0}\}$. If additionally, for all $k \in [d]$, $g_k(\boldsymbol{a})$ is convex in $\boldsymbol{a}$, then we say that the pseudo-game has **jointly convex constraints**, which implies that $\mathcal{X}$ is a convex set. A **game** [1] is a pseudo-game where, for all players $i \in [n]$, $\mathcal{X}_i$ is a constant correspondence, i.e., a set, in particular, $\mathcal{A}_i$.

Given a pseudo-game $\mathcal{G}$, an ε-**generalized Nash equilibrium (GNE)** is a strategy profile $\boldsymbol{a}^* \in \mathcal{X}(\boldsymbol{a}^*)$ s.t. for all $i \in [n]$ and $\boldsymbol{a}_i \in \mathcal{X}_i(\boldsymbol{a}^*_{-i})$, $u_i(\boldsymbol{a}^*) \geq u_i(\boldsymbol{a}_i, \boldsymbol{a}^*_{-i}) - \varepsilon$. An ε-**variational equilibrium (VE)** (or **normalized GNE**) of a pseudo-game *with joint constraints* is a strategy profile $\boldsymbol{a}^* \in \mathcal{X}$ s.t. for all $i \in [n]$ and $\boldsymbol{a} \in \mathcal{X}$, $u_i(\boldsymbol{a}^*) \geq u_i(\boldsymbol{a}_i, \boldsymbol{a}^*_{-i}) - \varepsilon$. A GNE (VE) is an ε-GNE (VE) with $\varepsilon = 0$. Note that the set of ε-VE of a pseudo-game with joint constraints is a subset of the set of the ε-GNE, as $\mathcal{X}(\boldsymbol{a}^*) \subseteq \mathcal{X}$. The converse, however, is not true, unless $\mathcal{A} \subseteq \mathcal{X}$. Indeed, when $\mathcal{G}$ is a game, the GNE and VE coincide; we refer to this set simply as NE.

Mathematical Preliminaries Finally, we define several mathematical concepts that are relevant to our convergence proofs. Given $A \subset \mathbb{R}^n$, the function $f : \mathcal{A} \to \mathbb{R}$ is said to be ℓ_f-**Lipschitz-continuous** iff $\forall \boldsymbol{x}_1, \boldsymbol{x}_2 \in \mathcal{X}, \|f(\boldsymbol{x}_1) - f(\boldsymbol{x}_2)\| \leq \ell_f \|\boldsymbol{x}_1 - \boldsymbol{x}_2\|$. If the gradient of f is $\ell_{\nabla f}$-Lipschitz-continuous, we then refer to f as $\ell_{\nabla f}$-**Lipschitz-smooth**. A function $f : \mathcal{X} \to \mathbb{R}$ is said to be **invex** w.r.t. a function $\boldsymbol{h} : \mathcal{X} \times \mathcal{X} \to \mathcal{X}$ if $f(\boldsymbol{x}) - f(\boldsymbol{y}) \geq \boldsymbol{h}(\boldsymbol{x}, \boldsymbol{y}) \cdot \nabla f(\boldsymbol{y})$, for all $\boldsymbol{x}, \boldsymbol{y} \in \mathcal{X}$. A function $f : \mathcal{X} \to \mathbb{R}$ is **convex** if it is invex w.r.t. $\boldsymbol{h}(\boldsymbol{x}, \boldsymbol{y}) = \boldsymbol{x} - \boldsymbol{y}$ and concave if $-f$ is convex. A function $f : \mathcal{X} \to \mathbb{R}$ is μ-**strongly convex (SC)** if $f(\boldsymbol{x}_1) \geq f(\boldsymbol{x}_2) + \langle \nabla_{\boldsymbol{x}} f(\boldsymbol{x}_2), \boldsymbol{x}_1 - \boldsymbol{x}_2 \rangle + \mu/2 \|\boldsymbol{x}_1 - \boldsymbol{x}_1\|^2$, and μ-**strongly concave** if $-f$ is μ-strongly convex.

3 From Exploitability Minimization To Min-Max Games

Given a pseudo-game $\mathcal{G}$, we define the **regret** felt by any player $i \in [n]$ for an action $\boldsymbol{a}_i$ as compared to another action $\boldsymbol{b}_i$, given the action profile $\boldsymbol{a}_{-i}$ of other players, as follows: $\text{Regret}_i(\boldsymbol{a}_i, \boldsymbol{b}_i; \boldsymbol{a}_{-i}) = u_i(\boldsymbol{b}_i, \boldsymbol{a}_{-i}) - u_i(\boldsymbol{a}_i, \boldsymbol{a}_{-i})$. Additionally, the **cumulative regret**, or the **Nikaida-Isoda function**, $\psi : \mathcal{A} \times \mathcal{A} \to \mathbb{R}$ between two action profiles $\boldsymbol{a} \in \mathcal{X}$ and $\boldsymbol{b} \in \mathcal{X}$ across all players in a pseudo-game is given by $\psi(\boldsymbol{b}; \boldsymbol{a}) = \sum_{i \in [n]} \text{Regret}_i(\boldsymbol{a}_i, \boldsymbol{b}_i; \boldsymbol{a}_{-i})$. Further, the **exploitability**, or **Nikaido-Isoda *potential* function**, $\varphi : \mathcal{A} \to \mathbb{R}$ of an action profile $\boldsymbol{a}$ is defined as $\varphi(\boldsymbol{a}) = \sum_{i \in [n]} \max_{\boldsymbol{b}_i \in \mathcal{X}_i(\boldsymbol{a}_{-i})} \text{Regret}_i(\boldsymbol{a}_i, \boldsymbol{b}_i; \boldsymbol{a}_{-i})$ [57]. Notice that the max is taken over $\mathcal{X}_i(\boldsymbol{a}_{-i})$, since a player can only deviate within the set of available strategies.

Observation 3.1 ([57]). *Given a pseudo-game $\mathcal{G}$, for all $\boldsymbol{a} \in \mathcal{A}$, $\varphi(\boldsymbol{a}) = \max_{\boldsymbol{b} \in \mathcal{X}(\boldsymbol{a})} \psi(\boldsymbol{a}, \boldsymbol{b})$.*

Proof. The per-player maximum operators can be pulled out of the sum, as the ith player's best action in hindsight is independent of the other players' best actions in hindsight, since the action profile $\boldsymbol{a}$ is fixed. That is, the optimization problem in the ith summand is independent of the optimization problem in the other summands, e.g., for any $\boldsymbol{y} \in [0, 1/2]^2$, $\max_{x_1 \in [0,1]: x_1 - y_1 \geq 0} \{x_1 y_1\} + \max_{x_2 \in [0,1]: x_2 - y_2 \geq 0} \{x_2 y_2\} = \max_{\boldsymbol{x} \in [0,1]^2 : \boldsymbol{x} - \boldsymbol{y} \geq \boldsymbol{0}} x_1 y_1 + x_2 y_2$. $\square$

$$\varphi(\boldsymbol{a}) = \sum_{i \in [n]} \max_{\boldsymbol{b}_i \in \mathcal{X}_i(\boldsymbol{a}_{-i})} \text{Regret}_i(\boldsymbol{a}_i, \boldsymbol{b}_i; \boldsymbol{a}_{-i}) = \max_{\boldsymbol{b} \in \mathcal{X}(\boldsymbol{a})} \sum_{i \in [n]} \text{Regret}_i(\boldsymbol{a}_i, \boldsymbol{b}_i; \boldsymbol{a}_{-i}) = \max_{\boldsymbol{b} \in \mathcal{X}(\boldsymbol{a})} \psi(\boldsymbol{b}; \boldsymbol{a})$$

A well-known [57][2] result is that any unexploitable strategy profile in a pseudo-game is a GNE.

Lemma 3.2. *Given a pseudo-game $\mathcal{G}$, for all $\boldsymbol{a} \in \mathcal{A}$, $\varphi(\boldsymbol{a}) \geq 0$. Additionally, a strategy profile $\boldsymbol{a}^* \in \mathcal{X}(\boldsymbol{a}^*)$ is a GNE iff it achieves the lowerbound, i.e., $\varphi(\boldsymbol{a}^*) = 0$.*

This lemma tells us that we can reformulate GNEP as the quasi-optimization problem of minimizing exploitability, i.e., $\min_{\boldsymbol{a} \in \mathcal{X}(\boldsymbol{a})} \varphi(\boldsymbol{a})$. Here, "quasi" refers to the fact that a solution to this problem

---

[2]yet hard to exploit(!)

is both a minimizer of φ *and* a fixed point $\boldsymbol{a}^*$ s.t. $\boldsymbol{a}^* \in \mathcal{X}(\boldsymbol{a}^*)$. Despite this reformulation of GNEP in terms of exploitability, no exploitability-minimization algorithms with convergence rate guarantees are known. The unexploitability(!) of exploitability may be due to the fact that it is not Lipschitz-smooth, which makes it difficult to derive convergence bounds.

The key insight that allows us to obtain convergence guarantees for our algorithms is that we treat the GNE problem not as a quasi-minimization problem, but rather as a quasi-min-max optimization problem, as $\min_{\boldsymbol{a} \in \mathcal{X}(\boldsymbol{a})} \varphi(\boldsymbol{a}) = \min_{\boldsymbol{a} \in \mathcal{X}(\boldsymbol{a})} \max_{\boldsymbol{b} \in \mathcal{X}(\boldsymbol{a})} \psi(\boldsymbol{a}, \boldsymbol{b})$. In pseudo-games with joint constraints, this quasi-min-max optimization problem reduces to a standard min-max optimization problem, namely $\min_{\boldsymbol{a} \in \mathcal{X}} \max_{\boldsymbol{b} \in \mathcal{X}} \psi(\boldsymbol{a}, \boldsymbol{b})$, which characterizes the VEs, a subset of the GNEs [65]. This problem is well understood in games with convex-concave objective functions [21, 83, 84, 96]. Furthermore, the cumulative regret ψ is indeed convex-concave, i.e., convex in $\boldsymbol{a}$ and concave in $\boldsymbol{b}$, in many pseudo-games of interest: e.g., two-player zero-sum, n-player pairwise zero-sum, and a large class of monotone and bilinear pseudo-games, as well as Cournot oligopoly games.

Going forward, we will restrict our attention to pseudo-games satisfying the following assumptions. Lipschitz-smoothness is a standard assumption in the convex optimization literature [97], and joint convexity is a standard assumption in the GNE literature [57]. Furthermore, these are weaker assumptions than ones made to obtain the few known results on convergence rates to GNEs [78].

Assumption 3.3. *The pseudo-game $\mathcal{G}$ has joint constraints $\boldsymbol{g} : \mathcal{A} \to \mathbb{R}^d$, and additionally, 1. (Lipschitz smoothness and concavity) for any player $i \in [n]$, their payoff u_i is $\ell_{\nabla_{\boldsymbol{u}}}$-Lipschitz smooth and concave in $\boldsymbol{a}_i$; 2. (Joint Convexity) $\boldsymbol{g}$ is component-wise concave.*

Using the simple observation that every GNE in a pseudo-game (with joint constraints) is the solution to a min-max optimization problem, we introduce our first algorithm (EDA; Algorithm 1), an extragradient method [83]. The algorithm works by interleaving extragradient ascent and descent steps: at iteration t, given $\boldsymbol{a}^{(t)}$, it ascends on $\psi(\boldsymbol{a}^{(t)}, \cdot)$, thereby generating a better response $\boldsymbol{b}^{(t+1)}$, and then descends on $\psi(\cdot, \boldsymbol{b}^{(t+1)})$, thereby decreasing exploitability.

Algorithm 1 Extragradient descent ascent (EDA)

Inputs: $n, \boldsymbol{u}, \mathcal{X}, \boldsymbol{\eta}, T, \boldsymbol{a}^{(0)}, \boldsymbol{b}^{(0)}$
Outputs: $(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)})_{t=0}^T$
  1: **for** $t = 0, \ldots, T_{\boldsymbol{a}} - 1$ **do**
  2:      $\boldsymbol{a}^{(t+1/2)} = \Pi_{\mathcal{X}} \left[\boldsymbol{a}^{(t)} - \eta \nabla_{\boldsymbol{a}} \psi(\boldsymbol{b}^{(t)}; \boldsymbol{a}^{(t)}) \right]$
  3:      $\boldsymbol{b}^{(t+1/2)} = \Pi_{\mathcal{X}} \left[\boldsymbol{b}^{(t)} + \eta \nabla_{\boldsymbol{b}} \psi(\boldsymbol{b}^{(t)}; \boldsymbol{a}^{(t)}) \right]$
  4:      $\boldsymbol{a}^{(t+1)} = \Pi_{\mathcal{X}} \left[\boldsymbol{a}^{(t)} - \eta \nabla_{\boldsymbol{a}} \psi(\boldsymbol{b}^{(t+1/2)}; \boldsymbol{a}^{(t+1/2)}) \right]$
  5:      $\boldsymbol{b}^{(t+1)} = \Pi_{\mathcal{X}} \left[\boldsymbol{b}^{(t)} + \eta \nabla_{\boldsymbol{b}} \psi(\boldsymbol{b}^{(t+1/2)}; \boldsymbol{a}^{(t+1/2)}) \right]$
  6: **return** $(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)})_{t=0}^T$

We combine several known results about the convergence of extragradient descent methods in min-max optimization problems to obtain the following convergence guarantees for EDA in pseudo-games. We note that the iteration complexity we derive is optimal: i.e., it is a tight upper bound, since the complexity of two-player zero-sum convex-concave games, a special case of our model, is $\Omega(1/\varepsilon)$. We also note that if the players' payoff functions have Lipschitz-continuous third-order derivatives, then convergence in last iterates can be obtained in $O(1/\varepsilon^2)$ iterations [98].[3]

Theorem 3.4 (Convergence rate of EDA)**.** *Consider a pseudo-game $\mathcal{G}$ with convex-concave cumulative regret that satisfies Assumption 3.3. Suppose that EDA (Algorithm 1) is run with $\eta < 1/\ell_{\nabla_\psi}$, and that doing so generates the sequence of iterates $(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)})_{t=0}^T$. Let $\overline{\boldsymbol{a}^{(T)}} = 1/T \sum_{t=1}^T \boldsymbol{a}^{(t)}$ and $\overline{\boldsymbol{b}^{(T)}} = 1/T \sum_{t=1}^T \boldsymbol{b}^{(t)}$. Then the following convergence rate to a GNE, i.e., to zero exploitability holds: $\max_{\boldsymbol{b} \in \mathcal{X}} \psi(\overline{\boldsymbol{a}^{(T)}}, \boldsymbol{b}) - \max_{\boldsymbol{a} \in \mathcal{X}} \psi(\boldsymbol{a}, \overline{\boldsymbol{b}^{(T)}}) \leq 1/T (d\ell_{\nabla_\psi})$, where $d = \max_{(\boldsymbol{a}, \boldsymbol{b}) \in \mathcal{X} \times \mathcal{X}} \left\| (\boldsymbol{a}, \boldsymbol{b}) - (\boldsymbol{a}^{(0)}, \boldsymbol{b}^{(0)}) \right\|_2^2$. If, additionally, ψ is μ-strongly-convex-μ-strongly-*

---

[3] All ommited proofs can be found in Appendix B.

concave, and the learning rate $\eta = 1/4\ell_\psi$, *then the following convergence bound also holds:*
$\max_{\boldsymbol{b} \in \mathcal{X}} \psi(\overline{\boldsymbol{a}^{(T)}}, \boldsymbol{b}) - \max_{\boldsymbol{a} \in \mathcal{X}} \psi(\boldsymbol{a}, \overline{\boldsymbol{b}^{(T)}}) \leq d\mu\ell_\psi (1 - 1/4\mu)^T$.

4 Pseudo-Games with Jointly Convex Constraints

More generally, cumulative regret can be a non-convex-concave function, in which case a minimax theorem does not hold, which precludes the existence of a NE. In such cases, min-max optimization problems are best seen as Stackelberg (i.e., sequential) games, with Stackelberg equilibria as their solutions, since the order of the minimum and the maximum operators matters. Although existence is guaranteed,[4] computing Stackelberg equilibria in non-convex-concave settings is NP-hard in general [99], so we instead set as our goal finding a stationary point $\boldsymbol{a}^* \in \mathcal{X}$ of the exploitability φ. Any stationary point $\boldsymbol{a}^*$ of the exploitability is a $\varphi(\boldsymbol{a}^*)$-VE of the associated pseudo-game.

In recent years, a variety of methods have been developed that could be applied to finding stationary points of the exploitability [19, 25, 26, 27, 31]. Using the most efficient of these methods, one could obtain convergence to an ε-stationary point of the exploitability in $O(1/\varepsilon^6)$ iterations [19]. However, as we will see, this rate would be very slow, and the convergence metric, not very strong, e.g., convergence in expected iterates. Instead, we demonstrate how to leverage the structure of the exploitability-minimization problem to obtain much faster convergence rates.

Unfortunately, the exploitability associated with the min-max Stackelberg game characterization of pseudo-games with joint constraints is not differentiable in general. This fact poses an obstacle when trying to design efficient algorithms that find its stationary points. However, by exploiting the structure of cumulative regret, we can regularize it to obtain a smooth objective. Observe the following: if $\boldsymbol{a}^* \in \arg\min_{\boldsymbol{a} \in \mathcal{X}} \max_{\boldsymbol{b} \in \mathcal{X}} \psi(\boldsymbol{a}, \boldsymbol{b})$, then $\boldsymbol{a}^* \in \arg\max_{\boldsymbol{b} \in \mathcal{X}} \psi(\boldsymbol{a}^*, \boldsymbol{b})$. We thus optimize the α-**regularized cumulative regret** $\psi_\alpha : \mathcal{A} \times \mathcal{A} \to \mathbb{R}$, defined as $\psi_\alpha(\boldsymbol{a}, \boldsymbol{b}) \doteq \psi(\boldsymbol{a}, \boldsymbol{b}) - \frac{\alpha}{2} \|\boldsymbol{a} - \boldsymbol{b}\|_2^2$, whose associated α-**regularized exploitability** $\varphi_\alpha : \mathcal{A} \to \mathbb{R}$ is given by $\varphi_\alpha(\boldsymbol{a}) = \max_{\boldsymbol{b} \in \mathcal{X}} \psi_\alpha(\boldsymbol{a}, \boldsymbol{b})$. Intuitively, since $\boldsymbol{b}^* = \boldsymbol{a}$ is a solution to the inner maximization problem, this regularized exploitability is still minimized at a VE. In fact, Von Heusinger and Kanzow [65] show that a strategy profile $\boldsymbol{a}^*$ has no α-regularized-exploitability, i.e., $\varphi_\alpha(\boldsymbol{a}^*) = 0$, iff $\boldsymbol{a}^*$ is a VE; and for all $\alpha > 0$ and $\boldsymbol{a} \in \mathcal{A}$, φ_α is a singleton-valued correspondence (Theorem 3.3 [65]).

The **parametric Moreau envelope** is a Moreau envelope [100] in which the objective function is a function of the point w.r.t. which we regularize the objective function, which in our case is cumulative regret. Our next theorem is a generalization of the Moreau envelope theorem [100], which shows that α-regularized exploitability is Lipschitz smooth, by allowing us to see φ_α as a parametric Moreau envelope for ψ, an observation which to our knowledge has not been made in previous work. This Lipschitz-smoothness of φ_α gives rise to the possibility of deriving algorithms that converge to a stationary point of φ_α, the key idea underlying our algorithm (ADA; Algorithm 2).

Theorem 4.1 (Parameteric Moreau Envelope Theorem). *Given* $\alpha > 0$, *consider the parametric Moreau envelope* $\varphi_\alpha(\boldsymbol{a}) \doteq \max_{\boldsymbol{b} \in \mathcal{X}} \psi(\boldsymbol{a}, \boldsymbol{b}) - \frac{\alpha}{2} \|\boldsymbol{a} - \boldsymbol{b}\|_2^2$ *and the associated proximal operator* $\{\boldsymbol{b}^*(\boldsymbol{a})\} \doteq \arg\max_{\boldsymbol{b} \in \mathcal{X}} \varphi_\alpha(\boldsymbol{a})$, *where* ψ *is* $\ell_{\nabla\psi}$-*Lipschitz smooth. Then* $\psi_\alpha(\boldsymbol{a})$ *is* $\left(\ell_{\nabla\psi} + \frac{\ell_{\nabla\psi}^2}{\alpha}\right)$-*Lipschitz-smooth, with gradients given by* $\nabla_{\boldsymbol{a}}\varphi_\alpha(\boldsymbol{a}) = \nabla_{\boldsymbol{a}}\psi_\alpha(\boldsymbol{a}, \boldsymbol{b}^*(\boldsymbol{a})) - \alpha(\boldsymbol{a} - \boldsymbol{b}^*(\boldsymbol{a}))$.

Next, let us clarify the definition of a stationary point. As the exploitability φ_α is in general non-convex, and the optimization problem $\min_{\boldsymbol{a} \in \mathcal{X}} \varphi_\alpha(\boldsymbol{a})$ is constrained, the first-order condition $\nabla\varphi_\alpha(\boldsymbol{a}) = 0$ is not sufficient for stationarity, since a solution on the boundary of the constraint set could also be first-order stationary. As a result, we use proximal mappings in our definition. In particular, we reformulate the constrained exploitability minimization problem as the unconstrained minimization problem $\min_{\boldsymbol{a} \in \mathbb{R}^{nm}} \varphi_\alpha(\boldsymbol{a}) + \mathbb{1}_\mathcal{X}(\boldsymbol{a})$. Here $\mathbb{1}_\mathcal{X}(\boldsymbol{a})$ is the indicator function of the set $\mathcal{X}$, i.e., $\mathbb{1}_\mathcal{X}(\boldsymbol{x}) = 0$ if $\boldsymbol{x} \in \mathcal{X}$ and $\mathbb{1}_\mathcal{X}(\boldsymbol{x}) = \infty$ if $\boldsymbol{x} \notin \mathcal{X}$. In this optimization problem, φ_α is continuous and Lipschitz smooth, while $\mathbb{1}_\mathcal{X}$ is continuous and convex. Additionally, the set of solutions is non-empty. As a result, one can solve this problem using the proximal gradient method, which, in this case, is exactly equivalent to the projected gradient method [97, 101]. This view of the problem as a proximal method allows us to provide a clear definition of a first-order equilibrium. Define

---

[4] We note that solution concepts such as first-order NE [25] are incompatible with our approach, as a first-order NE does not correspond to a stationary point of exploitability.

the **projected gradient operator** of φ_α as follows: $G^{\varphi_\alpha}_{\eta_a}(\boldsymbol{a}) = \boldsymbol{a} - \Pi_\mathcal{X}\left[\boldsymbol{a} - \eta_{\boldsymbol{a}}\nabla\varphi_\alpha(\boldsymbol{a})\right]$. The projected gradient operator is a special case of the gradient mapping operator, and a generalization of the gradient that is projected back onto the feasible set $\mathcal{X}$ [101]. The zeros of the projected gradient operator capture stationary points both at the boundary of the set $\mathcal{X}$ and in its interior. Indeed, $\boldsymbol{a} \in \mathcal{A}$ is a **stationary** point of φ_α if $G^{\varphi_\alpha}_{\eta_a}(\boldsymbol{a}) = \boldsymbol{0}$. Finally, for an action profile $\boldsymbol{a}^* \in \mathcal{A}$ to be a VE, it is necessary that it is stationary (Proposition 3, [80]). Our goal will thus be to achieve convergence to a strategy profile $\boldsymbol{a} \in \mathcal{X}$ s.t. $G^{\varphi_\alpha}_{\eta_a}(\boldsymbol{a}) = 0$.

ADA (Algorithm 2) is a nested GDA algorithm, similar to those of [25] and [85], with the objective function augmented by a smart regularizer. The algorithm works much like EDA, interleaving extragradient ascent and descent steps. The key difference is that whereas EDA runs only a single step of extragradient ascent (to find a better response), ADA runs multiple steps of extragradient ascent to approximate a best response. Indeed, as Theorem 4.2 shows, the ADA's accuracy depends on the accuracy of the best-response found.

Algorithm 2 Augmented Descent Ascent (ADA)

Inputs: $n, \boldsymbol{u}, \boldsymbol{g}, \alpha, \eta_{\boldsymbol{a}}, \eta_{\boldsymbol{b}}, T_{\boldsymbol{a}}, T_{\boldsymbol{b}}, \boldsymbol{a}^{(0)}, \boldsymbol{b}^{(0)}$

Outputs: $(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)})_{t=0}^{T_{\boldsymbol{a}}}$

1: **for** $t = 0, \ldots, T_{\boldsymbol{a}} - 1$ **do**
2:     **for** $i \in [n]$ **do**
3:         $\boldsymbol{a}^{(t+1)} = \Pi_\mathcal{X}\left[\boldsymbol{a}^{(t)} - \eta_{\boldsymbol{a}}\left(\nabla_{\boldsymbol{a}}\psi(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)}) - \alpha(\boldsymbol{a}^{(t)} - \boldsymbol{b}^{(t)}))\right]$
4:     $\boldsymbol{b} = \boldsymbol{0}$
5:     **for** $s = 0, \ldots, T_{\boldsymbol{b}} - 1$ **do**
6:         **for** $i \in [n]$ **do**
7:             $\boldsymbol{b}_i = \Pi_\mathcal{X}\left[\boldsymbol{b} + \eta_{\boldsymbol{b}}\left(\nabla_{\boldsymbol{b}}\psi(\boldsymbol{a}^{(t+1)}, \boldsymbol{b}) - \alpha(\boldsymbol{a}^{(t+1)} - \boldsymbol{b}))\right]$
8:     $\boldsymbol{b}^{(t+1)} = \boldsymbol{b}$
9: **return** $(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)})_{t=0}^{T_{\boldsymbol{a}}}$

To derive convergence rates for ADA, we rely on two technical lemmas. The first tells us that the inner loop can approximate the gradient of the exploitability to any desired precision. More specifically, we bound the error $\left\|\nabla_{\boldsymbol{a}}\varphi_\alpha(\boldsymbol{a}^{(t)}) - \nabla_{\boldsymbol{a}}\psi(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)})\right\| \leq \varepsilon$, for a desired ε and for some number of total inner loop iterations $T_{\boldsymbol{b}}$, for all outer loop iterations $t \in [T_{\boldsymbol{a}}]$. The second lemma bounds the algorithm's progress at each iteration of the outer loop, which we achieve by relating ε and $G^{\varphi_\alpha}_{\eta_a}(\boldsymbol{a}_t)$. Finally, by telescoping the inequalities in the progress lemma, we obtain our main theorem: The best iterate found by ADA, as measured by the norm of the projected gradient operator, converges to a stationary point of the exploitability in all Lipschitz-smooth pseudo-games with jointly convex constraints.

Theorem 4.2 (Convergence to Stationary Point of Exploitability). *Suppose that ADA is run on a pseudo-game $\mathcal{G}$ which satisfies Assumption 3.3 with learning rates $\eta_{\boldsymbol{a}} > \frac{\ell_{\nabla\psi_\alpha} + \frac{\ell_{\nabla\psi_\alpha}^2}{\alpha}}{2}$ and $\eta_{\boldsymbol{b}} = \frac{1}{\ell_{\psi_\alpha}}$, for any number of outer loop iterations $T_{\boldsymbol{a}} \in \mathbb{N}_{++}$ and for $T_{\boldsymbol{b}} \geq \frac{\log\left(\frac{\varepsilon}{\ell_{\nabla\psi_\alpha}}\sqrt{\frac{2\alpha}{c}}\right)}{\log\left(\frac{\alpha}{\ell_{\nabla\psi_\alpha}}\right)}$ total inner loop iterations. Then the outputs $(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)})_{t=0}^{T}$ satisfy $\min_{t=1,\ldots,T_{\boldsymbol{a}}}\left\|G^{\varphi}_{\eta_a}(\boldsymbol{a}^{(t)})\right\|_2^2 \leq$*

$$\left(\frac{\ell_{\nabla\psi_\alpha} + \frac{\ell_{\nabla\psi_\alpha}^2}{\alpha}}{2} - \eta_{\boldsymbol{a}}\right)\frac{\varphi(\boldsymbol{a}^{(0)}) - \varphi(\boldsymbol{a}^{(T_{\boldsymbol{a}})})}{T_{\boldsymbol{a}}} + \varepsilon\left(\ell_{\nabla\psi_\alpha} + \frac{\ell_{\nabla\psi_\alpha}^2}{\alpha}\right).$$

Note that the stationary points to which ADA converges are global minima of φ_α iff φ_α is invex, in which case ADA converges to a VE, and hence a GNE [102]. We can also obtain faster and last iterate convergence to VE in a more restricted class of games. A pseudo-game is said to be a μ-**PL-pseudo-game** if the regularized exploitability φ_α satisfies the μ-**projection-Polyak-Lojasiewicz (PL)** condition, i.e., the projected gradient operator associated with φ_α satisfies

$\frac{1}{2} \left\| G^{\varphi_\alpha}_{\eta_a}(\boldsymbol{a}) \right\|_2^2 \geq \mu \left(\varphi_\alpha(\boldsymbol{a}) - \min_{\boldsymbol{a} \in \mathcal{X}} \varphi_\alpha(\boldsymbol{a}) \right)$ for all $\boldsymbol{a} \in \mathcal{X}$.[5] A similar PL-condition for games was recently used by Raghunathan, Cherian, and Jha [104], which they argued is natural.

Theorem 4.3 (PL Exploitability Convergence). *Suppose ADA is run on a PL-pseudo-game $\mathcal{G}$ which satisfies Assumption 3.3 with learning rates $\eta_{\boldsymbol{a}} \in \left[\ell_{\nabla \psi_\alpha} + \frac{\ell^2_{\nabla \psi_\alpha}}{\alpha} - \mu, \ell_{\nabla \psi_\alpha} + \frac{\ell^2_{\nabla \psi_\alpha}}{\alpha} \right] \frac{1}{\ell_{\nabla \psi_\alpha} + \frac{\ell^2_{\nabla \psi_\alpha}}{\alpha}}$ and $\eta_{\boldsymbol{b}} = 1/\ell_{\nabla \psi_\alpha}$, for any number of outer loop iterations $T_{\boldsymbol{a}} \in \mathbb{N}_{++}$ and for $T_{\boldsymbol{b}} \geq \frac{\log\left(\frac{\varepsilon}{\nabla \psi_\alpha} \sqrt{\frac{2\alpha}{c}} \right)}{\log\left(\frac{\alpha}{\nabla \psi_\alpha} \right)}$ total inner loop iterations. Then the outputs $(\boldsymbol{a}^{(t)}, \boldsymbol{b}^{(t)})_{t=0}^T$ sat-isfy $v(\boldsymbol{a}^{(T_{\boldsymbol{a}})}) \leq \left[1 - \mu \left(\frac{\ell_{\nabla \psi_\alpha} + \frac{\ell^2_{\nabla \psi_\alpha}}{\alpha}}{2} - \eta_{\boldsymbol{a}} \right) \right]^{T_{\boldsymbol{a}}} \varphi_\alpha(\boldsymbol{a}^{(0)}) + \varepsilon \left(\ell_{\nabla \psi_\alpha} + \frac{\ell^2_{\nabla \psi_\alpha}}{\alpha} \right)$. Additionally, $\lim_{T_{\boldsymbol{a}} \to \infty} v(\boldsymbol{a}^{(T_{\boldsymbol{a}})}) = \varepsilon \left(\ell_{\nabla \psi_\alpha} + \frac{\ell^2_{\nabla \psi_\alpha}}{\alpha} \right)$.*

We note that this result also implies convergence to a VE in strongly-convex exploitability games in linear time as well, since strong convexity implies the PL-condition.

5 Experiments

In this section, we report on experiments that demonstrate the effectiveness of our algorithms as compared to others that were also designed to compute GNE. We present numerical results on benchmark psuedo-games that were studied empirically in previous work [104]: 1) monotone games with affine constraints and 2) bilinear games with jointly convex constraints.[6] We compare our algorithms to the **accelerated mirror-prox quadratic penalty method** (AMPQP), the only GNE-finding algorithm with theoretical convergence guarantees *and rates* [78].[7] For the AMPQP algorithm, we use the hyperparameter settings derived in theory when available, and otherwise conduct a grid search for the best ones. We compare the convergence rates of our algorithms to that of AMPQP, which converges at the same rate as EDA, but slower than ADA, in settings in which it is guaranteed to converge, i.e., in monotone pseudo-games.

For EDA, in the monotone game setting, we use a constant learning rate of $\eta = 0.02$, based on an approximation of the Lipschitz-smoothness parameter, and in the bilinear setting, we us learning rate of $\eta = 1/\|\boldsymbol{Q}\|$ as determined by our theory for the bilinear game setting (Theorem 3.4). Similarly, for ADA, in the monotone game setting, we use the constant learning rates of $\eta_{\boldsymbol{a}} = 0.02$ and $\eta_{\boldsymbol{a}} = 0.05$ based on an approximation of the Lipschitz-smoothness parameter, and in the bilinear game setting, we use the theoretically-grounded learning rates of $\eta_{\boldsymbol{a}} = \|\boldsymbol{Q}\| + \frac{\|\boldsymbol{Q}\|^2}{\alpha}$ and $\eta_{\boldsymbol{b}} = 1/\|\boldsymbol{Q}\|$, together with. For both of these settings, we use a regularization of $\alpha = 0.1$ for ADA, which was determined by grid search. In our implementation of AMPQP, grid search led us to initialize $\beta_0 = 0.01, \gamma = 1.05, \alpha = 0.2$ in both settings.[8] Additionally, because the iterates generated by AMPQP are not necessarily feasible, we projected them onto the feasible set of actions, so as to avoid infinite exploitability. This heuristic improved the convergence rate of AMPQP significantly. The first iterate for all methods was common, and initialized at random.

Monotone Games with Jointly Affine Constraints We begin by experimenting with monotone games with jointly affine constraints, the largest class of pseudo-games for which convergence rates exist for AMPQP. In particular, we consider norm-minimization pseudo-games with payoff

---

[5]We note that this is a special case of the proximal-Polyak-Lojasiwicz condition (See Section 4, [103]).

[6]We describe additional experiments in the supplemental work, with two-player zero-sum bilinear pseudo-games with jointly affine constraints and two-player zero-sum bilinear pseudo-games with jointly convex constraints. The results are not qualitatively different than those presented here. All our code can be found on https://anonymous.4open.science/r/exploit-min-E1B0/README.md.

[7]We note that we are not reporting on our results with the Accelerated Mirror-Prox Augmented Lagrangian Method (AMPAL), another method studied in the literature with the convergence rates as AMPQP, because we found this algorithm to be unstable on our benchmark pseudo-games.

[8]As suggested by Jordan, Lin, and Zampetakis [78], we replaced the convergence tolerance parameter δ, with the number of iterations for which the accelerated mirror-prox subroutine [105] was run. Then, at each iteration of AMPQP, this parameter was increased by a factor of γ of AMPQP.

(a) Phase portrait for a 2 player monotone game with $m = 1$

(b) Exploitability for a 5 player monotone game with $m = 10$

(c) Phase portrait for bilinear general-sum pseudo-game with $m = 1$

(d) Exploitability for a bilinear general-sum pseudo-game; $m = 10$

Figure 1: Convergence in monotone and bilinear general-sum pseudo-games.

functions $u_i(\boldsymbol{a}) = -\left\|\sum_{i \in [n]} \boldsymbol{a}_i - \boldsymbol{s}_i\right\|$, for all players $i \in [n]$, and for some randomly initialized shifting factors $\boldsymbol{s}_i$, as well as jointly affine constraints $g(\boldsymbol{a}) = 1 - \sum_{j \in [m]} a_{1j} - \sum_{i \in [m]} a_{2j}$, with action spaces $\mathcal{A}_i = [-10, 10]^m$, for all players $i \in [n]$. Although norm-minimization games are trivial, in the sense that they can be solved in closed form, this is not the case for pseudo-games; on the contrary, they form a bedrock example for monotone pseudo-games ([57], Example 1).

In Figure 1a, we observe that all three algorithms converge to a GNE. Interestingly, the three methodsEDA and ADA find distinct GNEs from AMPQP, which is not entirely surprising, as the three algorithms have different objectivesAMPQP is not an exploitability minimization algorithm. Although all the algorithms eventually find a GNE, exploitability does not decrease monotonically (Figure 1b); on the contrary, it increases before eventually decreasing to zero. Convergence to a GNE is expected for AMPQP, as per the theory. EDA, however, is not guaranteed to converge to a GNE in pseudo-games beyond convex exploitability; yet, we still observe convergence, albeit at a slower rate than AMPQP or ADA. Likewise, we observe convergence to a GNE for ADA, which is not guaranteed to converge, much faster than AMPQP, which is guaranteed to converge.

Bilinear General-Sum Games with Jointly Convex Constraints   Second, we consider the class of two-player general-sum games with jointly convex constraints with payoff functions $u_1(\boldsymbol{a}) = {\boldsymbol{a}_1}^T \boldsymbol{Q}_1 \boldsymbol{a}_2, u_2(\boldsymbol{a}) = {\boldsymbol{a}_1}^T \boldsymbol{Q}_2 \boldsymbol{a}_2, g(\boldsymbol{a}) = 1 - \|\boldsymbol{a}\|_2^2, \mathcal{A}_1 = \mathcal{A}_2 = [-10, 10]^m$. Such games are not monotone, and hence AMPQP is not guaranteed to converge in theory. In Figure 1c, we see that convergence is not guaranteed empirically either; shown is a sample run in which ADA and EDA converge, while AMPQP exhibits erratic behavior. Non-convergence for AMPQP was observed in 93 of the 100 experiments run. In fact, even though AMPQP gets very close a GNE (Figure 1d), i.e., zero exploitability, it does not stabilize there. We likewise found that ADA and EDA do not converge to a GNE from all random initializations. In such cases, we restarted the algorithms with a new random initialization; this process lead to on average 11 restarts for EDA and 10 restarts for ADA, meaning both algorithms converged to a GNE within this window.

6   Conclusion

In this paper, we provide an affirmative answer to an open question first posed by Flam and Ruszczynski in 1994, who suggested that projected gradient methods could be developed to minimize exploitability in pseudo-games (See Section 1, [80]). We solve this problem by incorporating the gradient mapping operator from proximal theory into a min-max optimization perspective, after which we propose and rigorously analyze an algorithm that converges to stationary points of the exploitability in all Lipschitz-smooth pseudo-games with jointly convex constraints. Our analysis, which relies on structural properties of exploitability, allows us obtain algorithms which are orders of magnitude faster than known min-max optimization algorithms. Along the way, we also develop a parameterized version of Moreau's envelope theorem, which may be of independent interest.

The design of efficient algorithms for constrained non-convex-concave min-max optimization problems is an open problem. The literature thus far has focused on problems in which only the variable to be maximized is constrained [25, 27, 29]. Our techniques may provide a path to solving non-convex-concave min-max optimization problems in entirely constrained domains, since our algorithms solve a non-convex-concave optimization problem where both variables are constrained.

References

[1] John F. Nash. "Equilibrium points in n-person games". In: *Proceedings of the National Academy of Sciences* 36.1 (1950), pp. 48–49. DOI: 10.1073/pnas.36.1.48. eprint: https://www.pnas.org/doi/pdf/10.1073/pnas.36.1.48. URL: https://www.pnas.org/doi/abs/10.1073/pnas.36.1.48.

[2] Martin J Osborne and Ariel Rubinstein. *A course in game theory*. MIT press, 1994.

[3] Noam Nissan and Tim Roughgarden. *Algorithmic Game Theory*. Cambridge University Press, 2007. DOI: 10.1017/CBO9780511800481.

[4] Christos H Papadimitriou. "On the complexity of the parity argument and other inefficient proofs of existence". In: *Journal of Computer and system Sciences* 48.3 (1994), pp. 498–532.

[5] Xi Chen and Xiaotie Deng. "3-Nash is PPAD-complete". In: *Electronic Colloquium on Computational Complexity*. Vol. 134. Citeseer. 2005, pp. 2–29.

[6] Xi Chen and Xiaotie Deng. "Settling the complexity of two-player Nash equilibrium". In: *2006 47th Annual IEEE Symposium on Foundations of Computer Science (FOCS'06)*. IEEE. 2006, pp. 261–272.

[7] Constantinos Daskalakis, Paul W Goldberg, and Christos H Papadimitriou. "The complexity of computing a Nash equilibrium". In: *SIAM Journal on Computing* 39.1 (2009), pp. 195–259.

[8] Paul Tseng. "On linear convergence of iterative methods for the variational inequality problem". In: *Journal of Computational and Applied Mathematics* 60.1 (1995). Proceedings of the International Meeting on Linear/Nonlinear Iterative Methods and Verification of Solution, pp. 237–252. ISSN: 0377-0427. DOI: https://doi.org/10.1016/0377-0427(94)00094-H. URL: https://www.sciencedirect.com/science/article/pii/037704279400094H.

[9] Yurii Nesterov and Laura Scrimali. "Solving strongly monotone variational and quasi-variational inequalities". In: *Discrete & Continuous Dynamical Systems* 31.4 (2011), pp. 1383–1396.

[10] Gauthier Gidel et al. *A Variational Inequality Perspective on Generative Adversarial Networks*. 2020. arXiv: 1802.10551 [cs.LG].

[11] Aryan Mokhtari, Asuman Ozdaglar, and Sarath Pattathil. *Convergence Rate of $\mathcal{O}(1/k)$ for Optimistic Gradient and Extra-gradient Methods in Smooth Convex-Concave Saddle Point Problems*. 2020. arXiv: 1906.01115 [math.OC].

[12] Adam Ibrahim et al. "Lower bounds and conditioning of differentiable games". In: *arXiv preprint arXiv:1906.07300* (2019).

[13] Mingyi Hong, Junyu Zhang, Shuzhong Zhang, et al. *On Lower Iteration Complexity Bounds for the Saddle Point Problems*. 2020. arXiv: 1912.07481 [math.OC].

[14] Tianyi Lin, Chi Jin, and Michael I Jordan. "Near-optimal algorithms for minimax optimization". In: *Conference on Learning Theory*. PMLR. 2020, pp. 2738–2779.

[15] Mohammad Alkousa et al. *Accelerated methods for composite non-bilinear saddle point problem*. 2020. arXiv: 1906.03620 [math.OC].

[16] Anatoli Juditsky, Arkadi Nemirovski, et al. "First order methods for nonsmooth convex large-scale optimization, ii: utilizing problems structure". In: *Optimization for Machine Learning* 30.9 (2011), pp. 149–183.

[17] Erfan Yazdandoost Hamedani and Necdet Serhat Aybat. "A primal-dual algorithm for general convex-concave saddle point problems". In: *arXiv preprint arXiv:1803.01401* 2 (2018).

[18] Zhao Renbo. *Optimal algorithms for stochastic three-composite convex-concave saddle point problems*. 2019. arXiv: 1903.01687 [math.OC].

[19] Kiran Koshy Thekumparampil et al. *Efficient Algorithms for Smooth Minimax Optimization*. 2019. arXiv: 1907.01543 [math.OC].

[20] Yuyuan Ouyang and Yangyang Xu. *Lower complexity bounds of first-order methods for convex-concave bilinear saddle-point problems*. 2018. arXiv: 1808.02901 [math.OC].

[21] Arkadi Nemirovski. "Prox-method with rate of convergence O (1/t) for variational inequalities with Lipschitz continuous monotone operators and smooth convex-concave saddle point problems". In: *SIAM Journal on Optimization* 15.1 (2004), pp. 229–251.

[22] Yurii Nesterov. "Dual extrapolation and its applications to solving variational inequalities and related problems". In: *Mathematical Programming* 109.2 (2007), pp. 319–344.

[23] Paul Tseng. "On accelerated proximal gradient methods for convex-concave optimization". In: *submitted to SIAM Journal on Optimization* 1 (2008).

[24] Maziar Sanjabi et al. "On the Convergence and Robustness of Training GANs with Regularized Optimal Transport". In: *Proceedings of the 32nd International Conference on Neural Information Processing Systems*. NIPS'18. Montreal, Canada: Curran Associates Inc., 2018, pp. 7091–7101.

[25] Maher Nouiehed et al. "Solving a class of non-convex min-max games using iterative first order methods". In: *arXiv preprint arXiv:1902.08297* (2019).

[26] Songtao Lu, Ioannis Tsaknakis, and Mingyi Hong. "Block alternating optimization for non-convex min-max problems: algorithms and applications in signal processing and communications". In: *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*. IEEE. 2019, pp. 4754–4758.

[27] Chi Jin, Praneeth Netrapalli, and Michael I. Jordan. *What is Local Optimality in Nonconvex-Nonconcave Minimax Optimization?* 2020. arXiv: `1902.00618 [cs.LG]`.

[28] Dmitrii M Ostrovskii, Andrew Lowy, and Meisam Razaviyayn. "Efficient search of first-order nash equilibria in nonconvex-concave smooth min-max problems". In: *arXiv preprint arXiv:2002.07919* (2020).

[29] Tianyi Lin, Chi Jin, and Michael Jordan. "On gradient descent ascent for nonconvex-concave minimax problems". In: *International Conference on Machine Learning*. PMLR. 2020, pp. 6083–6093.

[30] Renbo Zhao. *A Primal Dual Smoothing Framework for Max-Structured Nonconvex Optimization*. 2020. arXiv: `2003.04375 [math.OC]`.

[31] Hassan Rafique et al. *Non-Convex Min-Max Optimization: Provable Algorithms and Applications in Machine Learning*. 2019. arXiv: `1810.02060 [math.OC]`.

[32] Dov Monderer and Lloyd S Shapley. "Potential games". In: *Games and economic behavior* 14.1 (1996), pp. 124–143.

[33] William H Sandholm. "Potential games with continuous player sets". In: *Journal of Economic theory* 97.1 (2001), pp. 81–108.

[34] Stephane Durand and Bruno Gaujal. "Complexity and optimality of the best response algorithm in random potential games". In: *International Symposium on Algorithmic Game Theory*. Springer. 2016, pp. 40–51.

[35] Yurii Nesterov and Laura Scrimali. "Solving strongly monotone variational and quasi-variational inequalities". In: (2006).

[36] Yang Cai, Argyris Oikonomou, and Weiqiang Zheng. "Tight Last-Iterate Convergence of the Extragradient Method for Constrained Monotone Variational Inequalities". In: *arXiv preprint arXiv:2204.09228* (2022).

[37] Yu Malitsky. "Projected reflected gradient methods for monotone variational inequalities". In: *SIAM Journal on Optimization* 25.1 (2015), pp. 502–520.

[38] Eduard Gorbunov, Nicolas Loizou, and Gauthier Gidel. "Extragradient method: O (1/K) last-iterate convergence for monotone variational inequalities and connections with cocoercivity". In: *International Conference on Artificial Intelligence and Statistics*. PMLR. 2022, pp. 366–402.

[39] Tatiana Tatarenko and Maryam Kamgarpour. "Learning Nash equilibria in monotone games". In: *2019 IEEE 58th Conference on Decision and Control (CDC)*. IEEE. 2019, pp. 3104–3109.

[40] Bingsheng He et al. "A new inexact alternating directions method for monotone variational inequalities". In: *Mathematical Programming* 92.1 (2002), pp. 103–118.

[41] Yu V Malitsky and VV Semenov. "An extragradient algorithm for monotone variational inequalities". In: *Cybernetics and Systems Analysis* 50.2 (2014), pp. 271–277.

[42] Ian Goodfellow et al. "Generative Adversarial Nets". In: *Advances in Neural Information Processing Systems*. Ed. by Z. Ghahramani et al. Vol. 27. Curran Associates, Inc., 2014. URL: `https://proceedings.neurips.cc/paper/2014/file/5ca3e9b122f61f8f06494c97b1afccf3-Paper.pdf`.

[43] Antonia Creswell et al. "Generative Adversarial Networks: An Overview". In: *IEEE Signal Processing Magazine* 35.1 (2018), pp. 53–65. DOI: `10.1109/MSP.2017.2765202`.

[44] Kenneth Arrow and Gerard Debreu. "Existence of an equilibrium for a competitive economy". In: *Econometrica: Journal of the Econometric Society* (1954), pp. 265–290.

[45] Michael Brückner, Christian Kanzow, and Tobias Scheffer. "Static prediction games for adversarial learning problems". In: *J. Mach. Learn. Res.* 13 (2012), pp. 2617–2654. URL: http://dl.acm.org/citation.cfm?id=2503326.

[46] Michael Brückner and Tobias Scheffer. "Nash equilibria of static prediction games". In: *Advances in neural information processing systems* 22 (2009).

[47] Benjamin F. Hobbs and J. S. Pang. "Nash-Cournot Equilibria in Electric Power Markets with Piecewise Linear Demand Functions and Joint Constraints". In: *Operations Research* 55.1 (2007), pp. 113–127. DOI: 10.1287/opre.1060.0342. eprint: https://doi.org/10.1287/opre.1060.0342. URL: https://doi.org/10.1287/opre.1060.0342.

[48] Wei Jing-Yuan and Yves Smeers. "Spatial Oligopolistic Electricity Models with Cournot Generators and Regulated Transmission Prices". In: *Operations Research* 47.1 (1999), pp. 102–112. DOI: 10.1287/opre.47.1.102. eprint: https://pubsonline.informs.org/doi/pdf/10.1287/opre.47.1.102. URL: https://pubsonline.informs.org/doi/abs/10.1287/opre.47.1.102.

[49] Michele Breton, Georges Zaccour, and Mehdi Zahaf. "A game-theoretic formulation of joint implementation of environmental projects". In: *European Journal of Operational Research* 168.1 (2006), pp. 221–239.

[50] Jacek B. Krawczyk. "Coupled constraint Nash equilibria in environmental games". In: *Resource and Energy Economics* 27.2 (2005), pp. 157–181. ISSN: 0928-7655. DOI: https://doi.org/10.1016/j.reseneeco.2004.08.001. URL: https://www.sciencedirect.com/science/article/pii/S0928765504000661.

[51] Danilo Ardagna, Michele Ciavotta, and Mauro Passacantando. "Generalized Nash Equilibria for the Service Provisioning Problem in Multi-Cloud Systems". In: *IEEE Transactions on Services Computing* 10.3 (2017), pp. 381–395. DOI: 10.1109/TSC.2015.2477836.

[52] Danilo Ardagna, Barbara Panicucci, and Mauro Passacantando. "A Game Theoretic Formulation of the Service Provisioning Problem in Cloud Systems". In: *Proceedings of the 20th International Conference on World Wide Web*. WWW '11. Hyderabad, India: Association for Computing Machinery, 2011, pp. 177–186. ISBN: 9781450306324. DOI: 10.1145/1963405.1963433. URL: https://doi.org/10.1145/1963405.1963433.

[53] Xuegang (Jeff) Ban et al. "A general equilibrium model for transportation systems with e-hailing services and flow congestion". In: *Transportation Research Part B: Methodological* 129 (2019), pp. 273–304. ISSN: 0191-2615. DOI: https://doi.org/10.1016/j.trb.2019.08.012. URL: https://www.sciencedirect.com/science/article/pii/S0191261518309044.

[54] Oliver Stein and Nathan Sudermann-Merx. "The noncooperative transportation problem and linear generalized Nash games". In: *European Journal of Operational Research* 266.2 (2018), pp. 543–553. DOI: 10.1016/j.ejor.2017.10.00. URL: https://ideas.repec.org/a/eee/ejores/v266y2018i2p543-553.html.

[55] Zhu Han et al. *Game theory in wireless and communication networks: Theory, models, and applications*. English. Vol. 9780521196963. Publisher Copyright: © Cambridge University Press 2012. United Kingdom: Cambridge University Press, Jan. 2011. ISBN: 9780521196963. DOI: 10.1017/CBO9780511895043.

[56] Jong-Shi Pang et al. "Distributed power allocation with rate constraints in Gaussian parallel interference channels". In: *IEEE Transactions on Information Theory* 54.8 (2008), pp. 3471–3489.

[57] Francisco Facchinei and Christian Kanzow. "Generalized Nash equilibrium problems". In: *Annals of Operations Research* 175.1 (2010), pp. 177–211.

[58] Andreas Fischer, Markus Herrich, and Klaus Schönefeld. "GENERALIZED NASH EQUILIBRIUM PROBLEMS - RECENT ADVANCES AND CHALLENGES". In: *Pesquisa Operacional* 34 (2014), pp. 521–558.

[59] Francisco Facchinei, Andreas Fischer, and Veronica Piccialli. "Generalized Nash equilibrium problems and Newton methods". In: *Mathematical Programming* 117.1 (2009), pp. 163–194.

[60] Francisco Facchinei and Simone Sagratella. "On the computation of all solutions of jointly convex generalized Nash equilibrium problems". In: *Optimization Letters* 5.3 (2011), pp. 531–547.

[61] Dario Paccagnan et al. "Distributed computation of generalized Nash equilibria in quadratic aggregative games with affine coupling constraints". In: *2016 IEEE 55th Conference on Decision and Control (CDC)*. IEEE. 2016, pp. 6123–6128.

[62] Peng Yi and Lacra Pavel. "A distributed primal-dual algorithm for computation of generalized Nash equilibria via operator splitting methods". In: *2017 IEEE 56th Annual Conference on Decision and Control (CDC)*. IEEE. 2017, pp. 3841–3846.

[63] Eleftherios Couzoudis and Philipp Renner. "Computing generalized Nash equilibria by polynomial programming". In: *Mathematical Methods of Operations Research* 77.3 (2013), pp. 459–472.

[64] Axel Dreves. "Computing all solutions of linear generalized Nash equilibrium problems". In: *Mathematical Methods of Operations Research* 85.2 (2017), pp. 207–221.

[65] Anna Von Heusinger and Christian Kanzow. "Optimization reformulations of the generalized Nash equilibrium problem using Nikaido-Isoda-type functions". In: *Computational Optimization and Applications* 43.3 (2009), pp. 353–377.

[66] Tatiana Tatarenko and Maryam Kamgarpour. "Learning generalized Nash equilibria in a class of convex games". In: *IEEE Transactions on Automatic Control* 64.4 (2018), pp. 1426–1439.

[67] Axel Dreves and Nathan Sudermann-Merx. "Solving linear generalized Nash equilibrium problems numerically". In: *Optimization Methods and Software* 31.5 (2016), pp. 1036–1063.

[68] Anna von Heusinger, Christian Kanzow, and Masao Fukushima. "Newton's method for computing a normalized equilibrium in the generalized Nash game through fixed point formulation". In: *Mathematical Programming* 132.1 (2012), pp. 99–123.

[69] Alexey F Izmailov and Mikhail V Solodov. "On error bounds and Newton-type methods for generalized Nash equilibrium problems". In: *Computational Optimization and Applications* 59.1 (2014), pp. 201–218.

[70] Andreas Fischer et al. "A globally convergent LP-Newton method". In: *SIAM Journal on Optimization* 26.4 (2016), pp. 2012–2033.

[71] Jong-Shi Pang and Masao Fukushima. "Quasi-variational inequalities, generalized Nash equilibria, and multi-leader-follower games". In: *Computational Management Science* 2.1 (2005), pp. 21–56.

[72] Francisco Facchinei and Lorenzo Lampariello. "Partial penalization for the solution of generalized Nash equilibrium problems". In: *Journal of Global Optimization* 50.1 (2011), pp. 39–57.

[73] Masao Fukushima. "Restricted generalized Nash equilibria and controlled penalty algorithm". In: *Computational Management Science* 8.3 (2011), pp. 201–218.

[74] Christian Kanzow. "On the multiplier-penalty-approach for quasi-variational inequalities". In: *Mathematical Programming* 160.1 (2016), pp. 33–63.

[75] Christian Kanzow and Daniel Steck. "Augmented Lagrangian methods for the solution of generalized Nash equilibrium problems". In: *SIAM Journal on Optimization* 26.4 (2016), pp. 2034–2058.

[76] Christian Kanzow and Daniel Steck. "Augmented Lagrangian and exact penalty methods for quasi-variational inequalities". In: *Computational Optimization and Applications* 69.3 (2018), pp. 801–824.

[77] Qin Ba and Jong-Shi Pang. "Exact penalization of generalized Nash equilibrium problems". In: *Operations Research* (2020).

[78] Michael I. Jordan, Tianyi Lin, and Manolis Zampetakis. *First-Order Algorithms for Nonlinear Generalized Nash Equilibrium Problems*. 2022. DOI: 10.48550/ARXIV.2204.03132. URL: https://arxiv.org/abs/2204.03132.

[79] Hukukane Nikaidô and Kazuo Isoda. "Note on non-cooperative convex games". In: *Pacific Journal of Mathematics* 5.S1 (1955), pp. 807–815.

[80] Sjur Flam and Andrzej Ruszczynski. *Noncooperative Convex Games: Computing Equilibrium By Partial Regularization*. Working Papers. International Institute for Applied Systems Analysis, 1994. URL: https://EconPapers.repec.org/RePEc:wop:iasawp:wp94042.

[81] Edward Lockhart et al. "Computing Approximate Equilibria in Sequential Adversarial Games by Exploitability Descent". In: *CoRR* abs/1903.05614 (2019). arXiv: 1903.05614. URL: http://arxiv.org/abs/1903.05614.

[82] Ian M. Gemp et al. "Sample-based Approximation of Nash in Large Many-Player Games via Gradient Descent". In: *CoRR* abs/2106.01285 (2021). arXiv: 2106.01285. URL: https://arxiv.org/abs/2106.01285.

[83] Galina M Korpelevich. "The extragradient method for finding saddle points and other problems". In: *Matecon* 12 (1976), pp. 747–756.

[84] Angelia Nedic and Asuman Ozdaglar. "Subgradient methods for saddle-point problems". In: *Journal of optimization theory and applications* 142.1 (2009), pp. 205–228.

[85] Denizalp Goktas and Amy Greenwald. "Convex-Concave Min-Max Stackelberg Games". In: *Advances in Neural Information Processing Systems* 34 (2021).

[86] J. B. Rosen. "Existence and Uniqueness of Equilibrium Points for Concave N-Person Games". In: *Econometrica* 33.3 (1965), pp. 520–534. ISSN: 00129682, 14680262. URL: http://www.jstor.org/stable/1911749 (visited on 05/16/2022).

[87] S. Uryas'ev and R.Y. Rubinstein. *On relaxation algorithms in computation of noncooperative equilibria*. 1994. DOI: 10.1109/9.293193.

[88] Jacek B. Krawczyk and Stanislav Uryasev. "Relaxation algorithms to find Nash equilibria with economic applications". English. In: *Environmental Modeling & Assessment* 5.1 (2000). This revised version was published online in July 2006 with corrections to the Cover Date., pp. 63–73. DOI: 10.1023/A:1019097208499.

[89] A. Heusinger and C. Kanzow. "Relaxation Methods for Generalized Nash Equilibrium Problems with Inexact Line Search". In: *Journal of Optimization Theory and Applications* 143.1 (2009), pp. 159–183. URL: https://EconPapers.repec.org/RePEc:spr:joptap:v:143:y:2009:i:1:d:10.1007_s10957-009-9553-0.

[90] Axel Dreves et al. "A Globalized Newton Method for the Computation of Normalized Nash Equilibria". In: *J. of Global Optimization* 56.2 (June 2013), pp. 327–340. ISSN: 0925-5001. DOI: 10.1007/s10898-011-9824-9. URL: https://doi.org/10.1007/s10898-011-9824-9.

[91] Francisco Facchinei, Andreas Fischer, and Veronica Piccialli. "On generalized Nash games and variational inequalities". In: *Operations Research Letters* 35.2 (2007), pp. 159–164. ISSN: 0167-6377. DOI: https://doi.org/10.1016/j.orl.2006.03.004. URL: https://www.sciencedirect.com/science/article/pii/S0167637706000484.

[92] Koichi Nabetani, Paul Tseng, and Masao Fukushima. "Parametrized Variational Inequality Approaches to Generalized Nash Equilibrium Problems with Shared Constraints". In: *Comput. Optim. Appl.* 48.3 (Apr. 2011), pp. 423–452. ISSN: 0926-6003. DOI: 10.1007/s10589-009-9256-3. URL: https://doi.org/10.1007/s10589-009-9256-3.

[93] Dane A. Schiro, Jong-Shi Pang, and Uday V. Shanbhag. "On the solution of affine generalized Nash equilibrium problems with shared constraints by Lemke's method". English. In: *Mathematical Programming* 142.1-2 (2013). This work was based on research partially supported by the National Science Foundation under grant CMMI-0969600 and the Department of Energy under grant DOE DE-SC0003879., pp. 1–46. DOI: 10.1007/s10107-012-0558-3.

[94] Francisco Facchinei and Christian Kanzow. "Penalty Methods for the Solution of Generalized Nash Equilibrium Problems". In: *SIAM Journal on Optimization* 20.5 (2010), pp. 2228–2253. DOI: 10.1137/090749499. eprint: https://doi.org/10.1137/090749499. URL: https://doi.org/10.1137/090749499.

[95] Luís Felipe Bueno, Gabriel Haeser, and Frank Navarro Rojas. "Optimality Conditions and Constraint Qualifications for Generalized Nash Equilibrium Problems and Their Practical Implications". In: *SIAM Journal on Optimization* 29.1 (2019), pp. 31–54. DOI: 10.1137/17M1162524. eprint: https://doi.org/10.1137/17M1162524. URL: https://doi.org/10.1137/17M1162524.

[96] J v Neumann. "Zur theorie der gesellschaftsspiele". In: *Mathematische annalen* 100.1 (1928), pp. 295–320.

[97] Stephen Boyd, Stephen P Boyd, and Lieven Vandenberghe. *Convex optimization*. Cambridge university press, 2004.

[98] Noah Golowich et al. "Last Iterate is Slower than Averaged Iterate in Smooth Convex-Concave Saddle Point Problems". In: *CoRR* abs/2002.00057 (2020). arXiv: 2002.00057. URL: https://arxiv.org/abs/2002.00057.

[99] Ioannis Tsaknakis, Mingyi Hong, and Shuzhong Zhang. "Minimax Problems with Coupled Linear Constraints: Computational Complexity, Duality and Solution Methods". In: *arXiv preprint arXiv:2110.11210* (2021).

[100] Jean-Jacques Moreau. "Proximité et dualité dans un espace hilbertien". In: *Bulletin de la Société mathématique de France* 93 (1965), pp. 273–299.

[101]   Amir Beck. *First-order methods in optimization.* SIAM, 2017.

[102]   Shashi K Mishra and Giorgio Giorgi. *Invexity and optimization.* Vol. 88. Springer Science & Business Media, 2008.

[103]   Hamed Karimi, Julie Nutini, and Mark Schmidt. "Linear convergence of gradient and proximal-gradient methods under the polyak-łojasiewicz condition". In: *Joint European Conference on Machine Learning and Knowledge Discovery in Databases.* Springer. 2016, pp. 795–811.

[104]   Arvind Raghunathan, Anoop Cherian, and Devesh Jha. "Game theoretic optimization via gradient-based nikaido-isoda function". In: *International Conference on Machine Learning.* PMLR. 2019, pp. 5291–5300.

[105]   Yunmei Chen, Guanghui Lan, and Yuyuan Ouyang. "Accelerated schemes for a class of variational inequalities". In: *Mathematical Programming* 165.1 (2017), pp. 113–149.

[106]   Guido Van Rossum and Fred L Drake Jr. *Python tutorial.* Centrum voor Wiskunde en Informatica Amsterdam, The Netherlands, 1995.

[107]   Charles R. Harris et al. "Array programming with NumPy". In: *Nature* 585 (2020), pp. 357–362. DOI: `10.1038/s41586-020-2649-2`.

[108]   Steven Diamond and Stephen Boyd. "CVXPY: A Python-embedded modeling language for convex optimization". In: *Journal of Machine Learning Research* 17.83 (2016), pp. 1–5.

[109]   J. D. Hunter. "Matplotlib: A 2D graphics environment". In: *Computing in Science & Engineering* 9.3 (2007), pp. 90–95. DOI: `10.1109/MCSE.2007.55`.

[110]   Gauthier Gidel et al. "A variational inequality perspective on generative adversarial networks". In: *arXiv preprint arXiv:1802.10551* (2018).

[111]   John M. Danskin. "The Theory of Max-Min, with Applications". In: *SIAM Journal on Applied Mathematics* 14.4 (1966), pp. 641–664. ISSN: 00361399. URL: `http://www.jstor.org/stable/2946123`.

[112]   S. N. Afriat. "Theory of Maxima and the Method of Lagrange". In: *SIAM Journal on Applied Mathematics* 20.3 (1971), pp. 343–357. ISSN: 00361399. URL: `http://www.jstor.org/stable/2099955`.

[113]   Paul Milgrom and Ilya Segal. "Envelope theorems for arbitrary choice sets". In: *Econometrica* 70.2 (2002), pp. 583–601.

[114]   Elad Hazan, Karan Singh, and Cyril Zhang. "Efficient regret minimization in non-convex games". In: *International Conference on Machine Learning.* PMLR. 2017, pp. 1433–1441.