Automorphic Equivalence-aware Graph Neural Network

Abstract

Distinguishing the structural equivalence of nodes in a graph plays an essential role in many scientific domains, *e.g.*, computational biologist and social network analysis. However, existing graph neural networks (GNNs) fail to capture such an important property. To make GNN aware of structural equivalence, we first introduce a localized variant of the classic concept — automorphic equivalence (AE). Then, we design a novel variant of GNN, *i.e.*, GRAPE, that uses learnable AE-aware aggregators to explicitly differentiate the structural equivalences of each node's neighbors with the aids of various subgraph templates. To alleviate the barrier of subgraph template design, we also propose to automatically search the design space with an efficient genetic algorithm. Moreover, we theoretically prove that GRAPE is expressive in terms of generating distinct representations for nodes with different AE features, which fills in a fundamental gap of existing GNN variants. Finally, we empirically validate our model on eight real-world graph data, including social network, e-commerce co-purchase network, and citation network, and show that it consistently outperforms strong baselines.

1 Introduction

The past few years have witnessed the phenomenal success of GNNs in numerous graph learning tasks, such as node classification [28], link prediction [59], and community detection [21], which is largely due to their capability of simultaneously modeling the connecting patterns and feature distribution in each node's local neighborhood. As a result, it leads to a surge of interests from both academia and industry to develop more powerful GNN models [53]. Despite of various architectures, the most popular GNNs, like GCN [28], GraphSAGE [21], GAT [50] and GIN [55], apply permutation invariant aggregate function on each node's local neighborhood to learn node embeddings, which leads to concerns about their representational power [18, 55].

In this paper, we investigate GNN's expressiveness from an important and largely overlooked angle, *i.e.*, the capacity to distinguish structural equivalences within each node's local neighborhood. Modeling structurally equivalent nodes has been a central topic in computational biologist, social network analysis and other scientific domains [36, 37], where the structurally equivalent nodes are considered to exhibit similar properties because they are "structurally interchangable" [36, 22]. For example, one's social connections might be classified into strong ties and weak ties that have different level of influence on her, which can potentially be identified based on the structural equivalences, *e.g.*, individuals that form clique structure with her are more likely to be strong ties and simple edge connections are more likely to be weak ties [17]. Thus, modeling structural equivalences plays a vital role in graph analysis [30, 36].

Automorphic equivalence (AE) [14] is a classic concept to differentiate the structural role of each node in a given graph. Specifically, two nodes are considered to be AE only if they are interchangeable in some index permutations that preserve the connection matrix, *i.e.*, graph automorphisms [38].

Efficient algorithms have been proposed to identify the AE by enumerating all the automorphisms of the given graphs [7, 47]. AE can identify the nodes that exhibit identical structural features in a graph, which is important to predict each node's properties [36]. For example, empirical studies show AE is an important indicator of social position and behavior similarity in social network [16, 40], which thus might significantly benefit GNN architecture design. However, previous analytic methods only classify nodes into categorical equivalence sets, which cannot be optimized for various specific applications in an end-to-end manner. By principally incorporating AE into GNNs, we aim to design a data-dependent deep learning model that can be tuned based on the graph data and targeted applications, which will allow us to learn more expressive function to fully harness the power of AE.

Here, we propose GRaph AutomorPhic Equivalent network, *i.e.*, GRAPE, a novel variant of GNN that can learn expressive representation by differentiating the structural equivalences of each node's neighbors. First, GRAPE extends the classic AE concept into a localized setting, *i.e.*, Ego-AE, to accommodate the local nature of GNNs. Specifically, Ego-AE identifies the local neighborhoods of each node by mapping with given subgraph templates and then partitions the neighboring nodes into Ego-AE sets based on the graph automorphisms in neighborhood. Second, we design a learnable AE-aware aggregators to model the node features in these Ego-AE sets, which adaptively assigns different weights to neighboring nodes in different Ego-AE sets and explicitly model the interdependency among them. Moreover, in order to capture complex structural features, GRAPE proposes to fuse the embeddings learned from Ego-AE sets identified by different subgraph templates with a squeeze-and-excitation module [26]. Finally, to alleviate the barrier of subgraph template design, we propose an efficient genetic algorithm to automatically search for optimal subgraph templates. Specifically, it gradually optimizes a randomly initiated population of subgraph templates by iteratively exploring the adjacency of good performing candidates and eliminating the bad performing ones. To accelerate the search process, we further design an incremental subgraph matching algorithm that can leverage the similarity between subgraphs to greatly reduce the complexity of finding matched instances.

We theoretically prove that the proposed GRAPE model is expressive in terms of learning distinct representations for nodes with different Ego-AE sets, which fundamentally makes up the shortcomings of popular GNN variants, *e.g.*, GCN [28], GraphSAGE [21], GAT [50] and GIN [55]. Moreover, we empirically validate GRAPE on eight real-world datasets, which cover the scenarios of social network, citation network and e-commerce co-purchase network. Experiments show GRAPE is consistently the best performing model across all datasets with up to 26.7% accuracy improvement. Besides, case studies indicate GRAPE can effectively differentiate the structural roles of each node's neighbors. Moreover, the proposed genetic algorithm efficiently generates high quality subgraph templates that have comparable performance with the hand-crafted ones.

2 Related Works

In the sequel, we define a graph as $G = (\mathcal{V}, \mathcal{E})$, where $\mathcal{V} = \{v_1, \cdots, v_n\}$ is the set of nodes and $\mathcal{E} = \{(v_i, v_j)\}$ is the set of edges. Let the feature vector of node v_i be $\mathcal{X}(v_i)$, and $\mathcal{N}(v_i)$ represents the set of v_i's neighbor nodes. N is the number of node and M is the embedding size.

2.1 Automorphic Equivalence (AE) in Graph Analysis

As mentioned in Section 1, capturing structural equivalence is very important in graph analysis. Here, we investigate one of the most popular equivalence concepts, *i.e.,* automorphic equivalence (AE) [14] which plays a central role in computational biologist, social network analysis and other scientific domains [36, 37]. The most interesting part of AE is that it identifies the nodes with exact same structural patterns, *e.g.*, degree and centrality [15], but not necessarily connecting to the same neighboring nodes. Basically, AE is defined as follows.

Definition 2.1 *Given a graph* $G = (\mathcal{V}, \mathcal{E})$, *an **automorphism** $\pi(\star)$ is a node permutation that preserves the adjacency matrix, i.e., the permuted nodes $\pi(v_a)$ and $\pi(v_b)$ are connected if and only if nodes v_a and v_b are connected. Two nodes v_a and v_b are considered to be **Automorphic Equivalence** (**AE**) if there is a graph automorphism that maps one onto the other, i.e., $\pi(v_a) = v_b$.*

Nodes in $\mathcal{V}$ that are AE with each other constitutes a AE set. An example of such sets is in Figure 1 (a). Specifically, AE sets can be identified by enumerating the automorphism group of the given graph with efficient *Nauty* algorithm [38], and the nodes that are mapped onto each others in different automorphisms will be partitioned into same AE sets.

Figure 1: Illustration of AE and the limitation of MPNN framework.

Previous works have attempted to preserve the structural similarities on graph via various node embedding algorithms [13, 2, 43]. Recently, GraphWave [13] was proposed to leverage wavelet diffusion patterns to capture the structural roles in node representations. Besides, role2vec [2] introduced a generalized feature-based random walks that aims to represent the structural similarities among nodes. However, the connection between AE and GNN has not been examined in existing literature. Moreover, AE is defined on whole graph level, which is infeasible to compute in large graphs and goes against the inherent local nature of most GNN frameworks. In this paper, we aim to extend the AE concept to local setting, and propose a novel GNN model to harness its power.

2.2 The Expressive Power of GNNs

The recent success of GNNs draws increasing interests in investigating their capability in capturing structural properties [55, 18]. Specifically, message passing neural network (MPNN) is the most popular GNN framework [19, 21, 55].

Expressiveness of MPNN Framework. Let AGG be the *aggregate* function that collects feature from neighbors, and COMB be the *combine* function that integrates each node's self feature with those from AGG. Generally, MPNN generates representation for a node v_t at k-th layer as

$$\boldsymbol{h}_{v_t}^k = \mathsf{COMB}\big(\boldsymbol{h}_{v_t}^{k-1}, \ \mathsf{AGG}(\mathcal{H}_{v_t}^{k-1})\big), \tag{1}$$

where $\boldsymbol{h}^0(v_i) = \mathcal{X}(v_i)$, and $\mathcal{H}_{v_t}^{k-1} = \big\{\boldsymbol{h}_{v_j}^{k-1} | v_j \in \mathcal{N}(v_t)\big\}$. Existing MPNNs use local permutation invariant AGGs to compute node embeddings, which subsumes a large class of popular GNN models such as GCN [28], GraphSAGE [21], GAT [50], Geniepath [34] and GIN [55]. The family of MPNNs is proven to be theoretically linked to Weisfeiler-Lehman (WL) subtree kernel [21]. Subsequently, they are at most as powerful as 1-WL test on discriminating graph isomorphisms [55].

However, previous works have shown that identifying automorphic equivalence is a strictly more difficult task than discriminating graph isomorphisms [48]. Specifically, two AE nodes always have isomorphic neighborhood, while the nodes with isomorphic neighborhood are not necessary AE [15]. Therefore, it raises concerns about MPNN's expressive power of AE feature, which has not been adequately investigated in previous research.

Beyond MPNN Framework. More recently, several attempts have been made to improve the expressiveness of GNN [18]. They can mainly be classified into two categories: augmenting node features and designing more powerful architectures. In terms of augmenting node feature, recent works proposed to introduce various additional feature [45, 29, 59]. Specifically, GNN variants can in theory achieve universal approximation on graph by equipping nodes with randomly initialized feature vector, but they are difficult to generalize to different graphs in practice [6]. On the other hand, the previous efforts of designing more powerful GNN architecture are dedicated to different structural properties, e.g., graph isomorphism [55] and graph moment [12]. Although AE is an important concept for graph data analysis, it has not been addressed by previous GNN research. More detailed comparison with the existing GNN variants is provided in Appendix A.

In this paper, we aim to design a novel GNN model that is provably expressive in modeling Ego-AE, which falling in the category of designing novel GNN architecture. To the best of our knowledge, we are the first to empower GNN with the capability of capturing automorphic equivalence.

Figure 2: The GRAPE model. (a) The input graph with node v_1 as ego node. (b) Mapping node v_1's neighborhood with given subgraph templates, where nodes with same color are Ego-AE. (c) Aggregating features from AE sets with learnable AE-aware aggregators. (d) Fusing multi-channel node embedding with squeeze-and-excitation module.

2.3 Genetic Algorithm

Genetic algorithm [24, 3] is a widely adopted algorithm for combinatorial optimization problems, *e.g.*, traveling salesman problem [20]. Recently, it has also been used to tune hyper-parameters [35] and search neural architectures for deep networks [57, 54]. Basically, genetic algorithm mimics the natural selection process to iteratively to search for better solutions by exploring the adjacency of promising candidates and eliminating the worst-performing ones [11]. Therefore, it can iteratively optimize the candidate population from *parent generation* to *children generation*. Specifically, genetic algorithms are often made up the following four components: (i) *Mutation*: explores the adjacency of promising candidates in *parent generation* by generating slightly different candidates in *children generation*; (ii) *Crossover*: search for different combinations of genetic features in the candidates in *parent generation*; (iii) *Evaluation*: measure the fitness of candidates in given tasks; (iv) *Selection*: eliminating the candidates with worst performance.

Here, we design a genetic algorithm to automatically optimize the subgraph templates in the proposed GRAPE model. It effectively allows us to search the architecture of GRAPE in a data-dependent manner, which significantly reduces the barrier of subgraph template design.

3 The Proposed Method

One prominent feature of most GNN variants is that the node embedding are generated based on the local neighborhood, which significantly improved the scalability and generalization of GNN models. To accommodate the local nature of GNNs, the concept of AE needs to be fundamentally extended and redefined on each node's local neighborhood. Besides, the local neighborhoods defined by different subgraph templates may exert different influence on the ego node [58, 2]. Thus, we propose a subgraph template-dependent local version of AE, *i.e.*, ego-centered automorphic equivalence (Ego-AE). Specifically, a subgraph template is defined as a connected graphlet $S = (\mathcal{U}, \mathcal{R})$, where $\mathcal{U}$ and $\mathcal{R}$ are the sets of nodes and edges, respectively. To differentiate the unique role of ego node, we set an anchoring node in subgraph template that always maps to the ego node. Given a graph $G = (\mathcal{V}, \mathcal{E})$, a subgraph template $S = (\mathcal{U}, \mathcal{R})$ and a node v_t, the Ego-AE on v_t's local neighborhood is defined as follow.

Definition 3.1 *We define $\mathcal{M}_S(v_t)$ as the set of subgraphs that match the subgraph template S in v_t's local neighborhood. An ego-centered automorphism $\pi_e(\star)$ is an automorphism on the matched subgraphs $m \in \mathcal{M}_S(v_t)$ that has a fixed index of node v_t, i.e., $\pi_e(v_t) \equiv v_t$. Two nodes v_a and v_b are considered to be __Ego-centered Automorphic Equivalence (Ego-AE)__ if there exists an automorphism $\pi_e(\star)$ that maps one onto the other, i.e., $\pi_e(v_a) = v_b$.*

Without loss of generality, various forms of subgraph template S can be adopted to capture the structural patterns of different semantics. Figure 1 (b) shows the Ego-AE on v_1's local neighborhoods with the subgraph templates of *triangle* and *chordal cycle*. Specifically, we first identify all the matched subgraphs with the anchoring nodes (white color) in subgraph templates fixed to the ego node v_1, and then the nodes covered by the matched instances are partitioned into Ego-AE sets based

Figure 3: Illustration of the *mutate* and *crossover* operations in the proposed genetic algorithm.

on the corresponding automorphisms. We can observe that Ego-AE successfully differentiates the roles of v_1's neighboring nodes based on the structural features.

However, GNN's capacity in capturing Ego-AE is largely unknown in the literature. In fact, we prove that the standard MPNN has fundamental limitations (see Section 3.3), while other GNN variants focus on different graph properties which largely overlooked Ego-AE.

3.1 The Proposed GRAPE Model

We aim to propose a novel GNN model, *i.e.*, GRaph AutomorPhic Equivalence network (GRAPE), that is provably expressive in capturing Ego-AE. The overall framework is in Figure 2. In the sequel, we describe them in details, and the complete algorithm of GRAPE is in Appendix C.1.

AE-aware Aggregator. Here, we design a novel AE-aware aggregators to learn from the Ego-AE sets in each node's local neighborhood with given subgraph templates. Specifically, we denote v_t's Ego-AE sets with subgraph template S_l as $\mathcal{T}_l = \{\mathcal{A}_{l,1}(v_t), ..., \mathcal{A}_{l,j}(v_t), ..., \mathcal{A}_{l,m_l}(v_t)\}$, where $\mathcal{A}_{l,j}(v_t)$ is the set of nodes corresponding to the j-th sets of Ego-AE nodes in S_l and m_l is the total number Ego-AE sets. Then, v_t's node embedding $\boldsymbol{h}_l^k(v_t)$ can be computed as follows:

$$\boldsymbol{h}_l^k(v) = \mathsf{MLP}\big(\sum\nolimits_j \beta_{l,j} \cdot \sum\nolimits_{v_n \in \mathcal{A}_{l,j}(v_t)} \boldsymbol{h}_l^{k-1}(v_n)\big), \tag{2}$$

where $\beta_{l,j}$'s are learnable weights that model the importance of $\mathcal{A}_{l,j}(v_t)$ and $\mathsf{MLP}(\cdot)$ is a multi-layer perception (MLP) function [23] that generates output embeddings.

Equation (2) is illustrated in Figure 2 (c). Differs from MPNNs, the proposed AE-aware aggregator can explicitly differentiate the neighboring nodes with different structural roles by assigning different weights $\beta_{l,j}$ to them. It allows GRAPE to capture the combination of important Ego-AE sets and effectively models the interdenpency among them. Note that GRAPE does not have an explicit *COMBINE* function to account for the ego node's self feature, since the ego node v_t will always be captured in a unique Ego-AE set, such as the $\mathcal{A}_{1,1}$ and $\mathcal{A}_{2,1}$ in Figure 2 (c).

Fusing Embeddings from Different Aggregators. To simultaneously capture different structural feature, we design a squeeze-and-excitation module to fuse the node embeddings learned from a set of subgraph templates, which is inspired by the channel-wise enhancement technique recently proposed in CNN research [25]. Specifically, by leveraging a set of subgraph templates $\Omega = \{S_1, S_2, ..., S_L\}$, GRAPE can learn multiple AE-aware aggregators with each subgraph template to capture different structural features respectively. The GRAPE can learn to assign different weights $\boldsymbol{\alpha}^k$ for $\boldsymbol{h}_l^k(v_t)$ and generate the fused embedding for v_t as following

$$\boldsymbol{h}^k(v) = \sum\nolimits_{l \in 1,...,L} \boldsymbol{\alpha}^k[l] \cdot \boldsymbol{h}_l^k(v). \tag{3}$$

Here, the learnable weights $\boldsymbol{\alpha}^k$ is computed as following

$$\boldsymbol{\gamma}^k[l] = \frac{1}{N} \sum\nolimits_{n=1}^N \mathsf{MEAN}(\boldsymbol{h}_l^k(v_n)), \quad \boldsymbol{\alpha}^k = \mathsf{ReLU}\big(\boldsymbol{W}_2^k \cdot \mathsf{ReLU}\big(\boldsymbol{W}_1^k \cdot \boldsymbol{\gamma}^k\big)\big), \tag{4}$$

where $\boldsymbol{\gamma}^k[l]$ is the global average pooling on the node embeddings learned with subgraph template S_l, $\boldsymbol{W}_1^k$ and $\boldsymbol{W}_2^k$ are two learnable matrices with $\mathbb{R}^{L \times L}$ size, and ReLU is the relu activation function.

3.2 Genetic Search of Subgraph Templates

To reduce the barrier of hand-crafted subgraph templates, we formulate the automatic subgraph template design problem as an optimization problem that aims to search for the best performing

combinations of subgraph templates Ω. Let the designed GRAPE in Section 3.1 be F with model parameter Θ, which leverages the Ego-AE sets $\{\mathcal{T}_1, ..., \mathcal{T}_L\}$ identified by *Matching* Ω on the given graph G. This subsequently leads to the following bi-level optimization [8] problem:

$$\max_{\{\Omega|G\}} F\left(\{\mathcal{T}_1, ..., \mathcal{T}_L\}, \Theta^\star\right), \quad \text{s.t.} \quad \begin{cases} \{\mathcal{T}_1, ..., \mathcal{T}_L\} = \text{Match}(G, \Omega) \\ \Theta^\star = \arg\max_\Theta F(\{\mathcal{T}_1, ..., \mathcal{T}_L\}, \Theta) \end{cases}, \quad (5)$$

However, the proposed optimization problem is difficult mainly for two reasons: 1) the search space of subgraph templates is discrete and not differentiable; 2) matching subgraph templates in a large graph data is computationally expensive.

Our key intuition to address these challenges is that similar subgraph templates often have slightly different pool of matched instances, which is likely to result in similar model performance. Therefore, by gradually exploring the adjacent search space of promising subgraph templates we can effectively avoid bad candidates. This inspires us to design a genetic optimization framework, which can navigate through the discrete search space via the gradual mutations between generations. Moreover, the similarities between iteratively searched subgraphs can be further leveraged to design efficient subgraph matching algorithm. The details are described as follows.

Genetic Subgraph Template Search. We define gene population as a set of B genes, where each gene is a set of L subgraph templates. The gene population is initiated as the most basic subgraph templates, *i.e.*, edge. Then, the gene population is optimized through K_2 rounds of genetic operations, which consists of *mutate*, *crossover*, *evaluate* and *select*. As in Figure 3, the *mutate* operation allows us to explore slightly more complex subgraph templates, *i.e.*, the subgraph templates with one randomly added nodes or edges, which are denoted as *children subgraphs*. Besides, the *crossover* operation will randomly exchange some subgraph templates between two genes with certain probability. It allows us to try out different combinations of subgraph templates. Moreover, the *evaluate* and *select* operations will identify and remove the worst-performing Z genes and reproduce the best-performing genes. Thus, these operations allow us to gradually explore the adjacent search space of promising *genes* and automatically optimize the subgraph templates. Finally, we use the subgraph templates encoded in the best performing *gene* after iterative genetic operations as the input of F.

Efficient Subgraph Template Matching. We have the following Proposition 3.1 for the matched instances of the mutated *children subgraph*. It can be easily validated because the *children subgraphs* are extended from *parent subgraphs* by randomly adding one node or edge. In fact, the adding edge *mutation* effectively acts as a filtering mechanism on matched instances, and the adding node *mutation* effectively extends the matched instances of *parent subgraph*. Therefore, instead of computing the matched instances from scratch, the incremental *mutate* operation facilitates us to save significantly amount of computation by only examining the matched instances of *parent subgraphs*.

Proposition 3.1 *Given a graph G, a parent subgraph S_p and a children subgraph S_c, we denote S_p and S_c's match instances set as $\mathcal{M}_p$ and $\mathcal{M}_c$, respectively. Then, we have $m_p \subset m_c$: $\exists m_p \in \mathcal{M}_p$, for $\forall m_c \in \mathcal{M}_c$. That is the matched instances of children subgraphs m_c will always contain a matched instance of parent subgraphs m_p. Thus, m_c can be efficiently identified by incrementally extending m_p.*

This complete genetic subgraph template search algorithm is provided in Appendix C.2.

3.3 Theoretical Analysis

Here, we aim to answer two questions: 1) how does the expressiveness of AE-aware aggregator relate to previous works; and 2) is our designed AE-aware aggregator expressive enough to capture Ego-AE feature. Previous researches mainly investigate the expressiveness of GNN through the scope of graph isomorphism test, while it is expressive power on capturing AE feature is largely unknown. Specifically, we have the following proposition about the limitations of standard MPNNs.

Proposition 3.2 *There exist graphs that have different Ego-AE sets for a given node, but MPNNs in (1) with arbitrary number of layers and hidden units cannot distinguish them.*

We provide a constructive proof in Appendix B.1. Therefore, this proposition shows MPNNs have fundamental limitations in modeling the structural role of each node's neighbors. On the contrary, we have the following theorem about the expressive power of the proposed AE-aware aggregator. The

theoretical proof of this theorem is provided in Appendix B.2. It shows our AE-aware aggregator is provably expressive in capturing Ego-AE feature.

Theorem 3.1 *For countable feature space $\mathcal{X}$, let v_a and v_b be two nodes with different AE sets. The AE-aware aggregator in (2) can discriminate two nodes by learning distinct embeddings for them.*

4 Experiments

We conduct experiments to empirically validate GRAPE's representational power on real-world datasets. We first analyze the model performance and behavior of designed modules with hand-crafted subgraph templates. Then, we investigate the feasibility of automatically searching subgraph templates with the proposed genetic algorithm.

Datasets. Three types of real-world datasets are used, i.e., academic citation networks, social networks and e-commerce co-purchase network.

- *Citation networks* [46]: We consider 2 widely used citation networks, i.e. Cora and Citeseer. In these datasets, nodes represent academic papers and (undirected) edges denote the citation links between them. Following the setting in previous work [28], we use each paper's bag-of-words vector as its node feature and the subject as its label.
- *Social networks* [49]: We use 5 real-world social networks which are collected from the Facebook friendships within 5 universities, *i.e.*, Hamilton, Lehigh, Rochester, Johns Hopkins (JHU) and Amherst. The nodes represent students and faculties. Besides, we use one-hot encoding of their gender and major as node feature, and set the labels as their enrollment years.
- *E-commerce co-purchase networks* [31]: This dataset was collected by crawling the *music* items in Amazon website. If an item a is frequently co-purchased with b, the graph contains a directed edge from a to b. We use the average ratings of items as node labels, and we set the node features as the number of reviews and downloads.

Following [59, 55], to investigate the influence of the node feature on the expressiveness of GNN, we also evaluate the models on a dummy dataset that use all-ones vector as node feature. The experiment results are provided in Appendix D.3.

Compared Methods. We compare our GRAPE with state-of-the-art GNN models, including GCN [28], GraphSAGE [21], GIN [55], GAT [50], Geniepath [34], Mixhop [1], Meta-GNN [44] and DE-GNN [32]. Specifically, GCN and GraphSAGE are two most popular GNN variants, and GIN is customized to better capture structural property. Besides, GAT and Geniepath use the attention mechanism to learn adaptive neighborhood for each node. Moreover, as more recent baselines, Mixhop, Meta-GNN and DE-GNN learn node embeddings from higher-order structural information. Specifically, Mixhop proposes difference operators on different hops of neighbors; Meta-GNN leverages predefined subgraphs to identify higher-order neighborhood; DE-GNN encodes the shortest path distance among nodes. To ensure fair comparison, we follow the optimal architectures as described in previous works, and we use the official implementations released by the authors or integrated in Pytorch platform [42].

Following the common design choices in previous works [28, 21, 50], we adopt a 2-layer architecture. The hyper-parameter tuning and detailed experiment settings are discussed in Appendix D.1. Based on the prior knowledge in related areas [4, 22], we design five subgraph templates ($S_\star$) for each domain of datasets respectively, which are described in Appendix D.2. We use same subgraph templates for Meta-GNN for fair comparison.

4.1 Benchmark Comparison

The classification accuracy of all methods are compared in Table 1. We observe that GRAPE is the best performing model across all datasets. Specifically, the performance gains are most prominent in social datasets. The improvements are smaller yet still significant on citation and E-commerce datasets. One plausible explanation is the structural features play more important roles in social network analysis. The above indicates stronger topological information can usually boost learning performance, which echos previous research in this area [55, 59, 51].

We show the computation cost of GRAPE and exemplar GNNs in terms of wall-clock training time in Figure 4. Note that both Geniepath and GAT leverage attention mechanism, which can only be trained on CPU since they cause out-of-memory error in GPU training. Besides, Meta-GNN is coupled with complex graph sampling process. Therefore, they take much more time to train and are not

Table 1: Classification accuracy on datasets with original node feature (%). The best-performing GNNs are in boldface, and the second best ones are underlined.

Model	Social					Citation		Ecomm.
	Hamilton	Lehigh	Rochester	JHU	Amherst	Cora	Citeseer	Amazon
GCN	19.4±2.0	24.0±1.2	21.1±1.5	20.5±0.8	17.0±1.4	**86.9±1.7**	**74.8±1.0**	47.4±1.3
GraphSAGE	20.5±2.0	17.8±2.2	18.5±1.8	17.1±2.5	17.8±1.6	85.6±0.9	70.3±1.3	19.6±1.0
GIN	23.7±3.1	19.0±2.0	21.2±0.9	21.5±3.5	26.3±3.8	86.5±1.2	72.6±1.5	48.5±2.5
GAT	18.3±2.1	22.7±0.9	20.2±1.6	19.8±1.4	17.7±2.2	**87.1±2.1**	74.6±1.7	39.4±0.8
Geniepath	19.1±1.5	22.9±1.0	21.7±1.1	19.8±1.4	17.5±1.7	81.2±1.5	69.8±1.7	57.9±0.8
Meta-GNN	22.9±1.8	24.3±2.3	23.2±0.5	27.3±2.9	23.5±2.2	86.8±1.1	74.4±1.1	56.6±1.2
Mixhop	19.1±0.1	23.2±0.2	18.0±0.0	18.3±0.1	17.0±0.1	80.9±0.7	72.9±0.8	57.4±0.8
DE-GNN	21.7±2.5	24.9±2.1	18.0±0.0	19.8±1.7	18.9±2.2	31.9±0.0	39.1±2.3	58.1±0.1
GRAPE	**28.1±2.1**	**27.3±3.8**	**25.0±1.8**	**34.6±1.3**	**32.6±2.2**	87.1±1.8	74.6±1.5	**58.6±0.4**

(a) Wall-clock time   (b) Weights on subgraphs   (c) Weights on Ego-AE sets

Figure 4: Illustrating the wall-clock time for training different GNN variants the *Lehigh* datasets and the attention weights learned by GRAPE.

comparable to other models. In Figure 4 (a), we observe GRAPE takes comparable time to train on the example dataset as the classic GNN variants of Mixhop and GraphSAGE, which demonstrates the efficiency of our model. The theoretical time complexity analysis is provided in Appendix C.3.

Besides, we also analyze the learned squeeze-and-excitation weights on each subgraph template and Ego-AE set. From Figure 4 (b), we observe the weight is significantly skewed to edge template S_1 in first layer, while it distributes more evenly on more complex templates in the second layer. Figure 4 (c) shows the AE-aware aggregator can effectively distinguish the neighboring nodes with different structural roles. For example, in Lehigh dataset, GRAPE assigns lower weights to the Ego-AE set of ego node $\{u_1\}$ and higher weights to the AE set of neighbors $\{u_2\}$ on edge template S_1, while the weights distribute more evenly between $\{u_1\}$ and $\{u_2, u_3\}$ on triangle template S_3.

4.2 Case Study on AE-aware Aggregators

We conduct a case study to better understand how the AE-aware aggregators contribute to GRAPE. Specifically, we first randomly select a node v_c in *Lehigh* dataset that is wrongly classified by all GNN variants except GRAPE, and then analyze its 2-hop neighborhood $\mathcal{N}^2(v_c)$ and the neighboring nodes that match triangle template S_3 and 4-clique template S_5 in Figure 5 and Table 2. We observe that there are 3,600 nodes in $\mathcal{N}^2(v_c)$ and they distribute evenly on multiple labels, which not only might confuse MPNNs but also tend to cause over-smoothness problem [33]. On the other hand, both templates S_3 and S_5 significantly reduce the neighborhood size, and the percentage of neighbors that have same labels as v_c increases from 19.7% in $\mathcal{N}^2(v_c)$ (ranked 3^{rd}) to 45.3%~46.0% in $\mathcal{A}_{3,2}(v_c)$ and $\mathcal{A}_{5,2}(v_c)$ (ranked 1^{st}). It shows the AE-aware aggregator can successfully capture the "social homophily" effect, where the nodes in tightly connected communities, e.g., triangle and 4-clique structure, tend to have similar property [39].

Table 2: The number of nodes and most frequent labels in v_c's 2-hop neighborhood and Ego-AE sets.

	# nodes	The percentage of top 5 labels (v_c's label is 11)
2-hop neigh. $\mathcal{N}^2(v_c)$	3,600	13 (23.2%), 12 (21.8%), **11 (19.7%)**, 10 (17.3%), 14 (12.9%)
Ego-AE set $\mathcal{A}_{3,2}(v_c)$	46	**11 (45.3%)**, 10 (17.2%), 12 (14.1%), 13 (12.5%), 9 (7.8%)
Ego-AE set $\mathcal{A}_{5,2}(v_c)$	222	**11 (46.0%)**, 12 (24.9%), 10 (13.8%), 13 (11.0%), 9 (2.8%)

(a) 2-hop neighbors (inset is 100 random samples)

(b) Matched with S_3

(c) Matched with S_5

Figure 5: Case study of a node v_c in *Lehigh* dataset. The ego node v_c is positioned in the center of each subfigure and circled with red box. Node colors represent the ground-truth label.

4.3 Subgraph Template Search

We evaluate the genetic subgraph template search algorithm on the social dataset. Specifically, we initialize GRAPE model with three simplest subgraph template, *i.e.*, edges. Then, we run the genetic subgraph search algorithm to optimize the subgraph templates. We compare our algorithm with two baseline methods: 1) Genetic + ESU, which replaces the incremental subgraph matching algorithm in our genetic framework with a widely adopted baseline method, *i.e.*, *ESU* [52]; 2) Random + ESU: search randomly initialized subgraph templates with *ESU*. Besides, we also add a Bayesian Optimization (BO) + ESU baseline, which uses the the classic Bayesian optimization to search for optimal subgraph templates [56]. We use the BO model implemented in Hyperopt framework [5].

The optimization results are shown in Figure 6 and Table 3. Specifically, Table 3 shows the proposed Genetic method (Genetic + INC.) outperform all three baselines across all the datasets. Our genetic framework generates 3.0∼8.0% performance gain over the initialized simple edge template within 3000 seconds, which is 0.6∼2.8% higher compared with the best performing baseline. Moreover, the optimized performance is comparable with the hand-crafted subgraph templates in Table 1.

Table 3: Classification accuracy (%) after 3000 seconds optimization and computation time (seconds) composition per genetic generation.

		Hamilton	Lehigh	Rochester	JHU	Amherst
Classification Accuracy (%)	Edge Template (Init.)	25.8	23.3	22.6	26.0	28.3
	Random+ESU	29.2	24.5	24.8	26.0	28.3
	BO+ESU	30.1	25.0	24.6	26.2	29.5
	Genetic+ESU	31.0	27.0	25.0	27.5	33.0
	Genetic+INC.	33.8	27.9	25.6	30.3	34.5
Time Composition (Seconds)	ESU Matching	648.7	889.4	2592.0	1389.2	1357.1
	INC. Matching	24.0	55.3	134.3	129.9	124.6
	Model Evaluation	20.9	33.7	45.0	31.5	18.1

Besides, Figure 6 shows a case study of efficiency and searched subgraph templates of the proposed genetic algorithm. We observe that our Genetic method can generate similar prediction accuracy compared to the hand-craft subgraph templates in reasonable search time and it can output novel subgraph template design. These results combined to suggest that the Genetic method can indeed learn good performing and data-dependent subgraph templates, which greatly reduces the barrier of subgraph template design.

(a) Search efficiency.   (b) Subgraph templates.

Figure 6: Effectiveness of the proposed genetic algorithm on the *Lehigh* Dataset.

5 Conclusion

In this paper, we design a theoretical framework to examine GNN's expressiveness through the lens of structural equivalence, *i.e.*, Ego-AE. Besides, we prove that MPNNs and popular GNN variants have fundamental limitations in capturing this important structural property. Moreover, we propose a provably expressive GNN model, *i.e.*, GRAPE, which effectively extend GNN's

capability in modeling structural roles. We also design a genetic subgraph template search algorithm to automatically optimize the model architecture. Experiments on real-world datasets show consistent performance gain of the proposed methods. As for the future works, we will evaluate our model on more application domains and the efficiency of the genetic subgraph template search algorithm might need further improvement.

References

[1] Sami Abu-El-Haija, Bryan Perozzi, Amol Kapoor, Nazanin Alipourfard, Kristina Lerman, Hrayr Harutyunyan, Greg Ver Steeg, and Aram Galstyan. Mixhop: Higher-order graph convolutional architectures via sparsified neighborhood mixing. *arXiv preprint arXiv:1905.00067*, 2019.

[2] Nesreen Ahmed, Ryan Anthony Rossi, John Lee, Theodore Willke, Rong Zhou, Xiangnan Kong, and Hoda Eldardiry. Role-based graph embeddings. *IEEE Transactions on Knowledge and Data Engineering*, 2020.

[3] John E Beasley and Paul C Chu. A genetic algorithm for the set covering problem. *European journal of operational research*, 94(2):392–404, 1996.

[4] Austin R Benson, David F Gleich, and Jure Leskovec. Higher-order organization of complex networks. *Science*, 353(6295):163–166, 2016.

[5] James Bergstra, Dan Yamins, David D Cox, et al. Hyperopt: A python library for optimizing the hyperparameters of machine learning algorithms. In *Proceedings of the 12th Python in science conference*, volume 13, page 20. Citeseer, 2013.

[6] Giorgos Bouritsas, Fabrizio Frasca, Stefanos Zafeiriou, and Michael M Bronstein. Improving graph neural network expressivity via subgraph isomorphism counting. *arXiv preprint arXiv:2006.09252*, 2020.

[7] Charles J Colbourn and Kellogg S Booth. Linear time automorphism algorithms for trees, interval graphs, and planar graphs. *SIAM Journal on Computing*, 10(1):203–225, 1981.

[8] Benoît Colson, Patrice Marcotte, and Gilles Savard. An overview of bilevel optimization. *Annals of operations research*, 153(1):235–256, 2007.

[9] Luigi P Cordella, Pasquale Foggia, Carlo Sansone, and Mario Vento. A (sub) graph isomorphism algorithm for matching large graphs. *IEEE transactions on pattern analysis and machine intelligence*, 26(10):1367–1372, 2004.

[10] Gabriele Corso, Luca Cavalleri, Dominique Beaini, Pietro Liò, and Petar Veličković. Principal neighbourhood aggregation for graph nets. *arXiv preprint arXiv:2004.05718*, 2020.

[11] Charles Darwin. *The origin of species*. PF Collier & son New York, 1909.

[12] Nima Dehmamy, Albert-László Barabási, and Rose Yu. Understanding the representation power of graph neural networks in learning graph topology. In *NeurIPS*, pages 15387–15397, 2019.

[13] Claire Donnat, Marinka Zitnik, David Hallac, and Jure Leskovec. Learning structural node embeddings via diffusion wavelets. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1320–1329, 2018.

[14] Martin G Everett. Role similarity and complexity in social networks. *Social Networks*, 7(4):353–359, 1985.

[15] Martin G Everett, John P Boyd, and Stephen P Borgatti. Ego-centered and local roles: A graph theoretic approach. *Journal of Mathematical Sociology*, 15(3-4):163–172, 1990.

[16] Noah E Friedkin and Eugene C Johnsen. Social positions in influence networks. *Social networks*, 19(3):209–222, 1997.

[17] Adrien Friggeri, Guillaume Chelius, and Eric Fleury. Triangles to capture social cohesion. In *2011 IEEE Third International Conference on Privacy, Security, Risk and Trust and 2011 IEEE Third International Conference on Social Computing*, pages 258–265. IEEE, 2011.

[18] Vikas K Garg, Stefanie Jegelka, and Tommi Jaakkola. Generalization and representational limits of graph neural networks. *arXiv preprint arXiv:2002.06157*, 2020.

[19] Justin Gilmer, Samuel S Schoenholz, Patrick F Riley, Oriol Vinyals, and George E Dahl. Neural message passing for quantum chemistry. In *ICML*, pages 1263–1272. JMLR. org, 2017.

[20] John Grefenstette, Rajeev Gopal, Brian Rosmaita, and Dirk Van Gucht. Genetic algorithms for the traveling salesman problem. In *Proceedings of the first International Conference on Genetic Algorithms and their Applications*, volume 160, pages 160–168. Lawrence Erlbaum, 1985.

[21] Will Hamilton, Zhitao Ying, and Jure Leskovec. Inductive representation learning on large graphs. In *NIPS*, pages 1024–1034, 2017.

[22] Robert A Hanneman and Mark Riddle. Introduction to social network methods, 2005.

[23] Kurt Hornik, Maxwell Stinchcombe, Halbert White, et al. Multilayer feedforward networks are universal approximators. *NN*, 2(5):359–366, 1989.

[24] Christopher R Houck, Jeff Joines, and Michael G Kay. A genetic algorithm for function optimization: a matlab implementation. *Ncsu-ie tr*, 95(09):1–10, 1995.

[25] Jie Hu, Li Shen, Samuel Albanie, Gang Sun, and Enhua Wu. Squeeze-and-excitation networks. *IEEE TPAMI*, 2017.

[26] Jie Hu, Li Shen, and Gang Sun. Squeeze-and-excitation networks. In *CVPR*, pages 7132–7141, 2018.

[27] Hong Huang, Jie Tang, Sen Wu, Lu Liu, and Xiaoming Fu. Mining triadic closure patterns in social networks. In *WWW*, pages 499–504, 2014.

[28] Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. In *ICLR*, 2016.

[29] Johannes Klicpera, Janek Groß, and Stephan Günnemann. Directional message passing for molecular graphs. *arXiv preprint arXiv:2003.03123*, 2020.

[30] Elizabeth A Leicht, Petter Holme, and Mark EJ Newman. Vertex similarity in networks. *Physical Review E*, 73(2):026120, 2006.

[31] Jure Leskovec, Lada A Adamic, and Bernardo A Huberman. The dynamics of viral marketing. *ACM Transactions on the Web (TWEB)*, 1(1):5–es, 2007.

[32] Pan Li, Yanbang Wang, Hongwei Wang, and Jure Leskovec. Distance encoding: Design provably more powerful neural networks for graph representation learning. In *Advances in Neural Information Processing Systems*, volume 33, 2020.

[33] Qimai Li, Zhichao Han, and Xiao-Ming Wu. Deeper insights into graph convolutional networks for semi-supervised learning. In *AAAI*, 2018.

[34] Ziqi Liu, Chaochao Chen, Longfei Li, Jun Zhou, Xiaolong Li, Le Song, and Yuan Qi. Geniepath: Graph neural networks with adaptive receptive paths. In *AAAI*, volume 33, pages 4424–4431, 2019.

[35] Pablo Ribalta Lorenzo, Jakub Nalepa, Michal Kawulok, Luciano Sanchez Ramos, and José Ranilla Pastor. Particle swarm optimization for hyper-parameter selection in deep neural networks. In *Proceedings of the genetic and evolutionary computation conference*, pages 481–488, 2017.

[36] Francois Lorrain and Harrison C White. Structural equivalence of individuals in social networks. *Journal of mathematical sociology*, 1(1):49–80, 1971.

[37] Joseph J Luczkovich, Stephen P Borgatti, Jeffrey C Johnson, and Martin G Everett. Defining and measuring trophic role similarity in food webs using regular equivalence. *Journal of Theoretical Biology*, 220(3):303–321, 2003.

[38] Brendan D McKay and Adolfo Piperno. Practical graph isomorphism, ii. *Journal of Symbolic Computation*, 60:94–112, 2014.

[39] Miller McPherson, Lynn Smith-Lovin, and James M Cook. Birds of a feather: Homophily in social networks. *Annual review of sociology*, 27(1):415–444, 2001.

[40] Mark S Mizruchi. Cohesion, equivalence, and similarity of behavior: A theoretical and empirical assessment. *Social networks*, 15(3):275–307, 1993.

[41] Christopher Morris, Martin Ritzert, Matthias Fey, William L Hamilton, Jan Eric Lenssen, Gaurav Rattan, and Martin Grohe. Weisfeiler and leman go neural: Higher-order graph neural networks. In *AAAI*, volume 33, pages 4602–4609, 2019.

[42] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, et al. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, pages 8024–8035, 2019.

[43] Leonardo FR Ribeiro, Pedro HP Saverese, and Daniel R Figueiredo. struc2vec: Learning node representations from structural identity. In *Proceedings of the 23rd ACM SIGKDD international conference on knowledge discovery and data mining*, pages 385–394, 2017.

[44] Aravind Sankar, Xinyang Zhang, and Kevin Chen-Chuan Chang. Meta-gnn: Metagraph neural network for semi-supervised learning in attributed heterogeneous information networks. *ASONAM. IEEE*, pages 137–144, 2019.

[45] Ryoma Sato, Makoto Yamada, and Hisashi Kashima. Approximation ratios of graph neural networks for combinatorial problems. In *NeurIPS*, pages 4083–4092, 2019.

[46] Prithviraj Sen, Galileo Namata, Mustafa Bilgic, Lise Getoor, Brian Galligher, and Tina Eliassi-Rad. Collective classification in network data. *AI Magazine*, 29(3):93–93, 2008.

[47] Malcolm K Sparrow. A linear algorithm for computing automorphic equivalence classes: the numerical signatures approach. *Social Networks*, 15(2):151–170, 1993.

[48] Jacobo Torán. On the hardness of graph isomorphism. *SIAM Journal on Computing*, 33(5):1093–1108, 2004.

[49] Amanda L Traud, Peter J Mucha, and Mason A Porter. Social structure of facebook networks. *Physica A: Statistical Mechanics and its Applications*, 391(16):4165–4180, 2012.

[50] Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. Technical report, arXiv preprint arXiv:1710.10903, 2017.

[51] Xiao Wang, Meiqi Zhu, Deyu Bo, Peng Cui, Chuan Shi, and Jian Pei. Am-gcn: Adaptive multi-channel graph convolutional networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 1243–1253, 2020.

[52] Sebastian Wernicke and Florian Rasche. Fanmod: a tool for fast network motif detection. *Bioinformatics*, 22(9):1152–1153, 2006.

[53] Zonghan Wu, Shirui Pan, Fengwen Chen, Guodong Long, Chengqi Zhang, and S Yu Philip. A comprehensive survey on graph neural networks. *IEEE TNNLS*, 2020.

[54] Lingxi Xie and Alan Yuille. Genetic cnn. In *Proceedings of the IEEE international conference on computer vision*, pages 1379–1388, 2017.

[55] Keyulu Xu, Weihua Hu, Jure Leskovec, and Stefanie Jegelka. How powerful are graph neural networks? *arXiv preprint arXiv:1810.00826*, 2018.

[56] Quanming Yao, Mengshuo Wang, Yuqiang Chen, Wenyuan Dai, Yu-Feng Li, Wei-Wei Tu, Qiang Yang, and Yang Yu. Taking human out of learning applications: A survey on automated machine learning. *arXiv preprint arXiv:1810.13306*, 2018.

[57] Xin Yao. Evolving artificial neural networks. *Proceedings of the IEEE*, 87(9):1423–1447, 1999.

[58] Rex Ying, Dylan Bourgeois, Jiaxuan You, Marinka Zitnik, and Jure Leskovec. Gnn explainer: A tool for post-hoc explanation of graph neural networks. *arXiv preprint arXiv:1903.03894*, 2019.

[59] Jiaxuan You, Rex Ying, and Jure Leskovec. Position-aware graph neural networks. In *ICML*, pages 7134–7143, 2019.

[60] Manzil Zaheer, Satwik Kottur, Siamak Ravanbakhsh, Barnabas Poczos, Russ R Salakhutdinov, and Alexander J Smola. Deep sets. In *NIPS*, pages 3391–3401, 2017.