Learning Visual Representation with Synthetic Images and Topologically-defined Labels

Abstract

We propose a scheme for neural networks to learn visual representation with synthetic images and mathematically-defined labels that capture topological information. To verify that the model acquires a different visual representation than with the usual supervised learning with manually-defined labels, we show that the models pretrained with our scheme can be finetuned for image classification tasks to achieve an improved convergence compared to those trained from scratch. Convolutional neural networks, built upon iterative local operations, are good at learning local features of the image, such as texture, whereas they tend to pay less attention to larger structures. Our method provides a simple way to encourage the model to learn global features through a specifically designed task based on topology. Furthermore, our method requires no real images nor manual labels; hence it sheds light on some of the lately concerned topics in computer vision, such as the cost and the fairness in data collection and annotation.

1 Introduction

Self-supervised learning (SSL) has seen a great success both practically and scientifically by providing a scheme to train neural networks without human annotated labels and by showing the similarity to humans in the learning process and the learned representation. However, there are still large gaps between SSL and human learning. In visual representation, convolutional neural networks (CNNs) are famously known to be "shortsighted" by being biased to textural information (Geirhos et al., 2019). Most image features, hand-crafted or obtained in a data-driven manner, are *local* in the sense that they are computed from small patches in the image. For example, convolution, a typical and versatile form of the operation used to construct various image features, is local unless a huge kernel is used. Although local features can be aggregated by applying reduction operations such as the mean, the global information obtained in this way is limited. One way to capture global characteristics of images is to introduce a new model architecture. The attention mechanism has enabled to learn global image features in a data-driven manner as demonstrated by Vision Transformer (Dosovitskiy et al., 2021). Another way, which we concern in this paper, is to device a new training scheme, which works with virtually any model architecture with little modification. Topology is a study of shapes whose ultimate goal is to classify shapes by their topological types. Topologists have invented various *topological invariants* that can discern different shapes. Our idea is to design a task of computing topological invariants from an input image by a neural network so that the neural network is encouraged to learn visual representation that is relevant to the topology of the image. In contrast to the popular SSL schemes, which are largely based on *learning the distribution* of real (plausible) images, our method is based on *approximating the mathematical computation* of a topological invariant, called persistent homology, of synthesised images.

Persistent homology (PH), one of the main tools of the emerging field of *Topological Data Analysis* (TDA), provides efficient machinery for computing global topological features of data mathematically (Adams & Moy, 2021). It has been proved to be practically useful for image processing such as classification (Dunaeva et al., 2016) and segmentation (Tanabe et al., 2021). In recent years, applications of persistent homology have expanded to many areas in science and led to new discoveries (Giunti, 2021), but in most cases, it is used just as yet another feature extractor. In view of TDA, we proceed a step further and ask *if we can teach topology to a neural network* so that

the model learns low-level image features together with the mechanism for computing high-level topological features from low-level features. Answering this question affirmatively would lead to the acquisition of more abstract and generalisable representation by the model. More precisely, our scheme is to train the model with regression of the vectorised persistent homology for synthesised images. Through this task, the model is expected to learn relevant visual representation required to approximate persistent homology. We demonstrate the validity of our scheme by experiments showing that a CNN pretrained by the proposed method can be finetuned for image classification tasks to show an improved convergence compared with one trained from scratch.

It is also worth pointing out that our scheme does not rely on real images nor labels, but uses mathematically generated images annotated with mathematically defined features. In this way, it is free from human bias which lies not only in the manual annotation but also the image themselves; photos reflect the present world and the view of the photographer. In fact, the models trained with ImageNet by SSL, even without human annotated labels, are known to be subject to bias (Steed & Caliskan, 2021).

2 RELATED WORK

The proposed method is built on three key ingredients, which we discuss in this section. We introduce some novel ideas to each of the three and combine them to develop our scheme.

2.1 SELF-SUPERVISED LEARNING ON IMAGES

Self-supervised learning tasks, which we call pretext tasks, are designed to learn image features without manually-defined labels. There are three major types of pretext tasks. The first task is to tell if given two images come from the same image or not, where variations of images are generated by applying transformations in spacial and colour domains (see Jaiswal et al. (2021) for a survey). The second task is to undone degradation, such as adding noise and masking, and reconstruct the original image. The third is similar to the second one but to perform a pair of (approximately) invertible processes, such as compression-expansion, as represented by the celebrated autoencoder (Hinton & Salakhutdinov, 2006). All of the three tasks demand the model to acquire high-level representation of the images. The main objective of these methods lies in, more or less, capturing the distribution of the training data; to be good at in-painting and compression, one has to find a low-dimensional manifold which models the training data well. We propose another type of task that put more emphasis on the computation process rather than the distribution of the data. When the computation is based on a certain mathematical structure of the data, a model will be incentivised to focus on the structure through learning the task. Our pretext task is to approximate the computation of a topological invariant, called persistent homology, of the image. Persistent homology can be computed mathematically from the data and used as the label for a regression task. It is also notable that our pretext task does not rely on semantics or human perception but solely on mathematics. This allows us to use synthetic images almost meaningless to human eyes, and make the procedure completely free of real data.

2.2 LEARNING WITH SYNTHETIC IMAGES

Even though SSL saves the annotation costs, the preparation of training data is still a vexing problem. Publicly available datasets can be of low-quality, subject to bias, and violated usage rights and privacy. ImageNet, one of the most popular large-scale datasets, suffers from fairness issues (Yang et al., 2020), and there have been a growing interest in the fairness of machine learning Mehrabi et al. (2021). Steed & Caliskan (2021) points out that even models trained on ImageNet without using labels but with SSL learns racial, gender, and intersectional biases from the way people are stereotypically portrayed on the web. No matter how much care and attentions are paid for data collection, it is impossible to be free from all kinds of these issues as long as real images are used. Using generative adversarial networks (GANs) to generate image datasets for training is a popular and successful strategy to mitigate the situation (Besnier et al., 2020), but GANs are also trained with natural images and cannot avoid above-mentioned problems. A promising approach is to use algorithmically synthesised images. Formula-driven Supervised Learning introduced in Kataoka et al. (2020) considers pretraining with synthetic images generated by a mathematical formula. The labels

are assigned according to the parameters of the image generation. Several different formuli are tested and an iterated function system, which generates fractal images, is found to be effective. A wider variety of image generation methods have been tested since then (Baradad et al., 2021; Kataoka et al., 2022). To see how synthetic images are helpful in acquiring image features is interesting also in terms of cognitive science.

In this paper, we also use synthetic images, which are not very meaningful for human eyes, and try to learn topological features from them. One technical difference from the Formula-driven Supervised Learning is how the labels are generated. Instead of fixed labels associated with the image generation model parameters, we generate labels by a mathematical formula computed directly from the images, which has advantage of being applicable to any image generation model. The labels encode topological features (persistent homology, in our paper) and the model is encouraged to learn image features that are relevant to approximate the topological features.

2.3 PERSISTENT HOMOLOGY FOR IMAGE ANALYSIS

Persistent homology has an unusual input and output when it is seen as a feature extractor. PH takes a series of nested topological spaces and outputs a multiset of intervals of the real numbers. We view an image as a function $f : X \to \mathbb{R}$ defined over a rectangular domain X, and we obtain a series of nested spaces

$$\emptyset \subset X_{t_1} \subset X_{t_2} \subset \cdots \subset X_{t_m} = X, \quad X_{t_i} = \{(x, y) \in X \mid f(x, y) \leq t_i\},$$

where $t_m = \max(f)$. Applying the homology functor $H_d(-)$ with the coefficients in the field $\mathbf{F}_2$ with two elements, we obtain the corresponding sequence of $\mathbf{F}_2$ vector spaces, and this sequence is by definition the persistent homology $PH_d(X, f)$ of the pair (X, f). $PH_d(X, f)$ can be written as the direct sum of so-called the interval module having the form

$$0 \longrightarrow \cdots \longrightarrow 0 \longrightarrow \mathbf{F}_2 \longrightarrow \cdots \longrightarrow \mathbf{F}_2 \longrightarrow 0 \longrightarrow \cdots \longrightarrow 0$$

$$\| \qquad\qquad \cap \qquad\quad \cap \qquad\qquad\quad \cap \qquad\qquad \cap \qquad\qquad\quad \cap$$

$$H_d(\emptyset) \to \cdots \to H_d(X_{t_{i-1}}) \to H_d(X_{t_i}) \to \cdots \to H_d(X_{t_{j-1}}) \to H_d(X_{t_j}) \to \cdots \to H_d(X).$$

We denote the summand by the interval $[t_i, t_j)$. When $d = 0$, it may happen that $j - 1 = m$, in which case we represent the summand by $[t_i, \infty)$. See Fig. 1 for an example of PH of an image. To sum up, PH takes a function $f : X \to \mathbb{R}$ and outputs a multiset of intervals. The alien output as multiset can be transformed into a fixed-length vector using vectorisation techniques (Adams et al., 2017; Bubenik, 2015; Chung & Lawson, 2021) so that it fits in the standard machine learning pipeline.

CNNs tend to be biased towards texture when trained with a classification task of natural images (Geirhos et al., 2019). In contrast, human perception relies much on the global shape of the image content. Therefore, it would be beneficial for a model to learn global topological features as well as local features. This is supported by an experiment in which combining PH with other descriptors results in an increased performance in object recognition (Li et al., 2014), showing that PH provides a shape feature that is complementary to conventional ones. There are previous studies to assimilate PH into deep learning. To deal with PH with neural networks, a parametric representation of persistence homology with learnable parameters is introduced in Hofer et al. (2017) so that a task-optimal vectorisation is obtained in a data-driven manner. Dedicated architectures of CNNs are designed in Som et al. (2020) for computing vectorised PH of time-series and point clouds in the form of the persistence image. The topological autoencoder (Moor et al., 2020) learns a latent space of a point cloud that preserves the topological structure in terms of persistent homology. Our idea is based on the fact that one has to acquire a certain high-level image representation that encodes global topological features in order to compute PH, and this makes a good pretext task for training a neural network.

3 METHOD

Our proposed scheme can be viewed as a type of SSL in which desired image features are learned by solving a pretext task. The pretext task does not require any natural images, but synthesised images (Sec. 3.1) are used. The model learns the input-output relation (regression) for the image and the

Figure 1: The figure shows the sublevel sets of an image for different ranges of t. For an image, persistent homology consists of two components $PH_0(X, f)$ and $PH_1(X, f)$, which respectively records the transition of islands and holes in the sublevel sets under different threshold. In this example, $PH_0(X, f) = \{[0, 1), [0, \infty)\}$, where the interval $[0, 1)$ corresponds to the connected component consisting of the single pixel at the bottom-left corner in the left-most figure, which is merged to the other connected component in the central figure. Since this feature exists for $t \in [0, 1)$, it is represented by the interval $[0, 1)$, and said to have the birth time 0, death time 1, and life time $1(= 1 - 0)$. Similarly, the other component that exists for $t \geq 0$ is represented by $[0, \infty)$, which has the infinite life time. Similarly, $PH_1(X, f) = \{[1, 2)\}$ whose element represents the hole surrounding the two pixels with the value 2 in the central figure. This hole disappears in the right-most figure, and so, it is represented by $[1, 2)$. Persistent homology of an image records the topological features, such as islands and holes, with the threshold in which the features emerge and disappear. The distinctive idea of *persistence* is to trace the emergence and disappearance rather than computing features at each threshold separately.

Figure 2: The overall structure of the proposed method.

corresponding image feature vector computed through persistent homology (Sec. 3.2). The model is expected to learn relevant image features which are required for approximating PH. Intuitively, the procedure is described as follows. The teacher knows topology and gives problems to the student with the answer computed mathematically. The student tries to guess how the teacher's answer is computed and search for clues in the image. So it is not guaranteed that the student learns how to compute PH in the way it is defined mathematically, but the student collects image features that are helpful to approximate PH, and those features are necessarily global and topological, as so is PH. Similarly, any algorithmically computable vector associated with the image can be used. However, we particularly choose PH as our image feature since (1) it captures global topological characteristics of the image and is known to have discriminative power (Adams et al., 2017), (2) it has guaranteed stability (including robustness against the change in the pixel values and the invariance against isometric geometric transformations (Cohen-Steiner et al., 2005; Skraba & Turner, 2021)), and (3) it is defined for any image and is efficiently computed (Kaji et al., 2020). We elaborate on these points below.

(1) The image features obtained by PH are topological and global, whereas the features extracted through iterated convolutions by CNNs are mostly local. We expect that learning abstract topological

features first in pretraining and local features such as texture in finetuning will have complementary effects.

(2) Learning invariant features is one of the main principles in visual representation learning (Misra & Maaten, 2020). PH gives the same labelling for images that are rotated and reflected, and similar labelling for images with certain types of pixel values alteration, which is guaranteed by the stability theorems. The regression of PH encourages the model to learn those invariances. Furthermore, when a certain transformation of the image which changes its PH is applied, the model is asked to learn the *change in the label*; persistent homology is *functorial*. That is, the transformation in the input is systematically reflected by the transformation in the output, and the model is asked to learn this higher relation as well when trained with data augmentation such as by affine transformations.

(3) For randomly generated images, we cannot rely on semantics of the images that is meaningful for human eyes to design the pretext task. We do not have this problem with PH, which is mathematically defined. Moreover, computation of PH is cheap (Appendix A.1) so that it does not increase overall pretraining time substantially.

We evaluate our scheme[1] by finetuning the model pretrained by our scheme for an image classification task with some popular datasets (Figure 2 depicts a schema). We finetune the model with the training dataset and the performance in terms of the convergence of the classification accuracy for the validation dataset is measured. At the beginning of finetuning, we replace the fully-connected layer with a randomly initialised one. We remark that the topological features encoded by persistent homology alone are insufficient for image classification tasks, and they are meant to complement local features such as texture. For this reason, the weights of all layers are updated during finetuning.

The experiments are conducted with our codes publicly available under the MIT license at `https://XXX` (the URL is removed temporarily for the double-blind review. The codes are found in supplemental materials.).

3.1 IMAGE GENERATION

We use the following frequency-based random image generation method to create a dataset for pretraining. We choose this image generation model mainly because it is computationally inexpensive and produces images with various frequency profiles (see also Appendix A.3). In particular, the resulting images (see Fig. 3) contain patterns at different scales, and hence, have rich topological information.

1. Create an array h of dimension 256×256, where the values are drawn independently from the uniform distribution on $[0, 1]$.

2. For a frequency parameter β drawn from the uniform distribution on $[1, 2]$, set

$$g(x, y) = \text{Re}\left(\text{iFFT}\left(\frac{\text{FFT}(h)(x, y)}{((x+1)^2 + (y+1)^2)^\beta}\right)\right), \tag{1}$$

where FFT is the 2D discrete Fourier transform and iFFT is its inverse, and Re denotes the real part of a complex number.

3. With a probability of p, which we set to 0.5, binarise g by Otsu's thresholding Otsu (1979).

4. Repeat the process three times independently to create a colour image with RGB channels.

5. Convert the image into greyscale with a probability $q = 0.5$.

The random parameter β controls how fast the high-frequency components decay. The effect of the choices for the hyper-parameters p, q and the range of β does not seem to be large and we haven't done a comprehensive search. We have only checked that setting $p = 0.5$ and $q = 0.5$ is slightly better than $p = 0, 1$ or $q = 0, 1$.

3.2 PH LABEL COMPUTATION

The images labels for the pretext regression task are computed using persistent homology. There are various ways to utilise PH to encode topological information of images (see Turkeš et al. (2021);

---

[1]Some more experiments which corroborate or complement this evaluation experiment are given in Appendix A.2.

Figure 3: Two examples of synthesised images and their signed distance functions. Persistent homology is computed for the sequence of the sublevel sets for the signed distance function.

Garin & Tauzin (2019) for a survey). Our choice aims at extracting shapes contained in the image by their contours and capturing its topological features such as connected components and holes, together with their scale. To this end, a nested sequence of spaces, which is the input for PH, is built from the image by the following procedure: (1) Convert the image into greyscale (2) Binarise it using Otsu's thresholding (Otsu, 1979) (3) Compute the signed distance function (see Figure 3)

$$\phi(x, y) = \begin{cases} -\min_{(x',y'):\text{background}} |(x, y) - (x', y')| \\ \quad \text{if } (x, y) \text{ is foreground} \\ \min_{(x',y'):\text{foreground}} |(x, y) - (x', y')| \\ \quad \text{if } (x, y) \text{ is background.} \end{cases} \tag{2}$$

(4) Finally, obtain the sequence of the sublevel sets $X_t = \{(x, y) \in X \mid \phi(x, y) \leq t\}$, where X is the domain of the original image; that is, the rectangular grid of the size of the image. This procedure gives a bounded nested sequence satisfying $X_s \subset X_t$ when $s < t$ and $X_{-D} = \emptyset, X_D = X$, where D is the length of the diagonal of the image. The PH (with the coefficients in the field $\mathbf{F}_2$) of this sequence is computed by the software called Cubical Ripser (Kaji et al., 2020). An important remark is that instead of considering the sublevel sets with respect to the original (greyscaled) pixel values, we consider the sublevel sets of the signed distance function. In this way, the resulting PH captures the metric-aware structure of the original image; the scale of topological features are encoded as life time in persistent homology.

The degree 0 and 1 parts of persistence homology are vectorised separately and concatenated into a single vector, which serves as the label for the image. We test four different vectorisation techniques; the persistence image (Adams et al., 2017), the persistence landscape (Bubenik, 2015), the Betti number curve (Chung & Lawson, 2021), and the birth-life histogram. The last one is simply the histograms of the birth time (the left end of the interval) and the life time (the length of the interval) of the persistence homology for each degree. All the vectorisation techniques have hyper-parameters for the "resolution" of the output, which are determined from the specified output dimension in our experiments.[2] In most of the experiments, the output dimension is fixed to 200. We allocate the same dimension for the degree 0 and 1 persistence homology so that we obtain a pair of 100-dimensional vectors that are concatenated to form a 200-dimensional output vector. To reduce the dynamic range and suppress overflow, the square root is taken for each coordinate of the vector. Although we may elaborate on the hyper-parameter tuning for the PH vectorisation, Tab. 1 shows that even the choice of the vectorisation techniques does not have a large impact. Therefore, we limit ourselves to an essential set of experiments to find out the nature of the scheme as detailed in Sec. 3.3.

3.3 EVALUATION RESULT

We evaluate the effect of the pretraining by looking at the convergence of the accuracy in fine-tuning for classification tasks. Along with the popular ImageNet (IMN) (Deng et al., 2009) and CIFAR100 (C100) (Krizhevsky, 2009) datasets consisting of natural images, we use the animal dataset (ANM) (Bai et al., 2009), which is of relatively small size and consists of 2,000 binary images of animal contours of various size that are labelled with 20 classes. Since no texture information is present in the animal dataset, it is suitable to verify the effect of topology learning, and is used in

---

[2]The only non-canonical choices among the standard set of hyper-parameters of the vectorisation techniques are the number of *landscape functions* for the persistence landscape and the sigma of the Gaussian kernel used in the persistence image, which we set to 2 and 1.0 respectively.

Hofer et al. (2017) for evaluation of their method of incorporating PH into deep learning. We split the animal dataset into two sets with 1,600 training images (80 images per class) and 400 validation images.

The hyper-parameters for learning are fixed in a standard manner as follows. ResNet50 network architecture is used. Input images are resized to 256×256 and then cropped randomly down to 224×224. Random horizontal flipping is applied. Both in pretraining and finetuning, the model is trained for a total of 90 epochs for the CIFAR100 dataset (90 epochs for synthesised dataset, 300 epochs for the animal dataset, 45 epochs for ImageNet) by the stochastic gradient descent with a momentum of 0.9 and weight decay of 10^{-4}. The initial learning rate is set to 0.1 for pretraining (0.01 for finetuning) and multiplied by 0.1 twice at the 1/3 and the 2/3 of the total training epochs. The batch size is set to 128.

Table 1 shows the classification accuracy of the validation dataset after each pretrained model is finetuned with the training dataset using its labels. The finetuning phase is exactly the same for all pretrained models. **Scratch** is without any pretraining. **Label** is pretrained with the training dataset using its labels.[3] That is, the model is trained twice with the training dataset but with different learning rates. The four PH-based models are pretrained with the synthetic dataset with 400,000 images described in Sec. 3.2 with different PH vectorisation targets (**PH-PI** with the persistence image, **PH-LS** with the persistence landscape, **PH-BC** with the Betti number curve, and **PH-HS** with the birth-life histogram). For comparison, a model pretrained by a popular SSL scheme, **MoCo v2** (Chen et al., 2020), with the same synthetic dataset with 400,000 images is shown. As a comparison target for pretraining with synthesised images, the results of the FractalDB-pretrained models (**FDB-1k** consists of 1,000,000 images with 1,000 classes and **FDB-10k** consists of 10,000,000 images with 10,000 classes) that are publicly available[4] are shown. The values in Tab. 1 differ slightly from the ones reported in Kataoka et al. (2020), possibly due to minor differences in the experimental settings. We also list the accuracy of the ImageNet pretrained model (IMN) that is provided as a part of PyTorch's torchvision library (version 0.10.1). Although publicly available pretrained weights are used for FDB and IMN, the hours taken for pretraining with FDB-1k and IMN are measured on the same system used for pretraining other models. For FDB-10k, the time of FDB-1k is extrapolated by simply multiplied by ten.

Since there are only 400 validation images for the animal dataset, the accuracy values fluctuate. The values listed in Tabs. 1 and 2 are the mean for the last epochs from 290 to 300. The 90 percentile falls within ± 0.6 of the mean. Moreover, to see the stability of the results, we have performed ten trials of pretraining and finetuning with different random seeds for the entry of **PH-PI** for C100 in Tab. 1, and observed that the 90 percentile falls within ± 0.3 of the mean.

The PH-pretrained models show better convergence than **Scratch** and **Label**, and comparable convergence to the FractalDB-10k-pretrained one even though the PH models are trained with a much smaller number of 400,000 images and about 70 times less computation time. All PH-pretrained models show more or less similar convergence regardless of the used PH vectorisation techniques. Among them, **PH-BC** performs the worst, and this can be attributed to the fact that only **PH-BC** does not care about the "persistence"; **PH-BC** can be computed just as the sequence of the Betti numbers of the sublevel set X_t one t at a time without considering the relation among different t's, while the other three, **PH-PI**, **PH-LS**, and **PH-HS**, capture the relation. This suggests that not only homology but also its persistence structure helps learn image representation.

Figure 4 shows the transition of the accuracy in the finetuning of the models selected from Table 1. The ImageNet-pretrained model **IMN** surpasses all other models in both training and validation. The convergence behaviour of **PH-PI** and **FDB-10k** are quite similar, sitting between **IMN** and **MoCo-v2**.

To see the effect of various parameters and the nature of our method, we conduct a few more experiments. We fix the vectorisation method to the persistence image. Unless otherwise stated, the output dimension is fixed to 200 and the size of the synthetic image dataset is fixed to 200,000.

---

[3]The deteriorated accuracy of Label for Animal compared to Scratch is likely due to over-fitting. We observe the validation loss converges quickly although to a higher value.

[4]https://github.com/hirokatsukataoka16/FractalDB-Pretrained-ResNet-PyTorch

Table 1: Classification accuracy of models pretrained with various methods. For FDB-1k, the pretrained weight file made publicly available by the authors of Kataoka et al. (2020) is used. For ImageNet, the weight file that comes with the torchvision library is used. The hours taken for pretraining is measured on a PC with a single NVIDIA RTX 3090 and an Intel Core i9-10850K.

	Scratch	Label	PH-PI	PH-LS	PH-BC	PH-HS	MoCo-v2	FDB-1k	FDB-10k	IMN
C100	69.6	70.3	78.4	78.1	76.6	77.9	71.6	75.3	78.1	85.0
ANM	80.7	80.1	91.0	90.1	89.1	90.6	85.0	84.6	85.2	93.3
IMN	70.8	NA	72.9	72.0	71.4	72.8	71.0	71.8	72.4	75.3
time	0h	3h	22h	22h	22h	21h	38h	144h	1442h	74h

Figure 4: Transition of the training and validation accuracy in the finetuning of the CIFAR100 dataset.

The impact of the choice of the vectorisation dimension of PH is assessed by varying the value among $\{100, 200, 400, 800\}$. As we observe in Tab. 2 (left), the choice affects the performance and the optimal value, in this case, is about 200. However, we guess the optimal value depends on the complexity and the dimension of the synthesised images as the vectorisation dimension controls the resolution of the discretisation of PH.

The impact of the size of the pretraining dataset is assessed by varying the size of the synthesised dataset among $\{50,000, 200,000, 400,000, 800,000\}$. As is observed in Tab. 2 (middle), the performance increases as the size gets larger. At the size of 50,000, which is the same as that of the CIFAR100 training dataset, the **PH-PI** model performs better than **Label** in Tab. 1, which is pretrained with the same number of images and iterations with the same learning rates.

Table 2: (Left) Classification accuracy of PH-PI models pretrained with different dimensions of the PH vectorisation (the dimension of the vector of the regression target). (Middle) Classification accuracy of PH-PI models pretrained with the synthesised dataset of different sizes. The values for 400k are reproduced from Tab. 1. (Right) Classification accuracy of PH-PI models pretrained with with the CIFAR100 (PH-C) and the animal (PH-A) datasets. The values for Scratch are reproduced from Tab. 1.

	100	200	400	800	50k	200k	400k	800k	Scratch	PH-C	PH-A
C100	76.8	77.7	77.4	75.0	76.1	77.7	78.4	78.8	69.6	75.3	72.4
ANM	87.4	89.9	90.5	87.5	88.6	89.9	91.0	91.6	80.7	86.5	83.2

Our pretraining scheme also works with real images in place of synthetic ones. In the next experiment, we pretrain the model with the training split of the CIFAR100 dataset (and the animal dataset) using the PH-regression task, and then finetune the model using the class label of the dataset. The result is shown in Tab. 2 (right). In this example, the setting of **Label** and **PH-C** (**PH-A**, respectively) for the CIFAR100 dataset (the animal dataset, respectively) is the same except for the label used for the pretraining; **Label** uses the class label while **PH-C** uses the label computed with the persistence image. Pretraining with PH improves the performance, indicating the benefit of learning not only from the class labels but also with topology-based labels. Comparing with the entry for 50k in Tab. 2 (middle), we see our synthetic dataset offers slightly better quality for learning topology than the

CIFAR100 dataset, which consists of the same number of 50k natural images. This could be attributed to the design of the image generation model that produces patterns at various scales. In the case of the animal dataset, pretraining with PH does not lead to a large performance gain. This may be due to the small number of training images (1,600) and the variety is quite limited. The observation agrees with the result in Tab. 2 (middle) that indicates the necessity of a certain amount of data for learning topological features.

4 LIMITATIONS

We have seen that CNNs can learn useful image features from a regression task of persistent homology. However, (vectorised) PH alone is not a strong image feature for a classification task although it captures different characteristics of images than conventional techniques. We believe adding topology is helpful but does not replace textural information that CNNs naturally learns from natural image classification. Our proposed scheme forces the model to focus on topology during pretraining; binarisation and signed distance transform applied for the computation of the PH label strip textural information off and focus on topological features with their scale. The model learns other local features only during finetuning, where topology is not paid a particular attention. Although this splitting of topology learning from conventional learning makes the analysis more controlled, it would not be the optimal strategy to learn both local and global image features if the primary goal is a better performance in practical applications.

Another limitation, which is related to the explainability just as in most deep-learning schemes, is that we are not really sure what features are learned in our method although we have designed it for learning global topological features of images. We have observed that both the training and the validation losses converge during pretraining the PH-based models, but the latter stays about twice higher than the former, indicating that the models learn to *approximate* PH but fails to learn to *compute* PH in a fully generalisable (that is, mathematical) manner. Nonetheless, we have observed that the visual representation obtained by the model pretrained by PH is quite different from those pretrained by FractalDB and ImageNet (see Appendix A.2). From a practical viewpoint, this means the model would have strengths and weaknesses depending on the downstream tasks. Detailed and controlled experiments including more than simple classification tasks should be performed to verify the usefulness of the learned features across different tasks.

5 CONCLUSION

We proposed a scheme for learning visual representations that were relevant to the topological features of images through a regression task for a mathematical function defined by persistent homology. Our method can be applied to any image dataset and virtually any neural network architecture with a small cost. Our experiment with a synthetic image dataset suggested that even images that are little meaningful for human eyes could be used for learning certain visual representation. Our main contributions are two fold: (I) We proposed a pretext task that was mathematically defined and applicable to synthetic images without labels. (II) We experimentally showed that a convolutional neural network pretrained with the pretext task acquired visual representation that was different from those obtained by the usual supervised learning.

We would like to conclude the paper with a few possible future directions to investigate. (a) Since global topological features are generally robust compared to local ones, learning them could add resistance against adversarial attacks. (b) Regressing other mathematical invariants could be used to pretrain neural networks to equip them with understanding of geometric, topological, and algebraic structures of the image. This would provide a generic method to incorporate various knowledge established by mathematicians over past centuries to deep learning research. In terms of learning with synthetic images, regressing the random parameters used in the image generation models such as in (Kataoka et al., 2020; Baradad et al., 2021) would also be interesting. (c) A theoretical question related to this work is on the relation between the neural network architecture and the learning capacity. It is known that universal-approximation-theorem-type statements have some constraints that relate topology of the target function to be learned and the width of neural networks (Johnson, 2019). It would be interesting if we could compare the way in which a CNN learns to approximate PH and the rigorous mathematical definition of PH.

REPRODUCIBILITY STATEMENT

The experiments are conducted with our codes included as supplemental materials. We will release the final code at github under the MIT license. Robustness of the numbers in the tables and figures are discussed in Section 3.3.

REFERENCES

Henry Adams and Michael Moy. Topology applied to machine learning: From global to local. *Frontiers in Artificial Intelligence*, 4:54, 2021. ISSN 2624-8212. doi: 10.3389/frai.2021.668302. URL https://www.frontiersin.org/article/10.3389/frai.2021.668302.

Henry Adams, Tegan Emerson, Michael Kirby, Rachel Neville, Chris Peterson, Patrick Shipman, Sofya Chepushtanova, Eric Hanson, Francis Motta, and Lori Ziegelmeier. Persistence images: A stable vector representation of persistent homology. *J. Mach. Learn. Res.*, 18(1):218–252, January 2017. ISSN 1532-4435.

Xiang Bai, Wenyu Liu, and Zhuowen Tu. Integrating contour and skeleton for shape classification. In *Int. Conf. Comput. Vis. Worksh.*, pp. 360–367, 2009. doi: 10.1109/ICCVW.2009.5457679. URL https://doi.org/10.1109/ICCVW.2009.5457679.

Manel Baradad, Jonas Wulff, Tongzhou Wang, Phillip Isola, and Antonio Torralba. Learning to see by looking at noise. In *Adv. Neural Inform. Process. Syst.*, 2021.

Victor Besnier, Himalaya Jain, Andrei Bursuc, Matthieu Cord, and Patrick Pérez. This dataset does not exist: training models from generated images. In *Int. Conf. Acoustics, Speech, & Sign. Process.*, pp. 1–5, 2020.

Peter Bubenik. Statistical topological data analysis using persistence landscapes. *J. Mach. Learn. Res.*, 16(1):77–102, January 2015. ISSN 1532-4435.

Aditya Chattopadhay, Anirban Sarkar, Prantik Howlader, and Vineeth N Balasubramanian. Grad-cam++: Generalized gradient-based visual explanations for deep convolutional networks. In *2018 IEEE Winter Conference on Applications of Computer Vision (WACV)*, pp. 839–847, 2018. doi: 10.1109/WACV.2018.00097.

Xinlei Chen, Haoqi Fan, Ross Girshick, and Kaiming He. Improved baselines with momentum contrastive learning. *arXiv preprint arXiv:2003.04297*, 2020.

Yu-Min Chung and Austin Lawson. Persistence curves: A canonical framework for summarizing persistence diagrams, 2021. arXiv:1904.07768v4.

David Cohen-Steiner, Herbert Edelsbrunner, and John Harer. Stability of persistence diagrams. In *Proceedings of the Twenty-First Annual Symposium on Computational Geometry*, SCG '05, pp. 263–271, New York, NY, USA, 2005. Association for Computing Machinery. ISBN 1581139918. doi: 10.1145/1064092.1064133. URL https://doi.org/10.1145/1064092.1064133.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Alexey Dosovitskiy, Lucas Beyer, Alexander Kolesnikov, Dirk Weissenborn, Xiaohua Zhai, Thomas Unterthiner, Mostafa Dehghani, Matthias Minderer, Georg Heigold, Sylvain Gelly, Jakob Uszkoreit, and Neil Houlsby. An image is worth 16x16 words: Transformers for image recognition at scale. In *Int. Conf. Learn. Represent.*, 2021. URL https://openreview.net/forum?id=YicbFdNTTy.

Olga Dunaeva, Herbert Edelsbrunner, Anton Lukyanov, Michael Machin, Daria Malkova, Roman Kuvaev, and Sergey Kashin. The classification of endoscopy images with persistent homology. *Pattern Recognition Letters*, 83:13–22, 2016. ISSN 0167-8655. doi: https://doi.org/10.1016/j.patrec.2015.12.012. URL https://www.sciencedirect.com/science/article/pii/S0167865515004353.

Adélie Garin and Guillaume Tauzin. A topological "reading" lesson: Classification of MNIST using TDA. In *Proceedings of the IEEE International Conference on Machine Learning And Applications (ICMLA)*, pp. 1551–1556. IEEE, 2019. doi: 10.1109/ICMLA.2019.00256. URL `https://doi.org/10.1109/ICMLA.2019.00256`.

Robert Geirhos, Patricia Rubisch, Claudio Michaelis, Matthias Bethge, Felix A. Wichmann, and Wieland Brendel. Imagenet-trained CNNs are biased towards texture; increasing shape bias improves accuracy and robustness. In *Int. Conf. Learn. Represent.*, 2019. URL `https://openreview.net/forum?id=Bygh9j09KX`.

Barbara Giunti. TDA-Applications: Zotero database. `https://www.zotero.org/groups/2425412/tda-applications`, 2021. [Online; accessed 14-Oct-2021].

Geoffrey Hinton and Ruslan Salakhutdinov. Reducing the dimensionality of data with neural networks. *Science*, 313(5786):504–507, July 2006. doi: 10.1126/science.1127647. URL `http://www.ncbi.nlm.nih.gov/sites/entrez?db=pubmed&uid=16873662&cmd=showdetailview&indexed=google`.

Christoph Hofer, Roland Kwitt, Marc Niethammer, and Andreas Uhl. Deep learning with topological signatures. In *Adv. Neural Inform. Process. Syst.*, 2017. URL `https://proceedings.neurips.cc/paper/2017/file/883e881bb4d22a7add958f2d6b052c9f-Paper.pdf`.

Ashish Jaiswal, Ashwin Ramesh Babu, Mohammad Zaki Zadeh, Debapriya Banerjee, and Fillia Makedon. A survey on contrastive self-supervised learning. *Technologies*, 9(1), 2021. ISSN 2227-7080. doi: 10.3390/technologies9010002. URL `https://www.mdpi.com/2227-7080/9/1/2`.

Jesse Johnson. Deep, skinny neural networks are not universal approximators. In *Int. Conf. Learn. Represent.*, 2019. URL `https://openreview.net/forum?id=ryGgSsAcFQ`.

Shizuo Kaji, Takeki Sudo, and Kazushi Ahara. Cubical ripser: Software for computing persistent homology of image and volume data, 2020. arXiv:2005.12692.

Hirokatsu Kataoka, Kazushige Okayasu, Asato Matsumoto, Eisuke Yamagata, Ryosuke Yamada, Nakamasa Inoue, Akio Nakamura, and Yutaka Satoh. Pre-training without natural images. In *Asian. Conf. Comput. Vis.*, 2020.

Hirokatsu Kataoka, Ryo Hayamizu, Ryosuke Yamada, Kodai Nakashima, Sora Takashima, Xinyu Zhang, Edgar Josafat Martinez-Noriega, Nakamasa Inoue, and Rio Yokota. Replacing labeled real-image datasets with auto-generated contours. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 21232–21241, June 2022.

Alex Krizhevsky. Learning multiple layers of features from tiny images. *Master's thesis, Department of Computer Science, University of Toronto*, 2009.

Chunyuan Li, Maks Ovsjanikov, and Frederic Chazal. Persistence-based structural recognition. In *IEEE Conf. Comput. Vis. Pattern Recog.*, 2014.

Ninareh Mehrabi, Fred Morstatter, Nripsuta Saxena, Kristina Lerman, and Aram Galstyan. A survey on bias and fairness in machine learning. *ACM Comput. Surv.*, 54(6), July 2021. ISSN 0360-0300. doi: 10.1145/3457607. URL `https://doi.org/10.1145/3457607`.

Ishan Misra and Laurens van der Maaten. Self-supervised learning of pretext-invariant representations. In *IEEE Conf. Comput. Vis. Pattern Recog.*, 2020.

Michael Moor, Max Horn, Bastian Rieck, and Karsten Borgwardt. Topological autoencoders. In *Proceedings of the 37th International Conference on Machine Learning*, volume 119, pp. 7045–7054, 2020. URL `https://proceedings.mlr.press/v119/moor20a.html`.

Nobuyuki Otsu. A Threshold Selection Method from Gray-level Histograms. *IEEE Transactions on Systems, Man and Cybernetics*, 9(1):62–66, 1979. doi: 10.1109/TSMC.1979.4310076. URL `http://dx.doi.org/10.1109/TSMC.1979.4310076`.

Primoz Skraba and Katharine Turner. Wasserstein stability for persistence diagrams, 2021. arXiv:2006.16824.

Anirudh Som, Hongjun Choi, Karthikeyan Natesan Ramamurthy, Matthew P. Buman, and Pavan K. Turaga. Pi-net: A deep learning approach to extract topological persistence images. In *IEEE Conf. Comput. Vis. Pattern Recog. Worksh.*, pp. 3639–3648, 2020. doi: 10.1109/CVPRW50498.2020. 00425. URL https://doi.org/10.1109/CVPRW50498.2020.00425.

Ryan Steed and Aylin Caliskan. Image representations learned with unsupervised pre-training contain human-like biases. In *Proceedings of the 2021 ACM Conference on Fairness, Accountability, and Transparency*, FAccT '21, pp. 701–713, New York, NY, USA, 2021. Association for Computing Machinery. ISBN 9781450383097. doi: 10.1145/3442188.3445932. URL https://doi.org/10.1145/3442188.3445932.

Naoya Tanabe, Shizuo Kaji, Susumu Sato, Tomoo Yokoyama, Tsuyoshi Oguma, Kiminobu Tanizawa, Tomohiro Handa, Takashi Sakajo, and Toyohiro Hirai. A homological approach to a mathematical definition of pulmonary fibrosis and emphysema on computed tomography. *J. Appl. Physiol.*, 1985: 601–612, 2021. doi: https://doi.org/10.1152/japplphysiol.00150.2021.

Renata Turkeš, Jannes Nys, Tim Verdonck, and Steven Latré. Noise robustness of persistent homology on greyscale images, across filtrations and signatures. *PLOS ONE*, 16(9):1–26, 09 2021. doi: 10.1371/journal.pone.0257215. URL https://doi.org/10.1371/journal.pone.0257215.

Kaiyu Yang, Klint Qinami, Li Fei-Fei, Jia Deng, and Olga Russakovsky. Towards fairer datasets: Filtering and balancing the distribution of the people subtree in the imagenet hierarchy. In *Proceedings of the 2020 Conference on Fairness, Accountability, and Transparency*, FAT* '20, pp. 547–558, New York, NY, USA, 2020. Association for Computing Machinery. ISBN 9781450369367. doi: 10.1145/3351095.3375709. URL https://doi.org/10.1145/3351095.3375709.

A   APPENDIX

A.1   COMPUTATIONAL COST OF PH LABELLING

The worst-case complexity of the standard matrix reduction algorithm for computing PH is K^3, where K is the number of columns, which is linear with respect to the number of pixels in the cubical complex. The average time of computation for persistent homology and its persistence image as in PH-PI for a synthesised image described in Sec. 3.1 in different sizes is shown in Tab. 3. The increase rate looks almost linear with respect to the number of pixels in this particular set of images.

Table 3: Average computation time for PH and persistence image

image size	256×256	512×512	1024×1024	2048×2048
computation time in ms	22.62	89.85	436.93	2181.13

A.2   WHAT IS REALLY LEARNED?

Understanding and explaining what the model is learning is a difficult problem, which forms one of the central topics in machine learning research. Here, we show some experiments that indicate the difference between the models trained in our scheme and the classical supervised manner with real images and manual labels. First, we observe distinction in the weights of first few convolution layers among different models (Fig. 5). This shows that the model learns different low-level features through our scheme. To understand this phenomena, we conducted an experiment "in the other way around". We replaced the fully-connected layer of the ImageNet pretrained model with a randomly initialised one. Then, the model was finetuned for the PH-regression task as in the PH-PI pretraining while the weights of all but fully-connected layers frozen (we call this model IMG_fr). The model was compared with the one trained from scratch, which was exactly in the same manner as PH-PI

pretraining. Figure 6 shows that the validation loss as well as the training loss converges and the models are learning to approximate PH to some extent. However, we observe that the convergence of IMN_fr is much worse than Scratch, indicating that not only fully-connected but convolutional layers need to be trained for approximating PH. This explains Fig. 5; the convolutional layers in the PH-PI model learn features specific to PH computation, which are different from those features learned with usual image classification tasks. This behaviour sharply contrasts with the fact that the ImageNet pretrained model finetuned with frozen weights except for fully-connected layers works well with usual natural image classification tasks; the convolutional layers of IMN_fr have obtained image features sufficient for general classification tasks of natural images.

Figure 5: Visualisation of the filters of the first convolutional layer of PH-PI, FractalDB-10k, and ImageNet pretrained models.

Figure 6: Transition of loss for PH-regression task for the ImageNet pretrained model with the weights of all but fully-connected layers frozen (IMN_fr) and a model with randomly initialised weights (Scratch).

To investigate this direction further, we performed another experiment of the PH-regression with a different set of synthesised images with simple random blobs which had virtually no texture information (Fig. 7 (Top)). We finetuned the ImageNet pretrained (IMN_fr) and the PH-PI pretrained (PH-PI_fr) models while the weights of all but fully-connected layers frozen. The transition of the loss values is shown in Fig. 8. The validation loss of the PH-PI model converges to a lower value than that of IMN. This shows the visual representation leaned by the convolutional layers of PH-PI generalises to approximating PH of a different type of images. On the contrary, the features learned by pretraining with ImageNet are not sufficient to approximate PH even for very simple images. The visualisation of Grad-CAM++ (Chattopadhay et al., 2018) (with the target of the last convolution layer) of the two models is shown in Fig. 7 (second and last rows). Although it is hard to interpret, we may be able to say, for example, PH-PI_fr identifies a large circle as a single shape whereas IMN_fr has more focus on edges and find a large circle as collection of two or three shapes.

A.3 IMAGE SYNTHESIS METHOD

There are many different way to synthesise images such as various noise generation methods. We have not conducted a thorough test on dataset creation since the focus in the design of our pretext task

Figure 7: (Top) randomly synthesised blob images (Middle) Grad-CAM++ visualisation of IMN_fr, and (Bottom) PH-PI_fr

Figure 8: Transition of loss for PH-regression task for the ImageNet pretrained (IMN_fr) and the PH-PI (PH-PI_fr) models with the weights of all but fully-connected layers frozen.

is not in the distribution of the data but the process of approximating a certain computation (in our case, persistent homology) is based on mathematical structure. We list some reasons why we chose the particular image synthesis method. We can see from Eq. (1) in the paper that: (i) It is rotation invariant, except for the fact that the image is rectangular. (ii) It is scale (image size) independent. (iii) It produces various frequency profiles: The lifetime profile of the persistent homology is a very important factor of the topology of the image. With the signed distance transform, the total persistence (the sum of lifetime of all cycles) is bounded, so we can have either many short lifetime cycles or a small number of long lifetime cycles. In natural images, short lifetime cycles arise mainly from noise or texture, which are local. The denominator of Eq. (1) discourages the resulting image to have many high frequency components so that there are more long lifetime cycles, which represent global topology. (iv) It is computationally cheap. We emphasise that the fractal model used in Formula-driven Supervised Learning (Kataoka et al., 2020) requires tremendous computational power and their datasets are prepared on a computing cluster. Creation of our dataset with 400,000 images takes less than twenty minutes on a personal computer, and is generated on the fly during the first epoch of training.