Task-agnostic Prompt Compression with Context-aware Sentence Embedding and Reward-guided Task Descriptor

Abstract

The rise of Large Language Models (LLMs) has led to significant interest in prompt compression, a technique aimed at reducing the length of input prompts while preserving critical information. However, the prominent approaches in prompt compression often require explicit questions or handcrafted templates for compression, limiting their generalizability. We propose Task-agnostic Prompt Compression (TPC), a novel framework that generalizes compression across tasks and domains without requiring input questions or templates. TPC generates a context-relevant task description using a task descriptor trained on a curated dataset of context and query pairs, and fine-tuned via reinforcement learning with a reward function designed to capture the most relevant information. The task descriptor is then utilized to compute the relevance of each sentence in the prompt to generate the compressed prompt. We introduce 3 model sizes (Base, Large, and Huge), where the largest model outperforms the existing state-of-the-art methods on LongBench and ZeroSCROLLS, and our smallest model performs comparable to the existing solutions while being considerably smaller.

1 Introduction

The emergence of Large Language Models (LLMs) has spurred extensive research into prompting techniques, including chain-of-thought reasoning Wei et al. (2022), in-context learning Dong et al. (2022), and retrieval-augmented generation Lewis et al. (2020) to harness LLMs' generalization and reasoning abilities for various applications. In practice, effective prompting often requires detailed and lengthy inputs to generate high-quality responses in domain-specific tasks. However, long prompts significantly increase inference time and costs. To address this, a new research direction called *prompt compression* Jiang et al. (2023b;c); Liskavets et al. (2025) has emerged, which focuses on reducing prompt length while retaining the critical information needed to accurately answer user queries.

Early research on prompt compression predominantly focused on token-level techniques, which involve analyzing the importance of individual tokens in a prompt and removing less informative ones to generate the compressed prompt. However, token-level compression often leads to incoherent or fragmented sentences, hindering the overall performance. To address this, recent approaches, such as CPC Liskavets et al. (2025), have shifted to sentence-level compression, which evaluates the relevance of each sentence to the input question. While this method represents a significant improvement over token-level approaches, its reliance on explicit questions or manually crafted templates for non-question-based tasks (e.g. summarization or code) restricts its broader applicability.

In this work, we propose Task-agnostic Prompt Compression (TPC), a generic prompt compression method capable of compressing input prompts across tasks and domains without relying on input questions or handcrafted prompt templates. The central idea of TPC involves using a novel task descriptor to create a context-relevant task description, which facilitates compression by comparing its context-aware embedding similarity to each sentence in the prompt. Here, the task descriptor is a causal LM, trained on our curated dataset of prompt-question pairs, that generates a context-relevant task description encapsulating the main concept of the prompt. Since the effectiveness of the prompt compression relies on the quality of the generated

Figure 1: Comparison of model size versus performance for different prompt compression methods in both task-aware and task-agnostic setups. Our largest model, TPC-Huge, outperforms all existing methods while maintaining a comparable size to existing solutions. On the other hand, our smallest model, TPC-Base, achieves a competitive performance despite being significantly smaller in size.

task description, we introduce a reinforcement learning (RL) approach to further fine-tune the task descriptor with a novel reward function designed to encourage capturing the most relevant information of the prompt in the task description. Finally, the context-aware embedding is computed using a context-aware sentence encoder trained on our curated dataset of multi-hop questions, answers, and positive and negative pairs.

We present comprehensive experiments to evaluate our proposed solution and compare it against existing methods on two evaluation setups: task-aware compression and task-agnostic compression on two popular benchmarks LongBench and ZeroSCROLLS adopted by existing literature on prompt compression. We report the results for three variants of our model size: TPC-Base, TPC-Large, and TPC-Huge, containing 0.5B, 1B, and 7B parameters, respectively. As summarized in Figure 1, our TPC shows significant improvements over existing methods on both task-aware and task-agnostic setups. Our smallest model, while being considerably smaller in size, outperforms or performs comparable to the existing state-of-the-art (SOTA) methods. Overall, we make the following contribution in this paper:

- We introduce TPC, a task-invariant prompt compression method, which unlike existing methods doesn't require task-specific hand-crafted templates to achieve generalizable compression. TPC generates a context-relevant task description using a task descriptor LM that is used for compression by comparing the context-relevant embedding to each sentence in the prompt.
- We propose a novel reward function and use RL-based fine-tuning of the task descriptor to capture the most relevant task descriptions.
- We curate two datasets required for training the context-relevant task descriptor and context-aware sentence encoder of our proposed TPC.
- Our proposed solution outperforms existing methods in prompt compression on standard benchmark evaluations on both task-aware and task-agnostic compression setups and shows strong generalization across tasks and domains. To enable quick reproduction and further developments, we will release the datasets and the codebase upon acceptance.

2 Related Works

2.1 Prompt Compression

Recent efforts in prompt compression focus on reducing the inference cost of LLMs. A key line of research involves model-agnostic methods, which leverage pre-trained models for compression. Early works like token pruning during the forward pass (Kim et al., 2022) and recursive context summarization (Chen et al., 2023) introduced effective strategies but required access to the pre-trained LLM, which is often impractical. To address this limitation, newer approaches such as LLMLingua (Jiang et al., 2023b) utilize token-level

perplexities to filter out semantically insignificant tokens, while Selective-Context (Li et al., 2023a) retains high-perplexity tokens using decoder-only models like LLaMa and GPT-2. LongLLMLingua (Jiang et al., 2023c) further refines this idea by integrating question relevance for context-aware compression. However, these methods often lack adaptability to new domains, restricting their broader applicability.

In parallel, trainable methods for prompt compression have also gained traction as a key research direction. Soft prompt techniques (Wang et al., 2024; Bulatov et al., 2022; Chevalier et al., 2023) fine-tune or pre-train LLMs to achieve high compression rates, though they provide limited interpretability and control over the compression ratio. Sequence-to-sequence models compress context by generating a summary directly (Xu et al., 2024), but their autoregressive design introduces latency. Reinforcement learning approaches, such as optimizing for simplicity, fluency, and salience (Laban et al., 2021), or using compression ratio as a reward (Jung & Kim, 2024), offer an alternative, but may fall short in task-aware tasks. Recent innovations, such as (Pan et al., 2024), propose models that evaluate and prune tokens based on their information value, providing a more systematic approach to compression. Despite these advances, challenges remain in balancing efficiency, accuracy, and domain adaptability. More recently CPC Liskavets et al. (2025) proposed to utilize a context-aware sentence encoder to find the relevance of each sentence in the context to remove irrelevant sentences from the input prompt, achieving SOTA performance on existing benchmarks. However, a major limitation of such an approach is its reliance on the input question to guide the compression, requiring manual prompt formats for different tasks. While there have been some efforts towards building task-agnostic prompt compression Pan et al. (2024), the performance of such methods falls short of the task-aware counterpart. Our goal in this work is to develop a task-agnostic prompt compression method without sacrificing performance.

2.2 Sentence Embedding Learning

Sentence embedding learning aims to create high-dimensional vector representations of text that capture semantic meaning, facilitating tasks such as text classification, clustering, and similarity search. Early approaches like GloVe (Pennington et al., 2014) and Word2Vec (Mikolov et al., 2013) focused on word- or token-level embeddings. Later, sentence-level representation learning gained attention, with works like Reimers & Gurevych (2019) fine-tuning BERT-based models (Vaswani et al., 2017) to extract sentence embeddings for measuring text similarities. Subsequent research (Li et al., 2023b; Wang et al., 2022; Beltagy et al., 2020) enhanced the effectiveness of these embeddings, particularly for longer contexts. Later, BehnamGhader et al. (2024) leveraged the extensive knowledge of pre-trained LLMs to build robust sentence encoders. However, while these models excel at sentence representation, they lack context awareness, which is an essential property for our prompt compression approach. While a more recent work, CPC (Liskavets et al., 2025) explored context-aware sentence encoding to compress prompts based on their relevance to the question, the proposed encoder was not task-agnostic. In this work, we introduce a task-agnostic and context-aware sentence encoder, where the embedding captures the semantics of the context.

3 Proposed Method

3.1 Task-agnostic Prompt Compression

The conventional setup of task-aware prompt compression operates by leveraging an explicit question (or a hand-crafted prompt where no question is available, e.g. code) q provided along with the input context c. Specifically, this approach utilizes a sentence encoder f_s to encode both the question and individual sentences $\{s_1, .., s_n\}$ from the context into embeddings $\mathbf{e}_q = f_s(q)$ and $\mathbf{e}_{s_1}..\mathbf{e}_{s_n} = f_s(s_1, ..., s_n)$, respectively. The relevance of each sentence is then determined by a scoring function (e.g. cosine similarity) $\mathcal{R}(\mathbf{e}_q, \mathbf{e}_{s_i})$, to select the top k most relevant sentences:

$$\mathcal{S} = \phi(q, c) = \text{TopK}(\{\mathcal{R}(\mathbf{e}_q, \mathbf{e}_{s_i}) \mid s_i \in c\}), \tag{1}$$

where $\mathcal{S}$ is the compressed prompt containing the selected sentences. The encoder f_s is trained on a dataset of $(q, c, pos, \{neg^{i=1..m}\})$ tuples to learn context-aware sentence embeddings, where q is a question, c is the context, and pos is the positive sentence, and $neg^{i=1..m}$ are negative sentences. Here, a positive is a sentence containing relevant information to the question, while the negatives are context sentences containing no

Figure 2: Illustration of our proposed prompt compression method. The CTD module generates a task description that is relevant to the input context. This description is then utilized by the Context-Aware Sentence Encoder to evaluate the relevance of each sentence in the input prompt, ultimately generating the compressed prompt.

information regarding the question. While effective, this approach inherently relies on the availability of explicit questions and cannot be adapted to tasks with no explicit questions, such as summarization.

To address the limitations of task-aware compression, we propose Task-agnostic Prompt Compression (TPC), a novel solution for prompt compression that does not require such explicit questions. Instead, our approach generates a context-relevant task-description $\hat{q}$ from the input prompt p using our proposed Context-relevant Task Descriptor (CTD) model f_q as $\hat{q} = f_q(p; \theta_q)$. CTD is a lightweight module designed to generate a task description that highlights the most relevant information within p. The task description $\hat{q}$ is then used to find the relevance of each sentence in the input prompt with our context-aware sentence encoder. To ensure the generated task description is semantically meaningful and contextually relevant, we train f_q on a synthetic dataset of (p, q) pairs (curated using our proposed data curation pipeline discussed in Section 3.2), followed by a reward-guided fine-tuning stage with our proposed reward function (Section 3.3). Finally, we propose a new method for training the Context-aware Sentence Encoder (CSE) that effectively captures the context in the embedding (Section 3.4). Note that the CTD in our proposed method is a small LLM to generate the task description only; the final response is generated by a pre-trained LLM (like the existing method). Overall, the lightweight CTD add negligible overhead compared to the computation cost of the LLM. The overall diagram of our proposed method is illustrated in Figure 2, and a pseudo-code is provided in Algorithm 3 (Appendix 3.6).

3.2 Context-relevant Task Descriptor

CTD is the key component of our proposed solution that transforms a task-agnostic prompt compression task into a task-aware prompt compression task. Specifically, CTD generates a context-aware task description $\hat{q}$ from the input prompt p. The CTD comprises two primary components: (1) a dataset curation pipeline for generating high-quality (p, q) pairs, and (2) a causal encoder training process on the curated dataset to generate the task description $\hat{q}$. Below, we describe these components in detail.

3.2.1 Dataset Curation

To train the CTD, we require a dataset of (p, q) pairs, where p represents a long input prompt and q is a relevant query or description that highlights the essential information in p. We leverage an existing dataset of texts D_{init} and a pre-trained LLM to generate these pairs. Specifically, for a given input prompt p, the LLM is prompted to generate q using the pre-designed Prompt 1 in A.2. By applying this prompt to a dataset of long texts (e.g. Wikipedia), we generate a collection of question and input context pairs.

In real-world scenarios, user prompts are often structured, typically comprising an input context, a question, and a system prompt. To ensure that our generated dataset adheres to such a structure and remains suitable for downstream tasks, we refine the initially generated dataset by prompting the same pre-trained LLM

with Prompt 2 in A.2. This two-stage process yields a dataset $\mathcal{D}_{\text{CTD}}$ of input prompts and structured task descriptions, which is subsequently used to train the question generator f_q, as described in the next subsection. Additionally, we provide a few examples from the resulting training dataset in the Appendix.

3.2.2 Training CTD

At the core of CTD is a causal encoder, f_q, designed to generate contextually relevant task descriptions. We utilize a causal language model for f_q, initialized from a pre-trained LLM, to auto-regressively generate the task description $\hat{q}$ conditioned on the input prompt p. Formally, given input long prompt p, f_q generates the question $\hat{q}$ as follows:

$$P(q \mid p; \theta_q) = \prod_{t=1}^{T} P(q_t \mid q_{<t}, p; \theta_q), \tag{2}$$

where q_t is the t-th token in q, $q_{<t}$ represents the sequence of tokens generated up to step $t - 1$, and θ_q are the model parameters. We train the encoder f_q to maximize the likelihood of generating the target question q given the prompt p. The Supervised Training (ST) procedure is carried out using the following loss function:

$$\mathcal{L} = -\mathbb{E}_{(p,q) \sim \mathcal{D}'_{\text{CTD}}} \left[\sum_{t=1}^{T} \log P(q_t \mid q_{<t}, p; \theta_q) \right], \tag{3}$$

where T is the total number of tokens in q.

3.3 Reward-guided Refinement

As mentioned earlier, the generated task description serves as a guide for creating the compressed prompt by calculating the embedding similarity between the task description and each sentence in the prompt. Consequently, the quality of the compressed prompt is directly dependent on the generated task description. While the dataset $\mathcal{D}_{\text{CTD}}$ generated using the initial prompting pipeline provides a diverse set of (p, q) pairs for training f_q, there is no explicit constraint to ensure that $\hat{q}$ generated by the LLM is the most relevant task description for input prompt p. To this end, we propose a novel reward function for fine-tuning f_q through cross-entropy reinforcement learning. The reward function is specifically designed to achieve efficient prompt compression by generating a task description $\hat{q}$ that ensures the performance of the compressed prompt is on par with that of the original uncompressed input prompt.

Consider, task-descriptor f_q as a model that performs the action of generating candidate task-description $\hat{q}$ from an input prompt p of a real-world human instruction dataset (e.g. Tulu SFT dataset Ivison et al. (2023)), which is then used to generate the compressed prompt $\mathcal{S} = \phi(\hat{q}, p)$ using Eq. 1. We define the reward function as the KL divergence between the conditional probability of generating the response r from the whole input prompt p and the compressed prompt $\mathcal{S}$ as:

$$R(q_i) = -\text{KL}(P(r \mid \mathcal{S}) \| P(r \mid p)) \tag{4}$$

where, r is the response from the pre-trained LLM using the whole input prompt p as $r = f_{LLM}(p)$, and $P(r|\mathcal{S})$ is the conditional probability of generating the response r given the compressed prompt $\mathcal{S}$ with a pre-trained LLM f_{LLM},

$$P(r \mid \mathcal{S}) = f_{\text{LLM}}(\mathcal{S}, r; \theta), \tag{5}$$

and $P(r \mid p)$ is the conditional probability of generating the response r given the original input prompt p. The KL divergence measures how much the distribution $P(r \mid \mathcal{S})$ deviates from $P(r \mid p)$, which we use as the reward signal for encouraging the model to generate an informative task description $\hat{q}$ for compressing the prompt. Finally, using f_q as an agent to generate multiple task descriptions $\hat{q}$ (actions), and calculating the corresponding reward, we fine-tune the task descriptor LM with the following loss:

$$\mathcal{L}_{\text{RL}} = - \left[\sum_{t=1}^{T} \log P(q_{j,t} \mid q_{j,<t}, p; \theta_q) \right], \tag{6}$$

where q_j is the generated task-description with maximal reward from Eq 4. The overall process is illustrated in Figure 3.

Figure 3: Overview of our proposed reward system for refining CTD with RL. (left) A response is generated by the pre-trained LLM with the complete long input prompt. (right) The CTD and CSE modules generate the compressed prompt. KL divergence between the conditional distribution of the generated response from the long prompt and the compressed prompt is used as the reward signal for the RL.

3.4 Context-aware Sentence Encoder

CSE is the sentence encoder in our method, which captures the information of the surrounding context in the embedding of a sentence. Training CSE consists of two components discussed below: data curation and encoder training.

3.4.1 Dataset Curation

To train the context-aware sentence encoder, we require a dataset consisting of tuples containing long contexts, questions, positive sentence, and negative sentences. The context provides all the relevant information necessary to answer the question, positives are sentences within the context that contain partial but not necessarily complete information needed to answer the question, while negative sentences are context sentences that provide no relevant information. While a similar dataset (CQR) was introduced in CPC Liskavets et al. (2025), the simple prompt used in the pipeline did not explicitly ensure that all the information is not present in the positive alone for encouraging understanding of the context. To this end, we introduce a multi-hop question-answer prompt for generating a new dataset of contexts, questions, positive sentence, and negative sentences using Prompt 3 in A.2. The multi-hop question-answer prompt ensures that the generated questions require reasoning over multiple sentences in the context to arrive at an answer, thereby promoting deeper contextual understanding and ensuring that the positive does not contain the entire information required to answer the question. We denote the generated data of $(q, c, pos, \{neg^{i=1\cdots m}\})$ tuples as the Multi-hop Context-Question Relevant dataset (MCQR), which is then used to train the CSE f_s.

3.4.2 Encoder Training

CSE is trained to learn the context-aware sentence representations by distinguishing the positives and negatives. Specifically, this loss maximizes the similarity between the embeddings of the question and the positive sentence while minimizing the similarity between the question and the embeddings of negative sentences. Similar to CPC Liskavets et al. (2025), we use a contrastive loss along with the MNTP loss BehnamGhader et al. (2024) for more stable training on our newly curated MCQR dataset, with another key modification. Specifically, we introduce two new types of tokens into the tokenizer dictionary: the end-of-sentence token <end_of_sent> and the question token <end_of_question>. The <end_of_sent> token is inserted at the end of each particular sentence in the text, explicitly marking sentence boundaries and enabling the model to process text segments of varying lengths effectively. This token enables the adaptation to different input granularities while maintaining a clear structural understanding of the text. Similarly, the <end_of_question> token is appended to the end of each question, signalling its conclusion and helping the

Methods	LongBench						
	SingleDoc	MultiDoc	Summ.	FewShot	Synth.	Code	Tokens
task-aware compression							
Selective-Con.	29.74	43.86	23.61	57.95	22.75	45.32	1,925
LLMLingua	20.48	37.02	21.23	55.99	10.5	43.78	1,856
LLMLingua-2	33.23	52.4	24.64	46.74	26.0	59.94	1,868
LongLLMLingua	26.61	39.85	22.37	58.53	14.25	29.08	1,926
CompAct	19.8	40.55	-	59.91	-	-	831
FAVICOMP	27.13	51.65	-	41.63	-	-	95
CPC	43.79	62.67	25.8	67.67	**54.0**	56.74	1,936
TPC-Base	44.06	62.25	25.66	**70.1**	53.75	59.72	1,973
TPC-Large	42.96	58.38	25.34	69.34	52.75	58.9	1,983
TPC-Huge	**44.7**	**64.02**	**25.84**	68.91	**54.0**	**60.04**	1,969
task-agnostic compression							
Selective-Con.	14.72	13.08	22.04	21.09	1.0	19.3	1,756
LLMLingua	21.02	34.79	21.32	54.57	7.0	**64.62**	1,870
LLMLingua-2	20.18	7.0	22.86	13.02	1.34	23.3	1,866
TPC-Base	40.7	58.23	25.66	55.95	27.38	38.36	1,934
TPC-Large	41.59	57.59	**26.26**	47.86	**42.0**	35.25	1,978
TPC-Huge	**41.84**	**61.93**	26.22	**58.27**	39.0	36.25	1,962

Table 1: Performance of different methods in task-aware and task-agnostic setups on LongBench.

model handle questions with diverse syntactic structures. Together, these tokens improve the model's ability to generate embeddings that encode contextual and structural relationships more effectively.

3.5 Inference

During inference, we improve the computational and memory efficiencies of deploying TPC by unifying the CTD and CSE encoders. As both tasks utilize the same pretrained encoder, we employ one pre-trained encoder with task-specific LoRA adapters for CTD and CSE. The adapters are activated sequentially to generate $\hat{q}$ from p with CTD, followed by processing $(p, \hat{q})$ with CSE.

3.6 Algorithm

Next, we provide the pseudo-code of the overall pipeline of our proposed prompt compression method TPC in Algorithm 3, the pseudo-code for context-relevant task descriptor in Algorithm 2, and CTD refinement with RL in Algorithm 1.

4 Experiments

In this section, we discuss the experiments and results of our proposed solution for prompt compression. We begin by presenting the datasets, evaluation protocols, and implementation details. Subsequently, we discuss the main results, ablation studies, and qualitative findings on TPC.

4.1 Datasets

Evaluation datasets. To evaluate the performance of TPC, we adhere to the experimental protocols outlined in prior research Jiang et al. (2023c) and benchmark our method on **LongBench** Bai et al. (2023) and **ZeroSCROLLS** Shaham et al. (2023) datasets. LongBench features a diverse range of tasks, including both single-document and multi-document QA, summarization, few-shot learning, synthetic and code generation. Similarly, ZeroSCROLLS offers a collection of tasks, including GovReport, SummScreenFD, QMSUM, SQuality, Quality, NarrativeQA, Qasper, Musique, SpaceDigest, BookSumSort, and Tokens.

Algorithm 1 Reinforcement Learning for CTD Refinement

Input: Pre-trained task descriptor f_q, candidate task descriptions $\{\hat{q}_i\}$, pre-trained LLM f_{LLM}, input prompt p, response r
Output: Refined task descriptor f_q with updated parameters θ_q
// Generate candidate task descriptions using f_q
$\{\hat{q}_i\} = f_q(p; \theta_q)$
// For each q_i, construct compressed prompt $\mathcal{S}_i$ using ϕ
$\mathcal{S}_i = \phi(q_i, p) \quad \forall q_i \in \{\hat{q}_i\}$
// Compute initial response r using f_{LLM} and the initial non-compressed prompt p
$r = f_{\text{LLM}}(p)$
// Evaluate candidate task descriptions based on KL divergence reward
$R(q_i) = -\text{KL}(P(r \mid \mathcal{S}_i) \| P(r \mid p)) \quad \forall q_i \in \{\hat{q}_i\}$
// Optimize f_q using cross entropy RL for the generated task-description with maximal reward q_j
$\mathcal{L}_{\text{RL}} = -\left[\sum_{t=1}^{T} \log P(q_{j,t} \mid q_{j,<t}, p; \theta_q) \right]$
Update θ_q to minimize $\mathcal{L}_{\text{RL}}$
Return refined f_q

Algorithm 2 Context-relevant Task Descriptor (CTD)

Input: Prompt p, pre-trained LLM g, dataset $\mathcal{D}$, training parameters θ_q.
Output: Context-relevant Question Generator f_q
// Stage 1: Dataset Curation
Initialize empty dataset $\mathcal{D}_{\text{raw}}$
for each prompt $p \in \mathcal{D}$ **do**
    Generate raw question q using g: $q = g(p; \text{Prompt 1})$
    Append (p, q) to $\mathcal{D}_{\text{raw}}$
end for
// Stage 2: Structured Prompt Creation
Initialize empty dataset $\mathcal{D}_{\text{CTD}}$
for each $(p, q) \in \mathcal{D}_{\text{raw}}$ **do**
    Generate structured prompt p_{struct} using g: $p_{\text{struct}} = g(p, q; \text{Prompt 2})$
    Append (p_{struct}, q) to $\mathcal{D}_{\text{CTD}}$
end for
// Train Causal Encoder f_q
Initialize f_q with pre-trained weights θ_q
repeat
    Sample batch (p_{struct}, q) from $\mathcal{D}_{\text{CTD}}$
    Compute loss:
        $\mathcal{L}_{\text{CTD}} = -\sum_{t=1}^{T} \log P(q_t \mid q_{<t}, p_{\text{struct}}; \theta_q)$
    Update parameters θ_q using gradient descent
until convergence criteria met
Return trained question generator f_q

Our curated datasets. As outlined in the Methods section, TPC is trained using two of our curated datasets: CTD and MCQR. The CTD dataset comprises 4,100 context-question pairs specifically designed for training the CTD module. We initialize the seed dataset for training the CTD by combining Tulu-3-sft-mixture[1], MetaMathFewshot[2], Magicoder-Evol-Instruct-110K[3], consisting of 3,000 prompts. The MCQR dataset includes 9,300 samples, each consisting of a question, a context, a positive and negative sentences.

---

[1] huggingface.co/datasets/allenai/tulu-3-sft-mixture
[2] huggingface.co/datasets/abacusai/MetaMathFewshot
[3] huggingface.co/datasets/ise-uiuc/Magicoder-Evol-Instruct-110K

Algorithm 3 Task-Agnostic Prompt Compression (TPC)

Input: Prompt p, context c, number of top sentences k, context-aware sentence encoder f_s, context-relevant task descriptor LM, f_q.
Output: Compressed prompt $\mathcal{S}$
// Generate task description $\hat{q}$ from prompt p using f_q
$\hat{q} = f_q(p; \theta_q)$
// Encode task description $\hat{q}$ and each sentence s_i in context c using sentence encoder f_s
$\mathbf{e}_{\hat{q}} = f_s(\hat{q})$, $\{\mathbf{e}_{s_1}, ..., \mathbf{e}_{s_n}\} = f_s(s_1, .., s_n), \forall s_i \in c$
// Compute relevance scores for all sentences in c
$\mathcal{R}_i = \mathcal{R}(\mathbf{e}_{\hat{q}}, \mathbf{e}_{s_i}), \forall s_i \in c$
// Select top-t sentences based on relevance scores
$\mathcal{S} = \text{TopK}(\{\mathcal{R}_i \mid s_i \in c\}, k)$
Return compressed prompt $\mathcal{S}$

4.2 Evaluation Protocols

We conduct a series of experiments across multiple downstream tasks, following widely accepted protocols on the LongBench and ZeroSCROLLS subsets. Our approach adheres to the standard evaluation protocols established in prior studies Jiang et al. (2023c). Specifically, for summarization tasks, we assess our method by comparing the Rouge scores (Lin, 2004) between the ground truth responses and the outputs generated by the model using compressed prompts. In document QA tasks, the model's responses are evaluated against the ground truth using the F1 score. For code completion tasks, we rely on a textual similarity measure derived from the Levenshtein edit distance (Yujian & Bo, 2007).

We present the main results in two evaluation setups, including task-aware compression and task-agnostic compression. task-aware compression is the most common setup adopted by existing works where the long context is provided with a question, and the compression is performed based on the question and a system prompt. However, this limits its applicability to certain tasks such as summarization and code, where a manual hand-designed and task-specific prompt template is required for the compression. On the contrary, task-agnostic compression does not require such a template or an explicit question to compress the context. We use GPT-4o as the pretrained model to generate final answers. All main results are reported using a compressed prompt limited to 2,000 tokens.

4.3 Implementation Details

We use the subset of pile dataset Gao et al. (2020) as the seed dataset, D_{init} in CTD.. We train the f_q with our curated CTD dataset for 2 epochs with an AdamW optimizer, a learning rate of 1.5e-4, and a batch size of 16. This is followed by the reward-guided RL training for 3 iterations with Llama-3.1-8B Dubey et al. (2024) as the pre-trained LLM for the reward function. To obtain questions in the RL stage, we select 16 questions per prompt using a Nucleous Sampling Holtzman et al. (2019) with temperature = 0.7 and topP = 0.9. CSE is trained with an AdamW optimizer for 2 epochs, a learning rate of 5e-5, and a batch size of 32. We introduce three versions of TPC, namely Base, Large, and Huge, consisting of Qwen2 Yang et al. (2024) with 0.5B parameters, Llama-3.2-Instruct Dubey et al. (2024) with 1B parameters, and Mistral-Instruct-v0.2 Jiang et al. (2023a) with 7B parameters as the encoder, respectively. We initialize the encoder with the pre-trained weights and fine-tune it with LoRA Hu et al. (2022) of rank 16, and follow the training details from BehnamGhader et al. (2024) to turn the pre-trained causal encoder into bidirectional sentence encoder. All the experiments are conducted on an Nvidia A100 80GB GPU.

4.4 Main Results

We present the main results of our experiments on LongBench in Table 1 on both task-aware and task-agnostic compression setups. We perform the evaluations on all three sizes of our model (TPC-Base, TPC-Large, and TPC-Huge). As we find from this table, in the task-aware setup, TPC outperforms all the prior works across

Methods	ZeroSCROLLs										
	GovReport	SummScreenFD	QMSUM	SQuality	Quality	NarrativeQA	Qasper	Musique	SpaceDigest	BookSumSort	Tokens
task-aware compression											
Selective-Context	17.92	9.91	12.43	15.57	76.19	33.48	32.78	29.76	39.52	75.33	1,925
LLMLingua	15.03	6.52	11.03	12.14	71.43	23.08	15.85	**35.00**	43.15	56.17	1,856
LLMLingua-2	17.60	12.73	15.25	**17.37**	80.95	34.75	33.87	30.00	37.20	64.98	1,868
LongLLMLingua	0.0	0.0	0.0	14.45	71.43	21.6	22.81	0.0	0.0	0.0	1,926
CompAct	-	-	11.64	13.1	66.67	17.75	4.42	20.0	-	-	831
FAVICOMP	-	-	13.14	13.0	42.86	35.86	24.05	31.76	-	-	95
CPC	18.67	12.44	**17.06**	16.49	**100.0**	45.84	41.24	29.76	54.36	80.51	1,936
TPC-Base	18.67	12.26	15.78	17.00	90.48	44.75	**41.58**	29.76	53.90	80.36	2,027
TPC-Large	18.31	**13.54**	16.72	16.97	90.48	**46.42**	32.86	34.76	57.21	80.45	1,993
TPC-Huge	**19.30**	12.14	16.38	16.64	**100.00**	40.75	41.35	29.76	**61.42**	**83.33**	1,941
task-agnostic compression											
Selective-Context	17.94	10.71	7.96	13.14	33.33	1.14	25.58	33.33	19.31	**76.5**	1,756
LLMLingua	13.75	7.37	10.15	10.56	28.57	12.56	21.50	20.0	34.53	24.54	1,870
LLMLingua-2	18.24	**13.09**	11.07	16.33	38.10	1.11	**26.74**	**39.76**	29.49	63.63	1,866
TPC-Base	**19.72**	**13.07**	16.94	17.29	90.91	19.97	16.54	33.11	58.73	23.00	2,032
TPC-Large	18.48	12.3	16.02	17.29	90.91	**21.6**	**26.7**	33.29	59.51	5.24	1,978
TPC-Huge	17.73	12.4	16.28	17.26	86.36	16.42	15.19	24.62	**63.2**	48.56	2,012

Table 2: Performance of different methods in task-aware and task-agnostic setups on ZeroSCROLLs.

Ablation	Perf.
TPC	41.62
TPC w/o RL	37.97
TPC w/o SFT and RL	25.92

(a) Ablation on CTD.

Ablation	Perf.
CSE	51.28
CSE w/o MCQR	49.7
CSE w/o spec. tokens	50.23

(b) Ablation on CSE.

Setup	TPC-B	TPC-L	TPC-H	CPC
2k	52.59	51.28	52.92	51.78
3k	53.14	52.78	53.69	52.71

(c) Performance vs. context length.

Table 3: Ablation and analysis of different components of TPC on LongBench. In (c), B, L, and H represent Base, Large, and Huge, respectively.

the tasks, with up to 3.3 points improvement on individual tasks. While being considerably smaller than the existing SOTA (CPC), our smallest model (TPC-Base) outperforms it on most setups.

Similarly, TPC shows strong performance on the task-agnostic compression setup. Here, only a few of the existing methods can be adopted to the task-agnostic setup, due to the nature of the compression methods. In the task-agnostic setup, TPC outperforms existing methods by a larger margin than the task-aware setup. Specifically, TPC shows up to 35.0 points improvement (on synthetic task) over the existing methods, along with 20.82 points improvement on SingleDoc, and 27.14 points improvement on MultiDoc tasks. Despite having 14× less parameters than our largest model, our Base model achieves strong results, and considerably outperforms existing methods.

The results on the ZeroSCROLLs dataset are presented in Table 2. Similar to LongBench, the results are presented on both task-aware and task-agnostic compression setups for the three different model sizes. As we find from this table, on the task-aware setup, TPC outperforms prior works by up to 7.06 points (SpaceDigest). Notably, TPC outperforms existing methods by a larger margin on the task-agnostic setup. Specifically, we observe up to 51.81 points improvement on the Quality task. Additionally, we observe 28.67 and 9.04 points improvements for SpaceDigest and NarrativeQA tasks, respectively. Notably, our base encoder performs

Figure 4: Sensitivity study on CTD training epochs (left) and the number of RL iterations (right). Here, an RL iteration of 0 indicates no reward-guided refinement training.

comparable to that of the large encoder, surpassing it in a few tasks, possibly due to the relative simplicity of the tasks in ZeroSCROLLs dataset.

While we believe that LongBench and ZeroSCROLLs are the most representative benchmarks, we provide experiments on a broader set of datasets in the appendix.

4.5 Ablation

Here, we present ablation and sensitivity experiments on our proposed TPC. All the results in this section are reported as the averaged metrics on the LongBench dataset, with the GPT-4o model utilized as the pre-trained LLM to generate the responses. In Table 3(a) we study the impact of different components of the CTD module, including the supervised fine-tuning and the reward-guided refinement. We also provide results for the non-finetuned CTD model (before applying SFT and RL stages) for comparison. As we find from this experiment, removing the reward-guided refinement module shows a 3.65 point drop in the performance, while removing the ST module shows another 12.05 points drop in the overall performance, showing the importance of both modules in the final performance of the model. Note that RL is dependent on the ST module, and therefore can not be ablated alone.

Next, we ablate our two novel components in CSE, presented in Table 3(b). First, we remove the new multi-hop dataset MCQR and train CSE with CQR instead. This results in a 1.58-point drop in performance, indicating the impact of our curated MCQR dataset over the existing CQR dataset for training a context-aware sentence encoder. Then, we remove the special tokens (`<end_of_sent>` and `<end_of_question>`) from the encoder, leading to a 1.05-point drop in performance. These experiments demonstrate the importance of each component in our context-aware sentence encoder.

Next, in Table 3(c), we present additional studies on different constraints for context length, including 2,000 and 3,000 tokens, and compare them with the prior SOTA CPC. From this study, we observe that TPC outperforms CPC under both constraint setups, where TPC-Huge outperforms CPC with a larger margin on the 2K constraint compared to the 3K token constraint.

4.6 Sensitivity Analysis

Finally, we investigate two critical hyper-parameters of our method: the number of epochs for training the CTD model and the number of iterations for fine-tuning the CTD using RL. The number of training epochs is crucial to ensure that the task descriptions generated by the CTD model are sufficiently accurate for the subsequent reward-guided fine-tuning stage. As shown in Figure 4 (left), the model's performance drops after 2 epochs of training due to overfitting. The impact of the number of RL iterations is illustrated in Figure 4 (right). Here, iteration 0 represents the baseline performance without RL fine-tuning. As we find from this figure, the performance initially improves with the number of iterations. However, the performance drops after 2 iterations likely due to overfitting to the recent policies.

Figure 5: Latency estimates in milliseconds of the competitor methods and the TPC method in task-agnostic setup (left) and TPC method in task-aware setup (right).

4.7 Latency

In Figure 5, we present the latency evaluations of our method in both task-agnostic and task-aware setups, comparing it with other prompt compression techniques. As shown in the figure, although the latency of our method is slightly higher in the task-agnostic setup due to the overhead introduced by the CTD module, it remains lower than that of most SOTA prompt compression methods, while achieving significantly better performance than existing solutions.

5 Conclusion

We introduce TPC, a general-purpose prompt compression method that, unlike existing methods doesn't require an explicit question or handcrafted prompt for generating the compressed prompt. Instead, our method uses a task descriptor to generate a context-relevant task description, which is then utilized to find the relevance of each sentence in the prompt to produce the compressed prompt using CSE. Experiments on LongBench and ZeroSCROLLS demonstrate that our approach outperforms existing methods in both task-aware and task-agnostic compression settings. While achieving strong performance, our method is computationally efficient compared to existing SOTA. Our smallest variant with considerably fewer parameters performs on par with the previous SOTA.

References

Yushi Bai, Xin Lv, Jiajie Zhang, Hongchang Lyu, Jiankai Tang, Zhidian Huang, Zhengxiao Du, Xiao Liu, Aohan Zeng, Lei Hou, et al. Longbench: A bilingual, multitask benchmark for long context understanding. *arXiv preprint arXiv:2308.14508*, 2023.

Parishad BehnamGhader, Vaibhav Adlakha, Marius Mosbach, Dzmitry Bahdanau, Nicolas Chapados, and Siva Reddy. Llm2vec: Large language models are secretly powerful text encoders. *arXiv preprint arXiv:2404.05961*, 2024.

Iz Beltagy, Matthew E Peters, and Arman Cohan. Longformer: The long-document transformer. *arXiv preprint arXiv:2004.05150*, 2020.

Aydar Bulatov, Yury Kuratov, and Mikhail Burtsev. Recurrent memory transformer. *Advances in Neural Information Processing Systems*, pp. 11079–11091, 2022.

Howard Chen, Ramakanth Pasunuru, Jason E Weston, and Asli Celikyilmaz. Walking down the memory maze: Beyond context limit through interactive reading. *arXiv preprint arXiv:2310.05029*, 2023.

Alexis Chevalier, Alexander Wettig, Anirudh Ajith, and Danqi Chen. Adapting language models to compress contexts. In *Conference on Empirical Methods in Natural Language Processing*, pp. 3829–3846, 2023.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Zhiyong Wu, Baobao Chang, Xu Sun, Jingjing Xu, and Zhifang Sui. A survey on in-context learning. *arXiv preprint arXiv:2301.00234*, 2022.

Abhimanyu Dubey, Abhinav Jauhri, Abhinav Pandey, Abhishek Kadian, Ahmad Al-Dahle, Aiesha Letman, Akhil Mathur, Alan Schelten, Amy Yang, Angela Fan, et al. The llama 3 herd of models. *arXiv preprint arXiv:2407.21783*, 2024.

Leo Gao, Stella Biderman, Sid Black, Laurence Golding, Travis Hoppe, Charles Foster, Jason Phang, Horace He, Anish Thite, Noa Nabeshima, et al. The pile: An 800gb dataset of diverse text for language modeling. *arXiv preprint arXiv:2101.00027*, 2020.

Ari Holtzman, Jan Buys, Li Du, Maxwell Forbes, and Yejin Choi. The curious case of neural text degeneration. *arXiv preprint arXiv:1904.09751*, 2019.

Edward J Hu, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Lu Wang, Weizhu Chen, et al. Lora: Low-rank adaptation of large language models. In *International Conference on Learning Representations*, 2022.

Hamish Ivison, Yizhong Wang, Valentina Pyatkin, Nathan Lambert, Matthew Peters, Pradeep Dasigi, Joel Jang, David Wadden, Noah A Smith, Iz Beltagy, et al. Camels in a changing climate: Enhancing lm adaptation with tulu 2. *arXiv preprint arXiv:2311.10702*, 2023.

Albert Q Jiang, Alexandre Sablayrolles, Arthur Mensch, Chris Bamford, Devendra Singh Chaplot, Diego de las Casas, Florian Bressand, Gianna Lengyel, Guillaume Lample, Lucile Saulnier, et al. Mistral 7b. *arXiv preprint arXiv:2310.06825*, 2023a.

Huiqiang Jiang, Qianhui Wu, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. Llmlingua: Compressing prompts for accelerated inference of large language models. *arXiv preprint arXiv:2310.05736*, 2023b.

Huiqiang Jiang, Qianhui Wu, Xufang Luo, Dongsheng Li, Chin-Yew Lin, Yuqing Yang, and Lili Qiu. Longllmlingua: Accelerating and enhancing llms in long context scenarios via prompt compression. In *Annual Meeting of the Association for Computational Linguistics*, 2023c.

Hoyoun Jung and Kyung-Joong Kim. Discrete prompt compression with reinforcement learning. *IEEE Access*, 2024.

Sehoon Kim, Sheng Shen, David Thorsley, Amir Gholami, Woosuk Kwon, Joseph Hassoun, and Kurt Keutzer. Learned token pruning for transformers. In *ACM SIGKDD Conference on Knowledge Discovery and Data Mining*, pp. 784–794, 2022.

Philippe Laban, Tobias Schnabel, Paul Bennett, and Marti A Hearst. Keep it simple: Unsupervised simplification of multi-paragraph text. In *International Joint Conference on Natural Language Processing*, pp. 6365–6378, 2021.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in Neural Information Processing Systems*, 33:9459–9474, 2020.

Yucheng Li, Bo Dong, Frank Guerin, and Chenghua Lin. Compressing context to enhance inference efficiency of large language models. In *Conference on Empirical Methods in Natural Language Processing*, pp. 6342–6353, 2023a.

Zehan Li, Xin Zhang, Yanzhao Zhang, Dingkun Long, Pengjun Xie, and Meishan Zhang. Towards general text embeddings with multi-stage contrastive learning. *arXiv preprint arXiv:2308.03281*, 2023b.

Chin-Yew Lin. Rouge: A package for automatic evaluation of summaries. In *Text Summarization Branches Out*, pp. 74–81, 2004.

Barys Liskavets, Maxim Ushakov, Shuvendu Roy, Mark Klibanov, Ali Etemad, and Shane Luke. Prompt compression with context-aware sentence encoding for fast and improved llm inference. *AAAI Conference on Artificial Intelligence*, 2025.

Tomas Mikolov, Kai Chen, Greg Corrado, and Jeffrey Dean. Efficient estimation of word representations in vector space. *arXiv preprint arXiv:1301.3781*, 2013.

Zhuoshi Pan, Qianhui Wu, Huiqiang Jiang, Menglin Xia, Xufang Luo, Jue Zhang, Qingwei Lin, Victor Rühle, Yuqing Yang, Chin-Yew Lin, et al. Llmlingua-2: Data distillation for efficient and faithful task-agnostic prompt compression. *arXiv preprint arXiv:2403.12968*, 2024.

Jeffrey Pennington, Richard Socher, and Christopher D Manning. Glove: Global vectors for word representation. In *Conference on Empirical Methods in Natural Language Processing*, pp. 1532–1543, 2014.

Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. In *International Joint Conference on Natural Language Processing*, pp. 3982–3992, 2019.

Uri Shaham, Maor Ivgi, Avia Efrat, Jonathan Berant, and Omer Levy. Zeroscrolls: A zero-shot benchmark for long text understanding. In *Conference on Empirical Methods in Natural Language Processing*, 2023.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. *Advances in Neural Information Processing Systems*, 2017.

Cangqing Wang, Yutian Yang, Ruisi Li, Dan Sun, Ruicong Cai, Yuzhu Zhang, Chengqian Fu, and Lillian Floyd. Adapting llms for efficient context processing through soft prompt compression. *arXiv preprint arXiv:2404.04997*, 2024.

Liang Wang, Nan Yang, Xiaolong Huang, Binxing Jiao, Linjun Yang, Daxin Jiang, Rangan Majumder, and Furu Wei. Text embeddings by weakly-supervised contrastive pre-training. *arXiv preprint arXiv:2212.03533*, 2022.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Fangyuan Xu, Weijia Shi, and Eunsol Choi. Recomp: Improving retrieval-augmented lms with context compression and selective augmentation. In *International Conference on Learning Representations*, 2024.

An Yang, Baosong Yang, Beichen Zhang, Binyuan Hui, Bo Zheng, Bowen Yu, Chengyuan Li, Dayiheng Liu, Fei Huang, Haoran Wei, et al. Qwen2. 5 technical report. *arXiv preprint arXiv:2412.15115*, 2024.

Li Yujian and Liu Bo. A normalized levenshtein distance metric. *IEEE Transactions on Pattern Analysis and Machine Intelligence*, pp. 1091–1095, 2007.

Yi Zhao, Zuchao Li, Hai Zhao, Baoyuan Qi, and Guoming Liu. Dac: A dynamic attention-aware approach for task-agnostic prompt compression. *arXiv preprint arXiv:2507.11942*, 2025.

A Appendix

A.1 Qualitative Results

In this section, we first present an example demonstrating the CSE module in action. Figure 10 illustrates the importance of each sentence in the given context, as captured by the `<end_of_sent>` tokens. A darker colour indicates higher importance.

Next, we provide an example of compression in a coding task in Figure 6. First, the CTD module generates the $\hat{q}$ as:

> **CTD obtained task description** $\hat{q}$**:**
> What is the code for the 'test_rw' function in the 'TestSeek' class?

Next, the CSE module generates the compression scores using $\hat{q}$. The colour intensity in Figure 6 demonstrates the importance score. The final compressed prompt is visualized in Figure 7.

Finally, we present an example of summarization in Figure 8. Here, the CTD first generates the $\hat{q}$ as:

> **CTD obtained task description** $\hat{q}$**:**
> Write a one-page summary of the report by the government agency on the review process and documentation of clinical care at VA medical centers.

The $\hat{q}$ is then utilized by CSE to generate the compressed prompt as 9.

Finally, we provide examples illustrating the distinction between task-agnostic and task-aware prompt compression below. In the task-agnostic setup, no prior knowledge about the input is assumed; the input is treated as plain text. In contrast, the task-aware setup assumes that the input prompt can be segmented into distinct components, including the system prompt template I, question(s) Q, and context C, which can be compressed.

> **Task agnostic prompt compression:**
> Please select the answers to the questions presented to you and write out the results in the form of a table. First, read the text carefully, then give your answer.
> Here are the texts:
> Once upon a time, dinosaurs lived in the world, it was about 240 million years ago. Among them, ... stood out.
> ...
> Thus, climate change, provoked by the fall of a meteorite, put an end to the era of dinosaurs.
> Questions:
> When did dinosaurs live on earth?
> What types of dinosaurs are described in the text?
> What caused the end of the dinosaur era?
>
> Answer the questions in the form of a table with three columns: question, short answer, details. Write no more than five sentences in detail for each question

> **Task aware prompt compression:**
>
> I="""
> Please select the answers to the questions presented to you and write out the results in the form of a table. First, read the text carefully, then give your answer.
> Here are the texts:
> {C}
> Questions:
> {Q}
>
> Answer the questions in the form of a table with three columns: question, short answer, details. Write no more than five sentences in detail for each question """
>
> Q="""
> When did dinosaurs live on earth?
> What types of dinosaurs are described in the text?
> What caused the end of the dinosaur era?
> """
>
> C="""
> Once upon a time, dinosaurs lived in the world, it was about 240 million years ago. Among them, ... stood out.
> ...
> Thus, climate change, provoked by the fall of a meteorite, put an end to the era of dinosaurs.
> """

```
Please complete the code given below.  <end_of_sent>
#! /usr/bin/env python <end_of_sent>
# Last Change: Sun Dec 14 07:00 PM 2008 J <end_of_sent>
"""Test for the sndfile class.""" <end_of_sent>
from os.path import join, dirname <end_of_sent>
import os <end_of_sent>
import sys <end_of_sent>
from numpy.testing import TestCase, assert_array_equal, dec <end_of_sent>
import numpy as np <end_of_sent>
from audiolab import Sndfile, Format, available_encodings, available_file_formats <end_of_sent>
from testcommon import open_tmp_file, close_tmp_file, TEST_DATA_DIR <end_of_sent>
_DTYPE_TO_ENC = {np.float64 : 'float64', np.float32: 'float32',  <end_of_sent>
                 np.int32: 'pcm32', np.int16: 'pcm16'} <end_of_sent>
# XXX: there is a lot to refactor here <end_of_sent>
class TestSndfile(TestCase): <end_of_sent>
...
...
...
        a = Sndfile(ofilename, 'r') <end_of_sent>
        a.seek(-buffsize, 1) <end_of_sent>
        assert_array_equal(buff, buff2) <end_of_sent>
        a.close() <end_of_sent>
        # Now, read some frames, go back, and compare buffers <end_of_sent>
        # (check whence == 2 == SEEK_END) <end_of_sent>
        a = Sndfile(ofilename, 'r') <end_of_sent>
        buff = a.read_frames(nframes) <end_of_sent>
        a.seek(-buffsize, 2) <end_of_sent>
        buff2 = a.read_frames(buffsize) <end_of_sent>
        assert_array_equal(buff[-buffsize:], buff2) <end_of_sent>
    def test_rw(self): <end_of_sent>
        """Test read/write pointers for seek.""" <end_of_sent>
        ofilename = join(TEST_DATA_DIR, 'test.wav') <end_of_sent>
Next line of code: <end_of_sent>
```

Figure 6: CSE segment scores colormap for coding prompt. Darker colours indicate higher scores.

A.2 Dataset curation prompts

```
Prompt 1:
You are tasked with writing user queries based on a long context. Consider the topic of the context
when formulating the query. Queries should be concise and specific. You may also ask more complex
questions, such as requesting specific knowledge extraction from the text, extending the text,
answering questions based on the text, paraphrasing/rewriting the text, or summarizing the text.
Do not include the word "context" in the query.
Long context: {text}
Query:
```

```
Prompt 2:
You are tasked with writing a user query based on a long context. Create a complex template that
integrates this context and a question into a single instruction.
The template must include the placeholders {text} and {question}.
Template examples:
1. You are given a text and a question related to it. Answer the question based on the text.
Question: {question}
Text: {text}
Now answer the question:
2. Can you extend the following block of code: {text}
such that it satisfies the requirement: {question}
Now write the code:
Provide various templates, taking into account the topic of the text and the question.
```

```
Please complete the code given below.
#! /usr/bin/env python
"""Test for the sndfile class."""
# XXX: there is a lot to refactor here
class TestSndfile(TestCase):
    def test_basic_io(self):
        """ Check open, close and basic read/write"""
        # dirty !
    def test_basic_io_fd(self):
        """ Check open from fd works"""
    def test_raw(self):
        rawname = join(TEST_DATA_DIR, 'test.raw')
        """Check float32 write/read works"""
        """Check 32 bits pcm write/read works"""
        """Check 16 bits pcm write/read works"""
        self._test_read_write(np.int16)
    def _test_read_write(self, dtype):
    #def test_supported_features(self):
        """Check for bad arguments."""
        """ Try to seek really far."""
                              e.__class__)
class TestSeek(TestCase):
    def test_simple(self):
        ofilename = join(TEST_DATA_DIR, 'test.wav')
        # Open the test file for reading
    def test_rw(self):
        """Test read/write pointers for seek."""
        ofilename = join(TEST_DATA_DIR, 'test.wav')
Next line of code:
```

Figure 7: Compressed coding prompt after taking the top-scored segments.

Prompt 3:
You are given a long text consisting of numbered sentences. Your task is to generate complex multi-hop questions about this text, such that answering them requires step-by-step reasoning (in multiple hops). To achieve this, first, ask a series of sequential factual questions and identify the corresponding sentences that contain the answers to these questions. Then, formulate a final question that can only be answered by combining the information from the previously generated questions and answers. Additionally, specify which sentences (by their numbers) contain the information necessary to answer the final question.

Toy example: [[1]] John is married to Mary. [[2]] They've decided to spend their marriage anniversary in Spain. [[3]] Mary was afraid that their two small children, Jody and Sue, were too small for a flight. [[4]] That's why she asked her elder sister Jane to look after them.
Questions:
Question 1: Who is John married to?
Answer 1: John is married to Mary, as stated in [[1]].
Question 2: How many children does Mary have?
Answer 2: Mary has two children, as stated in [[3]].

Combining the questions to create a multi-hop question:
1. John is married to Mary, as stated in [[1]].
2. Mary has two children, as stated in [[3]].
Final question: How many children does John have?
Necessary sentences: [[1]], [[3]]

Now, solve this example:
{text}
Questions:

```
You are given a report by a government agency. <end_of_sent>
Write a one-page summary of the report.

 <end_of_sent>
Report:
 <end_of_sent>
We found that from October 2013 through March 2017, the five selected VA medical centers required reviews of a total of 148 providers' clini
cal care after concerns were raised about their care, but officials at these medical centers could not provide documentation to show that al
most half of these reviews were conducted. <end_of_sent>
We found that all five VA medical centers lacked at least some documentation of the reviews they told us they conducted, and in some cases,
we found that the required reviews were not conducted at all. <end_of_sent>
Specifically, across the five VA medical centers, we found the following: The medical centers lacked documentation showing that one type of
review—focused professional practice evaluations (FPPE) for cause—had been conducted for 26 providers after concerns had been raised about t
heir care. <end_of_sent>
FPPEs for cause are reviews of providers' care over a specified period of time, during which the provider continues to see patients and has
the opportunity to demonstrate improvement. <end_of_sent>
Documentation of these reviews is explicitly required under VHA policy. <end_of_sent>
Additionally, VA medical center officials confirmed that FPPEs for cause that were required for another 21 providers were never conducted. <
end_of_sent>
The medical centers lacked documentation showing that retrospective reviews—which assess the care previously delivered by a provider during
a specific period of time— had been conducted for 8 providers after concerns had been raised about their clinical care. <end_of_sent>
...
...
...
A committee within the VA medical center had recommended that the provider's privileges be revoked prior to the agreement. <end_of_sent>
There was no documentation of the reasons why this provider was not reported to the NPDB under VHA policy. <end_of_sent>
To improve VA medical centers' reporting of providers to the NPDB and state licensing boards and VHA oversight of these processes, we recomm
ended that VHA require its networks to establish a process for overseeing VA medical centers to ensure they are reporting to the NPDB and to
state licensing boards and to ensure that this reporting is timely. <end_of_sent>
VA concurred with this recommendation and told us that it plans to include oversight of timely reporting to the NPDB and state licensing boa
rds as part of the standard audit tool used by the networks. <end_of_sent>
If you or your staff members have any questions concerning this testimony, please contact me at (202) 512-7114 (williamsonr@gao.gov). <end_o
f_sent>
Contact points for our Office of Congressional Relations and Public Affairs may be found on the last page of this statement. <end_of_sent>
Other individuals who made key contributions to this testimony include Marcia A. Mann (Assistant Director), Kaitlin M. McConnell (Analyst-in
-Charge), Summar C. Corley, Krister Friday, and Jacquelyn Hamilton. <end_of_sent>
The published product may be reproduced and distributed in its entirety without further permission from GAO. <end_of_sent>
Now, write a one-page summary of the report.

 <end_of_sent>
Summary: <end_of_sent>
```

Figure 8: CSE segment scores colormap for summarization prompt. Darker colours indicate higher scores.

```
You are given a report by a government agency. Write a one-page summary of the report.

 Report:
 We found that from October 2013 through March 2017, the five selected VA medical centers required reviews of a total of 148 providers' clin
ical care after concerns were raised about their care, but officials at these medical centers could not provide documentation to show that a
lmost half of these reviews were conducted. The medical centers lacked documentation showing that retrospective reviews—which assess the car
e previously delivered by a provider during a specific period of time— had been conducted for 8 providers after concerns had been raised abo
ut their clinical care. One medical center lacked documentation showing that reviews had been conducted for another 12 providers after conce
rns had been raised about their care. In the absence of any documentation, we were unable to identify the types of reviews, if any, that wer
e conducted for these 12 providers. We also found that the five selected VA medical centers did not always conduct reviews of providers' cli
nical care in a timely manner. VA concurred with these recommendations and described plans for VHA to revise existing policy and update the
standardized audit tool used by the networks to include more comprehensive oversight of VA medical centers' reviews of providers' clinical c
are after concerns have been raised. Now, write a one-page summary of the report.

 Summary:
```

Figure 9: Compressed summarization prompt after taking the top-scored segments.

Figure 10: Visualization of the operation of the compression model with special tokens. Each <end_of_sent> token is highlighted with an intensity proportional to its importance in terms of answering the question.

Methods	Datasets			
	Krapivin	SummScreenFD	PubMed	Meetingbank
Task-aware evaluation				
CPC	0.435	0**0.2183**	**0.275**	0.1766
TPC (ours)	**0.628**	0.205	0.261	**0.181**
Task-agnostic evaluation				
CPC with fixed question	0.439	0.201	0.270	0.172
CPC w/o question	0.418	0.190	0.240	0.156
TPC (ours)	**0.724**	**0.205**	**0.276**	**0.186**

Table 4: Task-aware and task-agnostic evaluation.

A.3 Experiments

To further highlight the efficiency of our method against CPC, we conduct experiments on 4 additional out-of-distribution datasets. The results are presented in Table 4. As evident from the results, while being 7 times smaller (1B parameters) than CPC (7B parameters), TPC outperforms it on keyword extraction (Krapivin), and summarizing meetings (meetingbank), and performs as per on the PubMed and SummScreenFD datasets. More importantly, unlike CPC, TPC does not require any handcrafted prompts, explicit question format, or prompt template to work on these new tasks. Furthermore, TPC outperforms CPC with a larger margin in the prompt-agnostic setup. These results emphasize the effectiveness and generalization of the task-agnostic nature of TPC.

Next, we compare our method with a concurrent work, DAC (Zhao et al., 2025), on a subset of the datasets on which they evaluated their method. The results are presented in Table 5. As we find from this table, our method considerably outperforms DAC on most datasets, with DAC performing marginally better on only 3 datasets.

Methods	Datasets								
	NarrativeQA	Qasper	MultifieldQA	HotpotQA	2WikiMQA	Musique	GovReport	MultiNews	QMSum
DAC	**24.85**	33.46	40.12	42.37	39.57	22.44	30.40	**25.77**	**25.95**
TPC (ours)	23.72	**37.75**	**50.25**	**45.06**	**53.87**	**26.78**	**31.15**	25.45	21.82

Table 5: Comparison of DAC and TPC across nine datasets.

A.4 Licenses

We used pre-trained models and open-source datasets. In terms of models, we use models from the Qwen-2.5 family and Mistral family, which are licensed under the APACHE-2.0 license. We also used the LLama-3.2 model, which is licensed under the "LLAMA 3.2 COMMUNITY LICENSE AGREEMENT". All the models used are available for research purposes.

As our training dataset, we used "allenai/tulu-3-sft-mixture", which is licensed under the "Open Data Commons License Attribution family", as well as "abacusai/MetaMathFewshot" and "ise-uiuc/Magicoder-Evol-Instruct-110K", which are licensed under the APACHE-2.0 license. We assume that these data follow the well-known HHH paradigm. Therefore, taking data from these sources should not introduce potentially malicious behaviour into our models. We also used the Pile dataset, which is licensed under the MIT license. We conduct manual checks on subsamples of the datasets to verify the cleanliness and safety of the data. In addition, we provide full details on how we created the datasets in the 3.4.1 section.

We evaluate our method on benchmarks such as MIT-licensed LongBench and MIT-licensed ZeroScrolls. All aforementioned models, datasets, and benchmarks are publicly available and imply research use. Their prescribed terms of use are hereby aligned with our research work.