ConE: Cone Embeddings for Multi-Hop Reasoning over Knowledge Graphs

Abstract

Query embedding (QE)—which aims to embed entities and first-order logical (FOL) queries in low-dimensional spaces—has shown great power in multi-hop reasoning over knowledge graphs. Recently, embedding entities and queries with geometric shapes becomes a promising direction, as geometric shapes can naturally represent answer sets of queries and logical relationships among them. However, existing geometry-based models have difficulty in modeling queries with negation, which significantly limits their applicability. To address this challenge, we propose a novel query embedding model, namely **Con**e **E**mbeddings (ConE), which is the first geometry-based QE model that can handle all the FOL operations, including conjunction, disjunction, and negation. Specifically, ConE represents entities and queries as Cartesian products of two-dimensional cones, where the intersection and union of cones naturally model the conjunction and disjunction operations. By further noticing that the closure of complement of cones remains cones, we design geometric complement operators in the embedding space for the negation operations. Experiments demonstrate that ConE significantly outperforms existing state-of-the-art methods on benchmark datasets.

1 Introduction

Multi-hop reasoning over knowledge graphs (KGs)—which aims to find answer entities of given queries using knowledge from KGs—has attracted great attention from both academia and industry recently [22, 21, 15]. In general, it involves answering first-order logic (FOL) queries over KGs using operators including existential quantification ($\exists$), conjunction ($\wedge$), disjunction ($\vee$), and negation ($\neg$). A popular approach to multi-hop reasoning over KGs is to first transform a FOL query to its corresponding computation graph—where each node represents a set of entities and each edge represents a logical operation—and then traverse the KG according to the computation graph to identify the answer set. However, this approach confronts two major challenges. First, it needs to deal with all the intermediate entities on reasoning paths, leading to exponential computation cost. Second, when some links are missing in KGs, it has difficulties in identifying the correct answers.

To address these challenges, researchers have paid increasing attention to the query embedding (QE) technique, which embeds entities and FOL queries in low-dimensional spaces [12, 20, 19, 23]. QE models associate each logical operator in computation graphs with a logical operation in embedding spaces. Given a query, QE models generate query embeddings following the corresponding computation graph. Then, they determine whether an entity is a correct answer based on similarities between the query embeddings and entity embeddings.

Among the existing QE models, geometry-based models that embed entities and queries into geometric shapes have shown promising performance [12, 11, 5, 20]. Geometry-based models usually represent entity sets as "regions" (e.g., points and boxes) in Euclidean spaces and then design set operations

upon them. For example, Query2Box [20] represents entities as points and queries as boxes. If a point is inside a box, then the corresponding entity is the answer to the query. Compared with non-geometric methods, geometric shapes provide a natural and easily interpretable way to represent sets and logical relationships among them.

However, existing geometry-based models have difficulty in modeling queries with negations, which significantly limits their applicability. For example, GQE [12] and Query2Box [20]—which embed queries to points and boxes, respectively—cannot handle queries with negation, as the complement of a point/box is no longer a point/box. To tackle this problem, Ren & Leskovec [19] propose a probabilistic QE model using Beta distributions. However, it does not have some advantages of geometric models. For example, using Beta distributions, it is unclear how to determine whether an entity is an answer to a query as that in the box case [20]. Therefore, proposing a geometric QE model that can model all the FOL queries is still challenging but promising.

In this paper, we propose a novel geometry-based query embedding model—namely, **Con**e **E**mbeddings (ConE)—which represents entities and queries as Cartesian products of two-dimensional cones. Specifically, if the cones representing entities are subsets of the cones representing queries, then these entities are the answers to the query. To perform multi-hop reasoning in the embedding space, we define the conjunction and disjunction operations that correspond to the intersection and union of cones. Further, by noticing that the closure of complement of cones are still cones, we correspondingly design geometric complement operators in the embedding space for the negation operations. To the best of our knowledge, ConE is the first geometry-based QE model that can handle all the FOL operations, including conjunction, disjunction, and negation. Experiments demonstrate that ConE significantly outperforms existing state-of-the-art methods on benchmark datasets.

2 Related Work

Our work is related to answering multi-hop logical queries over KGs and other geometric embeddings.

Answering multi-hop logical queries over KGs. To answer multi-hop FOL queries, path-based methods [28, 16, 10] start from anchor entities and require traversing the intermediate entities on the path, which leads to exponential computation cost. Embedding-based models are another line of works, which embed FOL queries into low-dimensional spaces. For example, existing works embed queries to geometric shapes [12, 20, 11, 5], probability distributions [19], and complex objects [9, 23]. Our work also embeds queries to geometric shapes. The main difference is that our work can handle all the FOL operations, while existing works cannot.

Other Geometric embeddings. Geometric embeddings are popular in recent years. For example, geometric operations including translation [3, 17], rotation [26, 24], and complex geometric operations [1, 30] have been widely used in knowledge graph embeddings. Other geometric embedding methods also manage to use boxes [6], convex cones [14, 27], etc. Recent years have also witnessed the development of embeddings in non-Euclidean geometry, such as Poincaré embeddings [1, 18] and hyperbolic entailment cones [8]. Although there exist works that also use cone embeddings [14, 27, 8], they are not designed for the multi-hop reasoning task and their definition of cones are different from that in our work.

3 Preliminaries

In this section, we review the background of query embeddings in Section 3.1 and introduce some basic concepts of two-dimensional cones in Section 3.2.

3.1 Backgrounds

We review knowledge graphs, first-order logic, computation graphs, and query embeddings.

Knowledge Graphs (KGs). Given a set $\mathcal{V}$ of entities (vertices) and a set $\mathcal{E}$ of relations (edges), a knowledge graph $\mathcal{G} = \{(s_i, p_j, o_k)\} \subset \mathcal{V} \times \mathcal{E} \times \mathcal{V}$ is a set of factual triples, where $p_j \in \mathcal{E}$ is a predicate, and $s_i, o_k \in \mathcal{V}$ are subject and object, respectively. Suppose that $r_j(\cdot, \cdot) \in \mathcal{R}$ is a binary function $r_j : \mathcal{V} \times \mathcal{V} \to \{\text{True}, \text{False}\}$ corresponding to p_j, where $r_j(s_i, o_k) = \text{True}$ if and only if (s_i, p_j, o_k) is a factual triples. Then, for all $(s_i, p_j, o_k) \in \mathcal{G}$, we have $r_j(s_i, o_k) = \text{True}$.

(a) A Computation Graph   (b) Cones

Figure 1: Examples of a computation graph and several cones. In Figure 1a, the natural language interpretation of the query is "List all the directors of non-American movies that win the Academy Awards". In Figure 1b, the four cones are: a cone with aperture 0, a sector-cone with aperture $0 < \alpha_1 < \pi$, a sector-cone with aperture $\alpha_2 = 2\pi$, and a cone that is the union of two sector-cones.

First-Order Logic (FOL). FOL queries in the query embedding literature involve logical operations including existential quantification ($\exists$), conjunction ($\wedge$), disjunction ($\vee$), and negation ($\neg$). Universal quantification ($\forall$) is not included, as no entity connects with all other entities in real-world KGs [19].

We use FOL queries in its Disjunctive Normal Form (DNF) [7], which represents FOL queries as a disjunction of conjunctions. To formulate FOL queries, we assume that $\mathcal{V}_a \subset \mathcal{V}$ is the non-variable anchor entity set, $V_1, \ldots, V_k$ are existentially quantified bound variables, and $V_?$ is the target variable, i.e., the answers to a certain query. Then, a FOL query q in the disjunctive normal form is:

$$q[V_?] = V_?. \exists V_1, \ldots, V_k : c_1 \vee c_2 \vee \cdots \vee c_n.$$

Specifically, c_i are *conjunctions*, i.e., $c_i = e_{i1} \wedge \cdots \wedge e_{im}$, where $e_{ij} = r(v_a, V)$ or $\neg r(v_a, V)$ or $r(V', V)$ or $\neg r(V', V)$, $v_a \in \mathcal{V}_a, V \in \{V_?, V_1, \ldots, V_k\}, V' \in \{V_1, \ldots, V_k\}$, and $V \neq V'$.

Using the aforementioned notations, answering a query q is equivalent to *finding the set of entities* $[\![q]\!] \subset \mathcal{V}$, where $v \in [\![q]\!]$ if and only if $q[v]$ is True.

Computation Graphs. Given a query, we represent the reasoning procedure as a computation graph (see Figure 1a for an example), of which nodes represent entity sets and edges represent logical operations over entity sets. We map edges to logical operators according to the following rules.

- *Relation Traversal→Projection Operator $\mathcal{P}$.* Given a set of entities $S \subset \mathcal{V}$ and a relational function $r \in \mathcal{R}$, the projection operator $\mathcal{P}$ outputs all the adjacent entities $\cup_{v \in S} N(v, r)$, where $N(v, r)$ is the set of entities such that $r(v, v') =$ True for all $v' \in N(v, r)$.
- *Conjunction→Intersection Operator $\mathcal{I}$.* Given n sets of entities $\{S_1, S_2, \ldots, S_n\}$, the intersection operator $\mathcal{I}$ performs set intersection to obtain $\cap_{i=1}^n S_n$.
- *Disjunction→Union Operator $\mathcal{U}$.* Given n sets of entities $\{S_1, S_2, \ldots, S_n\}$, the union operator $\mathcal{U}$ performs set union to obtain $\cup_{i=1}^n S_n$.
- *Negation→Complement Operator $\mathcal{C}$.* Given an entity set $S \subset \mathcal{V}$, $\mathcal{C}$ gives $\bar{S} = \mathcal{V} \backslash S$.

Query Embeddings (QE). QE models generate low-dimensional continuous embeddings for queries and entities, and associate each logical operator for entity sets with an operation in embedding spaces. Since an entity is equivalent to a set with a single element and each query q is corresponding to a unique answer set $[\![q]\!]$, the aim of QE models is equivalent to embedding entity sets that can be answers to some queries.

3.2 Cones in Two-Dimensional Spaces

To represent FOL queries as Cartesian products of two-dimensional cones, we introduce some definitions about cones and the parameterization method of a special class of cones.

Definition 1 (Boyd & Vandenberghe [4]). *A set $C \subset \mathbb{R}^2$ is called a **cone**, if for every $x \in C$ and $\lambda \geq 0$, we have $\lambda x \in C$. A set is a **convex cone** if it is convex and a cone, which means that for any $x_1, x_2 \in C$ and $\lambda_1, \lambda_2 \geq 0$, we have $\lambda_1 x_1 + \lambda_2 x_2 \in C$.*

By letting $\lambda = 0$ in Definition 1, we know that a cone must contain the origin. In view of this property, we define a new operation called *closure-complement* for cones.

121 **Definition 2.** *Suppose that $C \subset \mathbb{R}^2$ is a cone. Then, the **closure-complement** of C is defined by*
122 $\tilde{C} = \boldsymbol{cl}(\mathbb{R}^2 \backslash C)$, *where $\boldsymbol{cl}(\cdot)$ is the closure of a set.*

123 Next, we introduce a class of cones that can be parameterized in a scalable way.

124 **Definition 3.** *A 2D closed cone is called a **sector-cone**, if its closure-complement or itself is convex.*

125 The set of sector-cones is closed under closure-complement and their union and intersection are still
126 cones. Besides, we have the following proposition, whose proof is provided in Appendix A.

127 **Proposition 1.** *A sector-cone is always axially symmetric.*

128 **Parameterization of 2D Sector-Cones.** Proposition 1 suggests that we can use a pair of parameters
129 to represent a two-dimensional sector-cone:

$$(\theta_{\mathrm{ax}}, \theta_{\mathrm{ap}}), \text{where } \theta_{\mathrm{ax}} \in [-\pi, \pi), \ \theta_{\mathrm{ap}} \in [0, 2\pi].$$

130 Specifically, θ_{ax} represents the angle between the symmetry axis of the sector-cone and the positive x
131 axis. θ_{ap} represents the aperture of the sector-cone. For any points in the cone, its phase will be in
132 $[\theta_{\mathrm{ax}} - \theta_{\mathrm{ap}}/2, \theta_{\mathrm{ax}} + \theta_{\mathrm{ap}}/2]$. Figure 1b gives examples of several (sector-)cones.

133 Let $\mathbb{K}$ be the space consisting of all $(\theta_{\mathrm{ax}}, \theta_{\mathrm{ap}})$. We can represent an arbitrary sector-cone C_0 as
134 $C_0 = (\theta_{\mathrm{ax}}, \theta_{\mathrm{ap}}) \in \mathbb{K}$. Then, for a d-ary Cartesian product of sector-cones

$$C = C_1 \times C_2 \times \ldots \times C_d, \tag{1}$$

135 we represent it via a d-dimensional vector in $\mathbb{K}^d$:

$$C = \left((\theta_{\mathrm{ax}}^1, \theta_{\mathrm{ap}}^1), \ldots, (\theta_{\mathrm{ax}}^d, \theta_{\mathrm{ap}}^d)\right) \subset \mathbb{K}^d. \tag{2}$$

136 where $\theta_{\mathrm{ax}}^i \in [-\pi, \pi)$, $\theta_{\mathrm{ap}}^i \in [0, 2\pi]$, for $i = 1, \ldots, d$. Or equivalently, $C = (\boldsymbol{\theta}_{\mathrm{ax}}, \boldsymbol{\theta}_{\mathrm{ap}})$, where
137 $\boldsymbol{\theta}_{\mathrm{ax}} = (\theta_{\mathrm{ax}}^1, \ldots, \theta_{\mathrm{ax}}^d) \in [-\pi, \pi)^d$ and $\boldsymbol{\theta}_{\mathrm{ap}} = (\theta_{\mathrm{ap}}^1, \ldots, \theta_{\mathrm{ap}}^d) \in [0, 2\pi]^d$.

138 4 Cone Embeddings

139 In this section, we propose **Co**ne **E**mbeddings (ConE) for multi-hop reasoning over KGs. We first
140 introduce cone embeddings for conjunctive queries and entities in Section 4.1. Afterwards, we
141 introduce the logical operators and the methods to learn ConE in Sections 4.2 and 4.3.

142 4.1 Cone Embeddings for Conjunctive Queries and Entities

143 As introduced in Section 3.1, conjunctive queries constitute the basis of all queries in the DNF form.
144 Embeddings of all queries can be generated by applying logical operators to conjunctive queries'
145 embeddings. Thus, we design embeddings for conjunctive queries in this section. We model queries
146 with disjunction using the Union Operator $\mathcal{U}$ in Section 4.2.

147 In general, the answer entities to a conjunctive query q have similar semantics. For example, answers
148 to the query that "List all the directors of American movies" should all be persons; answers to the
149 query that "List all the Asian cities that ever held Olympic Games" should all be places. If we embed
150 an entity set $[\![q]\!]$ into an embedding space, entities in $[\![q]\!]$ should have similar embeddings. Thus, we
151 expect their embeddings to form a "region" in the embedding space. If the embedding of an entity
152 is inside the region, then the entity is likely to be an answer. Further, we can find a semantic center
153 and a boundary for the region, where the semantic center represents the semantics of $[\![q]\!]$ and the
154 boundary designates how many entities are in $[\![q]\!]$.

155 To model the embedding region of $[\![q]\!]$, we propose to embed it to a Cartesian product of *sector-cones*.
156 Specifically, we use the parameter θ_{ax}^i to represent the semantic center, and the parameter θ_{ap}^i to
157 determine the boundary of $[\![q]\!]$. If we use a d-ary Cartesian product, i.e., the embedding dimension is
158 d, we define the embedding of $[\![q]\!]$ as

$$\mathbf{V}_q^c = (\boldsymbol{\theta}_{\mathrm{ax}}, \boldsymbol{\theta}_{\mathrm{ap}}),$$

159 where $\boldsymbol{\theta}_{\mathrm{ax}} \in [-\pi, \pi)^d$ are *axis embeddings* and $\boldsymbol{\theta}_{\mathrm{ap}} \in [0, 2\pi]^d$ are *aperture embeddings*.

160 An entity $v \in \mathcal{V}$ is equivalent to an entity set with a single element, i.e., $\{v\}$. We propose to represent
161 an entity as a Cartesian product of cones with apertures 0, where the axes indicates the semantics of
162 the entity. Formally, if the embedding dimension is d, the cone embedding of v is $\mathbf{v} = (\boldsymbol{\theta}_{\mathrm{ax}}, \mathbf{0})$, where
163 $\boldsymbol{\theta}_{\mathrm{ax}} \in [-\pi, \pi)^d$ is the axis embedding and $\mathbf{0}$ is a d-dimensional vector with all elements being 0.

| (a) Projection | (b) Intersection | (c) Union | (d) Complement | (e) Distance |

Figure 2: ConE's logical operators and distance function, of which the embedding dimension $d = 1$.

4.2 Logical Operators for Cone Embeddings

In this section, we introduce our designed logical operators of ConE in the embedding space, including projection, intersection, union, and complement.

It is worth noting that, the composition of logical operators may lead to non-sense queries. For example, the queries "List the intersection/union of American movies and non-American movies" and "List the intersection of American movies and Asian movies" make no sense in real-world applications. However, the main aim of a query embedding model is to represent all entity sets that *can be answer to some real-world query*. Therefore, we do not need to model the entity sets that only correspond to theoretically possible queries [19].

Projection Operator $\mathcal{P}$. The goal of $\mathcal{P}$ is to represent an entity's adjacent entities that are linked by a given relation. It maps an entity set to another entity set (see Figure 2a). Thus, we define a relation-dependent function in the embedding space for $\mathcal{P}$:

$$f_r : \mathbb{K}^d \to \mathbb{K}^d, \ \mathbf{V}_q^c \mapsto \mathbf{V}_q^{c'}.$$

We implement f_r in a neural way. First, we represent relations as relational translations of query embeddings and assign each relation with an embedding in the d-dimensional cone space, i.e., $\mathbf{r} = (\boldsymbol{\theta}_{\text{ax},r}, \boldsymbol{\theta}_{\text{ap},r}) \in \mathbb{K}^d$. Then, we define f_r as

$$f_r(\mathbf{V}_q) = g(\mathbf{MLP}([\boldsymbol{\theta}_{\text{ax}} + \boldsymbol{\theta}_{\text{ax},r}; \boldsymbol{\theta}_{\text{ap}} + \boldsymbol{\theta}_{\text{ap},r}])) \tag{3}$$

where $\mathbf{MLP} : \mathbb{R}^{2d} \to \mathbb{R}^{2d}$ is a multi-layer perceptron network, $[\cdot; \cdot]$ is the concatenation of two vectors, and g is a function that generates $\boldsymbol{\theta}'_{\text{ax}} \in [-\pi, \pi)^d$ and $\boldsymbol{\theta}'_{\text{ap}} \in [0, 2\pi]^d$. We define g as:

$$[g(\mathbf{x})]_i = \begin{cases} \theta'^i_{\text{ax}} = \pi \tanh(\lambda_1 x_i), & \text{if } i \leq d, \\ \theta'^{i-d}_{\text{ap}} = \pi \tanh(\lambda_2 x_i) + \pi, & \text{if } i > d. \end{cases}$$

where $[g(\mathbf{x})]_i$ denotes the i-th element of $g(\mathbf{x})$, λ_1 and λ_2 are two fixed parameters to control the scale. Note that the range of the hyperbolic tangent function ($\tanh$) are open sets. Thus, we cannot indeed get the boundary value $\theta'^i_{\text{ax}} = -\pi$ and $\theta'^i_{\text{ap}} = 0, 2\pi$. However, when we implement g in experiments, the value of g can be very close to 0 and 2π, which is equivalent to the closed set numerically.

Intersection Operator $\mathcal{I}$. Given a query q that is the conjunction of conjunctive queries q_i, the goal of $\mathcal{I}$ is to represent $\llbracket q \rrbracket = \cap_{i=1}^n \llbracket q_i \rrbracket$. Since the conjunction of conjunctive queries are still conjunctive queries, the entities in $\llbracket q \rrbracket$ should have similar semantics. Recall that we only need to model entity sets that can be answers. We still use a Cartesian product of sector-cones to represent $\llbracket q \rrbracket$ (see Figure 2b). Suppose that $\mathbf{V}_q^c = (\boldsymbol{\theta}_{\text{ax}}, \boldsymbol{\theta}_{\text{ap}})$ and $\mathbf{V}_{q_i}^c = (\boldsymbol{\theta}_{i,\text{ax}}, \boldsymbol{\theta}_{i,\text{ap}})$ are cone embeddings for $\llbracket q \rrbracket$ and $\llbracket q_i \rrbracket$, respectively. We define the intersection operator as follows:

$$\boldsymbol{\theta}_{\text{ax}} = \mathbf{SemanticAverage}(\mathbf{V}_{q_1}^c, \dots, \mathbf{V}_{q_n}^c),$$
$$\boldsymbol{\theta}_{\text{ap}} = \mathbf{CardMin}(\mathbf{V}_{q_1}^c, \dots, \mathbf{V}_{q_n}^c),$$

where $\mathbf{SemanticAverage}(\cdot)$ and $\mathbf{CardMin}(\cdot)$ generates semantic centers and apertures, respectively. In the following, we introduce these two functions in detail.

SemanticAverage. As the semantic center of $\mathbf{V}_q^c$, $\boldsymbol{\theta}_{\text{ax}}$ should be close to all the semantic centers $\boldsymbol{\theta}_{i,\text{ax}}$. Thus, we propose to represent $\boldsymbol{\theta}_{\text{ax}}$ as a semantic average of $\boldsymbol{\theta}_{i,\text{ax}}$. We note that the ordinary weighted average may lead to inconsistent semantics. For example, when $d = 1$, if $\boldsymbol{\theta}_{1,\text{ax}} = \pi - \epsilon$ and $\boldsymbol{\theta}_{2,\text{ax}} = -\pi + \epsilon$ ($0 < \epsilon < \pi/4$), then we expect $\boldsymbol{\theta}_{\text{ax}}$ to be around π. However, if we use the ordinary weighted sum, $\boldsymbol{\theta}_{\text{ax}}$ will be around 0 with a high probability. To tackle this issue, we propose a semantic average scheme, which takes periodicity of axes into account. For a figure illustration of the difference between the ordinary and semantic average, please refer to Appendix D.

Specifically, we first map $[\boldsymbol{\theta}_{i,\mathrm{ax}}]_j$ to points on the unit circle. Then, compute the weighted average of the points using an attention mechanism. Finally, map the points back to angles that represent axes. Formally, the computation process is

$$[\mathbf{x};\mathbf{y}] = \sum_{i=1}^{n}[\mathbf{a}_i \circ \cos(\boldsymbol{\theta}_{i,\mathrm{ax}}); \mathbf{a}_i \circ \sin(\boldsymbol{\theta}_{i,\mathrm{ax}})],$$

$$\boldsymbol{\theta}_{\mathrm{ax}} = \mathbf{Arg}(\mathbf{x},\mathbf{y}),$$

where cos and sin are element-wise cosine and sine functions; $\mathbf{a}_i \in \mathbb{R}^d$ are positive weights vectors that satisfy $\sum_{i=1}^{n}[\mathbf{a}_i]_j = 1$ for all $j = 1,\ldots,d$; $\circ$ is the element-wise multiplication; $\mathbf{Arg}(\cdot)$ is the function that computes arguments of (a Cartesian of) 2D points. Noticing that the weights $\mathbf{a}_i$ are relevant to both axes and apertures, we compute $[\mathbf{a}_i]_j$ via the following attention mechanism:

$$[\mathbf{a}_i]_j = \frac{\exp([\mathbf{MLP}([\boldsymbol{\theta}_{i,\mathrm{ax}} - \boldsymbol{\theta}_{i,\mathrm{ap}}/2; \boldsymbol{\theta}_{i,\mathrm{ax}} + \boldsymbol{\theta}_{i,\mathrm{ap}}/2])]_j)}{\sum_{k=1}^{n}\exp([\mathbf{MLP}([\boldsymbol{\theta}_{k,\mathrm{ax}} - \boldsymbol{\theta}_{k,\mathrm{ap}}/2; \boldsymbol{\theta}_{k,\mathrm{ax}} + \boldsymbol{\theta}_{k,\mathrm{ap}}/2])]_j)},$$

where $\mathbf{MLP} : \mathbb{R}^{2d} \to \mathbb{R}^d$ is a multi-layer perceptron network, $[\cdot;\cdot]$ is the concatenation of two vectors. We can see $\boldsymbol{\theta}_{i,\mathrm{ax}} - \boldsymbol{\theta}_{i,\mathrm{ap}}/2$ and $\boldsymbol{\theta}_{i,\mathrm{ax}} + \boldsymbol{\theta}_{i,\mathrm{ap}}/2$ as the lower and upper bound of sector-cones.

We use $\mathbf{Arg}(\cdot)$ to recover angles of 2D points. Suppose that $\beta_i = \arctan([\mathbf{y}]_i/[\mathbf{x}]_i)$, then

$$[\boldsymbol{\theta}_{\mathrm{ax}}]_i = \begin{cases} \beta_i + \pi, & \text{if } [\mathbf{x}]_i < 0, [\mathbf{y}]_i > 0, \\ \beta_i - \pi, & \text{if } [\mathbf{x}]_i < 0, [\mathbf{y}]_i < 0, \\ \beta_i, & \text{otherwise.} \end{cases}$$

Note that $[\mathbf{x}]_i = 0$ will lead to an illegal division. In experiments, we manually set $[\mathbf{x}]_i$ to be a small number (e.g., 10^{-3}) when $[\mathbf{x}]_i = 0$.

CardMin. Since $[\![q]\!]$ is the subset of all $[\![q_i]\!]$, θ_{ap}^i should be no larger than any apertures $\theta_{j,\mathrm{ap}}^i$. Therefore, we implement **CardMin** by a minimum mechanism with cardinality constraints:

$$\theta_{\mathrm{ap}}^i = \min\{\theta_{1,\mathrm{ap}}^i,\ldots,\theta_{n,\mathrm{ap}}^i\} \cdot \sigma([\mathbf{DeepSets}(\{\mathbf{V}_{q_j}\}_{j=1}^{n})]_i),$$

where $\sigma(\cdot)$ is the element-wise sigmoid function, $\theta_{j,\mathrm{ap}}^i$ is the i-th element of $\boldsymbol{\theta}_{j,\mathrm{ap}}$, $\mathbf{DeepSets}(\cdot)$ is a permutation-invariant function [29]. Specifically, $\mathbf{DeepSets}(\{\mathbf{V}_{q_j}\}_{j=1}^{n})$ is computed by

$$\mathbf{MLP}\left(\frac{1}{n}\sum_{j=1}^{n}\mathbf{MLP}\left([\boldsymbol{\theta}_{j,\mathrm{ax}} - \boldsymbol{\theta}_{j,\mathrm{ap}}/2; \boldsymbol{\theta}_{j,\mathrm{ax}} + \boldsymbol{\theta}_{j,\mathrm{ap}}/2]\right)\right).$$

Union Operator $\mathcal{U}$. Given a query q that is the disjunction of conjunctive queries q_i, the goal of the union operator $\mathcal{U}$ is to represent $[\![q]\!] = \cup_{i=1}^{n}[\![q_i]\!]$. As noted by Ren et al. [20], directly modeling the disjunction leads to unscalable models. Thus, we adopt the DNF technique [20], in which the union operation only appears in the last step in computation graphs.

Suppose that $\mathbf{V}_{q_i}^c = (\boldsymbol{\theta}_{i,\mathrm{ax}}, \boldsymbol{\theta}_{i,\mathrm{ap}})$ are cone embeddings for $[\![q_i]\!]$. To represent the union of several cones (see Figure 2c), we represent $[\![q]\!]$ as a set of $\mathbf{V}_{q_i}^c$:

$$\mathbf{V}_q^d = \{\mathbf{V}_{q_1}^c, \ldots, \mathbf{V}_{q_n}^c\},$$

where n may be various in different queries. Equivalently, $\mathbf{V}_q^d$ can be written as

$$\mathbf{V}_q^d = \left(\{(\theta_{1,\mathrm{ax}}^1, \theta_{1,\mathrm{ap}}^1), \ldots, (\theta_{n,\mathrm{ax}}^1, \theta_{n,\mathrm{ap}}^1)\}, \ldots, \{(\theta_{1,\mathrm{ax}}^d, \theta_{1,\mathrm{ap}}^d), \ldots, (\theta_{n,\mathrm{ax}}^d, \theta_{n,\mathrm{ap}}^d)\}\right).$$

As $\{(\theta_{1,\mathrm{ax}}^i, \theta_{1,\mathrm{ap}}^i), \ldots, (\theta_{n,\mathrm{ax}}^i, \theta_{n,\mathrm{ap}}^i)\}$ are the union of d sector-cones, it is also a cone. Thus, the cone embedding of q is also a Cartesian product of *two-dimensional cones*.

Complement Operator $\mathcal{C}$. Given an conjunctive query q and the corresponding entity set $[\![q]\!]$, the aim of $\mathcal{C}$ is to identify the set $[\![\neg q]\!]$, which is the complementary of $[\![q]\!]$, i.e., $\mathcal{V}\backslash[\![q]\!]$. Since the set of sector-cones is closed under closure-complement, we define $\mathcal{C}$ using the closure-complement. Thus, the apertures of $\mathbf{V}_q$ plus the apertures of $\mathbf{V}_{\neg q}$ should be a vector with all elements being 2π. Moreover, to represent the semantic difference between $[\![q]\!]$ and $[\![\neg q]\!]$, we assume that their semantic centers to be opposite. Please refer to Figure 2d for a figure illustration.

231 Suppose that $\mathbf{V}_q = (\boldsymbol{\theta}_{\mathrm{ax}}, \boldsymbol{\theta}_{\mathrm{ap}})$ and $\mathbf{V}_{\neg q} = (\boldsymbol{\theta}'_{\mathrm{ax}}, \boldsymbol{\theta}'_{\mathrm{ap}})$. We define the complement operator $\mathcal{C}$ as:

$$[\boldsymbol{\theta}'_{\mathrm{ax}}]_i = \begin{cases} [\boldsymbol{\theta}_{\mathrm{ax}}]_i - \pi, & \text{if } [\boldsymbol{\theta}_{\mathrm{ax}}]_i \geq 0, \\ [\boldsymbol{\theta}_{\mathrm{ax}}]_i + \pi, & \text{if } [\boldsymbol{\theta}_{\mathrm{ax}}]_i < 0, \end{cases}$$
$$[\boldsymbol{\theta}'_{\mathrm{ap}}]_i = 2\pi - [\boldsymbol{\theta}_{\mathrm{ap}}]_i.$$

4.3 Learning Cone Embeddings

233 To learn cone embeddings, we expect that the cone embeddings of entities $v \in [\![q]\!]$ are inside the
234 cone embeddings of q, and the cone embeddings of entities $v' \notin [\![q]\!]$ are far from the cone embedding
235 of q. This motivates us to define a distance function to measure the distance between a given query
236 embedding and an entity embedding, and a training objective with negative sampling.

237 **Distance Function.** We first define the distance function for conjunctive queries. Inspired by Ren
238 et al. [20], we divide the distance d into two parts—the outside distance d_o and the inside distance d_i.
239 Figure 2e gives an illustration of the distance function d. Suppose that $\mathbf{v} = (\boldsymbol{\theta}^v_{\mathrm{ax}}, \mathbf{0})$, $\mathbf{V}^c_q = (\boldsymbol{\theta}_{\mathrm{ax}}, \boldsymbol{\theta}_{\mathrm{ap}})$,
240 $\boldsymbol{\theta}_L = \boldsymbol{\theta}_{\mathrm{ax}} - \boldsymbol{\theta}_{\mathrm{ap}}/2$ and $\boldsymbol{\theta}_U = \boldsymbol{\theta}_{\mathrm{ax}} + \boldsymbol{\theta}_{\mathrm{ap}}/2$. We define the distance as

$$d_{con}(\mathbf{v}; \mathbf{V}^c_q) = d_o(\mathbf{v}; \mathbf{V}^c_q) + \lambda d_i(\mathbf{v}; \mathbf{V}^c_q).$$

241 The outside distance and the inside distance are

$$d_o = \|\min\left\{|\sin\left(\boldsymbol{\theta}^v_{\mathrm{ax}} - \boldsymbol{\theta}_L\right)/2|, |\sin\left(\boldsymbol{\theta}^v_{\mathrm{ax}} - \boldsymbol{\theta}_U\right)/2|\right\}\|_1,$$
$$d_i = \|\min\left\{|\sin\left(\boldsymbol{\theta}^v_{\mathrm{ax}} - \boldsymbol{\theta}_{\mathrm{ax}}\right)/2|, |\sin\left(\boldsymbol{\theta}_{\mathrm{ap}}\right)/2|\right\}\|_1,$$

242 where $\|\cdot\|_1$ is the L_1 norm, $\sin(\cdot)$ and $\min(\cdot)$ are element-wise sine and minimization functions.
243 Note that as axes and apertures are periodic, we use the sine function to enforce two close angles
244 have small distance. The parameter $\lambda \in (0, 1)$ is fixed during training, so that $\mathbf{v}$ is encouraged to be
245 inside the cones represented by $\mathbf{V}^c_q$, but not necessarily be equal to the semantic center of $\mathbf{V}^c_q$.

246 Since we represent the disjunctive queries as a set of embeddings, we cannot use d_{con} to directly
247 compute the distance. Nonetheless, the distance between a point and the union of several sets is
248 equal to the minimum distance between the point and each of those sets. Therefore, for a query
249 $q = q_1 \vee \cdots \vee q_n$ in the Disjunctive Normal Form, the distance between q and an entity is

$$d_{dis}(\mathbf{v}; \mathbf{V}^d_q) = \min\{d_{con}(\mathbf{v}; \mathbf{V}^c_{q_1}), \ldots, d_{con}(\mathbf{v}; \mathbf{V}^c_{q_n})\}.$$

250 If we use $\mathbf{V}_q$ to represent embeddings of both kinds of queries, the unified distance function d is

$$d(\mathbf{v}; \mathbf{V}_q) = \begin{cases} d_{con}(\mathbf{v}; \mathbf{V}_q), & \text{if } q \text{ is conjunctive queries}, \\ d_{dis}(\mathbf{v}; \mathbf{V}_q), & \text{if } q \text{ is disjunctive queries}. \end{cases}$$

251 **Training Objective.** Given a training set of queries, we optimize a negative sampling loss

$$L = -\log \sigma(\gamma - d(\mathbf{v}; \mathbf{V}_q)) - \frac{1}{k} \sum_{i=1}^{k} \log \sigma(d(\mathbf{v}'_i; \mathbf{V}_q) - \gamma),$$

252 where $\gamma > 0$ is a fixed margin, $v \in [\![q]\!]$ is a positive entity, $v'_i \notin [\![q]\!]$ is the i-th negative entity, k is the
253 number of negative entities, and $\sigma(\cdot)$ is the sigmoid function.

5 Experiments

255 In this section, we conduct experiments to demonstrate that: 1) ConE is a powerful model for the
256 multi-hop reasoning over knowledge graphs; 2) the aperture embeddings of ConE are effective in
257 modeling cardinality (i.e., the number of elements) of answer sets. We first introduce experimental
258 settings in Section 5.1 and then present the experimental results in Sections 5.2 and 5.3.

5.1 Experimental Settings

260 We adopt the commonly used experimental settings for query embeddings [12, 20, 19].

261 **Datasets and Queries.** We use three datasets: FB15k [2], FB15k-237 (FB237) [25], and NELL995
262 (NELL) [28]. QE models focus on answering queries involved with incomplete KGs. Thus, we aim
263 to find non-trivial answers to FOL queries that cannot be discovered by traversing KGs. For a fair
264 comparison, we use the same query structures as those in Ren & Leskovec [19]. The training and

Table 1: MRR results for answering queries without negation ($\exists$, $\wedge$, $\vee$) on FB15k, FB237, and NELL. The results of BETAE are taken from Ren & Leskovec [19].

Dataset	Model	1p	2p	3p	2i	3i	pi	ip	2u	up	AVG
FB15k	GQE	53.9	15.5	11.1	40.2	52.4	27.5	19.4	22.3	11.7	28.2
	Q2B	70.5	23.0	15.1	61.2	71.8	41.8	28.7	37.7	19.0	40.1
	BETAE	65.1	25.7	24.7	55.8	66.5	43.9	28.1	40.1	25.2	41.6
	ConE	**73.3**	**33.8**	**29.2**	**64.4**	**73.7**	**50.9**	**35.7**	**55.7**	**31.4**	**49.8**
FB237	GQE	35.2	7.4	5.5	23.6	35.7	16.7	10.9	8.4	5.8	16.6
	Q2B	41.3	9.9	7.2	31.1	45.4	21.9	13.3	11.9	8.1	21.1
	BETAE	39.0	10.9	10.0	28.8	42.5	22.4	12.6	12.4	9.7	20.9
	ConE	**41.8**	**12.8**	**11.0**	**32.6**	**47.3**	**25.5**	**14.0**	**14.5**	**10.8**	**23.4**
NELL	GQE	33.1	12.1	9.9	27.3	35.1	18.5	14.5	8.5	9.0	18.7
	Q2B	42.7	14.5	11.7	34.7	45.8	23.2	17.4	12.0	10.7	23.6
	BETAE	53.0	13.0	11.4	37.6	47.5	24.1	14.3	12.2	8.5	24.6
	ConE	**53.1**	**16.1**	**13.9**	**40.0**	**50.8**	**26.3**	**17.5**	**15.3**	**11.3**	**27.2**

validation queries consist of five conjunctive structures ($1p/2p/3p/2i/3i$) and five structures with negation ($2in/3in/inp/pni/pin$). We also evaluate models' generalization ability, i.e., answering queries with structures that models have never seen during training. The extra query structures include $ip/pi/2u/up$. Please refer to Appendix B.1 for more details about datasets and query structures.

Training Protocol. We use Adam [13] as the optimizer, and use grid search to find the best hyperparameters based on the performance on the validation datasets. For the search range and best hyperparameters, please refer to Appendix B.2.

Evaluation Protocol. We use the same evaluation protocol as that in Ren & Leskovec [19]. We first build three KGs: the training KG $\mathcal{G}_{\text{train}}$, the validation KG $\mathcal{G}_{\text{valid}}$, and the test KG $\mathcal{G}_{\text{test}}$ using training edges, training+validation edges, training+validation+test edges, respectively. Given a test (validation) query q, we aim to discover non-trivial answers $[\![q]\!]_{\text{test}} \backslash [\![q]\!]_{\text{valid}}$ ($[\![q]\!]_{\text{valid}} \backslash [\![q]\!]_{\text{train}}$). In other words, to answer an entity, we need to impute at least one edge to create an answer path to it. For each non-trivial answer v of a test query q, we rank it against non-answer entities $\mathcal{V} \backslash [\![q]\!]_{\text{test}}$. We denote the rank as r and calculate the Mean Reciprocal Rank (MRR), of which the definition is provided in Appendix B.3. Higher MRR indicates better performance.

Baselines. We compare ConE against three state-of-the-art models, including GQE [12], Query2Box (Q2B) [20], and BETAE [19]. GQE and Q2B are trained only on five conjunctive structures as they cannot model the queries with negation. Since the best embedding dimension d for ConE is 800, we retrain all the baselines with $d = 800$. The results of GQE and Q2B are better than those reported in Ren & Leskovec [19], while the results of BETAE become slightly worse. Therefore, we reported the results of GQE and Q2B with $d = 800$ and BETAE with $d = 400$. For the results of BETAE with $d = 800$, please refer to Appendix C.1.

5.2 Main Results

We compare ConE against baseline models on queries with and without negation. We run our model five times with different random seeds and report the average performance. For the error bars of the performance, please refer to Appendix C.5.

Queries without Negation. Table 1 shows the experimental results on queries without negation, i.e., existentially positive first-order (EPFO) queries, where **AVG** denotes average performance. Overall, ConE significantly outperforms compared models. ConE achieves on average 19.7%, 12.0%, and 10.6% relative improvement MRR over previous state-of-the-art BETAE on the three datasets, which demonstrates the superiority of geometry-based models. Compared with Q2B, which uses boxes to embed queries, ConE gains up to 24.2% relative improvements. The results demonstrate that cones are better geometric shapes than boxes for query embeddings. ConE also gains an impressive improvement on queries $ip/pi/2u/up$, which are not in the training graph. For example, ConE outperforms BETAE by 38.9% for $2u$ query on FB15k. The results show the superior generality ability of ConE. Since ConE is capable of modeling complement, we can also implement disjunctive queries using De Morgan's law. We include the results in Appendix C.2 due to the space limit.

Table 2: MRR results for answering queries with negation on FB15k, FB237, and NELL. The results of BETAE are taken from Ren & Leskovec [19].

Dataset	Model	2in	3in	inp	pin	pni	AVG
FB15k	BETAE	14.3	14.7	11.5	6.5	12.4	11.8
	ConE	**17.9**	**18.7**	**12.5**	**9.8**	**15.1**	**14.8**
FB237	BETAE	5.1	7.9	7.4	3.6	3.4	5.4
	ConE	**5.4**	**8.6**	**7.8**	**4.0**	**3.6**	**5.9**
NELL	BETAE	5.1	7.8	10.0	3.1	3.5	5.9
	ConE	**5.7**	**8.1**	**10.8**	**3.5**	**3.9**	**6.4**

Table 3: Spearman's rank correlation between learned aperture embeddings and the number of queries' answers on FB15k. The results of Q2B and BETAE are taken from Ren & Leskovec [19].

Model	1p	2p	3p	2i	3i	pi	ip	2in	3in	inp	pin	pni
Q2B	0.30	0.22	0.26	0.33	0.27	0.30	0.14	-	-	-	-	-
BETAE	0.37	0.48	0.47	0.57	0.40	0.52	0.42	0.62	0.55	0.46	0.47	0.61
ConE	**0.60**	**0.68**	**0.70**	**0.68**	**0.52**	**0.59**	**0.56**	**0.84**	**0.75**	**0.61**	**0.58**	**0.80**

Queries with Negation. Table 2 shows the results of ConE against BETAE on modeling FOL queries with negation. Since GQE and Q2B are not capable of handling the negation operator, we do not include their results in the experiments. Overall, ConE outperforms BETAE by a large margin. Specifically, ConE achieves on average 25.4%, 9.3%, and 8.5% relative improvement MRR over BETAE on FB15k, FB237, and NELL, respectively.

5.3 Modeling the Cardinality of Answer Sets

As introduced in Section 4.1, the aperture embeddings can designate the cardinality (i.e., the number of elements) of $[\![q]\!]$. In this experiment, we demonstrate that although we do not explicitly enforce ConE to learn cardinality during training, the learned aperture embeddings are effective in modeling the cardinality of answer sets. The property also accounts for the empirical improvements of ConE.

We compute the correlations between learned aperture embeddings and the cardinality of answer sets. Specifically, for the cone embedding $\mathbf{V}_q = (\boldsymbol{\theta}_{ax}, \boldsymbol{\theta}_{ap})$ of a given query q, we use the L_1 norm of $\boldsymbol{\theta}_{ap}$ to represent the learned cardinality of $[\![q]\!]$. Then, we compute the Spearman's rank correlation (SRC) between the learned cardinality and the real cardinality, which measures the statistical dependence between the ranking of two variables. Higher correlation indicates that the embeddings can better model the cardinality of answer sets. As we model queries with disjunction using the DNF technique, we do not include the results of disjunctive queries following Ren & Leskovec [19].

Table 3 shows the results of SRC for ConE, Query2Box (Q2B), and BETAE on FB15k. For the results on FB237 and NELL, please refer to Appendix C.3. As Query2Box cannot handle queries with negation, we do not include its results on these queries. On all query structures, ConE outperforms the previous state-of-the-art method BETAE. Note that BETAE is a probabilistic model, of which the authors claim that it can well handle the uncertainty of queries, i.e., the cardinality of answer set. Nonetheless, ConE still outperforms BETAE by a large margin, which demonstrates the expressiveness of cone embeddings. We also conduct experiments using Pearson's correlation, which measures the linear correlation between two variables. Please refer to Appendix C.3 for the results.

6 Conclusion

In this paper, we propose a novel query embedding model, namely Cone Embeddings (ConE), to answer multi-hop first-order logical (FOL) queries over knowledge graphs. We represent entity sets as Cartesian products of cones and design corresponding logical operations. To the best of our knowledge, ConE is the first geometric query embedding models that can model all the FOL operations. Experiments demonstrate that ConE significantly outperforms previous state-of-the-art models on benchmark datasets. One future direction is to adapt ConE to queries in the natural language, which will further improve ConE's applicability.

References

[1] Balazevic, I., Allen, C., and Hospedales, T. Multi-relational poincaré graph embeddings. In *Advances in Neural Information Processing Systems*, 2019.

[2] Bollacker, K., Evans, C., Paritosh, P., Sturge, T., and Taylor, J. Freebase: A collaboratively created graph database for structuring human knowledge. In *Proceedings of the 2008 ACM SIGMOD International Conference on Management of Data*, pp. 1247–1250, 2008.

[3] Bordes, A., Usunier, N., Garcia-Duran, A., Weston, J., and Yakhnenko, O. Translating embeddings for modeling multi-relational data. In *Advances in Neural Information Processing Systems 26*, pp. 2787–2795, 2013.

[4] Boyd, S. and Vandenberghe, L. *Convex Optimization*. Cambridge University Press, USA, 2004. ISBN 0521833787.

[5] Das, R., Neelakantan, A., Belanger, D., and McCallum, A. Chains of reasoning over entities, relations, and text using recurrent neural networks. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers*, pp. 132–141, 2017.

[6] Dasgupta, S., Boratko, M., Zhang, D., Vilnis, L., Li, X., and McCallum, A. Improving local identifiability in probabilistic box embeddings. In *Advances in Neural Information Processing Systems*, 2020.

[7] Davey, B. A. and Priestley, H. A. *Introduction to lattices and order*. Cambridge university press, 2002.

[8] Ganea, O., Becigneul, G., and Hofmann, T. Hyperbolic entailment cones for learning hierarchical embeddings. In *Proceedings of the 35th International Conference on Machine Learning*, volume 80, pp. 1646–1655, 2018.

[9] Garg, D., Ikbal, S., Srivastava, S. K., Vishwakarma, H., Karanam, H., and Subramaniam, L. V. Quantum embedding of knowledge for reasoning. In *Advances in Neural Information Processing Systems*, 2019.

[10] Guo, S., Wang, Q., Wang, L., Wang, B., and Guo, L. Knowledge graph embedding with iterative guidance from soft rules. In *Proceedings of the Thirty-Second AAAI Conference on Artificial Intelligence*, 2018.

[11] Guu, K., Miller, J., and Liang, P. Traversing knowledge graphs in vector space. In *Proceedings of the 2015 Conference on Empirical Methods in Natural Language Processing*, pp. 318–327. Association for Computational Linguistics, 2015.

[12] Hamilton, W. L., Bajaj, P., Zitnik, M., Jurafsky, D., and Leskovec, J. Embedding logical queries on knowledge graphs. In *Proceedings of the 32nd International Conference on Neural Information Processing Systems*, pp. 2030–2041, 2018.

[13] Kingma, D. P. and Ba, J. Adam: A method for stochastic optimization. In *Proceedings of the International Conference on Learning Representations (ICLR)*, 2015.

[14] Lai, A. and Hockenmaier, J. Learning to predict denotational probabilities for modeling entailment. In *Proceedings of the 15th Conference of the European Chapter of the Association for Computational Linguistics: Volume 1, Long Papers*, pp. 721–730, 2017.

[15] Li, F.-L., Qiu, M., Chen, H., Wang, X., Gao, X., Huang, J., Ren, J., Zhao, Z., Zhao, W., Wang, L., Jin, G., and Chu, W. Alime assist: An intelligent assistant for creating an innovative e-commerce experience. In *Proceedings of the 2017 ACM on Conference on Information and Knowledge Management*, pp. 2495–2498, 2017.

[16] Lin, X. V., Socher, R., and Xiong, C. Multi-hop knowledge graph reasoning with reward shaping. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 3243–3253, 2018.

[17] Lin, Y., Liu, Z., Sun, M., Liu, Y., and Zhu, X. Learning entity and relation embeddings for knowledge graph completion. In *Proceedings of the Twenty-Ninth AAAI Conference on Artificial Intelligence*, pp. 2181–2187, 2015.

[18] Nickel, M. and Kiela, D. Poincaré embeddings for learning hierarchical representations. In *Advances in Neural Information Processing Systems*, 2017.

[19] Ren, H. and Leskovec, J. Beta embeddings for multi-hop logical reasoning in knowledge graphs. In *Neural Information Processing Systems*, 2020.

[20] Ren, H., Hu, W., and Leskovec, J. Query2box: Reasoning over knowledge graphs in vector space using box embeddings. In *International Conference on Learning Representations*, 2020.

[21] Saxena, A., Tripathi, A., and Talukdar, P. Improving multi-hop question answering over knowledge graphs using knowledge base embeddings. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pp. 4498–4507, 2020.

[22] Sun, H., Bedrax-Weiss, T., and Cohen, W. PullNet: Open domain question answering with iterative retrieval on knowledge bases and text. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 2380–2390, 2019.

[23] Sun, H., Arnold, A. O., Bedrax-Weiss, T., Pereira, F., and Cohen, W. W. Faithful embeddings for knowledge base queries. In *Advances in Neural Information Processing Systems*, 2020.

[24] Sun, Z., Deng, Z.-H., Nie, J.-Y., and Tang, J. Rotate: Knowledge graph embedding by relational rotation in complex space. In *International Conference on Learning Representations*, 2019.

[25] Toutanova, K. and Chen, D. Observed versus latent features for knowledge base and text inference. In *3rd Workshop on Continuous Vector Space Models and Their Compositionality*, 2015.

[26] Trouillon, T., Welbl, J., Riedel, S., Gaussier, E., and Bouchard, G. Complex embeddings for simple link prediction. In *Proceedings of The 33rd International Conference on Machine Learning*, volume 48, pp. 2071–2080, 2016.

[27] Vendrov, I., Kiros, R., Fidler, S., and Urtasun, R. Order-embeddings of images and language. In *4th International Conference on Learning Representations*, 2016.

[28] Xiong, W., Hoang, T., and Wang, W. Y. DeepPath: A reinforcement learning method for knowledge graph reasoning. In *Proceedings of the 2017 Conference on Empirical Methods in Natural Language Processing*, pp. 564–573, 2017.

[29] Zaheer, M., Kottur, S., Ravanbakhsh, S., Poczos, B., Salakhutdinov, R. R., and Smola, A. J. Deep sets. In *Advances in Neural Information Processing Systems*, volume 30, pp. 3391–3401, 2017.

[30] Zhang, Z., Cai, J., Zhang, Y., and Wang, J. Learning hierarchy-aware knowledge graph embeddings for link prediction. In *Proceedings of the Thirty-Fourth AAAI Conference on Artificial Intelligence*, 2020.