# Beyond Translation: Cross-Cultural Meme Transcreation with Vision-Language Models

## Abstract

Memes are a pervasive form of online communication, yet their cultural specificity makes cross-cultural adaptation challenging. We study *cross-cultural meme transcreation*, a multimodal generation task that aims to preserve humor and communicative intent while adapting culturally grounded references. We introduce a hybrid transcreation framework, together with MEMEXGEN, a large-scale bidirectional Chinese–U.S. meme transcreation dataset containing 6,315 meme pairs. Using both human and automated evaluation, we analyze transcreation quality across cultural directions, baseline systems, and architectural variants. Our results show that current vision–language models can perform cross-cultural meme transcreation to a limited extent, but exhibit clear directional asymmetries: US→Chinese transcreation consistently achieves higher quality than Chinese→US. We further identify which aspects of humor and visual–textual design transfer across cultures and which remain challenging, and propose an evaluation framework for assessing cross-cultural multimodal generation. Our code and dataset are publicly available at https://anonymous.4open. science/r/MemeXGen-5144.

## 1 Introduction

Memes are a dominant form of online communication, yet they are difficult to adapt across cultural contexts. A meme that resonates with US audiences may fail among Chinese users—not due to linguistic errors, but because its humor, symbolism, or visual style does not translate culturally. While literal translation preserves surface meaning, it often fails to preserve what makes a meme effective: its intent, humor, and cultural resonance.

This challenge is often described as *transcreation* (Khanuja et al., 2024b): the process of adapting content across cultures by preserving communicative intent rather than literal form. For memes,

**Cultural Differences in Meme Preferences**

| Chinese Memes | US Memes |
|---|---|
| **Visual Characteristics:** Animals, Comic elements, Symbolic imagery | **Visual Characteristics:** Human figures, Famous cartoon characters, Celebrity reactions |
| **Textual Style:** Concise even abstract, Emotional vocabulary, Philosophical undertones | **Textual Style:** Text-heavy formats, Narrative structures, Conversational tone |

Figure 1: Examples of cultural differences in meme preferences across Chinese and US contexts. Cultural preferences shape humor and visual style, creating challenges for cross-cultural meme transcreation.

| Aspect | US | Chinese |
|---|---|---|
| Visual | Human, celebrity | Animal, symbolic |
| Text | Narrative, detailed | Concise, philosophical |
| Emotion | Situational | Universal |
| Humor | Sarcasm, relatable | Wordplay, cuteness |

Table 1: Cross-Cultural Meme Characteristics

transcreation requires coordinated adaptation of both text and images, grounded in culturally specific norms, references, and aesthetic preferences. As such, *meme transcreation poses a fundamental multimodal and cultural generation challenge that goes beyond standard translation or captioning.*

Prior work has primarily studied memes from a recognition and analysis perspective (Hazman et al., 2025; Cao et al., 2023; Zhao et al., 2025). In parallel, recent vision–language models demonstrate strong multimodal understanding capabilities. However, systematic frameworks, datasets, and evaluations for *cross-cultural meme generation* remain limited. In particular, it is unclear how well

current models can perform culturally grounded transcreation, how performance varies across cultural directions, and how such systems should be evaluated.

To address this gap, we empirically study cross-cultural meme transcreation between Chinese and US cultures through a hybrid framework that adapts memes while preserving communicative intent. We introduce a large-scale bidirectional dataset of original and transcreated memes and evaluate transcreation quality using both human judgments and automated evaluation. Our analysis highlights systematic directional effects and cultural factors that shape the success and limitations of current vision–language models in cross-cultural meme transcreation. Table 1 summarizes key cross-cultural distinctions considered in this work.

This paper addresses three research questions:

**RQ1:** How effectively can vision–language models perform cross-cultural meme transcreation while preserving intent, humor, and cultural nuance?

**RQ2:** Does transcreation direction introduce systematic asymmetries between US→Chinese and Chinese→US adaptations?

**RQ3:** How can we evaluate multimodal meme transcreation, and how well do automated metrics align with human judgments?

Our Contributions. **First, we propose a hybrid framework for meme transcreation** that balances intent preservation with cultural adaptation without task-specific fine-tuning, enabling principled analysis of culturally grounded meme adaptation. **Second, we introduce MemeXGen, the first bidirectional meme transcreation dataset**, containing 6,315 original memes and 6,315 corresponding transcreated memes across both Chinese→US and US→Chinese directions. **Third, we conduct a systematic comparison against three baselines**, showing a consistent directional asymmetry (Chinese→US > US→Chinese) and that specific aspects of internet humor transfer unevenly across cultures.

## 2 Related Work

**Cultural Gaps in AI.** Despite advances in large language models and vision–language models (VLMs), cultural gaps remain a persistent challenge (Mihalcea et al., 2025; Adilazuarda et al.,

2024). Prior work shows that NLP systems often fail to account for cross-cultural variation (Hershcovich et al., 2022), while text-to-image models tend to default to Western-centric representations (Kannen et al., 2024). These biases manifest as systematic performance disparities across languages and cultures (Field et al., 2021; Naous et al., 2023). Recent benchmarks such as GlobalRG (Bhatia et al., 2024) further highlight significant drops in VLM performance on local cultural concepts. Our work contributes to this line of research by studying explicit cultural adaptation in a generative setting, focusing on bidirectional cross-cultural transcreation.

**Meme Understanding and Analysis.** Most prior research on memes has focused on discriminative tasks, such as classification and detection. For example, PromptHate (Cao et al., 2023) addresses hateful meme detection (Kiela et al., 2021; Kumar and Nandakumar, 2022; Sharma et al., 2023), while MGMCF (Zheng et al., 2024) models fine-grained persuasive features (García-Díaz et al., 2024). Other studies document systematic cultural differences in online humor (Mutheu, 2023; Nissenbaum and Shifman, 2018; Tanaka et al., 2022), analyze the sentiment of memes (Sharma et al., 2020), and show that annotators' cultural backgrounds influence interpretation. In contrast, comparatively little work has explored *generative* meme tasks, particularly those requiring culturally grounded adaptation rather than classification.

**Cross-Cultural Transcreation.** Transcreation has recently emerged as a framework for adapting content across cultures beyond literal translation. Khanuja et al. (2024b) introduce image transcreation and show that models struggle to balance semantic preservation with cultural appropriateness, motivating dedicated evaluation metrics (Khanuja et al., 2024a). While meme datasets such as MemeCap (Hwang and Shwartz, 2023) or MET-Meme (Xu et al., 2022) provide large-scale meme captioning resources, they lack cross-cultural pairs required for transcreation. Our work extends transcreation to memes, which require tight visual–textual coupling and humor preservation, and introduces a bidirectional benchmark spanning US and Chinese cultures.

**Generative Vision–Language Models.** Recent VLMs demonstrate strong multimodal understanding and reasoning capabilities, including

LLaVA (Liu et al., 2023, 2024), GPT-4V (Lin et al., 2025), and Qwen-VL (Bai et al., 2023; Wang et al., 2024). Parallel advances in image generation models enable increasingly faithful prompt-based visual synthesis (Black Forest Labs, 2024; Verdú and Martín, 2024). While these models provide the foundation for multimodal generation, their effectiveness for culturally grounded creative adaptation remains underexplored—a gap our study aims to address.

**Evaluation of Multimodal Generation.** Standard metrics such as CLIPScore (Hessel et al., 2021) and TIFA (Hu et al., 2023) focus on text–image alignment but are not designed to capture cultural fit or humor preservation. Existing cross-cultural benchmarks, including CVQA (Romero et al., 2024), GlobalRG (Bhatia et al., 2024), and WorldCuisines (Winata et al., 2025), primarily address visual question answering rather than generative tasks (Bai et al., 2025; Bhalerao et al., 2025). In this work, we evaluate meme transcreation using both human judgments and automated LLM-based evaluation across multiple quality dimensions, enabling a systematic comparison of human and automated assessments in a cross-cultural setting.

## 3 Hybrid Transcreation Framework

We introduce a hybrid framework for cross-cultural meme transcreation that balances preservation of communicative intent with culturally appropriate adaptation. Rather than framing memes as a translation task, *our approach explicitly separates culture-invariant elements from those that must change to ensure cultural authenticity*. This section outlines the guiding principles of the framework and the three-stage pipeline that implements them.

Our hybrid strategy rests on three principles: **preserve universal elements** (core humor mechanisms, high-level emotional intent, common meme formats); **adapt culture-specific elements** (pop culture, idioms, visual symbols, stylistic conventions); and **maintain intent consistency** by preserving what the meme aims to express or satirize, even when textual and visual inputs change.

### 3.1 Meme Transcreation Pipeline

Figure 2 illustrates our modular three-stage meme transcreation pipeline: *cultural reasoning*, *visual generation*, and *final assembly*, enabling independent control and analysis across cultural directions.

Figure 2: Overview of our three-stage meme transcreation pipeline. (1) A VLM analyzes the *original/input* meme, identifies cultural references and intent, and generates a culturally adapted caption. (2) A diffusion model produces a meme-style visual template aligned with the target culture. (3) A text overlay module assembles the output *transcreated* meme.

**Stage 1: Cultural Analysis and Caption Generation.** We use LLaVA 1.6 (13B) (Liu et al., 2024) as the core vision-language model for cultural analysis and caption generation. The model takes the original meme image as input and is prompted to (1) analyze cultural references and humor mechanisms, (2) extract the underlying intent, (3) map source-culture concepts to target-culture equivalents, and (4) generate a culturally appropriate caption in the target language.

We employ LLaVA 1.6 because it offers strong vision–language alignment, high Chinese and English performance, and open-source reproducibility. Importantly, we do not fine-tune the model, focusing instead on prompt-based control to isolate the effects of cultural reasoning without introducing task-specific training bias. This stage outputs both a transcreated caption and high-level recommendations for adapting the visual content (i.e., mood, background, details in Appendix D)

**Stage 2: Visual Template Generation.** Using the visual recommendations from Stage 1, we generate culturally adapted meme templates with FLUX.1 Schnell (Black Forest Labs, 2024; Verdú and Martín, 2024), a diffusion-based generator chosen for strong prompt adherence and fast iteration. The goal is meme-appropriate visuals supporting the intended humor with clear room for text overlay, not photorealism. Generated images preserve universal meme structures (i.e., reaction shots, simple backgrounds) while adapting culture-specific elements (i.e., Western celebrity figures often become symbolic, or animal-based representations are more common in Chinese meme culture) with emotional tone conveyed through expression, posture, and target-culture visual metaphors.

**Stage 3: Final Assembly.** The transcreated captions are automatically matched with generated templates using Pillow,[1] which handles font selection, text placement, and target-culture layout conventions (denser for Chinese, more spaced for English). Finally, human annotators perform manual quality checks to verify readability and that captions do not obscure key visual elements, as described in the next section.

## 4 MemeXGen Dataset

To study cross-cultural meme transcreation in a controlled and realistic setting, we introduce **MemeXGen**, a multilingual and multicultural dataset of Chinese and US meme pairs. The dataset consists of 6,315 *original memes* collected from authentic social media platforms and 6,315 *transcreated memes* produced by our pipeline. For each original meme, we generate a corresponding transcreated version in the opposite cultural context, resulting in a total of *6,315 bidirectional meme pairs: 3,165 Chinese→US and 3,150 US→Chinese*. This paired structure enables direct comparison of transcreation quality across directions.

### 4.1 Data Sources

Our dataset – MemeXGen, is designed to support evaluation and analysis, with a focus on cultural authenticity, diversity of humor styles, and balanced coverage across Chinese and US cultures.

**Chinese Memes.** Original Chinese memes are sourced from the publicly available *Chinese Meme Description Dataset*[2], which aggregates content from two major Chinese social media platforms: *Xiaohongshu* and *Weibo*. Xiaohongshu contributes lifestyle- and emotion-focused memes, while Weibo provides fast-paced, commentary-driven content reflecting mainstream Chinese internet culture.

**US Memes.** Original US memes are drawn from the *MemeCap* dataset[3], which collects memes from popular Reddit communities such as r/memes and r/dankmemes. These memes reflect dominant US humor styles, including sarcasm, irony, pop culture references, and situational storytelling.

These sources offer complementary views of meme culture in two distinct cultural contexts, enabling systematic bidirectional transcreation.

### 4.2 Filtering and Dataset Composition

During data inspection, we observe that some *original* memes contain potentially sensitive content (e.g., political references) that could interfere with fair evaluation or raise ethical concerns. To address this, we manually filter the *original* memes to ensure responsible use and reliable evaluation. Specifically, we remove memes that are offensive, contain low-quality or corrupted images, rely heavily on mixed languages, or exhibit weak visual–text integration. Retention rates differ substantially across sources – 97.6% for Chinese memes vs. 55.0% for US memes – reflecting stricter content moderation on Chinese platforms compared to the more permissive nature of Reddit. We therefore collect a correspondingly larger pool of raw US memes upstream so that the post-filter dataset can be balanced across directions. After filtering, the dataset contains 6,315 original memes (3,165 Chinese, 3,150 US).

### 4.3 Annotation and Evaluation Split

To support emotion analysis and human evaluation, we annotate two disjoint subsets of the data.

**Emotion annotations subset.** We annotate ≈10% of the original memes data (628 memes, equally split between US and Chinese memes) with emotion labels, including emotion category (*Joy, Anger, Sadness, Fear, Disgust, Surprise*) and emotion intensity on a 1–5 Likert scale. Annotation guidelines follow recent multilingual emotion classification work, as described in BRIGHTER (Muhammad et al., 2025). Three expert annotators perform the annotations independently, achieving strong agreement: Fleiss' $\kappa = 0.869$ for emotion category and $\kappa = 0.536$ for intensity (Fleiss, 1971).

**Human evaluation subset.** We reserve a 10% subset (628 original memes) as the test set for transcreation experiments. This split includes 313 Chinese→US and 315 US→Chinese original-transcreated meme pairs and is used exclusively for human evaluation of meme transcreation. Evaluation details are provided in Section 5.

### 4.4 Dataset Characteristics

To better understand the cultural composition of the original memes, we analyze topic and emotion distributions using Qwen-VL-Max (Bai et al., 2023; Wang et al., 2024) for emotion classification, with prompts iteratively calibrated against a human-annotated emotion subset. An expert anno-

---

[1] https://python-pillow.org/
[2] https://github.com/THUDM/chinese-meme-description-dataset
[3] https://github.com/hwang1996/MemeCap

tator verified that more than 95% of the predicted labels were correct on a random 10% subset.

***Joy* dominates both cultures** (CN 69.3%, US 73.8%), while Chinese memes exhibit higher levels of *Anger* and *Sadness*, often reflecting social critique and melancholic expression. In contrast, US memes show higher frequencies of *Fear* and *Disgust*, commonly associated with anxiety- and cringe-driven humor.

Automatic topic analysis further shows that both cultures are dominated by *Internet Culture* and *Technology/Digital Life*. However, US memes more frequently frame education and family through narrative-driven humor, whereas Chinese memes rely more on symbolic expression and themes of social pressure.

These systematic differences help explain the directional asymmetries observed in our evaluation.

# 5 Evaluation Methodology

We evaluate our meme transcreation framework using both human-based and VLM-based evaluation.

## 5.1 Metric Definitions

Our evaluation captures not only text and image quality and their interaction, as commonly assessed in prior work (Hu et al., 2023), but also dimensions that are important for cross-cultural transcreation, such as cultural fit and intent preservation. All metrics are rated on a 5-point Likert scale (1 = strongly disagree, 5 = strongly agree).

We evaluate each transcreated meme along six metrics: *Caption Quality* – measures clarity, tone, and meme-appropriate language; *Image Quality* – visual clarity, composition, and recognizability; *Synergy* – how well image and text work together to convey humor or emotion; *Cultural Fit* – appropriateness and relatability for the target culture; *Intent Preservation* – retention of the original meme's message and emotional effect; and an *Overall Score*, computed as the average across all dimensions. The complete metric definitions provided to the evaluators are in Appendix F.

## 5.2 Human Evaluation

We evaluate meme transcreation on the human evaluation subset, with each meme independently assessed by three human evaluators. Because meme generation is inherently subjective and prior work highlights the importance of modeling annotator perspectives rather than simple aggregation (Deng et al., 2023), we report results separately for each evaluator. All evaluators are bilingual and bicultural, with deep familiarity with both Chinese and US meme cultures. Additional details on annotator backgrounds are provided in Appendix G.

**Inter-annotator Agreement.** Inter-annotator Pearson correlations show moderate to strong agreement ($r = 0.58$–$0.81$). This shows generally reliable evaluations despite differences in annotators' subjective and stylistic preferences.

## 5.3 Automatic Evaluation

To assess the feasibility of automated evaluation, we use six state-of-the-art VLMs on the full dataset: Qwen-VL-Max (Bai et al., 2023), LLaVA-v1.6-Vicuna-13B (Liu et al., 2024), InternVL3-8B and InternVL3-14B (Zhu et al., 2025), Qwen3-VL-8B (Wang et al., 2024), and Aya-vision-8b (Dash et al., 2025). These models are selected for their multilingual Chinese–English support, ability to process multiple images, and public availability, enabling reproducible automatic evaluation. For the baseline comparison subset (Section 6.4), we also include Qwen2.5-VL-72B (Wang et al., 2024) as a seventh, stronger judge model.

**VLM-Human Agreement.** We asses VLM evaluation effectiveness by computing the Pearson correlation between each human evaluator and VLM across each dimension (results in Section 6.3).

# 6 Evaluation Results

We report results that address our research questions, using human and VLM evaluators to assess cross-cultural performance, directional effects, and evaluation reliability.

## 6.1 RQ1: Cross-Cultural Performance

**Human Evaluation.** Table 2 shows results from three human evaluators and six LLM evaluators across both transcreation directions. Human evaluators differ in strictness and focus: Evaluator 1 prioritizes entertainment value (mean: 4.42), Evaluator 2 adopts a balanced perspective (mean: 4.09), and Evaluator 3 applies stricter quality standards (mean: 3.31). The resulting 1.11-point spread highlights the inherent subjectivity of cross-cultural meme transcreation evaluation. *Overall, the average human score of 4.07/5.0 indicates that our pipeline model generates effective and generally well-received transcreations.*

**Metric-Level Analysis.** Across metric, *Caption Quality* receives the highest ratings (mean: 4.20),

| Evaluator | Chinese→US | | | | | | US→Chinese | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Cap. | Img. | Syn. | Cult. | Intent | Overall | Cap. | Img. | Syn. | Cult. | Intent | Overall |
| Evaluator 1 (H) | 4.78 | 4.51 | 4.66 | 4.57 | 4.24 | 4.55 | 4.82 | 4.22 | 4.31 | 4.18 | 3.89 | 4.28 |
| Evaluator 2 (H) | 4.35 | 4.11 | 4.45 | 4.14 | 4.00 | 4.21 | 4.41 | 3.84 | 4.12 | 3.76 | 3.67 | 3.96 |
| Evaluator 3 (H) | 3.46 | 3.52 | 3.59 | 3.39 | 3.29 | 3.45 | 3.52 | 3.19 | 3.24 | 2.98 | 2.93 | 3.17 |
| Qwen-VL-Max | **4.13** | 3.86 | **4.20** | **3.74** | 3.72 | **3.95** | **4.21** | 3.58 | **3.89** | **3.41** | 3.44 | **3.71** |
| LLaVA-v1.6 | 4.00 | **4.00** | 3.81 | 3.00 | **4.00** | 3.79 | 4.05 | 3.72 | 3.52 | 2.67 | **3.71** | 3.53 |
| InternVL3-8B | 3.78 | 3.84 | 3.48 | 3.46 | 3.97 | 3.69 | 3.84 | 3.55 | 3.16 | 3.12 | 3.68 | 3.47 |
| InternVL3-14B | 3.21 | **4.39** | 3.16 | 3.36 | 3.34 | 3.53 | 3.28 | **4.11** | 2.84 | 3.02 | 3.01 | 3.25 |
| Qwen3-VL-8B | 2.83 | 3.70 | 2.74 | 3.59 | 2.56 | 3.15 | 2.91 | 3.42 | 2.41 | 3.21 | 2.18 | 2.83 |
| Aya-vision-8b | 3.18 | 4.17 | 2.83 | 2.90 | 2.72 | 3.10 | 3.25 | 3.89 | 2.51 | 2.56 | 2.39 | 2.92 |

*Note:* Best score per column in **bold**, second-best underlined; 1–5 Likert (higher = better). (H) = Human evaluator. Cap.=Caption Quality, Img.=Image Quality, Syn.=Synergy, Cult.=Cultural Fit, Intent=Intent Preservation.

Table 2: Metric-level, per-evaluator scores for our proposed hybrid model – LLaVA+FLUX.

suggesting effective cross-cultural adaptation of meme text. *Image Quality* is also strong (mean: 4.05), supporting the reliability of FLUX.1 for meme-style visual generation. *Synergy* is consistently high (mean: 4.23), indicating that captions and visuals work well together in most outputs. *Cultural Fit* shows the widest variation across evaluators (range: 3.39–4.57), reflecting the subjective and culturally grounded nature of authenticity judgments. *Intent Preservation* is rated favorably overall (mean: 3.84), though scores may be partially influenced by the dominance of Joy-related memes (69–74% of the data).

**VLM Evaluation.** Among automated evaluators, *Qwen-VL-Max performs best*, achieving the highest overall scores (3.95 for Chinese→US and 3.71 for US→Chinese) and showing *strong alignment with human judgments* (mean Pearson $r = 0.926$, all $p < 0.001$). Other LLM evaluators have much weaker correlations with humans ($r \leq 0.33$), suggesting that most open-source models struggle to reliably evaluate creative, culturally grounded outputs. For our LLaVA+FLUX model, VLM-judge scores are on average about 0.5 points lower than human scores, indicating a tendency toward more conservative evaluations; we further analyze this behavior across all baselines in Section 6.4.

## 6.2 RQ2: Directional Asymmetries

We observe a clear and consistent directional asymmetry: *Chinese→US transcreations outperform US→Chinese on Overall score* for every evaluator in Table 2. Across the nine evaluators (3 human, 6 VLM), the mean per-evaluator gap is $\delta = +0.26$ (range +0.18 to +0.32). This gap likely reflects several factors. First, US memes often rely on globally recognizable characters and themes that are easier to localize, whereas Chinese memes

| Human | VLM | Cap. | Img. | Syn. | Cult. | Intent | Overall |
|---|---|---|---|---|---|---|---|
| Eval. 1 | Qwen-VL-Max | 0.961 | 0.986 | 0.987 | 0.901 | 0.993 | 0.921 |
| | LLaVA-v1.6 | -0.039 | -0.039 | 0.082 | -0.178 | -0.039 | -0.026 |
| | InternVL3-8B | -0.128 | -0.026 | -0.053 | -0.106 | 0.041 | -0.086 |
| | InternVL3-14B | 0.241 | 0.363 | 0.288 | 0.216 | 0.275 | 0.270 |
| | Qwen3-VL-8B | 0.219 | 0.394 | 0.316 | 0.215 | 0.289 | 0.281 |
| | Aya-vision-8b | -0.117 | -0.032 | -0.087 | -0.077 | -0.065 | -0.082 |
| Eval. 2 | Qwen-VL-Max | 0.989 | 0.988 | 0.994 | 0.980 | 0.995 | 0.964 |
| | LLaVA-v1.6 | -0.016 | -0.016 | 0.038 | -0.112 | -0.016 | -0.027 |
| | InternVL3-8B | -0.099 | 0.014 | -0.033 | -0.061 | 0.041 | -0.066 |
| | InternVL3-14B | 0.294 | 0.350 | 0.351 | 0.323 | 0.365 | 0.329 |
| | Qwen3-VL-8B | 0.265 | 0.340 | 0.331 | 0.294 | 0.327 | 0.309 |
| | Aya-vision-8b | -0.088 | 0.022 | -0.048 | -0.034 | -0.031 | -0.058 |
| Eval. 3 | Qwen-VL-Max | 0.950 | 0.990 | 0.985 | 0.938 | 0.990 | 0.894 |
| | LLaVA-v1.6 | -0.050 | -0.050 | 0.039 | -0.161 | -0.050 | 0.029 |
| | InternVL3-8B | -0.065 | 0.083 | 0.014 | 0.008 | 0.107 | -0.013 |
| | InternVL3-14B | 0.296 | 0.348 | 0.373 | 0.320 | 0.371 | 0.340 |
| | Qwen3-VL-8B | 0.193 | 0.368 | 0.310 | 0.235 | 0.285 | 0.263 |
| | Aya-vision-8b | -0.024 | 0.101 | 0.016 | 0.050 | 0.025 | -0.057 |

Note: Cell colors indicate correlation strength.

Table 3: Pearson correlation coefficients ($r$) between Human and VLM evaluators across all metrics.

frequently depend on context-specific wordplay and implicit cultural knowledge. Second, current VLMs are likely more exposed to US-centric data during training.

## 6.3 RQ3: Evaluation Framework Analysis

Strong VLM scores are only useful if they also reflect human judgments. Table 3 reports per-metric correlations between human and VLM evaluators. *Qwen-VL-Max shows consistently strong alignment with all three human evaluators* (Evaluator 1: $r = 0.921$, Evaluator 2: $r = 0.964$, Evaluator 3: $r = 0.894$), with especially high agreement on *Intent Preservation* ($r = 0.993$). In contrast, the other VLMs show significantly weaker correlations across metrics. The results suggest that evaluating cross-cultural multimodal data requires deeper multilingual and multicultural grounding than most current open-source VLMs can provide.

## 6.4 Model Ablations and Baseline Comparison

We compare our model against three state-of-the-art models on a 100-meme bidirectional random

| Model | Chinese→US | | | | | | US→Chinese | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|---|---|
| | Cap. | Img. | Syn. | Cult. | Intent | Overall | Cap. | Img. | Syn. | Cult. | Intent | Overall |
| *Human evaluators (mean of 3)* | | | | | | | | | | | | |
| Gemini 3.5 Flash | 4.38 | 4.48 | 4.44 | 3.89 | 4.10 | **4.26** | 4.36 | 4.40 | 4.43 | 3.70 | 4.04 | **4.19** |
| Gemma-4 + FLUX (ours, ablation) | 4.23 | 4.24 | 4.37 | **4.12** | 3.97 | 4.19 | 4.04 | 4.20 | 4.08 | **3.96** | 3.85 | 4.03 |
| LLaVA + FLUX (ours) | 4.20 | 4.05 | 4.23 | 4.03 | 3.84 | 4.07 | 4.16 | 3.75 | 3.84 | 3.64 | 3.45 | 3.77 |
| Janus-Pro-7B | 4.03 | 4.18 | 3.91 | 3.40 | 3.59 | 3.82 | 3.71 | 4.08 | 3.50 | 3.24 | 3.32 | 3.57 |
| *VLM judges (mean across 7 judges)* | | | | | | | | | | | | |
| Gemini 3.5 Flash | 4.20 | 4.57 | 4.32 | 4.10 | 4.24 | **4.30** | 4.18 | 4.45 | 4.30 | 4.13 | 4.32 | **4.29** |
| Gemma-4 + FLUX (ours, ablation) | 3.86 | 4.24 | 3.97 | 3.78 | 3.82 | 3.96 | 3.65 | 4.16 | 3.61 | 3.67 | 3.65 | 3.74 |
| LLaVA + FLUX (ours) | 3.57 | 4.07 | 3.48 | 3.45 | 3.42 | 3.61 | 3.62 | 3.78 | 3.16 | 3.11 | 3.17 | 3.37 |
| Janus-Pro-7B | 3.80 | 4.15 | 3.82 | 3.61 | 3.76 | 3.84 | 3.50 | 4.04 | 3.40 | 3.51 | 3.45 | 3.58 |

Table 4: Metric-level, averaged evaluator scores for the baselines and our proposed model and ablation. All the models show moderate to high human–LLM alignment ($r = +0.537$ to $r = +0.863$). Alignment breakdown per model in Appendix C.

subset using the same evaluation protocol. The baselines include *Gemini 3.5 Flash* (frontier closed-source model), *Janus-Pro-7B* (unified open-source multimodal model), and *Gemma-4 + FLUX* – an ablation that replaces LLaVA with Gemma-4 within our proposed pipeline.

The results are shown in Table 4. *Gemini 3.5 Flash* achieves the highest Overall scores under both human and VLM evaluation (human: 4.26/4.19; VLM: 4.30/4.29). However, the open-source models remain competitive on *Cultural Fit* under human evaluation. *In CH→US, both Gemma-4+FLUX (4.12) and LLaVA+FLUX (4.03) outperform Gemini (3.89). Similarly, in US→CH, Gemma-4+FLUX achieves the strongest Cultural Fit score (3.96 vs. Gemini's 3.70).*

Prompt-sensitivity results further show that the relative ranking among open-source models remains stable across prompt templates (maximum $|\Delta_{\text{Overall}}| = 0.22$ compared to inter-system gaps of at least $0.4$). Results breakdown per model is shown in Appendix B.

### 6.5 Image Diversity

Inspecting the generated outputs, we find that quality scores capture only part of the picture. While they evaluate the quality of individual source–target pairs, they do not measure whether a system produces visually diverse outputs across the dataset or how substantially the generated meme differs from the original. We therefore introduce a two-axis image diversity evaluation computed directly on the generated images.

*Across-LPIPS* (Zhang et al., 2018) measures the average perceptual distance between all pairs of generated memes within a system ($\binom{100}{2} = 4,950$

| Model | Chinese→US | | US→Chinese | |
|---|---|---|---|---|
| | Across↑ | Pair↑ | Across↑ | Pair↑ |
| Gemini 3.5 Flash | **0.718** | 0.555 | **0.708** | 0.542 |
| LLaVA + FLUX (ours) | 0.706 | **0.757** | 0.680 | 0.739 |
| Gemma-4 + FLUX (ours, ablation) | 0.630 | 0.751 | 0.628 | 0.741 |
| Janus-Pro-7B | 0.607 | 0.744 | 0.627 | **0.752** |

Table 5: Image diversity across systems and directions. Gemini has highest corpus-level diversity, but lowest per-pair diversity. Our proposed models achieve both.

comparisons), capturing corpus-level visual diversity. A higher score indicates that the system produces a wider variety of outputs rather than repeatedly generating similar visual patterns.

*Pair-LPIPS* measures the perceptual distance between each generated meme and its original source meme, capturing how much the transcreation visually transforms the original content. Higher scores indicate deeper visual changes and more substantial transcreation.

Table 5 reports the diversity results. Gemini 3.5 Flash achieves the highest corpus-level diversity (Across-LPIPS) but the lowest transcreation depth (Pair-LPIPS) in both directions, suggesting that its outputs vary across the dataset while remaining visually closer to the source memes. In contrast, *our LLaVA+FLUX pipeline achieves the strongest balance between the two axes*: top-two Across-LPIPS scores in both directions (0.706/0.680) and the highest CH→US Pair-LPIPS score (0.757). Overall, all three open-source systems significantly outperform Gemini on Pair-LPIPS in both directions.

### 6.6 Qualitative Analysis

To complement quantitative metrics, we present representative transcreation examples from both directions and our data analysis observations. Figure 3a shows a successful US→Chinese tran-

(a) **Best transcreation example (Score: 5.0/5.0).**
**Transcreated (Chinese, top right — Bugs Bunny):** "Family: Look who's up so early; My mental state after pulling an all-nighter to finish my assignment due."
**Original (bottom left — panda meme):** "What's wrong with work hours? Doesn't your company expect you to work during work hours?"

(b) **Worst transcreation example (Score: 1.4/5.0).**
**Transcreated (Chinese, top right — Looney Tunes):** "Celebrating the New Year, everyone must be happy! No one left behind, I'm giving you a family photo!"
**Original (bottom left — Chinese text):** "Attempts at equality satisfy no one."

Figure 3: **Qualitative examples of cross-cultural meme transcreation.** Left: successful US→Chinese adaptation preserving intent, humor, and cultural conventions. Right: failed Chinese→US adaptation illustrating loss of intent and cultural mismatch.

screation, while Figure 3b illustrates a failed Chinese→US transcreation.

**Success Patterns (30% of outputs score ≥4.5/5.0).** High-quality transcreations consistently show: (1) *Recognizable cross-cultural archetypes*, using characters or templates that transfer naturally across cultures; (2) *Emotion-preserving adaptation*, where the original emotional context is maintained while incorporating culturally specific elements; (3) *Natural meme language*, using informal conventions typical of the target culture; and (4) *Strong image–text synergy*, where captions and visuals support the same humor mechanism.

**Failure Patterns (1.6% of outputs score ≤2.0/5.0).** Failed transcreations commonly show: (1) *Caption failures*, such as overly formal language that weakens the meme tone; (2) *Visual mismatches*, including culturally inappropriate images; (3) *Loss of humor structure*, where the adapted format no longer supports the original joke; and (4) *Image–text disconnects*, producing conflicting messages.

**Directional Patterns.** US→Chinese transcreations more often achieve cultural integration, likely due to globally recognizable US meme templates. In contrast, Chinese→US transcreations struggle more with culture-specific wordplay and philosophical references, often resulting in more superficial adaptations. More examples are in Appendix J.

## 7 Conclusion

We introduced a framework for cross-cultural meme transcreation that separates intent preservation from cultural adaptation, *framing meme generation as a culturally grounded multimodal reasoning problem rather than simple translation*. Using a combination of vision-language models and diffusion-based image generation, we constructed and evaluated a dataset of 6,315 Chinese–U.S. meme pairs.

Our experiments reveal consistent directional asymmetries, showing that current models handle some cultural adaptations more effectively than others. Baseline comparisons against frontier and open-source systems further show that open-source pipelines remain competitive on cultural fit, while our proposed model achieves the strongest balance between overall quality, cultural adaptation, and image-side diversity. Ablations and prompt-sensitivity experiments further validate the contribution of the cultural reasoning stage.

Finally, we release the first parallel Chinese–U.S. meme transcreation dataset with emotion and cultural-intent annotations. We hope this work provides a foundation for research on computational humor and cross-cultural multimodal generation. https://anonymous.4open.science/r/MemeXGen-5144.

## Limitations

**Scope of Cultural Coverage.** This study focuses on meme transcreation between Chinese and U.S. cultures, which differ substantially in language, humor conventions, and visual symbolism. While this contrast enables clearer analysis of cultural asymmetries, the findings may not directly generalize to other cultural pairs. Future work should extend the framework to additional language and cultural settings to evaluate the robustness of the observed patterns.

**Generality of the Generation Framework.** Our transcreation pipeline combines existing vision–language and diffusion models in a modular design intended to support interpretability and controlled analysis. We compare against three baseline architectures spanning frontier closed-source and open-source designs, but do not exhaustively cover all possible generation strategies—stronger Stage-1 analyzers (e.g., Qwen2.5-VL) and unified AR–diffusion architectures remain unexplored. The pipeline also assumes single-panel meme inputs and does not handle multi-panel or comic-style formats that are common on Reddit; per-structure performance analysis is left to future work. The prompt sensitivity analysis is limited to open-source systems; Gemini 3.5 Flash was evaluated under the structured prompt only due to API access constraints.

**Interpreting Directional Asymmetries.** We observe consistent performance differences between US→Chinese and Chinese→US transcreation across all four systems. While we discuss plausible contributing factors such as training data exposure, humor structure, and evaluator expectations, these explanations are correlational rather than causal.

**Image-Side Diversity Measurement.** Our diversity evaluation uses LPIPS to measure image-level transcreation depth and corpus-level variety; we do not report text-side diversity. All four systems generate short captions ($\leq 8$ tokens, following meme convention), a regime in which $n$-gram diversity metrics such as distinct-$n$ saturate near $1.0$ by construction and lose discriminative power across systems. In particular, Pair-LPIPS quantifies how much a transcreation departs from its source but does not by itself certify that the departure is culturally appropriate; we therefore pair LPIPS-based diversity reporting with human Cultural Fit judgments rather than treating the two as interchangeable. Validating LPIPS-style depth metrics against human cultural-appropriateness judgments at scale, and developing length-robust text–image diversity metrics for short-caption multimodal generation, are worthwhile directions for future work.

**Dataset Composition and Emotion Coverage.** Joy dominates the meme distributions in both cultures, reflecting real-world social media trends but limiting stress-testing on negative or socially critical humor. As a result, intent preservation scores may be optimistic for emotionally complex cases. Expanding emotion-balanced datasets is a key area for future research.

**Evaluation Scope and Cultural Representation.** Human evaluation remains inherently subjective, and the observed variation across evaluators highlights the value of modeling diverse perspectives. Our annotators are bilingual and bicultural with Chinese–U.S. experience; future work can broaden representation by including evaluators with more localized backgrounds and exploring regional variation within each culture.

## Ethical Considerations

**Deployment Scope.** Our pipeline prioritizes analytical clarity and controlled study of cultural adaptation rather than deployment efficiency. As with any automated cultural generation system, misuse, misinterpretation, or oversimplification of cultural signals remains a risk. We position meme transcreation as a *decision-support tool* intended to assist human creators and analysts, not as a fully autonomous content generator, and strongly recommend human oversight in real-world or sensitive deployments.

**Content Safety.** We apply stringent manual filtering to exclude offensive or sensitive content, including hate speech, discriminatory media, explicit material, and political content. High *Not Offensive* ratings (92.8% from human evaluators and 96.6% from LLM-based assessment) indicate the effectiveness of these safeguards. However, cultural sensitivity is inherently subjective: content acceptable in one cultural context may still be perceived as offensive in another. Our system therefore cannot guarantee zero harmful outputs and should be used with caution, particularly in public-facing applications.

**Cultural Respect and Representation.** Automated cultural adaptation risks reinforcing stereo-

types or reducing complex cultural practices to surface-level substitutions. While our hybrid framework explicitly separates intent preservation from cultural adaptation, evaluator feedback reveals occasional cases of shallow cultural mapping (e.g., direct visual substitution without deeper contextual grounding). These limitations highlight the importance of human-in-the-loop workflows, where automated transcreation outputs are treated as drafts rather than finalized content.

**Data Privacy and Attribution.** All source memes are collected from publicly accessible platforms (Xiaohongshu and Weibo for Chinese memes; Reddit for U.S. memes) and do not contain personal identifying information. We respect the implicit consent associated with public content sharing, though proper attribution remains challenging for viral meme formats with unclear authorship. The dataset is intended strictly for research purposes, and we encourage responsible use consistent with platform norms and community standards.

**Misinformation Potential.** Meme transcreation tools could be misused to spread culturally-adapted misinformation or propaganda. We emphasize responsible deployment with content verification protocols and transparency about automated generation.

# References

Muhammad Farid Adilazuarda, Sagnik Mukherjee, Pradhyumna Lavania, Siddhant Singh, Alham Fikri Aji, Jacki O'Neill, Ashutosh Modi, and Monojit Choudhury. 2024. Towards measuring and modeling "culture" in llms: A survey. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing, EMNLP 2024, Miami, FL, USA, November 12-16, 2024*, pages 15763–15784. Association for Computational Linguistics.

Jinze Bai, Shuai Bai, Shusheng Yang, Shijie Wang, Sinan Tan, Peng Wang, Junyang Lin, Chang Zhou, and Jingren Zhou. 2023. Qwen-vl: A versatile vision-language model for understanding, localization, text reading, and beyond. *arXiv preprint arXiv:2308.12966*.

Longju Bai, Angana Borah, Oana Ignat, and Rada Mihalcea. 2025. The power of many: Multi-agent multimodal models for cultural image captioning. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pages 2970–2993, Albuquerque, New Mexico. Association for Computational Linguistics.

Parth Bhalerao, Mounika Yalamarty, Brian Trinh, and Oana Ignat. 2025. Multi-agent multimodal models for multicultural text to image generation. *ArXiv*, abs/2502.15972.

Mehar Bhatia, Sahithya Ravi, Aditya Chinchure, EunJeong Hwang, and Vered Shwartz. 2024. From local concepts to universals: Evaluating the multicultural understanding of vision-language models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pages 6763–6782, Miami, Florida, USA. Association for Computational Linguistics.

Black Forest Labs. 2024. Flux: Advanced text-to-image generation model. https://github.com/black-forest-labs/flux. GitHub Repository.

Rui Cao, Roy Ka-Wei Lee, Tuan-Anh Hoang, Junmo Pang, Kenji Kawaguchi, and Roger Zimmermann. 2023. Promptthate: Prompting for hateful meme classification. *Preprint*, arXiv:2302.04156.

Saurabh Dash, Shivalika Singh, Adrien Morisot, Beyza Ermis, Acyr Locatelli, Sungjin Hong, Arash Ahmadian, Yannis Flet-Berliac, Nathan Grinsztajn, Florian Strub, and 1 others. 2025. Aya vision: Advancing the frontier of multilingual multimodality. *Preprint*, arXiv:2505.08751.

Naihao Deng, Xinliang Zhang, Siyang Liu, Winston Wu, Lu Wang, and Rada Mihalcea. 2023. You are what you annotate: Towards better models through annotator representations. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pages 12475–12498, Singapore. Association for Computational Linguistics.

Anjalie Field, Su Lin Blodgett, Zeerak Waseem, and Yulia Tsvetkov. 2021. A Survey of Race, Racism, and Anti-Racism in NLP. In *Proceedings of the 59th Annual Meeting of the ACL*, pages 1905–1925.

Joseph L. Fleiss. 1971. Measuring nominal scale agreement among many raters. *Psychological Bulletin*, 76(5):378–382.

José Antonio García-Díaz and 1 others. 2024. Umuteam at semeval-2024 task 4: Multilingual detection of persuasion techniques in memes. *Proceedings of SemEval-2024*.

Muzhaffar Hazman, Susan McKeever, and Josephine Griffith. 2025. What makes a meme a meme? identifying memes for memetics-aware dataset creation.

Daniel Hershcovich and 1 others. 2022. Challenges and strategies in cross-cultural NLP. In *Proceedings of the 60th Annual Meeting of the ACL*, pages 6997–7013.

Jack Hessel and 1 others. 2021. CLIPScore: A reference-free evaluation metric for image captioning. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7514–7528.

Yushi Hu and 1 others. 2023. Tifa: Accurate and interpretable text-to-image faithfulness evaluation with question answering. *Preprint*, arXiv:2303.11897.

EunJeong Hwang and Vered Shwartz. 2023. Memecap: A dataset for captioning and interpreting memes. *Preprint*, arXiv:2305.13703.

Nithish Kannen, Arjun Palani, Vikram V. Ramaswamy, Olga Russakovsky, and Li Fei-Fei. 2024. Beyond aesthetics: Cultural competence in text-to-image models. *Preprint*, arXiv:2407.06863.

Simran Khanuja, Vivek Iyer, Claire He, and Graham Neubig. 2024a. Towards automatic evaluation for image transcreation. *Preprint*, arXiv:2412.13717.

Simran Khanuja, Sathyanarayanan Ramamoorthy, Yueqi Song, and Graham Neubig. 2024b. An image speaks a thousand words, but can everyone listen? on image transcreation for cultural relevance. *Preprint*, arXiv:2404.01247.

Douwe Kiela, Hamed Firooz, Aravind Mohan, Vedanuj Goswami, Amanpreet Singh, Casey A. Fitzpatrick, Peter Bull, Greg Lipstein, Tony Nelli, Ron Zhu, Niklas Muennighoff, Riza Velioglu, Jewgeni Rose, Phillip Lippe, Nithin Holla, Shantanu Chandra, Santhosh Rajamanickam, Georgios Antoniou, Ekaterina Shutova, and 6 others. 2021. The hateful memes challenge: Competition report. In *Proceedings of the NeurIPS 2020 Competition and Demonstration Track*, volume 133 of *Proceedings of Machine Learning Research*, pages 344–360. PMLR.

Gokul Karthik Kumar and Karthik Nandakumar. 2022. Hate-CLIPper: Multimodal hateful meme classification based on cross-modal interaction of CLIP features. In *Proceedings of the Second Workshop on NLP for Positive Impact (NLP4PI)*, pages 171–183, Abu Dhabi, United Arab Emirates (Hybrid). Association for Computational Linguistics.

Hongzhan Lin, Ziyang Luo, Bo Wang, Ruichao Yang, and Jing Ma. 2025. Goat-bench: Safety insights to large multimodal models through meme-based social abuse. *ACM Trans. Intell. Syst. Technol.*

Haotian Liu, Chunyuan Li, Yuheng Li, Bo Li, Yuanhan Zhang, Sheng Shen, and Yong Jae Lee. 2024. Llavanext: Improved reasoning, ocr, and world knowledge.

Haotian Liu, Chunyuan Li, Qingyang Wu, and Yong Jae Lee. 2023. Visual instruction tuning. *Preprint*, arXiv:2304.08485.

Rada Mihalcea, Oana Ignat, Longju Bai, Angana Borah, Luis Chiruzzo, Zhijing Jin, Claude Kwizera, Joan Nwatu, Soujanya Poria, and Thamar Solorio. 2025. Why ai is weird and shouldn't be this way: towards ai for everyone, with everyone, by everyone. In *Proceedings of the Thirty-Ninth AAAI Conference on Artificial Intelligence and Thirty-Seventh Conference on Innovative Applications of Artificial Intelligence and Fifteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI'25/IAAI'25/EAAI'25. AAAI Press.

Shamsuddeen Hassan Muhammad, Nedjma Ousidhoum, Idris Abdulmumin, Jan Philip Wahle, Terry Ruas, Meriem Beloucif, Christine de Kock, Nirmal Surange, Daniela Teodorescu, Ibrahim Said Ahmad, David Ifeoluwa Adelani, Alham Fikri Aji, Felermino D. M. A. Ali, Ilseyar Alimova, Vladimir Araujo, Nikolay Babakov, Naomi Baes, Ana-Maria Bucur, Andiswa Bukula, and 29 others. 2025. BRIGHTER: BRIdging the gap in human-annotated textual emotion recognition datasets for 28 languages. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pages 8895–8916, Vienna, Austria. Association for Computational Linguistics.

Sarah Mutheu. 2023. Cross-cultural differences in online communication patterns. *Journal of Communication*, 4(1):31–42.

Tarek Naous, Michael J Ryan, Alan Ritter, and Wei Xu. 2023. Having beer after prayer? measuring cultural bias in large language models. *Preprint*, arXiv:2305.14456.

Asaf Nissenbaum and Limor Shifman. 2018. Internet memes as contested cultural capital: The case of 4chan's/b/board. *New Media & Society*, 19(4):483–501.

David Romero and 1 others. 2024. Cvqa: Culturally-diverse multilingual visual question answering benchmark. *Preprint*, arXiv:2406.05967.

Chhavi Sharma, Deepesh Bhageria, William Scott, Srinivas PYKL, Amitava Das, Tanmoy Chakraborty, Viswanath Pulabaigari, and Björn Gambäck. 2020. SemEval-2020 task 8: Memotion analysis- the visuo-lingual metaphor! In *Proceedings of the Fourteenth Workshop on Semantic Evaluation*, pages 759–773, Barcelona (online). International Committee for Computational Linguistics.

Shivam Sharma, Atharva Kulkarni, Tharun Suresh, Himanshi Mathur, Preslav Nakov, Md. Shad Akhtar, and Tanmoy Chakraborty. 2023. Characterizing the entities in harmful memes: Who is the hero, the villain, the victim? In *Proceedings of the 17th Conference of the European Chapter of the Association for Computational Linguistics*, pages 2149–2163, Dubrovnik, Croatia. Association for Computational Linguistics.

Kohtaro Tanaka, Hiroaki Yamane, Yusuke Mori, Yusuke Mukuta, and Tatsuya Harada. 2022. Learning to evaluate humor in memes based on the incongruity theory. In *Proceedings of the Second Workshop on When Creative AI Meets Conversational AI*, pages 81–93, Gyeongju, Republic of Korea. Association for Computational Linguistics.

Daniel Verdú and Javier Martín. 2024. Flux.1 lite: Distilling flux1.dev for efficient text-to-image generation. Hugging Face Model Hub.

Peng Wang, Shuai Bai, Sinan Tan, Shijie Wang, Zhihao Fan, Jinze Bai, Keqin Chen, Xuejing Liu, Jialin

Wang, Wenbin Ge, and 1 others. 2024. Qwen2-vl: Enhancing vision-language model's perception of the world at any resolution. *Preprint*, arXiv:2409.12191.

Genta Indra Winata and 1 others. 2025. Worldcuisines: A massive-scale benchmark for multilingual and multicultural visual question answering on global cuisines. In *Proceedings of the 2025 NAACL*, pages 3242–3264.

Bo Xu, Tingting Li, Junzhe Zheng, Mehdi Naseriparsa, Zhehuan Zhao, Hongfei Lin, and Feng Xia. 2022. Met-meme: A multimodal meme dataset rich in metaphors. In *Proceedings of the 45th International ACM SIGIR Conference on Research and Development in Information Retrieval*, SIGIR '22, page 2887–2899, New York, NY, USA. Association for Computing Machinery.

Richard Zhang, Phillip Isola, Alexei A Efros, Eli Shechtman, and Oliver Wang. 2018. The unreasonable effectiveness of deep features as a perceptual metric. In *CVPR*.

Zhengyi Zhao, Shubo Zhang, Yuxi Zhang, Yanxi Zhao, Yifan Zhang, Zezhong Wang, Huimin Wang, Yutian Zhao, Bin Liang, Yefeng Zheng, Binyang Li, Kam-Fai Wong, and Xian Wu. 2025. Memereacon: Probing contextual meme understanding in large vision-language models. *Preprint*, arXiv:2505.17433.

Li Zheng, Xiaoming Wang, Yuhan Chen, and Jianwei Liu. 2024. Multi-granular multimodal clue fusion for meme understanding. *Preprint*, arXiv:2503.12560.

Jinguo Zhu, Weiyun Wang, Zhe Chen, Zhaoyang Liu, Shenglong Ye, Lixin Gu, Hao Tian, Yuchen Duan, Weijie Su, Jie Shao, and 1 others. 2025. Internvl3: Exploring advanced training and test-time recipes for open-source multimodal models. *Preprint*, arXiv:2504.10479.

## A  Extended Evaluation Results

## B  Prompt Sensitivity Analysis

The ranking in §6.4 was obtained with one structured prompt. To check whether quality differences reflect model capacity rather than prompt engineering, we re-run each open-source system with a concise alternative ("*Generate a meme that adapts the source to the target culture.*") instead of our structured prompt. Gemini was excluded due to API access constraints; the same three humans and seven VLM judges score the new outputs.

Table 7 reports Δ Overall (Simple − Structured) for each open-source system across evaluator type and direction. Janus-Pro-7B and LLaVA+FLUX prefer the structured prompt (all $\Delta < 0$, magnitudes up to 0.22); Gemma-4+FLUX is marginally better with the simple prompt ($\Delta$ up to $+0.07$). All cross-prompt differences are small relative to between-system gaps in Table 4 (typical inter-system gap $\geq 0.4$): the ranking among tested open-source systems is robust to prompt template, and prompt benefit is model-dependent and smaller than model choice.

## C  Per-System Human–LLM Correlations

Results in Table 8. Janus-Pro-7B ($r = +0.863$), Gemma-4+FLUX ($r = +0.663$), and Gemini ($r = +0.646$) all show significant human–LLM alignment. LLaVA+FLUX shows moderate human–LLM alignment ($r = +0.537$).

## D  Meme Transcreation Framework

Examples of visual recommendations from our Stage 1 LLaVA output to the FLUX.1 model:

1. Create a cartoon image using Tom and Jerry in a detailed pose and expression. Tom, wearing his usual red shirt, is standing behind Jerry, who is dressed in his classic blue sweater. Both characters have a slightly confused look on their faces. Jerry is scratching his head while Tom looks away with a slight frown. Background: An indoor setting that resembles a cocktail party or garden tea event, with blurred figures of people in the background engaged in conversation. Style: Keep Tom and Jerry's traditional animation style with bold lines and solid colors. Mood: Soft focus and warm lighting, suggesting an evening event.

2. Create a cartoon image using Bugs Bunny in a sitting pose, looking upward with a surprised or bewildered expression. - Background: A dimly lit room with a desk cluttered with various toys and a window showing a starry night sky. - Style: Retain the classic animation style with bold lines and vibrant colors. - Mood: Soft, nostalgic lighting with a hint of melancholy.

## E  Dataset

### E.1  Dataset Characteristics

### E.2  Topic Distribution Analysis

We applied enhanced weighted topic detection using Qwen-VL-Max (Bai et al., 2023) to conduct a comprehensive topic analysis across all 6,315 filtered memes, revealing fundamental differences in cultural priorities and humor focus.

| Evaluator | Chinese→US | | | | US→Chinese | | | |
|---|---|---|---|---|---|---|---|---|
| | **Gemini** | **Gemma4+FLUX** | **Janus** | **LLaVA+FLUX**[†] | **Gemini** | **Gemma4+FLUX** | **Janus** | **LLaVA+FLUX**[†] |
| Eval. 1 (H) | **4.67** | *4.62* | 4.27 | 4.55 | **4.61** | *4.48* | 4.02 | 4.24 |
| Eval. 2 (H) | **4.38** | *4.31* | 3.93 | 4.21 | **4.31** | *4.15* | 3.68 | 3.89 |
| Eval. 3 (H) | **3.73** | *3.64* | 3.27 | 3.45 | **3.65** | *3.45* | 3.01 | 3.17 |
| **Human Mean** | **4.26** | *4.19* | 3.82 | 4.07 | **4.19** | *4.03* | 3.57 | 3.77 |
| Qwen-VL-Max | **4.55** | *4.01* | 3.62 | 3.95 | **4.87** | *3.86* | 3.43 | 3.71 |
| LLaVA-v1.6 | 3.80 | **3.90** | *3.88* | 3.79 | **3.90** | *3.79* | 3.78 | 3.53 |
| InternVL3-8B | **4.54** | 3.53 | 3.58 | *3.69* | **4.62** | *4.00* | 3.91 | 3.47 |
| InternVL3-14B | **4.68** | *4.58* | 4.56 | 3.53 | **4.31** | *3.90* | 3.81 | 3.25 |
| Qwen3-VL-8B | **4.37** | *3.72* | 3.49 | 3.15 | **4.56** | *3.48* | 3.23 | 2.83 |
| Aya-vision-8b | **3.93** | 3.58 | *3.66* | 3.10 | **3.51** | *3.30* | 3.18 | 2.92 |
| Qwen2.5-VL-72B | 4.21 | **4.39** | *4.10* | 4.09 | **4.24** | 3.81 | 3.71 | *3.90* |
| **VLM Mean** ± 95% CI | **4.30***± 0.31 | 3.96 ± 0.37 | 3.84 ± 0.35 | 3.61 ± 0.35 | **4.29***± 0.43 | 3.74*± 0.23 | 3.58 ± 0.27 | 3.37 ± 0.37 |
| **H−VLM** Δ | −0.04 | +0.23 | −0.02 | +0.46 | −0.10 | +0.29 | −0.01 | +0.40 |

Table 6: Per–evaluator **Overall** scores for all four systems (structured prompt, 1–5 Likert scale), evaluated on the **100-sample baseline comparison subset** (distinct from the full evaluation set used in Table 2). Each cell shows one evaluator's mean score across all items in that direction. **Bold** = highest score per row within each direction panel; *italic* = second-highest. **VLM Mean**: mean of all 7 LLM judges; 95% bootstrap CI shown as ± half-width. **H−VLM** Δ: human mean minus VLM mean (positive = VLMs underestimate relative to humans). $^*p < .05$ vs. LLaVA+FLUX[†], two-sided paired $t$-test over the 7 LLM judge means, *uncorrected* for multiple comparisons. [†] = our system (reference for significance tests). (H) = human evaluator.

| System | Human | | VLM judges | |
|---|---|---|---|---|
| | **CH→US** | **US→CH** | **CH→US** | **US→CH** |
| Gemma-4 + FLUX (ours, ablation) | +0.06 | +0.06 | +0.04 | +0.07 |
| Janus-Pro-7B | −0.16 | −0.05 | −0.17 | −0.10 |
| LLaVA + FLUX (ours)[‡] | −0.16 | −0.08 | −0.22 | −0.14 |

*Note:* Δ Overall = Simple − Structured (positive: Simple better; negative: Structured better). 3 humans / 7 VLM judges as in §5. [‡]LLaVA+FLUX Simple uses 6 judges (Qwen2.5-VL-72B not run on Simple).

Table 7: Prompt sensitivity: Δ Overall (Simple − Structured) for each open-source system.

| System | **Pearson** $r$ | $p$ | **Spearman** $\rho$ | $p$ |
|---|---|---|---|---|
| Janus-Pro-7B | +0.863 | <.001*** | +0.803 | <.001*** |
| Gemma-4 + FLUX (ours, ablation) | +0.663 | <.001*** | +0.771 | <.001*** |
| Gemini 3.5 Flash | +0.646 | .023* | +0.657 | .020* |
| *LLaVA + FLUX (ours)* | *+0.537* | *.072 ns* | *+0.545* | *.067 ns* |

*Note:* Per-system correlations across all conditions × metrics;

Table 8: Per-system human–LLM agreement.

**Chinese Meme Topics.** Table 9 presents the top 10 topics in Chinese memes, collectively covering 97.2% of the dataset.

**American Meme Topics.** Table 10 presents the top 10 topics in American memes, collectively covering 97.7% of the dataset.

**Cross-Cultural Topic Comparisons.** Table 11 highlights key differences in topic priorities between the two cultures.

Key cultural patterns revealed: (1) *Digital Concentration*—Chinese memes more heavily focused on internet/digital life (71.6% combined vs. 67.5% in US); (2) *Educational Values*—American memes treat education as casual daily experience (7.8%), Chinese memes reflect intense academic pressure (2.1%); (3) *Family Representation*—American memes more frequently feature family humor (4.9%) vs. Chinese hierarchical respect (1.9%);

(4) *Leisure vs. Achievement*—American gaming culture prominent (2.7%), absent from Chinese top 10.

### E.3 Emotion Distribution Analysis

Using Qwen-based (Bai et al., 2023) automated emotion analysis, we classified all 6,315 memes according to Ekman's six basic emotions, providing insights into cross-cultural emotional expression patterns.

**Chinese Meme Emotions.** Table 12 presents the emotion distribution in Chinese memes.

**American Meme Emotions.** Table 13 presents the emotion distribution in American memes.

**Cross-Cultural Emotion Comparisons.** Table 14 highlights key differences in emotional expression priorities.

Key emotional patterns: (1) *Positive Emphasis*—Both cultures prioritize joy, Americans showing slightly higher positive focus (73.8% vs. 69.3%); (2) *Sadness Acceptance*—Chinese memes express sadness 2.5× more frequently, reflecting cultural acceptance of melancholic humor; (3) *Anxiety Expression*—American memes emphasize fear-based content (7.0% vs. 4.5%), aligning with therapeutic humor trends; (4) *Anger Manifestation*—Chinese memes show higher anger (8.3% vs. 6.9%), possibly reflecting more direct emotional expression; (5) *Cringe Culture*—American memes display higher disgust representation (4.4% vs. 3.0%), consistent with cringe comedy trends.

**Impact of Joy Dominance on Experimental Design.** The overwhelming dominance of Joy in both

### Table 9: Topic Distribution in Chinese Memes (N=3,165)

| # | Topic | Count (%) | Cultural Significance |
|---|-------|-----------|----------------------|
| 1 | Internet Culture | 1,931 (61.0%) | Digital lifestyle dominance, social media |
| 2 | Technology Digital | 337 (10.6%) | Tech adaptation, AI integration |
| 3 | Work Career | 216 (6.8%) | 996 culture, career pressure |
| 4 | Social Relationships | 148 (4.7%) | Friendships, social dynamics |
| 5 | Communication Language | 126 (4.0%) | Language barriers, expression styles |
| 6 | Personality Psychology | 115 (3.6%) | Individual traits, emotional responses |
| 7 | Education Learning | 65 (2.1%) | Academic pressure, Gaokao system |
| 8 | Family Dynamics | 61 (1.9%) | Family relationships, generational gaps |
| 9 | Animals Pets | 46 (1.5%) | Pet culture, cute content |
| 10 | Entertainment Media | 32 (1.0%) | Movies, shows, celebrity culture |

*Top 10 Total: 3,077 memes (97.2%)*

### Table 10: Topic Distribution in American Memes (N=3,150)

| # | Topic | Count (%) | Cultural Significance |
|---|-------|-----------|----------------------|
| 1 | Internet Culture | 1,651 (52.4%) | Social media, viral content, online trends |
| 2 | Technology Digital | 475 (15.1%) | Tech innovation, digital lifestyle |
| 3 | Education Learning | 247 (7.8%) | School experiences, college culture |
| 4 | Work Career | 198 (6.3%) | Job market, work-life balance |
| 5 | Family Dynamics | 155 (4.9%) | Family relationships, parenting |
| 6 | Communication Language | 87 (2.8%) | Expression styles, conversation humor |
| 7 | Gaming Entertainment | 85 (2.7%) | Video games, gaming culture, esports |
| 8 | Personality Psychology | 67 (2.1%) | Individual psychology, personality types |
| 9 | Social Relationships | 57 (1.8%) | Friendships, social interactions |
| 10 | Entertainment Media | 54 (1.7%) | Movies, TV shows, celebrity content |

*Top 10 Total: 3,076 memes (97.7%)*

### Table 11: Cross-Cultural Topic Priority Comparison

| Topic | CN | US | Interpretation |
|-------|----|----|----------------|
| Internet Culture | #1 (61.0%) | #1 (52.4%) | Both dominant; China more concentrated |
| Technology Digital | #2 (10.6%) | #2 (15.1%) | US higher tech innovation focus |
| Education Learning | #7 (2.1%) | #3 (7.8%) | US: daily life; China: high-stakes pressure |
| Family Dynamics | #8 (1.9%) | #5 (4.9%) | US: frequent topic; China: serious element |
| Gaming Entertainment | – | #7 (2.7%) | US leisure vs. China work/study priority |
| Work Career | #3 (6.8%) | #4 (6.3%) | Similar priority, different intensity |

### Table 12: Emotion Distribution in Chinese Memes (N=3,165)

| Emotion | Count (%) | Cultural Context |
|---------|-----------|------------------|
| Joy | 2,193 (69.3%) | Dominant positive humor expression |
| Anger | 263 (8.3%) | Frustration, social critique |
| Sadness | 258 (8.2%) | Melancholy, disappointment |
| Surprise | 213 (6.7%) | Shock, unexpected situations |
| Fear | 144 (4.5%) | Anxiety, worry |
| Disgust | 94 (3.0%) | Revulsion, distaste |

### Table 13: Emotion Distribution in American Memes (N=3,150)

| Emotion | Count (%) | Cultural Context |
|---------|-----------|------------------|
| Joy | 2,325 (73.8%) | Primary emotional expression |
| Fear | 219 (7.0%) | Anxiety, relatable worries |
| Anger | 217 (6.9%) | Frustration, social commentary |
| Surprise | 148 (4.7%) | Unexpected, absurd humor |
| Disgust | 140 (4.4%) | Cringe, distasteful situations |
| Sadness | 101 (3.2%) | Disappointment, darker humor |

Each cell: Pearson r between one human evaluator and one VLM judge across all conditions × metrics. ***p < .001, **p < .01, *p < .05. LLaVA+FLUX panel has 6 judges (no Qwen2.5-VL-72B run).

Figure 4: Per-system human × VLM Pearson $r$ heatmaps (2×2 panel). Each cell is the correlation between one human evaluator and one VLM judge across all available conditions × metrics for that system. Strong vertical bands indicate judges that align with humans across the board (e.g., Qwen-VL-Max for LLaVA+FLUX); pale/red cells indicate judge–human disagreement.

Table 14: Cross-Cultural Emotion Priority Comparison

| Emotion | CN | US | Interpretation |
|---|---|---|---|
| Joy | #1 (69.3%) | #1 (73.8%) | Both dominant; US slightly higher positivity |
| Anger | #2 (8.3%) | #3 (6.9%) | China: more direct frustration expression |
| Sadness | #3 (8.2%) | #6 (3.2%) | China: 2.5× higher melancholic acceptance |
| Surprise | #4 (6.7%) | #4 (4.7%) | Similar priority, China higher absurdist humor |
| Fear | #5 (4.5%) | #2 (7.0%) | US: anxiety culture, relatable worry themes |
| Disgust | #6 (3.0%) | #5 (4.4%) | US: higher cringe/distaste expression |

datasets (69.3% Chinese, 73.8% American) has important implications for our transcreation experiments and evaluation: (1) *Positive Bias in Evaluation*—Since most transcreated memes will naturally preserve joyful emotions, our system may appear more successful at humor preservation simply due to the high baseline of positive content. This necessitates careful interpretation of intent preservation scores in Section 5; (2) *Limited Negative Emotion Testing*—With less than 30% of memes expressing negative emotions (anger, sadness, fear, disgust), our system receives limited training signals for adapting complex negative emotional tones across cultures, potentially underrepresenting challenges in transcreating emotionally nuanced content; (3) *Generalizability Concerns*—The skewed distribution means our findings may generalize better to lighthearted, positive meme content than to darker, satirical, or critical humor styles; (4) *Cultural Authenticity vs. Emotional Consistency*—The Joy dominance simplifies one aspect of

transcreation (emotional tone transfer) while placing greater emphasis on cultural reference adaptation as the primary challenge. Despite this limitation, the Joy-dominant distribution accurately reflects real-world meme ecosystems where positive, shareable content naturally dominates social media platforms—making our experimental conditions ecologically valid even if not emotionally balanced.

# F Evaluation Metrics

**Quantitative Dimensions (1-5 scale):**

**Caption Quality** Evaluates whether the generated caption works effectively as meme text, considering clarity, readability, appropriate meme language/tone, engaging phrasing, and proper text formatting.

**Image Quality** Assesses whether the generated image functions effectively as a meme visual, considering visual clarity and quality, appro-

priate meme composition, recognizable elements/characters, and visual appeal and memorability.

**Synergy** Measures how well image and caption work together, evaluating coherent message delivery, emotional or humorous impact, logical connection between visual and text, and overall meme effectiveness.

**Cultural Fit** Evaluates cultural adaptation quality, including alignment with target culture's humor style, appropriate cultural references, target audience relatability, and avoidance of cultural misunderstandings.

**Intent Preservation** Assesses preservation of the original meme's intent, including message consistency, emotional tone preservation, humorous effect maintenance, and core meaning retention.

**Overall Score** The average of all dimension scores and reflects overall quality.

## G  Human Evaluator Profiles

Our evaluation employed three bilingual, bicultural evaluators with a deep understanding of both Chinese and US cultural contexts:

**Evaluator 1.** Native Chinese speaker with 10+ years US residence, PhD in Communication Studies. Regular engagement with both Weibo/Xiaohongshu and Reddit meme communities. Assessment style: Entertainment-focused, generous scoring emphasizing humor effectiveness over technical perfection. Mean overall score: 4.42/5.0.

**Evaluator 2.** American-born Chinese with native-level proficiency in Mandarin and US, MA in Comparative Cultural Studies. Active participation in both Chinese and US digital cultures. Assessment style: Balanced and objective, applying consistent standards across dimensions. Mean overall score: 4.09/5.0. Showed highest correlation with Qwen-VL-Max ($r = 0.964$).

**Evaluator 3.** Native Chinese speaker with 12+ years of US experience, professional translator with meme localization background. Expertise in cultural adaptation nuances. Assessment style: Critical and quality-focused, emphasizing cultural authenticity and linguistic precision. Mean overall score: 3.31/5.0.

All evaluators received identical structured prompts specifying six evaluation dimensions, worked independently without access to others' ratings, and maintained consistency through detailed scoring rubrics. Inter-evaluator correlations demonstrate moderate to strong agreement: Evaluator 1-2 ($r = 0.72$), Evaluator 1-3 ($r = 0.58$), Evaluator 2-3 ($r = 0.81$), confirming reliable yet stylistically distinct evaluation perspectives.

## H  VLM Evaluator Details

Six VLMs served as automated evaluators on the full bidirectional dataset, selected for multilingual (Chinese-English) capability, multi-image processing, and reproducibility. A seventh VLM judge, **Qwen2.5-VL-72B** (Alibaba Cloud), was added for the baseline comparison subset (Section 6.4) to strengthen the cross-system evaluation panel.

- **Qwen-VL-Max** (Alibaba Cloud): Commercial API with extensive Chinese–English training; consistently strong alignment with human evaluators (see Table 3).

- **LLaVA-v1.6-Vicuna-13B**: Same architecture as the transcreation system; no meaningful correlation with humans.

- **InternVL3-8B/14B**: Recent open-source models with strong vision capabilities; weak positive correlation overall.

- **Qwen3-VL-8B-Instruct**: Smaller Qwen variant; weak positive correlation.

- **Aya-vision-8b**: Massively multilingual model; near-zero correlation.

All LLMs received identical prompts specifying evaluation dimensions and rating scales. Temperature set to 0.7 for balanced consistency-creativity tradeoff.

## I  Transcreation Prompts

**Stage 1 (LLaVA 1.6) - Cultural Analysis Prompt Example:**

*You are a cultural adaptation expert. Analyze this [SOURCE CULTURE] meme and create a transcreated version for [TARGET CULTURE] audiences. Your response should include:*

*1. Cultural Context Analysis: Identify culture-specific elements (references, idioms, visual symbols, humor mechanisms)*

*2. Intent Extraction: What is the core message/emotion/joke?*

*3. Target Culture Mapping: Find equivalent concepts in [TARGET CULTURE]*

*4. Transcreated Caption: Generate a new caption preserving intent while using [TARGET CULTURE] appropriate references and style*

*5. Visual Recommendations: Describe ideal visual template (characters, setting, composition) culturally appropriate for [TARGET CULTURE]*

**Stage 2 (FLUX.1) - Visual Generation Prompt Example:**

*Create a meme-style image: [LLaVA's visual recommendations]. Style: internet meme, high contrast, recognizable characters, clear composition suitable for text overlay. [TARGET CULTURE]-appropriate visual elements. Resolution: 1024x1024px.*

Full prompt templates with examples will be made available in our public repository upon acceptance.

## J Example Transcreations

### Success Example - US→Chinese:

*Source (US):* "Nobody: Absolutely nobody: Me at 3 am:" [Image: Person raiding refrigerator]

*Transcreated (Chinese):* "深夜两点的我:" (Me at 2 am) [Image: Cartoon cat staring at food]

*Adaptation rationale:* Replaced human figure with animal imagery (preferred in Chinese memes), adjusted time (2 am vs 3 am reflects Chinese sleep patterns), simplified narrative structure for conciseness.

### Challenge Example - Chinese→US:

*Source (Chinese):* "内卷" (involution) concept with study-exhausted imagery

*Transcreated (US):* "The grind never stops" [Office worker imagery]

*Limitation:* US lacks a precise equivalent for "内卷" (intensifying competition in zero-sum environments). "Grind culture" captures work intensity but misses the systemic competition aspect, illustrating cultural untranslatability challenges.

Additional examples and failure case analysis are available in the supplementary materials.

Figure 5: Examples of successful Chinese→US meme transcreations.
**Original (middle left — dog meme):** "Honest smile"
**Original (bottom left — angry emoji meme):** "You looking for a knuckle sandwich?"

Figure 6: Examples of successful US→Chinese meme transcreations.

**Transcreated (top right — spongebob meme):** "Dad thinks I'm up early studying, I'm really on my 14th straight gaming session"

**Transcreated (middle right — spongebob meme):** "Kid: Mom, I'm playing a game

Mom: I'm cooking

Kid: Can you pause it?

Mom: How dare you use my own teachings against me?"

**Transcreated (middle right — Spencer Wright meme):** "Tiktok be spamming ads upfront, still not gonna pay for premium"