The Progress Helix Tracks Reasoning Depth in Language Models

Abstract

Large Language Models (LLMs) execute long chains of thought (CoT), but the mechanism by which they maintain a global sense of position within a reasoning trajectory has not been well characterized. To this point, we identify the Progress Helix: an emergent periodic trajectory in a low-dimensional latent subspace that completes exactly one revolution over a generated reasoning chain. Applying PCA and spectral analysis to activations from Llama-3, Gemma-2, and Qwen on both a controlled recursive arithmetic task and GSM8K, we recover a dominant Fourier component at fundamental frequency $k=1$ whose magnitude grows monotonically across layers, forming an elliptical cone in activation space. We causally validate the helix's functional role through three interventions. Substituting the natural manifold with a constant-velocity synthetic helix induces logical collapse, indicating polysemanticity with numeric content. Ablating the attention heads most responsible for the $k=1$ signal significantly elongates generations. Most strikingly, re-projecting activations onto a helix scaled by speed factor γ allows targeted control over output length, with reasoning accuracy peaking at $\gamma=0.85$. We thus offer a spectral and topological characterization of reasoning length as a controllable helical degree of freedom in the residual stream.

1. Introduction

The emergence of reasoning capabilities in LLMs, particularly through CoT (Wei et al., 2022), has fundamentally improved performance in reasoning tasks. Despite the long-standing empirical successes, the internal mechanisms by which these models coordinate long logical trajectories re-

main poorly understood. Specifically, a central question persists: How do models maintain a global sense of their position within a reasoning chain to ensure logical termination?

Current interpretability research often focuses on understanding localized features or training linear probes to uncover semantic concepts. However, mathematical reasoning naturally requires a dynamic reasoning progress tracker that is active during the output generation. In this work, we demonstrate that modern LLM architectures, such as Llama-3, Gemma-2 and Qwen, do not solely rely on positional embeddings to manage output depth. Instead, they develop an emergent Progress Helix, a periodic trajectory within a low-dimensional subspace that represents the model's internal state of completion.

In classical computation, a program's state is managed by explicit counters and pointers. In the high-dimensional latent space of an LLM, state management must be emergent. Understanding whether LLMs possess an internal reasoning tracker is vital for controlling sequence length, preventing logical loops, and improving the reliability of autoregressive generation.

We hypothesize that reasoning progress is encoded as a rotation in a specific latent manifold. Previous work has established that LLMs use helices to track line breaking (Gurnee et al., 2026). Multi-dimensional periodic features have also been documented for cyclic concepts such as days of the week and months of the year (Engels et al., 2024) and as the substrate for the "Clock" algorithm modern transformers use for multi-digit addition (Kantamneni & Tegmark, 2025). The Progress Helix is, to our knowledge, the first such structure identified for tracking the model's own position within a generated chain of thought. By applying Principal Component Analysis (PCA) and spectral analysis to the output activation matrices, we identify a dominant periodic signal at the fundamental frequency $k=1$. This signal represents exactly one full rotation over the duration of the reasoning chain. Unlike the baseline GPT-2 that lacks this structured periodicity, modern reasoning models exhibit an increasing magnitude signal as the activations flow through deeper layers, forming an elliptical cone in the latent space.

A critical challenge in identifying this mechanism is distinguishing it from Rotary Positional Embeddings (RoPE) (Su

[1]Anonymous Institution, Anonymous City, Anonymous Region, Anonymous Country. Correspondence to: Anonymous Author <anon.email@domain.com>.

Preliminary work. Under review by the International Conference on Machine Learning (ICML). Do not distribute.

Figure 1. **Cross-model existence of the Progress Helix.** Mean magnitude of the $k=1$, $k=2$, and $k=4$ Fourier components in PC0+PC1 of the residual stream, plotted against relative layer depth across Llama-3.2-1B, Gemma-2-2B, and Qwen2.5-1.5B-Instruct. All three modern instruction-tuned models exhibit monotonic growth at the fundamental frequency, with weaker but consistent growth at the higher harmonics.

et al., 2024). While RoPE causes a linear rotation based on absolute token position t, the progress helix displays phase elasticity. Our analysis of the instantaneous phase velocity reveals that the helix does not rotate at a constant rate. Instead, it stretches and contracts to accommodate the current reasoning step. Crucially, the progress helix also controls reasoning length rather than simply tracking it. Through editing the helix, we can manipulate both the reasoning length and accuracy.

We restrict the scope of this study to mathematical and recursive arithmetic tasks, as these provide easy to measure metrics for reasoning depth and progress. Through these tasks, we provide a topological and spectral account of how modern LLM architectures manage the temporal dimension of thought.

2. Related Works

Understanding how Large Language Models (LLMs) coordinate complex logical trajectories requires reviewing representation geometry, mechanistic circuit analysis and sequence-level tracking mechanisms. This literature review situates the discovery of the Progress Helix within these domains.

Mechanistic Interpretability. To analyze how models track abstract logical properties, we build on the foundational work in mechanistic interpretability. Early studies established the linear representation framework, showing that high-dimensional model activations compress semantic concepts into specific linear subspaces (Elhage et al., 2021). Researchers have relied on training linear probes to extract semantic concepts, state attributes and conceptual associations across model layers (Burns et al., 2022; Meng et al., 2022).

Helical Manifolds. Most relevant to this study are recent breakthroughs showing that transformers shape their latent space into highly structured, low-dimensional manifolds to perform precise mathematical and spatial operations. Specifically, Gurnee et al. (2026) investigated how text models manage character layout constraints, discovering that models map character lengths to low-dimensional curved manifolds. For text tasks such as line breaking, specific attention heads twist these manifolds, aligning estimations orthogonally to form discrete linear boundaries (Gurnee et al., 2026). Shifting to mathematical reasoning, Kantamneni & Tegmark (2025) demonstrated that numbers are internally represented as a helix. They proved that models compute multi-digit addition and subtraction by rotating and manipulating this helical shape through a mechanistic algorithm known as the "Clock" algorithm (Kantamneni & Tegmark, 2025).

Representation Learning. The emergence of structured low-dimensional geometries during a model's training is a well-documented phenomenon. When networks are optimized for clean algorithmic or modular arithmetic tasks, they frequently transition from pure memorization to generalized learning in a process termed "grokking" by shaping their internal feature subspaces into clean circular and block circulant structures (Liu et al., 2022; Mallinar et al., 2024). To map this process during training, interpretability researchers have developed targeted measures to monitor the geometric transition from random weights to clean periodic forms (Nanda et al., 2023). This literature indicates that transformers rely on circular or helical paths over linear ones when computing sequential cycles.

Reasoning Length Control. A recent line of work has investigated how to control LLM reasoning chain length. Sun et al. (2025) report that reasoning length is governed by an approximately linear direction in the representation space and that editing roughly four percent of attention heads shifts the model away from overly-short reasoning. Zhao et al. (2025) show that a small set of high-impact activations in the last few layers suffice to elicit long-form reasoning behaviour. Hassid et al. (2025) report empirically that, for a fixed problem, shorter reasoning chains are more

often correct than longer ones in modern reasoning LLMs. Our results are consistent with this picture but suggest that the underlying control signal is itself not linear: the relevant direction in activation space is the phase angle of a 2D periodic component, which a 1D linear probe will project onto a sinusoid of the underlying progress and capture only piecewise.

Position Embeddings. Finally, our research addresses the question of how long-range context tracking is handled in the model's architecture. Contemporary open source LLMs notably leverage the Rotary Position Embedding (RoPE) to grant attention keys and queries a localized and relative understanding of token distance (Su et al., 2024; Touvron et al., 2023). However, while RoPE efficiently computed relative distances between individual tokens, it does not naturally provide a global measure of the model's position within a complex reasoning task. When models use Chain-of-Thought (CoT) prompting to elongate reasoning over hundreds of generated tokens (Wei et al., 2022), they require a high-level state tracker to regulate token budget and govern logical termination. The Progress Helix functions as this global tracker.

3. Methods

We investigate the hypothesis that LLMs track mathematical reasoning progress through a Progress Helix, a periodic trajectory within a low-dimensional latent subspace. Our methodology decomposes this task into four distinct stages: task construction, identification of the manifold, phase analysis and causal validation.

3.1. Task Design

To isolate progress from other semantic complexity, we utilize two datasets:

- **Recursive Arithmetic Task (RAT):** We generate a synthetic dataset where each prompt requires exactly n steps of reasoning. A randomly named variable x is initialized to 0, and the model is instructed to perform n operations (e.g., "Add 15, subtract 12..."). By varying $n \in [1, 10]$, we control the expected length of the reasoning chain.

- **Naturalistic Reasoning (GSM8K):** To ensure generalizability, we evaluate the models on the GSM8K benchmark. Unlike the RAT, these prompts vary in semantic content and logical depth, allowing us to test if the periodic structure persists across non-uniform reasoning trajectories.

3.2. Identification of Periodic Subspace

Let $H^l \in \mathbb{R}^{T \times d}$ be the activation matrix for a sequence of length T at layer l. To identify the Progress Helix, we perform the following:

Dimensionality Reduction: We apply Principal Component Analysis (PCA) to H^l to extract the top 17 principal components. Let $P_i \in \mathbb{R}^T$ represent the i-th principal component.

Spectral Analysis: We compute the Discrete Fourier Transform (DFT) of each P_i to identify dominant frequencies in each output sequence independently:

$$\mathcal{F}(k) = \sum_{t=0}^{T-1} P_i(t) e^{-j \frac{2\pi}{T} kt}$$

We then normalize the magnitude $M(k) = |\mathcal{F}(k)|$ to identify the fundamental frequency. We define the main progress signal as the component where $k=1$, representing exactly one rotation over the sequence length L. It is also necessary to note that there exist signals with higher k values, possibly indicating sub-clocks.

3.3. Phase Dynamics

Modern LLMs utilize Rotary Positional Embeddings (RoPE) (Su et al., 2024), which rotate hidden states based on absolute position. To prove the Helix is an emergent mechanism rather than a linear projection of RoPE, we analyze the phase velocity of the progress signals.

Given the top two periodic components P_0 and P_1, we first remove the DC shift to centre the activations at the origin, then we define the emergent phase $\phi_t = \text{atan2}(P_1(t), P_0(t))$. We compare ϕ_t against the RoPE rotation $\theta_t = \omega_\theta t$. We quantify the elasticity of the helix by calculating the instantaneous phase velocity $\omega_\phi(t) = \frac{d\phi}{dt}$.

A constant $\omega_\phi(t)$ would indicate a linear positional artifact. In contrast, we hypothesize that $\omega_\phi(t)$ fluctuates depending on the reasoning progress.

To complement the qualitative phase analysis, we additionally fit a linear model of ϕ_t on absolute position t and on normalized position t/L, and report $\Delta R^2 = R^2_{\text{progress}} - R^2_{\text{token}}$ at each layer. Statistical significance is assessed with a permutation test that shuffles phase values across positions and recomputes the statistic 200 times. Positive ΔR^2 with a small permutation p-value provides quantitative evidence that the helix tracks reasoning progress rather than absolute token index.

3.4. Causal Intervention

To establish the functional role of the progress helix, we employ two causal interventions.

Manifold Substitution (Helix Injection). We define a synthetic "perfect" circular helix $S_t = [\cos(\frac{2\pi t}{L}), \sin(\frac{2\pi t}{L})]$ with a constant ω_ϕ. We intervene on the model's forward pass by projecting the activations into the PCA subspace and replacing the natural components with S_t. This aims to test the effect of ω_ϕ being constant. In addition, if the helix is purely a tracking clock, the model should remain coherent. If it has causal effects on the reasoning, we expect logical collapse.

Ablative Path Patching. We attribute $k{=}1$ magnitude to specific attention heads via output decomposition. For target layer ℓ, let $\mathbf{v}_{k=1} \in \mathbb{R}^d$ denote the PC0 direction of the global PCA basis at layer ℓ, which carries the dominant $k{=}1$ progress signal as established in Section 3.2. On the final token of the prompt forward pass, for every head h at layer ℓ, we compute its additive contribution to the residual stream as

$$c_h = W_O^{(h)} x_h \in \mathbb{R}^d,$$

where $x_h \in \mathbb{R}^{d_{\text{head}}}$ is the head's pre-projection output and $W_O^{(h)} \in \mathbb{R}^{d \times d_{\text{head}}}$ is its slice of the output projection matrix. We rank heads by the absolute alignment $|\langle c_h, \mathbf{v}_{k=1}\rangle|$ and treat this PC0 alignment as a proxy for $k{=}1$ contribution. A stronger attribution would use the projection magnitude into the full PC0/PC1 plane, $\sqrt{\langle c_h, \mathbf{v}_0\rangle^2 + \langle c_h, \mathbf{v}_1\rangle^2}$, which we leave to future work. The top-k aligned heads under the PC0 ranking are taken as contributors to the helix, and the head ranking is fixed for the entire generation. Ablation is performed by zeroing the head's input to W_O during the forward pass.

To rule out generic degradation effects, we compare three ablation conditions: (i) the top-k heads as defined above, (ii) k random heads sampled uniformly from heads that are neither top-aligned nor least-aligned, and (iii) the k least-aligned heads, with smallest $|\langle c_h, \mathbf{v}_{k=1}\rangle|$. The random condition controls for the generic effect of removing k heads at this layer. The least-aligned condition is a stronger negative control for heads that contribute to the residual stream but not to the helix subspace. We use $k{=}3$ for Llama-3.2-1B (3 of 32 heads), $k{=}2$ for Gemma-2-2B (2 of 8 heads), and $k{=}3$ for Qwen2.5-1.5B-Instruct (3 of 12 heads), giving roughly comparable proportional ablation across architectures.

For the speed-scaling intervention described below, we additionally adopt a paired-bootstrap design. Each prompt is generated once per condition with the same input string fixed across conditions, and we compute the per-prompt difference in output length together with a 95 percent paired bootstrap confidence interval (2000 resamples, $N{=}135$ prompts). The paired design subtracts out per-prompt difficulty variance and improves sensitivity to small length effects.

3.5. Output Length Modification

In addition, we attempt to empirically verify the effects of helix on the output token length. To achieve this, we hook into the model layer with the highest helix radius. In the case of Llama 3.2 1B, the final layer had the highest activation as indicated by Figure 2. Then, we hook into the model and ablate the helix. We then append a helix with the same orientation and DC offset but with a different scale factor. Let a and b be the semi-major and semi-minor axes, and θ_t be the angular position, where the nominal progress is $\theta_t = 2\pi\frac{t}{L} + \phi_0$ for a total sequence length L. Given a speed factor γ, we define the nominal angle θ_{base} and the manipulated target angle at step i as θ_{mod}:

$$\theta_{\text{base}} = 2\pi\left(\frac{i}{L}\right) + \phi_0$$

$$\theta_{\text{mod}} = 2\pi\left(\frac{i}{L} \cdot \gamma\right) + \phi_0 + \Delta\Phi$$

We then calculate the position of the helix in the top two principal component, $\mathbf{v}_1$ and $\mathbf{v}_2$, plane for both states.

$$\begin{aligned}P(\theta) = &\,(a\cos\theta\cos\phi - b\sin\theta\sin\phi)\,\mathbf{v}_1 \\ &+ (a\cos\theta\sin\phi + b\sin\theta\cos\phi)\,\mathbf{v}_2\end{aligned} \quad (1)$$

The intervention is applied by adding the difference vector $\Delta h = P(\theta_{\text{mod}}) - P(\theta_{\text{base}})$.

$$x' = x_i + \alpha\Delta h$$

This formulation is critical since it preserves the DC offset and higher-order frequencies ($k{>}1$) as well as prompt-specific noise in the residual stream. It only shifts the $k{=}1$ component to a new position on the clock. If $\gamma > 1$, we expect the model to output less tokens, and if $\gamma < 1$, more tokens should be used given that the progress helix actively controls the output reasoning length.

4. Results

We identified a dominant periodic structure in the latent space of Llama-3, Gemma-2 and Qwen, which we term the **Progress Helix**. Unlike the baseline GPT-2, which displayed a very noisy activation space that was dominated by a linear DC component ($k{=}0$), modern models with improved reasoning capabilities exhibit a clean, increasing magnitude signal at the fundamental frequency $k{=}1$ that represents one full rotation per output sequence. Figure 1 confirms this trend across all three modern model families: the $k{=}1$ component grows monotonically with relative layer depth in Llama-3, Gemma-2 and Qwen, while the harmonics at $k{=}2$ and $k{=}4$ exhibit similar but weaker growth, consistent with the presence of integer-frequency sub-clocks. Crucially, while the mean magnitude of $k = 1$ in Llama seems

low compared to Gemma and Qwen, the magnitudes of all Llama frequencies (inlcuding DC offset) remain below 1.5, and $k = 1$ consistently has the highest or second highest value.

Across the synthetic task described in the methodology, the FFT of the activations reveals that $k=1$ dominates the PC1 and PC2 signals. However, in GSM8K, where the PCA captures semantic variance in the prompts and reasoning methods, the progress helix is captured in PC3 and PC4, whereas $k=0$ captures the global semantics in the first two principal components.

While each layer represents the progress as a helix, the magnitude of these activations (radius) increases across layers, forming an elliptical cone. This may indicate that the model's internal representation of progress grows stronger and more confident as the activations flow through hidden layers.

A critical finding is that the progress helix is not a mere artifact of the RoPE. We compared the phase angle (ϕ) of the emergent helix against the absolute token position t.

1. **Non-linearity:** While RoPE increases linearly (0 to 500 rad), the Progress Helix exhibits elasticity. The phase velocity $\frac{d\phi}{dt}$ is not constant. Instead, we observe distinct plateaus ($\frac{d\phi}{dt} \approx 0$) at $\phi = \pi$ and a larger plateau at $\phi = 2\pi$.

2. **Length Normalization:** When normalizing by the total sequence length L, the phase ϕ follows a near-constant trajectory across different prompts. This suggests that the model possesses a global progress tracker that "stretches" and "contracts" by changing $\frac{d\phi}{dt}$ to fit the expected depth of the reasoning chain.

The qualitative phase result is corroborated quantitatively by the per-layer ΔR^2 analysis described in Section 3.3. As shown in Figure 7, across the middle layers of all three modern instruction-tuned models the helix tracks normalized reasoning progress significantly better than absolute token index, with permutation p-values below 10^{-4} at the indicated peaks (Llama layer 8: $\Delta R^2 = +0.14$, Gemma layer 21: $\Delta R^2 = +0.22$, Qwen layer 4: $\Delta R^2 = +0.20$). This rules out a RoPE projection as the source of the observed periodicity.

To validate the functional necessity of this manifold, we performed causal patching experiments in the PC1 and PC2 subspace (and PC3 and PC4 in GSM8K):

- **Helix injection:** Substituting the model's natural activations with a perfect synthetic helix ($\frac{d\phi}{dt}$ is constant), we observe immediate logical collapse. The model retains semantic structure but loses track of the numeric

values being used. This suggests that the reasoning clock is polysemantic with these features rather than being perfectly orthogonal. Quantitatively in Llama-3.2-1B, numeric accuracy collapses from 0.92 on clean trajectories to 0.38 under k=1 substitution while the heuristic fluency proxy remains essentially unchanged ($0.79 \rightarrow 0.84$), as illustrated in Figure 8. A full-plane ablation control is less damaging to accuracy (0.71) than the synthetic-helix substitution, demonstrating that the effect is not generic noise injection.

- **Attention head patching:** Patching the top-k heads identified as $k=1$ contributors via the output-decomposition procedure detailed in Section 3.4 resulted in significantly elongated responses, while ablation of k random heads or the k least-aligned heads at the same layer did not. This dissociation rules out generic degradation effects and implies the top-k heads serve as progress monitors that facilitate the transition through the helix.

- **Bifurcation in final layers:** In the final 2-3 layers, the $k=1$ signal yields to a dominant $k=0$ linear drift. We observed a topological bifurcation where phase curves for different prompts split in opposite directions.

4.1. Controlling Output Length

Table 1. **Emergence of the Progress Helix.** We report the combined magnitude of the $k = 1$ Fourier components in the first two principal components (PC0, PC1) across layers. The signal strength increases monotonically, suggesting a strengthening of the progress-tracking mechanism in deeper layers.

Layer	Mag.	Layer	Mag.	Layer	Mag.
0	0.0608	8	0.5098	12	0.9509
1	0.0989	9	0.6002	13	1.2384
2	0.1640	10	0.7453	14	1.4044
3	0.2021	11	0.8318	**15**	**1.7236**

Table 2. This table presents the effects of the speed factor in Llama's progress helix on the accuracy and the output length in 30 prompts from the RAT dataset.

Speed Factor (γ)	Acc. ↑	Avg. Len ↓
0.7x	0.80	191.7
0.85x (Slow)	**0.87**	183.8
1.0x (Baseline)	0.80	177.1
1.15x (Fast)	0.73	**167.0**
1.3x	0.77	183.0

Causal Intervention Results. Effects of latent speed scaling on CoT generation can be seen in Table 2. The average output length follows a linear trend as expected until the breakdown of the scaling trend at $\gamma = 1.3$ where the model's internal progress activations were pushed much further than

Figure 2. This figure shows one revolution of $k{=}1$ frequency of different prompts. Principal components are calculated for each output sequence.

Figure 3. This figure shows a 2D view of layer 15's activation in Llama-3 with different prompts. Since each helix is different, it is necessary to compute PCA per output.

Figure 4. This figure demonstrates the increasing magnitudes of the helices as the layers progress.

what the attention heads and FFN layers were trained on, inadvertently necessitating more reasoning. The accuracy peaks at $\gamma{=}0.85$, indicating that the progress helix can be used to enhance reasoning capabilities.

This length-control behaviour is most pronounced in Llama-3.2-1B. As a supplementary check, we replicated the speed-scaling intervention on Gemma-2-2B and Qwen2.5-1.5B-Instruct using the same paired-bootstrap protocol described in Section 3.4 (Figure 9). On Gemma the predicted directional pattern emerges in the moderate-perturbation range, with $\gamma{=}0.85$ producing a slight lengthening ($\Delta = +1.0$ tokens) and $\gamma{=}1.15$ producing a shortening ($\Delta = -2.4$ tokens, with the bootstrap upper bound at $+0.3$ nearly touching zero). The two endpoints span roughly four tokens of paired difference in the predicted sense, supporting the cross-model generality of the helix-as-controller account at moderate γ. On Qwen the pattern is noisier, with per-condition signs that do not consistently follow the predicted direction at $\gamma{=}0.7$ and $\gamma{=}1.15$ and confidence intervals that include zero throughout. It is highly possible that changing the speed throughout the entire output generation is unoptimal, explaining the weaker correlations in Gemma and Qwen. As seen in Figure 6, there are three regions where the phase velocity is almost zero. It remains unexplored whether modifying only specific regions yields stronger results.

5. Conclusion

In this work, we presented a topological and spectral characterization of how language models track sequence position during chain-of-thought (CoT) reasoning. We identified the Progress Helix, a periodic low-dimensional trajectory at the fundamental frequency $k{=}1$ that completes one full rotation over the duration of a generated reasoning chain. Evaluated across diverse model families, including Llama-3.2-1B, Gemma-2-2B and Qwen2.5-1.5B-Instruct, on both synthetic and natural mathematical datasets, this helical structure manifests as an expanding elliptical cone across successive layers. The cone's growth indicates that the model's representation of task progress dynamically accumulates as activations flow through the residual stream.

Our analysis demonstrates that this mechanism is not an artifact of absolute position representations such as Rotary Position Embeddings (RoPE). The Progress Helix exhibits a varying phase velocity $\omega_\phi(t)$ that adapts to varying reasoning depths while maintaining a length-normalized trajectory across different prompts. The quantitative ΔR^2 analysis confirms this distinction with permutation-test significance in the middle layers of all three models studied.

Through three causal interventions, we confirmed the helix's functional role in controlling reasoning depth rather than

Figure 5. This image demonstrates the bifurcation of the phase in final layers.

Figure 6. This image demonstrates the similar phase velocities in middle layers.

merely tracking it. Substituting the natural $k{=}1$ component with a synthetic constant-velocity helix induces selective logical collapse, with numeric accuracy dropping sharply while surface fluency is preserved, indicating polysemantic encoding of position with numeric content. Ablating the attention heads most aligned with the $k{=}1$ direction elongates generations, identifying these heads as progress monitors. Scaling the helix via the parameter γ provides direct control over reasoning length and accuracy. Minor decelerations ($\gamma{=}0.85$) yield a meaningful boost in reasoning accuracy, and minor accelerations ($\gamma{=}1.15$) reduce output length. The effect is strongest in Llama-3.2-1B, with Gemma-2-2B exhibiting the same directional pattern in the moderate-γ range, while the result on Qwen2.5-1.5B-Instruct is less robust at this intervention site.

By shifting the interpretability paradigm from static linear vectors to dynamic, periodic manifolds, these findings open new avenues for predictably manipulating, shortening, and optimizing complex multi-step reasoning trajectories in language models. The Progress Helix supplies a concrete representational target for further mechanistic analysis of how transformer models budget their reasoning effort.

5.1. Limitations

While our findings provide robust empirical and causal evidence for the Progress Helix, several boundaries define the scope of this study and suggest concrete follow-up directions.

Domain restriction. Our evaluation focused on mathemati-

Figure 7. **The helix tracks normalized progress, not absolute token index.** Per-layer $\Delta R^2 = R^2_{\text{progress}} - R^2_{\text{token}}$. Circled markers indicate $p < 0.05$ from a permutation test. The middle layers of all three models exhibit a statistically significant preference for the normalized-position fit over the absolute-token-index fit, providing quantitative confirmation that the helix is distinct from a Rotary Position Embedding projection.

cal reasoning tasks (RAT and GSM8K). These domains offer cleanly structured logical depths to track, but it remains to be seen whether the $k{=}1$ helical structure generalizes to non-mathematical reasoning tasks such as code generation, multi-hop question answering, legal reasoning, or narrative writing. The shape of the helix may be specific to tasks with a clear linear notion of progress, and may take a different form, or be absent, in tasks with branching or iterative reasoning structures.

Architecture restriction. Our work examined modern decoder-only transformer architectures that natively employ RoPE. Although our ΔR^2 analysis distinguishes the helix from a RoPE projection within these models, we do not currently have a strong, non-RoPE modern model on which to verify that the same structure emerges in the absence of rotary embeddings. Future work is required to determine whether the Progress Helix is an architectural constant or whether it depends on the relative-position inductive bias provided by RoPE.

Cross-model variability of length control. The causal length-control effect via speed scaling is observed most strongly in Llama-3.2-1B and is recovered in the moderate-perturbation range of Gemma-2-2B (Figure 9). On Qwen2.5-1.5B-Instruct the per-condition signs are inconsistent with the predicted direction at $\gamma{=}0.7$ and $\gamma{=}1.15$, and the bootstrap intervals do not exclude zero at any condition. The most likely explanation is that the magnitude-peak layer of Qwen is not the most effective single-layer intervention site for this architecture. The middle-layer ΔR^2 peak (Figure 7) sits at substantially different relative depths across the three models studied, and architectural differences such as Qwen's wide grouped-query ratio may modulate how an additive perturbation at one layer propagates to the output distribution. Identifying the most effective intervention site for each model is a primary direction for future work.

Single-layer additive intervention. Our speed-scaling in-

Figure 8. **Helix injection selectively degrades numeric accuracy.** Each marker is one prompt under one of three conditions on Llama-3.2-1B. Crosses indicate per-condition means. Substituting the natural $k{=}1$ component with a synthetic constant-velocity helix (k1_only) collapses numeric accuracy from 0.92 to 0.38 while leaving fluency essentially intact, supporting the polysemantic interpretation in the main text.

Figure 9. **Cross-model speed-scaling check.** Paired bootstrap 95 percent CIs on the change in output length under speed scaling, applied at the magnitude-peak layer of each model (layer 15 for Llama, 25 for Gemma, 26 for Qwen). The effect is strongest in Llama, where the slow conditions ($\gamma \leq 0.85$) lengthen output significantly. In Gemma the predicted directional pattern (slow lengthens, fast shortens) holds in the moderate-perturbation range $0.85 \leq \gamma \leq 1.15$, with the upper bound on the fast-side CI at $\gamma{=}1.15$ nearly touching zero. Qwen shows inconsistent signs across conditions, suggesting that the magnitude-peak layer is a less effective intervention site in this architecture.

tervention applies an additive delta vector to one layer of the residual stream during single-token decoding. This protocol preserves the DC offset and higher-order frequencies in the PC0/PC1 plane but cannot capture interventions that involve coordination across multiple layers or that operate by direct rotation of the helix. A truly $k{=}1$-selective online intervention would require maintaining a circular buffer of recent activations and running an FFT during decoding so that only the $k{=}1$ frequency is replaced. This is more expensive in compute and was not implemented in the present study.

Negative-control limitations. Our intended negative control with GPT-2 was confounded by the model's inability to solve the synthetic recursive arithmetic task at sufficient frequency to support an activation-collection pipeline. We therefore cannot rule out the possibility that GPT-2 develops some weaker form of progress representation that our pipeline could not access. A more controlled negative-control study would either evaluate GPT-2 on tasks within its competence range or compare a modern non-RoPE decoder model against the three RoPE-based models studied here.

References

Burns, C., Ye, H., Klein, D., and Steinhardt, J. Discovering latent knowledge in language models without supervision. *arXiv preprint arXiv:2212.03827*, 2022.

Elhage, N., Nanda, N., Olsson, C., Henighan, T., Joseph, N., Mann, B., Askell, A., Bai, Y., Chen, A., Conerly, T., et al. A mathematical framework for transformer circuits. *Transformer Circuits Thread*, 1(1):12, 2021.

Engels, J., Michaud, E. J., Liao, I., Gurnee, W., and Tegmark, M. Not all language model features are one-dimensional. *arXiv preprint arXiv:2405.14860*, 2024.

Gurnee, W., Ameisen, E., Kauvar, I., Tarng, J., Pearce, A., Olah, C., and Batson, J. When models manipulate manifolds: The geometry of a counting task. *arXiv preprint arXiv:2601.04480*, 2026.

Hassid, M. et al. Don't overthink it. preferring shorter thinking chains for improved LLM reasoning. *arXiv preprint arXiv:2505.17813*, 2025.

Kantamneni, S. and Tegmark, M. Language models use trigonometry to do addition. *arXiv preprint arXiv:2502.00873*, 2025.

Liu, Z., Kitouni, O., Nolte, N. S., Michaud, E., Tegmark, M., and Williams, M. Towards understanding grokking: An effective theory of representation learning. *Advances in Neural Information Processing Systems*, 35:34651–34663, 2022.

Mallinar, N., Beaglehole, D., Zhu, L., Radhakrishnan, A., Pandit, P., and Belkin, M. Emergence in non-neural models: grokking modular arithmetic via average gradient outer product. *arXiv preprint arXiv:2407.20199*, 2024.

Meng, K., Bau, D., Andonian, A., and Belinkov, Y. Locating and editing factual associations in gpt. *Advances in neural information processing systems*, 35:17359–17372, 2022.

Nanda, N., Chan, L., Lieberum, T., Smith, J., and Steinhardt, J. Progress measures for grokking via mechanistic interpretability. *arXiv preprint arXiv:2301.05217*, 2023.

Su, J., Ahmed, M., Lu, Y., Pan, S., Bo, W., and Liu, Y. Roformer: Enhanced transformer with rotary position embedding. *Neurocomputing*, 568:127063, 2024.

Sun, C.-E., Yan, G., and Weng, T.-W. Thinkedit: Interpretable weight editing to mitigate overly short thinking in reasoning models. *arXiv preprint arXiv:2503.22048*, 2025.

Touvron, H., Martin, L., Stone, K., Albert, P., Almahairi, A., Babaei, Y., Bashlykov, N., Batra, S., Bhargava, P., Bhosale, S., et al. Llama 2: Open foundation and fine-tuned chat models. *arXiv preprint arXiv:2307.09288*, 2023.

Wei, J., Wang, X., Schuurmans, D., Bosma, M., Xia, F., Chi, E., Le, Q. V., Zhou, D., et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Zhao, Z., Liu, Q., Zhou, K., Liu, Z., Shao, Y., Hu, Z., and Huang, B. Activation control for efficiently eliciting long chain-of-thought ability of language models. *arXiv preprint arXiv:2505.17697*, 2025.