NEURAL POTTS MODEL

ABSTRACT

We propose the Neural Potts Model objective as an amortized optimization problem. The objective enables training a single model with shared parameters to explicitly model energy landscapes across multiple protein families. Given a protein sequence as input, the model is trained to predict a pairwise coupling matrix for a Potts model energy function describing the local evolutionary landscape of the sequence. Plausible couplings are predicted for train and validation sequences. A controlled ablation experiment assessing unsupervised contact prediction on sets of related protein families finds a gain from amortization for low-depth MSAs; the result is confirmed on a larger database with broad coverage of protein sequences.

1 INTRODUCTION

Recently, language modeling has emerged as a promising avenue for learning representations of protein sequences that are useful across a variety of protein modeling tasks (Rives et al., 2019; Alley et al., 2019; Rao et al., 2019; Heinzinger et al., 2019). The self supervision objectives from NLP studied for protein sequence modeling use the input sequence directly. In this paper we extend self-supervision to information from a set of evolutionarily related sequences to shape a model to predict a local evolutionary energy landscape for the input sequence.

The standard method for unsupervised contact prediction fits a linear or log linear model to a multiple sequence alignment (MSA) summarizing evolutionary variation around the input sequence (Balakrishnan et al., 2011; Ekeberg et al., 2013; Morcos et al., 2011; Marks et al., 2011; Jones et al., 2011; Kamisetty et al., 2013). To construct the MSA for an input sequence, a similarity query is performed across a large database to identify related sequences, and the returned set of sequences are aligned to each other. Coevolution of a pair of positions in the alignment is associated with a spatial contact between their amino acids in the folded structure (Göbel et al., 1994). Statistical couplings between positions in the MSA can be used to infer protein contacts (Weigt et al., 2009). These couplings can be extracted from a Potts Model trained with pseudolikelihood on the MSA (Balakrishnan et al., 2011; Ekeberg et al., 2013). Contact prediction performance depends on the depth of the MSA and is reduced when few related proteins can be used to fit the model.

We introduce the Neural Potts Model (NPM) objective. The objective is formally expressed as an amortized optimization problem across sequences and MSAs. A Transformer model is trained to predict the parameters of a Potts model energy function defined by the MSA of each input sequence. The hope is that the model will learn to generalize at test time to predict energy functions for sequences not seen during training or for which limited MSA information is available.

We investigate the approach in a controlled ablation experiment on a group of related protein families in PFAM (Bateman et al., 2004). In this artificial setting information can be generalized by the pre-trained shared parameters to improve unsupervised contact prediction on a subset of the MSAs that have been artificially purged to reduce their number of sequences. We then study the model in the setting of a large dataset without artificial purging, training the model on MSAs for UniRef50 (Suzek et al., 2007) sequences. In this setting there is also an improvement on average for low depth MSAs both for sequences in the training set as well as for sequences held-out from training.

2 BACKGROUND

Multiple sequence alignments An MSA is a set of aligned protein sequences that are evolutionarily related. MSAs are constructed by retrieving related sequences from a sequence database and aligning

Figure 1: (a) Standard Potts model requires constructing an MSA and optimizing parameters W. (b) Neural Potts Model (NPM) predicts W in a single feedforward pass from a single sequence.

the returned sequences using a heuristic. An MSA can be viewed as a matrix where each row is a sequence, and columns contain aligned positions after removing insertions and replacing deletions with gap characters.

Potts model The generalized Potts model defines a Gibbs distribution over a protein sequence $(x_1, \ldots, x_L)$ of length L with the negative energy function:

$$-E(\boldsymbol{x}) = \sum_i h_i(x_i) + \sum_{ij} J_{ij}(x_i, x_j) \tag{1}$$

Which defines potentials h_i for each position in the sequence, and couplings J_{ij} for every pair of positions. The parameters of the model are $W = \{h, J\}$ the set of fields and couplings respectively. The distribution $p(\boldsymbol{x}; W)$ is obtained by normalization as $\exp\{-E(\boldsymbol{x}; W)\}/Z(W)$.

Since the normalization constant is intractable, pseudolikelihood is commonly used to fit the parameters (Balakrishnan et al., 2011; Ekeberg et al., 2013). Pseudolikelihood approximates the likelihood of a sequence $\boldsymbol{x}$ as a product of conditional distributions: $\ell_{\mathrm{PL}}(\boldsymbol{x}; W) = -\sum_i \log p(x_i | x_{-i}; W)$. To estimate the Potts model, we take the expectation:

$$\mathcal{L}_{\mathrm{PL}}(W) = \underset{\boldsymbol{x} \sim \mathcal{M}}{\mathbb{E}}[\ell_{\mathrm{PL}}(\boldsymbol{x}; W)] \tag{2}$$

over an MSA $\mathcal{M}$. In practice, we have a finite set of sequences $\hat{\mathcal{M}}$ in the MSA to estimate Eq. (2). L_2 regularization $\rho(W) = \lambda_J \|J\|^2 + \lambda_h \|h\|^2$ is added, and sequences are reweighted to account for redundancy Morcos et al. (2011). We write the regularized finite sample estimator as:

$$\hat{\mathcal{L}}_{\mathrm{PL}}(W) = \frac{1}{M_{\mathrm{eff}}} \sum_{m=1}^{M} w^m [\ell_{\mathrm{PL}}(\boldsymbol{x}^m; W)] + \rho(W) \tag{3}$$

Which sums over all the M sequences of the finite MSA $\hat{\mathcal{M}}$, weighted with w^m summing collectively to M_{eff}. The finite sample estimate of the parameters $\hat{W}^*$ is obtained by minimizing $\hat{\mathcal{L}}_{\mathrm{PL}}$.

Idealized MSA Notice how in Eq. (2), we idealized the MSA $\mathcal{M}$ as a distribution, defined by the protein family. We consider the set of sequences actually retrieved in the MSA $\hat{\mathcal{M}}$ in Eq. (3) as a finite sample from this underlying idealized distribution. For some protein families this sample will contain more information than for others, depending on what sequences are present in the database. We will refer to W^* as a hypothetical idealized estimate of the parameters to explain how the Neural Potts Model can improve on the finite sample estimate $\hat{W}^*$ for low-depth MSAs.

2.1 Amortized Optimization

We review amortized optimization (Shu, 2017), a generalization of amortized variational inference (Kingma & Welling, 2013; Rezende et al., 2014) that uses learning to predict the solution to continuous optimization problems to make the computation more tractable and potentially generalize across problem instances. We are interested in repeatedly solving expensive optimization problems

$$W^*(x) = \underset{W}{\arg\min} \, \mathcal{L}(W; x), \tag{4}$$

where $W \in \mathbb{R}^m$ is the optimization variable, $x \in \mathbb{R}^n$ is the input or conditioning variable to the optimization problem, and $\mathcal{L} : \mathbb{R}^m \times \mathbb{R}^n \to \mathbb{R}$ is the objective. We assume $W^*(x)$ is unique. We consider the setting of having a distribution over optimization problems with inputs $x \sim p(x)$, and the $\arg\min$ of those optimization problems $W^*(x)$.

Amortization uses learning to leverage the shared structure present across the distribution, *e.g.* a solution $W^*(x)$ is likely correlated with another solution $W^*(x')$. Assuming an underlying regularity of the data and loss $\mathcal{L}$, we can imagine learning to predict the outcome of the optimization problem with an expressive model $W_\theta(x)$ such that hopefully $W_\theta \approx W^*$. Modeling and learning $W_\theta(x)$ are the key design decisions when using amortization.

Modeling approaches. In this paper we consider models $W_\theta(x)$ that directly predict the solution to Eq. (4) with a neural network, which follows fully amortized variational inference models and the meta-learning method Mishra et al. (2017). The model can also leverage the objective information $\mathcal{L}(W; x)$ and gradient information $\nabla_W \mathcal{L}(W; x)$, *e.g.* by predicting multiple candidate solutions W and selecting the most optimal one. This is sometimes referred to as semi-amortization or unrolled optimization-based models and is considered in Gregor & LeCun (2010) for sparse coding, Li & Malik (2016); Andrychowicz et al. (2016); Finn et al. (2017) for meta-learning, and Marino et al. (2018); Kim et al. (2018) for posterior optimization.

Learning approaches. There are two main classes of learning approaches for amortization:

$$\arg\min_\theta \mathbb{E}_{p(x)} \mathcal{L}(W_\theta(x); x) \qquad (5) \qquad\qquad \arg\min_\theta \mathbb{E}_{p(x)} \|W_\theta(x) - W^*(x)\|_2^2. \qquad (6)$$

Gradient-based approaches leverage gradient information of the objective $\mathcal{L}$ and optimize Eq. (5) whereas *regression-based* approaches optimize a distance to ground-truth solutions W^*, such as the squared L^2 distance in Eq. (6). Prior work has shown that models trained with these objectives can learn to predict the optimal W^* directly as a function of x. Given enough regularity of the domain, if we observe new (test) samples $x' \sim p(x)$ we expect the model to generalize and predict the solution to the original optimization problem Eq. (4). Gradient-based approaches have the computational advantage of not requiring the expensive ground-truth solution W^* while regression-based approaches are less susceptible to poor local optima in $\mathcal{L}$. Gradient-based approaches are used in variational inference (Kingma & Welling, 2013), style transfer (Chen & Schmidt, 2016), meta learning (Finn et al., 2017; Mishra et al., 2017), and reinforcement learning, *e.g.* for the policy update in model-free actor-critic methods (Sutton & Barto, 2018). Regression-based approaches are more common in control for behavioral cloning and imitation learning (Duriez et al., 2017; Ratliff et al., 2007; Bain & Sammut, 1995).

3   NEURAL POTTS MODEL

In Eq. (2) we introduced the Potts model for a single MSA $\mathcal{M}$ (aligned set of sequences $\boldsymbol{x}$), to optimize $W^* = \{h^*, J^*\} = \arg\min_W \mathbb{E}_{\tilde{\boldsymbol{x}} \sim \mathcal{M}}[\ell_{\text{PL}}(\tilde{\boldsymbol{x}}; W)]$. As per Eq. (5) We will now introduce a neural network to estimate Potts model parameters from a single sequence: $\{h_\theta(\boldsymbol{x}), J_\theta(\boldsymbol{x})\} = W_\theta(\boldsymbol{x})$ with a single forward pass.

We propose minimizing the following objective for the NPM parameters θ, which directly minimizes the Potts model losses in expectation over our data distribution $\boldsymbol{x} \sim \mathcal{D}$ and their MSAs $\tilde{\boldsymbol{x}} \sim \mathcal{M}(\boldsymbol{x})$:

$$\mathcal{L}_{\text{NPM}}(\theta) = \mathbb{E}_{\boldsymbol{x} \sim \mathcal{D}} \left[\mathbb{E}_{\tilde{\boldsymbol{x}} \sim \mathcal{M}(\boldsymbol{x})} \ell_{\text{PL}}(\tilde{\boldsymbol{x}}; W_\theta(\boldsymbol{x})) \right] \qquad (7)$$

To compute the loss for a given sequence $\boldsymbol{x}$ we compute the Potts model parameters $W_\theta(\boldsymbol{x})$, and evaluate its pseudo-likelihood loss ℓ_{PL} on a set of sequences $\tilde{\boldsymbol{x}}$ from the MSA constructed with $\boldsymbol{x}$ as query sequence. This fits exactly in "amortized optimization" in Section 2.1 Eq. (5): we train a model to predict the outcome of a set of highly related optimization problems. One key extension to the described amortized optimization setup is that the model W_θ estimates the Potts Model parameters from only the MSA query sequence $\boldsymbol{x}$ as input rather than the full MSA $\mathcal{M}(\boldsymbol{x})$. Thus, our model must learn to distill the protein energy landscape into its parameters, since it cannot look up related proteins during runtime. A full algorithm is given in Appendix A.

Similar to the original Potts model, we need to add a regularization penalty $\rho(W)$ to the main objective. For a finite sample of N different query sequences $\{\boldsymbol{x}_n\}$, and a sample of aligned sequences $\{\tilde{\boldsymbol{x}}_n^m\}$ from MSA $\hat{\mathcal{M}}(\boldsymbol{x}_n)$, the finite sample regularized loss, i.e. NPM training objective, becomes:

Figure 2: Inductive generalization gain. $\hat{W}^*$ is the standard Potts model, estimated on the finite observed MSA $\hat{\mathcal{M}}$. Though it minimizes the training objective, it does not achieve perfect generalization performance. However the Neural Potts Model $W_\theta(\boldsymbol{x})$ can generalize better than $\hat{W}^*$ through transfer learning from related samples, guided by the inductive bias of the model. We expect this especially when the estimate $\hat{W}^*$ is far from W^*, e.g. on small or biased MSAs.

$$\hat{\mathcal{L}}_{\mathrm{NPM}}(\theta) = \sum_{n=1}^{N} \left[\frac{1}{M_{\mathrm{eff}}(n)} \sum_m w_n^m \left[\ell_{\mathrm{PL}}(\tilde{\boldsymbol{x}}_n^m; W_\theta(\boldsymbol{x}_n)) \right] + \rho(W_\theta(\boldsymbol{x}_n)) \right] \tag{8}$$

Inductive generalization gain   (Fig. 2) is when the Neural Potts Model improves over the individual Potts model. Intuitively this is possible because the individual Potts Models are not perfect estimates (finite/biased MSAs), while the shared parameters of W_θ can transfer information between related protein families and from pre-training with another objective like masked language modeling (MLM).

Let us start with the normal amortized optimization setting, where we expect an amortization gap (Cremer et al., 2018). The amortization gap means that $W_\theta(x)$ will be behind the optimal W^* for the objective $\mathcal{L}$: $\mathcal{L}(W_\theta(x)) > \mathcal{L}(W^*)$. This is closely related to underfitting: the model W_θ is not flexible enough to capture $W^*(x)$. However, recall that in the Potts model setting, there is a finite-sample training objective $\hat{\mathcal{L}}$ (Eq. (8)), with minimizer $\hat{W}^*$. We can expect an amortization gap in the training objective; however this amortization gap can now be advantageous. Even if the amortized solution $W_\theta(\boldsymbol{x})$ is near-optimal on $\hat{\mathcal{L}}$, it can likely find a more generalizable region of the overparametrized domain W by parameter sharing of θ, allowing to transfer information between related instances. The inductive bias of $W_\theta(\boldsymbol{x})$ can allow the neural amortized estimate to generalize better, especially when the finite sample $\hat{\mathcal{M}}$ is poor. This inductive bias depends on the choice of model class for W_θ, its pre-training, as well as the shared structure between the protein families in the dataset. Concretely, when evaluating the generalization or validation loss $\mathcal{L}$[1], we will show that for some samples $\mathcal{L}(W_\theta(\boldsymbol{x})) < \mathcal{L}(\hat{W}^*)$, i.e. there is an inductive generalization gain. This is visually represented in Fig. 2, and Table 1 compares between amortized optimization, NPM, and makes a connection to multi-task learning (Caruana, 1998). Additionally, we could frame NPM as a hypernetwork, a neural network that predicts the weights of second network (in this case the Potts model) as in, *e.g.* Gomez & Schmidhuber (2005); Ha et al. (2016); Bertinetto et al. (2016).

In summary, the goal for the NPM is to "distill" an ensemble of Potts models into a single feedforward model. From a self-supervised learning perspective, rather than supervising the model with the input directly, we use supervision from an energy landscape around the input.

---

[1]Validation loss $\mathcal{L}$ could refer to either the validation pseudo-likelihood loss (estimating the expectation $\mathbb{E}$ with heldout samples), or performance on downstream validation objectives like predicting contact which captures the underlying structure.

Table 1: Comparison between (A) "standard" amortized optimization, (B) Neural Potts Model, and (C) Multi-task learning. From row (A) amortized optimization to (B) Neural Potts Model, a finite-sample training loss is introduced which comes with considerations of generalization and regularization. This is related to multi-task learning, but with a major difference that (B) the solo optimization is over a single tensor W in the Potts model, but (C) a function f_θ in a learning problem. In the amortized/multi-task setting, the distribution over query sequences $\boldsymbol{x}$ in (B) NPM plays the role that different related tasks play in (C) MTL. In the NPM setting (B), W_θ takes $\boldsymbol{x}$ explicitly as argument, versus (C) MTL typically just has a separate output head per task.

	Solo objective Training	Solo objective Generalization	Amortized / Multi-task	Parametrization + model choices
(A) Optim→ Amortized	$\mathcal{L}(s; W)$	$\mathcal{L}(s; W)$ (= Training)	Amortized optim: $\mathbb{E}_{p(s)}\,\mathcal{L}(s; W_\theta(s))$	**Solo**: $W \in \mathbb{R}^n$ **Amor**: $W_\theta : \mathbb{R}^d \to \mathbb{R}^n$ +learner class
(B) Potts → NPM	PLL, finite MSA $\hat{M}$: $\hat{\mathcal{L}}(W) = \sum_m \ell_{\mathrm{PL}}(\tilde{\boldsymbol{x}}^m; W)$	Distr $\mathcal{L}(W) = \mathbb{E}[\ell_{\mathrm{PL}}(\tilde{\boldsymbol{x}}; W)]$ or Contact pred	Neural Potts $\mathbb{E}_{\boldsymbol{x}}[\hat{\mathcal{L}}^M(W_\theta(\boldsymbol{x}))]$	**Solo**: $W \in \mathbb{R}^n$ +regularization **Amor**: $W_\theta : \mathbb{R}^d \to \mathbb{R}^n$ +learner class
(C) ML → MTL (Multi-task learning)	ERM: $\hat{\mathcal{L}}(f_\theta) = \sum_m \ell(f_\theta(x_m), y_m)$	$\mathcal{L}(f_\theta) = \mathbb{E}_{xy} \ell(f_\theta(x), y)$	Multi-task learning: $\sum_{t=1}^T [\hat{\mathcal{L}}^t(f_\theta^t)]$ for T related tasks	**Solo**: $f_\theta : \mathbb{R}^d \to \mathbb{R}$ +regularization +learner class **MTL**: $f_\theta^t : \mathbb{R}^d \to \mathbb{R}$ + param sharing f_θ^t

4 EXPERIMENTS

In Section 4.1 we present results on a small set of related protein domain families from PFAM, where we artificially purge sequences from a few families to study the inductive generalization gain from the shared parameters. In Section 4.2 we present results on a large Transformer trained on MSAs for all of UniRef50.

For the main representation $g_\theta(\boldsymbol{x})$ we use a Transformer model (Vaswani et al., 2017). To compute the four-dimensional pairwise coupling tensor $J_\theta(\boldsymbol{x})$ from sequence embedding $g_\theta(\boldsymbol{x})$ we introduce the multi-head bilinear form (mhbf) in Appendix B. One can think of the multi-head bilinear form as the $L \times L$ self-attention maps of the Transformer's multi-head attention module but without softmax normalization. There are K^2 heads, one for every amino acid pair k, l. We discuss ways to symmetrize and tie the weights of those K^2 heads. We initialize $g_\theta(\boldsymbol{x})$ with a Transformer pre-trained with masked language modeling.

To evaluate Neural Potts Model energy landscapes, we will focus on proteins with structure in the Protein Data Bank (PDB), using the magnitude of the couplings after APC correction to rank contacts. The protocol is described in Appendix C.2.

4.1 PFAM P-LOOP-NTPASE CLAN

To study generalization in a controlled setting, we investigate a small set of structurally-related MSAs from the PFAM domain family database (Finn et al., 2016). We expect that on a collection of related MSAs, information could be generalized to improve performance on low-depth MSAs. We select all 198 families in the P-loop NTPase clan. Families within a PFAM clan are linked by a distant evolutionary relationship, giving them related but not trivially-similar structure. We obtain contact maps for the sequences in each of the families where a structure is available in the PDB. At test time we input the sequence and compare the generated couplings under the model to the corresponding structure.

We perform the experiment using a five-fold cross-evaluation scheme, in which we partition the 198 families into five equally-sized buckets of 40 families each. As in standard cross-validation, each bucket will eventually serve as an evaluation set. However, we do not remove the evaluation bucket,

Figure 3: Contact prediction precision on PFAM families at different levels of depth reduction. Columns show (from left to right) short, medium and long-range precision for top-L threshold. Across the metrics, NPM outperforms the standard independent Potts model trained on the shallowest MSAs, but the effect is most pronounced for long range.

but artificially reduce the number of sequences in the MSAs in the evaluation bucket to a small fixed depth. MSAs in the remaining buckets remain unaltered. The goal of this setup is to check the model's ability to infer contacts on artificially limited sets of sequences. Both NPM and the baseline are fit on the reduced set of sequences. Note that while the baseline Potts model uses the reduced MSA of the target directly, NPM is trained on the reduced MSA but evaluated using only the target sequence as input. We train a separate NPM on each of the five cross-evaluation rounds, evaluate on the structures corresponding to the bucket with reduced MSAs, and show averages and standard deviations across rounds. Further details are provided for model training in Appendix C.1 and on the PFAM dataset in Appendix C.3.

Figure 3 shows the resulting contact prediction performance. We initialize a 12-layer Transformer from MLM pre-training. Because of the small dataset size, we keep the weights of the base Transformer g_θ frozen and only finetune the final layers (the multi-head bilinear form, convolutional layers, and single-site output head). As a function of increasing MSA depth, contact precision improves for both NPM and independent Potts models. For the shallowest MSAs, NPM has a higher precision relative to the independent Potts models. The advantage at low MSA depth is most pronounced for long range contacts, outperforming independent Potts models up to MSA depth 1000. These experiments suggest NPM is able to realize an inductive gain by sharing parameters in the pre-trained base model as well as the fine-tuned final layers and output head.

4.2 UNIREF50

For a realistic evaluation setting for the NPM approach, we start from the UniRef50 (2018-03) database (Suzek et al., 2007), which provides full coverage of sequence space, clustered at 50% identity. We randomly partition the clusters in 90% train and 10% heldout sets. For each of the sequences in UniRef50 we compute the MSA. During training, we iterate over all sequences and their MSAs on every epoch, and subsample to M=30 sequences per MSA. For contact prediction performance evaluation, the train and heldout split is preserved from NPM training. More details are found in Appendix C.4 (data), Appendix C.1 (model and training).

Figure 4 shows a comparison between the NPM predictions and individual Potts models fit from the MSA with CCMpred (Seemayer et al., 2014). The Neural Potts Model is given only the query sequence as input. On top-L/5 long range precision, NPM has better precision than independent Potts models for 22.3% of train and 22.7% of heldout proteins. We visualize in Fig. 5 example proteins with low MSA-depth where NPM does better than the individual Potts model. For shallow MSAs, the average performance of NPM is higher than the Potts model, suggesting an inductive generalization gain in this regime.

Figure 4: UniRef50: contact prediction precisions (higher is better) on medium range (left), long range (middle), binned by MSA depth M_{eff}. Top row: sequences from the train set; bottom row: sequences from the held-out set. For shallow MSAs, average performance of NPM is higher than the independent Potts model. Right: scatter plot comparing long range precision from NPM vs independent Potts model, each point is a protein.

Figure 5: Examples where NPM does well compared to the independent Potts model fit directly on the MSA. NPM top-L/5_LR contact prediction (lower diagonal, red) compared to the independent Potts model prediction (upper diagonal, blue). All ground truth contacts are indicated in black. True and false hits are indicated with dots and crosses, respectively.

5 DISCUSSION

This paper explores how a protein sequence model can be trained to produce a local energy landscape that is defined by a set of evolutionarily related sequences for each input. The training objective is cast as an amortized optimization problem. By learning to output the parameters for a Potts model energy function across many sequences, the model may learn to generalize across the sequences. Extending self-supervision objectives for sequence modeling of proteins to richer sources of information that can be constructed from the underlying organization of the sequence space is a direction with many further possibilities.

We also formally and empirically investigate the generalization capability of models trained through amortized optimization. We consider the setting of training independent Potts models on the MSA of each sequence, in comparison with training a single model using the amortized objective to predict Potts model parameters for many inputs. Empirically the amortized objective appears to provide an inductive gain when few related sequences are available in the MSA for training the independent Potts model.

REFERENCES

Ethan C Alley, Grigory Khimulya, Surojit Biswas, Mohammed AlQuraishi, and George M Church. Unified rational protein engineering with sequence-only deep representation learning. *bioRxiv*, pp. 589333, 2019.

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, and Nando de Freitas. Learning to learn by gradient descent by gradient descent. *arXiv preprint arXiv:1606.04474*, 2016.

Michael Bain and Claude Sammut. A framework for behavioural cloning. In *Machine Intelligence 15*, pp. 103–129, 1995.

Sivaraman Balakrishnan, Hetunandan Kamisetty, Jaime G Carbonell, Su-In Lee, and Christopher James Langmead. Learning generative models for protein fold families. *Proteins: Structure, Function, and Bioinformatics*, 79(4):1061–1078, 2011.

Alex Bateman, Lachlan Coin, Richard Durbin, Robert D Finn, Volker Hollich, Sam Griffiths-Jones, Ajay Khanna, Mhairi Marshall, Simon Moxon, Erik LL Sonnhammer, et al. The pfam protein families database. *Nucleic acids research*, 32(suppl_1):D138–D141, 2004.

Luca Bertinetto, João F Henriques, Jack Valmadre, Philip Torr, and Andrea Vedaldi. Learning feed-forward one-shot learners. In *Advances in neural information processing systems*, pp. 523–531, 2016.

Rich Caruana. Multitask learning. In *Learning to learn*, pp. 95–133. Springer, 1998.

Tian Qi Chen and Mark Schmidt. Fast patch-based style transfer of arbitrary style. *arXiv preprint arXiv:1612.04337*, 2016.

Chris Cremer, Xuechen Li, and David Duvenaud. Inference suboptimality in variational autoencoders. *arXiv:1801.03558*, 2018.

Stanley D Dunn, Lindi M Wahl, and Gregory B Gloor. Mutual information without the influence of phylogeny or entropy dramatically improves residue contact prediction. *Bioinformatics*, 24(3):333–340, 2008.

Thomas Duriez, Steven L Brunton, and Bernd R Noack. *Machine learning control-taming nonlinear dynamics and turbulence*, volume 116. Springer, 2017.

Magnus Ekeberg, Cecilia Lövkvist, Yueheng Lan, Martin Weigt, and Erik Aurell. Improved contact prediction in proteins: using pseudolikelihoods to infer potts models. *Physical Review E*, 87(1):012707, 2013.

Chelsea Finn, Pieter Abbeel, and Sergey Levine. Model-agnostic meta-learning for fast adaptation of deep networks. *arXiv preprint arXiv:1703.03400*, 2017.

Robert D Finn, Penelope Coggill, Ruth Y Eberhardt, Sean R Eddy, Jaina Mistry, Alex L Mitchell, Simon C Potter, Marco Punta, Matloob Qureshi, Amaia Sangrador-Vegas, et al. The pfam protein families database: towards a more sustainable future. *Nucleic acids research*, 44(D1):D279–D285, 2016.

Ulrike Göbel, Chris Sander, Reinhard Schneider, and Alfonso Valencia. Correlated mutations and residue contacts in proteins. *Proteins: Structure, Function, and Bioinformatics*, 18(4):309–317, 1994.

Faustino Gomez and Jürgen Schmidhuber. Evolving modular fast-weight networks for control. In *International Conference on Artificial Neural Networks*, pp. 383–389. Springer, 2005.

Karol Gregor and Yann LeCun. Learning fast approximations of sparse coding. In *Proceedings of the 27th International Conference on Machine Learning (ICML-10)*, pp. 399–406, 2010.

David Ha, Andrew Dai, and Quoc V Le. Hypernetworks. *arXiv:1609.09106*, 2016.

Michael Heinzinger, Ahmed Elnaggar, Yu Wang, Christian Dallago, Dmitrii Nechaev, Florian Matthes, and Burkhard Rost. Modeling aspects of the language of life through transfer-learning protein sequences. *BMC bioinformatics*, 20(1):723, 2019.

David T Jones, Daniel WA Buchan, Domenico Cozzetto, and Massimiliano Pontil. Psicov: precise structural contact prediction using sparse inverse covariance estimation on large multiple sequence alignments. *Bioinformatics*, 28(2):184–190, 2011.

Hetunandan Kamisetty, Sergey Ovchinnikov, and David Baker. Assessing the utility of coevolution-based residue–residue contact predictions in a sequence- and structure-rich era. *Proceedings of the National Academy of Sciences*, 110(39):15674–15679, 2013. ISSN 0027-8424. doi: 10.1073/pnas.1314045110. URL https://www.pnas.org/content/110/39/15674.

Yoon Kim, Sam Wiseman, Andrew C Miller, David Sontag, and Alexander M Rush. Semi-amortized variational autoencoders. *arXiv:1802.02550*, 2018.

Diederik P Kingma and Max Welling. Auto-encoding variational bayes. *ICLR*, 2013.

Ke Li and Jitendra Malik. Learning to optimize. *arXiv:1606.01885*, 2016.

Joseph Marino, Yisong Yue, and Stephan Mandt. Iterative amortized inference. *arXiv:1807.09356*, 2018.

Debora S Marks, Lucy J Colwell, Robert Sheridan, Thomas A Hopf, Andrea Pagnani, Riccardo Zecchina, and Chris Sander. Protein 3d structure computed from evolutionary sequence variation. *PloS one*, 6(12), 2011.

Nikhil Mishra, Mostafa Rohaninejad, Xi Chen, and Pieter Abbeel. A simple neural attentive meta-learner. *arXiv:1707.03141*, 2017.

Faruck Morcos, Andrea Pagnani, Bryan Lunt, Arianna Bertolino, Debora S Marks, Chris Sander, Riccardo Zecchina, José N Onuchic, Terence Hwa, and Martin Weigt. Direct-coupling analysis of residue coevolution captures native contacts across many protein families. *Proceedings of the National Academy of Sciences*, 108 (49):E1293–E1301, 2011.

Roshan Rao, Nicholas Bhattacharya, Neil Thomas, Yan Duan, Xi Chen, John Canny, Pieter Abbeel, and Yun S Song. Evaluating protein transfer learning with tape. *arXiv:1906.08230*, 2019.

Nathan Ratliff, J Andrew Bagnell, and Siddhartha S Srinivasa. Imitation learning for locomotion and manipulation. In *2007 7th IEEE-RAS International Conference on Humanoid Robots*, pp. 392–397. IEEE, 2007.

Danilo J Rezende, Shakir Mohamed, and Daan Wierstra. Stochastic backpropagation and approximate inference in deep generative models. In *Proceedings of the 31st International Conference on Machine Learning (ICML-14)*, pp. 1278–1286, 2014.

Alexander Rives, Joshua Meier, Tom Sercu, Siddharth Goyal, Zeming Lin, Demi Guo, Myle Ott, C Lawrence Zitnick, Jerry Ma, and Rob Fergus. Biological structure and function emerge from scaling unsupervised learning to 250 million protein sequences. *bioRxiv*, pp. 622803, 2019. URL https://doi.org/10.1101/622803.

Stefan Seemayer, Markus Gruber, and Johannes Söding. Ccmpred—fast and precise prediction of protein residue–residue contacts from correlated mutations. *Bioinformatics*, 30(21):3128–3130, 2014.

Rui Shu. Amortized optimization. *http://ruishu.io/2017/11/07/amortized-optimization*, 2017. Retrieved 2020-09-22.

Martin Steinegger, Markus Meier, Milot Mirdita, Harald Vöhringer, Stephan J Haunsberger, and Johannes Söding. Hh-suite3 for fast remote homology detection and deep protein annotation. *BMC bioinformatics*, 20 (1):1–15, 2019.

Richard S Sutton and Andrew G Barto. *Reinforcement learning: An introduction*. MIT press, 2018.

Baris E. Suzek, Hongzhan Huang, Peter McGarvey, Raja Mazumder, and Cathy H. Wu. UniRef: Comprehensive and non-redundant UniProt reference clusters. *Bioinformatics*, 23(10):1282–1288, 5 2007. ISSN 13674803. doi: 10.1093/bioinformatics/btm098. URL http://www.uniprot.org. UniRef50 database licensed under (CC BY 4.0).

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention is all you need. *NeurIPS*, 2017.

Martin Weigt, Robert A White, Hendrik Szurmant, James A Hoch, and Terence Hwa. Identification of direct residue contacts in protein–protein interaction by message passing. *Proceedings of the National Academy of Sciences*, 106(1):67–72, 2009.

Appendix

A LEARNING THE NEURAL POTTS MODEL

Algorithm 1 Learning the Neural Potts Model

Initialize the amortized model W_θ
while unconverged **do**
    Sample N sequences $\boldsymbol{x}_n \sim \mathcal{D}$ and M MSA sequences $\tilde{\boldsymbol{x}}_n^m \sim \mathcal{M}(\boldsymbol{x}_n)$
    grad_update$(\theta, \nabla_\theta \hat{\mathcal{L}}_{\mathrm{NPM}}(\theta; \{\boldsymbol{x}_n\}, \{\tilde{\boldsymbol{x}}_n^m\}))$ ▷ Optimize the regularized loss in Eq. (8)
end while

B MODEL ARCHITECTURE: MULTI-HEAD BILINEAR FORM FOR PAIRWISE COUPLINGS

In this Section, we describe the model architecture to compute a four-dimensional pairwise coupling tensor $J_\theta(\boldsymbol{x})$ from sequence embedding $g_\theta(\boldsymbol{x})$.

B.1 MULTI-HEAD BILINEAR FORM

We write sequence length L and amino acid vocabulary $K = 21$. The single site potentials $h \in \mathbb{R}^{L \times K}$, and the pairwise couplings are a four-dimensional tensor: $J \in \mathbb{R}^{L \times K \times L \times K}$ indexed as $J_{ij}(k, l)$.

We start with a sequence-level model to produce the embedding e of the sequence (typically final hidden layer output): $e = g_\theta(\boldsymbol{x}) \in \mathbb{R}^{L \times d}$. The estimator for single-site potential $h_\theta(\boldsymbol{x})$ is a linear projection layer on the embedding; $h_\theta(\boldsymbol{x}) = g_\theta(\boldsymbol{x}) P^h$ with $P^h \in \mathbb{R}^{d \times K}$. Now we discuss how to parametrize the estimator $J_\theta(\boldsymbol{x}) \in \mathbb{R}^{L \times K \times L \times K}$.

We introduce a *multi-head bilinear form* (mhbf) on the embedding e; i.e. for every pair k, l of amino acids we have a bilinear form, parametrized with a learned interaction matrix $B^{kl} \in \mathbb{R}^{d \times d}$ connecting the hidden states at positions $e_i, e_j \in \mathbb{R}^{1 \times d}$. So we compute the K^2 bilinear forms for amino acid pairs (k, l) between $L \times L$ position pairs (i, j): $J_{ij}(k, l) = e_i B^{kl} e_j^\top$. We use a low-rank decomposition $B^{kl} = U^{kl} V^{kl\top}$ with both $U^{kl}, V^{kl} \in \mathbb{R}^{d \times d'}$, so the bilinear form becomes the inner product in the lower-dimensional space with d' the projection dimension: $(e_i U^{kl})(e_j V^{kl})^\top$. We can interpret this as an inner product of embeddings i, j after linear projection to a space specific to amino acid pair (k, l). This low-rank multi-head bilinear form is similar to the multi-head attention mechanism introduced in Vaswani et al. (2017), but without softmax normalization.

Notation-wise, our parameters θ include the parameters of the transformer that produces the embedding and the components of the interaction matrix $\{U^{kl}, V^{kl}\}$.

Tied projection One way to reduce the number of parameters in the multi-head bilinear form, is for the low-rank decompositions of the K^2 heads B^{kl} to share their decomposition per k, l. Instead we can *share/tie* the projection matrices between amino acids k, l: $U^{kl} = U^k$ and $V^{kl} = V^l$, such that head $B^{kl} = U^k V^{l\top}$. Note that the dot product in this case is after a linear projection specific to single-site amino acid k and l separately; $J_{ij}(k, l) = e_i B^{kl} e_j^\top = (e_i U^k)(e_j V^l)^\top$.

Symmetry We can or should parametrize the estimator of J to be symmetrical against interchanging both i,j and k,l: $J_{ij}(k, l) = J_{ji}(l, k)$, i.e. no difference between the order of considering interaction between AA k at position i with AA l at position j. This does not mean symmetry of each interaction matrix! We ask that

$$J_{ij}(k, l) = e_i B^{kl} e_j^\top = e_j B^{lk} e_i^\top = e_i B^{lk\top} e_j$$

The second equality is the symmetry, the last equality by transposing the bilinear form. From $B^{kl} = B^{lk\top}$ it follows that

$$U^{kl} V^{kl\top} = V^{lk} U^{lk\top}$$
$$U^{kl} = V^{lk}$$

The last equality the obvious choice. In the tied parametrization, this simply becomes $U^{kl} = U^k = V^k = V^{lk}$ such that $W_{kl} = U^k U^{l\top}$. Once again, note that the dot product now becomes $J_{ij}(k,l) = (e_i U^k)(e_j U^l)^\top$. We present a Tensor decomposition perspective on this multi-head bilinear form in Appendix B.2.

Convolutional layers after multi-head bilinear form   As an extended model architecture, we consider having convolutional layers after the multi-head bilinear form (only used for the PFAM experiments). In this case, rather than having K^2 heads B^{kl}, we now have an arbitrary number of heads F which will become the feature maps to consecutive convolutional layers: $B^F = U^F V^{F\top}$. We add 1×1 convolutional layers having also F hidden feature maps, and finally K^2 output feature maps. Weight tying and symmetry considerations of the mhbf do not apply in this model variation.

B.2   Tensor decomposition view on multi-head bilinear form

We can see the multi-head bilinear form as a tensor decomposition of J, for which we will use Einstein notation to indicate that any pair of indices appearing both in subscript and superscript are summed over their range. Let us write the tensor collecting the U^{kl} matrices as $\mathcal{U} \in \mathbb{R}^{K \times K \times d \times d'}$; and index into $\mathcal{U}$ in the same notation as for U: $\mathcal{U}^{kl}_{\alpha r} = U^{kl}_{\alpha r}$. With $\alpha, \beta \in [1\ldots d]$, $r \in [1\ldots d']$ The same for $\mathcal{V}$. Now the J estimate in the full untied asymmetric case, written as tensor, becomes

$$J^{kl}_{ij} = e^\alpha_i \, \mathcal{U}^{kl}_{\alpha r} \, \mathcal{V}^{klr}_\beta \, e^\beta_j$$

or the symmetric ($\mathcal{U}^{kl}_{\alpha r} = \mathcal{V}^{lk}_{\alpha r}$) and tied ($\mathcal{U} \in \mathbb{R}^{K \times d \times d'}$) version:

$$J^{kl}_{ij} = e^\alpha_i \, \mathcal{U}^k_{\alpha r} \mathcal{U}^{lr}_\beta \, e^\beta_j$$

Note that the $\mathcal{U}, \mathcal{V}$ are shared across proteins, while the embeddings $e = g_\theta(\boldsymbol{\sigma})$ are specific per protein, based on a high-capacity sequence level model.

C   Experiment Details

C.1   Training details

		PFAM	**UniRef50**
	Parameters	111M (frozen: 26M trained)	519M
	Number of layers	12	32
Model details	Embed dim	768	1024
	Attention heads	12	16
	mhbf U, V projection dimension	128	512
	mhbf number of heads	128	$K^2 = 441$
	Conv after mhbf	1×1 (3 layers)	No
	mhbf tied	N/A	No
MLM pre-training (UniRef50)	# of epochs	21	50
	# of gradient updates	175k	449k
	Learning rate	4e-4	3e-5
NPM training	Number of updates	10k	135k
	Adam learning rate	1e-5 / 1e-4 (frozen)	3e-5
	$\rho(W)$ multipliers λ_J, λ_h	1e-3, 1e-2	1e-3, 1e-2
	M (samples per MSA)	100	30
	Batch size (# seqs)	64	2048
	Max sequence length	512	512
	Base model frozen	Yes/No	No

Table 2: Hyperparameters

We summarize the precise model architecture and optimization settings in Table 2. During NPM pseudo-likelihood loss evaluation the MSAs are downsampled to M sequences (M=100 or 30, see Table 2). Each sequence is selected with probability according to its sequence weight w^m. Additionally, in the PFAM experiments the loss term for family n in Eq. (8) is upweighted with a factor $\sqrt{M_{\text{eff}}(n)}$. In both the PFAM and Uniref experiments, we enforce a max sequence length of 512 via random contiguous crops of positions.

C.2 VALIDATION DETAILS

To compute precisions, we convert the pairwise couplings $J \in \mathbb{R}^{L \times K \times L \times K}$ to an $L \times L$ pairwise coupling score by (1) zeroing all positions in J corresponding to gap characters, (2) computing the magnitude via Frobenius norm over the $K \times K$ matrix J_{ij} for every pair of positions i, j, (3) applying the Average Product Correction (Dunn et al., 2008), and (4) zeroing the diagonal of the final matrix. True contacts are defined as pairwise distances less than or equal to 8 Angstroms. Precision is calculated as the true positive fraction of the top L, $\lfloor L/2 \rfloor$, or $\lfloor L/5 \rfloor$ predicted contacts, at sequence separations s of short ($6 \leq s < 12$), medium ($12 \leq s < 24$), and long ($24 < s$) ranges.

C.3 PFAM TRAINING DATA AND SETUP

Data Selection. For the PFAM experiments in 4.1, we retrieved the PFAM database (Finn et al., 2016) version 28.0. All MSAs in the P-loop NTPase clan, (n=198) clan were parsed from the multiple alignment file Pfam-A.full. PFAM clans are collections of evolutionarily related families with similar, but not trivially-similar structure. We choose the P-loop-NTPase clan, as we found that the largest clan in PFAM, HTH, had MSAs which yielded poor long-range contact predictions on the Independent Potts baseline.

For contact precision evaluation, we use the `pdbmap` file included in the PFAM28.0 release. This file contains associations between proteins with known structure in PFAM families and PDB files.

Dataset splits. Most MSAs in the P-loop NTPase clan are deep (>1000 sequences). As described in Section 4.1, we partititon the dataset into 5 equally-sized buckets of MSAs, and purge down the number of sequences in the fifth MSA bucket, similar to holding out a bucket during cross-validation. Like cross-validation, we rotate over which bucket is purged, train an independent NPM on each rotation, and plot results as an average with single standard deviation error bars.

MSA Processing. We load the first 10,000 sequences from each PFAM MSA in the P-loop NTPase clan. Then, all MSAs in our setup go through a common set of transforms. HHfilter from the HHSuite3 (Steinegger et al., 2019) toolset is applied to each MSA, with default settings (we find that filtering improves contact prediction accuracy of the baseline, Independent Potts). At training time, we randomly select a sequence in an MSA as input sequence x, and drop all MSA columns in positions where that sequence has gaps. To ensure sequences stay constrained in length, if the remaining MSA has more than 512 positions, we take a random contiguous crop of columns. Finally, we randomly subsample the MSA down to 100 sequences as NPM target sequences $\tilde{x}$.

C.4 UNIREF50 TRAINING DATA AND SETUP

For the experiments in Section 4.2, we retrieved the UniRef-50 (Suzek et al., 2007) database dated 2018-03. The UniRef50 clusters were partitioned randomly in 90% train and 10% heldout sets. For all sequences, we construct MSAs using HHblits (Steinegger et al., 2019) against the Uni-Clust30_2017_10 database. HHblits was performed for 3 iterations, with an e-value of 0.001.

It's important to note that given this MSA generation procedure, validation sequences can be included in MSAs of train sequences. However, we are guaranteed that validation sequences are not trained on as input to NPM.

Contact precision targets In order to show out-of-distribution generalization on contacts, we are motivated to create a dataset where the training and validation set splits also respect the pretraining data splits. First we query PDB to obtain a list of all protein structures submitted with a resolution of at most 2.5 Å, a length greater than 40 residues, and submitted before May 1, 2020.

Figure 6: A random sample of 1000 MSAs from 1000 sequences in Uniref50 were analyzed. The graph shows cumulative density plots with MSA depth in log-scale on the x axis, for different coverage requirements specified by a call to HHfilter, applied to each MSA. The percentage of MSAs with depth < 100 spans from 30% - 55%, depending on the desired coverage parameter. The prevalence of these shallow MSAs in this comprehensive dataset, highlights the value of methods that work well in this low-depth setting.

To be sure that we respect pre-training splits, we search each PDB sequence against UniRef50 using the MMSeqs2 software suite. We run the `easy-search` routine with a minimum sequence identity of 50% at 80% coverage - using the target coverage mode, meaning that 80% of the UniRef50 sequence must be more than 50% identical to be counted as a hit. This labels each sequence in the structural dataset with a list of UniRef50 hits. A protein structure is included in the training set only if the list of hits do not include any sequences in the UniRef50 validation set. Similarly, a structure is included in the validation set if the list of hits do not include any sequences in the training set. If we detect hits in both UniRef50 training and validation sets, these structures are discarded in the resulting dataset. We then cluster the datasets at 50% sequence similarity, resulting in a dataset of 11040 training structures and 211 validation structures.

To predict contact on these structures, NPM only needs the corresponding primary sequence. For the standard Potts model baseline, we construct an MSA for the structures by searching Uniclust30 (2017) with HHblits with n=3 iterations and the default E-value cutoff 0.001.