PROVABLY ROBUST ADVERSARIAL EXAMPLES

ABSTRACT

We introduce the concept of provably robust adversarial examples – connected input regions constructed from standard adversarial examples which are guaranteed to be provably robust to a set of perturbations (such as changes in pixel intensity and geometric transformations). We present a novel method for generating these regions in a scalable manner which works by iteratively refining the region initially obtained via sampling until certification with state-of-the-art methods is achieved. At each step, a novel optimization procedure is applied to maximize the region's volume under the constraint that the resulting convex relaxation implies a chosen bound on the certification objective. Our experimental evaluation shows the effectiveness of the method: it successfully finds large provably robust regions including ones containing $\approx 10^{573}$ adversarial examples for pixel intensity and $\approx 10^{599}$ for geometric transformations. We verify empirically that our robust adversarial examples are significantly more effective against state-of-the-art defenses based on randomized smoothing than the individual attacks used to construct the regions.

1 INTRODUCTION

Deep neural networks (DNNs) are vulnerable to adversarial attacks: small input perturbations that cause misclassification (Szegedy et al., 2013). This has caused an increased interest in investigating powerful attacks (Goodfellow et al., 2015; Carlini & Wagner, 2017; Madry et al., 2018; Andriushchenko et al., 2019; Zheng et al., 2019; Wang et al., 2019; Croce & Hein, 2019; Tramèr et al., 2020). An important limitation of existing attack methods is that they only produce a single *concrete* adversarial example and their effect can often be mitigated with existing defenses (Madry et al., 2018; Hu et al., 2019; Sen et al., 2020; Xiao et al., 2020; Pang et al., 2020; Lécuyer et al., 2019; Cohen et al., 2019; Salman et al., 2019; Fischer et al., 2020; Li et al., 2020). The effectiveness of these attacks can be improved by *robustifying* them: to consolidate the individual examples to produce a large symbolic region guaranteed to only contain adversarial examples.

This Work: Provably Robust Adversarial Examples   We present the concept of a *provably robust adversarial example* – input region capturing a very large set (e.g., $> 10^{100}$) of points guaranteed to be adversarial. We then introduce a novel algorithm for generating such regions and apply it to the setting of pixel intensity changes and geometric transformations. Our work relates to prior approaches on generating robust adversarial examples (Athalye et al., 2018; Qin et al., 2019) but differs in a crucial point: our regions are *guaranteed* to be adversarial while prior approaches are empirical and offer no such guarantees.

Main Contributions Our key contributions are:

- The concept of a *provably robust adversarial example* – a connected input region capturing a very large set of points, generated by a set of perturbations, guaranteed to be adversarial.

- A novel scalable method for synthesizing provably robust adversarial examples, based on iterative refinement and certification techniques.

- A thorough evaluation of our method demonstrating it can generate provable regions containing $\approx 10^{573}$ concrete adversarial points for pixel intensity changes, in ≈ 2 minutes, and $\approx 10^{599}$ concrete points for geometric transformations, in ≈ 20 minutes, on a challenging CIFAR10 network. We also demonstrate that our robust adversarial examples are significantly more effective against state-of-the-art defenses based on randomized smoothing than the individual attacks used to construct the regions.

2 BACKGROUND

We now discuss the background necessary for the remainder of the paper. We consider a neural network $f \colon \mathbb{R}^{n_0} \to \mathbb{R}^{n_l}$ with l layers, n_0 input neurons and n_l output classes. The network classifies an input x to class $y(x)$ with the largest corresponding output value, i.e., $y(x) = \operatorname{argmax}_i [f(x)]_i$. Note for brevity we will omit the argument to y when it is clear from the context.

2.1 NEURAL NETWORK CERTIFICATION

In this work, we rely on state-of-the-art neural network certification methods based on convex relaxations to prove that the adversarial examples produced by our algorithm are robust. These certification methods take a convex input region $\mathcal{I} \subset \mathbb{R}^{n_0}$ and prove that every point in $\mathcal{I}$ is classified as target label y_t by f. They propagate the set $\mathcal{I}$ through the layers of the network, producing a convex region that covers all possible values of output neurons (Gehr et al., 2018). Robustness follows by proving that, for all combinations of output neuron values in this region, the output neuron corresponding to class y_t has a larger value than the one corresponding to any other class $y \neq y_t$.

Commonly, one proves this property by computing a function $L_y \colon \mathbb{R}^{n_0} \to \mathbb{R}$ for each label $y \neq y_t$, such that, for all $x \in \mathcal{I}$, we have $L_y(x) \leq [f(x)]_{y_t} - [f(x)]_y$. For each L_y, one computes $\min_{x \in \mathcal{I}} L_y(x)$ to obtain a global lower bound that is true for all $x \in \mathcal{I}$. If we obtain positive bounds for all $y \neq y_t$, robustness is proven. To simplify notation, we will say that the *certification objective* $L(x)$ is the function $L_y(x)$ with the smallest minimum value on $\mathcal{I}$. We will call its corresponding minimum value the *certification error*. We require $L_y(x)$ to be a linear function of x. This requirement is consistent with many popular certification algorithms based on convex relaxation, such as CROWN (Zhang et al., 2018), DeepZ (Singh et al., 2018a), and DeepPoly (Singh et al., 2019). Without loss of generality, for the rest of this paper, we will treat DeepPoly as our preferred certification method.

2.2 GEOMETRIC CERTIFICATION

While DeepPoly is general enough to prove robustness to many different types of pixel intensity transformations, it does not handle geometric transformations directly. To prove the robustness of our examples to geometric transformations, we rely on DeepG (Balunović et al., 2019) which, given a region of geometric transformation parameters, creates overapproximation of the region of input images to the network. DeepG then leverages DeepPoly to certify the input image region. When generating our geometric robust examples, we work directly in the geometric parameter space and, thus, our input region $\mathcal{I}$ and the inputs to our certification objective $L(x)$ are in also in geometric space. Despite this change, for most of this work the algorithms do not distinguish between certification with DeepPoly and DeepG, so in the rest of the paper we will assume the certification is done using DeepPoly unless otherwise stated.

2.3 RANDOMIZED SMOOTHING

Randomized smoothing (Lécuyer et al., 2019; Cohen et al., 2019) is a provable defense mechanism against adversarial attacks. For a chosen standard deviation σ and neural network f as defined above, randomized smoothing computes a smoothed classifier g based on f, such that $g(x) = \operatorname{argmax}_c \mathbb{P}(y(x + \epsilon) = c)$ with random Gaussian noise $\epsilon \sim \mathcal{N}(0, \sigma^2 I)$. This construction of g allows Cohen et al. (2019) to introduce the procedure CERTIFY that provides probabilistic guarantees on the robustness of g around a point x:

Proposition 1. *(From Cohen et al. (2019)) With probability at least $1 - \alpha$ over the randomness in* CERTIFY, *if* CERTIFY *returns a class y and a radius R (i.e does not abstain), then g predicts y within radius R around x: $g(x + \delta) = y$, for all $\|\delta\|_2 < R$.*

We define adversarial attacks on smoothed classifiers as follows:

Definition 1 (Adversarial attack on smoothed classifiers)**.** *We call $\tilde{x} \in \mathbb{R}^{n_0}$ an adversarial attack on the smoothed classifier g at the point $x \in \mathbb{R}^{n_0}$ if $\|\tilde{x} - x\|_2 < R'$ and $g(x) \neq g(\tilde{x})$ for some σ and α and $R' \in \mathbb{R}^{>0}$.*

Figure 1: Overview of our algorithm. The green triangle denoted $\mathcal{T}$ represents the ground truth adversarial region and the repred crosses represent the attacks obtained by α. The dashed blue and violet dotted rectangles denoted $\mathcal{O}$ and $\mathcal{U}$, represent the fitted overapproximation and underapproximation boxes, respectively. The solid black lines represent hyperplanes generated by the verification procedure, while their dash-dotted counterparts represent the hyperplanes after bias-adjustment. The arrows going out of the hyperplanes represent the direction of their corresponding half-spaces.

In this work we will consider adversarial attacks $\tilde{x}$ on the original image x with R' the smallest such that f is attackable by PGD (Kurakin et al., 2016) on x. Intuitively, for this R' the smoothed classifier is hardest to attack. We then define the strength of such an attack as follows:

Definition 2 (Strength of adversarial attack on smoothed classifiers). *We measure the strength of an attack $\tilde{x}$ in terms of R_{adv}– the radius around $\tilde{x}$, whose L_2 ball is certified as adversarial by g using* CERTIFY *for a chosen σ and α.*

Intuitively, this definition states that for points $\tilde{x}$ for which R_{adv} is bigger, the smoothed classifier is less confident about predicting the correct class, since more adversarial examples are sampled in this region and therefore, the attack on g is stronger. We use this measure in Section 5 to compare the effectiveness of our adversarial examples to examples obtained by PGD on g.

3 OVERVIEW

Existing methods for generating robust adversarial examples focus on achieving empirical robustness (Qin et al., 2019; Athalye et al., 2018). In contrast, we consider *provably* robust adversarial examples, defined below:

Definition 3 (Provably Robust Adversarial Example). *We define provably robust adversarial example to be any large connected neural network input region, defined by a set of perturbations of an image, that can be formally proven to only contain adversarial examples.*

In this section, we outline how we generate such regions. The technical details are given in Section 4.

To generate a provably robust adversarial example, ideally, we would like to directly maximize the input region's size, under the constraint that it only contains adversarial examples. This leads to multiple challenges: Small changes of the parametrization of the input region (e.g., as a hyperbox) can lead to large changes of the certification objective, necessitating a small learning rate for optimization algorithms based on gradient descent. At the same time, the optimizer would have to solve a full forward verification problem in each optimization step, which is slow and impractical. Additionally, according to Balunovic & Vechev (2020), bad initialization of the robust region might further cause convergence to local minima, resulting in small robust regions. We now provide an overview of how we generate robust adversarial regions while alleviating these problems.

Our method for generating robust examples in the shape of a hyperbox is shown in Figure 1 and assumes an algorithm α that generates adversarial examples and a neural network verifier $\mathbb{V}$. We require $\mathbb{V}$ to provide the certification objective $L(x)$ as a linear function of the network's input neurons (whose values can be drawn from the input hyperbox), as described in Section 2. We split our algorithm into two steps, described in Section 3.1 and Section 3.2, to address the challenges outlined above. An optional final step, illustrated in Figure 2 and outlined in Appendix C, demonstrates the extension of our algorithm to generate polyhedral examples.

3.1 Computing an Overapproximating Region

In the first step, we compute an overapproximation hyperbox $\mathcal{O}$ by fitting a hyperbox around samples obtained from α. $\mathcal{O}$ is represented as a dashed blue rectangle in Figure 1. Intuitively, we use $\mathcal{O}$ to restrict the search space for adversarial regions to a part of the input space that α can attack.

3.2 Computing an Underapproximating Region

In the second step, we compute the hyperbox robust adversarial example $\mathcal{U}$, represented as a dotted violet rectangle in Figure 1. We will refer to $\mathcal{U}$ as underapproximation hyperbox to distinguish it from the polyhedral robust example $\mathcal{P}$ generated in Appendix C. $\mathcal{U}$ is obtained by iteratively shrinking $\mathcal{O}$ until arriving at a provably adversarial region. We denote the hyperbox created at iteration i of the shrinking process with $\mathcal{U}_i$, where $\mathcal{U}_0 = \mathcal{O}$. At each iteration i, we compute the certification objective $L^{i-1}(x)$ of the region $\mathcal{U}_{i-1}$ computed in the previous iteration. If the objective is proven to be positive, we assign $\mathcal{U}$ to $\mathcal{U}_{i-1}$, as in Step 4 in Figure 1, and return. Otherwise, we solve an optimization problem, seeking the largest hyperbox $\mathcal{U}_i \subseteq \mathcal{U}_{i-1}$ under the constraint that $\min_{x \in \mathcal{U}_i} L^{i-1}(x) \geq -p_{i-1}$, for a chosen bound $p_{i-1} \geq 0$. We describe the optimization problem involved in the shrinking procedure in the next paragraph. In Section 4, we will present and motivate our choice of p_{i-1}.

An important property of our choice of p_{i-1} is that it becomes smaller over time and thus forces the certification objective to increase over time until it becomes positive. We note that optimizing $L(x)$ this way is simpler than directly optimizing for $\mathcal{U}$ by differentiating through the convex relaxation of the network. In particular, our method does not require propagating a gradient through the convex relaxation of the network and the convex relaxation is updated only once per iteration. Additionally, it allows our algorithm to work with convex relaxation procedures that are not differentiable, such as the DeepG method employed in this paper. The resulting hyperbox $\mathcal{U}$ is a provable adversarial region.

Shrinking $\mathcal{U}_{i-1}$ There are multiple ways to shrink $\mathcal{U}_{i-1}$ so that the condition $\min_{x \in \mathcal{U}_i} L^{i-1}(x) \geq -p_{i-1}$ is satisfied. However, we aim to obtain the largest possible underapproximation box $\mathcal{U}$, so we make the greedy choice to shrink $\mathcal{U}_{i-1}$ in a way that results in the largest possible new box $\mathcal{U}_i$. This may not be the globally optimal choice across all iterations of the algorithm, which is harder to compute, but our choice is locally optimal.

One possible solution to the shrinking problem is to use a scheme that we call uniform shrinking, where all lower bounds $[l^{i-1}]_j$ and upper bounds $[u^{i-1}]_j$ in each dimension j of the hyperbox $\mathcal{U}_{i-1}$ are changed by the same amount. The optimal amount for this uniform shrinking scheme can then be selected using a binary search. While this gives an efficient shrinking algorithm, in practice we observe that uniform shrinking produces small regions. This is expected, as it may force all dimensions of the hyperbox to be shrunk by a large amount even though it might be enough to shrink only along some subset of the dimensions.

In contrast, our shrinking scheme adjusts each $[l^{i-1}]_j$ and $[u^{i-1}]_j$ individually. While this shrinking scheme is much more powerful, optimizing the size of $\mathcal{U}_i$ with respect to its lower and upper bounds $[l^i]_j$ and $[u^i]_j$ becomes more complex. We approach the problem differently in the high dimensional input setting related to L_∞ pixel intensity transformations and the low dimensional input setting related to geometric transformations.

Shrinking for L_∞ Transformations For the high dimensional setting of L_∞ pixel transformations, we choose to maximize $\sum_{j=1}^{n_0} [w^i]_j$, where $[w^i]_j = [u^i]_j - [l^i]_j$ denotes the width of the j^{th} dimension of $\mathcal{U}_i$. The linear error function allows for solutions where a small number of dimensions are shrunk to 0 width in favour of allowing most of the input dimensions to retain big width. This translates to sacrificing a few pixels where the network is not very robust in favour of obtaining a region $\mathcal{U}_i$ covering big ranges of other pixels. Since, $\sum_{i=j}^{n_0} [w^i]_j$ is a linear function of $[l^{i-1}]_j$ and $[u^{i-1}]_j$, the optimization can be posed as a Linear Program (LP) (Schrijver, 1998) and be efficiently solved with an LP solver to obtain optimal values for $[u^i]_j$ and $[l^i]_j$ w.r.t the objective, as we show in Section 4.

Shrinking for Geometric Transformations For the low-dimensional setting of geometric transformations, we choose to maximize the logarithm of the volume of $\mathcal{U}_i$. This error function encourages roughly equally-sized ranges for the geometric parameters of $\mathcal{U}_i$. We solve the maximization problem

using PGD, which might lead to merely locally optimal solutions. We, therefore, rely on multiple random initializations of PGD and choose the best result. Section 4 describes the process in detail.

3.3 PROVABLY ROBUST POLYHEDRAL ADVERSARIAL EXAMPLES

We remark that our provably robust adversarial examples are not restricted to hyperbox shapes. Appendix A describes an optional final step of our algorithm that generates provably robust polyhedral adversarial examples $\mathcal{P}$ from $\mathcal{U}$ and $\mathcal{O}$. $\mathcal{P}$ is iteratively cut from $\mathcal{O}$, such that $\mathcal{P} \supseteq \mathcal{U}$ is ensured. Therefore, $\mathcal{P}$ represents a bigger region, but takes additional time to compute. The computation of $\mathcal{P}$, requires a $\mathbb{V}$ that accumulates imprecision only at activation functions, such as ReLU or sigmoid, in order to work. This property is violated by DeepG's handling of the geometric transformations. For this reason, we only apply it in the L_∞-transformation setting. We refer interested readers to Appendix A for information on how we generate polyhedral adversarial examples.

4 OUR FRAMEWORK

We now present our algorithm in more formal terms. We already discussed in detail how to compute $\mathcal{O}$ in Section 3. We use Algorithm 1 to compute $\mathcal{U}$. It requires a neural network $f \colon \mathbb{R}^{n_0} \to \mathbb{R}^{n_l}$ with l layers, adversarial target class y_t, an overapproximation hyperbox $\mathcal{O}$, a speed/precision trade-off parameter $c \in [0, 1]$, a maximum number of iterations u_{it} and a neural network certification method $\mathbb{V}(f, \mathcal{U}_{i-1}, y_t)$ that takes a neural network f, a hyperbox $\mathcal{U}_{i-1}$ and a target y_t and returns a linear certification objective $L^{i-1}(x)$.

Algorithm 1 GENERATE_UNDERAPPROX

1: **func** GENERATE_UNDERAPPROX(f, $\mathcal{O}$, $\mathbb{V}$, y_t, c, u_{it})
2:     $\mathcal{U}_0 = \mathcal{O}$
3:     **for** $i \in \{1, 2, \ldots, u_{\text{it}}\}$ **do**
4:         $L^{i-1}(x)$, $e^{i-1} = \mathbb{V}(f, \mathcal{U}_{i-1}, y_t)$
5:         **if** $e^{i-1} \geq 0$ **then**
6:             **return** $\mathcal{U}_{i-1}$
7:         **end if**
8:         $p_{i-1} = -e^{i-1} \cdot c$
9:         **if** $L_\infty\_transformation$ **then**
10:         $\mathcal{U}_i = \text{Shrink\_LP}(\mathcal{U}_{i-1}, L^{i-1}(x), p_{i-1})$
11:         **else**
12:         $\mathcal{U}_i = \text{Shrink\_PGD}(\mathcal{U}_{i-1}, L^{i-1}(x), p_{i-1})$
13:         **end if**
14:     **end for**
15:     **return** FailedToConverge
16: **end func**

As described in Section 3.2, the algorithm generates a sequence of hyperboxes $\mathcal{U}_0 \supseteq \mathcal{U}_1 \supseteq \ldots \supseteq \mathcal{U}_{u_{\text{it}}}$ with $\mathcal{U}_0 = \mathcal{O}$ and returns the first hyperbox from the sequence proven to be adversarial by $\mathbb{V}$. At each iteration, the algorithm attempts to certify the hyperbox from the previous iteration $\mathcal{U}_{i-1}$ to be adversarial by computing the certification error e^{i-1} (Line 4) and checking if it is positive (Line 5). If successful, $\mathcal{U}_{i-1}$ is returned. Otherwise, we use $L^{i-1}(x)$ generated by our attempt at verifying $\mathcal{U}_{i-1}$ (Line 4) and generate the constraint $\min_{x \in \mathcal{U}_i} L^{i-1}(x) \geq -p_{i-1}$ based on a parameter $p_{i-1} \geq 0$. We note that $\min_{x \in \mathcal{U}_i} L^{i-1}(x)$ is a function of the hyperbox $\mathcal{U}_i$, parametrized by its lower and upper bounds. In order to shrink $\mathcal{U}_{i-1}$, we optimize the lower and upper bounds of $\mathcal{U}_i$ explicitly, such that the constraint holds true for the bounds. The next section specifies and motivates our choice of p_{i-1}.

4.1 CHOOSING p_{i-1}

At each iteration i, we use the constraint $\min_{x \in \mathcal{U}_i} L^{i-1}(x) \geq -p_{i-1}$ to shrink $\mathcal{U}_{i-1}$ (Line 9 – Line 13) by calling either the SHRINK_LP or SHRINK_PGD optimization procedure. SHRINK_LP is detailed in Section 4.2 below, while SHRINK_PGD is detailed in Appendix A.2. To enforce progress of the algorithm, we require the constraint to remove volume from $\mathcal{U}_{i-1}$. Therefore, the values of p_{i-1} for which $p_{i-1} \geq p_{i-1}^{\max}$, with $p_{i-1}^{\max} = -\min_{x \in \mathcal{U}_{i-1}} L^{i-1}(x) = -e^{i-1}$ are invalid because: $\min_{x \in \mathcal{U}_i} L^{i-1}(x) \geq \min_{x \in \mathcal{U}_{i-1}} L^{i-1}(x) \geq -p_{i-1}$. We show the hyperplane $L^{i-1}(x) = -p_{i-1}^{\max}$ denoted as *Upper* in Step 3 in Figure 1. We note that *Upper* always touches $\mathcal{U}_{i-1}$ by construction. Decreasing the value of p_{i-1}, increases the volume removed from $\mathcal{U}_{i-1}$, as demonstrated by the other two hyperplanes in Step 3 in Figure 1. Additionally, we require $p_{i-1} \geq 0$ as any value of $p_{i-1} = 0$ creates $\mathcal{U}_i$ that is provably adversarial. Choosing a negative value for p_{i-1} generates smaller provably adversarial $\mathcal{U}_i$ than with $p_{i-1} = 0$. We denote the hyperplane corresponding to $p_{i-1} = 0$ in Step 3 in Figure 1 denoted *Provable*. We use $p_{i-1} \in [0, p_{i-1}^{\max})$.

We note that while $p_{i-1} = 0$ is guaranteed to generate a provable region $\mathcal{U}_i$, it is often too greedy. This is due to the fact that with an imprecise $\mathbb{V}$, $L^{i-1}(x)$ itself is also imprecise and, therefore a more precise certification method may certify $\mathcal{U}_i$ as adversarial for $p_{i-1} > 0$. Further, as the region $\mathcal{U}_{i-1}$ shrinks, the precision of $\mathbb{V}$ increases and vice versa. Thus $\mathbb{V}$ might be capable of certifying $\mathcal{U}_i$, for $p_{i-1} > 0$, since on the next iteration of the algorithm the more precise certification objective $L^i(x)$ will be used for certifying the robustness of the smaller $\mathcal{U}_i$. We choose p_{i-1} heuristically, by setting $p_{i-1} = p_{i-1}^{\max} \cdot c$, for a chosen parameter $c \in [0, 1)$. This is depicted in Line 8 in Algorithm 1. The closer c is to 1, the bigger the chance that the modified region will not verify, but, also, the bigger the region we produce and vice versa. Thus, c balances the precision and the speed of convergence of the algorithm. We empirically verify the effect of c in Appendix B.1. The hyperplane resulting from $c = 0.65$ is denoted as *Chosen* in Step 3 in Figure 1. We further note that, when the upper and provable hyperplanes, at a particular iteration get closer than a threshold t we set $p_{i-1} = 0$ to allow for immediate termination of the algorithm. This speeds up the convergence of the algorithm in the final stages, when the precision loss of $\mathbb{V}$ is not too big.

4.2 SHRINK_LP

We now describe in detail the function SHRINK_LP, used to shrink $\mathcal{U}_{i-1}$ to $\mathcal{U}_i$ when generating examples robust to pixel intensity changes, based on the parameters $L^{i-1}(x)$ and p_{i-1}. SHRINK_LP defines two sets of LP variables for the lower bounds $l^i \in \mathbb{R}^{n_0}$ and the upper bounds $u^i \in \mathbb{R}^{n_0}$ of $\mathcal{U}_i$. As described in Section 3.2, the LP optimizes the sum of widths of the dimensions of $\mathcal{U}_i$, i.e., $\sum_{j=1}^{n_0}([u^i]_j - [l^i]_j)$. Recall that $L^{i-1}(x)$ is a linear function of x represented as $L^{i-1}(x) = a \cdot x + b$. As described in Section 3.2, the LP we define needs to enforce $\min_{x \in \mathcal{U}_i} L^{i-1}(x) \geq -p_{i-1}$. We rewrite $\min_{x \in \mathcal{U}_i} L^{i-1}(x)$ as: $\text{hp}(l^i, u^i) = \max(0, a) \cdot l^i + \min(0, a) \cdot u^i + b$.

Since $\text{hp}(l^i, u^i)$ is a linear function of l^i and u^i, we add the constraint $\text{hp}(l^i, u^i) \geq -p_{i-1}$ to the LP:

$$\bar{l}^i, \bar{u}^i = \underset{}{\arg\max} \sum_{j=1}^{n_0}([u^i]_j - [l^i]_j)$$
$$\text{s.t. } \text{hp}(l^i, u^i) \geq -p_{i-1}, [l^{i-1}]_j \leq [l^i]_j \leq [u^i]_j \leq [u^{i-1}]_j \text{ for all } j.$$

where $l^{i-1}, u^{i-1} \in \mathbb{R}^{n_0}$ represent the lower and upper bounds of $\mathcal{U}_{i-1}$, the second constraint enforces $\mathcal{U}_i \subseteq \mathcal{U}_{i-1}$ and $\bar{l}^i, \bar{u}^i \in \mathbb{R}^{n_0}$ denotes the LP solution. Finally, SHRINK_LP constructs $\mathcal{U}_i = [\bar{l}^i, \bar{u}^i]$.

5 EXPERIMENTAL EVALUATION

We now evaluate the effectiveness of our approach on realistic networks. We implemented our framework in Python and used Tensorflow (Abadi et al., 2015) for generating PGD attacks. We use Gurobi 9.0 (Gurobi Optimization, LLC, 2020) for solving LP instances. We rely on ERAN (Singh et al., 2018b) for its DeepPoly and DeepG implementations. We ran all our experiments on a 2.8 GHz 16 core Intel(R) Xeon(R) Gold 6242 with 64 GB RAM.

Neural Networks We use MNIST (LeCun et al., 1998) and CIFAR10 (Krizhevsky, 2009) based networks. Table 4 in Appendix A.1 shows the sizes and types of different neural networks. All networks in our L_∞ experiments except the CIFAR10 ConvBig are not adversarially trained. In our experiments, normally trained networks were more sensitive to geometric perturbations than L_∞. Therefore, we use DiffAI-trained (Mirman et al., 2018) networks which tend to be less sensitive against geometric transformations. Our deepest network is the MNIST 8×200 fully-connected network (FFN) which has 8 layers with 200 neurons each and another layer with 10 neurons. Our largest network is the CIFAR10 `ConvBig` network with 6 layers and $\approx 62K$ neurons. This network is among the largest benchmarks that existing verifiers can handle in a scalable and precise manner. We compare the methods on the first 100 test images of the datasets, a standard practice in the verification literature (Balunović et al., 2019; Singh et al., 2019), while filtering the wrongly-classified ones. For each experiment, we tuned the value of c to balance runtime and size.

5.1 ADVERSARIAL EXAMPLES ROBUST TO INTENSITY CHANGES

Table 1 summarizes the results of generating examples robust to intensity changes. Further, Appendix D.2 shows visualizations of the adversarial examples obtained in the experiment. For both

Table 1: Comparison between methods for creating adversarial examples robust to intensity changes.

DATASET	MODEL	ϵ	#CORR	#IMG	#REG	BASELINE			OUR METHOD BOX			OUR METHOD POLY		
						#VERREG	TIME	SIZE	#VERREG	TIME	SIZE	#VERREG	TIME	SIZEO
MNIST	8 x 200	0.045	97	22	53	41	272 s	10^{24}	53	114 s	10^{121}	53	1556 s	10^{191}
	CONVSMALL	0.12	100	21	32	31	171 s	10^{339}	32	74 s	10^{494}	32	141 s	10^{561}
	CONVBIG	0.05	98	18	29	15	1933s	10^{9}	28	880 s	10^{137}	28	5636 s	10^{173}
CIFAR10	CONVSMALL	0.006	59	23	44	28	238 s	10^{360}	44	113 s	10^{486}	44	264 s	10^{543}
	CONVBIG	0.008	60	25	36	26	479 s	10^{380}	36	404 s	10^{573}	36	610 s	10^{654}

Table 2: Comparison between methods for creating adversarial examples robust to geometric changes.

DATASET	TRANSFORM	#CORR	#IMG	#REG	BASELINE			OUR METHOD				
					#VERREG	TIME	#SPLITS	#VERREG	TIME	#SPLITS	UNDER	OVER
MNIST CONVSMALL	R(17) Sc(18) Sh(0.03)	99	38	54	10	890 s	2x5x2	51	774 s	1x2x1	10^{96}	10^{195}
	Sc(20) T(-1.7,1.7,-1.7,1.7)	99	32	56	5	682 s	4x3x3	51	521 s	2x1x1	10^{71}	10^{160}
	Sc(20) R(13) B(10, 0.05)	99	33	48	2	420 s	3x2x2x2	40	370 s	2x1x1x1	10^{70}	10^{455}
MNIST CONVBIG	R(10) Sc(15) Sh(0.03)	95	40	50	9	812 s	2x4x2	44	835 s	1x2x1	10^{77}	10^{205}
	Sc(20) T(0,1,0,1)	95	34	46	2	435 s	4x2x2	42	441 s	2x1x1	10^{64}	10^{174}
	Sc(15) R(9) B(5, 0.05)	95	39	52	2	801 s	3x2x2x2	46	537 s	2x1x1x1	10^{119}	10^{545}
CIFAR CONVSMALL	R(2.5) Sc(10) Sh(0.02)	53	24	29	1	1829 s	5x2x2	29	1369 s	2x1x1	10^{599}	10^{1173}
	Sc(10) T(0,1,0,1)	53	28	32	1	1489 s	4x3x3	32	954 s	2x1x1	10^{66}	10^{174}
	Sc(5) R(8) B(1, 0.01)	53	21	25	1	2189 s	5x2x2x2	21	1481 s	2x1x1x1	10^{513}	10^{2187}

datasets, we compare against the uniform shrinking described in Section 3, used as a baseline, to our method for generating provably robust hyperbox and polyhedral adversarial examples. In all experiments, we compute $\mathcal{O}$ using adversarial examples collected within an L_∞ ball around a test image with the radius ϵ specified in Table 1. The values of ϵ are chosen such that the attack has a non-trivial probability (> 0 but < 1) of success. We use 2500 adversarial examples obtained using the Frank-Wolfe optimization algorithm (Frank & Wolfe, 1956), 2500 examples each from PGD with step 0.1ϵ and 0.01ϵ, respectively. For the PGD examples, we use output diversification (Tashiro et al., 2020) with 5 iterations. In all experiments, we initialize $c = 0.99$ and multiply it by a factor of 0.99 at each iteration of Algorithm 1.

For the hyperbox adversarial examples obtained by both our method and the baseline, we calculate the size of the example in terms of the number of concrete adversarial examples it contains and we report the median of all regions under the Size columns in Table 1. For the polyhedral adversarial examples, we report the median number of concrete adversarial examples contained within an overapproximated hyperbox around the polyhedral region in the SizeO column. We note that an underapproximation of the number of concrete adversarial examples in the polyhedral region is the same as those in the hyperbox adversarial examples obtained by our method. We also report the average runtime.

We note that for MNIST ConvBig and 8×200, the regions obtained for $\mathcal{O}$ produced huge certification error > 1000, which prevented our underapproximation algorithm $\mathcal{U}$ to converge on these networks. To alleviate the problem, we used uniform shrinking to lower the error to under 100. We then used the obtained box in place of $\mathcal{O}$. We conjecture the reason for this issue is the huge amount of imprecision accumulated in the networks due to their depth and width and note that the uniform shrinking on these networks alone performs worse. For each network, in Table 1, we report the number of distinct pairs of an image and an adversarial target on which α succeeds (column #Regions), as well as the number of unique images on which α succeeds (column #Images). We further report the number of test images that are correctly classified by the networks (column #Corr). The table details the number of regions on which the different methods succeed (column #VerReg), that is, they find a robust adversarial example containing > 1000 concrete adversarial examples. As can be seen in Table 1, our framework creates symbolic regions that consistently contain more concrete adversarial examples (up to 10^{573} images on CIFAR10 ConvBig) than the baseline which being faster. Our method also succeeds more often, failing only for a single region due to the corresponding hyperbox $\mathcal{O}$ also containing < 1000 concrete examples versus 53 failures for the baseline. In Appendix B.2, we further compare our method to Liu et al. (2019) and find we generate more and larger regions in similar runtime. Overall, our method, unlike the baselines, generates robust examples containing large number of examples in almost all cases in which the image is attackable, in a few minutes.

5.2 ADVERSARIAL EXAMPLES ROBUST TO GEOMETRIC CHANGES

Next, we demonstrate the results of our algorithm in the geometric transformation setting. Our method relies on DeepG for robustness certification. To increase its precision, DeepG selectively

Table 3: The robustness of different examples to L_2 smoothing defenses.

METHOD	MNIST			CIFAR	
	8x200	CONVSMALL	CONVBIG	CONVSMALL	CONVBIG
BASELINE	0.55	0.38	0.59	0.53	0.26
OURS	**1.00**	**1.00**	**1.00**	**1.00**	**1.00**
INDIVIDUAL ATTACKS MEAN	0.29	0.16	0.18	0.48	0.25
INDIVIDUAL ATTACKS 95% PERCENTILE	0.53	0.44	0.51	0.61	0.37

employs input space splitting, where each split is verified individually. This strategy is effective due to the low dimensionality of the input space (3 to 4 geometric parameters in our experiments). To this end we also employ splitting for our method on $\mathcal{O}$, where size obtained for the different splits is individually shrunken and summed. We compare our method against a baseline based on a more aggressive uniform splitting of $\mathcal{O}$ that does not use our shrinking procedure.

Table 2 summarizes the results of our method and the baseline for the MNIST and CIFAR10 datasets. Further, Appendix D.3 shows visualizations of the adversarial examples obtained in the experiment. The Transform column in the table represents the set of geometric transformations on the images. Here, $R(x)$ signifies a rotation of up to $\pm x$ degrees; $Sc(x)$ signifies scaling of up to $\pm x\%$; $Sh(m)$ signifies shearing with a shearing factor between $\pm m\%$; $B(\alpha, \beta)$ signifies changes in contrast between $\pm\alpha\%$ and brightness between $\pm\beta\%$; and $T(x_l, x_r, y_d, y_u)$ signifies translation of up to x_l pixels left, x_r pixels right, y_d pixels down and y_u pixels up. Similar to L_∞, we chose the geometric regions such that the attack algorithm has a non-trivial probability of success.

In all experiments, we compute $\mathcal{O}$ using random sampling attacks which are the state-of-the-art for geometric transformations (Engstrom et al., 2019). For the 3 dimensional experiments, we rely on 15000 random samples, while for the 4D configurations we use 50000. For all experiments, we use $c = 0.65$, except for the 4 dimensional CIFAR10 experiment, where we use $c = 0.75$. We rely on the polyhedra created by DeepG that binds the values of the image pixels to estimate the number of concrete adversarial examples contained within our robust examples. In particular, underapproximation and overapproximation hyperboxes are computed for each image, where the underapproximation hyperbox is based on (Gopinath et al., 2019) and the overapproximation relies on computing the extreme values of each pixel. The median number of concrete examples are depicted in the Over and Under columns in Table 2. For all experiments, the baseline failed to generate regions with > 1000 examples on most images and, thus, we omit its computed size in Table 2 to save space. We note that on the few images where it does not, the size generated by our method is always more.

We report the number of concrete examples, the number of splits, the average runtime, and the number of successfully verified regions for both the baseline and our method in the #Splits, Time, and #VerReg columns, respectively. Table 2 demonstrates that in a similar or smaller amount of time, our algorithm is capable of generating robust adversarial examples for most regions $\mathcal{O}$, while the baseline fails for most. Further, our regions are non-trivial as they contain more than 10^{64} concrete adversarial attacks. We note that the runtimes for generating robust examples in this setting is higher than in Table 1. This is due to both the inefficiency of the attack and the time required for the robustness certification of a single region. Due to the flexibility and the generality of our method, we believe it can be easily adapted to more efficient attack and certification methods in the future.

5.3 ROBUSTNESS OF ADVERSARIAL EXAMPLES TO RANDOMIZED SMOOTHING

We show that our adversarial examples robust to intensity changes are significantly more effective against state-of-the-art defenses based on randomized smoothing compared to the individual attacks used to create the regions as well as the baseline from Table 1. We note that our setting here is different than Salman et al. (2019) which directly attacks the smoothed classifier. We instead create our robust examples from L_2 PGD attacks on networks f with the architecture described in Table 1 but trained on images with added Gaussian noise with a standard deviation of 0.15. The training procedure is consistent with Cohen et al. (2019). As described in Section 2.3, we choose the radius R' of the attacks on a per-image basis, so that it is the smallest one allowing attacks on f. We exclude images whose radius is too big, as we consider them robust against L_2 attacks. Following the intuition presented in Section 2.3, we compare the different attacks based on the criterion in Definition 2

with $\tilde{x}$ selected for our method as the middle point of the underapproximation box of our examples projected back on the L_2 ball with radius R'.

We observe that all adversarial examples are only certifiably robust to smoothed classifiers g with significantly smaller σ compared to the original image. Since assessing all individual attacks with multiple values of σ is computationally intensive, we select σ by searching for a value that produces the biggest certified radius R_{adv} for our adversarial examples. Throughout the experiment, we use $\alpha = 0.005$, as suggested by Cohen et al. (2019), and the chosen σ to compute the attack strength of both the baseline algorithm and the individual attacks involved in the creation of our robust examples. In Table 3 we compare our method versus the others on the ratio of the radii produced. We observe that our examples produce attacks with much bigger strength on average compared to the alternatives.

5.4 Comparison with Empirically Robust Examples

We compare our provably robust adversarial examples to empirically robust adversarial examples (Athalye et al., 2018) – large input regions, defined by a set of perturbations of an image, that are empirically verified to be adversarial. The empirical verification is based on calculating the expectation over transformations (EoT) of the obtained region defined in Athalye et al. (2018). We consider a region to be an empirically robust adversarial example if it has an EoT $\geq 90\%$. We demonstrate that EoT is a limited measure, as it is not uniform. That is, empirically robust adversarial examples can exhibit high EoT - e.g 95%, while specially chosen subregions incur very low EoT scores. In Appendix A.3, we discuss our extension to Athalye et al. (2018) used in this experiment.

We execute the experiment on the first MNIST ConvBig transformation in Table 2. We note that the algorithm from Athalye et al. (2018) relies on sampling and does not scale to high dimensional L_∞ perturbations. The algorithm produces 24 different regions, significantly less than our 44 provable regions. The 24 empirically robust adversarial examples produced achieve average EoT of 95.5%. To demonstrate the non-uniformness of the empirical robustness, for each region, we considered a subregion of the example, with dimensions of size 10% of the original example, placed at the corner of the example closest to the original image. We calculated the EoT of these subregions and found that $14/24$ regions had an EoT of $< 50\%$, with 9 having an EoT of 0%.

This demonstrates that the fundamental assumption that the EoT of a region is roughly uniform throughout does not hold and instead it is possible and even common in practice that a significant part of an empirically robust example is much less robust than the remaining region. Further, this often happens close to the original input image, thus providing the misleading impression that an empirically robust adversarial example is a much stronger adversarial attack than it actually is. This misleading behaviour suggests that provably robust adversarial examples, which cannot exhibit such behaviour by construction, provide a more reliable method of constructing adversarial examples invariant to intensity changes and geometric transformations. We note that a limiting factor to the practical adoption of our method remains scalability to real world networks and datasets such as ImageNet, due to the reliance on certification techniques that do not scale there yet. We note that our method is general and efficient enough to directly benefit from any future advancement in verification.

6 Conclusion

We introduced the concept of provably robust adversarial examples – large input regions guaranteed to be adversarial to a set of perturbations. We presented a scalable method for synthesizing such examples, generic enough to handle multiple perturbations types including pixel intensity changes and geometric transformations. We demonstrated the effectiveness of our method by showing it creates more and larger regions than baselines, in similar or less time, including regions containing $\approx 10^{573}$ adversarial examples for pixel intensity and $\approx 10^{599}$ for geometric transformations.

REFERENCES

Martín Abadi, Ashish Agarwal, Paul Barham, Eugene Brevdo, Zhifeng Chen, Craig Citro, Greg S. Corrado, Andy Davis, Jeffrey Dean, Matthieu Devin, Sanjay Ghemawat, Ian Goodfellow, Andrew Harp, Geoffrey Irving, Michael Isard, Yangqing Jia, Rafal Jozefowicz, Lukasz Kaiser, Manjunath Kudlur, Josh Levenberg, Dan Mané, Rajat Monga, Sherry Moore, Derek Murray, Chris Olah, Mike Schuster, Jonathon Shlens, Benoit Steiner, Ilya Sutskever, Kunal Talwar, Paul Tucker, Vincent Vanhoucke, Vijay Vasudevan, Fernanda Viégas, Oriol Vinyals, Pete Warden, Martin Wattenberg, Martin Wicke, Yuan Yu, and Xiaoqiang Zheng. TensorFlow: Large-scale machine learning on heterogeneous systems, 2015. URL http://tensorflow.org/. Software available from tensorflow.org.

Maksym Andriushchenko, Francesco Croce, Nicolas Flammarion, and Matthias Hein. Square attack: a query-efficient black-box adversarial attack via random search, 2019.

Anish Athalye, Logan Engstrom, Andrew Ilyas, and Kevin Kwok. Synthesizing robust adversarial examples. In *Proc. International Conference on Machine Learning (ICML)*, volume 80, pp. 284–293, 10–15 Jul 2018.

Mislav Balunovic and Martin Vechev. Adversarial training and provable defenses: Bridging the gap. 2020.

Mislav Balunović, Maximilian Baader, Gagandeep Singh, Timon Gehr, and Martin Vechev. Certifying geometric robustness of neural networks. *Advances in Neural Information Processing Systems 32*, 2019.

Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. In *Proc. IEEE Symposium on Security and Privacy (SP)*, pp. 39–57, 2017.

Jeremy Cohen, Elan Rosenfeld, and Zico Kolter. Certified adversarial robustness via randomized smoothing. In *International Conference on Machine Learning*, pp. 1310–1320. PMLR, 2019.

Francesco Croce and Matthias Hein. Minimally distorted adversarial examples with a fast adaptive boundary attack, 2019.

Ruediger Ehlers. Formal verification of piece-wise linear feed-forward neural networks. In D. D'Souza and K. N. Kumar (eds.), *International Symposium on Automated Technology for Verification and Analysis*, pp. 269–286. Springer, 2017.

Logan Engstrom, Brandon Tran, Dimitris Tsipras, Ludwig Schmidt, and Aleksander Madry. Exploring the landscape of spatial robustness. In *International Conference on Machine Learning*, pp. 1802–1811. PMLR, 2019.

Marc Fischer, Maximilian Baader, and Martin T. Vechev. Certified defense to image transformations via randomized smoothing. In *Proc. Neural Information Processing Systems (NeurIPS)*, 2020.

Marguerite Frank and Philip Wolfe. An algorithm for quadratic programming. *Naval research logistics quarterly*, 3(1-2):95–110, 1956.

Timon Gehr, Matthew Mirman, Dana Drachsler-Cohen, Petar Tsankov, Swarat Chaudhuri, and Martin Vechev. Ai2: Safety and robustness certification of neural networks with abstract interpretation. In *2018 IEEE Symposium on Security and Privacy (SP)*, pp. 3–18. IEEE, 2018.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations (ICLR)*, 2015.

Divya Gopinath, Hayes Converse, Corina Pasareanu, and Ankur Taly. Property inference for deep neural networks. In *2019 34th IEEE/ACM International Conference on Automated Software Engineering (ASE)*, pp. 797–809. IEEE, 2019.

Gurobi Optimization, LLC. Gurobi optimizer reference manual, 2020. URL http://www.gurobi.com.

Shengyuan Hu, Tao Yu, Chuan Guo, Wei-Lun Chao, and Kilian Q. Weinberger. A new defense against adversarial images: Turning a weakness into a strength. In *Proc. Neural Information Processing Systems, (NeurIPS)*, pp. 1633–1644, 2019.

Max Jaderberg, Karen Simonyan, Andrew Zisserman, and Koray Kavukcuoglu. Spatial transformer networks. *arXiv preprint arXiv:1506.02025*, 2015.

Alex Krizhevsky. Learning multiple layers of features from tiny images. 2009.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *arXiv preprint arXiv:1607.02533*, 2016.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 86(11):2278–2324, 1998.

Mathias Lécuyer, Vaggelis Atlidakis, Roxana Geambasu, Daniel Hsu, and Suman Jana. Certified robustness to adversarial examples with differential privacy. In *2019 IEEE Symposium on Security and Privacy, SP*, pp. 656–672. IEEE, 2019.

Linyi Li, Maurice Weber, Xiaojun Xu, Luka Rimanic, Tao Xie, Ce Zhang, and Bo Li. Provable robust learning based on transformation-specific smoothing. *CoRR*, abs/2002.12398, 2020.

Chen Liu, Ryota Tomioka, and Volkan Cevher. On certifying non-uniform bounds against adversarial attacks. In *International Conference on Machine Learning*, pp. 4072–4081. PMLR, 2019.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *Proc. International Conference on Learning Representations (ICLR)*, 2018.

Matthew Mirman, Timon Gehr, and Martin Vechev. Differentiable abstract interpretation for provably robust neural networks. In *International Conference on Machine Learning*, pp. 3578–3586. PMLR, 2018.

Tianyu Pang, Kun Xu, Yinpeng Dong, Chao Du, Ning Chen, and Jun Zhu. Rethinking softmax cross-entropy loss for adversarial robustness. In *Proc. International Conference on Learning Representations, ICLR*, 2020.

Yao Qin, Nicholas Carlini, Garrison Cottrell, Ian Goodfellow, and Colin Raffel. Imperceptible, robust, and targeted adversarial examples for automatic speech recognition. In *International conference on machine learning*, pp. 5231–5240. PMLR, 2019.

Hadi Salman, Jerry Li, Ilya P. Razenshteyn, Pengchuan Zhang, Huan Zhang, Sébastien Bubeck, and Greg Yang. Provably robust deep learning via adversarially trained smoothed classifiers. In *Proc. Neural Information Processing Systems (NeurIPS)*, pp. 11289–11300, 2019.

Alexander Schrijver. *Theory of linear and integer programming*. John Wiley & Sons, 1998.

Sanchari Sen, Balaraman Ravindran, and Anand Raghunathan. EMPIR: ensembles of mixed precision deep networks for increased robustness against adversarial attacks. In *Proc. International Conference on Learning Representations, ICLR*, 2020.

Gagandeep Singh, Timon Gehr, Matthew Mirman, Markus Püschel, and Martin Vechev. Fast and effective robustness certification. In *Advances in Neural Information Processing Systems*, pp. 10802–10813, 2018a.

Gagandeep Singh, Jonathan Maurer, Matthew Mirman, Timon Gehr, Adrian Hoffmann, Petar Tsankov, Dana Drachsler Cohen, Markus Püschel, and Martin Vechev. ERAN: ETH Robustness Analyzer for Neural Networks, 2018b. URL https://github.com/eth-sri/eran.

Gagandeep Singh, Timon Gehr, Markus Püschel, and Martin Vechev. An abstract domain for certifying neural networks. *Proceedings of the ACM on Programming Languages*, 3(POPL):41, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Yusuke Tashiro, Yang Song, and Stefano Ermon. Output diversified initialization for adversarial attacks. *arXiv preprint arXiv:2003.06878*, 2020.

Florian Tramèr, Nicholas Carlini, Wieland Brendel, and Aleksander Madry. On adaptive attacks to adversarial example defenses. *CoRR*, abs/2002.08347, 2020.

Shiqi Wang, Yizheng Chen, Ahmed Abdou, and Suman Jana. Enhancing gradient-based attacks with symbolic intervals, 2019.

Chang Xiao, Peilin Zhong, and Changxi Zheng. Enhancing adversarial defense by k-winners-take-all. In *Proc. International Conference on Learning Representations, ICLR*, 2020.

Huan Zhang, Tsui-Wei Weng, Pin-Yu Chen, Cho-Jui Hsieh, and Luca Daniel. Efficient neural network robustness certification with general activation functions. In *Advances in neural information processing systems*, pp. 4939–4948, 2018.

Tianhang Zheng, Changyou Chen, and Kui Ren. Distributionally adversarial attack. *Proc. AAAI Conference on Artificial Intelligence*, 33:2253–2260, 07 2019.

Table 4: Neural networks used in our experiments.

DATASET	MODEL	TYPE	NEURONS	LAYERS
	8×200	FFN	1,610	9
MNIST	CONVSMALL	CONV	3,604	3
	CONVBIG	CONV	48,064	6
CIFAR10	CONVSMALL	CONV	4,852	3
	CONVBIG	CONV	62,464	6

Algorithm 2 PGD_PROJECT

1: **func** PGD_PROJECT(l^i, u^i, l^{i-1}, u^{i-1}, hp, a, b, p_{i-1})
2:     l^i = Clip(l^i, l^{i-1}, u^{i-1})
3:     u^i = Clip(u^i, l^{i-1}, u^{i-1})
4:     val = hp(l^i, u^i) $- b$
5:     **if** val $\geq -p_{i-1}$ **then**
6:         **return** l^i, u^i
7:     **end if**
8:     $[l^i]_{a>0}$ = $-\frac{[l^i]_{a>0} \cdot (p_{i-1} - b)}{\text{val}}$
9:     $[u^i]_{a<0}$ = $-\frac{[u^i]_{a<0} \cdot (p_{i-1} - b)}{\text{val}}$
10:     l^i = Clip(l^i, l^{i-1}, u^{i-1})
11:     u^i = Clip(u^i, l^{i-1}, u^{i-1}) RETURN l^i, u^i
12: **end func**

A   IMPLEMENTATION DETAILS

A.1   NETWORKS

Table 4 shows the architectures of the networks on which we evaluate.

A.2   DETAILED DESCRIPTION OF SHRINK_PGD

In this section we describe in detail the function SHRINK_PGD, used to shrink $\mathcal{U}_{i-1}$ to $\mathcal{U}_i$ for generating regions robust to geometric transformations, based on the parameters $L^{i-1}(x)$ and p_{i-1}.

SHRINK_PGD relies on PGD to optimize the log volume of $\mathcal{U}_i$ with respect to its lower and upper bounds, as described in §sec:under. The optimization problem can be written as:

$$
\begin{aligned}
\bar{l}^i, \overline{u}^i = \ & \text{argmax} \sum_{j=1}^{n_0} \log([u^i]_j - [l^i]_j) \\
& \text{s.t. } \text{hp}(l^i, u^i) \geq -p_{i-1} \\
& \quad [l^{i-1}]_j \leq [l^i]_j \leq [u^i]_j \leq [u^{i-1}]_j \text{ for all } j,
\end{aligned}
\tag{1}
$$

where we use the same notations as in the previous section. Since we rely on PGD, we need to define how to project values of l^i and u^i that violate the constraints in equation 1.

Algorithm 2 demonstrates the heuristic we use for the projection. Algorithm 2 slightly abuses the notations above, and treats l^i and u^i, as the concrete values of l^i and u^i to be projected, instead of treating them as variables.

It first clips l^i and u^i to enforce $\mathcal{U}_i \subseteq \mathcal{U}_{i-1}$ (Line 2—Line 3). It then checks whether $\text{hp}(l^i, u^i) \geq -p_{i-1}$ is satisfied and if so returns (Line 4—Line 7). Otherwise, all elements of l^i corresponding to positive values of a, $[l^i]_{a>0}$, and all elements of u^i corresponding to negative values of a, $[u^i]_{a<0}$, are adjusted by a factor of $-\frac{p_{i-1}-b}{\text{val}}$, where val $= \text{hp}(l^i, u^i) - b$. This enforces $\text{hp}(l^i, u^i) \geq -p_{i-1}$ (Line 8—Line 9). In rare cases the second projection can result in values of l^i and u^i violating $\mathcal{U}_i \subseteq \mathcal{U}_{i-1}$. Our solution is to clip again (Line 10—Line 11).

After the last clip, in the rare case mentioned above the returned values for l^i and u^i violate $\text{hp}(l^i, u^i) \geq -p_{i-1}$. However, we did not find this to be a problem in practice, as it occurs rarely and one can continue as if choosing a different value for c in Algorithm 1.

Table 5: Geometric results for different c.

C	#VERREG	UNDER	OVER	TIME	#IT
0.45	25	10^{59}	10^{167}	264 s	1.6
0.55	36	10^{52}	10^{162}	333 s	2.9
0.65	42	10^{64}	10^{174}	441 s	4.5
0.75	44	10^{67}	10^{181}	585 s	6.7
0.85	44	10^{113}	10^{199}	871 s	10.6

A.3 DETAILED DESCRIPTION OF ADAPTED EoT USED IN EXPERIMENTS IN SECTION 5.4

In this section we discuss the extension of Athalye et al. (2018) we use to produce the empirically robust adversarial examples for the experiment in §sec:eotcomp. We define an optimization procedure, where we seek a hyperbox geometric region $\mathcal{U}_{\text{emp}} \subseteq \mathbb{R}^{n_0}$, defined in terms of the lower bound $l_{\text{emp}} \in \mathbb{R}^{n_0}$ and the upper bound $u_{\text{emp}} \in \mathbb{R}^{n_0}$ vectors. We seek to find $\mathcal{U}_{\text{emp}}$ within the set of allowed geometric transformations $\mathcal{I} \subseteq \mathbb{R}^{n_0}$, such that $\mathcal{U}_{\text{emp}}$ is an empirically robust adversarial example with maximal log volume, and high EoT. Similarly to Athalye et al. (2018) EoT is calculated on set of samples from $\mathcal{U}_{\text{emp}}$. We rely on differentiable bilinear interpolation (Jaderberg et al., 2015) to allow gradients to flow through the geometric transformations we consider and optimize l_{emp} and u_{emp} using PGD.

B ADDITIONAL EXPERIMENTS

B.1 DEPENDENCE OF OUR METHOD ON THE VALUE OF c

In this section, we examine the effect of the parameter c on our algorithm. We show how the volume of our regions robust to geometric transformations vary, as a function of c. Table 5 depicts the results on the MNIST ConvBig scaling and translation experiment, originally depicted in Table 2. The results correspond to our intuition about c: the higher the value of c is, the greater the volume produced by our method, even allowing the algorithm to succeed for two additional images. However, this increases runtime as the average number of iterations (column #It) increases.

B.2 COMPARISON WITH LIU ET AL. (2019)

In this section, we compare our method against the method proposed in Liu et al. (2019), which is also capable of generating provably robust hyperbox regions. Since the code provided in Liu et al. (2019) only applies to fully connected networks, we trained 8x200 MNIST fully connected network using the code provided in Liu et al. (2019). We chose to compare on networks trained with Liu et al. (2019) since their code did not allow for easy way to load our networks in their framework. The network has the same architecture as the one used in Table 1 and we generate adversarial examples provably robust against pixel intensity changes. We initialize both methods with the same overapproximation hyperbox $\mathcal{O}$ and compare the shrinking phase. With similar runtime ($\approx$ 200s), out of 84 possible regions, our method and Liu et al. (2019) created 84 and 76 regions with median underapproximation volume of 10^{184} and 10^{46}, respectively. We also point out that our method can additionally create polyhedral regions and handle the geometric perturbations while Liu et al. (2019) cannot.

C PROVABLY ROBUST POLYHEDRA ADVERSARIAL EXAMPLES

In this section, we show an extension to our method that allows us to generate provably robust adversarial examples represented as a general polyhedron shapes $\mathcal{P}$ in the neural network input space. The approach relies on the underapproximation and overapproximation boxes $\mathcal{U}$ and $\mathcal{O}$, presented in the main body, to guide the search of $\mathcal{P}$ and is demonstrated in Figure 2. The results of the method presented in this section were shown in Table 1 in Section 5.1.

Figure 2: Overview of our method for creation of provably robust polyhedral adversarial examples. The green triangle denoted $\mathcal{T}$ represents the ground truth adversarial region. The dashed blue rectangle denoted $\mathcal{O}$ and the violet dotted rectangle denoted $\mathcal{U}$ represent the fitted overapproximation and underapproximation boxes, respectively. The solid black lines represent hyperplanes generated by the verification procedure, while their dash-dotted counterparts represent the hyperplanes after bias-adjustment. The small arrows going out of the hyperplanes in Steps 1 and 2 represent the direction which is retained by the hyperplanes' corresponding half-spaces. The output polyhedral region denoted $\mathcal{P}$ is shown in red in step 3.

C.1 BACKGROUND

Our method for generating polyhedral robust adversarial examples requires more restricted form for $\mathbb{V}$, compared to the algorithms presented in the main body. In this subsection we discuss the relevant background and the additional requirements we pose on $\mathbb{V}$ and introduce the relevant notation for the rest of this section.

For this section, we will focus on ReLU-based neural networks. We note that our concepts can easily be extended to networks with other activation functions such as sigmoid or tanh. We consider neural network with l layers $f_1, \ldots, f_l$. The first $l-1$ layers are of the form $f_i(\mathbf{x}) = \max(0, A_i \cdot \mathbf{x} + \mathbf{b}_i)$ for $i \in \{1, \ldots, l-1\}$ and the final layer is of the form $f_l(\mathbf{x}) = A_l \cdot \mathbf{x} + \mathbf{b}_l$. The neural network f is the composition of all layers: $f = f_l \circ \cdots \circ f_1$. Let n_i be the number of neurons in layer i. If $z_{i,j}^a$ is the input to the j-th ReLU activation in layer i and $z_{i,j}^r$ is the corresponding ReLU output, we can represent the neural network as the following system of constraints: For $i \in \{1, \ldots, l\}$ and $j \in \{1, \ldots, n_i\}$,

$$z_{i,j}^a = [b_i]_j + \sum_{k=1}^{n_{i-1}} [A_i]_{j,k} \cdot z_{i-1,k}^r,$$
$$z_{i,j}^r = \max(0, z_{i,j}^a).$$

Here, $z_{0,j}^r$ describes the j-th of n_0 input activations. We call the two types of constraints affine constraints and ReLU constraints, respectively. We additionally constrain our inputs z_0^r to be points of a polyhedron $\mathcal{P} \subseteq \mathbb{R}^{n_0}$. An adversarial class y_t has the highest score on all inputs in $\mathcal{P}$ if $\min(z_{l,y_t}^a - z_{l,y}^a) > 0$ with respect to all constraints for all $y \in \{1, \ldots, n_l\} \setminus \{y_t\}$. The goal in section will be to find a large polyhedron $\mathcal{P}$ for which we can verify that this is true.

Linear approximations of ReLU As reasoning about neural network constraints directly is often intractable, given bounds $l_{i,j} \leq z_{i,j}^a \leq u_{i,j}$, the *triangle approximation* (Ehlers, 2017) relaxes the ReLU constraints such that all involved inequalities are linear:

$$z_{i,j}^r \geq z_{i,j}^a, \quad z_{i,j}^r \geq 0,$$
$$z_{i,j}^r \leq \lambda_{i,j} \cdot z_{i,j}^a + \mu_{i,j}.$$

Figure 3 (a) visualizes the triangle approximation. Here, $\lambda_{i,j} = u_{i,j}/(u_{i,j} - l_{i,j})$ and $\mu_{i,j} = -l_{i,j} \cdot u_{i,j}/(u_{i,j} - l_{i,j})$ are selected such that this set of constraints describes the convex hull of the ReLU constraints in the $(z_{i,j}^a, z_{i,j}^r)$-plane and the given bounds.

Figure 3: Convex approximations for the ReLU function: (a) shows the triangle approximation Ehlers (2017) with the minimum area in the input-output plane, (b) and (c) show the two convex approximations used in DeepPoly Singh et al. (2019). In the figure, $\lambda_{i,j} = u_{i,j}/(u_{i,j} - l_{i,j})$ and $\mu_{i,j} = -l_{i,j} \cdot u_{i,j}/(u_{i,j} - l_{i,j})$.

The DeepPoly approximation (Singh et al., 2019) further relaxes the triangle approximation by keeping only one of the lower bounds on each variable $z_{i,j}^r$. It picks either $z_{i,j}^r \geq z_{i,j}^a$ or $z_{i,j}^r \geq 0$, whichever minimizes the area of the resulting triangle in the $(z_{i,j}^a, z_{i,j}^r)$-plane. Figure 3 (b) and (c) show the two convex relaxations used in DeepPoly.

We can obtain $l_{i,j}$ and $u_{i,j}$ by optimizing each component of $z_{i,j}^a$ according to the previously determined constraints for layers $0, \ldots, i$. We note that in the special case where $u_{i,j} \leq 0$ or $l_{i,j} \geq 0$, no approximation is needed and $z_{i,j}^r$ is directly assigned 0 or $z_{i,j}^a$, respectively. Neurons for which the approximation is needed are called *undecided*.

Computing neuron bounds   Most verification algorithms based on convex relaxation start with a chosen input region for which they calculate the bounds $l_{i,j}$ and $u_{i,j}$ of $z_{i,j}^a$ in layer-by-layer fashion, where the constraints for previous layers are used to derive the bounds for layer i. In addition to DeepPoly and the triangle approximation, this is also true for other commonly used convex relaxation algorithms such as CROWN (Zhang et al., 2018) and DeepZ (Singh et al., 2018a).

Next, we briefly describe how the bounds are computed for a particular layer in DeepPoly. We focus on DeepPoly since it is the particular convex relaxation algorithm we chose to employ in this section. For all neurons, DeepPoly stores a single linear lower and upper bound inequality. These inequalities bound the neuron's value in terms of the values of neurons from previous layers in the network. For ReLU neurons, these are the inequalities described above. For affine neurons, these are simply the affine transformations, where the affine equality is converted to a pair of inequalities.

To arrive at the bounds $l_{i,j}$ and $u_{i,j}$ of $z_{i,j}^a$, DeepPoly repeatedly backsubstitutes variables in the linear inequalities of $z_{i,j}^a$ with their corresponding linear inequalities from previous layers. The process continues until we arrive at linear inequalities $L_{i,j}(z_0^r) \leq z_{i,j}^a \leq U_{i,j}(z_0^r)$, with $L_{i,j}(x) = \underline{a}_{i,j} \cdot x + \underline{b}_{i,j}$ and $U_{i,j}(x) = \overline{a}_{i,j} \cdot x + \overline{b}_{i,j}$ denoting linear functions in terms of input variables $x \in \mathbb{R}^{n_0}$ with coefficients $\underline{a}_{i,j}, \overline{a}_{i,j} \in \mathbb{R}^{n_0}$ and $\underline{b}_{i,j}, \overline{b}_{i,j} \in \mathbb{R}$. The final bounds $l_{i,j}$ and $u_{i,j}$ are obtained by optimizing the respective functions $L_{i,j}(x)$ and $U_{i,j}(x)$ over the input region.

We note that our algorithm does not depend on details of DeepPoly's backsubstitution algorithm: It only requires the existence of linear functions $L_{i,j}(x)$ and $U_{i,j}(x)$ bounding neuron values $z_{i,j}^a$ in terms of input activations. This makes it compatible with other popular verification algorithms based on convex relaxation, such as CROWN (Zhang et al., 2018) and DeepZ (Singh et al., 2018a).

Certification Objective   To certify the robustness of an input region, $\mathbb{V}$ needs to certify that $\min(z_{l,y_t}^a - z_{l,y}^a) > 0$ for all $y \in \{1, \ldots, n_l\} \setminus \{y_t\}$. To calculate lower bounds on those minima, a common trick is to introduce an affine layer that computes the objectives $z_{l,y_t}^a - z_{l,y}^a$ for each y. We will refer to this layer as objective layer. To obtain lower bounds on our objectives, we compute lower bounds of the corresponding neuron activations in the objective layer with the usual backsubstitution procedure.

Algorithm 3 GEN_POLY

1: **func** GEN_POLY(f, $\mathcal{U}$, $\mathcal{O}$, $\mathbb{V}$, y_t, p_{it})
2:     $\mathcal{P}_0 = \mathcal{O}$
3:     **for** it $\in \{1, 2, \ldots, p_{\text{it}}\}$ **do**
4:         hs $_o$, Ver = Gen_Obj_Planes(f, $\mathcal{U}$, $\mathcal{P}_{\text{it}-1}$, $\mathbb{V}$, y_t)
5:         hs $_b$ = Gen_Bound_Planes(f, $\mathcal{U}$, $\mathcal{P}_{\text{it}-1}$, $\mathbb{V}$)
6:         $\mathcal{P}_{\text{it}}$ = Add_Planes($\mathcal{P}_{\text{it}-1}$, hs $_b$ $\cup$ hs $_o$)
7:         **if** Ver **then**
8:             **return** $\mathcal{P}_{\text{it}-1}$
9:         **end if**
10:     **end for**
11:     **return** FailedToConverge
12: **end func**

For the rest of the section we will denote the backsubstituted linear lower bounds on our objectives in terms of input activations for a given target y_t with $L_{l+1,y}(x) = \underline{a}_{l+1,y} \cdot x + \underline{b}_{l+1,y}$ for each y. Finally, to verify that $\min(z_{l,y_t}^a - z_{l,y}^a) > 0$, it suffices to show that $L_{l+1,y}(x) > 0$ for each point x in the input region. We note that the function denoted $L_{l+1,y}(x)$ in this section corresponds to the function denoted $L_y(x)$ in the main body.

C.2 COMPUTING $\mathcal{P}$

The algorithm for computing $\mathcal{P}$ is presented in Algorithm 3. It takes as input:

- The neural network f, as described in Section C.1.
- The underapproximation hyperbox $\mathcal{U}$.
- The overapproximation hyperbox $\mathcal{O}$.
- A neural network certification method $\mathbb{V}(f$, $\mathcal{P}_{\text{it}-1}$, i, j) that takes a neural network f, a polyhedron $\mathcal{P}_{\text{it}-1}$ at iteration it $- 1$, the layer number i and the neuron number j and returns the linear functions $L_{i,j}(x)$ and $U_{i,j}(x)$ and the corresponding concrete bounds $l_{i,j}$ and $u_{i,j}$ (See Section C.1).
- The adversarial attack's target class y_t.
- The maximum number p_{it} of iterations used to generate the polyhedron $\mathcal{P}$.

The algorithm computes $\mathcal{P}$, such that $\mathcal{U} \subseteq \mathcal{P} \subseteq \mathcal{O}$ is satisfied. We motivate this choice by noting that we know that $\mathcal{U}$ is certifiably robust and it is therefore a lower bound on $\mathcal{P}$. The algorithm generates a sequence of polyhedra $\mathcal{P}_0 \supseteq \mathcal{P}_1 \supseteq \ldots \supseteq \mathcal{P}_p$ with $\mathcal{P}_0 = \mathcal{O}$. At each iteration, it computes two sets of half-space constraints – hs $_o$(Line 4) and hs $_b$(Line 5), corresponding to the neurons in the objective and the affine layers of the network. We detail how these constraints are computed in the next two paragraphs. We add these constraints to the polyhedron from the last iteration $\mathcal{P}_{\text{it}-1}$ to obtain $\mathcal{P}_{\text{it}}$ (Line 6). The algorithm terminates when $\mathcal{P}_{\text{it}-1}$ is certified to be robust (Line 7 – Line 9) and $\mathcal{P}_{\text{it}-1}$ is returned. The result of our algorithm is represented by the red region denoted as $\mathcal{P}$ in Step 3 in Figure 2. We note that, since $\mathcal{P}_0 = \mathcal{O}$, $\mathcal{P} \subseteq \mathcal{O}$ is guaranteed by construction, as each subsequent iteration of the algorithm shrinks the polyhedron further. However, $\mathcal{U} \subseteq \mathcal{P}$ depends on the choice of the half-space constraints.

Generating Certification Objective Constraints   Algorithm 4 details the procedure we use to collect the half-space constraints corresponding to the objective layer of the network. To obtain constraints from $\mathbb{V}$, we collect $L_{l+1,y}(x) \geq 0$ for all output classes $y \in \{1, \ldots, n_l\} \setminus \{y_t\}$ (Line 5). We know that adding these hyperplanes to our polyhedron $\mathcal{P}_{\text{it}-1}$ will result in a certifiably robust region $\mathcal{P}_{\text{it}}$, however the region will not obey $\mathcal{U} \subseteq \mathcal{P}_{\text{it}}$. Therefore, we adjust the bias of constraints, so that the hyperplanes $L_{l+1,y}(x) = 0$ do not intersect $\mathcal{U}$ (Line 8). This will be described in more detail below.

All resulting bias-adjusted hyperplanes are collected in the set hs $_o$ (Line 9) and returned. We note that if $l_j > 0$, the half-spaces $L_{l+1,y}(x) \geq 0$ are trivial. That is $\{L_{l+1,y}(x) \geq 0\} \cap \mathcal{P}_{\text{it}-1} = \mathcal{P}_{\text{it}-1}$, and thus they are filtered out of hs $_o$ (Line 6). In addition to detecting the trivial constraints, we use l_j to check if $\mathcal{P}_{\text{it}-1}$ is certifiably robust and return the result alongside hs $_o$ in Line 11.

Algorithm 4 GEN_OBJ_PLANES

1: **func** GEN_OBJ_PLANES(f, $\mathcal{U}$, $\mathcal{P}_{\text{it}-1}$, $\mathbb{V}$, y_t)
2:     hs$_o$ = []
3:     Ver = True
4:     **for** $j \in \{1, \ldots, n_l\} \setminus \{y_t\}$ **do**
5:         $L_{l+1,j}(x)$, _, l_j, _ = $\mathbb{V}(f, \mathcal{P}_{\text{it}-1}, l+1, j)$
6:         **if** $l_j \leq 0$ **then**
7:             Ver = False
8:             $\tilde{L}_{l+1,j}(x)$ = Adjust_Bias($\mathcal{U}$, $L_{l+1,j}(x)$)
9:             hs$_o$ += [$\tilde{L}_{l+1,j}(x) \geq 0$]
10:        **end if**
11:    **end for**
12:    **return** hs$_o$, Ver
13: **end func**

Algorithm 5 GEN_BOUND_PLANES

1: **func** GEN_BOUND_PLANES(f, $\mathcal{U}$, $\mathcal{P}_{\text{it}-1}$, $\mathbb{V}$)
2:     hs$_b$ = []
3:     **for** $i \in \{1, 2, \ldots, l-1\}$ **do**
4:         **for** $j \in \{1, 2, \ldots, n_i\}$ **do**
5:             $L_{i,j}(x), U_{i,j}(x), l_{i,j}, u_{i,j} = \mathbb{V}(f, \mathcal{P}_{\text{it}-1}, i, j)$
6:             **if** $l_{i,j} \leq 0$ **and** $u_{i,j} \geq 0$ **then**
7:                 $\tilde{L}_{i,j}(x)$ = Adjust_Bias($\mathcal{U}$, $L_{i,j}(x)$)
8:                 $\tilde{U}_{i,j}(x)$ = Adjust_Bias($\mathcal{U}$, $-U_{i,j}(x)$)
9:                 hs$_b$ += [$\tilde{L}_{i,j}(x) \geq 0$, $\tilde{U}_{i,j}(x) \geq 0$]
10:            **end if**
11:        **end for**
12:    **end for**
13:    **return** hs$_b$
14: **end func**

Issues Related to Using Only Objective Constraints   In our experiments, we found that only adding bias-adjusted objective constraints leads to slow convergence of our algorithm. In particular, we found that the first few iterations of the algorithm result in a substantial improvement in the certification objective. However, after this initial fast progress, we observe that the change in the certification objective becomes very small. The reason for this is that the generated constraints from consecutive executions of $\mathbb{V}$ are very similar. We conjecture that the underlying reason is that the constraints no longer change the input shape enough to substantially change the convex approximation of the network. This is in contrast to what we observe when computing the underapproximation hyperbox region $\mathcal{U}$. The difference between the two settings comes from the number of added constraints per iteration. For $\mathcal{U}$, usually many lower and upper bounds are adjusted each iteration, while the objective constraints added are much less, especially for the pixel intensity changes experiment, where the input is very high-dimensional.

Generating Constraints from Affine Layers   To facilitate faster convergence, we generate additional constraints for all undecided neurons in the network. We generate two constraints, one with respect to the lower bound of the neuron $L_{i,j}(x) \geq 0$ and one with respect to the upper bound $U_{i,j}(x) \leq 0$. Algorithm 5 describes the process. $L_{i,j}(x)$ and $U_{i,j}(x)$ are computed by $\mathbb{V}$ (Line 5) alongside their concrete bounds $l_{i,j}$ and $u_{i,j}$. The concrete bounds are used to check which neurons are undecided (Line 6).

The generated constraints have the effect of making the neurons decided and, while also enforcing substantial change in the convex relaxation of the neural network. Note that the newly obtained constraints are bias-adjusted similar to the objective constraints described above (Line 7–Line 8). We point out that the bias adjustment described below takes care of the problem that $L_{i,j}(x) \geq 0$ and $U_{i,j}(x) \leq 0$ cannot be simultaneously true. Empirically, these hyperplanes serve an important role for improving the convergence rate of our algorithm. Algorithm 5 collects them in the set hs$_b$ (Line 9) and returns them to be added to $\mathcal{P}_{\text{it}-1}$.

Algorithm 6 ADJUST_BIAS

1: **func** ADJUST_BIAS($\mathcal{U}$, $h(x)$)
2:    $h_{\min} = \min\limits_{x \in \mathcal{U}}(h(x))$
3:    $b_{\text{adj}} = \min(0, h_{\min})$
4:    $\tilde{h}(x) = h(x) - b_{\text{adj}}$
5:    **return** $\tilde{h}(x)$
6: **end func**

Hyperplane bias adjustment So far, we have discussed how constraints are generated but not how we adjust their biases. The bias adjustment algorithm is given in Algorithm 6. The bias adjustment for a lower bound constraint $h(x) \geq 0$ enforces that the intersection of the constraint and the given underapproximation hyperbox $\mathcal{U}$ is $\mathcal{U}$. It does so by computing $h_{\min} = \min\limits_{x \in \mathcal{U}}(h(x))$ (Line 2) and changing the given constraint to $h(x) \geq h_{\min}$ (Line 4). The optimization $h_{\min} = \min\limits_{x \in \mathcal{U}}(h(x))$ is analytically solvable, as demonstrated Section 4.2. Note that our algorithm adjusts only the constraints with negative $h_{\min}$ (Line 3), since constraints with positive $h_{\min}$ already satisfy the property. The following lemma shows the soundness of our bias-adjustment algorithm:

Lemma C.1. *The intersection of the bias-adjusted half-space constraint $\tilde{h}(x) \geq 0$ defined in Algorithm 6 with $\mathcal{U}$ is $\mathcal{U}$.*

Proof. By the construction of $h_{\min}$, for all points $x \in \mathcal{U}$ we have $h(x) \geq h_{\min}$. We distinguish two cases for the value of $h_{\min}$ — non-negative and negative.

If $h_{\min} \geq 0$, the bias adjustment b_{adj} is assigned to 0 and $\tilde{h}(x) = h(x)$. Since $h(x) \geq h_{\min}$ for all points $x \in \mathcal{U}$, $\tilde{h}(x) = h(x) \geq h_{\min} \geq 0$ for all points $x \in \mathcal{U}$. Therefore, there does not exist point in $\mathcal{U}$ for which the bias-adjusted half-space constraint $\tilde{h}(x) \geq 0$ is violated. If $h_{\min} < 0$, the bias adjustment b_{adj} is assigned to $h_{\min}$ and $\tilde{h}(x) = h(x) - h_{\min}$. Therefore, $\tilde{h}(x) = h(x) - h_{\min} \geq h_{\min} - h_{\min} = 0$ for all points $x \in \mathcal{U}$. Analogously to the other case, $\tilde{h}(x) \geq 0$ is not violated by the points in $\mathcal{U}$. $\qquad\square$

The bias adjustment for upper bound constraints $h(x) \geq 0$ is achieved by calling Algorithm 6 with $-h(x)$, as in Line 8 in Algorithm 5. Geometrically, the bias adjustment is represented at Step 2 in Figure 2.

Adapting DeepPoly to Polyhedral Input Regions Out of the box DeepPoly only handles certification of hyperbox input regions. This is because in order to obtain the concrete bounds $l_{i,j} = \min_{x \in \mathcal{I}} L_{i,j}(x)$ and $u_{i,j} = \max_{x \in \mathcal{I}} U_{i,j}(x)$ for an input region $\mathcal{I} \subseteq \mathbb{R}^{n_0}$ it uses the analytical solution of the optimization problems discussed in §sec:lpshrink. In order to use DeepPoly for polyhedral region $\mathcal{I}$, we solve the optimization problem using an Linear Program (LP). This is computationally expensive – it involves solving two LP instances per neuron. For large networks, this can be prohibitive.

To alleviate this issue, in the first iteration of Algorithm 3, we remember which neurons are undecided. The computation of the undecided neurons in the first iteration can be done using regular DeepPoly, as $\mathcal{P}_0 = \mathcal{O}$. In future iterations we solve the LP instances only for the undecided neurons, while using the $\mathcal{P}_0$ bounds for the decided neurons. This optimization is sound, since we have $\mathcal{P}_{\text{it}} \subseteq \mathcal{P}_{\text{it}-1}$ by construction. This improves the performance substantially – for most certifiably robust input regions in ReLU-based networks we have just a few undecided neurons.

Proving that $\mathcal{P}$ constraints $\mathcal{U}$ and is contained within $\mathcal{O}$ In this paragraph, we present a proof for the desired property of Algorithm 3 that $\mathcal{P}$ constraints $\mathcal{U}$ and is contained within $\mathcal{O}$.

Theorem C.2. *For all polyhedral regions $\mathcal{P}$ generated by Algorithm 3, $\mathcal{U} \subseteq \mathcal{P} \subseteq \mathcal{O}$ holds.*

Proof. Here we briefly outline the proof of Theorem C.2. The proof is divided into two parts. We first prove that $\mathcal{P} \subseteq \mathcal{O}$ and then $\mathcal{U} \subseteq \mathcal{P}$.

To prove $\mathcal{P} \subseteq \mathcal{O}$ we leverage the fact that the polyhedra $\mathcal{P}$ is constructed from the overapproximation box $\mathcal{O}$ by intersecting it with the half-space constraints hb_b^i and hb_o^i. Since all constraints only reduce the volume of the polyhedra, it follows by induion that $\mathcal{P}_i \subseteq \mathcal{O}$ for all i. Therefore, $\mathcal{P} \subseteq \mathcal{O}$.

To prove $\mathcal{U} \subseteq \mathcal{P}$ we note that the generated half-space constraints hb_b and hb_o are chosen such that $hb_b \cap \mathcal{U} = \mathcal{U}$ and $hb_o \cap \mathcal{U} = \mathcal{U}$ (See Lemma C.1). Applying this property by induction over the generated half-space constraints, it follows that $\mathcal{U}_i \subseteq \mathcal{P}$ for all i. Therefore, $\mathcal{U} \subseteq \mathcal{P}$ □

C.3 Convergence of the Underapproximation Region Algorithm

In this section, we demonstrate that Algorithm 1 converges exponentially fast under a suitable assumption for the monotonicity of the neural network certification method $\mathbb{V}$. To this end, we introduce the following definition of monotonicity of $\mathbb{V}$, that we will leverage for the rest of the section.

Definition 4. *Let* $\mathbb{V}(f, \mathcal{I}, y_t)$ *be a neural network certification method that returns the certification objective* $L^{\mathcal{I}}(x)$ *for an input region* $\mathcal{I}$ *and target* y_t *on the neural network* f. *We call* $\mathbb{V}$ *objective-monotonic if for all* f *and input regions* $\mathcal{X}$ *and* $\mathcal{Y}$ *with* $\mathcal{X} \subseteq \mathcal{Y}$ *the property:*

$$\min_{x \in \mathcal{X}} L^{\mathcal{X}}(x) \geq \min_{x \in \mathcal{X}} L^{\mathcal{Y}}(x)$$

is satisfied.

Intuitively, Definition 4 states that a verifier is objective-monotonic if the certification objective produced for a smaller region $\mathcal{X}$ is always higher (closer to verification) than the certification objective produced for a bigger region $\mathcal{Y}$, when both of them are optimized over the smaller region $\mathcal{X}$.

We note that most practical neural network certification methods, including DeepPoly, are not objective-monotonic — that is one can find triples f, $\mathcal{X}$ and $\mathcal{Y}$ violating the definitions above. However, in practice we find that for all practical neural network certification methods the definitions hold for most triples. This is expected, as for violating triples we know that the overapproximation generated for $\mathcal{X}$ needs to be larger than the one generated for $\mathcal{Y}$. Intuitively, if that was the case for a large portion of the triples, the certification method will not be tight.

Next, we leverage this defition to demonstrate that our algorithm converges exponentially fast under the idealized condition that the certification method used is objective-monotonic.

Theorem C.3. *For objective-monotonic certification methods* $\mathbb{V}$ *in Algorithm 1, the certification error at the* i-*th iteration* e^i *converges exponentially fast towards* 0 *(towards certification).*

Proof. To prove Theorem C.3, we will leverage the definition of objective-monotonic certification method above to bind the certification error between consequitive iterations of Algorithm 1. We will then use the bound to derive a bound on the certification error e^i in terms of the intial certification error e^0. Finally, we will use the bound to show the exponential convergence.

Since $\mathcal{U}_i \subseteq \mathcal{U}_{i-1}$, we can apply Definition 4 to get the inequality:

$$\min_{x \in \mathcal{U}_i} L^i(x) \geq \min_{x \in \mathcal{U}_i} L^{i-1}(x).$$

By construction of $\mathcal{U}_i$, we further know:

$$\min_{x \in \mathcal{U}_i} L^{i-1}(x) \geq -p_{i-1} = e^{i-1} \cdot c.$$

Combining both inequalities and noting that $e^i = \min_{x \in \mathcal{U}_i} L^i(x)$, we get:

$$e^i \geq e^{i-1} \cdot c. \tag{2}$$

Since equation 2 holds for all i, we can apply it recursively on its right-hand side to get:

$$e^i \geq e^0 \cdot c^i. \tag{3}$$

We recall that e^i is negative unless $\mathcal{U}_i$ verifies. Therefore by equation 3, e^i converges exponentially fast towards 0, regardless of e^0. □

D   VISUALISATION OF ROBUST ADVERSARIAL EXAMPLES

D.1   DISCUSSION

Figure 4: Adversarial region robust to pixel intensity changes.

Figure 4 shows an adversarial region provably robust to intensity changes containing 10^{284} adversarial images produced by our method on MNIST ConvBig. The original image is of the digit 5, and all images in our region are classified as 3 by the network. The colorbar in Figure 4 quantifies the number of values each pixel can take in our inferred region. The yellow and violet colors represent the two extremes. The intensity of the yellow-colored pixels can vary the most, thus these pixels contribute to more adversarial examples. The intensity of the purple-colored varies the least, thus the adversarial examples in our region are sensitive to the intensity values of these pixels. In our region, the intensity of most background pixels on the edges of the image can vary a lot, as these are green. Violet and green color are more evenly distributed among pixels closer to the foreground (part of the digit "5"). Further, the intensity of several pixels in the foreground can also vary significantly. We note that all yellow pixels occur in the foreground. In summary, our region can capture examples that can be generated by significant variations in the intensities of several background and foreground pixels. We supply visualizations for all of the experiments described in Section 5.1 and 5.2 in Appendix D.

D.2   ADVERSARIAL EXAMPLES ROBUST TO INTENSITY CHANGES

In Figure 5 – Figure 8 we visualise adversarial examples provably robust to pixel intensity changes for the different networks in Table 1. For all figures, the colorbar on the right-hand side quantifies the number of values each pixel can take in our inferred region. The yellow and violet colors represent the two extremes. The intensity of the yellow-colored pixels can vary the most, thus these pixels contribute more to the adversarial examples.

In Figure 5 we show adversarial examples for the MNIST `ConvBig` network. The 3 sub-figures represent the digits 9, 5, and 3, but the images in our regions are classified as 4, 3, and 8, respectively. Our regions are of size 10^{220}, 10^{284}, and 10^{262}, respectively.

In Figure 5 we show adversarial examples for the MNIST `ConvSmall` network. The 3 sub-figures represent the digits 2, 9, and 9, but the images in our regions are classified as 3, 5, and 4, respectively. Our regions are of size 10^{520}, 10^{652}, and 10^{708}, respectively.

In Figure 7 we show adversarial examples for the MNIST 8×200 network. The 3 sub-figures represent the digits 5, 9, and 2, but the images in our regions are classified as 8, 8, and 3, respectively. Our regions are of size 10^{148}, 10^{128}, and 10^{157}, respectively.

| (a) | (b) | (c) |

Figure 5: Sensitivity of probably robust adversarial examples based on pixel intensity changes on the MNIST `ConvBig` network.

| (a) | (b) | (c) |

Figure 6: Sensitivity of probably robust adversarial examples based on pixel intensity changes on the MNIST `ConvSmall` network.

| (a) | (b) | (c) |

Figure 7: Sensitivity of probably robust adversarial examples based on pixel intensity changes on the MNIST 8×200 network.

In Figure 8 we show adversarial examples for the CIFAR10 `ConvSmall` network. The 3 sub-figures represent a boat, a bird, and another bird, but the images in our regions are classified as an airplane , a frog, and a dog, respectively. Our regions are of size 10^{626}, 10^{563}, and 10^{608}, respectively.

| (a) | (b) | (c) |

Figure 8: Sensitivity of probably robust adversarial examples based on pixel intensity changes on the CIFAR10 `ConvSmall` network.

D.3 ADVERSARIAL EXAMPLES ROBUST TO GEOMETRIC CHANGES

In Figure 9 – Figure 11 we visualise adversarial examples provably robust to geometric perturbations for the different networks in Table 2. For all figures, the colorbar on the right-hand side quantifies the number of values each pixel can take in our inferred region. The yellow and violet colors represent the two extremes. The intensity of the yellow-colored pixels can vary the most, thus these pixels contribute more to the adversarial examples. For all figures, the subfigures represent an adversarial example for each of the rows in Table 2.

In Figure 9 we show adversarial examples for the MNIST `ConvBig` network. The 3 sub-figures represent the digits 6, 1, and 3, but the images in our regions are classified as 5, 8, and 7, respectively. Our regions have underapproximations of size 10^{159}, 10^{183}, and 10^{13}, respectively.

(a)   (b)   (c)

Figure 9: Sensitivity of probably robust adversarial examples based on geometric perturbations. Subfigures (a), (b) and (c) correspond to the first, second, and third geometric perturbations for the MNIST `ConvBig` network in Table 2, respectively.

In Figure 10 we show adversarial examples for the MNIST `ConvSmall` network. The 3 sub-figures represent the digits 6, 1, and 3, but the images in our regions are classified as 5, 8, and 7, respectively. Our regions are of size 10^{115}, 10^{82}, and 10^{63}, respectively.

(a)   (b)   (c)

Figure 10: Sensitivity of probably robust adversarial examples based on geometric perturbations. Subfigures (a), (b) and (c) correspond to the first, second, and third geometric perturbations for the MNIST `ConvSmall` network in Table 2, respectively.

In Figure 11 we show adversarial examples for the CIFAR10 `ConvSmall` network. The 3 sub-figures represent a dog, a truck, and a frog, but the images in our regions are classified as a frog, an automobile, and a deer, respectively. Our regions are of size 10^{1422}, 10^{1270}, and 10^{1505}, respectively.

(a)   (b)   (c)

Figure 11: Sensitivity of probably robust adversarial examples based on geometric perturbations. Subfigures (a), (b) and (c) correspond to the first, second and third geometric perturbations for the CIFAR10 `ConvSmall` network in Table 2, respectively.