AlphaZero in Sparsely Rewarded Games: Limits and Auxiliary Supervision

Brent Kong   BKONG@CALTECH.EDU
Tejas Ram   TRAM@CALTECH.EDU
Tony Yue Yu   TYY@CALTECH.EDU
California Institute of Technology, US

Abstract

AlphaZero has demonstrated that a neural-guided Monte Carlo Tree Search can achieve superhuman performance, but strong play does not necessarily imply perfect play. We study this gap in two oracle-evaluable domains with contrasting structure: Connect Four, a solved partisan game with exact game-theoretic values, and Chomp, an impartial game whose optimal play is governed by Grundy-number structure. Under a unified self-play + MCTS pipeline, we compare vanilla AlphaZero, a multi-frame variant (limited to Chomp), and an AlphaZero Auxiliary Loss (AZAL) that adds oracle-derived policy supervision. We find that vanilla AlphaZero achieves strong play across both domains but cannot preserve the exact trajectories required for optimal play: in Connect Four, it fails to maintain the optimal line of play, while in Chomp, it fails to consistently restore the $g = 0$ invariant. On rectangular Chomp boards, multi-frame inputs alone do not remove this gap. Nevertheless, AZAL substantially improves oracle consistency across multi-seeded full-game traces and sampled-state evaluations. On Chomp, AZAL reaches perfect full-game oracle consistency on 10×11 and high but not complete consistency on 9×10; on Connect Four, AZAL improves oracle-match rate and delays the first oracle mistake, but does not reach perfect play. Our codes can be found at: https://anonymous.4open.science/r/AlphaZero-Auxiliary-Loss-F74E/readme.md

Keywords: AlphaZero, Monte Carlo Tree Search, self-play reinforcement learning, game-theoretic learning, oracle evaluation, perfect play

1. Introduction

AlphaZero established the Monte Carlo Tree Search (MCTS) as a central paradigm in modern game AI. Building on the broader ideas of planning and generalization, AlphaGo Zero showed that search can be embedded directly into the reinforcement learning loop, improving policy targets while self-play supplies value supervision [2, 8]. AlphaZero then generalized this recipe across Go, chess, and shogi, illustrating that a single policy–value network guided by MCTS can achieve superhuman play from random initialization, provided only the rules of the game [9].

Yet superhuman play is not identical to perfect play. An AlphaZero-style system may achieve excellent results from the standard starting position while fail to choose the optimal move. This distinction has become especially important in games that depend on sparse global features and not dense local tactics. In such settings, errors in policy and value estimation do not remain isolated: they affect the search targets used to generate future self-play data. This weakens the positive feedback loop on which AlphaZero depends [7, 11].

This paper analyzes the gap between strong play and perfect play through two contrasting domains: Connect Four and Chomp. Connect Four is a solved partisan game with exact game-

theoretic values, allowing direct comparison to winning trajectories [1]. By contrast, Chomp is an impartial combinatorial game whose winning structure is naturally studied through Grundy numbers [5, 10]. Despite classical theoretical results, the explicit optimal strategies of Chomp remain difficult to characterize [3, 4]. Together, these games provide a useful test of whether AlphaZero fails to recover exact play across games with very different strategic structure.

We provide an empirical study of AlphaZero-style learning on both domains under a standard self-play + MCTS pipeline. We evaluate vanilla AlphaZero against exact oracles, compare it with a multi-frame variant inspired by [7] (limited to Chomp), and introduce an AlphaZero Auxiliary Loss (AZAL) variant designed to provide a stronger learning signal. Across both domains, multi-seed and sampled-state oracle evaluations reveal that vanilla AlphaZero remains far from exact oracle consistency. Multi-frame inputs do not resolve the Chomp rectangular-board failure in our experiments. AZAL substantially improves oracle consistency, achieving perfect full-game consistency on Chomp 10×11, high but incomplete consistency on Chomp 9×10, and decent but still imperfect improvement on Connect Four.

Our contributions are as follows:

1. We show that vanilla AlphaZero can learn strong self-play policies without routinely recovering oracle-consistent play in Connect Four and Chomp, as measured by exact oracle evaluation over multi-seed full-game traces and randomly sampled states.

2. We compare two possible remedies under a unified self-play + MCTS framework: a multi-frame representation (for Chomp) and an auxiliary-loss variant, AZAL.

3. We find that AZAL substantially improves oracle consistency across full-game and sampled-state evaluations, especially in Chomp, suggesting the standard AlphaZero search-learning signal is a plausible bottleneck for recovering exact play.

2. Problem Setting and Oracle Evaluation

Our goal is to study the disparity between *superhuman* and *perfect* play in AlphaZero-style agents. We do so in two oracle-evaluable domains with contrasting structure: Connect Four and Chomp. In both games, the oracle allows us to assess if the learned agent preserves the trajectories required by optimal play.

In this paper, we distinguish between *superhuman* and *perfect* play. By superhuman play, we mean empirical performance that exceeds strong practical baselines or human-level play. By perfect play, we mean selecting an optimal move from every legal state, as judged by an exact solver or oracle. This distinction is central to our study: an AlphaZero-style agent may achieve high win rates but fail to preserve the oracle-optimal trajectories required for exact play. In Connect Four, both players can be evaluated against exact game-theoretic value, whereas in Chomp, players are evaluated by their ability to preserve the winning invariant by moving to $g = 0$ states.

For Connect Four, we use the perfect solver of Pascal Pons [6]. Since Connect Four is a partisan game, the natural oracle quantity is an exact *game-theoretic score*. For Chomp, we use a recursive *Grundy-number solver*. Because Chomp is an impartial normal-play game, every state s admits a Grundy number $g(s) \in \mathbb{N}$, with $g(s) = 0$ if and only if the position is losing for the player to move [5, 10]. From any winning position $(g(s) \neq 0)$, an optimal move is one that reaches a successor with Grundy number zero.

3. Methods

We compare three closely related AlphaZero-style agents: vanilla AlphaZero, a multi-frame variant (restricted to Chomp), and AlphaZero-Auxiliary Loss (AZAL). In all cases, self-play games are generated with MCTS guided by a policy–value network, replay tuples are collected from those games, and the network is updated from search-improved policy targets and game outcomes. The methods therefore differ only in the representation provided to the network and in the strength of the supervision signal.

Vanilla AlphaZero. Our baseline follows the standard AlphaZero recipe [9]: a policy–value network is trained from self-play data, where MCTS produces improved policy targets and terminal outcomes provide value targets. The policy is learned only through search-improved self-play.

Multi-frame AlphaZero. To test if the main bottleneck derives from state representation, we evaluate a multi-frame variant inspired by Riis [7]. The training loop, search procedure, and optimization objective are identical to vanilla AlphaZero; the only difference is that the network receives a short stack of recent states instead of a single board snapshot. We therefore treat multi-frame AlphaZero as a representation ablation rather than a distinct learning algorithm.

AlphaZero-Auxiliary Loss (AZAL). To strengthen the training signal, AZAL augments the standard AlphaZero objective with an oracle-derived auxiliary policy loss:

$$\mathcal{L} = \mathcal{L}_{\text{policy}} + \mathcal{L}_{\text{value}} + \lambda_{\text{aux}}\mathcal{L}_{\text{aux}}.$$

This auxiliary term favors oracle-consistent actions during training, but leaves self-play, MCTS, and value targets unchanged. Thus, AZAL is a minimal modification of vanilla AlphaZero that changes supervision, not search.

Experimental protocol. All methods use the same self-play + MCTS loop and search budget, so comparisons distinguish the effects of representation and supervision rather than changes in compute or replay generation. Evaluation uses exact oracles: the perfect solver in Connect Four and the Grundy oracle in Chomp. In addition to aggregate losses, we analyze deterministic self-play trace rollouts and evaluate them with exact oracle annotations to distinguish strong empirical play from exact optimality. Only the final checkpoints are evaluated; checkpoint sensitivity is left for future work.

Trace-level metrics. To summarize oracle alignment compactly, we report three shared trace-level metrics: *oracle-match rate* (Match), the fraction of oracle-labeled moves that lie in the oracle-optimal action set, and the *longest oracle-consistent chain* (Chain), defined as the longest contiguous run of oracle-consistent moves within the rollout, and *first non-oracle ply* (FirstFail), defined as the first move that does not follow oracle supervision. The main aggregate trace-level metrics appear in Table 1, and representative trace panels are shown in Figure 1.

We report both aggregate and representative trace evaluations. The main full-game results aggregate 60 self-play traces across three seeds per model and game setting. We also report sampled-state oracle evaluation from random-start positions to test if the observed behavior persists beyond opening rollouts. Sample states are generated from random legal moves and sampled across three seeds. They are evaluated only when an oracle-best moveset is defined, evaluating behavior beyond the standard opening rollout.

Table 1: Multi-seed full-game oracle consistency across model variants. Each row aggregates 60 full-game self-play traces across three seeds. Perfect denotes the fraction of traces with no labeled oracle mistake. Match denotes pooled oracle-match rate over all labeled plies. Chain denotes the mean longest oracle-consistent chain per trace. FirstFail denotes the mean first labeled non-oracle ply, excluding perfect traces.

Game	Model	Traces	Perfect	Match	Chain	FirstFail
Chomp 9×10	Vanilla	60	0.000 (0/60)	0.609 (487/800)	7.867 ± 1.565	0.000 ± 0.000
	Multi-Frame	60	0.000 (0/60)	0.483 (272/563)	4.400 ± 1.846	0.000 ± 0.000
	AZAL	60	0.567 (34/60)	0.948 (1065/1123)	13.450 ± 2.801	11.923 ± 1.035
Chomp 10×11	Vanilla	60	0.000 (0/60)	0.474 (484/1021)	7.550 ± 1.175	0.000 ± 0.000
	Multi-Frame	60	0.000 (0/60)	0.463 (317/685)	5.217 ± 1.292	0.000 ± 0.000
	AZAL	60	1.000 (60/60)	1.000 (793/793)	13.217 ± 1.392	N/A
Connect Four	Vanilla	60	0.000 (0/60)	0.785 (1700/2165)	17.000 ± 8.325	0.867 ± 1.310
	AZAL	60	0.000 (0/60)	0.849 (1828/2153)	16.967 ± 5.335	5.283 ± 3.933

Table 2: Random-start sampled-state oracle evaluation. Positions denotes the number of sampled states evaluated across three seeds. Labeled denotes the number of sampled states with a defined oracle-best moveset. Match denotes pooled oracle-match rate over labeled sampled states. RunMean reports the mean and standard deviation of sampled-state match rate across evaluation runs.

Game	Model	Positions	Labeled	Match	RunMean
Chomp 9×10	Vanilla	36	34	0.500 (17/34)	0.481 ± 0.114
	Multi-Frame	36	34	0.176 (6/34)	0.171 ± 0.051
	AZAL	36	34	1.000 (34/34)	1.000 ± 0.000
Chomp 10×11	Vanilla	39	35	0.400 (14/35)	0.381 ± 0.135
	Multi-Frame	39	35	0.286 (10/35)	0.267 ± 0.134
	AZAL	39	35	0.829 (29/35)	0.816 ± 0.093
Connect Four	Vanilla	56	56	0.589 (33/56)	0.587 ± 0.147
	AZAL	56	56	0.768 (43/56)	0.769 ± 0.097

4. Vanilla AlphaZero: Strong Play Without Perfect Play

Vanilla AlphaZero learns a strong Connect Four policy but does not reliably recover oracle-consistent play. The main failure is an inability to *preserve* the optimal moveset. This distinction is clearest at the trace level.

Table 1 reinforces these trends. Although the baseline model's oracle-match rate is 0.785 (1700/2165), its first labeled failure occurs very early on average (0.867 ± 1.310), indicating that the model is unable to discern the correct opening move. Table 2 confirms the gap beyond the opening trace: the vanilla model matches the oracle on only 0.589 (33/56) of sampled Connect Four positions.

On the rectangular boards, the picture changes sharply across both representative traces and aggregate evaluations. Vanilla AlphaZero no longer reliably preserves the winning invariant, and the gap between strong and perfect play becomes immediate and structural rather than occasional.

From Table 1, vanilla AlphaZero matches the oracle 60.9% of the time on 9×10 and 47.4% on 10×11. The model's first failure occurs immediately on average: FirstFail = 0.000 on both boards. Sampled-state evaluation confirms a similar pattern (Table 2): the baseline model reaches a match rate of only 0.500 on 9×10 and 0.400 on 10×11.

5. Strengthening the Signal: Multi-frame and AZAL

The vanilla results suggest that the standard self-play signal may be too weak to recover exact play. We therefore examine two possible remedies. The first is a multi-frame representation motivated by prior work on impartial games [7]; the second is AlphaZero Auxiliary Loss (AZAL), which injects sparse oracle-derived supervision directly into training.

The multi-frame variant does not resolve the main failure of vanilla AlphaZero. The self-play traces and the trajectories in Figure 1(*b*)subfigure and (*c*)subfigure reveal that multi-frame AlphaZero still fails to preserve the winning invariant reliably.

From Table 1, Multi-frame AlphaZero performs inferior to its vanilla counterpart. On 9×10, Multi-frame is significantly worse than Vanilla in full-game match (0.483 vs. 0.609), while on 10×11, it matches the performance of the baseline (0.463 vs. 0.474). Multi-frame also has shorter mean chains than Vanilla on both boards, with an average chain of 4.400 on 9×10 and 5.217 on 10×11.

We evaluate multi-frame only on Chomp, so our multi-frame conclusion is restricted to the rectangular Chomp settings.

AZAL improves Connect Four oracle consistency, especially by increasing oracle-match rate and delaying the first oracle mistake, but it does not reach perfect play.

From Tables 1 and 2, AZAL improves full-game match from 0.785 to 0.849, increases sampled-state match from 0.589 to 0.768, and delays the first failure from 0.867 to 5.283. However, AZAL does not improve mean longest chain (16.967 vs. Vanilla 17.000) and has zero perfect traces. Thus, AZAL improves the density and timing of oracle-consistent decisions in Connect Four, but does not produce fully oracle-consistent play.

AZAL changes the Chomp results more dramatically than in Connect Four, with perfect full-game oracle consistency on 10×11 and high but incomplete consistency on 9×10.

On Chomp 10×11, AZAL achieves 60/60 perfect traces and a 1.000 (793/793) pooled oracle-match rate (Table 1). However, on Chomp 9×10, AZAL reaches 34/60 perfect traces and a 0.948 (1065/1123) match rate. On average, AZAL delays first failure on 9×10 to 11.923, while Vanilla and Multi-frame fail immediately on average.

(*a*) Connect Four trace panel.

(*b*) Chomp 9×10 trace panel.

(*c*) Chomp 10×11 trace panel.

Figure 1: Deterministic greedy-rollout trace panels across games. Filled markers denote oracle-consistent moves; hollow markers denote non-oracle moves.

6. Discussion and Conclusion

The central conceptual result of this paper is that *superhuman play is not the same as perfect play*. Across both Connect Four and Chomp, vanilla AlphaZero attains strong empirical behavior, yet the trace analysis shows that decisive failures occur earlier, where the agent must preserve a long-horizon value invariant.

We studied the gap between strong play and perfect play in AlphaZero-style agents using Connect Four and Chomp as complementary oracle-evaluable domains. Vanilla AlphaZero achieves strong play in both games, but it does not preserve the exact trajectories required for optimal play. In Connect Four, it is better at tracking correct tactical continuations than at preserving the winning trajectory from the start. In Chomp, it fails to consistently maintain the $g = 0$ invariant that characterizes optimal winning play.

We then showed that stronger supervision materially changes this picture. Multi-frame inputs alone do not resolve the rectangular Chomp failure, while AZAL substantially improves oracle consistency across multi-seed full-game traces and sampled-state evaluations. AZAL reaches perfect full-game oracle consistency on Chomp 10×11, high but incomplete consistency on Chomp 9×10, and measurable but still imperfect improvement on Connect Four. These results suggest that weak search-derived supervision is a plausible limiting factor in AlphaZero-style recovery of exact play. Better supervision can close much of the gap, but the remaining challenge is to design search and training procedures that recover oracle-consistent play without relying on external oracles.

References

[1] L. V. Allis. *A Knowledge-Based Approach of Connect-Four*. PhD thesis, Vrije Universiteit Amsterdam, 1988.

[2] T. Anthony, Z. Tian, and D. Barber. Thinking fast and slow with deep learning and tree search. *arXiv preprint arXiv:1705.08439*, 2017.

[3] A. E. Brouwer, G. Horváth, I. Molnár-Sáska, and C. Szabó. On three-rowed chomp. *Integers: Electronic Journal of Combinatorial Number Theory*, 5(G07), 2005.

[4] David Gale. A curious nim-type game. *The American Mathematical Monthly*, 81(8):876–879, 1974. doi: 10.2307/2319446.

[5] P. M. Grundy. Mathematics and games. *Eureka*, 2:6–8, 1939.

[6] Pascal Pons. connect4: Connect 4 solver. https://github.com/PascalPons/connect4, 2015. Accessed 2026.

[7] S. Riis. Mastering NIM and impartial games with weak neural networks: An AlphaZero-inspired multi-frame approach. *arXiv preprint arXiv:2411.06403*, 2024.

[8] D. Silver, J. Schrittwieser, K. Simonyan, I. Antonoglou, A. Huang, A. Guez, T. Hubert, L. Baker, M. Lai, A. Bolton, Y. Chen, T. Lillicrap, F. Hui, L. Sifre, G. van den Driessche, T. Graepel, and D. Hassabis. Mastering the game of go without human knowledge. *Nature*, 550:354–359, 2017.

[9] D. Silver, T. Hubert, J. Schrittwieser, I. Antonoglou, M. Lai, A. Guez, M. Lanctot, L. Sifre, D. Kumaran, T. Graepel, and D. Hassabis. A general reinforcement learning algorithm that masters chess, shogi, and go through self-play. *Science*, 362(6419):1140–1144, 2018.

[10] R. P. Sprague. Über mathematische kampfspiele. *Tôhoku Mathematical Journal*, 41:438–444, 1935.

[11] B. Zhou and S. Riis. Impartial games: A challenge for reinforcement learning. *arXiv preprint arXiv:2205.12787*, 2022.

Appendix A. Oracle Implementation Details

A.1. Connect Four oracle details

Our Connect Four oracle is the perfect solver of Pascal Pons [6], which evaluates positions via exact negamax alpha–beta search with transposition reuse. Actions are indexed by column, with illegal moves masked when a column is full. Internally, however, the solver uses a compact bitboard representation rather than an explicit two-dimensional array update. Although standard 6×7 Connect Four is solved [1], exact evaluation remains expensive in tactically delayed positions, where many legal continuations remain plausible and decisive structure appears deep in the tree. Under optimal play, a player on a winning state preserves positive-value control, while a player on a losing state selects the move with largest available score to delay defeat as long as possible.

A.2. Chomp oracle details

Our Chomp oracle represents each state by its non-increasing row-length profile $\mathbf{s} = (s_0, \ldots, s_{H-1})$, where s_r is the number of remaining squares in row r. A legal move selects a remaining square (r, c) and truncates all rows at and below r to length at most c:

$$s'_{r'} = \min(s_{r'}, c) \qquad \text{for all } r' \geq r.$$

Moves are indexed in row-major order by a single integer $n = rW + c$, providing a fixed-size action space with masking of illegal moves. The solver enumerates legal successors, recursively determines their Grundy numbers, and applies the mex rule with memoization. Even with memoization, the number of reachable profiles grows exponentially with board size, so runtime becomes restrictive on larger boards. The hardest states are typically dense configurations in which small local changes have long-horizon consequences.

Appendix B. Additional Method Details

B.1. Vanilla AlphaZero implementation

The vanilla baseline uses a convolutional residual policy–value network of the standard AlphaZero. Given an encoded board state s, the network outputs (i) policy logits over the fixed action space and (ii) a scalar value estimate:

$$(\mathbf{p}_\theta(s), v_\theta(s)) = f_\theta(s). \tag{1}$$

In our implementation, the input is a single board frame. The network begins with a 3×3 convolution, batch normalization, and ReLU activation, then passes through a stack of residual blocks with identity skip connections. The shared trunk is followed by separate policy and value heads. The policy head ends in a linear projection to the action space, while the value head ends in a scalar output with $\tanh$ activation so predictions lie in $[-1, 1]$.

More concretely, if $\mathbf{h}_0$ denotes the output of the initial convolutional block, then the residual trunk computes

$$\mathbf{h}_{k+1} = \mathbf{h}_k + F_k(\mathbf{h}_k), \tag{2}$$

where each F_k consists of two 3×3 convolutions with batch normalization and ReLU nonlinearity. The policy head maps the final shared representation to logits over legal actions, and the value head maps it to a single scalar:

$$\mathbf{p}_\theta(s) \in \mathbb{R}^{|\mathcal{A}|}, \qquad v_\theta(s) \in [-1, 1]. \tag{3}$$

Search uses a PUCT-style selection rule,

$$a^* = \arg\max_a \left[Q(s,a) + C\,P(a \mid s) \frac{\sqrt{\sum_b N(s,b)}}{1 + N(s,a)} \right], \tag{4}$$

where $Q(s,a)$ is the running value estimate, $N(s,a)$ is the visit count, and $P(a \mid s)$ is the policy prior returned by the network. Root priors are perturbed with Dirichlet noise during self-play, legal moves are masked before normalization, and the final root visit counts define the improved policy target.

Training data are generated by parallel self-play. For each visited state, the replay buffer stores the encoded state, the normalized MCTS visit-count distribution, and the final game outcome from the perspective of the player to move at that state. During optimization, the network is trained on minibatches sampled from this replay memory using the standard policy-plus-value loss

$$\mathcal{L}_{\text{AZ}} = \mathcal{L}_{\text{policy}} + \mathcal{L}_{\text{value}}, \tag{5}$$

where the policy term is cross-entropy against the MCTS-improved target distribution and the value term is mean-squared error against the terminal game outcome.

B.2. Multi-frame AlphaZero implementation

The multi-frame AlphaZero model is included as a representation ablation. All search, replay, and optimization procedures are kept fixed so that the comparison isolates the effect of input representation alone.

The only substantive change relative to vanilla AlphaZero is the input encoding. Instead of supplying a single board snapshot s_t, the model receives a short history of recent board states,

$$(s_t, s_{t-1}, \ldots, s_{t-K+1}),$$

stacked along the channel dimension. In our implementation, the replay buffer stores encoded histories constructed from the three most recent frames of game state, rather than a single-frame board tensor.

The multi-frame network uses the same residual architecture as the vanilla baseline, with one change at the input layer: the first convolution accepts multiple input channels instead of one. In the implementation, the start block maps `num_frames` input channels into the shared hidden dimension, after which the same residual backbone, policy head, and value head are used as in the single-frame model. Thus, the multi-frame experiment should be interpreted as a controlled representation change, not as a different search procedure or optimization pipeline.

B.3. AZAL-specific implementation

AZAL shares the same network architecture, self-play loop, MCTS procedure, and value targets as vanilla AlphaZero. The only implementation change is the addition of an auxiliary policy term:

$$\mathcal{L} = \mathcal{L}_{\text{policy}} + \mathcal{L}_{\text{value}} + \lambda_{\text{aux}} \mathcal{L}_{\text{aux}}, \tag{6}$$

where λ_{aux} corresponds to the implementation parameter `p_move_lambda`. Domain-specific oracle-label construction for Connect Four and Chomp is described below.

Connect Four auxiliary labels.   In Connect Four, oracle supervision comes from the perfect solver of Pascal Pons. During self-play, each replay element stores not only the encoded state, MCTS policy target, and final outcome, but also the move sequence leading to that state. After each self-play iteration, duplicated sequences are removed and the remaining unique sequences are queried in batches through the solver. The returned exact scores are then converted into oracle-best movesets and cached as replay-side labels before gradient updates begin. This means that oracle labels are attached once per iteration rather than recomputed inside every training batch.

Chomp auxiliary labels.   In Chomp, oracle labels are derived from the Grundy solver. Positions that are terminal or fail oracle evaluation are masked out of the auxiliary term. To avoid repeated work, the set of best oracle moves is cached by serialized board state. As a result, the fraction of batch elements that contribute to the auxiliary loss can vary across training.

Relationship to vanilla AlphaZero.   AZAL is therefore a slight modification of the standard AlphaZero loop. It does not replace MCTS-based policy improvement, alter value targets, or inject oracle information into search itself. Instead, it sharpens the learning signal at training time by explicitly favoring moves known to be optimal under an exact oracle, while leaving the rest of the self-play pipeline unchanged.

B.4. Protocol and logging details

All experiments use the same high-level training loop. At each iteration, the current network is placed in evaluation mode and used to guide MCTS-based self-play across multiple games in parallel. For each root state, MCTS returns visit counts over legal actions, these counts are normalized to produce an improved policy target, and an action is sampled from a temperature-adjusted distribution for rollout generation. Once a game terminates, every stored state in that trajectory is assigned the final outcome from the perspective of the player to move at that state and added to replay memory.

For vanilla and multi-frame AlphaZero, the total loss is the sum of policy and value losses. In practice, we log these components separately as `policy_loss` and `value_loss`, along with their sum `total_loss`. For AZAL, we additionally log the auxiliary policy term `p_move_loss` and the fraction of batch elements for which oracle supervision is available, `p_move_labeled_frac`. In Connect Four, we also track oracle-query statistics per iteration, including the total number of queried positions and the number of unique positions after deduplication.

We evaluate each method against exact or oracle-derived notions of optimality rather than relying only on empirical win rate. In Connect Four, we compare play against the exact game-theoretic scores returned by the perfect solver. In Chomp, we use the Grundy oracle to classify positions as winning or losing and to determine if a move preserves the invariant $g(s) \neq 0 \rightarrow g(s') = 0$ that characterizes optimal first-player control.

To make these comparisons explicit, we log move-by-move self-play traces and evaluate each move with oracle annotations. In Chomp, for each ply t we record the played action, the oracle Grundy number $g(s_t)$ of the state before the move, and an oracle reference best move when $g(s_t) \neq 0$. In Connect Four, we log the played column together with the oracle score of the current position and the solver's optimal moveset for that state.

Appendix C. Additional Results

Appendix C reports player-specific oracle-match rates for the aggregate full-game traces. These results separate first-player and second-player labeled decisions, which is important in Chomp as positions with Grundy number zero have no oracle-best move. Thus, N/A entries indicate the absence of labeled oracle decisions.

Table 3: Player-specific oracle-match rates across full-game self-play traces. Match$_1$ is computed over labeled first-player plies and Match$_2$ over labeled second-player plies. In Chomp, states with Grundy number zero have no oracle-best move; therefore, some player-specific entries are N/A as no labeled oracle decision is defined.

Game	Model	Match	Match$_1$	Match$_2$
Chomp 9×10	Vanilla	0.609 (487/800)	0.578 (236/408)	0.640 (251/392)
	Multi-Frame	0.483 (272/563)	0.456 (136/298)	0.513 (136/265)
	AZAL	0.948 (1065/1123)	0.962 (861/895)	0.895 (204/228)
Chomp 10×11	Vanilla	0.474 (484/1021)	0.416 (204/490)	0.527 (280/531)
	Multi-Frame	0.463 (317/685)	0.458 (168/367)	0.469 (149/318)
	AZAL	1.000 (793/793)	1.000 (793/793)	N/A
Connect Four	Vanilla	0.785 (1700/2165)	0.771 (843/1094)	0.800 (857/1071)
	AZAL	0.849 (1828/2153)	0.840 (913/1087)	0.858 (915/1066)

Appendix D. Hyperparameter Table

Appendix D summarizes the main reproducibility details for all aggregate experiments. These settings specify the architecture, search budget, self-play volume, optimization parameters, auxiliary-loss weight, exploration schedule, checkpoint rule, and number of seeds used in the reported results.

Table 4: Reproducibility details for the main experiments. Res. denotes residual blocks/channels. MCTS denotes simulations per move. Iter. denotes training iterations. Games/Iter. denotes self-play games per training iteration. Buffer indicates replay-buffer contents. Temp. denotes the self-play temperature schedule. Noise denotes root Dirichlet noise. Ckpt. denotes the checkpoint-selection rule. Seeds are reported as training seeds / evaluation seeds. Multi-Frame was evaluated only on the rectangular Chomp boards, so no Connect Four Multi-Frame row is reported.

Game	Model	Board	Arch.	Res.	MCTS	Iter.	Games/Iter.	Buffer	Batch	LR	λ_{aux}	Temp.	Noise	Ckpt.	Seeds
Chomp	Vanilla	9×10	Conv-ResNet, 1-plane	9/128	800	10	700	all states / 700 games	128	0.001	N/A	const. 1.25	$\epsilon = 0.25, \alpha = 0.3$	last iter.	0,1,2 / 100000–100002
	Vanilla	10×11	Conv-ResNet, 1-plane	9/128	800	10	700	all states / 700 games	128	0.001	N/A	const. 1.25	$\epsilon = 0.25, \alpha = 0.3$	last iter.	0,1,2 / 100000–100002
	Multi-Frame	9×10	Conv-ResNet, 3-frame	9/128	800	10	700	all states / 700 games	128	0.001	N/A	const. 1.25	$\epsilon = 0.25, \alpha = 0.3$	last iter.	0,1,2 / 100000–100002
	Multi-Frame	10×11	Conv-ResNet, 3-frame	9/128	800	10	700	all states / 700 games	128	0.001	N/A	const. 1.25	$\epsilon = 0.25, \alpha = 0.3$	last iter.	0,1,2 / 100000–100002
	AZAL	9×10	Conv-ResNet, 1-plane	9/128	800	10	700	all states / 700 games	128	0.001	1.0	const. 1.25	$\epsilon = 0.25, \alpha = 0.3$	last iter.	0,1,2 / 100000–100002
	AZAL	10×11	Conv-ResNet, 1-plane	9/128	800	10	700	all states / 700 games	128	0.001	1.0	const. 1.25	$\epsilon = 0.25, \alpha = 0.3$	last iter.	0,1,2 / 100000–100002
Connect Four	Vanilla	6×7	Conv-ResNet, 3-plane	9/128	1000	20	700	all states / 700 games	128	0.001	N/A	const. 1.25	$\epsilon = 0.25, \alpha = 0.3$	last iter.	0,1,2 / 100000–100002
	AZAL	6×7	Conv-ResNet, 3-plane	9/128	1000	20	700	all states / 700 games	128	0.001	1.0	const. 1.25	$\epsilon = 0.25, \alpha = 0.3$	last iter.	0,1,2 / 100000–100002

Table 5: Move-level trace tables for vanilla AlphaZero on Chomp in self-play across board sizes. Here $g(s_t)$ denotes the Grundy number of the position before the move at ply t. When $g(s_t) = 0$, the position is losing, so the oracle does not define a "best" move; these entries are shown as −.

Ply t	Player	$g(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	20	10	10	yes
1	AZ-2	0	72	–	–
2	AZ-1	15	8	8	yes
3	AZ-2	0	63	–	–
4	AZ-1	1	7	7	yes
5	AZ-2	0	54	–	–
6	AZ-1	3	6	6	yes
7	AZ-2	0	5	–	–
8	AZ-1	1	45	45	yes
9	AZ-2	0	36	–	–
10	AZ-1	7	4	4	yes
11	AZ-2	0	3	–	–
12	AZ-1	1	27	27	yes
13	AZ-2	0	18	–	–
14	AZ-1	3	2	2	yes
15	AZ-2	0	1	–	–
16	AZ-1	1	9	9	yes
17	AZ-2	0	0	–	–

Table 6: Chomp Vanilla AZ (9×9)

Ply t	Player	$g(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	19	11	11	yes
1	AZ-2	0	90	–	–
2	AZ-1	1	9	9	yes
3	AZ-2	0	80	–	–
4	AZ-1	15	8	8	yes
5	AZ-2	0	70	–	–
6	AZ-1	1	7	7	yes
7	AZ-2	0	6	–	–
8	AZ-1	3	60	60	yes
9	AZ-2	0	5	–	–
10	AZ-1	1	50	50	yes
11	AZ-2	0	4	–	–
12	AZ-1	7	40	40	yes
13	AZ-2	0	3	–	–
14	AZ-1	1	30	30	yes
15	AZ-2	0	2	–	–
16	AZ-1	3	20	20	yes
17	AZ-2	0	1	–	–
18	AZ-1	1	10	10	yes
19	AZ-2	0	0	–	–

Table 8: Chomp Vanilla AZ (10×10)

Ply t	Player	$g(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	15	72	67, 84	no
1	AZ-2	48	24	46	no
2	AZ-1	12	52	33, 52, 60	yes
3	AZ-2	0	60	–	–
4	AZ-1	13	33	8, 17, 33	yes
5	AZ-2	0	18	–	–
6	AZ-1	15	23	23	yes
7	AZ-2	0	8	–	–
8	AZ-1	4	42	16	no
9	AZ-2	18	14	14	yes
10	AZ-1	0	32	–	–
11	AZ-2	3	13	13	yes
12	AZ-1	0	22	–	–
13	AZ-2	11	50	50	yes
14	AZ-1	0	5	–	–
15	AZ-2	3	30	11, 30	yes
16	AZ-1	0	12	–	–
17	AZ-2	1	4	4	yes
18	AZ-1	0	11	–	–
19	AZ-2	1	3	3	yes
20	AZ-1	0	10	–	–
21	AZ-2	2	1	1	yes
22	AZ-1	0	0	–	–

Table 7: Chomp Vanilla AZ (9×10)

Ply t	Player	$g(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	68	6	24	no
1	AZ-2	38	93	46	no
2	AZ-1	37	35	46	no
3	AZ-2	7	88	88	yes
4	AZ-1	0	26	–	–
5	AZ-2	18	45	45	yes
6	AZ-1	0	25	–	–
7	AZ-2	3	34	34	yes
8	AZ-1	0	15	–	–
9	AZ-2	10	23	23, 77	yes
10	AZ-1	0	12	–	–
11	AZ-2	2	66	66	yes
12	AZ-1	0	55	–	–
13	AZ-2	1	5	5	yes
14	AZ-1	0	4	–	–
15	AZ-2	7	44	44	yes
16	AZ-1	0	33	–	–
17	AZ-2	1	3	3	yes
18	AZ-1	0	22	–	–
19	AZ-2	3	2	2	yes
20	AZ-1	0	1	–	–
21	AZ-2	1	11	11	yes
22	AZ-1	0	0	–	–

Table 9: Chomp Vanilla AZ (10×11)

Table 10: Move-level trace tables for Multi-Frame AlphaZero and AlphaZero-Auxiliary Loss on Chomp in self-play across board sizes. Here $g(s_t)$ denotes the Grundy number of the position before the move at ply t. When $g(s_t) = 0$, the position is losing, so the oracle does not define a "best" move; these entries are shown as –.

Ply t	Player	$g(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	15	48	67, 84	no
1	AZ-2	52	46	66	no
2	AZ-1	25	30	54, 72	no
3	AZ-2	21	4	15	no
4	AZ-1	9	22	12	no
5	AZ-2	7	12	12	yes
6	AZ-1	0	11	–	–
7	AZ-2	1	3	3	yes
8	AZ-1	0	20	–	–
9	AZ-2	3	2	2	yes
10	AZ-1	0	1	–	–
11	AZ-2	1	10	10	yes
12	AZ-1	0	0	–	–

Table 11: Chomp Multi-Frame AZ (9×10)

Ply t	Player	$g(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	68	70	24	no
1	AZ-2	40	100	24	no
2	AZ-1	12	25	2	no
3	AZ-2	14	12	2	no
4	AZ-1	3	10	10	yes
5	AZ-2	0	9	–	–
6	AZ-1	1	7	99	no
7	AZ-2	15	77	77	yes
8	AZ-1	0	66	–	–
9	AZ-2	3	6	6	yes
10	AZ-1	0	55	–	–
11	AZ-2	1	5	5	yes
12	AZ-1	0	4	–	–
13	AZ-2	7	44	44	yes
14	AZ-1	0	33	–	–
15	AZ-2	1	3	3	yes
16	AZ-1	0	11	–	–
17	AZ-2	2	1	1	yes
18	AZ-1	0	0	–	–

Table 13: Chomp Multi-Frame AZ (10×11)

Ply t	Player	$g(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	15	84	67, 84	yes
1	AZ-2	0	55	–	–
2	AZ-1	25	74	18, 36, 74	yes
3	AZ-2	0	49	–	–
4	AZ-1	10	83	83	yes
5	AZ-2	0	46	–	–
6	AZ-1	7	18	18	yes
7	AZ-2	0	54	–	–
8	AZ-1	5	82	35, 82	yes
9	AZ-2	0	73	–	–
10	AZ-1	10	35	35	yes
11	AZ-2	0	60	–	–
12	AZ-1	24	7	7	yes
13	AZ-2	0	44	–	–
14	AZ-1	17	53	53	yes
15	AZ-2	0	52	–	–
16	AZ-1	20	34	34	yes
17	AZ-2	0	43	–	–
18	AZ-1	18	26	26	yes
19	AZ-2	0	25	–	–
20	AZ-1	4	41	41	yes
21	AZ-2	0	5	–	–
22	AZ-1	2	33	33	yes
23	AZ-2	0	32	–	–
24	AZ-1	13	24	24	yes
25	AZ-2	0	31	–	–
26	AZ-1	9	3	3, 12	yes
27	AZ-2	0	22	–	–
28	AZ-1	9	50	50	yes
29	AZ-2	0	2	–	–
30	AZ-1	6	40	40	yes
31	AZ-2	0	21	–	–
32	AZ-1	4	30	30	yes
33	AZ-2	0	20	–	–
34	AZ-1	2	11	11	yes
35	AZ-2	0	10	–	–
36	AZ-1	1	1	1	yes
37	AZ-2	0	0	–	–

Table 12: Chomp Auxiliary Loss AZ (9×10)

Ply t	Player	$g(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	68	24	24	yes
1	AZ-2	0	19	–	–
2	AZ-1	13	99	99	yes
3	AZ-2	0	18	–	–
4	AZ-1	20	67	10, 67	yes
5	AZ-2	0	10	–	–
6	AZ-1	15	17	17	yes
7	AZ-2	0	56	–	–
8	AZ-1	14	15	15	yes
9	AZ-2	0	88	–	–
10	AZ-1	8	7	7, 14, 34	yes
11	AZ-2	0	34	–	–
12	AZ-1	4	13	13	yes
13	AZ-2	0	66	–	–
14	AZ-1	4	23	5, 23	yes
15	AZ-2	0	4	–	–
16	AZ-1	2	55	55	yes
17	AZ-2	0	44	–	–
18	AZ-1	1	12	12	yes
19	AZ-2	0	2	–	–
20	AZ-1	2	22	22	yes
21	AZ-2	0	11	–	–
22	AZ-1	1	1	1	yes
23	AZ-2	0	0	–	–

Table 14: Chomp Auxiliary Loss AZ (10×11)

Table 15: Move-level trace tables for vanilla AlphaZero and AlphaZero-Auxiliary Loss on Connect Four in self-play. Here $\sigma(s_t)$ denotes the oracle score associated with the action chosen at ply t from state s_t. Positive values indicate winning continuations, negative values indicate losing continuations, and zero indicates drawing continuations.

Ply t	Player	$\sigma(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	-1	5	3	no
1	AZ-2	1	4	4	yes
2	AZ-1	-2	2	4, 5	no
3	AZ-2	1	2	4	no
4	AZ-1	-1	4	4	yes
5	AZ-2	1	4	4	yes
6	AZ-1	-1	4	4	yes
7	AZ-2	1	4	4, 5	yes
8	AZ-1	-3	4	3, 2, 5, 0, 6	no
9	AZ-2	0	0	3	no
10	AZ-1	-2	2	0	no
11	AZ-2	2	2	2	yes
12	AZ-1	-2	2	3, 2, 0, 6	yes
13	AZ-2	0	2	5	no
14	AZ-1	0	0	3, 0	yes
15	AZ-2	0	6	3, 1, 5, 0, 6	yes
16	AZ-1	0	0	3, 5, 0	yes
17	AZ-2	0	0	3, 1, 5, 0, 6	yes
18	AZ-1	0	0	3, 1, 5, 0, 6	yes
19	AZ-2	0	0	3, 1, 5, 0, 6	yes
20	AZ-1	0	3	3, 1, 5, 6	yes
21	AZ-2	-2	3	1, 5, 6	no
22	AZ-1	2	3	3	yes
23	AZ-2	-2	3	3	yes
24	AZ-1	2	5	5	yes
25	AZ-2	-2	5	5	yes
26	AZ-1	2	3	3, 5	yes
27	AZ-2	-2	3	3, 5, 6	yes
28	AZ-1	2	5	5	yes
29	AZ-2	-2	5	5	yes
30	AZ-1	2	5	1, 5, 6	yes
31	AZ-2	-2	6	1, 6	yes
32	AZ-1	2	1	1, 6	yes
33	AZ-2	-2	6	6	yes
34	AZ-1	2	6	6	yes
35	AZ-2	-2	6	6	yes
36	AZ-1	2	6	6	yes
37	AZ-2	-2	1	1	yes
38	AZ-1	2	1	1	yes

Table 16: Connect Four Vanilla AZ

Ply t	Player	$\sigma(s_t)$	AZ move n	Oracle best n	Optimal?
0	AZ-1	1	3	3	yes
1	AZ-2	-1	3	3	yes
2	AZ-1	1	3	3	yes
3	AZ-2	-1	3	3	yes
4	AZ-1	1	3	3	yes
5	AZ-2	-1	2	3, 2, 4, 1, 5, 0, 6	yes
6	AZ-1	1	2	2, 5	yes
7	AZ-2	-1	2	2	yes
8	AZ-1	1	2	2	yes
9	AZ-2	-1	0	2, 5, 0	yes
10	AZ-1	1	5	3, 2, 5	yes
11	AZ-2	-1	6	6	yes
12	AZ-1	1	4	3, 2, 4, 5, 0, 6	yes
13	AZ-2	-1	4	4	yes
14	AZ-1	1	4	4	yes
15	AZ-2	-1	4	4, 5, 6	yes
16	AZ-1	1	4	4	yes
17	AZ-2	-1	2	3, 2, 4, 1, 5, 0, 6	yes
18	AZ-1	-3	6	5	no
19	AZ-2	3	6	6	yes
20	AZ-1	-3	6	6	yes
21	AZ-2	3	6	6	yes
22	AZ-1	-3	4	3, 2, 4, 5, 0, 6	yes
23	AZ-2	3	3	3, 2, 5, 0, 6	yes
24	AZ-1	-3	6	2, 5, 0, 6	yes
25	AZ-2	0	1	2, 5, 0	no
26	AZ-1	0	1	1	yes
27	AZ-2	0	1	1	yes
28	AZ-1	-1	1	2	no
29	AZ-2	1	2	2	yes
30	AZ-1	-1	0	1, 5, 0	yes
31	AZ-2	1	5	5, 0	yes
32	AZ-1	-1	5	1, 5, 0	yes
33	AZ-2	1	5	5, 0	yes
34	AZ-1	-1	0	1, 5, 0	yes
35	AZ-2	1	0	0	yes
36	AZ-1	-1	1	1, 5, 0	yes
37	AZ-2	1	1	1	yes
38	AZ-1	-1	5	5	yes
39	AZ-2	1	5	5	yes
40	AZ-1	-1	0	0	yes
41	AZ-2	1	0	0	yes

Table 17: Connect Four Auxiliary Loss AZ

Camera-Ready Edits Summary

This summary page is intended solely for workshop administration and transparency and will not be considered part of the technical content of the paper.

- Revisions addressing reviewer comments: The main full-game results aggregate 60 self-play traces across three seeds per model and game setting.

- Additional experiments: We also report sampled-state oracle evaluation from random-start positions to test if the observed behavior persists beyond opening rollouts.

- Clarifications: Only the final checkpoints are evaluated; checkpoint sensitivity is left for future work.

- Updated results: AZAL substantially improves oracle consistency, achieving perfect full-game consistency on Chomp 10×11, high but incomplete consistency on Chomp 9×10, and decent but still imperfect improvement on Connect Four.

- Updated references: Chomp is an impartial combinatorial game whose winning structure is naturally studied through Grundy numbers [5, 10].