Stutter-TTS: Synthetic Generation of Diverse Stuttered Voice Profiles

Xin Zhang*   Iván Vallés-Pérez*   Olabanji Shonibare   Chengzhu Yu
Jasha Droppo   Andreas Stolcke   Roberto Barra-Chicote   Venkatesh Ravichandran
Amazon Alexa AI
{xizhanga, olabanjs, czyu, drojasha, stolcke, veravic}@amazon.com
{ivallesp, rchicote}@amazon.co.uk

Abstract

Stuttering is a speech disorder where the natural flow of speech is interrupted by blocks, repetitions or prolongations of syllables, words and phrases. The majority of existing automatic speech recognition (ASR) interfaces perform poorly on utterances with stutter, mainly due to lack of matched training data. Synthesis of speech with stutter thus presents an opportunity to improve ASR for this type of speech. We describe Stutter-TTS, an end-to-end neural text-to-speech model capable of synthesizing diverse types of stuttering utterances. We develop a simple, yet effective prosody-control strategy whereby additional tokens are introduced into source text during training to represent specific stuttering characteristics. By choosing the position of the stutter tokens, Stutter-TTS allows word-level control of where stuttering occurs in the synthesized utterance. We are able to synthesize stutter events with high accuracy (F1-scores between 0.63 and 0.84, depending on stutter type). By fine-tuning an ASR model on synthetic stuttered speech we are able to reduce word error by 5.7% relative on stuttered utterances, with only minor ($< 0.2\%$) degradation for fluent utterances.

1 Introduction

According to the National Institute on Deafness and Other Communication Disorders, nearly three million Americans suffer from lifelong stuttering. Advances in deep learning have facilitated the development of ASR systems and encourage the integration of voice assistant in various commercial products (Kepuska and Bohouta [1]). However, people who stutter by and large have not benefited from this added convenience, as existing ASR systems have difficulties understanding atypical speech, resulting in poor performance when it comes to stuttering (Barrett et al. [2]).

Driven by deep neural networks, recent research efforts have been dedicated to improved detection and recognition of disfluent speech (Bayerl et al. [3], Jouaiti and Dautenhahn [4]). Despite advances in modeling technology, one of the persisting bottlenecks is the lack of data representative of diverse stuttering patterns. The performance of stutter detection and recognition systems greatly depends on sufficient stuttered speech for model training (Barrett et al. [2]). For example, the recently introduced SEP-28 dataset contains utterances with stutter comprising less than 24 hours (Lea et al. [5]).

One possible solution to this scarcity of matched speech data would be synthetic speech generated by text-to-speech (TTS) systems, as has already been used for other ASR training scenarios (Zheng et al. [6]). As a necessary first step towards this goal, we focus here on the design of a TTS model capable of generating realistic and natural speech with diverse forms of stutter, with an initial validation of the benefit to ASR performance.

---

*These authors contributed equally.

NeurIPS 2022 Workshop on Synthetic Data for Empowering ML Research.

TTS technology has been widely utilized to produce artificial voices that closely emulate natural human speech (Bilinski et al. [7]). In particular, end-to-end TTS synthesis has attracted wide attention as a result of the simplification in training and improved naturalness of synthetic utterances. Recent work has demonstrated the creation of multiple voices for context-aware conversational speech synthesis (Stanton et al. [8], Cong et al. [9]). Soleymanpour et al. [10] reported on synthesis of dysarthric speech based on a multi-speaker TTS framework. To the best of our knowledge, no literature has investigated how to leverage TTS for synthesizing different types of stuttering voices. For people who stutter, the natural flow of speech is interrupted by various irregular acoustic patterns, such as sound repetition, syllable prolongation, and long pausing. Consequently, it remains a challenge to extend current TTS approaches to the production of realistic stuttering with high naturalness and fine-grained control over the location and types of stutter events.

To address these limitations, we introduce Stutter-TTS, a novel TTS approach that achieves both naturalness and natural prosody in stuttered speech synthesis. We propose a novel control strategy for supervised learning by incorporating special tokens into the source text to represent different prosodic-phonetic characteristic of stutter, including phoneme repetition, dysrhythmic phonation, and blocks. By manipulating the input source text, Stutter-TTS can generate either fluent speech (without stutter) or specific types of stutter in specific locations. We systematically produce 100 hours of diverse types of utterances containing stutter and quantify the generation performance by randomly sampling 400 utterances for evaluation.

2   Methods

A multi-speaker transformer-based TTS network has been used previously to model stuttering speech. The architecture is essentially similar as Chen et al. [11] and Li et al. [12], consisting of a transformer backbone, featuring a phonetic encoder, and an acoustic auto-regressive decoder. A scaled dot product (Kamath et al. [13]) attention mechanism is used to align the acoustic and phonetic features.

2.1   Stutter-TTS Architecture

Several modules are added on top of the base transformer. To condition the decoder on speaker identity information, a global audio reference encoder is included as a lightweight replacement of a speaker embedding model. This module consists of a Gated Recurrent Unit (GRU) (Chung et al. [14]) network that receives a set of randomly drawn frames from a reference Mel-spectrogram, and aggregates them into a time-independent representation. The reference is set to be the target Mel-spectrogram at training time, and the random sampling of frames is a mechanism to prevent the content of the target to be leaked to the decoder by destroying the time-dependent information while keeping an unbiased estimation of the frequency bins energy distributions. At inference time, a reference Mel-spectrogram of the desired speaker is used as input to the global audio reference encoder, as a prototype of the voice to use to synthesize the input sentence.

A stuttering disorder is often characterized by unintentional repetitions, prolongations, or interruption of sounds. It is very difficult to predict which phonemes in an utterance will be affected by stutter (Dash et al. [15]). From the speech generation perspective, this leads to a situation where the text-to-speech mapping is more ambiguous than for regular speakers. Following this line of reasoning, a probabilistic embedding is added as input to the phonetic encoder. Instead of modeling a constant embedding for each phoneme, the parameters of a diagonal Gaussian are used. This feature allows the model to learn the pronunciation uncertainty at phoneme level. Additionally, a learnable parameter α is used to weight the sum of the positional encoding, together with a layer normalization (Ba et al. [16]), which as described in Chen et al. [11], assures that both phonetic and positional information are preserved.

Auto-regressive decoders, especially when dealing with data that features local correlations as found in speech, often stall into a failure mode known as exposure bias (Arora et al. [17]): the decoder, instead of predicting the next step, copies its last input step. To prevent exposure bias, a prenet with a strong regularization is included before the decoder. This module is vital for the correct generalization of the model. It consists of a strong dropout (60%) that is kept active at inference time (Gal and Ghahramani [18]) followed by a strong bottleneck projection Chen et al. [11]. This regularization reduces the amount of information that is given to the decoder at each step, preventing it to stall into

Figure 1: Diagram of Stutter-TTS architecture.

the exposure bias failure mode. Finally, after the decoder module, a postnet and a stop signal are included, similar to the Tacotron 2 architecture (Wang et al. [19]).

To train the model, the L1-loss between the target and the predicted Mel spectrogram is minimized using stochastic gradient descent, similar to the original loss function of Tacotron 2 (Wang et al. [19]). An additional L1-loss is included to enforce that the decoder module produces an output signal in the same domain as its input (autoregression requirement). Equation 1 shows the full loss function, where $\hat{\mathbf{m}}_{\text{final}}$ is the mel-spectrogram after the postnet, $\hat{\mathbf{m}}_{\text{intermediate}}$ is the mel-spectrogram before the postnet and $\mathbf{m}$ is the target mel-spectrogram. The TTS model is train using *teacher-forcing* method (Williams and Zipser [20], Goodfellow et al. [21]). At inference time, the free-running mode is used, generating the samples one step at a time in an auto-regressive fashion. The auto-regressive loop contains the decoder and the prenet modules, but not the postnet module Wang et al. [19].

$$J(\mathbf{m}, \hat{\mathbf{m}}_{\text{intermediate}}, \hat{\mathbf{m}}_{\text{final}}) = \cdot ||\hat{\mathbf{m}}_{\text{intermediate}} - \mathbf{m}||_1 + ||\hat{\mathbf{m}}_{\text{final}} - \mathbf{m}||_1 \qquad (1)$$

2.2 Stutter Tokens

To replicate recurring prosodic-phonetic phenomena associated with stutter, we use a list of special tokens to denote different stuttering patterns and their location. Specifically, we insert stutter tokens immediately in front of the word where stuttering occurs in the corresponding audio.[2] In this work, we mainly focus on three common stutter types as described in Table 1. During grapheme-to-phoneme (G2P) conversion, each stutter token is mapped to a corresponding special phoneme; these stutter phonemes are added to the regular phoneme set. The TTS model will hence learn embedding vectors associated with each of the stutter types.

Table 1: The mapping rule from different types of stutter to corresponding tokens inserted in the source sentence. Type frequencies in the annotated training dataset are given relative to the total number of utterances.

Stutter type	Stutter token	Rel. frequency (%)
Phoneme repetition	s_repetition	40.11
Dysrhythmic phonation	s_phonation	21.40
Block	s_block	15.59

As illustrated in Figure 2, stutter labels are introduced into the input sentence to denote certain prosodic-phonetic structure. It is worthwhile pointing out that the proposed processing approach achieves word-level control in terms of where stuttering happens in the synthetic utterances. This design allows fine-grained control of stutter occurrences at synthesis time. In the inference stage, we can simply place the token for the desired stuttering pattern prior to the word where we want the model to render a stutter event. The resulting synthetic audio will produce a stutter at the designated position in the source sentence.

Figure 2: Encoding of stutter events in the TTS input transcript. A stutter token is inserted in the utterance precisely prior to the stuttered word. The stutter token type is chosen according to the desired type of stutter pattern.

3 Experimental Results

3.1 Dataset and Model Training

The Stutter-TTS model is trained using a combination of two internal datasets, one containing fluent speech (without stutter) captured on close-talking microphones, and one with "golden" (annotated) stuttering speech. The fluent speech dataset contains 10 professional speakers with 13,000 studio-recorded utterances per speaker (600 hours in total). The golden stuttering dataset is collected from speakers who exhibit stutter, in a noise-free environment via mobile phones; it contains 146 native English speakers, with 125 utterances per speaker (40 hours in total). Utterances in both datasets are 6 to 12 seconds long.

We process all audio at 16 kHz and generate 80-dimensional Mel spectrograms. The length of a frame is 50 ms with an overlap of 12.5 ms. We employ the universal neural vocoder proposed by Lorenzo-Trueba et al. [23] to synthesize audio samples from spectrograms generated by Stutter-TTS.

---

[2]Representing prosodic and structural properties with between-word tags for the purpose of word sequence modeling is quite natural and has been used in other speech modeling tasks, such as for prosody-based ASR [22].

Figure 3: Comparison of Mel spectrograms of ground truth versus synthetic stuttered speech.

3.2   Evaluation of Synthetic Stuttered Speech

To evaluate the synthesis of utterances with stutter, we compare the Mel spectrogram generated from Stutter-TTS with the associated recording, collected from speakers with stutter. We modify the original transcription by inserting the stutter tokens where the speaker stuttered, with the aim to reproduce the stutter pattern of the original recording. As shown in Figure 3, our model is able to mimic repetition patterns, as highlighted in the red rectangle. More importantly, we observe that when eliminating the stutter token from the source text, the resulting synthetic utterance contains no stuttering, thus preserving the ability to produce fluent utterances with high naturalness.

In this experiment, we sample 20 reference recordings for each of 10 speakers, and paired with 10,000 sentences for each of the speakers. We randomly insert one stutter token into input transcripts with equal probability for all word positions. We systematically synthesize 100 hours of speech containing all three stutter types. To measure generation performance with stutter, we randomly sampled 500 utterances containing phoneme repetition, dysrhythmic phonation, block and non-stutter. We evaluate the existence of specific stutter types in a subjective manner, by listening to the synthesized waveforms and identifying whether the desired stuttering patterns occur; we also excluded about 20% of samples for which the TTS had failed to produce any intelligible speech.

Table 2: F1 scores for correct synthesis of different types of stutter, while varying the ratio of fluent to stuttered utterances in training.

Training ratio	Phoneme Repetition	Dysrhythmic Phonation	Block	Non-Stutter
95:5	0.692	0.503	0.720	0.647
90:10	**0.786**	**0.633**	0.837	**0.733**
85:15	0.773	0.615	**0.853**	0.575

Evaluation results are summarized in Table 2, in terms of F1 scores for successful generation of the specified stutter types.[3] It is crucial for good performance to train on a combination of fluent and stuttered speech. We vary the ratio between the two types of utterances when sampling data for assembling minibatches for training; a fluent-to-stuttered ratio of 90:10 gives a good compromise

---

[3]The F1 score is the harmonic mean of recall and precision; recall is the rate at which an intended stutter is correctly realized in the audio; precision is the rate at which an observed stutter was intended based on the input specification.

between over- and under-generating stutter events, and similar F1 scores for stutter events and fluent word synthesis (ranging from 0.633 to 0.837).

3.3 Evaluation of ASR Performance

We also evaluate the effect of synthetic speech containing stutter on ASR training. Specifically, we fine-tuned an RNN-T-based ASR model (Zheng et al. [6]) for an additional five epochs using the 100 hours of synthetic utterances produced by Stutter-TTS, along with fluent speech sampled from a corpus of 66k hours of recorded utterances (the same data used for training the baseline model). Instead of checking for TTS failures by listening we used an automatic script to remove empty waveforms.[4] Each epoch consists of 1000 steps with minibatch sizes of 32, 16, and 8 for utterances of length up to 3, 6, and 9 seconds, respectively. During minibatch assembly for fine-tuning, we explore different sampling ratios of utterances with versus without stutter. The sampling ratio is a critical hyperparameter chosen so as to improve the ASR accuracy on stuttered speech without a substantial degradation on fluent speech. Table 3 summarizes the relative word error rate (WER) reduction at different sampling ratios, compared to the baseline RNN-T model, showing the tradeoff between WER reduction on stuttered versus fluent test speech. A good tradeoff is obtained by sampling 3% of the training data from synthetic speech with stutter, achieving 5.74% relative WER reduction for golden utterances with stutter, while limiting the WER degradation on fluent speech to 0.18% relative. All WER reductions for speech with stutter are statistically significant (with $p < 10^{-6}$).

Table 3: Relative change in ASR word error rate when fine-tuning an RNN-T ASR model using different ratios of fluent to synthetic stuttered speech. The last column gives the results of a Wilcoxon rank sum test for the error reduction seen for stuttered speech.

Training ratio	Test set with stutter	Test set without stutter	p-value
99:1	-2.78	2.13	$< 10^{-6}$
97:3	**-5.74**	**0.18**	$< 10^{-6}$
95:5	-3.89	0.35	$< 10^{-6}$
90:10	-4.17	1.24	$< 10^{-6}$

It is worth pointing out that less-than-perfect accuracy in synthesizing stutter events is not necessarily a problem for using Stutter-TTS in ASR training. A certain number of omitted or spurious stutter events should not affect ASR training as long as the overall distribution of event types is not too skewed, since the reference transcription used in ASR training always consists of the corresponding fluent transcript.

4 Conclusion

We present a novel text-to-speech system, Stutter-TTS, that can fabricate stuttered speech in a highly controlled manner. We employ a set of special tokens to specify the locations and types of different stuttering patterns in the source text. When training Stutter-TTS, it is critical to optimize the sampling ratio between fluent and stuttered speech. Stutter-TTS achieves faithful synthesis of utterances with stutter types including phoneme repetition, dysrhythmic phonation, and blocks. In a listening experiment, we find that Stutter-TTS synthesized intended stutter events, as well as non-stuttered words, with high accuracy ($0.63 < $ F1 $ < 0.84$). We also demonstrate that fine-tuning an RNN-T ASR model with synthetic stuttered speech improves the recognition of real stuttered speech, with minimal degradation on fluent speech.

References

[1] Veton Kepuska and Gamal Bohouta. Next-generation of virtual personal assistants (Microsoft Cortana, Apple Siri, Amazon Alexa and Google Home). In *Proc. 8th IEEE Annual Computing and Communication Eorkshop and Conference (CCWC)*, pages 99–103, 2018.

---

[4]https://sites.utexas.edu/margolis/2021/04/16/script-the-removal-of-blank-mp3-files-with-python/

[2] Liam Barrett, Junchao Hu, and Peter Howell. Systematic review of machine learning approaches for detecting developmental stuttering. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 30:1160–1172, 2022.

[3] Sebastian P. Bayerl, Dominik Wagner, Elmar Nöth, and Korbinian Riedhammer. Detecting dysfluencies in stuttering therapy using wav2vec 2.0. In *Proc. Interspeech*, pages 2868–2872, 2022.

[4] Melanie Jouaiti and Kerstin Dautenhahn. Dysfluency classification in stuttered speech using deep learning for real-time applications. In *Proc. IEEE ICASSP*, pages 6482–6486, 2022.

[5] Colin Lea, Vikramjit Mitra, Aparna Joshi, Sachin Kajarekar, and Jeffrey P Bigham. Sep-28k: A dataset for stuttering event detection from podcasts with people who stutter. In *Proc. IEEE ICASSP*, pages 6798–6802, 2021.

[6] Xianrui Zheng, Yulan Liu, Deniz Gunceler, and Daniel Willett. Using synthetic audio to improve the recognition of out-of-vocabulary words in end-to-end ASR systems. In *Proc. IEEE ICASSP*, pages 5674–5678, 2021.

[7] Piotr Bilinski, Thomas Merritt, Abdelhamid Ezzerg, Kamil Pokora, Sebastian Cygert, Kayoko Yanagisawa, Roberto Barra-Chicote, and Daniel Korzekwa. Creating new voices using normalizing flows. In *Proc. Interspeech*, pages 2958–2962, 2022.

[8] Daisy Stanton, Matt Shannon, Soroosh Mariooryad, RJ Skerry-Ryan, Eric Battenberg, Tom Bagby, and David Kao. Speaker generation. In *Proc. IEEE ICASSP*, pages 7897–7901, 2022.

[9] Jian Cong, Shan Yang, Na Hu, Guangzhi Li, Lei Xie, and Dan Su. Controllable context-aware conversational speech synthesis. *arXiv preprint arXiv:2106.10828*, 2021.

[10] Mohammad Soleymanpour, Michael T. Johnson, Rahim Soleymanpour, and Jeffrey Berry. Synthesizing dysarthric speech using multi-talker TTS for dysarthric speech recognition. *arXiv preprint arXiv:2201.11571*, 2022.

[11] Mingjian Chen, Xu Tan, Yi Ren, Jin Xu, Hao Sun, Sheng Zhao, Tao Qin, and Tie-Yan Liu. Multispeech: Multi-speaker text to speech with transformer. *arXiv preprint arXiv:2006.04664*, 2020.

[12] Naihan Li, Shujie Liu, Yanqing Liu, Sheng Zhao, and Ming Liu. Neural speech synthesis with transformer network. In *Proc. AAAI Conference on Artificial Intelligence*, volume 33, pages 6706–6713, 2019.

[13] Uday Kamath, John Liu, and James Whitaker. *Deep learning for NLP and speech recognition*, volume 84. Springer, 2019.

[14] Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling. *arXiv preprint arXiv:1412.3555*, 2014.

[15] Ankit Dash, Nikhil Subramani, Tejas Manjunath, Vishruti Yaragarala, and Shikha Tripathi. Speech recognition and correction of a stuttered speech. In *2018 International Conference on Advances in Computing, Communications and Informatics (ICACCI)*, pages 1757–1760. IEEE, 2018.

[16] Jimmy Lei Ba, Jamie Ryan Kiros, and Geoffrey E. Hinton. Layer normalization. arXiv preprint arXiv:1607.06450, July 2016.

[17] Kushal Arora, Layla El Asri, Hareesh Bahuleyan, and Jackie Chi Kit Cheung. Why exposure bias matters: An imitation learning perspective of error accumulation in language generation. *arXiv preprint arXiv:2204.01171*, 2022.

[18] Yarin Gal and Zoubin Ghahramani. Dropout as a Bayesian approximation: Representing model uncertainty in deep learning. In *international conference on machine learning*, pages 1050–1059. PMLR, 2016.

[19] Yuxuan Wang, RJ Skerry-Ryan, Daisy Stanton, Yonghui Wu, Ron J. Weiss, Navdeep Jaitly, Zongheng Yang, Ying Xiao, Zhifeng Chen, Samy Bengio, Quoc Le, Yannis Agiomyrgiannakis, Rob clark, and Rif A. Saurous. Tacotron: Towards end-to-end speech synthesis. In *Proc. Interspeech*, pages 4006–4010, 2017.

[20] Ronald J Williams and David Zipser. A learning algorithm for continually running fully recurrent neural networks. *Neural computation*, 1(2):270–280, 1989.

[21] Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep learning*. MIT Press, 2016.

[22] Andreas Stolcke, Elizabeth Shriberg, Dilek Hakkani-Tür, and Gökhan Tür. Modeling the prosody of hidden events for improved word recognition. In *Proc. Eurospeech*, pages 307–310, 1999.

[23] Jaime Lorenzo-Trueba, Thomas Drugman, Javier Latorre, Thomas Merritt, Bartosz Putrycz, Roberto Barra-Chicote, Alexis Moinet, and Vatsal Aggarwal. Towards achieving robust universal neural vocoding. In *Proc. Interspeech*, pages 181–185, 2019.