Low-Dimensional Structure in the Space of Language Representations is Reflected in Brain Responses

Abstract

How related are the representations learned by neural language models, translation models, and language tagging tasks? We answer this question by adapting an encoder-decoder transfer learning method from computer vision to investigate the structure among 100 different feature spaces extracted from hidden representations of various networks trained on language tasks. This method reveals a low-dimensional structure where language models and translation models smoothly interpolate between word embeddings, syntactic and semantic tasks, and future word embeddings. We call this low-dimensional structure a *language representation embedding* because it encodes the relationships between representations needed to process language for a variety of NLP tasks. We find that this representation embedding can predict how well each individual feature space maps to human brain responses to natural language stimuli recorded using fMRI. Additionally, we find that the principal dimension of this structure can be used to create a metric which highlights the brain's natural language processing hierarchy. This suggests that the embedding captures some part of the brain's natural language representation structure.

1 Introduction

There are a multitude of common techniques for analytically representing the information contained in natural language. At the word level, language is often represented by word embeddings, which capture some aspects of word meaning using word co-occurrence statistics [6, 19]. Language representations that highlight specific linguistic properties, such as parts-of-speech [23] or sentence chunks [1], or that utilize well-known NLP models such as the intermediate layers of pretrained language models [5, 7, 16, 21], are also frequently studied [9, 25]. In fields such as linguistics, natural language processing, and cognitive psychology, qualitative adjectives are often used to describe these language representations – e.g. "low-level" or "high-level" and "syntactic" or "semantic". The use of these words belies an unstated hypothesis about the nature of the space of language representations – namely that this space is fundamentally low-dimensional, and therefore that the information from the representations in this space can be efficiently described using a few categorical descriptors. In this work, we attempt to directly map the low-dimensional space of language representations by generating "representation embeddings" using a method inspired by the work of Zamir et al. [38]. This method uses the *transfer properties between representations* to map their relationships.

The work described here has two main contributions. First, we used the representation embeddings to demonstrate the existence of low-dimensional structure within the space of language representations. We then used this structure to explore the relationships between – and gain deeper insight about – frequently used language representations. How do the intermediate layers of prominent language models relate to one another? How do the abstractions used by these layers evolve from low-level

word embeddings of a context to a representation of the predicted next word for that context? Do different language models follow similar representation patterns? What are the differences between how unidirectional and bidirectional language models represent information? These are examples of the types of questions we can explore utilizing our representation embedding space. Second, we showed that this low-dimensional structure is reflected in brain responses predicted by these representation embeddings. In particular, we show that mapping the principal dimension of the representation embeddings onto the brain recovers, broadly, known language processing hierarchies. We also show that the representation embeddings can be used to predict which representations map well to each area in the brain.

2 Related Work

Our work closely follows the methods developed by Zamir et al. [38]. Those authors generated a taxonomy of vision tasks and analyzed their relationships in that space. This was achieved by applying transfer learning across vision tasks, and showed that this can reduce data labeling requirements. We used some of their methods, such as transfer modeling and normalization using analytic hierarchy process (AHP) [22], for our analysis on language tasks. Following the same lines but for NLP, the work from Vu et al. [31] explores transferability across NLP tasks. Those authors focus on the application of transfer learning to show that the amount of labeled data, source and target tasks, and domain similarity are all relevant factors for the quality of transferability. Kornblith et al. [15] investigated and compared techniques for measuring the similarity of neural network representations, such as canonical correlation analysis (CCA) and centered kernel alignment (CKA).

Our analysis of the relationship of between the language representation space and the brain leans heavily on the concept of "encoding models". Recently, encoding models have been widely applied as predictive models of brain responses to natural language [12, 34]. Jain and Huth [13] applied encoding models to representations of an LSTM language model that incorporates context into neural representations. These representations are explored for different timescales of language processing in Jain et al. [14]. Toneva and Wehbe [27] explored the encoding model performance of different language model layers to improve neural network performance. Caucheteux and King [4] observed differences in the convergence of hidden state representations from ANNs trained on various visual and language processing tasks to brain-like representations. Schrimpf et al. [24] systematically examined the performance of encoding models across a variety of representations and neural response datasets and observed consistent high performance of Transformer-based model hidden states at predicting neural responses to language. Wang et al. [33] constructed encoding models on a set of 21 vision tasks from Zamir et al. [38] with the objective of localizing tasks to specific brain regions. Those authors built a task graph of brain regions showing similar representation for highly transferable tasks.

3 Methods Overview

Our method aims to use the transfer properties between different language representations to generate quantitative descriptions of their relationships. These descriptions can then be used as an embedding space, without labelling any individual representation with predefined notions of what that representation is or how it relates to other representations. This is analogous to how word embeddings are generated by using co-occurrence statistics to generate quantitative descriptions of each word, without labelling any individual word with our predefined notions of what that word means. By using transfer properties to generate the embedding for each representation, we implicitly assume that language representations with similar transfer properties are themselves similar.

Formally, we define a *representation* t as a function over a language input that extracts a vector of meaningful features for each word. Some representations can be computed independently for each word, such as word embeddings [1, 7, 19], while others depend on both a word and its context, such as part of speech labels [1], or the hidden state in some intermediate layer of a language model [4, 5, 21, 24]. We define a stimulus $\mathbf{s}$ as a string of words drawn from some natural language source, and $\mathcal{S}$ the set with all stimuli from that source. Our goal is to generate a representation embedding over a set of representations $\mathcal{T}$ that are derivable from the same stimuli $\mathcal{S}$. That is, for a representation $t \in \mathcal{T}$, and for all times j in our stimulus $\mathbf{s} \in \mathcal{S}$, $t(\mathbf{s}_j)$ is defined. By extension, there is a natural time-dependent mapping between representations, as for each pair of representations

$t_1, t_2 \in \mathcal{T}$ for identical times, we can attempt to map $t_1(\mathbf{s}_j)$ to $t_2(\mathbf{s}_j)$. This provides a standardized transfer mapping $f_{t_1 \to t_2}(\cdot)$ that can be learned for each pair of representations,

$$f_{t_1 \to t_2}(t_1(\mathbf{s}_j)) \approx t_2(\mathbf{s}_j) \qquad \forall j.$$

However, learning these transfer mappings directly would make comparison across representations difficult, as many of the representations have different dimensionalities. Instead, we adapted the encoder-decoder framework proposed in Zamir et al. [38], which ensures that every transfer mapping has the same input dimensionality. This method proceeds in three parts (Figure 1):

First, we train a linear encoder for each representation that compresses the information in the input down into a latent space. The latent space should only contain information necessary to predict the given representation's features from our input. This is accomplished by training an encoder-decoder from the input to the given representation via a latent space, then discarding the decoder.

Second, we train a new decoder for each pair of representations that uses the previously generated latent space for one representation to predict the other representation.

Third, we evaluate the performance of each decoder targeting a given representation relative to every other decoder for that same representation. This provides a measure of how much of the information in one representation is present in each other representation. Just as words that have similar co-occurrence statistics–when measured against a large enough group of other words–are thought to have similar meanings, we argue that pairs of representations that have similar transfer properties–when measured against a large enough group of other representations–have similar information content.

Figure 1: The encoder-decoder setup of our method, adapted from Zamir et al. [38]. $\mathcal{S}$ is our natural language story stimuli. This can be represented by in many ways, including by our universal input feature space $U(\mathcal{S})$, which were GloVe word embeddings. Encoders E_{t_i} were trained using a bottlenecked linear encoder-decoder network, which outputs to $t_i(\mathcal{S})$ (*blue arrows*). The decoding half of this network was then discarded, and the encoding half used to generate a latent space $\mathcal{L}_{t_i}$ for each representation t_i. Then, a decoder is trained from each latent space to each representation (*orange arrows*). The performance of decoders that map to the same final representation are then compared to one another.

3.1 Generating Representation Encoders

We define[1] $U(\mathcal{S})$ as the universal input feature space for our stimuli $\mathcal{S}$. In practice, this space should represent the input with high fidelity, so could be selected as a one-hot encoding of each input token, or word embeddings for each input token. We use GloVe word embeddings for $U(\mathcal{S})$. Now let $\mathcal{T}$ be a set of representations over $\mathcal{S}$. For each representation $t \in \mathcal{T}$, we generate an encoder $E_t(\cdot)$ such that the encoder extracts only information in $U(\mathcal{S})$ that is needed to predict $t(\mathcal{S})$. We do this by using a bottlenecked linear neural network that maps every $\mathbf{u} \in U(\mathcal{S})$ to an intermediate low-dimensional latent space $\mathcal{L}_t = E_t(U(\mathcal{S}))$ and then maps it to the given representation space,

$$t(\mathbf{s}) \approx f(E_t(\mathbf{u})) \qquad \forall \mathbf{s} \in \mathcal{S} \wedge \mathbf{u} = U(\mathbf{s}),$$

where $f(\cdot)$ is mapping from $\mathcal{L}_t$ to $t(\mathcal{S})$. We used a small latent space of 20 dimensions to encourage the encoder to extract only the information in $U(\mathcal{S})$ that is relevant to compute $t(\mathcal{S})$. Experimentation showed that variations in the latent space size do not meaningfully change encoder performance. Once we have learned these mappings, we assign E_t to be our representation encoder for each

---

[1]We assume that elements j in a string $\mathbf{s}_j$ are properly treated, such that we can exclude the positional indexes for all $\mathbf{s}$. Thus, we define $U(\mathcal{S}) = \{U(\mathbf{s}) | \mathbf{s} \in \mathcal{S}\}$ as the result of applying a function $U(\cdot)$ to all elements $s \in \mathcal{S}$.

representation $t \in \mathcal{T}$. Regardless of the dimensionality of the representation, each latent space has a fixed dimensionality, which enables a fair comparison between representations.

3.2 Generating Representation Decoders

The encoders for each representation generate a latent space $\mathcal{L}_t$ that extracts the information in $U(\mathcal{S})$ relevant to computing $t(\mathcal{S})$, while compressing away irrelevant information. For every pair of representations $(t_1, t_2) \in \mathcal{T}$, we next generate a decoder $D_{t_1 \to t_2}$ such that $D_{t_1 \to t_2}(\mathcal{L}_{t_1}) = D_{t_1 \to t_2}(E_{t_1}(U(\mathcal{S})))$ approximates $t_2(\mathcal{S})$. This yields a total of n^2 decoders, where $|\mathcal{T}| = n$ is the total number of representations. All networks were trained with batch normalization with batches of size 1024 and standard stochastic gradient descent with a learning rate of 10^{-4} for the initial encoders and 2×10^{-5} for the decoders. Hyperparameters were chosen via coordinate descent.

3.3 Generating the Representation Embedding Matrix

Finally, we compare the performance of the n decoders for each representation in order to generate the representation embedding space. We use a held-out set of data for this step. To ensure that comparisons are made on equal footing, we only compare decoders with the same output representation (e.g. $D_{t_1 \to t_2}$ is compared with $D_{t_3 \to t_2}$, $D_{t_4 \to t_2}$, etc.).

Specifically, we generate a pairwise *tournament matrix* $\mathbf{W}_t$ for each representation t by "fighting" all pairs of decoders that output to representation t using a held-out test set. For example, if the decoder $D_{A \to C}$ has lower mean squared error than decoder $D_{B \to C}$ for 75% of the data, we assign the ratio of $0.75/0.25 = 3$ to the triplet of representations (A, B, C). This value would be stored in entry (A, B) in the tournament matrix $\mathbf{W}_C$ for representation C.

We then use this set of pairwise comparisons to approximate a total order over the quality of all encoders for each decoded representation. We do this using a technique called the Analytic Hierarchy Process (AHP) [22], a technique commonly used in operations research to convert many pairwise comparisons into an estimated total order. AHP establishes that the elements of the principal eigenvector of $\mathbf{W}_t$ constitutes a good candidate for a total order over the encoders for t. This eigenvector is proportional to the time that an infinite length random walk on the weighted bidirected graph induced by $\mathbf{W}_t$ will spend at any given representation. Thus, if the encoder for one representation is better than the others, the weight on that representation will be higher as compared to the weights of other encoders. This eigenvector is then normalized to sum to 1. This procedure yields a length n vector for each of the n representations. We set a value of 0.1 into each vector at the position corresponding to the target representation, and then stack the resulting length n vectors together into the representation embedding matrix, $\mathbf{R}$.

4 Results

4.1 Language Representation Embeddings

We applied our method to a set of 100 language representations taken from precomputed word embeddings or pretrained neural networks for NLP tasks operating on English language inputs. We extracted representations from numerous different tasks, which included three word embedding spaces (GloVe, BERT-E, FLAIR) [19, 7, 1], three unidirectional language models (GPT-2 Small, GPT-2 Medium, Transformer-XL) [21, 5, 35], two masked bidirectional language models (BERT, ALBERT) [7, 16], four common interpretable language tagging tasks (named entity recognition, part-of-speech identification, sentence chunking, frame semantic parsing) [1], and two machine translation models (English $\to$ Mandarin, English $\to$ German) [26]. We also included the GloVe embedding for the next word in the sequence, which constitutes a low-dimensional representation the ideal output of a language model. For multilayered networks (language and translation models), we extracted all intermediate layers as separate representations. Full descriptions of all representations, as well as details on how each feature space is extracted, can be found in Appendix A.

Applying our method to these representations, we generated a representation embedding space (Figure 2). Generating this space took roughly one week of compute time on a cluster of 53 GPUs (a combination of Titan X, Titan V, and Quadro RTXs) and 64 CPU servers of different characteristics (Intel Broadwell, Skylake, and Cascade Lake). The representations were trained on a text corpus of

Figure 2: *Language Representation Embeddings with Low Dimensionality:* (*Left*): The representation embedding matrix **R** shows how well a given linguistic feature space (encoder, columns) transfers to another feature space (decoder, rows). For better visualization, rows and columns corresponding to different layers from the same network have been scaled down in this plot. A full-scale matrix is in the supplementary material. (*Right*): Applying multi-dimensional scaling to the representation embedding matrix reveals low-dimensional structure in the linguistic feature spaces. It is dominated by a left-to-right progression from the input word embedding, to syntactic and semantic tagging tasks near the middle layers of language models, to the next word embedding. Multidimensional scaling was weighted such that each full model had equal weight, ensuring that models were not more influential on account of having more layers. The dominant main diagonal was set to 0.1 to preserve the effects of off-diagonal values. The scree plot in the lower left shows that these first two dimensions explain substantially more variance (22% and 10%) than other dimensions, demonstrating that the structure in this space is low-dimensional.

stories from *The Moth Radio Hour* [30] which totalled approximately 54,000 words. Each row shows the relative performance of each of the 99 other representations in decoding a given representation. Each column shows how well a given encoded representation can decode to the other representations. Note that there is a distinct asymmetry: if a given representation (e.g. part-of-speech tagging) is never the best encoder for any other representation, then its column will contain very low values. However, other representations may decode to this one quite well, so the corresponding part-of-speech row can contain higher values.

4.1.1 Multidimensional Scaling Analysis

To better visualize the relationships between the representations, we performed multidimensional scaling (MDS) [28] on the rows of the representation embedding matrix. We then plotted the representations according to their locations on the first two MDS dimensions (Figure 2). This showed that the layers of each of the unidirectional language models form a similar trajectory through the space, beginning near the word embeddings (*green*) and ending at a point that is relatively close to the next-word embedding (*black*). This appears to be the dominant trajectory in our low-dimensional embedding of the representation embedding matrix. Language tagging tasks that require semantic information, such as framing and named entity recognition (*blue*), are close in space to the middle layers of the unidirectional language models. Language tagging tasks that required syntactic information, such as part-of-speech identification and sentence chunking (*red*), are similarly clustered.

We also observe several other interesting relationships. The machine translation representations also begin near the word embeddings. However, translation to Mandarin (Eng→Zh) appears to align more closely to fairly deep layers of the unidirectional language models, compared to translating from English to German. This may be because English and Mandarin are less closely related to one another, and could require deeper syntactic and semantic processing for successful translation.

We also observe that the bidirectional language model representations begin farther away from the input word embedding, closer to the middle of the unidirectional language models. However, they do also end up in a similar point, closer to the next-word embedding. This may be a result of the procedure to extract a feature space from the intermediate layers of the bidirectional language models, which differed meaningfully from extracting the intermediate layers of the unidirectional language models. Since these networks are trained on a masked language modeling task, we extracted the hidden representation for the token immediately preceding the mask token.

To study the dimensionality of the space of language representations, we examined the variance explained by low-dimensional approximations of the embedding matrix. The scree plot in Figure 2 shows the result of applying exploratory factor analysis (EFA) [37] to the representation embedding matrix. We see that the first few dimensions explain much more variance in the matrix than the other dimensions. The first dimension alone constitutes a full 22% of variance. This demonstrates that the representation embedding matrix–and thus, we infer, the space of language representations–has low-dimensional structure.

4.2 Representation Embeddings Predict fMRI Encoding Model Performance

Next, we hypothesized that these language representation embeddings are a useful representation of how natural language is processed in the human brain. Since it is the only system truly capable of producing and understanding complex language, the human brain is an excellent litmus test to determine whether this low-dimensional embedding captures the underlying structure of linguistic information. To test this hypothesis, we used the representation embeddings generated above to predict how well each representation is able to predict fMRI data collected from the human brain as the subject is listening to natural language stories.

4.2.1 fMRI Data

We used functional magnetic resonance imaging (fMRI) data collected from 5 human subjects as they listened to English language podcast stories over Sensimetrics S14 headphones. Subjects were not asked to make any responses, but simply to listen attentively to the stories. For encoding model training, each subject listened to at approximately 5 hours of unique stories across 5 scanning sessions, yielding a total of 9189 datapoints for each voxel across the whole brain. For model testing, the subjects listened to the same test story once in each session (i.e. 5 times). These responses were then averaged across repetitions. Training and test stimuli are listed in Appendix B.1. Functional signal-to-noise ratios in each voxel were assessed by applying the mean-explainable variance method from Nishimoto et al. [18] to the repeated test data. Only voxels within 8 mm of the mid-cortical surface were analyzed, yielding roughly 90,000 voxels per subject.

MRI data were collected on a 3T Siemens Skyra scanner at the **anonymized for review** using a 64-channel Siemens volume coil. Functional scans were collected using a gradient echo EPI sequence with repetition time (TR) = 2.00 s, echo time (TE) = 30.8 ms, flip angle = 71°, multi-band factor (simultaneous multi-slice) = 2, voxel size = 2.6mm x 2.6mm x 2.6mm (slice thickness = 2.6mm), matrix size = 84x84, and field of view = 220 mm. Anatomical data were collected using a T1-weighted multi-echo MP-RAGE sequence with voxel size = 1mm x 1mm x 1mm following the Freesurfer [11] morphometry protocol.

Experiments were approved by the **anonymized for review** IRB. All subjects gave written informed consent. Subjects were compensated for their time at a rate of $25 per hour, or $262 for the entire experiment. Compensation for the 5 subjects totaled $1260.

4.2.2 fMRI Encoding Models

Encoding models predict a measured brain response B, e.g. blood-oxygen-level dependent (BOLD) responses recorded with fMRI, based on the stimulus observed by the subject. Due to limitations on dataset size, encoding models are typically structured as linearized regression, where each regression predictor is some feature of the stimulus. Encoding models can provide insight into where and how information is represented in the brain. For instance, an encoding model that has a feature for whether a given auditory stimulus is a person's name can be used to determine which regions of the brain are activated by hearing names.

Figure 3: *Embedding Brain Voxels in the first MDS dimension:* Projection of the encoding performance vectors for each voxel in one subject over the 100 representations onto the first MDS dimension of the representation embeddings, which explains about 20% of the variance in the representation embeddings. Voxels with high values in this embedding (*red*) are well-explained by representations that are more positive on the main MDS dimension (e.g. later language model layers), and voxels with low values (*blue*) are explained by representations that are more negative (e.g. word embeddings). This dimension is notable as it is the main dimension along which language representations evolve from "earlier" representations such as word embeddings, to "later" representations such as intermediate layers in deep language models. Similar maps for the other subjects are shown in Appendix D.

Here we constructed voxelwise encoding models using ridge regression for each of the 100 language representations t analyzed above. Let $g(t_i)$ indicate a linearized ridge regression model that uses a temporally transformed version of the representation t_i as predictors in the regression. The temporal transformation accounts for the lag in the hemodynamic response function [17]. For each subject x, voxel v, and representation t_i, we fit a separate encoding model to predict the BOLD response $\hat{B}$, i.e. $\hat{B}_{(x,v,t_i)} = g_{(x,v,t_i)}(t_i)$. An optimal ridge parameter α was estimated for each $g_{(x,v,t_i)}$ by using 50-fold Monte Carlo cross-validation, with a held-out validation set of 20% of the datapoints from the training dataset. We then measured the encoding model performance by computing the correlation between the true and predicted BOLD responses for a separate test dataset consisting of one story, $\rho_{(x,v,t_i)} = corr(B_{(x,v)}, \hat{B}_{(x,v,t_i)})$.

4.2.3 Mapping the First Dimension of the Representation Embedding Space to the Brain

The main MDS dimension (left to right in Figure 2) is especially interesting as it seems to capture an intuitive notion of a language representation hierarchy. Representations with low values along the main dimension include word embeddings as well as the earliest layers of most of the language models and machine translation models. Representations with high values along the main dimension include the deeper layers of these models, as well as the majority of the interpretable syntactic and semantic representations. We tested whether this MDS dimension could capture patterns of hierarchical processing observed in cortex. First we defined $\mathbf{p}_{(x,v)} = \text{zscore}([\rho_{(x,v,t_1)} \cdots \rho_{(x,v,t_n)}])$ as the 100-dimensional vector that denotes the encoding model performances for each subject x and voxel v, z-scored over all representations $\mathcal{T}$. We then projected each $\mathbf{p}_{(x,v)}$ onto the first MDS dimension by taking their dot product. This gave us a value that quantifies which part of the first MDS dimension best predicts the activity of a given voxel. Figure 3 shows that voxels that are thought to involve to higher-order, longer timescale language processing (e.g. in prefrontal cortex

Figure 4: *Representation Embeddings Reflect Brain Responses*: (*Left*): Discriminability score matrix $\mathbf{M}$, the average across each subject matrix $\mathbf{M}_x$, which is computed as described in Section 4.3.3. Similar representations have similar brain responses and are therefore more difficult to distinguish. For instance, the word embeddings (green labels) are all similar, as are nearby layers of the same network. A representation similarity matrix is given in Appendix C. (*Upper Right*): The percentage of pairwise matches for each representation where the match is correct more often than not (on 3 or more subjects). Almost all representations can be correctly matched with their corresponding performance vector $\mathbf{p}$, with the interpretable representations being the most difficult to distinguish. (*Lower Right*): Mean voxelwise correlation for encoding models built using each representation of the natural language story stimuli. Prior to computation of this metric, a noise ceiling filter was applied to only include voxels with an mean-explainable variance of at least 0.05 [18]. The best encoding models are derived from two of the contextual unidirectional language models (GPT-2 Small & Medium), similar to earlier reports [4, 24]. Error bars show variance across the 5 subjects.

and the precuneus) are also best predicted by representations with high values along the first MDS dimension [14].

4.2.4 Predicting Encoding Model Performance with Representation Embeddings

Next, we tested whether the structure observed in the language representations using our transfer method is reflected in the brain. We used the language representation embeddings to predict encoding model performance by training linear regression models in a leave-two-out cross-validation procedure. We then calculated a discriminability score that quantifies how well a given linear regression model can predict encoding model performance across the brain for both held out representations. For each subject x and pair of language representations (t_i, t_j), we trained a linear regression $\hat{h}_{(x,i,j)}$ to map a representation embedding $\mathbf{r}_k$ to the corresponding encoding model performance built from t_k over all voxels.

$$\hat{h}_{(x,t_i,t_j)}(\mathbf{r}_k) \approx corr(g_{(x,\bullet,k)}(t_k), B_{(x,\bullet)}) = \rho_{(x,\bullet,t_k)},$$

$\mathbf{r}_k$ is defined as the 196-element vector that concatenates the row and column that correspond to the representation t_i, leaving out the four elements corresponding to the held out pair: $\mathbf{R_{ii}}$, $\mathbf{R_{ij}}$, $\mathbf{R_{ji}}$, and $\mathbf{R_{jj}}$. The model $\hat{h}_{(x,t_i,t_j)}$ was then used to predict the held out encoding model performance across all voxels, $\rho(x, \bullet, t_i)$ and $\rho(x, \bullet, t_j)$. For each subject, we then computed discriminability scores for all pairs of representations to generate a matrix $\mathbf{M}_x$. This quantifies how much better the predicted encoding model performance for t_i matched with the true encoding model performance for t_i than the true encoding model performance for t_j (and vice versa):

$$\mathbf{M}_{x_{(i,j)}} = (corr(\hat{h}_{(x,t_i,t_j)}(\mathbf{r}_i), \rho_{(x,\bullet,t_i)}) + (corr(\hat{h}_{(x,t_i,t_j)}(\mathbf{r}_j), \rho_{(x,\bullet,t_j)})))$$
$$- (corr(\hat{h}_{(x,t_i,t_j)}(\mathbf{r}_i), \rho_{(x,\bullet,t_j)}) + (corr(\hat{h}_{(x,t_i,t_j)}(\mathbf{r}_j), \rho_{(x,\bullet,t_i)})))$$

Figure 4 shows the discriminability scores for all representation pairs averaged across subjects, as well as the average encoding model performance for each individual representation. Most pairs have high discriminability scores (*red*), indicating that the representation embeddings broadly capture the structure of the brain's language representations.

We also computed how often the discriminability score was higher than 0 in the majority of subjects (at least 3 out of 5). We see (Figure 4, *upper right*) that encoding model performances are well predicted by the representation embeddings, with representation embeddings getting matched to their corresponding encoding model performances over 90% of the time for all representations, and 100% of the time for the majority of representations.

5   Future Work, Limitations, and Conclusions

By measuring transferability between different language representations, we were able to visualize the relationships between these representations extracted from common NLP tasks. This uncovered a low-dimensional structure that illustrates how different tasks are related to one another, and how representations evolve over depth in different language models. Finally, we show evidence that these representation embeddings capture the structure of language representations in the human brain.

There are further possible iterations of this method that may shed additional light on the structure of language representations in the brain. Since this method relies on using the transfer properties between representations to generate embeddings, it is necessary that the chosen set of representations spans the rich space of language representations. If some part of the space of language representations has not been sampled, then the representation embeddings may fail to capture some aspects of the structure of that space. We tried to ameliorate this concern by sampling a large number of representations (100). However, it is likely that these chosen representations still do not capture the full diversity of the space. In future work, an even larger number of representations could be used to better map this space.

In a similar vein, we also represented the input to our encoder-decoder setup as a "universal" representation, for which we decided to use GloVe embeddings. GloVe embeddings are likely not "universal" in a true sense, in the same way that a one-hot encoding of the story might be, but practical concerns made this approximation necessary. Use of other universal spaces could also be enlightening, such as directly using fMRI data to map to a latent representation space – i.e. replace $U(S)$ in Figure 1 with some fMRI BOLD responses B recorded from the same language comprehension experiment. Of course the possibilities are not restricted to language representations, as previous work had focused on vision instead [33, 38].

We also used linear networks as opposed to a nonlinear architecture for our encoder-decoders. This constraint limits the expressiveness of the transfer networks, and thus may under-estimate the relatedness between tasks. However, using only linear networks also increases interpretability by ensuring that only simply-related representations can transfer to one another, as also noted by others [2, 20]. Future work may explore the use of regularized nonlinear models for the encoder-decoder networks.

This method does require extracting representations from a neural network trained to accomplish some task. For many tasks used in linguistics, neuroscience, and cognitive psychology, there is no existing pre-trained network. However, training artificial neural networks on a task that is used to measure cognition in humans and animals is an emerging method that can shed light on how these tasks are accomplished [8, 29, 36]. We argue that we can additionally use our proposed method to understand what representations are needed to accomplish different tasks, and to visualize the relationships between those representations. For example, the debate on whether lexico-semantic and syntactic representations are actually separable [10] centers on evidence from different tasks that claim to measure syntactic representations versus semantic ones. Our proposed method may provide new evidence in other domains where overlap has been observed between neural representations elicited by ostensibly different cognitive tasks [3, 32].

In sum, we believe that our work can provide a template for investigating relationships between linguistic and cognitive representations in many different domains.

References

[1] Alan Akbik, Tanja Bergmann, Duncan Blythe, Kashif Rasul, Stefan Schweter, and Roland Vollgraf. Flair: An easy-to-use framework for state-of-the-art nlp. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics (Demonstrations)*, pages 54–59, 2019.

[2] Guillaume Alain and Yoshua Bengio. Understanding intermediate layers using linear classifier probes. *arXiv preprint arXiv:1610.01644*, 2016.

[3] Edward Awh and John Jonides. Overlapping mechanisms of attention and spatial working memory. *Trends in Cognitive Sciences*, 5(3):119–126, Mar 2001. ISSN 1364-6613. doi: 10.1016/S1364-6613(00)01593-X.

[4] Charlotte Caucheteux and Jean-Rémi King. Language processing in brains and deep neural networks: computational convergence and its limits. *bioRxiv*, 2020. doi: 10.1101/2020.07.03. 186288. URL `https://www.biorxiv.org/content/early/2020/07/04/2020.07.03. 186288`.

[5] Zihang Dai, Zhilin Yang, Yiming Yang, William W Cohen, Jaime Carbonell, Quoc V Le, and Ruslan Salakhutdinov. Transformer-xl: Attentive language models beyond a fixed-length context. *arXiv preprint arXiv:1901.02860*, 2019.

[6] Scott Deerwester, Susan T Dumais, George W Furnas, Thomas K Landauer, and Richard Harshman. Indexing by latent semantic analysis. *Journal of the American society for information science*, 41(6):391–407, 1990.

[7] Jacob Devlin, Ming-Wei Chang, Kenton Lee, and Kristina Toutanova. Bert: Pre-training of deep bidirectional transformers for language understanding. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pages 4171–4186, 2019.

[8] Daniel B. Ehrlich, Jasmine T. Stone, David Brandfonbrener, Alexander Atanasov, and John D. Murray. Psychrnn: An accessible and flexible python package for training recurrent neural network models on cognitive tasks. *eNeuro*, 8(1), Jan 2021. ISSN 2373-2822. doi: 10.1523/ENEURO.0427-20.2020. URL `https://www.eneuro.org/content/8/1/ENEURO. 0427-20.2020`.

[9] Kawin Ethayarajh. How contextual are contextualized word representations? comparing the geometry of bert, elmo, and gpt-2 embeddings. *arXiv preprint arXiv:1909.00512*, 2019.

[10] Evelina Fedorenko, Idan Asher Blank, Matthew Siegelman, and Zachary Mineroff. Lack of selectivity for syntax relative to word meanings throughout the language network. *Cognition*, 203, Oct 2020. ISSN 0010-0277. doi: 10.1016/j.cognition.2020.104348.

[11] Bruce Fischl. Freesurfer. *Neuroimage*, 62(2):774–781, 2012.

[12] Alexander G Huth, Wendy A De Heer, Thomas L Griffiths, Frédéric E Theunissen, and Jack L Gallant. Natural speech reveals the semantic maps that tile human cerebral cortex. *Nature*, 532 (7600):453–458, 2016.

[13] Shailee Jain and Alexander Huth. Incorporating context into language encoding models for fmri. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018. URL `https://proceedings.neurips.cc/paper/2018/file/ f471223d1a1614b58a7dc45c9d01df19-Paper.pdf`.

[14] Shailee Jain, Vy Vo, Shivangi Mahto, Amanda LeBel, Javier S Turek, and Alexander Huth. Interpretable multi-timescale models for predicting fmri responses to continuous natural speech. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin, editors, *Advances in Neural Information Processing Systems*, volume 33, pages 13738–13749. Curran Associates, Inc., 2020. URL `https://proceedings.neurips.cc/paper/2020/file/ 9e9a30b74c49d07d8150c8c83b1ccf07-Paper.pdf`.

[15] Simon Kornblith, Mohammad Norouzi, Honglak Lee, and Geoffrey Hinton. Similarity of neural network representations revisited. In *International Conference on Machine Learning*, pages 3519–3529. PMLR, 2019.

[16] Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. *arXiv preprint arXiv:1909.11942*, 2019.

[17] Shinji Nishimoto, An T Vu, Thomas Naselaris, Yuval Benjamini, Bin Yu, and Jack L Gallant. Reconstructing visual experiences from brain activity evoked by natural movies. *Current biology*, 21(19):1641–1646, 2011.

[18] Shinji Nishimoto, Alexander G Huth, Natalia Y Bilenko, and Jack L Gallant. Eye movement-invariant representations in the human visual system. *Journal of vision*, 17(1):11–11, 2017.

[19] Jeffrey Pennington, Richard Socher, and Christopher Manning. Glove: Global vectors for word representation. In *Proceedings of the 2014 conference on empirical methods in natural language processing (EMNLP)*, pages 1532–1543, 2014.

[20] Tiago Pimentel, Josef Valvoda, Rowan Hall Maudslay, Ran Zmigrod, Adina Williams, and Ryan Cotterell. Information-theoretic probing for linguistic structure. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4609–4622, 2020.

[21] Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, and Ilya Sutskever. Language models are unsupervised multitask learners. *OpenAI Blog*, 1(8), 2019.

[22] R.W. Saaty. The analytic hierarchy process—what it is and how it is used. *Mathematical Modelling*, 9(3):161–176, 1987. ISSN 0270-0255. doi: https://doi.org/10.1016/0270-0255(87)90473-8. URL https://www.sciencedirect.com/science/article/pii/0270025587904738.

[23] Helmut Schmid. Part-of-speech tagging with neural networks. *arXiv preprint cmp-lg/9410018*, 1994.

[24] Martin Schrimpf, Idan Blank, Greta Tuckute, Carina Kauf, Eghbal A. Hosseini, Nancy Kanwisher, Joshua Tenenbaum, and Evelina Fedorenko. The neural architecture of language: Integrative reverse-engineering converges on a model for predictive processing. *bioRxiv*, 2020. doi: 10.1101/2020.06.26.174482. URL https://www.biorxiv.org/content/early/2020/10/09/2020.06.26.174482.

[25] Youwei Song, Jiahai Wang, Zhiwei Liang, Zhiyue Liu, and Tao Jiang. Utilizing bert intermediate layers for aspect based sentiment analysis and natural language inference. *arXiv preprint arXiv:2002.04815*, 2020.

[26] Jörg Tiedemann and Santhosh Thottingal. OPUS-MT — Building open translation services for the World. In *Proceedings of the 22nd Annual Conferenec of the European Association for Machine Translation (EAMT)*, Lisbon, Portugal, 2020.

[27] Mariya Toneva and Leila Wehbe. Interpreting and improving natural-language processing (in machines) with natural language-processing (in the brain). In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/749a8e6c231831ef7756db230b4359c8-Paper.pdf.

[28] Warren S Torgerson. Multidimensional scaling: I. theory and method. *Psychometrika*, 17(4):401–419, 1952.

[29] Ben Tsuda, Kay M. Tye, Hava T. Siegelmann, and Terrence J. Sejnowski. A modeling framework for adaptive lifelong learning with transfer and savings through gating in the prefrontal cortex. *Proceedings of the National Academy of Sciences*, 117(47):29872–29882, Nov 2020. ISSN 0027-8424, 1091-6490. doi: 10.1073/pnas.2009591117.

[30] https://themoth.org. The moth radio hour, 2020.

[31] Tu Vu, Tong Wang, Tsendsuren Munkhdalai, Alessandro Sordoni, Adam Trischler, Andrew Mattarella-Micke, Subhransu Maji, and Mohit Iyyer. Exploring and predicting transferability across NLP tasks. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 7882–7926, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.635. URL `https://www.aclweb.org/anthology/2020.emnlp-main.635`.

[32] Vincent Walsh. A theory of magnitude: common cortical metrics of time, space and quantity. *Trends in Cognitive Sciences*, 7(11):483–488, Nov 2003. ISSN 1364-6613. doi: 10.1016/j.tics.2003.09.002.

[33] Aria Wang, Michael Tarr, and Leila Wehbe. Neural taskonomy: Inferring the similarity of task-derived representations from brain activity. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett, editors, *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL `https://proceedings.neurips.cc/paper/2019/file/f490c742cd8318b8ee6dca10af2a163f-Paper.pdf`.

[34] Leila Wehbe, Brian Murphy, Partha Talukdar, Alona Fyshe, Aaditya Ramdas, and Tom Mitchell. Simultaneously uncovering the patterns of brain regions involved in different story reading subprocesses. *PloS one*, 9(11):e112575, 2014.

[35] Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, R'emi Louf, Morgan Funtowicz, and Jamie Brew. Huggingface's transformers: State-of-the-art natural language processing. *ArXiv*, abs/1910.03771, 2019.

[36] Guangyu Robert Yang, Madhura R. Joglekar, H. Francis Song, William T. Newsome, and Xiao-Jing Wang. Task representations in neural networks trained to perform many cognitive tasks. *Nature Neuroscience*, 22(2), Feb 2019. ISSN 1546-1726. doi: 10.1038/s41593-018-0310-2.

[37] An Gie Yong, Sean Pearce, et al. A beginner's guide to factor analysis: Focusing on exploratory factor analysis. *Tutorials in quantitative methods for psychology*, 9(2):79–94, 2013.

[38] Amir R. Zamir, Alexander Sax, William Shen, Leonidas J. Guibas, Jitendra Malik, and Silvio Savarese. Taskonomy: Disentangling task transfer learning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2018.