Beyond Single-Turn: A Survey on Multi-Turn Interactions with Large Language Models

Abstract

Recent advances in large language models (LLMs) have substantially improved single-turn task performance, yet real-world applications increasingly demand sophisticated multi-turn interactions. This survey provides a comprehensive review of recent progress in evaluating and enhancing multi-turn LLM interactions. Centered on a task-oriented taxonomy—spanning instruction following in domains such as mathematics and coding, and conversational engagement in role-playing, healthcare, education, and adversarial jailbreak settings—we systematically examine the challenges of maintaining context, coherence, fairness, and responsiveness across prolonged dialogues. We organize existing benchmarks and datasets into coherent categories reflecting the evolving landscape of multi-turn dialogue evaluation, and review a broad spectrum of enhancement methodologies, including model-centric strategies (in-context learning, supervised fine-tuning, reinforcement learning, and architectural innovations), external integration approaches (memory augmentation, retrieval-based methods, and knowledge graphs), and agent-based techniques for collaborative interaction. Finally, we identify open challenges and promising directions for future research to further improve the robustness and effectiveness of multi-turn LLM interactions.

1 Introduction

The advent of Large Language Models (LLMs), exemplified by influential systems such as GPT series (Radford et al., 2019; Brown et al., 2020; Achiam et al., 2023), PaLM (Chowdhery et al., 2023), and LLaMA (Touvron et al., 2023), has significantly reshaped numerous domains, from education and healthcare to customer service and software engineering. These powerful language models demonstrate remarkable proficiency in generating coherent and contextually relevant responses, achieving groundbreaking performances across various language understanding and generation benchmarks.

However, much of the early progress in both the evaluation and improvements of LLMs has been concentrated in single-turn setting, where models are tested on isolated prompts without considering prior conversational context. While this approach has yielded strong benchmark performance, it underexplores LLMs' broader potential in multi-turn dialogue—the setting that best reflects real-world use. In practice, user needs rarely arise as isolated queries; meaningful and productive interactions typically unfold through sustained, multi-turn exchanges. Effective communication between humans and artificial intelligence inherently demands an understanding of conversational history, nuanced interpretation of previous exchanges, iterative refinement of goals, and adaptive response strategies. Single-turn interaction thus presents a significant limitation, restricting the deployment and utilization of the robust capabilities that LLMs possess.

Recognizing this crucial limitation, substantial research attention has recently shifted toward multi-turn interactions, focusing on enhancing LLM capabilities to sustain context, maintain consistency, handle ambiguity, and dynamically respond across sequential conversational turns. Multi-turn interactions introduce additional layers of complexity, such as managing dialogue coherence, maintaining alignment with user intentions, and addressing issues like cumulative errors, hallucinations, and contextual drift.

This emerging field presents rich opportunities and considerable challenges, prompting a rapidly expanding body of research dedicated to optimizing, evaluating, and deploying LLMs within multi-turn settings.

Understanding these multi-turn dynamics and systematically addressing their inherent complexities is essential for unlocking the next stage in LLM evolution, thereby significantly expanding their applicability and effectiveness in real-world scenarios.

Scope   To provide clarity and facilitate further advancements, this survey specifically addresses multi-turn interaction with LLMs, categorized by tasks along with corresponding evaluation standards, improvement techniques, and current challenges in this domain. We categorize multi-turn interactions according to two main tasks: instruction following tasks and conversational engagement tasks, with the latter encompassing various real-world domain applications. While we refer to several LLM agent-based approaches, we emphasize that LLM-based agents represent a distinct research direction that, though related, falls outside our primary scope. Similarly, despite the growing body of research in Multi-modal LLMs (MLLMs) - including notable benchmarks and frameworks such as ConvBench (Liu et al., 2024b), MMDU (Liu et al., 2024g), MMMT-IF (Epstein et al., 2024), MMDialog Feng et al. (2023), TheaterGen (Cheng et al., 2024), and SVBench (Yang et al., 2025d) - this survey deliberately excludes multimodal capabilities to maintain a focused analysis of text-based multi-turn interactions. Such boundary allows us to provide a comprehensive exploration and in-depth analysis of the landscape of multi-turn interactions specific to LLMs.

Existing Surveys   Foundational surveys (Zhou et al., 2023; Zeng et al., 2024) provide rigorous analyses of LLMs' instruction-following ability in single-turn settings. These works assess properties such as faithfulness, robustness, and generalization in static, one-off interactions. While they establish important baselines for instruction alignment, they do not address the dynamic and context-dependent challenges of multi-turn interaction, including cross-turn coherence, state tracking, and adaptation to evolving user intent.

Several surveys on dialogue systems are also closely related. Yi et al. (2025) provides an overview of recent advances in LLM-based multi-turn dialogue systems, while healthcare-oriented dialogue systems are reviewed in (Valizadeh & Parde, 2022; Shi et al., 2024c). In addition, Zhang et al. (2025a) specifically examines LLMs' multi-turn interaction capabilities, with emphasis on core abilities, evaluation metrics, and algorithmic enhancements for multi-turn contexts.

Comparison with Previous Surveys   Instruction-following surveys primarily focus on single-turn settings, and dialogue-system surveys typically emphasize performance within specific domains or tasks. However, the literature lacks a structured, holistic synthesis that compares methods and findings under broad multi-turn interaction settings.

Among existing work, Zhang et al. (2025a) is most closely related to ours. It centers on core multi-turn capabilities, evaluation methodologies, and algorithmic improvements, adopting a largely capability-oriented perspective. In contrast, we take a task-oriented view motivated by real-world deployment, where performance arises from the interplay of multiple capabilities rather than isolated skills. Accordingly, we organize multi-turn interactions by tasks to provide a more application-driven taxonomy. Moreover, Zhang et al. (2025a) offers limited discussion of multi-turn interaction in high-impact settings such as healthcare consultation and educational assistance, where sustained dialogue is essential, and provides comparatively less analysis of improvement strategies and open challenges in multi-turn contexts.

Main Contributions   To address these gaps and facilitate greater research efforts in multi-turn LLM interactions, this survey presents a structured and detailed analysis that explicitly considers practical scenarios and characteristics of multi-turn deployments. We categorize multi-turn interactions by task, exploring both mixed-topic instruction-following tasks (§2.1) and more complex, open-ended conversational engagement tasks (§2.2) across several key domains where LLMs have demonstrated substantial impacts.

Beyond categorization, we contribute by detailing improvement methodologies across three crucial dimensions: (1) Model-Centric Approaches, directly refining and adapting LLMs to effectively handle sequential dialogue dynamics through strategies like in-context learning, supervised fine-tuning, reinforcement learning, and innovative architectures (§3.1); (2) External Integration Approaches, enhancing LLM performance by leveraging external resources such as memory structures, retrieval mechanisms, and knowledge graphs to overcome contextual limitations and maintain factual consistency (§3.2); and (3) Agent-Based Approaches,

representing a paradigm shift toward proactive, iterative agents that interact individually or collaboratively, managing complexity and improving reasoning capabilities in extended interactions (§3.3).

Additionally, we thoroughly discuss open challenges (§4), proposing a clear taxonomy that categorizes these challenges into five major areas: Context Understanding, Complex Reasoning, Adaptation & Learning, Evaluations, and Ethical & Safety Issues. Finally, we summarize key insights, reflect on overarching themes, and provide perspectives on future directions in a dedicated conclusion (§5).

To the best of our knowledge, this survey is the first to provide a comprehensive overview of multi-turn LLM interactions, spanning task formulations, real-world applications, evaluation methodologies, improvement strategies, and key open challenges.

2 Multi-Turn Interaction Tasks

In this survey, we categorize multi-turn interactions based on tasks rather than capabilities because real-world multi-turn scenarios inherently require integrating multiple capabilities to accomplish a particular objective. Although capabilities such as reasoning, memory, contextual understanding, or adaptability are critical, they rarely function in isolation within conversational contexts. Instead, different capabilities intertwine and complement each other dynamically to achieve specific task goals. By focusing on well defined tasks such as multi turn instruction following and conversational engagement, we better capture the practical complexity of these interactions and provide an intuitive framework for understanding how LLMs satisfy user requirements and perform in real world multi turn conversational settings. Table 1 provides an overview of recent multi-turn instruction-following benchmarks or datasets and their evaluation methods, offering readers a detailed reference for understanding current trends and practices in multi-turn LLM evaluation.

Before diving into detailed discussions on multi-turn instruction-following and conversational engagement tasks, we briefly clarify our rationale behind this categorization. We distinguish these tasks primarily based on two dimensions: user intention clarity and task complexity. Specifically, multi-turn instruction-following tasks typically involve clear, explicit instructions provided by the user, with well-defined user intentions. Consequently, the LLM's performance in these tasks is evaluated directly by how precisely it adheres to or successfully executes the given instructions. Conversely, multi-turn conversational engagement tasks are often characterized by more open-ended user interactions, in which the user's intention may initially be unclear, partially defined, or dynamically evolving throughout the dialogue. The LLM's role in these interactions generally extends beyond strict compliance with instructions; it assumes roles such as an assistant or consultant—examples include health consultants, teaching assistants, or customer service representatives. Such tasks may involve proactive information-seeking, synthesizing insights across multiple topics, interpreting implied user intentions, and utilizing external knowledge bases or tool calls to curate relevant and contextually appropriate responses throughout multi-turn conversations.

2.1 Instruction Following Tasks

In this section, we specifically focus on multi-turn instruction-following tasks, highlighting their unique characteristics, challenges, and recent benchmark developments. Inspired by task categorization of MT-Bench (Zheng et al., 2023), We group existing multi-turn instruction-following benchmarks into three primary categories: general (mixed) instruction-following, mathematics, and coding. Most benchmarks naturally fall into the general category due to their coverage of diverse task types. Nevertheless, specialized benchmarks targeting math and coding interactions have also emerged prominently, demonstrating unique evaluation dimensions and challenges distinct from general-purpose tasks.

2.1.1 Instruction Following Tasks in General

Recent research has increasingly focused on evaluating the multi-turn interaction abilities of large language models (LLMs), aiming to capture the complexities of real-world dialogue that single-turn benchmarks, such as BIG-Bench (Ghazal et al., 2013), CSQA (Talmor et al., 2019), MMLU (Hendrycks et al., 2021), and GSM8K (Cobbe et al., 2021), often fail to address.

Date[a]	Benchmark Dataset	Category	Total #Dial.	Avg. #Turns/Dial.	Human-based	LLM-based	Rule-based	Human-as-a-judge[b]	LLM-as-a-judge	Agreement Check[c]	Evaluation Criteria
			Dataset Size		Data Curation		Evaluator				
Mar 2022	MTPB (Nijkamp et al., 2023b)	Coding	115	/	no	no	yes	no	no	/	Pass rate, Perplexity
Dec 2022	ABC-Eval[d](Finch et al., 2023)	Conversation	400	30.3	yes	no	no	yes	no	/	Consistency, Emotion, Understanding, Engagingness, Grammaticality, Informativeness, Quality, Proactivity, Relevance
Jun 2023	MathChat-Agent (Wu et al., 2024b)	IF-math	/	15	no	no	yes	no	no	/	Accuracy
Jun 2023	MT-Bench (Zheng et al., 2023)	IF-general	80	2	yes	no	no	no	yes	yes	Correctness, Helpfulness
Jun 2023	InterCode (Yang et al., 2023)	IF-coding	/	10	no	yes	yes	no	no	/	Execution Success
Sep 2023	MINT (Wang et al., 2024f)	IF-reasoning	586	< 5	no	yes	yes	no	no	yes	Evaluation Quality, Success Rate
Oct 2023	MT-Bench++ (Sun et al., 2024)	IF-general	80	8	no	yes	no	no	yes	no	Helpfulness, Relevance, Accuracy, Depth, Creativity, Level of Detail
Oct 2023	BotChat (Duan et al., 2024)	Conversation	547	16	yes	yes	no	no	yes	/	Quality, Similarity to Human Dialogues
Jan 2024	EHRAgent (Shi et al., 2024a)	IF-coding	/	/	yes	no	yes	no	no	/	Success Rate, Complete Rate
Jan 2024	MT-Eval (Kwan et al., 2024)	IF-general	168	6.96	no	yes	yes	no	yes	no	Helpfulness, relevance, accuracy, depth, creativity, how well it conforms to constraints; accuracy of classification and recollection
Jan 2024	WebLINX (Lù et al., 2024)	IF-general	2337	43	yes	no	yes	no	no	/	Intent Match, Element Similarity Using IoU, Text Similarity Using F1, Turn-Level Score and Overall Score
Feb 2024	AQA-Bench (Yang et al., 2025b)	IF-reasoning	/	15,30[e]	/	/	yes	no	no	/	Goal Metric, Policy Metric (Both for Each Interactive Environment)
Feb 2024	MT-Bench-101 (Bai et al., 2024)	IF-general	1388	3.03	no	yes	no	no	yes	yes	Perceptivity (Context Memory, Context Understanding, Context Interference), Adaptability (Rephrasing, Reflection, Reasoning), Interactivity (Questioning)
May 2024	MathChat-Bench (Liang et al., 2024)	IF-math	5276	4	no	yes	no	no	yes	yes	Follow-Up QA, Error Correction, Error Analysis, Problem Generation
Jun 2024	M2Lingual[f] (Maheshwary et al., 2025)	IF-general	1140	2.48	no	yes	*MT-Bench*				*same as MT-Bench's*
Aug 2024	SysBench (Qin et al., 2025)	IF-general	500	5	yes	no	yes	no	no	/	Constraint Satisfaction Rate, Instruction Satisfaction Rate, Session Stability Rate
Oct 2024	FB-Bench (Li et al., 2025b)	IF-general	591	2	yes	yes	no	no	yes	yes	Error Correction, Response Maintenance
Oct 2024	WILT (Banatt et al., 2024)	IF-reasoning	50	< 30	/	/	yes	no	no	/	Accuracy in Deducing the Hidden Functions
Oct 2024	Multi-IF (He et al., 2024)	IF-general	909	3	no	yes	yes	no	no	/	Instruction- and Conversation-Level Accuracy of Instruction Following
Oct 2024	FairMT-Bench (Fan et al., 2025)	IF-fairness	10k	4	no	yes	no	no	yes	yes	Direct and Implicit Bias
Dec 2024	MMSQL (Guo et al., 2025)	IF-coding	6493	6	no	yes	yes	no	yes	yes	Exact Matching, Execution Accuracy, Dual Assessment of Question Type Detection, Execution Accuracy, Response Quality Score

[a] We use the date of their initial version on arXiv to rank them, allowing the development trajectory and patterns to be revealed.

[b] Do not include the human evaluation done for agreement check between LLM and human.

[c] If LLM-as-a-judge is used, whether there is an agreement check between LLM and human annotators on a subset of the dataset.

[d] We intentionally include ABC-Eval and BotChat in this table as they represent early explorations in multi-turn interactions. Their presence illustrates the developmental trajectory of the field, although a more detailed discussion can be found in §2.2.

[e] 15 for easy mode, 30 for hard mode.

[f] M2Lingual includes dialogues for 70+ languages. The statistics shown here are restricted to only English multi-turn dialogues.

Note. Information is reported as of January 2025 (time of writing).

Table 1: An Overview of Recent Multi-Turn Instruction Following Benchmark or Datasets and Evaluation Methods.

MT-Bench (Zheng et al., 2023) emerged as one of the first curated benchmarks designed to evaluate multi-turn instruction following capabilities in LLMs. It consists of 80 two-turn dialogues that span eight categories: writing, roleplay, information extraction, reasoning, math, coding, STEM knowledge, and social science. The benchmark evaluates model responses through pairwise comparisons, assessing correctness and helpfulness. A key contribution of MT-Bench (along with AlpacaEval (Li et al., 2023e)) is its systematic study of **LLM-as-a-judge**, where strong LLMs, such as GPT-4, serve as automated evaluators. The study shows that LLM judges achieve over 80% agreement with human evaluators, making them a scalable alternative to human assessments. It also examines potential biases and limitations of LLM judges and suggests mitigation strategies. Since its introduction, LLM-as-a-judge has become a widely adopted evaluation method, shaping benchmarking practices. However, MT-Bench is limited to two-turn dialogues and a relatively small dataset, underscoring the need for more comprehensive benchmarks.

Building on this foundation, MT-Bench++ (Sun et al., 2024) extends the original MT-Bench dataset by incorporating additional follow-up turns per dialogue, resulting in eight-turn interactions. These extended interactions, enriched with carefully crafted ellipsis and anaphora, further challenge models' abilities to maintain context and coherence over prolonged exchanges.

Increasing dialogue length alone was insufficient for comprehensive evaluation. MT-Bench-101 (Bai et al., 2024) introduces a fine-grained taxonomy for multi-turn dialogues. It categorizes interactions into aspects such as perceptivity (context understanding and memory), interactivity (eliciting clarifying questions), and adaptability (reasoning and reflection). With 4,208 turns across 1,388 dialogues and a three-tier ability taxonomy, this benchmark facilitates a detailed assessment of specific interaction skills. Evaluations on 21 prominent LLMs have revealed that even state-of-the-art chat-tuned models exhibit uneven performance across different turns and task types, and that standard alignment techniques (e.g., supervised fine-tuning and RLHF) do not guarantee consistent improvements in multi-turn settings.

MT-Eval (Kwan et al., 2024) takes a different approach by investigating the performance disparities between single-turn and multi-turn interactions. Utilizing 1,170 multi-turn queries derived from human-chat transcripts, MT-Eval categorizes user tasks into four distinct types: follow-up (building upon previous responses), refinement (modifying prior requests), expansion (elaborating on earlier topics), and recollection (retrieving information from earlier turns). The study demonstrates that most LLMs suffer significant performance degradation in multi-turn scenarios, with errors compounding over successive exchanges and the temporal distance from the relevant context further exacerbating the decline This interaction taxonomy has since been adopted by subsequent research, notably M2Lingual (Maheshwary et al., 2025), which extends multi-turn evaluation into the multilingual domain. M2Lingual applies these interaction categories across 12 diverse languages, revealing concerning cross-lingual brittleness in context retention abilities. The benchmark demonstrates that even advanced models struggle to maintain contextual understanding across language boundaries, with performance deteriorating more severely in non-English interactions, highlighting a critical gap in the multilingual capabilities of current LLMs for sustained dialogues.

M2Lingual is not the only research highlighting such cross-lingual challenges. Multi-IF (He et al., 2024), a benchmark for multi-turn and multilingual instructions, introduces a challenging evaluation set for LLMs involving multi-turn, verifiable writing instructions (e.g., style or format requirements) across 8 languages. The Multi-IF dataset contains 4,501 dialogues created by expanding a single-turn English benchmark (IFEval (Zhou et al., 2023)) into more challenging multi-turn sequences and translating them into 7 additional languages. Concurrently, FairMT-Bench (Fan et al., 2025) focuses explicitly on fairness in multi-turn dialogues. FairMT-Bench is the first comprehensive benchmark designed to evaluate fairness in open-domain multi-turn dialogues for LLMs, formulating a task taxonomy that targets LLM fairness capabilities across three stages: context understanding, user interaction, and instruction trade-offs—challenges discussed further in Section 4. Based on this taxonomy, the authors constructed fairness datasets, FairMT-1K and FairMT-10K, encompassing two major bias types (stereotype and toxicity) and six bias attributes (age, gender, race, religion, disabled, and appearance), covering nearly all bias categories commonly addressed in fairness evaluation.

While most multi-turn benchmarks focus on context retention and reasoning across turns, FB-Bench (Li et al., 2025b) introduces a novel dimension by measuring LLMs' responsiveness to human feedback in multi-turn interaction settings. This Chinese-language benchmark evaluates two crucial aspects of feedback handling:

error correction (the ability to fix mistakes when prompted) and response maintenance (the ability to maintain correct responses when challenged). FB-Bench spans diverse task categories, including mathematics, reasoning, coding, text extraction, text error correction, text creation, knowledge Q&A, and text translation. Findings from this benchmark reveal that leading LLMs demonstrate comparable capabilities in error correction across tasks, but their performance varies significantly in response maintenance. Moreover, the research indicates that hinting guidance substantially improves response quality, while exposure to misinformation or fabricated credentials often results in misleading outputs.

Li et al. (2025c) recently draw attention to the challenge of maintaining consistent responses in multi-turn LLM interactions, introducing a framework that assumes models should remain "firm" rather than "fickle" when faced with challenging follow-up prompts. Their work introduces the Position-Weighted Consistency (PWC) score, a novel metric that considers the temporal dimension of dialogue by assigning greater penalties to inconsistencies occurring in earlier interaction rounds. This approach reflects the real-world importance of early stability in establishing user trust. Through experiments with leading models across carefully designed challenge scenarios, the authors demonstrated that even high-performing LLMs can be swayed by various follow-up strategies, including emotional appeals and expert authority claims. To enhance response stability, they propose the Confidence-Aware Response Generation (CARG) framework, which integrates model confidence signals into the generation process. Empirical results demonstrate that CARG significantly improves response consistency without compromising accuracy, highlighting the necessity of incorporating turn-based considerations into LLM evaluations.

In addition to task-oriented evaluations, a complementary line of work has explored abstract reasoning benchmarks designed to test LLMs' core reasoning capabilities in multi-turn settings. AQA-Bench (Yang et al., 2025b) evaluates LLMs in interactive environments requiring sequential decision-making, such as binary search and graph traversal (DFS, BFS). It emphasizes memory maintenance, procedural adherence, and planning over multiple turns, with both algorithmic and "embodied" (narrative) settings. WILT (Wason Inductive Logic Test) (Banatt et al., 2024) further assesses inductive reasoning by asking models to iteratively discover hidden rules through evidence gathering and hypothesis testing. These benchmarks are task-agnostic and explicitly designed to avoid memorization, targeting core skills such as logical consistency, strategic exploration, and hypothesis refinement.

Besides these abstract reasoning evaluations, other studies have addressed multi-turn interactions from specialized task perspectives. For instance, WebLINX (Lù et al., 2024) tackles the problem of conversational web navigation, where an LLM-based agent must follow user instructions via dialogue to accomplish tasks on real websites. Tasks range from booking tickets to finding information, requiring the agent to understand natural language commands and manipulate a web page accordingly (click links, fill forms, etc.) over multiple turns. MULTITURNINSTRUCT (Han et al., 2025) proposes a systematic benchmark to probe LLMs' ability to handle sequential, potentially conflicting instructions in a conversation. SysBench (Qin et al., 2025) is a benchmark specifically designed to evaluate how well LLMs adhere to system-level instructions (the hidden directives guiding an AI assistant) in multi-turn interactions. Emphasizing clear and explicit user intentions, we categorize two recent recommendation system works in this subsection: SAPIENT (Du et al., 2025) and ECR (Zhang et al., 2024b). SAPIENT (Du et al., 2025) is a multi-turn conversational recommender system that integrates a planning module for strategic dialogue management, while ECR (Zhang et al., 2024b) introduces an "empathetic" conversational recommender that enhances traditional recommendation dialogues with emotional awareness.

Together, these works underscore ongoing challenges in developing robust multi-turn instruction-following interactions in LLMs, particularly regarding context retention, dialogue coherence, multilingual interactions, fairness considerations, and responsiveness to user feedback. To effectively address the nuanced demands of specialized domains such as mathematics and coding, recent research has introduced targeted benchmarks and approaches. The following subsections explore these specialized areas, highlighting how they deepen our understanding of multi-turn instruction-following tasks.

2.1.2 Instruction Following Tasks in Math

LLMs have demonstrated impressive performance in solving math problems via single-turn prompts, often generating detailed, step-by-step "chain-of-thought" solutions. For example, providing a few worked examples allows a 540B-parameter model to achieve state-of-the-art accuracy on the GSM8K math word problems (Wei et al., 2022). However, complex mathematical tasks frequently require LLMs to engage in multi-turn, instruction-following interactions that involve incremental reasoning, clarification questions, and iterative refinement based on interactive feedback (Liang et al., 2024; Romera-Paredes et al., 2024). In these instruction-following math tasks, users iteratively guide LLMs by providing clarifications, corrections, or additional contextual instructions. Such dynamic interactions not only enhance the models' reasoning processes but also facilitate effective use of external computational tools, enabling the models to perform sophisticated tasks like simulating scenarios or executing complex calculations through code (Romera-Paredes et al., 2024; Lightman et al., 2023). Instruction-following tasks in math also encompass advanced skills such as follow-up questioning, errors diagnosing and correcting, and educational feedback delivering, thus capturing broader capabilities essential for deploying LLMs in diverse educational and problem-solving contexts.

Several approaches have leveraged multi-turn dialogue with LLMs to enhance mathematical reasoning. For example, Wu et al. (2024b) introduces MathChat-Agent, a framework where an LLM collaborates with a user-proxy agent (responsible for tool use, such as a Python solver) via iterative conversation. This approach solved competition-level math problems more effectively, improving accuracy by roughly 6% over standard single-turn chain-of-thought prompts. Similarly, Keating (2024) employs a multi-agent strategy in which two GPT-4 agents engage in debate-style interactions to reach a solution. This dual-agent zero-shot method achieved about 62.7% accuracy on the MATH benchmark—surpassing single-agent baselines and illustrating the benefits of peer deliberation in reasoning. Moving further, Xiong et al. (2025) propose a method to train LLMs to better combine tool usage with their own reasoning for complex tasks. It gathers trajectory-level feedback from users over multiple turns, to refine problem-solving strategies. The learning process is modeled as a Markov decision process (MDP) and adapts direct preference learning algorithms to multi-turn interactions that include external messages. In practice, the model is trained on multi-turn chats where a user first asks a question and then gives Python outputs in later turns. The accuracy of the method is evaluated on the GSM8K and MATH test sets.

Benchmarks & Evaluation in Math Several benchmarks now target multi-turn math dialogues. MathChat-Bench (Liang et al., 2024) extends GSM8K with four new tasks: follow-up QA, problem generation, error correction, and error analysis. The original problems are modified using GPT-4 to meet specific requirements. For instance, in the follow-up QA task, three rounds of dialogue are created: first, GSM8K test problems with ground-truth answers are presented; then GPT-4o generates two follow-up questions; finally, GPT-4 produces the final answers, which are verified or revised by two other LLMs and human annotators. LLMs are evaluated by both accuracy and scores, assigned by GPT-4, which measure their instruction follow-up abilities. Evaluations of state-of-the-art models on MathChat showed that while they excel at standard one-shot math questions, performance drops sharply on these multi-turn interactions requiring sustained reasoning and dialogue comprehension. To address this gap, the authors also released MathChatSync, a synthetic dialogue dataset for fine-tuning LLMs on conversational math problem solving. Fine-tuning on MathChatSync yielded notable improvements in multi-turn performance.

More broadly, the MINT benchmark (Wang et al., 2024f) evaluates multi-turn tool use and user feedback across domains (including math reasoning). MINT provides an automated framework where the LLM can call a Python interpreter and receive natural language feedback (simulated by GPT-4) in successive turns. Findings from MINT show that multi-turn tool-aided dialogues consistently improve problem-solving success (each tool use or feedback turn yields additional 1–17% accuracy gains). Interestingly, this evaluation also found that some models fine-tuned only on single-turn instructions (via standard supervised tuning or RLHF) underperform in multi-turn settings, suggesting that multi-turn-specific training is needed to excel in interactive math tasks.

Noticeably, several studies have found that LLMs struggle with generalizing to new problems. For example, Liang et al. (2024) show that math-specific LLMs lack adaptive behavior, and their difficulty with generating novel problems highlights their rigidity. Similarly, Macina et al. (2023) report that dialogue tutoring

models do not generalize well to unseen math problems. To improve multi-turn math problem solving and generalization, many researchers propose using SFT (Liang et al., 2024; Macina et al., 2023; Wang et al., 2024f) or RLHF (Wang et al., 2024f; Xiong et al., 2025). Although RLHF can affect LLM–tool interactions and leveraging feedbacks (Wang et al., 2024f), studies consistently find that fine-tuning with preference data and instructions boosts downstream performance. Macina et al. (2023) demonstrate that small, fine-tuned models perform significantly better, in terms of correctness and equitable tutoring, than prompting a large model like ChatGPT.

2.1.3 Instruction Following Tasks in Coding

LLMs often struggle to produce correct code and perform self-debugging in a single pass, frequently requiring multi-turn or iterative interactions (Zhong et al., 2024; Chen et al., 2025e; Shi et al., 2024d). Instruction-following tasks in coding contexts commonly involve collaborative, iterative interactions, where users provide detailed instructions that the LLM translates into executable code. Through subsequent turns, the LLM iteratively integrates feedback, refines initial solutions, strategically plans modifications, executes and tests submodules, and performs debugging until satisfying the given specifications. Such iterative instruction-following tasks are essential to evaluate LLM performance and robustness in dynamic coding scenarios.

Benchmarks & Evaluation in Coding Different frameworks and playgrounds are developed for evaluating code generation qualities (Yang et al., 2023; Zheng et al., 2025). InterCode (Yang et al., 2023) introduces a generation pipeline for evaluating LLM coding quality through multi-turn interactions that simulate a real-world coding environment. The InterCode framework requires as input a natural language prompt paired with either an answer or a correct code block. The LLM is evaluated using one of three strategies: "Try-again", where the execution output is fed back as an observation; ReACT, which terminates once the thought chain is complete; or Plan & Solve, which terminates when the plan is fully executed. The experiments involve three programming environments with Spider (Yu et al., 2018), MBPP (Austin et al., 2021) and NL2Bash (Lin et al., 2018) datasets. Zheng et al. (2025) propose a framework for systematically evaluating various prompting techniques for multi-turn code generation by LLMs. Their evaluation is conducted in a zero-shot setting using two competitive coding benchmarks, CodeContests (Li et al., 2022) and TACO (Li et al., 2023d). PyBench (Zhang et al., 2024c) proposes a unified benchmark to evaluate LLM Python coding ability in several categories such as chart analysis, software development, etc. For each task, LLMs are interacting with a code interpreter for a few turns before making a formal response. The LLMs are evaluated on the success rates and average turns to complete a unit test for each task.

Toward effective code generations, CodeGEN (Nijkamp et al., 2023b) and CodeGEN2 (Nijkamp et al., 2023a) are a family of LLMs designed to generate programs from natural language descriptions in multiple turns. The models are evaluated using the Pass Rate metric on their Multi-Turn Programming Benchmark (MTPB), which comprises 115 expert-written problems. Each problem includes multi-step natural language prompts, created by human annotators who decompose the problem into sequential steps. Models are required to generate the complete solution from scratch. Chen et al. (2025d) propose to fine-tune existing LLMs with SFT and DPO. They introduce CodeSteer, a framework that guides LLMs through multiple rounds of interaction to generate code. In this system, the primary model (TaskLLM) produces responses, both in natural language and in code, while a supervisory agent (CodeSteerLLM) reviews these outputs using symbolic reasoning and self-answer checking to ensure correctness and provide refined guidance. They are fine-tuned and evaluated on subsets of SymBench, which comprises 37 symbolic tasks with adjustable complexity and includes a synthesized dataset of multi-round guidance/generation trajectories and guidance comparison pairs. OpenCodeInterpreter (Zheng et al., 2024b) proposes to fine-tune LLMs with CodeFeedback, a dataset of challenging LeetCode questions, incorporating multi-turn execution feedback (with code interpreters) and dialogues of human (synthesized by GPT-4). CodeAct (Wang et al., 2024e) collects an instruction-tuning dataset, CodeActInstruct, which contains 7,000 multi-turn interactions. PyInstruct (Zhang et al., 2024c) is used in PyBench for continuous pretraining and fine-tuning. Zheng et al. (2025) explore a wide range of prompting strategies for effective code generation, focusing on automatic re-prompting over multiple runs.

SQL generation is a subcategory of coding generation that focuses more on data acquisition through large-scale data warehouses. Two benchmarks for SQL generation multi-turn LLMs are identified during the

literature search. MMSQL (Guo et al., 2025) focuses on text-to-SQL generation tasks and introduces a Multi-type and Multi-turn text to-SQL test suite, which is a comprehensive benchmark engineered to evaluate the proficiency of LLMs in handling multi-turn text-to-SQL tasks across diverse question types. MMSQL contains a multi-agent framework anchored by a core Question Detector and Question Decomposer tasked with identifying question types and determining appropriate answering strategies. The framework includes two supportive agents: the Schema Selector, which identifies and provides the essential subset of a database schema, and the SQL Refiner, which is dedicated to refining SQL queries. EHRAgent (Shi et al., 2024a) demonstrates a specific application of SQL generation in healthcare settings, which speeds up the extraction and interaction of clinician information within electronic health record (EHR) systems. EHRAgent (Shi et al., 2024a) translates EHR question-answering into a tool-use planning process, which integrates query-specific medical information and formulates executable code plans through multi-turn dialogues. The model is evaluated based on their ability to reason across multiple tables and generate accurate, actionable insights from complex EHR data.

For educational applications, TreeInstruct (Kargupta et al., 2024) transforms LLMs into Socratic instructor agents that guide users in debugging and writing better code. It operates via two roles: an instructor that generates tree-structured sequential questions, and a verifier that identifies tasks to help students understand, assess, and correct their code. To evaluate TreeInstruct, the authors introduce MULTIDEBUG, a dataset derived from LeetCode problems with expert-injected syntactic and conceptual bugs, assessed through both qualitative measures (relevance, indirectness, logical flow) and quantitative metrics (success rate).

Several compelling research questions recur in efforts to adapt LLMs for reliable code generation in multi-turn settings. First, when explicit cues are unavailable, how should an LLM decide between purely textual reasoning and executing programmatic actions to reach a solution (Chen et al., 2025e)? Second, which iterative interaction protocols best support incremental refinement—enabling the model to diagnose errors, incorporate feedback, and converge on a final answer (Yang et al., 2023; Zheng et al., 2025; Nijkamp et al., 2023b;a; Wang et al., 2024e)? Third, how should we evaluate coding performance across programming languages, task types, and application domains in a way that is both comparable and representative of real-world use (Yang et al., 2023; Zhang et al., 2024c)?

2.1.4 Discussions

Based on our analysis and the overview presented in Table 1, several noteworthy trends emerge in the evolution of multi-turn instruction following benchmarks and evaluation methodologies.

Dataset Evolution We observe a clear trajectory toward larger and more comprehensive datasets, with benchmark sizes expanding from just 80 examples in MT-bench to over 1,000 in newer benchmarks like MT-Bench 101, M2Lingual, and FairMT-Bench. This growth reflects a recognition that robust evaluation requires broader coverage of interaction patterns and abilities. Simultaneously, data curation methodologies have evolved from primarily human-generated content toward automated and LLM-assisted generation processes, addressing scalability challenges while maintaining quality. Despite this expansion, current benchmarks predominantly limit conversations to 10 or fewer turns, leaving the domain of extended multi-turn interactions (dozens or hundreds of turns) largely unexplored.

Evaluation Methodologies The evaluation landscape has diversified considerably, transitioning from relatively simple rule-based metrics toward more nuanced and fine-grained assessment frameworks. This evolution parallels the increasing sophistication of LLM capabilities and application scenarios. LLM-as-judge approaches have emerged as particularly promising, offering cost-effective evaluation solutions that can scale with the growing complexity of benchmarks. MT-bench (Zheng et al., 2023) pioneers this approach while acknowledging inherent biases, subsequent studies have further elucidated critical issues.

Recent studies highlight several concerning limitations: Preference Leakage, as demonstrated by Li et al. (2026), shows bias toward responses from models sharing architectural or training lineage with the judge model, compromising evaluation fairness. Contextual Sensitivity, revealed by Xu et al. (2025), manifests as performance degradation when evaluating outputs dependent on external context, such as retrieval-augmented generation, where even state-of-the-art judges struggle with consistency. Reference Dependence

is another issue, as evaluations often exhibit brittleness when reference solutions are unavailable or when multiple valid approaches exist, a common scenario in open-ended multi-turn interactions.

These challenges underscore the continued importance of human evaluation validation. Human-AI agreement checks are essential for establishing the reliability of automated evaluation methods, yet relatively few benchmarks incorporate substantial human agreement verification—a critical gap that risks allowing biases and inconsistencies to persist undetected.

2.2 Conversational Engagement

Conversational engagement tasks in multi-turn dialogue have been catalyzed by several pioneering studies that established how to define and measure an LLM's capacity to sustain interactions over multiple turns. One early effort is the ABC-Eval framework by Finch et al. (2023), which introduced a dimensional human evaluation scheme for open-domain chat. ABC-Eval defines 16 fine-grained conversational behavior categories (spanning aspects like factual accuracy, consistency, relevance, and empathy) and uses these as binary turn-level labels to quantify dialogue quality. Although this benchmark relies on labor-intensive human evaluations, its initial findings underscore the inherent challenges in assessing iterative interactions, thereby motivating the development of more scalable and nuanced evaluation frameworks.

Shortly afterward, Duan et al. (2024) introduce the BotChat evaluation paradigm, which reduces reliance on costly human judges by leveraging LLMs for both conversation generation and evaluation. In BotChat, models are prompted to extend real-world dialogue seeds (ChatSEED prompts) into extended multi-turn conversations, subsequently evaluated by top-tier LLMs (e.g., GPT-4) serving as automated judges. Notably, GPT-4-generated dialogues were found to be nearly indistinguishable from human conversations, successfully fooling discriminator models, whereas other contemporary LLMs exhibited shortcomings in instruction adherence and conciseness, underscoring specific challenges in maintaining human-like coherence across multi-turn dialogues.

Most recently, Deshpande et al. (2025) introduce MultiChallenge, a benchmark designed to rigorously evaluate conversational persistence and context management in frontier LLMs. MultiChallenge encompasses four realistic scenarios—long-term instruction retention, implicit information recall, iterative revision, and consistent non-sycophantic responses—each demanding the simultaneous exercise of instruction following, context tracking, and reasoning.

Building upon these frameworks, recent work explores conversational engagement within specialized real-world contexts, including immersive role-playing, healthcare consultations, educational interactions, and adversarial jailbreak scenarios. Extending evaluations into these practical domains provides deeper insights into several key applications of conversational capabilities essential for modern LLMs.

2.2.1 Conversational Engagements in Roleplay

Role-playing significantly enhances conversational engagement by immersing users in specific scenarios, making interactions feel authentic and contextually relevant. Incorporating explicit roles into dialogue systems encourages users to perceive the interactions as genuine, thereby increasing engagement and satisfaction. Within conversational AI, there is an emerging research domain specifically dedicated to role-playing, which aims to create realistic and persona-consistent interactions through LLMs.

Early persona-grounded dialogue systems aimed at maintaining consistent character personas over multi-turn conversations using architectures like memory networks and transformers. Significant contributions include the persona embeddings introduced by Li et al. (2016), the personalized memory networks developed by Kottur et al. (2017), and notably, the PersonaChat dataset and memory-based models from Zhang et al. (2018), which established foundational benchmarks for persona consistency. These initial works primarily trained models from scratch, facing challenges in sustained persona adherence across interactions. The recent survey by Chen et al. (2024g) extensively covers role-playing before and after the advent of LLMs. Within the scope of this survey, we focus specifically on role-playing interactions under multi-turn LLM settings.

In-Context Learning   Early LLMs demonstrated an ability to impersonate user-defined personas through prompting alone. Users could supply descriptions like "You are a wise old wizard..." in a system or context prompt, and models like GPT-3 would attempt to respond "in character." PersonaLLM (Jiang et al., 2024a) introduces a benchmark for personalization and highlighted that simply prefixing instructions with high-level persona descriptions yields limited diversity; instead, it proposed simulating nuanced user preferences via prompt-based reward models. It showed that prompting can move beyond trivial traits to tailor outputs to idiosyncratic user needs. Similarly, CharacterChat (Tu et al., 2023) uses role-playing prompts with behavior presets and dynamic memory to maintain a character's persona over long conversations. It constructed an MBTI-based persona bank and prompted ChatGPT to produce dialogues between a "seeker" and a compatible "supporter," injecting preset behavioral tendencies and retrieving context-specific memory each turn to keep interactions coherent.

Beyond persona style, prompting has been used to improve reasoning. Role-play prompting (Kong et al., 2024a) shows that instructing an LLM to "pretend to be" a domain expert can implicitly trigger step-by-step reasoning. In zero-shot settings across 12 tasks, prompting models with a role (e.g. "You are an excellent math teacher...") led to significantly higher accuracy than a vanilla prompt. The method uses a two-stage prompting framework: first having the model generate an "immersive" backstory or persona acknowledgement, then using that along with the query. These studies collectively demonstrate prompting-based role-play as a powerful lever: it can induce consistent persona adherence (persona and behavior presets) and even boost cognitive performance (reasoning via expert roles) without any parameter updates.

Supervised Fine-Tuning   To achieve more robust in-character behavior, researchers introduced instruction tuning and fine-tuning with role-playing data. PIPPA (Gosling et al., 2023) releases a partially synthetic corpus of over 1 million role-play messages, crowdsourced from an online community of role-play enthusiasts. By fine-tuning on PIPPA's diverse persona-conditioned conversations, small LLMs dramatically improved at staying in character, underscoring that sheer volume and diversity of persona-rich dialogues can teach consistent role-playing. UltraChat (Ding et al., 2023) constructs 1.5M multi-turn dialogues via self-chat with GPT-4, covering broad topics and user types. Fine-tuning LLaMA on this yielded UltraLLaMA, which surpassed previous open models in general conversation quality (including user engagement and coherence). Other data efforts target specific role-play domains: PRODIGy (Occhipinti et al., 2024) builds a dialogue dataset from movie scripts aligned with detailed character profiles (biographies, personality traits). Fine-tuning models on these profile-grounded movie dialogues significantly improved consistency when emulating those characters – e.g. including a character's backstory and speaking style led to higher human preference for in-character responses.

A parallel direction creates models specialized for particular characters or customizable personas. ChatHaruhi (Li et al., 2023b) focuses on anime characters, compiling 54k dialogues for 32 characters by combining original script lines with simulated conversations. The model fine-tuned on this data, augmented with a "memory" of past events for each character, was able to "revive" characters like Haruhi Suzumiya, accurately quoting lore and personality in new interactions.In another example, CharacterGLM (Zhou et al., 2024a) builds on the Chinese GLM model to allow explicit profile injection for any character: it fine-tuned ChatGLM variants on a corpus of dialogues with richly annotated character profiles (covering identity, style, relationships) and achieved state-of-the-art human-likeness and consistency for customized personas. RoleCraft-GLM (Tao et al., 2024) further extends this concept by crafting original non-celebrity personas with emotional depth and fine-tuning a model on dialogues involving those characters. This yielded more nuanced emotional consistency, validating that meticulous character development during fine-tuning yields agents that are engaging and lifelike in their persona.

Recent work also explores fine-tuning strategies for role consistency. Ditto (Lu et al., 2024) introduces a self-alignment pipeline in which the model generates its own role-play dialogues for 4,000 distinct characters and trains on them. By leveraging the model's internal knowledge to produce training data—with feedback to ensure character distinctiveness—Ditto achieves strong persona fidelity across a wide range of roles, outperforming fine-tuned baselines on a role-play benchmark. Notably, Ditto frames role-play generation as a reading-comprehension task to avoid style collapse, distinguishing it from UltraChat's broader synthetic data approach. CharacterLLM (Shao et al., 2023) follows a complementary pipeline: for each target char-

acter—particularly historical figures—Wikipedia biographies and documents are used to prompt an LLM to produce character-specific dialogues, and fine-tuning on this synthetic data enables a single agent to robustly portray many roles, effectively transferring factual knowledge into conversational skill. Together, these works reflect a broader trend in role-play fine-tuning from large-scale data harvesting toward increasingly sophisticated data generation and specialization strategies.

Personalization and Rapid Adaptation Even with instruction tuning, a given model has limits in the number of distinct characters or styles it can perfectly emulate. Thus, a key theme is personalization: adapting an LLM to a new persona with minimal data or effort. Recent research has explored parameter-efficient tuning modules that allow rapid persona swapping without retraining the entire model. PersonaPKT (Han et al., 2023) proposes representing each persona as a continuous embedding vector that can be learned from a small set of that user's dialogues. By keeping the pre-trained model fixed and only training a tiny persona-specific vector (less than 0.1% of parameters), PersonaPKT efficiently imbues the model with that user's speaking style and preferences. In a related vein, PPlug (Liu et al., 2025b) introduced a plug-and-play user encoder that on-the-fly computes a user embedding from their conversation history . Instead of a static learned vector, it employs a small model to read a user's past messages and output a "personal embedding" summarizing their quirks and facts. This embedding is then prepended to the LLM's input to personalize the response. Such design lets the LLM be dynamically personalized each turn based on context, and experiments showed significant gains in personalization metrics across tasks.

As LLMs are used to power multiple characters simultaneously, it becomes important to switch personas quickly and even maintain many personas at once. Neeko (Yu et al., 2024b) addresses this with a dynamic LoRA (Low-Rank Adapter) framework for multi-character role-play. It pre-trains a separate LoRA module for each character and uses a gating network to activate the appropriate one based on the dialogue context. This incremental ability means an unlimited number of personas can gradually accrue, each encapsulated in a plug-in adapter. An agent can seamlessly swap roles by toggling adapters, which showed superior consistency when one model needed to portray many characters in a group chat. Another challenge is preserving persona over multiple dialogue rounds. Standard fine-tuning often splits dialogues into independent turns, which can break character memory. MIDI-Tuning (Wang et al., 2024c) proposes to explicitly model the user and system roles with separate adapters and a round-level state. In their framework, an LLM-based agent is trained by alternating between a "user adapter" (processing user utterances) and an "agent adapter" (generating responses), carrying hidden state forward through turns.

Reinforcement Learning While supervised learning can teach a model a persona, it doesn't explicitly punish lapses. Reinforcement learning (RL) provides a way to directly optimize consistency and other long-horizon behaviors. Shea & Yu (2023) demonstrates this by applying offline RL to a dialogue model for persona consistency. They took an existing high-quality chatbot and defined a reward that penalizes persona breaks (e.g. contradicting provided profile or previous statements) and rewards in-character responses. Rather than interact with humans live, they performed RL on a static dataset of conversations – adjusting the model's policy to maximize the persona consistency reward while leveraging off-policy data. The result was a chatbot that, in human evaluation, more reliably adhered to its given persona description and avoided contradictions compared to its purely supervised counterpart. This work bridged the gap between static fine-tuning and RLHF: it shows one can inexpensively refine a model to be more in-character by offline RL on existing dialogues, getting some benefits of RL (direct control of behavior) without an expensive online loop.

Another aspect of multi-turn role-play that benefits from RL-like thinking is maintaining long-term coherence. COMEDY (Chen et al., 2025c) approaches this via a compressive memory mechanism that can be seen as the model "reinforcing" important memory content over a conversation. Instead of a traditional retrieval pipeline, COMEDY has the LLM periodically summarize and compress the dialogue history (including user persona hints and past events) into a concise memo, which is fed back into itself for future responses. This one-model architecture learns through supervised fine-tuning to generate useful summaries (e.g. remembering the user's preferences or the agent's own backstory) and to consult them when answering. While not an RL in algorithm, COMEDY's design implicitly optimizes a long-term reward: the compressed memory serves to avoid contradictions and boring repetition, much like an RL agent maximizing a reward for user engagement would learn to recall relevant facts.

Benchmarks & Evaluation   As role-playing agents become more advanced, evaluating their effectiveness requires moving beyond standard metrics like BLEU or response fluency. Instead, the field has introduced a suite of specialized benchmarks to assess whether an LLM can faithfully embody a persona, maintain consistency over time, interact appropriately in social settings, and remain aligned with ethical norms.

One line of work focuses on general personalization. The LaMP benchmark (Salemi et al., 2024) evaluates whether LLMs can adapt to user-specific profiles across a range of tasks—such as rewriting text in a personalized tone or classifying based on individual preferences. While not limited to dialogue, LaMP highlights the broader need for systems that understand and leverage identity cues, and confirms that retrieval-based methods are especially effective for on-the-fly personalization.

A more targeted category of benchmarks examines character-specific fidelity. CharacterEval (Tu et al., 2024) is a Chinese benchmark featuring 77 characters from novels, each with multi-turn dialogues and detailed profiles. It defines 13 metrics across four dimensions – including character consistency, behavior realism, and conversational quality – and provides human and model-based evaluation for each. CharacterEval revealed that even GPT-4, when role-playing in Chinese, could be outperformed by fine-tuned local models on consistency, indicating that specialized training made a measurable difference. On the English side, RoleEval (Shen et al., 2023a) poses factual and commonsense questions about 300 well-known characters, assessing whether models accurately retain and apply character-specific knowledge. Results show that global models like GPT-4 excel with internationally known figures, while locally fine-tuned models do better with culturally specific roles. Meanwhile, TimeChara (Ahn et al., 2024) explores a new dimension—temporal consistency—by checking if a model role-playing a character at a given point in a story inadvertently leaks future events. Even the strongest models often violate timeline boundaries, suggesting the need for narrative-aware mechanisms to constrain temporal knowledge. SimulBench (Jia et al., 2025) is a benchmark assessing LLM performance in interactive simulation scenarios – imaginative, role-playing and tool-use tasks that unfold over multiple turns. The benchmark includes tasks like acting as a Linux terminal, playing text-based games, and complex, long-horizon simulations requiring dynamic interaction with a user.

Moving from factual to psychological evaluation, InCharacter (Wang et al., 2024g) assesses if a role-playing agent truly internalizes a character's personality. It uses an interview-style personality test: the agent (in role) is asked a battery of questions akin to a psychological survey, and its answers are compared to the expected personality profile of the character. Complementing this, RoleInteract (Chen et al., 2024d) evaluates social interaction skills at two levels: one-on-one conversation quality (empathy, politeness, etc.) and group dynamics (how well an agent plays its role in a multi-agent conversation). RoleInteract includes 500 characters and diverse scenarios (e.g., an office meeting with several personas). One finding was that some agents that excel in bilateral chat struggled in group settings – sometimes a normally consistent character would conform or get sidetracked when other AI characters were present, indicating influence and social pressure effects.

A different angle on evaluation is to test how well models understand a character from source material. Yuan et al. (2024) argue that a truly aligned role-play model should be able to read a narrative and produce a coherent character profile. They created the CROSS dataset of expert-written character profiles (covering attributes, relationships, events, and personality) for characters in novels. Models are evaluated on how well they can generate similar profiles after "reading" the novel (or being given chapters as input). In addition to intrinsic metrics (overlap with the expert profile), they evaluate extrinsically via a motivation recognition task: given a scenario from the story, does the model's profile help it answer why the character acted a certain way. Such evaluation drives home that role-play is not only about output style, but also about the model's internal model of the character.

Overall, the rapid advancements in LLM-based role-playing research demonstrate a clear evolution: moving from basic persona adherence to sophisticated, adaptable, multi-agent interactions, supported by advanced evaluation and continuous alignment efforts. This evolution highlights ongoing efforts toward creating engaging, realistic conversational agents capable of sustained, immersive role-play interactions. Such role-playing also plays a crucial role throughout all conversational engagement cases discussed in the remaining subsections.

2.2.2 Conversational Engagements in Healthcare

Healthcare is one of the key domains where multi-turn conversational large language models (LLMs) demonstrate significant potential. A defining characteristic of these models in the medical domain is their ability to emulate a doctor's role by engaging in task-oriented, context-aware dialogues with patients. Unlike single-turn medical knowledge question-answering systems, such as BenTsao Wang et al. (2023a) (formerly named HuaTuo), ChatMed, ShenNong-TCM, MING Liao et al. (2024a), and DoctorGLM Xiong et al. (2023), responding to isolated queries with full information at a time Mutabazi et al. (2021), multi-turn healthcare LLMs operate in a setting where patient information is often incomplete or ambiguous at the outset.

Ideally, multi-turn healthcare conversational LLMs should be capable of proactively generating a sequence of questions to refine their understanding of the patient's condition through iterative inquiry. This concept has been referred to by different names in various studies, including chain of questions (CoQ) (Chen et al., 2023), proactive questioning (Chen et al., 2023), symptom inquiry (Zhang et al., 2023; Liao et al., 2024b), proactivity (Bao et al., 2023), and information seeking (Li et al., 2024). Despite the differences in terminology, they all describe the model's ability to **dynamically gather relevant details over multiple exchanges, ultimately leading to a more accurate diagnosis.** Additionally, multi-turn healthcare LLMs need to retain dialogue history, so that enabling seamless continuity in conversations, and integrate medical knowledge to ensure responses are accurate, reliable, and contextually appropriate.

While prior surveys Valizadeh & Parde (2022); Shi et al. (2024c) provide a broad overview of medical dialogue systems, including both pre-LLM and LLM-based approaches, our focus is specifically on multi-turn LLMs and related evaluation framework. Traditional medical dialogue systems typically rely on rule-based logic or task-specific neural networks, which can be rigid and require extensive manual engineering. We explore the specific tasks these models address, the architectural advancements in their development, and the characteristics of the datasets used for pre-training and fine-tuning. In addition, we discuss the evaluation frameworks used to assess these models, highlighting key metrics, established benchmarks, the growing focus on their information-seeking capabilities, and the challenges faced in online conversational healthcare systems.

Conversational Medical LLMs Development   The development of multi-turn healthcare LLM methods has seen significant progress. The following collected LLMs demonstrate the efficacy of customized training methodologies, curated data sets, and evaluation metrics, in improving healthcare domain performance, showing the potential of LLMs in advancing medical and psychological applications.

Several studies have aimed to make medical LLM communication more interactive and accessible. Clinical Camel (Toma et al., 2023) is an open-source medical LLM that introduces dialogue-based knowledge encoding (DBKE) to transform dense medical texts into conversational formats, enhancing multi-turn dialogue capability. Fine-tuned from LLaMA-2 via QLoRA, Clinical Camel outperforms GPT-3.5, GPT-4, and Med-PaLM2 on benchmarks including USMLE (FSMB, 2023), PubMedQA (Jin et al., 2019), and MedQA (Jin et al., 2021). T-Agent (Hu et al., 2024) enhances medical dialogue generation through a term-aware approach, integrating a term extraction tool and a term prediction model within a two-stage training framework; experiments demonstrate improvements in ROUGE scores and term extraction F1. In contrast, APP (Ask Patients with Patience) (Zhu et al., 2025) operates as a reasoning and guidance layer atop an existing LLM to support diagnostic decision-making in online consultations, emphasizing grounded reasoning, entropy minimization, and patient-centered communication without requiring additional fine-tuning.

A majority of studies have focused on building medical LLMs that generate accurate and reliable responses in dialogue settings through SFT on healthcare-specific data. DISC-MedLLM (Bao et al., 2023) is fine-tuned on DISC-Med-SFT, a 400K-sample Chinese medical instruction dataset covering single-turn Q&A, multi-turn consultations, and multiple-choice Q&A, evaluated via rule-based accuracy for single-turn and GPT-4 scoring for multi-turn conversations across proactivity, accuracy, helpfulness, and linguistic quality. BianQue (Chen et al., 2023) integrates multi-turn doctor–patient Q&A to enable a Chain of Questioning (CoQ) approach that emulates real consultations, fine-tuned on ChatGLM-6B using the 2.4M-sample BianQueCorpus, improving CoQ by balancing questions and suggestions. BiMediX (Pieri et al., 2024), a bilingual mixture-of-experts LLM supporting English and Arabic, is fine-tuned via QLoRA and outperforms Med42 and Meditron on

English medical benchmarks while substantially surpassing the bilingual Jais-30B on Arabic and bilingual assessments. In psychological counseling, CPsyCounX (Zhang et al., 2024a) is fine-tuned over InternLM2-7B-Chat on CPsyCounD—3,134 high-quality multi-turn consultation dialogues—while PsycoLLM (Hu et al., 2025b) is fine-tuned on single-turn Q&A, multi-turn dialogues, and knowledge-based Q&A atop Qwen1.5-14B-Chat. Complementing these, the SMILE method (Qiu et al., 2024) leverages ChatGPT to convert single-turn counseling pairs from PsyQA (Sun et al., 2021) into multi-turn dialogues via diverse topic prompts and format filtering, yielding SMILECHAT, a corpus of 55K multi-turn counseling dialogues in Chinese.

Beyond SFT alone, several studies adopt a comprehensive pipeline encompassing pre-training, SFT, and RLHF. Zhongjing (Yang et al., 2024), the first Chinese medical LLaMA-based LLM, exemplifies this through continuous pre-training, targeted SFT, and RLHF optimization. The authors construct CMtMedQA—approximately 7,000 QA pairs from authentic doctor–patient exchanges across 14 clinical departments and over 10 medical scenarios—and apply a self-instruct methodology (Wang et al., 2023b) to standardize responses into a uniform, professional, and empathetic style. The external medical knowledge graph CMeKG (Byambasuren et al., 2019) is further integrated to verify medical accuracy and safety. HuaTuoGPT (Zhang et al., 2023) fine-tunes a medical consultation LLM on data distilled from ChatGPT and real-world clinical data, using RLAIF to align outputs with the complementary strengths of both sources. Evaluation spans rule-based NLP metrics, LLM-based assessment of language quality and diagnostic utility, and expert human evaluation of diagnosis and treatment accuracy, demonstrating superior performance over baselines. The same team subsequently developed HuaTuoGPT II (Chen et al., 2024f), which adopts a one-stage domain adaptation protocol that unifies heterogeneous pre-training and supervised data into a unified instruction-output format for efficient knowledge injection, achieving performance competitive with GPT-4 on multiple benchmarks and excelling in Chinese medical and pharmacist license examinations.

Several studies also incorporate Direct Preference Optimization (DPO) into the full training pipeline. Aquila-Med (Zhao et al., 2024) undergoes continued pre-training, SFT, and DPO using 12,727 preference pairs, demonstrating significant improvements in fluency, relevance, completeness, and proficiency across single- and multi-turn medical consultations. Similarly, Qilin-Med (Ye et al., 2023) employs a multi-stage pipeline combining domain-specific continued pre-training, SFT, and DPO over the ChiMed dataset (Tian et al., 2019)—encompassing question answering, plain text, knowledge graphs, and dialogues. SFT improves accuracy over the Baichuan-7B baseline on CMExam (Liu et al., 2023), while the subsequent DPO phase achieves BLEU-1 of 16.66 and ROUGE-1 of 27.44 on the Huatuo-26M test set, reflecting further gains beyond SFT.

In addition to the mainstream approaches, Google's Articulate Medical Intelligence Explorer (AMIE) (Tu et al., 2025) represents a comprehensive advancement in conversational medical AI for training and evaluation. AMIE utilizes a chain-of-reasoning strategy within a simulated environment, incorporating self-play and automated feedback mechanisms to enhance its diagnostic dialogue capabilities across diverse medical conditions. Its training data includes both human-curated and AI-generated datasets, encompassing multiple-choice medical questions, long-form medical reasoning queries, clinical note summaries, and simulated dialogues based on various medical conditions. Evaluated through a randomized, double-blind crossover study using Objective Structured Clinical Examination scenarios, AMIE demonstrated superior diagnostic accuracy compared to primary care physicians and received higher ratings from both specialist physicians and patient actors on multiple assessment criteria.

Multi-turn Medical LLM Evaluation framework Beyond the development of large language models (LLMs), we also found a growing body of literature focused on designing evaluation frameworks specifically for medical LLM systems, as traditional LLM evaluation methods often fall short in addressing the complexity and safety requirements of clinical applications.

Recent studies have proposed evaluation frameworks for medical LLMs that emphasize interactive quality, clinical reasoning, and human-centered communication. MedGPTEval (Xu et al., 2023) assesses LLMs like ChatGPT and Dr.PJ using 27 multi-turn dialogue cases and 7 case reports, measuring the accuracy, empathy, and clinical logic of the LLMs' responses. Similarly, Liao et al. (2023) proposes an automated evaluation framework, emphasizing assessing LLM abilities, such as recognizing knowledge limitations, gathering relevant information, and improving diagnostic accuracy. The researchers reformulated medical multiple-choice questions from the USMLE into consultation tasks, creating a specialized benchmark for assessment. Addi-

tionally, they verify that fine-tuning with a consultation-specific dataset reduced hallucinations and improved benchmark performance.

Besides, a growing number of studies emphasize simulation-based interactive evaluation to approximate real-world clinical consultation. For instance, Liao et al. (2024b) introduces the Automated Interactive Evaluation (AIE) framework featuring the State-Aware Patient Simulator (SAPS), which incorporates a state tracker, memory bank, and response generator to support dynamic, multi-turn evaluation. Similarly, MMD-Eval (Multi-turn Medical Dialogue Evaluation) (Liu et al., 2025c) offers a locally deployable, task-oriented dialogue simulator, providing more resource-efficient and consistent evaluations than LLM-based scoring. MediQ (Li et al., 2024) introduces an interactive benchmark for medical evaluation by simulating clinical interactions between a patient system and an adaptive expert system, emphasizing the assessment of information seeking ability. It employs abstention strategies to better estimate confidence and determine when to seek additional information. The benchmark converts existing datasets like MedQA and Craft-MD into interactive formats, simulating clinical interactions for evaluation purposes.

Complementing these efforts, MedFuzz (Ness et al., 2024) focuses on evaluating the adversarial robustness of healthcare LLMs by introducing ambiguous or unexpected inputs that could lead to clinical misconceptions and harmful decisions. It questions the assumption that high benchmark scores reflect real-world reliability by introducing complexities like ambiguous patient traits and biased data into medical QA benchmarks. Results show that GPT-3.5, GPT-4, and Med-PaLM 2 perform worse on the "MedFuzzed" benchmark, showing their vulnerability to clinical biases, demographic stereotypes, and incomplete data interpretation.

Recently, OpenAI introduced *HealthBench* (Arora et al., 2025), an open-source benchmark constructed from real-world healthcare conversations designed explicitly for evaluating LLM performance. HealthBench includes 5,000 multi-turn conversations averaging 2.6 turns per dialogue (ranging from 1 to 19 turns), capturing diverse and realistic patient-clinician interactions. It emphasizes clinical accuracy, appropriate communication depth, handling of uncertainty, and context awareness. Unique to HealthBench is its extensive use of physician-developed rubrics, consisting of over 48,000 distinct evaluation criteria, making it a robust tool for assessing nuanced aspects of clinical dialogue. Moreover, HealthBench introduces specialized subsets such as *HealthBench Consensus*, validated across multiple experts, and *HealthBench Hard*, comprising notably challenging interactions that test the limits of current LLM capabilities. This systematic, clinician-validated approach significantly enriches the landscape of multi-turn medical LLM evaluation by explicitly aligning automated assessment closely with clinical judgment.

In the development of healthcare conversational LLMs, a widely adopted strategy is to construct multi-turn medical dialogue datasets and fine-tune models using SFT, sometimes followed by RL-based methods. Interestingly, while some studies in general multi-turn dialogue suggest that SFT+RLHF may not yield significant improvements, this pipeline has proven surprisingly effective in the healthcare domain. This may be attributed to the relatively high quality and domain specificity of medical data, which contrasts with the noisier, less structured data used in broader multi-turn applications. Evaluation metrics in this area include traditional rule-based NLP measures (e.g., BLEU and ROUGE), diagnostic accuracy, and both AI-based and human assessments using more nuanced, subjective, domain-knowledge judgment criteria. However, very few papers conduct the human and AI agreement check (Tu et al., 2025; Liao et al., 2024b; Chen et al., 2024f), even if a considerable of literature use both of them. Notably, information-seeking and clinical reasoning are essential capabilities in this domain and are increasingly prioritized in newer benchmarks, which now place more emphasis on clinical relevance than conventional NLP metrics. Please refer to the appendix for details on the papers discussed.

2.2.3 Conversational Engagements in Education

Multi-turn conversational systems are increasingly central in education, enabling dynamic back-and-forth interactions that mimic human tutoring. Recent work can be grouped into three key areas: Intelligent Tutoring Systems, which use dialogic exchanges to teach or guide students; Automated Grading & Feedback, where AI provides iterative evaluation and comments on student work; and Scenario Simulation, which involves simulating students or classrooms with AI agents. Below, we survey advances in each category, highlighting how multi-turn conversation enhances educational effectiveness.

Intelligent Tutoring System

Socratic and Strategy-Guided Tutoring   Early LLM-based tutors often fell into a simple question-answer pattern, providing direct answers and explanations that made students passive. To address this, researchers have developed Socratic and guided approaches that engage learners in multi-turn dialogue. SocraticLM (Liu et al., 2024a) is a notable example, proposing a "thought-provoking" teaching paradigm in which the tutor asks open-ended questions and prompts the student's reasoning instead of giving away solutions. SocraticLM was trained on SocraTeach, a new dataset of 35k multi-turn dialogues where a simulated teacher guides students with diverse cognitive states through math problems. Similarly, Kargupta et al. (2024) tackle the "answer-too-direct" issue in the coding domain with TreeInstruct, an LLM-based tutor that plans a hierarchy of questions to help students debug code. TreeInstruct models the student's knowledge state and asks targeted questions for each error, effectively guiding learners to independently correct mistakes. It achieved state-of-the-art results on code debugging benchmarks and demonstrated in a user study that students could fix bugs with minimal direct hints.

Beyond specific algorithms, others have explored controlling LLM tutors through high-level pedagogical strategies. StratL (Puech et al., 2025) introduces a pedagogical steering framework that optimizes prompts to guide an LLM tutor along a predefined teaching plan represented as a graph, rather than allowing unconstrained generation. Applied to Productive Failure—a strategy where students wrestle with problems before receiving instruction—StratL successfully steers the tutor to withhold answers and encourage trial-and-error. In a field experiment with 17 high school students, the StratL-guided tutor adhered to the target strategy and facilitated student-driven discovery. Collectively, these efforts mark a shift from straightforward Q&A toward multi-turn, strategy-aware dialogue, bringing LLM tutors closer to human teachers who ask, hint, and adapt rather than simply tell.

Adaptive Tutoring   Traditional intelligent tutoring systems often suffered from a "one-size-fits-all" design that poorly accommodated individual learners. PACE (PersonAlized Conversational tutoring agEnt) (Liu et al., 2025a) directly addresses this limitation by explicitly modeling student learning styles and personas. Built on the Felder–Silverman learning style model, PACE's multi-turn tutor adapts its explanations accordingly—providing concrete examples for sensory learners and abstract prompts for intuitive ones—while employing Socratic questioning to stimulate critical thinking. To support this, the authors construct a new dataset of personalized tutoring dialogues simulating students with diverse backgrounds and personalities interacting with an LLM tutor.

Moreover, LLM tutors can track a student's step-by-step reasoning in multi-turn exchanges and provide targeted help at the right moment. This ability to model the student within the conversation marks a key advantage of multi-turn tutoring. An illustrative real-world deployment is JeepyTA (Liu et al., 2025d), a GPT-based virtual teaching assistant used in an online course forum. JeepyTA monitors student questions on course material and responds in seconds with context-specific help, adapting its style to the informal, conversational tone of forum discussions. It distinguishes logistical queries from conceptual ones and provides hints or explanations accordingly. By continuously engaging with students' follow-up questions, such an always-on conversational TA exemplifies how personalization and instant adaptivity can scale via LLMs.

Evaluating LLM Tutoring in Mathematics   Recent research further explores ways to deepen assessments of LLM tutoring capabilities, particularly regarding their subject expertise and pedagogical effectiveness in mathematics. An influential early example is the work of Macina et al. (2023), who introduced *MathDial* to systematically evaluate LLMs' abilities as tutors, emphasizing faithful and equitable teaching. Their approach involved collecting high-quality, teacher–student dialogues through human–LLM interactions, with InstructGPT simulating student behaviors—including common misconceptions—and expert annotators assuming the teacher role. Diverse student responses were elicited using temperature sampling, prompting the LLM to generate realistic errors. Human teachers then employed scaffolding strategies to guide the simulated students toward solutions. Dialogue quality was ensured through rigorous human annotation. Evaluation metrics included the simulated student's success rate and the telling@k score, indicating how frequently teachers prematurely revealed answers. Models fine-tuned on the MathDial dataset demonstrated improved student outcomes by emphasizing hints and prompting over direct answers. Similarly, Ding et al.

(2024) introduce *SocraticLLM*, a knowledge-enhanced model emulating Socratic questioning to foster critical thinking and self-discovery. To support this method, they developed the publicly available *SocraticMATH* dataset, containing structured Socratic dialogues that cover 513 primary-school math topics. Another benchmark, *MathTutorBench* by Macina et al. (2025), specifically targets one-on-one math tutor–student dialogues, assessing LLM tutors across multiple dimensions, including Math Expertise (accuracy in problem-solving), Student Understanding (ability to diagnose and correct misconceptions), and Teacher Response Quality (effectiveness in providing hints and Socratic guidance).

Most recently, retrieval-augmented generation (RAG) techniques have further advanced the field. For instance, Feng et al. (2024) develop *CourseAssist*, a system that grounds tutor-generated responses explicitly in course syllabi and lecture notes, ensuring alignment with instructor expectations. Levonian et al. (2025) explore alignment methods to enhance generative tutors' outputs, making responses safer, pedagogically appropriate, and closely relevant to student queries, significantly improving multi-turn algebra tutoring dialogues. Expanding upon this theme, Scarlatos et al. (2025) argue for the necessity of adaptive AI tutors that subtly adjust responses across dialogues, strategically guiding students toward correct understanding without explicit intervention. They operationalize this idea by generating multiple potential tutor replies at each conversational turn and then assessing them with a student model—which predicts students' subsequent correctness—and a pedagogical evaluator. By ranking tutor responses based on these dual criteria, they successfully fine-tune a new tutor model through direct preference optimization, thereby rewarding interactions that consistently promoted student learning.

Bridging Research and Real Classrooms   The emerging trend in conversational tutors involves integrating research insights directly into classroom practice, facilitated by the increasing availability of large language models tailored specifically for education. Major industry players, including Google with LearnLM (Wiggers, 2024) and Anthropic with Claude for Education (Anthropic, 2025), have actively embraced this approach, developing specialized educational versions of their flagship AI models. These initiatives reflect a convergence between academic research and industry applications, emphasizing personalized, adaptive tutoring methods grounded in evidence-based dialogue strategies and instructional principles.

Automated Feedback & Grading Support

Automated Feedback Support   Large language models are increasingly leveraged to generate automated feedback and grading, aiming to support instructors with large-scale assessments (Silva & Costa, 2025). Similarly, in open-ended writing tasks, LLMs can produce fluent and plausible comments that appear insightful, yet often include content not grounded in the student's work (Jia et al., 2024b). This lack of faithfulness (e.g. fabricated critiques or irrelevant suggestions) is a critical limitation, as unfaithful feedback can mislead or confuse learners. Improving the accuracy and alignment of feedback with students' actual mistakes has therefore become a central research focus.

To address these limitations, recent work has introduced strategies to make LLM feedback more interactive, adaptive, and pedagogically grounded. Daheim et al. (2024) incorporate a verification step in which an LLM first analyzes student reasoning step-by-step to pinpoint errors, then guides a tutor model to deliver targeted hints—significantly reducing hallucinated advice and improving alignment to the student's actual misunderstanding. Scarlatos et al. (2024) instead optimize feedback quality through human pedagogical preferences: they define a rubric covering correctness, encouragement, and misconception-addressing, use GPT-4 to label outputs along these criteria, and apply reinforcement learning to fine-tune the model, yielding measurably higher factual correctness and better tutoring alignment. Going further, Nair et al. (2024) close the feedback loop by having the model simulate student revisions in response to its own feedback and iteratively refine that feedback to maximize draft improvement—producing greater actual writing gains and enhanced pedagogical qualities compared to static feedback.

Studies are also examining how well LLM feedback aligns with real classroom needs and how students and instructors perceive it. Initial deployments show mixed but encouraging results. In a graduate computer science course, an automated tool generated paragraph-level comments on project reports that students found broadly helpful (Tomova et al., 2024), yet the instructor observed that the AI's comments did not always

reflect the assignment's pedagogical objectives—preferring to treat LLM output as a draft to edit rather than send directly to students (Jia et al., 2024a). This underscores a recurring limitation: LLM feedback often requires human oversight to remain consistent with instructional goals. Domain-focused deployments, however, demonstrate clearer benefits when carefully integrated. Riazi & Rooshenas (2025) develop an LLM-driven tutor for a databases course capable of analyzing student entity-relationship diagrams and generating detailed, context-specific critiques and follow-up questions. Similarly, in medical education, LLMs have been used to produce explanatory feedback for board-style multiple-choice questions; expert evaluators found such feedback relevant and useful—not a replacement for human judgment, but a meaningful supplement to the numeric scores students typically receive (Tomova et al., 2024).

Efforts like Lohr et al. (2025)'s, which prompt LLMs to produce specific types of feedback from established educational taxonomies (e.g. an error-identification vs. a hint vs. an elaboration), further illustrate the push toward more controlled and purposefully designed feedback messages. In addition to feedback itself, researchers are beginning to evaluate LLMs on related teaching skills such as asking good questions – for instance, the Dr.Academy benchmark assesses whether LLMs can generate high-quality, higher-order questions in line with Bloom's taxonomy, finding that models like GPT-4 already show strong capability in formulating deep conceptual questions. Together, these advances show a clear developmental trajectory: from basic feedback generation that often wandered off-target, to increasingly faithful, adaptive, and pedagogically-aware feedback loops facilitated by LLMs' multi-turn interaction capacity.

Automated Grading Support   In parallel with feedback generation, researchers have started leveraging LLMs to grade student work and provide evaluative judgments (scores, ratings, or rubric-based assessments). Automatic grading by AI is not entirely new, but LLMs offer a unified, flexible approach that can handle open-ended responses more like a human grader. Recent studies suggest that, for certain types of assignments, LLM graders can approach human-level performance in both consistency and accuracy. Capdehourat et al. (2025) explore LLMs for scoring short free-response questions in Spanish, a scenario involving language complexity beyond the typical English-centric datasets. They found that state-of-the-art models (including GPT-4 and advanced open-source LLMs) could predict expert graders' scores with over 95% accuracy in a three-tier grading scale, and even 98% accuracy on simpler right/wrong judgments.

Another study compared ChatGPT directly against university instructors for grading full exam papers in higher education. Out of 463 Master's-level exam responses graded, about 70% of the AI's assigned scores fell within a 10% margin of the human-given score, and 31% were within a 5% margin (Flodén, 2025). Teachers involved in the experiment expressed surprise at how closely ChatGPT's evaluations matched their own in these exams. However, important discrepancies were observed. The AI grader tended to be more conservative, avoiding very high or very low scores on individual questions.

In the domain of essay scoring, which demands understanding of content, organization, style, and often providing feedback, LLMs still struggle to meet human-level nuance. Kostic et al. (2024) conduct a case study using GPT-4 to evaluate German-language student essays at a business school . The LLM could generate a score and some comments, but it often failed to apply the rubric criteria consistently and lacked the depth of feedback that human lecturers provided. Complex aspects of writing quality (critical analysis, creativity, etc.) proved difficult for the model to judge correctly, highlighting a gap between what current LLMs can do and the "nuanced requirements" of real essay evaluation.

Scenario Simulation Recent advances have explored scenario simulation as a means to leverage LLMs for enacting multi-turn educational interactions between virtual teachers and students. Early work focused on using LLM-simulated student profiles to evaluate learning materials. For example, Generative Students introduced a prompt-based architecture (grounded in the Knowledge-Learning-Instruction framework) to instantiate diverse student profiles defined by mastered vs. confused knowledge components (Lu & Wang, 2024). Each simulated student (powered by GPT-4) answered multiple-choice questions, producing responses that aligned with its knowledge profile. Notably, these generative students exhibited answer patterns highly correlated with real student performance, correctly flagging many of the same difficult questions. This result suggested that realistic virtual learners can serve as proxies for human students in content evaluation, allowing instructors to identify problematic questions before deployment.

Subsequent research broadened the fidelity of simulated students by incorporating individual differences in ability and personality. Liu et al. (2024f) develop a personality-aware simulation framework that enriches student profiles with both cognitive level (e.g. language proficiency) and noncognitive traits (e.g. conscientiousness). In a language tutoring scenario, an LLM could then produce diverse student utterances consistent with a given persona, which in turn successfully triggered the tutor's adaptive scaffolding strategies. Building on this idea, Jin et al. (2025) introduce TeachTune, a system enabling teachers to test their pedagogical conversational agents (PCAs) against diverse simulated students. Teachers specify a student's presumed prior knowledge and motivation, and an LLM-driven student agent engages in a multi-turn chat with the PCA. This automated student–teacher dialogue reveals how well the PCA adapts its explanations and feedback to different learner needs, going beyond single-turn Q&A tests. The TeachTune pipeline ensured that each simulated student's behavior remained faithful to its profile, with measured deviations under 5–10%. These efforts highlight that richly modeled virtual students can support teacher agents and tutoring systems by surfacing potential shortcomings in adaptive instruction in a cost-effective manner.

Researchers have also scaled scenario simulation to multi-party settings. Zhang et al. (2025b) propose SimClass, a framework in which multiple LLM-based agents assume typical classroom roles. A novel class-level control mechanism orchestrates the agents' turn-taking and topic flow to emulate a live classroom lesson. In user trials with real students, SimClass was able to simulate dynamic classroom interactions featuring both teacher–student exchanges and student–student discussions. The emergent group behavior was strikingly human-like – the student agents would ask and answer each other's questions and collaboratively debate topics, creating an enlivened atmosphere. These collective simulations improved the human participant's learning experience by maintaining engagement and peer-like dialogue support. The success of SimClass demonstrates that LLMs can collectively model complex social dynamics of a classroom, opening the door to virtual class rehearsals and large-scale peer interaction scenarios.

Scenario simulation has since been extended to specialized pedagogical needs for both learners and instructors. To better support low-performing or metacognitively weak students, Li et al. (2025a) devise a pipeline that automatically generates struggling student agents with diverse learning deficiencies, then filters them through a two-round LLM evaluation—validated by human experts—to ensure authenticity. The resulting high-fidelity "at-risk" agents allow educators and tutoring systems to safely experiment with interventions targeting self-regulation and reflective thinking, without ethical concerns of testing on real students. On the instructor side, Hu et al. (2025a) use LLM-based simulation to improve lesson planning: an LLM plays out a full classroom lesson from a teacher's draft plan, simulating both instruction and student reactions, then generates a reflective critique. These simulated insights are used to iteratively refine the lesson plan before deployment. Additionally, Wang et al. (2024d) propose Book2Dial, a framework to automatically generate synthetic teacher-student dialogues from textbook content to address data scarcity in developing educational chatbots. Three dialogue-generation approaches—Multi-turn QG-QA, Dialogue Inpainting, and LLM-based Role-Playing—are introduced and evaluated using automated metrics (e.g., coherence, answerability, factual consistency) and human judgment (specificity). The results demonstrate that LLM-based Role-Playing performs best, highlighting a cost-effective method for chatbot training in educational domains.

In summary, multi-turn conversational simulations serve as a valuable sandbox for educational innovation. By leveraging LLMs to generate realistic student and teacher behaviors, researchers and practitioners can prototype and test interventions rapidly, ethically, and inexpensively. These simulations complement live studies: they can uncover issues and inform design decisions before real students are involved, and suggest which approaches merit real-world trials. From generative students for item analysis to full classrooms for teacher training, the common thread is that rich, multi-turn interactions are the fabric of these simulations.

2.2.4   Conversational Engagements in Jailbreak

In multi-turn settings, LLMs face not only heightened requirements for consistency but also an increased risk of malicious exploitation. Although LLMs excel at various tasks, their vulnerabilities can lead to harmful outputs—such as generating dangerous instructions—that highlight significant limitations compared to human judgment. The phenomenon of multi-turn jailbreaking, where adversaries bypass guardrails over a series of exchanges, has thus emerged as a critical area of concern.

Most prior research has focused on single-turn jailbreaks, in which adversaries use a single prompt—often few-shot—to trigger harmful content. For example, optimization-based methods by Zou et al. (2023) and Liu et al. (2024e) utilize gradient-derived gibberish suffixes to elicit such outputs, but these techniques depend on internal token probability knowledge and are not applicable to closed-source models. To explore alternative strategies, subsequent studies (Carlini et al., 2023; Yu et al., 2023) have investigated unconventional communication patterns, such as role-playing scenarios, and developed multi-turn conversational methods that leverage the entire dialogue history. These approaches demonstrate that multi-turn jailbreaking, where even seemingly innocuous prompts contribute to later interventions, presents a far more complex challenge.

Crescendo and ActorAttack Multi-turn jailbreak can employ more diverse strategies. Crescendo (Russinovich et al., 2025; Ren et al., 2025) is one of the strategies, which implicitly instruct victim LLMs to provide harmful information. The intuition behind this strategy is that LLMs agreeing to a small, initial request increases the likelihood of complying with subsequent, larger demands. By asking innocuous but implicitly suggestive questions, the token distribution of LLMs shifts towards the direction where tokens containing more harmful information are more likely to be generated. The multi-turn interactions as a whole jailbreaks LLMs instead of one specific questions plays the role. Besides, the implicitness of questions and the order to present the questions to LLMs are important to the success of jailbreak. Following the crescendo idea, Ren et al. (2025) generalizes the crescendo method used in Russinovich et al. (2025), where in Russinovich et al. (2025) fixed and human-crafted seed instances are needed to generate attacks, making it challenging to generate diverse attacks. In Ren et al. (2025), the novelty focuses on the process of self-discovering diverse attack clues inside the model's prior knowledge via network structures and the classification of the clues, by constructing the two-layer relation tree according to Latour's actor-network theory (Latour, 2005).

Decomposition Another important strategy for multi-turn jailbreaks is to decompose the one harmful prompt into several pieces where each contains less malicious contents (Gibbs et al., 2024; Zhou et al., 2024c; Liu et al., 2024c). Therefore, language models can incrementally generate harmful content through multi-turn dialogue. By decomposing the original malicious query into several less harmful sub-questions can evade the guardrail of LLMs and induce harmful responses. Due to the in-context learning capabilities, harmful knowledge can be gathered together in the final turn. Using such decomposition, alignment is quite successful for each turn in a multi-turn dialogue, except the final turn when all responses are gathered and combined. However, the cumulative harmful content across the dialogue results in an overall alignment failure. Following the idea, Wang et al. (2024a) train a red-team jailbreak agent through the interactions with target LLMs to generate decomposed yet coherent jailbreak prompts. Jiang et al. (2024b) propose a scenario-based jailbreak method to disguise the malicious intent from guardrails of LLMs, assuming LLMs can only detect direct harmful intent but would be misled if the attacker creates a scenario claiming that others are planning harmful actions and positioning the attacker as the protector. The attack is decomposed into multi-turns, where the attacker firstly describes others' harmful intent and seeks prevention, secondly asks about possible evidence items, finally requests an example harmful plan for comparison.

Datasets for Multi-Turn Jailbreaks AdvBench (Zou et al., 2023) and HarmBench (Mazeika et al., 2024) are two widely used benchmarks for jailbreaking LLMs. AdvBench provides 500 harmful behavioral instructions and 500 harmful/toxic strings, while HarmBench contains 510 unique harmful behaviors spanning 400 textual and 110 multimodal instances. Though neither is designed specifically for multi-turn jailbreaks, both serve as representative testbeds. Building on them, Russinovich et al. (2025) manually craft Crescendo multi-turn prompts, while Ren et al. (2025) scale attack-chain generation via LLM self-talk guided by six clues from Latour's actor-network theory, compiling the results into SafeMTData. Gibbs et al. (2024) apply a word substitution cipher (Handa et al., 2024) to HarmBench data processed with Mixtral-8x7b to isolate the effect of multi-turn structure, and Zhou et al. (2024c) use a decomposed version of AdvBench for jailbreaking. In contrast, Liu et al. (2024c) draw from HarmfulQ (Shaikh et al., 2023)—200 explicit harmful questions in English—for multi-turn jailbreak construction. Wang et al. (2024a) use AdvBench for training and JBB (Chao et al., 2024) for evaluation, while Jiang et al. (2024b) leverage the BeaverTails dataset (Ji et al., 2023)—covering malicious queries across 14 refusal-test categories—and apply sentence transformers (Ni et al., 2022) to generate multi-turn dialogues and harmful actions targeting GPT-4o.

Defenses against Multi-Turn Jailbreaks While numerous multi-turn jailbreak methods have been proposed, effective defenses specifically targeting such attacks remain scarce. Conventional approaches—perplexity filters, input/output filters, rephrase/retokenize, and random token dropping—show limited efficacy against extended conversational attacks. Among targeted efforts, Yu et al. (2024a) show that system prompts combined with Chain-of-Thought reasoning (Wei et al., 2022) can partially counteract attacks by refusing harmful queries, albeit at the cost of reduced helpfulness. Gibbs et al. (2024) find that NeMoGuardrails (Rebedea et al., 2023) can be overzealous, flagging even benign prompts, and Liu et al. (2024c) observe that stronger defenses frequently compromise usability. Collectively, these findings reveal a stark security–usability trade-off, underscoring the urgent need for adaptive, context-aware defense strategies that maintain both robustness and user-friendly performance.

3   Improvements

Recent advances in enhancing multi-turn interactions with Large Language Models (LLMs) have pursued diverse approaches that address the unique challenges of extended conversations. As illustrated in our taxonomy (Fig. 1), current improvement methods can be categorized into three main branches: (1) Model-Centric Approaches, which focus directly on adapting and refining LLMs to better handle sequential dialogue dynamics through strategies such as in-context learning, supervised fine-tuning, reinforcement learning, and novel architectures (§3.1); (2) External Integration Approaches, which augment LLM capabilities by incorporating external resources, including memory structures, retrieval mechanisms, and knowledge graphs, to mitigate context limitations and ensure factual consistency (§3.2); and (3) Agent-Based Approaches, which represent a paradigm shift toward treating LLMs as proactive, iterative agents that interact either individually or collaboratively to manage complexity and enhance reasoning over sustained interactions (§3.3). Collectively, these methods represent an evolving toolkit that significantly expands the potential for sophisticated, context-aware, and reliable multi-turn interactions with LLMs.

Figure 1: Taxonomy of Improvements Methodologies in Multi-turn LLM Interactions.

3.1 Model-Centric Approaches

This section surveys key model-centric strategies aimed at improving the performance of LLM on multi-turn interaction tasks. As dialogue tasks shift from static, single-turn queries to dynamic, multi-turn exchanges, traditional modeling techniques often fall short. We examine four major approaches that address these challenges from different angles: (1) In-Context Learning, which explores prompt-based adaptation using multi-turn exemplars (§3.1.1); (2) Supervised Fine-Tuning, which focuses on data curation and training strategies for maintaining coherence and context over multiple rounds (§3.1.2); (3) Reinforcement Learning, which aligns multi-turn behaviors with human preferences through trajectory-level optimization (§3.1.3); and (4) New Architectures, which reimagine the Transformer design to better support long-range memory and dialog flow (§3.1.4). Together, these techniques represent an evolving toolkit for building LLMs that can reason, remember, and respond effectively in sustained interactions.

3.1.1 In-Context Learning

In-context learning (ICL) (Dong et al., 2024a) in multi-turn settings yields nuanced outcomes according to recent empirical studies. While providing exemplars usually aids single-turn tasks, naive in-context prompting with interactive multi-turn examples can sometimes hurt performance in sequential dialog scenarios (Yang et al., 2025b). For instance, on the AQA-Bench sequential reasoning benchmark, certain models (e.g. LLaMA2 and DeepSeek-LLM in a coin-guessing game environment) actually saw their accuracy drop when given a single in-context demonstration, recovering only as more examples were provided. This surprising inversion of the typical few-shot benefit is attributed to the multi-round nature of the examples, which may cause overfitting to specific interaction trajectories. In other words, multi-turn example formats behave differently from standard one-turn Q&A prompts. Consistent with this, dedicated dialogue benchmarks like MT-Bench (Zheng et al., 2023) and its fine-grained successor MT-Bench-101 (Bai et al., 2024) highlight that multi-turn interactions demand evaluating facets such as context retention, proactivity, and adaptability that one-shot QA tests often overlook.

Across diverse domains, a variety of prompting techniques have been explored to improve multi-turn LLM interactions, with mixed empirical results. In code generation, interactive multi-turn prompting proves beneficial: the InterCode benchmark (Yang et al., 2023) shows that step-by-step reasoning strategies such as Chain-of-Thought (Wei et al., 2022) and ReAct, or iterative plan-and-refine prompting, yield concrete performance gains by leveraging compiler feedback across turns. In the clinical domain, Clinical Camel (Toma et al., 2023) uses dialogue-based knowledge encoding to cast medical texts into a Q&A format, surpassing GPT-3.5 on multiple medical benchmarks in few-shot evaluations. By contrast, persona-driven prompts do not universally improve objective accuracy: a systematic study found that adding a persona via system prompts generally fails to boost factual question-answering performance (Zheng et al., 2024a). Nevertheless, persona-centric role-play can enhance conversational quality in the right context—CharacterChat (Tu et al., 2023) employs MBTI-aligned personas with preset behaviors and dynamic memory, facilitating effective personalized social support dialogues. Finally, explicitly steering dialogue structure shows promise: StratL (Puech et al., 2025) optimizes prompts to guide an LLM tutor along a predefined teaching plan, successfully inducing a more pedagogically effective multi-turn tutoring strategy in practice.

Collectively, these findings suggest that the impact of ICL and prompt design on multi-turn performance is highly context-dependent: gains emerge when the prompting strategy aligns well with the task's interactive dynamics, while misaligned or naive prompts can degrade performance in complex multi-turn settings.

3.1.2 Supervised Fine-Tuning

Classic supervised fine-tuning (SFT) methods like InstructGPT (Ouyang et al., 2022) and FLAN (Chung et al., 2024), along with parameter-efficient techniques such as AdapterDrop (Rücklé et al., 2021) and LoRA (Hu et al., 2022), have driven major progress in single-turn LLM tasks. A comprehensive survey of SFT is provided by (Zhang et al., 2026). However, to enhance LLMs' multi-turn interaction ability, SFT must be modified; as Wang et al. (2024f) point out, treating each round independently can lead to context forgetting and incoherent responses can lead to context forgetting and incoherent responses in multi-turn

dialogues. This limitation has motivated the development of tailored strategies that both leverage realistic multi-turn data and adjust training methods to fully exploit such data.

SFT remains one of the most widely used techniques for improving multi-turn LLM performance. As discussed in §2, incorporating domain-specific multi-turn interaction data into SFT consistently yields further gains. Evidence spans multi-turn instruction following—including math reasoning and multilingual contexts (Bai et al., 2024; Maheshwary et al., 2025; Liang et al., 2024)—role-play (Ding et al., 2023; Occhipinti et al., 2024), and clinical dialogue (Toma et al., 2023; Zhang et al., 2023; Bao et al., 2023; Yang et al., 2024; Liao et al., 2023; Ye et al., 2023; Zhao et al., 2024; Pieri et al., 2024; Wang et al., 2024d; Macina et al., 2023; Scarlatos et al., 2025). These results underscore the need for further research into fine-tuning strategies tailored specifically to multi-turn settings.

Realistic Multi-Turn Dialogue Data Curation Recent works have addressed multi-turn challenges by generating datasets that capture natural dialogue flows. For example, Vicuna (Chiang et al., 2023) fine-tunes on user-shared ChatGPT conversations to retain genuine multi-turn interactions, though scaling such data remains costly. Other methods, such as those in UltraChat (Ding et al., 2023), use self-chat to create extensive multi-turn data; however, these auto-generated dialogues can be overly scripted and lack diversity. To mitigate these issues, approaches like PlatoLM (Kong et al., 2024b) incorporate sophisticated user simulators (e.g., the "Socratic" agent) to produce more dynamic and realistic multi-round dialogues, thereby enhancing topic shifts and follow-up naturalness. In addition, Parrot (Sun et al., 2024) generates multi-turn data by first mimicking human asking styles for query generation, then constructing negative responses that simulate context neglect or misunderstanding, and finally combining this with context-aware preference signals for fine-tuning.

Optimized SFT Approaches Alongside dataset curation, new fine-tuning strategies have been proposed to fully exploit multi-turn data, targeting loss design, context length, and training efficiency. Vicuna (Chiang et al., 2023) employs a modified loss function and extended context lengths, supported by gradient checkpointing (Chen et al., 2016) and FlashAttention (Dao et al., 2022) to handle long dialogue histories efficiently. ChatGLM2 (GLM et al., 2024) similarly extends context length while reducing GPU memory costs via multi-query attention (Shazeer, 2019) and causal masking. More generally, Teng et al. (2024) optimize a combined cross-entropy and KL divergence loss across all dialogue turns rather than the final turn alone, yielding more coherent outputs and more efficient training. Finally, Chen et al. (2025d) address multi-round gradient cancellation—where gradients from early turns can cancel those from later, more informative ones—by doubling the loss weights of the final two rounds, ensuring that the most influential guidance steps drive model updates and improving selection of optimal initial actions.

In summary, these advances illustrate two complementary avenues for enhancing multi-turn interactions in LLMs with SFT: generating realistic dialogue data and optimizing fine-tuning strategies. Together, these approaches promote better context retention and coherent multi-turn responses, marking a significant step toward more robust conversational models.

3.1.3 Reinforcement Learning

Reinforcement learning (RL) has become central to aligning LLMs with human preferences, improving their safety, helpfulness, and coherence. While initial RL successes focused on optimizing single-turn interactions using human or AI feedback, real-world conversations often span multiple turns, introducing complexities beyond single-turn methods. Addressing these challenges has motivated recent developments in specialized multi-turn RL algorithms designed explicitly for extended conversational interactions.

Single-Turn RL Reinforcement learning from human feedback (RLHF) aligns LLMs with human preferences via reward models trained on human rankings, substantially improving response quality and safety. Notably, a 1.3B-parameter InstructGPT fine-tuned with RLHF outperformed a 175B-parameter GPT-3 in human evaluations, exhibiting greater truthfulness and reduced toxicity (Ouyang et al., 2022). Reinforcement learning from AI feedback (RLAIF) extends this paradigm by substituting AI-generated feedback for human labels; Anthropic's Constitutional AI (Bai et al., 2022) exemplifies this approach, training models

via AI-authored principles and self-critique to reduce harmful behaviors without direct human supervision. Both RLHF and RLAIF have proven effective for aligning single-turn LLM responses with human values.

Early RLHF successes largely utilized Proximal Policy Optimization (PPO), an on-policy method offering stable and sample-efficient fine-tuning of large models. For example, OpenAI's InstructGPT (Ouyang et al., 2022) employed PPO to optimize human-preference-based reward models, significantly enhancing helpfulness and reducing harmful outputs with minimal performance loss on traditional NLP benchmarks.

While PPO-based RLHF is effective, it can be complex due to reward modeling and tuning. Direct Preference Optimization (DPO) (Rafailov et al., 2023) simplifies this by converting RLHF into a supervised classification task, analytically deriving optimal policies from preference models. Context-aware Preference Optimization (CaPO, (Sun et al., 2024)) extends DPO by integrating context-aware preferences, promoting correct context utilization. Additionally, Action-Based Contrastive Self-Training (ACT) (Chen et al., 2025a) applies DPO quasi-online, enhancing LLMs' clarifying behaviors in ambiguous contexts while preserving DPO's simplicity.

Many prior studies have investigated RLHF for enhancing multi-turn LLM interactions (Sun et al., 2024; Bai et al., 2024; Wang et al., 2024f; Lù et al., 2024; Du et al., 2025; Wu et al., 2024b; Yang et al., 2023; Chen et al., 2025d; Bao et al., 2023; Yang et al., 2024; Ye et al., 2023; Chen et al., 2024f; Scarlatos et al., 2024). A horizontal comparison of these works, however, reveals a nuanced and somewhat contradictory picture. On one hand, specialized domains such as medical QA (Yang et al., 2024; Ye et al., 2023) and coding (Yang et al., 2023; Chen et al., 2025d) demonstrate substantial gains from carefully implemented approaches like DPO and interactive feedback loops. Similarly, the Parrot framework (Sun et al., 2024) highlights how explicitly training on negative examples can steer models toward better contextual alignment and fewer repetitive errors.

On the other hand, broader analyses from MINT (Wang et al., 2024f) and MT-Bench 101 (Bai et al., 2024) reveal that generalized RLHF methods frequently yield limited or even negative impacts in multi-turn scenarios. This discrepancy highlights the inherent limitations of RLHF methods in terms of generalizability, emphasizing the necessity for tailored RL strategies explicitly designed for multi-turn interactions.

Multi-Turn RL Recent research has therefore extended preference optimization and reinforcement learning techniques to optimize entire conversation trajectories rather than single responses. Below, we review key developments organized by technique.

Multi-Turn DPO and Variants A straightforward way to align multi-turn behavior is to generalize the single-turn preference optimization objective across an entire dialogue trajectory. Direct Multi-Turn Preference Optimization (DMPO) (Shi et al., 2024b) is one such approach that adapts DPO to multi-turn agent tasks. A technical obstacle in multi-turn DPO is that the partition function (normalization factor) no longer cancels out between preferred and dispreferred trajectory pairs, complicating the loss computation. DMPO addresses this by re-formulating the optimization: it replaces the per-response probability ratio with a state-action occupancy measure and normalizes for sequence length differences. The result is a novel DMPO loss that comes with theoretical justification for multi-turn settings.

Related work by Xiong et al. (2025), which we covered in §2.1.2, introduced an iterative multi-turn preference learning framework with two implementations: Multi-turn DPO (M-DPO) and Multi-turn KTO (M-KTO). (Kahneman-Tversky Optimization (KTO) is a recently proposed RLHF approach inspired by prospect theory, designed to better align model outputs with human preferences by explicitly modeling decision-making biases (Ethayarajh et al., 2024).) Their focus was on mathematical reasoning agents that utilize tools (code interpreters) across multiple turns. Because single-turn preference methods did not fully capture multi-step reasoning quality, they extended DPO and the prospect-theoretic KTO loss to handle entire solution trajectories. In this framework, a reward model (augmented with tool feedback) judges the quality of a full reasoning trace, and the model is tuned to prefer better traces. Both M-DPO and M-KTO yielded substantial performance gains on math problem benchmarks: for instance, a 7B model's accuracy on GSM8K math questions jumped from 77.5% to 83.9% after multi-turn preference optimization.

Hierarchical RL and Credit Assignment   Multi-turn interactions intensify the credit assignment problem—attributing outcomes to specific decisions made across several dialogue turns. Hierarchical reinforcement learning addresses this challenge by structuring decision-making across multiple abstraction levels. ArCHer (Zhou et al., 2024b) employs a two-level architecture: a high-level module managing dialogue-turn granularity and a low-level module generating tokens within each turn. Its high-level off-policy learner computes Q-values based on accumulated dialogue rewards, guiding low-level updates via actor-critic methods. ArCHer achieves substantial sample efficiency, outperforming non-hierarchical baselines by approximately $100\times$ in terms of training samples.

DeepMind's SCoRe (Kumar et al., 2025), an extension of ArCHer, explicitly targets self-correction by training models on synthetic two-turn dialogues to recognize and rectify errors. SCoRe yields significant gains on self-correction benchmarks in math and coding. Together, hierarchical frameworks like ArCHer and SCoRe effectively address multi-turn credit assignment through structured training and specialized reward design.

Off-Policy Value Optimization   Another promising direction frames multi-turn LLM alignment as an off-policy value-learning problem. REFUEL (Gao et al., 2025b) addresses covariate shift issues in multi-turn RLHF by iteratively training a Q-value function on accumulated trajectories, directly regressing future cumulative rewards. Unlike standard on-policy methods, REFUEL continuously leverages self-generated dialogues, ensuring accurate value estimation for inference-time states. Empirically, REFUEL outperformed state-of-the-art methods like DPO on long dialogue benchmarks; notably, an 8B-parameter REFUEL model surpassed a 70B-parameter model fine-tuned via single-turn methods, highlighting the value of explicit long-term reward modeling for improved conversational coherence.

Benchmarks & Evaluation   Effectively evaluating multi-turn RL algorithms requires specialized benchmarks that capture long-horizon interaction and credit assignment. LMRL-Gym (Abdulhai et al., 2025) provides a suite of interactive language tasks—spanning open-ended dialogues to text-based games—designed to measure intentionality, information-gathering, and strategic planning over extended interactions, supporting both offline and online RL evaluation. Similarly, SWEET-RL (Zhou et al., 2025) introduces ColBench, a set of collaborative human-AI tasks emphasizing multi-turn dialogue and reasoning, where sparse delayed feedback makes traditional RL unreliable. SWEET-RL addresses this by training a turn-wise advantage critic with additional training-time signals, yielding significant gains on collaborative tasks such as coding and UI design. Together, LMRL-Gym and SWEET-RL underscore the importance of tailored benchmarks and evaluation protocols for reliably advancing multi-turn conversational abilities.

3.1.4   New Architectures

Some researchers have questioned whether inherent limitations of the Transformer architecture itself might be responsible for observed performance degradation in complex, multi-turn scenarios (Dziri et al., 2023). Motivated by this concern, in addition to advances in contextual learning, supervised fine-tuning, and reinforcement learning, recent efforts have explored optimizing LLM architectures to specifically enhance performance in multi-turn interactions.

Cached Transformers (Zhang et al., 2024d) introduce a novel model architecture that extends the traditional Transformer by incorporating a Gated Recurrent Cache (GRC) into its self-attention mechanism. This differentiable memory cache compresses historical token representations into fixed-length vectors that are continuously updated through gating, enabling the model to attend efficiently to both past and current tokens. By effectively capturing long-range dependencies without significant computational overhead, Cached Transformers improve performance on various language tasks. In multi-turn conversations, this mechanism can help LLMs maintain coherent and contextually rich dialogue histories by providing a persistent, efficient memory of earlier interactions, thereby enhancing the model's ability to reference and build upon past conversational turns.

Beyond caching, researchers are exploring stateful transformer designs that maintain an internal dialogue state. For example, Wu & Yu (2024) introduce a memory-augmented transformer (MemBART) that carries a "memory state" alongside the normal model hidden state, updated at each turn. MemBART employs a dual attention stream to separately handle memory reading and writing, along with a residual gated update

mechanism that determines how much past information to retain versus update at each timestep. This design allows the model to efficiently store and retrieve important historical context without needing excessively large input windows, thereby enhancing its ability to maintain coherent multi-turn conversations with lower computational overhead and improved latency.

Recent advances in long-context language modeling have also leveraged recurrence to extend Transformers' effective context. Transformer-XL (Dai et al., 2019) reuses hidden states from previous segments with a novel relative positional encoding to mitigate context fragmentation. The Recurrent Memory Transformer (Bulatov et al., 2022) augments this idea by inserting dedicated memory tokens into the sequence, which are recurrently updated to store global information. He et al. (2025) present a transformer framework that mimics the brain's memory hierarchy by segmenting information into sensory, short-term, and long-term layers, thereby facilitating the processing of lengthy contexts with lower computational overhead. Similarly, RWKV (Peng et al., 2023) reformulates attention in an RNN-like manner, achieving linear complexity while retaining Transformer parallelism. Enhancing RWKV-based models (Pan, 2025), recent work introduces adaptive gating and position-aware convolutional shifts to dynamically regulate inter-token information flow. All four approaches share the common goal of overcoming fixed-length limitations by propagating information across segments, thereby capturing long-term dependencies more efficiently while balancing training parallelism with inference efficiency.

Integrating memory and recurrence mechanisms allows transformers to capture long-term dependencies across segments, improving multi-turn dialogue coherence. These advances enhance model performance and efficiency, making conversational AI more robust and scalable.

3.2 External Integration Approaches

Beyond model-centric approaches, another prominent strategy involves external integration methods, where LLMs are augmented with additional resources to enhance their performance in multi-turn interactions. These approaches incorporate external tools such as memory augmentation, retrieval-augmented generation (RAG), and knowledge graphs to facilitate external information retrieval, verification, and reasoning. By leveraging these external integrations, LLMs can mitigate compounding errors and misinformation propagation commonly encountered in extended interactions, thereby significantly improving their reliability, accuracy, and consistency in multi-turn settings.

3.2.1 Memory-Augmented Methods

Memory-augmented methods address the challenge of maintaining context over extended conversations by equipping LLMs with mechanisms to store and recall past interactions. These techniques help models correct misinterpretations, reduce repeated errors, and adapt to evolving dialogue, ultimately fostering more coherent multi-turn conversations.

MemPrompt (Madaan et al., 2022) demonstrates an early external memory approach where the system records pairs of misunderstood inputs and corresponding user corrections in a dynamic memory bank. When a similar query arises later, the stored corrective feedback is retrieved and appended to the prompt, guiding the model toward a more accurate interpretation. In a related effort, Wu et al. (2025) propose a unified framework that decomposes memory design into indexing, retrieval, and reading stages. Their work introduces detailed optimizations—including session decomposition, fact-augmented key expansion, and time-aware query expansion—that significantly enhance memory recall and downstream question-answering accuracy, even for models designed with extended contexts.

Taking inspiration from human cognition, Pink et al. (2025) argue for the integration of episodic memory into LLMs. Their framework emphasizes long-term storage, explicit reasoning, and instance-specific detail capture, outlining four research directions: discretizing continuous interactions into episodes, retrieving relevant past experiences, consolidating episodic traces into generalized knowledge, and establishing benchmarks for evaluation. Meanwhile, hierarchical memory structures offer another avenue for improvement. Rezazadeh et al. (2025) introduce MemTree, a dynamic tree-based system that aggregates dialogue content into hierarchical nodes to enable efficient retrieval and improved long-term reasoning.

Together, these works illustrate that integrating external, episodic, and hierarchical memory mechanisms can substantially enhance the consistency and contextual understanding of LLMs in multi-turn conversations.

3.2.2 Retrieval Augmented Generated

Retrieval-augmented generation (RAG) is an advanced framework introduced by Lewis et al. (2020) that enhances the capabilities of NLP models by integrating external knowledge sources into the generation process. The RAG integration allows LLMs to access up-to-date and domain-specific information, improving the accuracy and relevance of their responses. It also helps mitigate AI hallucinations by grounding outputs in reliable data.

Studies have applied retrieval-based architectures to multi-turn dialogue systems, enabling the generation of more informative and factual responses by conditioning on both the user's input and relevant external documents. For instance, Wizard of Wikipedia (Dinan et al., 2018) incorporated retrieval into each dialogue turn, resulting in significantly higher factual accuracy and user engagement compared to non-retrieval baselines. Similarly, Komeili et al. (2022) explicitly generate search queries from the dialogue context to pull in up-to-date knowledge (e.g. via internet search) and then conditions the response on the retrieved results. Other variants, like Karpukhin et al. (2020), retrieve from a fixed knowledge base or enterprise documents, using dense vector search to find passages related to the user's query, where the generator model then conditions on both the dialogue context and the fetched evidence to produce a response. BlenderBot 2.0 (Xu et al., 2022) extend the RAG idea by integrating both internet search and a long-term memory component, allowing the model to sustain coherent conversations across multiple turns and sessions while retrieving past facts when needed. This allows the system to handle context dependencies that go beyond the immediate dialogue window. Overall, RAG offers a principled mechanism for overcoming the context length and memory limitations of LLMs, making it a valuable technique for improving dialogue coherence, answer accuracy, and user trust in multi-turn interactions.

To assess the effectiveness of RAG systems in multi-turn conversational settings, benchmarks such as MTRAG (Katsis et al., 2025), CORAL (Cheng et al., 2025), and RAD-Bench (Kuo et al., 2025) have been developed. MTRAG comprises 110 conversations averaging 7.7 turns each, totaling 842 tasks across four domains and incorporates diverse question types (factoid, comparison, explanation, etc.), varying answerability (answerable, partially answerable, unanswerable), and multi-turn dynamics (follow-up and clarification questions), providing a comprehensive evaluation framework for multi-turn RAG systems. The benchmark emphasizes active retrieval, where relevant documents are dynamically fetched based on user inquiries throughout the conversation, simulating a more realistic conversational experience. Similarly, CORAL offers a large-scale benchmark designed to assess RAG systems in realistic multi-turn conversational settings, supporting tasks such as passage retrieval, response generation, and citation labeling. RAD-Bench provides a frame to assess multi-turn LLMs' capabilities in augmented generation with retrieved context in multi-turn scenarios with both Retrieval Synthesis and Retrieval Reasoning mechanisms. The evaluation framework contains 89 multi-turn question samples sampled across six practical scenarios inspired by human-LLM multi-turn dialogue interactions requiring retrieved context to complete tasks.

3.2.3 Knowledge Graph Integration

Graph neural networks (GNN), especially when integrated with knowledge graphs (KG), have emerged as effective approaches for enhancing the multi-turn reasoning and interaction capabilities of LLMs. They notably improve tasks such as tracking entities and resolving coreferences, managing dialogue context structures, and enabling more robust reasoning over structured knowledge.

Much research in this area focuses on deriving graph-structured embeddings via GNNs and integrating them during continuous pre-training or fine-tuning of LLMs (Wang et al., 2024i; Jain & Lapata, 2024; Gao et al., 2025a). Several works draw on existing knowledge graphs (KGs) to supply commonsense or domain knowledge absent from conversational context. Wang et al. (2024i) tackle rational response candidate selection, where commonsense knowledge is often implicitly omitted in human–LLM interactions; they construct KGs from external commonsense sources and jointly fine-tune GNN and LLM using a response selection loss that measures correct-response ranking. Jain & Lapata (2024) build a dynamic graph over both the ongoing

conversation and Wikidata (Waagmeester et al., 2020), jointly training a GNN and LLM with an additional memory module to maintain context across turns and improve reasoning over heterogeneous sources. In healthcare, Gao et al. (2025a) integrate LLMs with UMLS-based KGs (Bodenreider, 2004) via a graph isomorphism network to rank clinically relevant knowledge pathways, enhancing diagnostic reasoning.

Being able to refer entities and coreferences from past dialogues and conversations can help LLMs with reasoning and instruction following abilities. Consequently, several research initiatives are now focusing on constructing or modifying KGs to integrate historical dialogue data. This integration helps to create richer, context-aware models that not only understand isolated queries but also leverage prior conversational context for improved performance. The works of Wang et al. (2024i) and Jain & Lapata (2024), as discussed above, append existing KGs with entities and relationships from past conversations. SURGE (Kang et al., 2023) builds KGs that specifically encode relevant knowledge for ongoing conversation, with triplets consisting of entities and their relations as items. The GNN is incorporated to perform multi-hop reasoning and connect disparate pieces of information. Tan et al. (2025) propose to prune existing KGs to remove irrelevant information, incorporating improved graph structures with additional prompting and LLMs to find candidate paths in multi-hop and multi-entity QAs.

Besides directly intergating graphs into training or finetuning LLMs, several research focus on Graph RAG for enhancing reasoning and flexibility in dynamic conversations. Typically, Graph RAG extracts entities and their relationships from documents or dialogues to build a KG. Then, it traverses the knowledge graph to retrieve subgraphs. The retrieved graph information is then integrated into the LLM's prompt, which allows LLM to generate a response that is richer, more coherent, and better grounded in factual knowledge (Wang et al., 2024h; Mavromatis & Karypis, 2025; Yang et al., 2025c).

3.3 Agent-Based Approaches

An emerging paradigm in enhancing multi-turn interactions is using Large Language Models (LLMs) as agents, a framework commonly termed as LLM-based agents. In contrast to traditional static use of language models (where an LLM passively responds to inputs), an LLM-based agent proactively engages in iterative loops of reasoning, planning, and interacting with external resources or environments to accomplish complex goals over multiple conversational turns.

This subsection reviews recent works on LLM-based agents, grouped into two broad categories: (1) single-agent systems (one LLM agent interacting iteratively with an environment or tools), and (2) multi-agent systems (multiple LLM agents collaboratively interacting or engaging in structured multi-turn dialogues).

3.3.1 Single Agent Approaches

Single-agent approaches use one LLM as a sole agent that iteratively interacts with external tools, environments, or its own internal reasoning trace to improve multi-turn performance. These methods enhance the agent's ability to answer complex queries, perform decision-making, or solve long-horizon tasks by breaking problems into iterative steps. Key themes include interleaving reasoning with actions, using tools or external APIs, and self-refinement via feedback.

One influential example is the ReAct by Yao et al. (2023), which integrates explicit reasoning steps with action executions, enabling the agent to interact dynamically with knowledge bases or external APIs. In this paradigm, the agent proactively decides when to retrieve external information, significantly reducing hallucination issues in open-domain question answering and interactive decision-making tasks. Empirical evaluations showed notable performance gains on benchmarks such as HotpotQA (Yang et al., 2018), FEVER (Thorne et al., 2018), ALFWorld (Shridhar et al., 2021), and WebShop (Yao et al., 2022) compared to static prompting or reinforcement learning baselines.

Extending this concept, the Toolformer framework (Schick et al., 2023) trains an LLM to autonomously determine the necessity and timing of external tool usage, such as calculators or web search APIs, by inserting specialized API-call tokens within its generations. By learning to integrate tool use in a self-supervised manner, Toolformer achieves substantial accuracy improvements on zero-shot arithmetic, knowledge retrieval, and translation tasks. This method demonstrates how explicit training for proactive tool invocation can

significantly enhance multi-turn problem-solving without increasing model size. Similarly, HuggingGPT (Shen et al., 2023b) employs an LLM as a centralized orchestrator that autonomously decomposes complex user requests into manageable sub-tasks delegated to specialized external models. Although HuggingGPT primarily emphasizes multi-modal and multi-model coordination, its relevance here lies in showcasing an LLM's capability for sophisticated planning and iterative decision-making across multi-step interactions, reinforcing the power of agent-based decomposition strategies.

The Reflexion framework introduced by Shinn et al. (2023) further pushes the concept of single-agent improvement by enabling self-reflective feedback loops. Instead of relying on traditional gradient-based learning methods, Reflexion employs verbal reinforcement learning, allowing the LLM to record textual reflections of its previous mistakes into episodic memory. Subsequent interactions utilize these reflections for iterative self-improvement, significantly boosting the agent's performance on coding and sequential decision-making benchmarks, surpassing even highly advanced models like GPT-4 in single-pass accuracy on code-generation tasks such as HumanEval. Extending this iterative self-improvement paradigm, the Voyager agent by Wang et al. (2024b) exemplifies lifelong learning capabilities within an open-ended virtual environment (Minecraft). Voyager autonomously engages in continuous loops of planning, code generation, environment-based execution, and observation, incrementally refining its skill repository through persistent, multi-turn interactions. This approach demonstrates impressive exploration efficiency, rapid skill generalization, and improved cumulative task success compared to prior single-agent baselines, highlighting the effectiveness of iterative, experience-driven knowledge acquisition in complex, open-ended environments.

For comprehensive agent evaluation, Liu et al. (2024d) introduce AgentBench, a rigorous benchmark designed to assess LLMs on agentic tasks—contexts requiring LLMs to make decisions and execute actions within interactive environments to accomplish specific goals. AgentBench features eight diverse simulated environments, spanning embodied navigation, interactive games, tool utilization, reasoning puzzles, and web interaction, enabling systematic evaluation of LLMs' reasoning, planning, and decision-making capabilities across extended interaction sequences. The authors evaluate 27 LLMs, spanning open-source and proprietary API-based models, and find large performance differences. Leading proprietary systems such as GPT-4 and Claude are notably effective as coherent agents on complex, long-horizon tasks, often completing scenarios that defeat other models. However, even these models have clear limitations, and a substantial gap remains between them and the strongest open-source alternatives.

Collectively, these single-agent works underscore a paradigm shift toward proactive, iterative interaction of LLMs with external tools, environments, and internal memory states, enabling significantly enhanced reasoning, decision-making, and self-improvement capabilities across diverse multi-turn interaction settings.

3.3.2 Multi-Agents Approaches

Multi-agent approaches involve multiple LLM-based agents collaboratively interacting to jointly solve complex problems. Drawing inspiration from human teamwork and structured debate, these methods leverage collective intelligence to surpass single-agent capabilities. Recent works can be grouped into three main categories: (1) role-based collaborative agents, (2) debate-based approaches, and (3) dynamic agent composition.

Role-based Collaborative Agents Role-based frameworks assign distinct roles to agents, guiding structured multi-turn dialogues. CAMEL (Li et al., 2023c) uses inception prompting to enable autonomous role-playing between agents (e.g., user and assistant), successfully generating conversational data and revealing emergent cognitive behaviors. Extending structured cooperation, ChatDev (Qian et al., 2024) organizes multiple specialized agents into virtual software-development teams (architect, coder, tester) that sequentially interact, significantly improving software quality over single-agent baselines such as GPT-4. Similarly, Dong et al. (2024b) propose structured collaboration among analyst, coder, and tester agents, greatly enhancing code-generation accuracy. Further emphasizing clear workflows, MetaGPT (Hong et al., 2024) encodes human-like Standard Operating Procedures into prompts, ensuring systematic verification and substantially reducing cascading errors, thus outperforming simpler multi-agent setups. Similarly, the Mixture-of-Search-Agents (MoSA) approach (Yang et al., 2025a) leverages multiple LLMs that propose and refine solutions in tandem. Each agent can independently suggest a next step or critique another agent's partial solution, and

through this multi-turn collaboration the group avoids single-model blind spots. MoSA demonstrated higher accuracy on challenging math sets (e.g. a MATH benchmark subset) than any single model working alone.

Chen et al. (2025b) propose BUTTON ("Bottom-Up then Top-Down"), a systematic method for training LLMs on multi-step tool use in conversational settings. The bottom-up phase generates atomic instruction–function pairs from real-world scenarios, while the top-down phase simulates multi-turn dialogues among user, assistant, and tool agents. This process yields BUTTONInstruct, a dataset of 8,000 multi-turn dialogues with compositional function-calling tasks. Models fine-tuned on BUTTONInstruct show significant improvements in planning and executing complex API call sequences.

Debate-based Approaches Debate-based methods enhance reasoning accuracy by structuring iterative critiques among agents. Du et al. (2024) show multi-agent debate significantly improves factual correctness and logical reasoning, outperforming single-agent solutions on mathematical and strategic tasks through structured back-and-forth critique. Complementarily, Generative Agents by Park et al. (2023) explore multi-turn social simulations, demonstrating emergent realistic behaviors (planning, social interactions) that arise naturally through iterative dialogue, highlighting the broader implications of structured deliberation in multi-agent interactions.

Dynamic Agent Composition Dynamic agent-composition methods create flexible agent teams tailored to specific tasks. AutoAgents (Chen et al., 2024a) automatically generates specialized agents, accompanied by an observer agent that monitors and adjusts the interaction dynamically, surpassing fixed-role approaches on heterogeneous tasks. Similarly, AgentVerse (Chen et al., 2024h) provides a versatile platform for agents to dynamically join or leave teams, enhancing adaptability and performance, while simultaneously producing beneficial emergent behaviors like negotiation and consensus formation.

Overall, these multi-agent frameworks collectively demonstrate how structured roles, deliberative debates, and dynamic compositions significantly enhance multi-turn interactions, paving the way toward robust, adaptive, and human-aligned AI collaboration.

Despite their promising results, multi-agent LLM systems still exhibit notable challenges and limitations. Recent critiques commonly highlight recurring issues such as role misassignments (Han et al., 2024; Cemri et al., 2025), where agents frequently misunderstand or deviate from their assigned responsibilities, causing redundancy, confusion, or omission of crucial tasks. Inefficient communication overhead and compounded errors (Han et al., 2024; Cemri et al., 2025; Hammond et al., 2025) are also prevalent, stemming from extensive interactions required for coordination among agents, which not only increases computational costs but also propagates and amplifies mistakes made by individual agents. Additionally, inadequate verification mechanisms (Han et al., 2024; Cemri et al., 2025) lead to unreliable or inconsistent outcomes, as agents often fail to effectively validate intermediate or final results, causing errors to remain undetected or improperly resolved. Emergent risks such as miscoordination, conflicts, and unintended collusion among autonomous agents (Hammond et al., 2025) further complicate multi-agent interactions, highlighting deeper issues related to the unpredictability and complexity inherent in systems of multiple interacting entities. Collectively, these insights underline the necessity for future research to prioritize robust coordination protocols, scalable memory-sharing mechanisms, adaptive verification strategies, and comprehensive evaluation frameworks to effectively harness the full potential of multi-agent collaborative intelligence, enhancing multi-turn interactions and paving the way toward robust, adaptive, and human-aligned AI collaboration.

4 Open Challenges

Despite remarkable advancements in large language models that have silently solved many previously formidable AI obstacles—such as understanding physical rules of the real world, generating human-like text, extending context memory length, and demonstrating creativity—significant challenges persist specifically in multi-turn interactions that limit their robustness, reliability, and alignment with user expectations. While earlier sections of this survey have reviewed common multi-turn tasks and discussed state-of-the-art methods aimed at improving performance, it is crucial to recognize that existing approaches fall short of addressing all complexities comprehensively. As illustrated in Figure 2, we systematically categorize these

open challenges into six major areas: Context Understanding, Complex Reasoning, Adaptation & Learning, Evaluations, and Ethical & Safety Issues, each with their associated sub-challenges. By highlighting these critical limitations and under-explored areas, we aim to guide future research efforts and encourage the development of LLM multi-turn systems that can maintain coherence, context-awareness, adaptability, and ethical soundness over prolonged interactions.

Figure 2: Illustration of open challenges in multi-turn LLM interactions, categorized into six major areas: Context Understanding, Complex Reasoning, Adaptation & Learning, Evaluations, Ethical & Safety Issues, and associated sub-challenges.

4.1 Context Understanding & Management

4.1.1 Context Retention & Coherence

LLMs struggle to maintain long-term context across extended dialogues, leading to incoherence and contradictions. As conversations grow, models tend to forget or confuse earlier details: performance degrades as the distance between a query and its relevant prior context increases (Kwan et al., 2024), and even advanced chat-oriented models show only modest gains in multi-turn coherence despite larger context windows and alignment tuning (Bai et al., 2024). Multi-turn benchmarks further reveal that instruction retention and self-consistency remain difficult—models frequently fail to remember instructions or maintain a coherent narrative over several turns (Deshpande et al., 2025). Preserving conversational state across turns thus remains an open problem.

4.1.2 Anaphora & Ellipsis Resolution

Multi-turn dialogue requires resolving pronouns, omissions, and references to earlier utterances. LLMs routinely misinterpret expressions such as "That one looks good" or "I did it," particularly in complex dialogues with many entities, failing to link utterances to the correct antecedents. Recent evaluations highlight inference memory as a key gap: models frequently forget or conflate user-provided attributes—such as a name or previously stated fact—when referenced implicitly in later turns (Deshpande et al., 2025). Robust anaphora and ellipsis resolution, analogous to coreference resolution in dialogue, remains an open challenge for cross-turn coherence.

4.1.3 Ambiguity Recognition & Clarification

When inputs are ambiguous or underspecified, aligned LLMs tend to either over-hedge with vague answers or silently guess user intent rather than asking clarifying questions. Chen et al. (2025a) find that conversational agents frequently fail to disambiguate—responding generically rather than seeking clarification. An instruction such as "Tell me about that report" may elicit an arbitrary guess about which report rather than a targeted follow-up. Such unresolved ambiguities compound across turns, motivating research into LLMs that proactively recognize and resolve underspecification as humans naturally do.

4.2 Complex Reasoning Across Turns

4.2.1 Error Propagation & Compounding

Errors introduced in early turns—whether by the model or the user—tend to persist and amplify through subsequent dialogue. Once an incorrect answer or false premise enters the context, most LLMs continue building on it rather than self-correcting, leading to compounding reasoning failures (Kwan et al., 2024). This effect is especially pronounced in sequential decision tasks, where minor mistakes accumulate across interaction trajectories. The root difficulty is that models lack a robust mechanism to detect and retract mid-dialogue errors. Designing models that can identify mistakes and accept corrections—whether self-initiated or user-supplied—remains an open problem.

4.2.2 Topic Switching & Discontinuous Reasoning

Real conversations frequently shift topics or revisit earlier threads after detours, posing significant challenges for LLMs. Models either fail to retain the prior thread when a topic is resumed or inappropriately carry over context from an unrelated topic—neither behavior matching human conversational fluency. Effective attention re-allocation across non-linear dialogue flows remains unsolved. Benchmarks such as MT-Bench (Zheng et al., 2023) and MT-Bench-101 (Bai et al., 2024) explicitly test category shifts, and even top-tier models frequently break coherence under non-linear conversation flows. Better mechanisms for tracking multiple concurrent topics and segmenting context are needed.

4.2.3 Proactive Information Seeking

In complex interactive settings such as medical diagnosis, troubleshooting, or tutoring, an ideal agent should proactively ask clarifying questions rather than passively answer. Most general-purpose LLMs, however, are largely reactive: trained primarily on single-turn Q&A, they lack exposure to multi-turn dialogue policies governing when to ask versus when to inform (Chen et al., 2025a), and tend to produce immediate answers even to underspecified queries. In a medical context, a user stating "I feel sick" should prompt targeted symptom questions; most LLMs instead offer generic advice without seeking clarification. Some recent work addresses this in constrained settings such as ambiguous text-to-SQL tasks (Chen et al., 2025a), but robust proactive dialogue behavior across arbitrary domains remains an open challenge.

4.2.4 Multilingual & Code-Switching Scenarios

Multi-turn interactions spanning multiple languages introduce additional complexity. While LLMs can handle single-turn non-English queries reasonably well, maintaining coherent cross-lingual context across

turns is far more difficult. Code-switching—alternating languages across or within turns—often causes models to lose referential links or respond in the wrong language. Evaluation has been heavily skewed toward English, and performance degrades noticeably in lower-resource languages. There are also safety implications: mixing languages can circumvent content filters and expose weaknesses in multilingual alignment. Yoo et al. (2025) find that code-switching prompts can elicit undesirable behaviors that would not surface in English-only inputs, revealing gaps in multilingual robustness. Handling multi-turn dialogue in a culturally and linguistically consistent manner thus remains an open challenge.

4.3 Adaptation & Learning

4.3.1 Dynamic Preference & Objective Adaptation

Unlike human assistants, LLMs have no true long-term personalization within a conversation—they rely solely on the provided context window. While current chat models follow explicit style instructions, they often miss subtler cues or gradual shifts in user preferences. An ideal assistant might proactively simplify its language upon detecting user confusion; today's LLMs typically require explicit instruction to do so. Dynamic adaptation is challenging because it requires inferring and retaining user preferences across turns without explicit reminders, yet model parameters are fixed during inference—any adaptation must emerge entirely from processing the conversation context. This leaves LLMs prone to either forgetting preferences or applying inferred styles inappropriately. Some initial work has explored updating pseudo-personas or user profiles during conversation, but reliable and safe mechanisms remain unresolved.

4.3.2 Knowledge Adaptation

Human conversationalists naturally absorb new facts and adjust to corrections during dialogue. Current LLMs, by contrast, have a fixed knowledge base at deployment: information provided mid-conversation resides only in the context window and is lost once the session resets. Enabling persistent memory and continual learning in interactive settings is an important open challenge (Wu et al., 2024a). Retrieval-augmented generation partially addresses this by fetching relevant facts from external databases, but still depends on pre-established knowledge sources. True on-the-fly learning—updating internal representations from user-provided data without retraining—remains difficult due to catastrophic forgetting and the risk that users could inject false or malicious information. Recent work has explored external memory modules and dynamic context augmentation as surrogates, writing new facts to a persistent scratchpad. Nonetheless, balancing plasticity and stability in real time remains unsolved.

4.3.3 Robustness to Misinformation & Adversarial Inputs

Multi-turn interactions introduce new attack surfaces: malicious users can gradually manipulate context or employ social-engineering tactics across turns to elicit unsafe outputs where single-turn attacks would fail. Recent studies confirm that even top-tier aligned models such as GPT-4 can be coerced into policy-violating behavior through carefully staged multi-turn strategies (Zhou & Arel, 2025). Beyond deliberate attacks, users may also introduce subtly incorrect facts across turns; lacking real-time fact-checking, LLMs tend to propagate such falsehoods. Prompt leakage—models inadvertently revealing hidden system instructions under sustained pressure—poses an additional concern. Collectively, these adversarial scenarios underscore that static safety training is insufficient when attacks are staged gradually. Building conversational agents capable of detecting inconsistent or malicious inputs and responding safely without disrupting the interaction remains an open research problem.

4.4 Evaluations

4.4.1 Scalable Data Curation

Achieving scalable data collection for multi-turn interactions remains a significant challenge at the intersection of data engineering and model training. Promising approaches include leveraging domain-specific

real dialogues, forging institutional collaborations, and developing synthetic data pipelines—yet scalability in curating conversational datasets remains an open and pressing problem.

As discussed in §2.1.1 and §2.2.2, healthcare uniquely benefits from access to extensive real-world patient-doctor conversational datasets that inherently provide rich diversity and realism, making them well-suited for continual pre-training, SFT, and RLHF. Replicating such collection pipelines in other domains is difficult: most fields lack established protocols for recording and anonymizing real-world conversations, and meeting rising demand for specialized conversational data will require broader collaboration among researchers, governments, and institutions.

Recent work has explored converting single-turn or limited-turn exchanges into richer multi-turn dialogues—either manually or via automated frameworks (Qiu et al., 2024; Li et al., 2023a; Wang et al., 2024d)—and using LLMs for synthetic generation and rewriting (Yang et al., 2024; Ding et al., 2023; Maheshwary et al., 2025; Xu et al., 2024). However, synthetic approaches carry well-documented drawbacks (Seddik et al., 2024; Chen et al., 2024e;c): they tend to lack the spontaneity and nuance of real conversations, risk amplifying factual inaccuracies and unnatural patterns, and over-rely on generic conversational templates. Going forward, progress requires not merely increasing data volume but improving quality—through better dialogue generation, robust filtering of synthetic outputs, and shared multi-domain repositories of multi-turn dialogues.

4.4.2 Metric Design

Beyond datasets, the metrics for evaluating multi-turn interactions remain inadequate. Traditional measures such as single-turn accuracy or BLEU fail to capture dialogue-level qualities, motivating both fine-grained turn-level metrics and holistic conversation-level criteria.

Fine-Grained Capability Evaluation Benchmarks like MT-Bench-101 evaluate discrete abilities—logical consistency, factual recall, politeness—at the turn level (Bai et al., 2024), revealing which skills degrade over a conversation. Fine-grained scoring can expose, for instance, that a model maintains fluency but loses factual accuracy after many turns. Designing such rubrics is challenging, requiring careful identification and weighting of sub-skills along with expert annotation or LLM-as-judge evaluation. MultiChallenge's instance-level rubrics (Deshpande et al., 2025) represent progress in this direction, but no universally adopted standard has yet emerged.

Long-Term Effectiveness Evaluating the global quality of a multi-turn exchange remains an open problem. Ideal metrics would capture whether the conversation as a whole succeeded—whether the user's goal was achieved and the model remained helpful and coherent throughout. Some work measures conversational return-on-investment, assessing whether additional turns genuinely help or introduce confusion (Kwan et al., 2024), while others probe memory retention and consistency across turns. Metrics that directly quantify sustained performance over 10+ turns, or eventual convergence to a correct and useful outcome, remain underdeveloped. Evaluation measures analogous to task success rates in traditional dialogue systems are an important open research direction.

Cultural and Sociolinguistic Diversity Most evaluation setups remain Western and English-centric, limiting assessments of model performance for diverse users. A model may perform well on formal Q&A but poorly on casual, code-mixed, or culturally idiomatic conversations. FairMT-Bench (Fan et al., 2025) is a step toward addressing bias and fairness across demographic attributes in multi-turn settings, but defining metrics that quantify model behavior across a broad sociolinguistic spectrum—capturing bias, respectfulness, and user satisfaction for varied user profiles—remains an important and largely unsolved challenge.

4.4.3 LLM-based vs. Human Judging

Multi-turn dialogue evaluation has increasingly turned to LLM-as-a-judge frameworks, where a strong model such as GPT-4 assesses response quality at scale. MT-Bench and Chatbot Arena exemplify this approach, achieving high consistency at low cost (Zheng et al., 2023). GPT-4-based evaluators align with human preferences roughly 80% of the time, approaching inter-annotator agreement levels (Zheng et al., 2023).

However, AI judges exhibit systematic biases—including self-enhancement bias (favoring outputs from similar models) and verbosity bias (rewarding unnecessarily long responses)—and can miss subtle factual errors or nuanced value judgments that human reviewers would catch (Chen et al., 2024b). To mitigate these issues, researchers have proposed hybrid approaches combining LLM scoring with human oversight, such as prompting judges with explicit rubrics and incorporating periodic human audits, aiming to preserve the scalability of automated evaluation while maintaining reliability closer to human standards.

4.5 Ethical & Safety

4.5.1 Bias Amplification

Multi-turn dialogues can inadvertently magnify model biases across turns: a biased assumption introduced early may be reinforced by subsequent exchanges, and the interactive nature of dialogue can cause the model to adapt to the user's own biases, compounding problematic content. Fan et al. (2025) confirm this risk, finding that LLMs accumulate bias more readily in multi-turn settings than in single-turn prompts—a slight gender bias in an early response, for instance, can intensify as the conversation continues. FairMT-Bench reveals significant variability across state-of-the-art models, with many showing degraded fairness under back-and-forth discussions involving sensitive attributes. Addressing this challenge likely requires mechanisms beyond single-response detoxification, including dialogue-level self-monitoring, diverse data augmentation, and consistency enforcement with ethical guidelines across turns.

4.5.2 Privacy Leakage

Prolonged conversations increase the risk of LLMs revealing sensitive information—either disclosed by the user during dialogue or memorized from training data. Nasr et al. (2025) demonstrate that LLMs can memorize training data such as phone numbers and addresses, and that adversaries can extract this information through crafted prompt sequences. Multi-turn interactions amplify this threat by allowing iterative, context-building probes that may succeed where a single query would not. Beyond memorization, multi-turn manipulation has been used to elicit system prompt or context leakage, with users extracting hidden instructions or prior conversation contents. Mitigations include reducing memorization during training, deploying real-time filters for sensitive content, and restricting model access to private context. Completely preventing memorized-data leakage remains an open problem, with ongoing efforts to quantify its extent and develop safer training regimes (Nasr et al., 2025).

4.5.3 Hyper-Realism and User Perception

As dialogue models grow more fluent and emotionally resonant, users may struggle to recognize they are conversing with an AI—raising concerns about unintentional deception and overtrust (Akbulut et al., 2025). Studies document users forming strong personal bonds with chatbots, with therapeutic alliance scores in some cases approaching those of human therapists (Beatty et al., 2022). While such engagement can provide genuine comfort, it also risks fostering dependence and giving AI undue influence over vulnerable individuals (Fang et al., 2025; Boine, 2023). In response, the proposed EU AI Act mandates clear disclosure of artificial identity in human-facing AI systems (Boine, 2023). Design-level mitigations include persistent identity reminders and deliberately less human-like stylistic choices to maintain healthy user boundaries and reduce the illusion of personhood (Akbulut et al., 2025).

5   Conclusion

This survey has provided a comprehensive overview of the rapidly evolving landscape of multi-turn interactions with Large Language Models, contributing several advances to the field.

We introduced a task-oriented taxonomy for analyzing multi-turn LLM interactions, departing from the capability-oriented frameworks prevalent in existing literature. Prior surveys have largely focused on isolated capabilities—reasoning, memory, or contextual understanding—yet real-world multi-turn applications demand the coordinated interplay of multiple such capabilities. By organizing interactions around

tasks—instruction following and conversational engagement—rather than isolated abilities, our taxonomy better reflects how LLMs are deployed and evaluated in practice. This perspective enabled substantive analysis of critical application domains, including role-playing, healthcare consultation, education, and jailbreaking, where performance is determined by the joint operation of many capabilities.

Our analysis establishes that multi-turn interaction represents a fundamental paradigm shift in LLM utilization and evaluation. Unlike single-turn settings that dominated early benchmarks, multi-turn contexts more closely mirror real-world use—from sustained dialogue to complex iterative problem-solving—demanding not only factual knowledge but also context retention, coherent cross-turn reasoning, adaptive behavior, and robust handling of ambiguous or evolving user intent.

The improvement methodologies we surveyed span model-centric approaches (in-context learning, fine-tuning, reinforcement learning, and architectural innovations), external integration strategies (memory augmentation, retrieval mechanisms, and knowledge graphs), and agent-based frameworks (single- and multi-agent systems). This detailed methodological landscape addresses a significant gap in prior surveys, which have often treated multi-turn enhancements only superficially.

Significant challenges nonetheless remain. Even state-of-the-art models struggle to maintain coherence across extended conversations, and complex cross-turn reasoning remains susceptible to error propagation and topic-switching failures. Adaptation capabilities are similarly limited, particularly regarding dynamic preference learning and on-the-fly knowledge updates. Our structured organization of these open challenges provides a concrete roadmap for future research.

Multi-turn interaction capabilities represent both a frontier challenge and a transformative opportunity for LLM research. Advances in this domain will not only improve technical performance but also enhance the practical utility and trustworthiness of LLMs across diverse real-world settings. Our task-oriented taxonomy, domain-level analysis, methodological survey, and organization of open challenges together provide a foundation for future work in this critical area.

References

Marwa Abdulhai, Isadora White, Charlie Victor Snell, Charles Sun, Joey Hong, Yuexiang Zhai, Kelvin Xu, and Sergey Levine. LMRL gym: Benchmarks for multi-turn reinforcement learning with language models. In *Forty-second International Conference on Machine Learning*, 2025.

Josh Achiam, Steven Adler, Sandhini Agarwal, Lama Ahmad, Ilge Akkaya, Florencia Leoni Aleman, Diogo Almeida, Janko Altenschmidt, Sam Altman, Shyamal Anadkat, et al. Gpt-4 technical report. *arXiv preprint arXiv:2303.08774*, 2023.

Jaewoo Ahn, Taehyun Lee, Junyoung Lim, Jin-Hwa Kim, Sangdoo Yun, Hwaran Lee, and Gunhee Kim. TimeChara: Evaluating point-in-time character hallucination of role-playing large language models. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 3291–3325, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-acl.197. URL https://aclanthology.org/2024.findings-acl.197/.

Canfer Akbulut, Laura Weidinger, Arianna Manzini, Iason Gabriel, and Verena Rieser. All too human? mapping and mitigating the risks from anthropomorphic ai. In *Proceedings of the 2024 AAAI/ACM Conference on AI, Ethics, and Society*, AIES '24, pp. 13–26. AAAI Press, 2025.

Anthropic. Introducing Claude for Education. https://www.anthropic.com/news/introducing-claude-for-education, 2025.

Rahul K Arora, Jason Wei, Rebecca Soskin Hicks, Preston Bowman, Joaquin Quiñonero-Candela, Foivos Tsimpourlas, Michael Sharman, Meghan Shah, Andrea Vallone, Alex Beutel, et al. Healthbench: Evaluating large language models towards improved human health. *arXiv preprint arXiv:2505.08775*, 2025.

Jacob Austin, Augustus Odena, Maxwell Nye, Maarten Bosma, Henryk Michalewski, David Dohan, Ellen Jiang, Carrie Cai, Michael Terry, Quoc Le, and Charles Sutton. Program synthesis with large language models, 2021.

Ge Bai, Jie Liu, Xingyuan Bu, Yancheng He, Jiaheng Liu, Zhanhui Zhou, Zhuoran Lin, Wenbo Su, Tiezheng Ge, Bo Zheng, et al. Mt-bench-101: A fine-grained benchmark for evaluating large language models in multi-turn dialogues. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7421–7454, 2024.

Yuntao Bai, Saurav Kadavath, Sandipan Kundu, Amanda Askell, Jackson Kernion, Andy Jones, Anna Chen, Anna Goldie, Azalia Mirhoseini, Cameron McKinnon, et al. Constitutional AI: Harmlessness from AI Feedback. *arXiv preprint arXiv:2212.08073*, 2022.

Eryk Banatt, Jonathan Cheng, Skanda Vaidyanath, and Tiffany Hwu. Wilt: A multi-turn, memorization-robust inductive logic benchmark for llms. *arXiv preprint arXiv:2410.10998*, 2024.

Zhijie Bao, Wei Chen, Shengze Xiao, Kuang Ren, Jiaao Wu, Cheng Zhong, Jiajie Peng, Xuanjing Huang, and Zhongyu Wei. DISC-MedLLM: Bridging General Large Language Models and Real-World Medical Consultation. *arXiv preprint arXiv:2308.14346*, 2023.

Clare Beatty, Tanya Malik, Saha Meheli, and Chaitali Sinha. Evaluating the therapeutic alliance with a free-text CBT conversational agent (Wysa): a mixed-methods study. *Frontiers in Digital Health*, 4:847991, 2022.

Olivier Bodenreider. The Unified Medical Language System (UMLS): integrating biomedical terminology. *Nucleic acids research*, 32(suppl_1):D267–D270, 2004.

Claire Boine. Emotional Attachment to AI Companions and European Law. *MIT Case Studies in Social and Ethical Responsibilities of Computing*, Feb 27 2023.

Tom B. Brown, Benjamin Mann, Nick Ryder, Melanie Subbiah, Jared Kaplan, Prafulla Dhariwal, Arvind Neelakantan, Pranav Shyam, Girish Sastry, Amanda Askell, Sandhini Agarwal, Ariel Herbert-Voss, Gretchen Krueger, Tom Henighan, Rewon Child, Aditya Ramesh, Daniel M. Ziegler, Jeffrey Wu, Clemens Winter, Christopher Hesse, Mark Chen, Eric Sigler, Mateusz Litwin, Scott Gray, Benjamin Chess, Jack Clark, Christopher Berner, Sam McCandlish, Alec Radford, Ilya Sutskever, and Dario Amodei. Language models are few-shot learners. In *Proceedings of the 34th International Conference on Neural Information Processing Systems*, NIPS '20, Red Hook, NY, USA, 2020. Curran Associates Inc.

Aydar Bulatov, Yury Kuratov, and Mikhail Burtsev. Recurrent memory transformer. *Advances in Neural Information Processing Systems*, 35:11079–11091, 2022.

Odma Byambasuren, Yunfei Yang, Zhifang Sui, Damai Dai, Baobao Chang, Sujian Li, and Hongying Zan. Preliminary study on the construction of chinese medical knowledge graph. *Journal of Chinese Information Processing*, 33(10):1–9, 2019.

Germán Capdehourat, Isabel Amigo, Brian Lorenzo, and Joaquín Trigo. On the effectiveness of LLMs for automatic grading of open-ended questions in Spanish. *arXiv preprint arXiv:2503.18072*, 2025.

Nicholas Carlini, Milad Nasr, Christopher A Choquette-Choo, Matthew Jagielski, Irena Gao, Pang Wei W Koh, Daphne Ippolito, Florian Tramer, and Ludwig Schmidt. Are aligned neural networks adversarially aligned? *Advances in Neural Information Processing Systems*, 36:61478–61500, 2023.

Mert Cemri, Melissa Z Pan, Shuyi Yang, Lakshya A Agrawal, Bhavya Chopra, Rishabh Tiwari, Kurt Keutzer, Aditya Parameswaran, Dan Klein, Kannan Ramchandran, Matei Zaharia, Joseph E. Gonzalez, and Ion Stoica. Why do multi-agent LLM systems fail? In *The Thirty-ninth Annual Conference on Neural Information Processing Systems Datasets and Benchmarks Track*, 2025.

Patrick Chao, Edoardo Debenedetti, Alexander Robey, Maksym Andriushchenko, Francesco Croce, Vikash Sehwag, Edgar Dobriban, Nicolas Flammarion, George J Pappas, Florian Tramer, et al. Jailbreakbench: An open robustness benchmark for jailbreaking large language models. *Advances in Neural Information Processing Systems*, 37:55005–55029, 2024.

Guangyao Chen, Siwei Dong, Yu Shu, Ge Zhang, Jaward Sesay, Börje Karlsson, Jie Fu, and Yemin Shi. Autoagents: A framework for automatic agent generation. In Kate Larson (ed.), *Proceedings of the Thirty-Third International Joint Conference on Artificial Intelligence, IJCAI-24*, pp. 22–30. International Joint Conferences on Artificial Intelligence Organization, 8 2024a. doi: 10.24963/ijcai.2024/3. URL `https://doi.org/10.24963/ijcai.2024/3`. Main Track.

Guiming Hardy Chen, Shunian Chen, Ziche Liu, Feng Jiang, and Benyou Wang. Humans or LLMs as the judge? a study on judgement bias. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 8301–8327, Miami, Florida, USA, November 2024b. Association for Computational Linguistics.

Hao Chen, Abdul Waheed, Xiang Li, Yidong Wang, Jindong Wang, Bhiksha Raj, and Marah I Abdin. On the diversity of synthetic data and its impact on training large language models. *arXiv preprint arXiv:2410.15226*, 2024c.

Hongzhan Chen, Hehong Chen, Ming Yan, Wenshen Xu, Xing Gao, Weizhou Shen, Xiaojun Quan, Chenliang Li, Ji Zhang, Fei Huang, et al. Roleinteract: Evaluating the social interaction of role-playing agents. *arXiv e-prints*, pp. arXiv–2403, 2024d.

Jie Chen, Yupeng Zhang, Bingning Wang, Wayne Xin Zhao, Ji-Rong Wen, and Weipeng Chen. Unveiling the flaws: Exploring imperfections in synthetic data and mitigation strategies for large language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 14855–14865, Miami, Florida, USA, November 2024e. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.873. URL `https://aclanthology.org/2024.findings-emnlp.873/`.

Junying Chen, Xidong Wang, Ke Ji, Anningzhe Gao, Feng Jiang, Shunian Chen, Hongbo Zhang, Song Dingjie, Wenya Xie, Chuyi Kong, Jianquan Li, Xiang Wan, Haizhou Li, and Benyou Wang. HuatuoGPT-II, one-stage training for medical adaption of LLMs. In *First Conference on Language Modeling*, 2024f.

Maximillian Chen, Ruoxi Sun, Tomas Pfister, and Sercan O Arik. Learning to clarify: Multi-turn conversations with action-based contrastive self-training. In *The Thirteenth International Conference on Learning Representations*, 2025a.

Mingyang Chen, Haoze Sun, Tianpeng Li, Fan Yang, Hao Liang, Keer Lu, Bin Cui, Wentao Zhang, Zenan Zhou, and Weipeng Chen. Facilitating multi-turn function calling for LLMs via compositional instruction tuning. In *The Thirteenth International Conference on Learning Representations*, 2025b.

Nuo Chen, Yan Wang, Yang Deng, and Jia Li. The oscars of ai theater: A survey on role-playing with language models. *arXiv preprint arXiv:2407.11484*, 2024g.

Nuo Chen, Hongguang Li, Jianhui Chang, Juhua Huang, Baoyuan Wang, and Jia Li. Compress to impress: Unleashing the potential of compressive memory in real-world long-term conversations. In *Proceedings of the 31st International Conference on Computational Linguistics*, pp. 755–773. Association for Computational Linguistics, January 2025c.

Tianqi Chen, Bing Xu, Chiyuan Zhang, and Carlos Guestrin. Training deep nets with sublinear memory cost, 2016. *arXiv preprint arXiv:1604.06174*, 2016.

Weize Chen, Yusheng Su, Jingwei Zuo, Cheng Yang, Chenfei Yuan, Chi-Min Chan, Heyang Yu, Yaxi Lu, Yi-Hsin Hung, Chen Qian, Yujia Qin, Xin Cong, Ruobing Xie, Zhiyuan Liu, Maosong Sun, and Jie Zhou. Agentverse: Facilitating multi-agent collaboration and exploring emergent behaviors. In *The Twelfth International Conference on Learning Representations*, 2024h. URL https://openreview.net/forum?id=EHg5GDnyq1.

Yirong Chen, Zhenyu Wang, Xiaofen Xing, Zhipei Xu, Kai Fang, Junhong Wang, Sihang Li, Jieling Wu, Qi Liu, Xiangmin Xu, et al. Bianque: Balancing the questioning and suggestion ability of health llms with multi-turn health conversations polished by chatgpt. *arXiv preprint arXiv:2310.15896*, 2023.

Yongchao Chen, Yilun Hao, Yueying Liu, Yang Zhang, and Chuchu Fan. Codesteer: Symbolic-augmented language models via code/text guidance. In *Forty-second International Conference on Machine Learning*, 2025d.

Yongchao Chen, Harsh Jhamtani, Srinagesh Sharma, Chuchu Fan, and Chi Wang. Steering large language models between code execution and textual reasoning. In *The Thirteenth International Conference on Learning Representations*, 2025e. URL https://openreview.net/forum?id=5X5Z7Ffrjb.

Junhao Cheng, Baiqiao Yin, Kaixin Cai, Minbin Huang, Hanhui Li, Yuxin He, Xi Lu, Yue Li, Yifei Li, Yuhao Cheng, et al. Theatergen: Character management with llm for consistent multi-turn image generation. *arXiv preprint arXiv:2404.18919*, 2024.

Yiruo Cheng, Kelong Mao, Ziliang Zhao, Guanting Dong, Hongjin Qian, Yongkang Wu, Tetsuya Sakai, Ji-Rong Wen, and Zhicheng Dou. CORAL: Benchmarking Multi-turn Conversational Retrieval-Augmentation Generation. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Findings of the Association for Computational Linguistics: NAACL 2025*, pp. 1308–1330, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. ISBN 979-8-89176-195-7. doi: 10.18653/v1/2025.findings-naacl.72. URL https://aclanthology.org/2025.findings-naacl.72/.

Wei-Lin Chiang, Zhuohan Li, Ziqing Lin, Ying Sheng, Zhanghao Wu, Hao Zhang, Lianmin Zheng, Siyuan Zhuang, Yonghao Zhuang, Joseph E Gonzalez, et al. Vicuna: An open-source chatbot impressing gpt-4 with 90%* chatgpt quality. *See https://vicuna. lmsys. org (accessed 14 April 2023)*, 2(3):6, 2023.

Aakanksha Chowdhery, Sharan Narang, Jacob Devlin, Maarten Bosma, Gaurav Mishra, Adam Roberts, Paul Barham, Hyung Won Chung, Charles Sutton, Sebastian Gehrmann, Parker Schuh, Kensen Shi, Sasha Tsvyashchenko, Joshua Maynez, Abhishek Rao, Parker Barnes, Yi Tay, Noam Shazeer, Vinodkumar

Prabhakaran, Emily Reif, Nan Du, Ben Hutchinson, Reiner Pope, James Bradbury, Jacob Austin, Michael Isard, Guy Gur-Ari, Pengcheng Yin, Toju Duke, Anselm Levskaya, Sanjay Ghemawat, Sunipa Dev, Henryk Michalewski, Xavier Garcia, Vedant Misra, Kevin Robinson, Liam Fedus, Denny Zhou, Daphne Ippolito, David Luan, Hyeontaek Lim, Barret Zoph, Alexander Spiridonov, Ryan Sepassi, David Dohan, Shivani Agrawal, Mark Omernick, Andrew M. Dai, Thanumalayan Sankaranarayana Pillai, Marie Pellat, Aitor Lewkowycz, Erica Moreira, Rewon Child, Oleksandr Polozov, Katherine Lee, Zongwei Zhou, Xuezhi Wang, Brennan Saeta, Mark Diaz, Orhan Firat, Michele Catasta, Jason Wei, Kathy Meier-Hellstern, Douglas Eck, Jeff Dean, Slav Petrov, and Noah Fiedel. PaLM: Scaling Language Modeling with Pathways. *Journal of Machine Learning Research*, 24(240):1–113, 2023.

Hyung Won Chung, Le Hou, Shayne Longpre, Barret Zoph, Yi Tay, William Fedus, Yunxuan Li, Xuezhi Wang, Mostafa Dehghani, Siddhartha Brahma, et al. Scaling instruction-finetuned language models. *Journal of Machine Learning Research*, 25(70):1–53, 2024.

Karl Cobbe, Vineet Kosaraju, Mohammad Bavarian, Mark Chen, Heewoo Jun, Lukasz Kaiser, Matthias Plappert, Jerry Tworek, Jacob Hilton, Reiichiro Nakano, et al. Training verifiers to solve math word problems. *arXiv preprint arXiv:2110.14168*, 2021.

Nico Daheim, Jakub Macina, Manu Kapur, Iryna Gurevych, and Mrinmaya Sachan. Stepwise verification and remediation of student reasoning errors with large language model tutors. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 8386–8411. Association for Computational Linguistics, November 2024.

Zihang Dai, Zhilin Yang, Yiming Yang, Jaime Carbonell, Quoc Le, and Ruslan Salakhutdinov. Transformer-XL: Attentive language models beyond a fixed-length context. In Anna Korhonen, David Traum, and Lluís Màrquez (eds.), *Proceedings of the 57th Annual Meeting of the Association for Computational Linguistics*, pp. 2978–2988, Florence, Italy, July 2019. Association for Computational Linguistics. doi: 10.18653/v1/P19-1285. URL https://aclanthology.org/P19-1285/.

Tri Dao, Dan Fu, Stefano Ermon, Atri Rudra, and Christopher Ré. Flashattention: Fast and memory-efficient exact attention with io-awareness. *Advances in neural information processing systems*, 35:16344–16359, 2022.

Kaustubh Deshpande, Ved Sirdeshmukh, Johannes Baptist Mols, Lifeng Jin, Ed-Yeremai Hernandez-Cardona, Dean Lee, Jeremy Kritz, Willow E. Primack, Summer Yue, and Chen Xing. MultiChallenge: A realistic multi-turn conversation evaluation benchmark challenging to frontier LLMs. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 18632–18702. Association for Computational Linguistics, July 2025.

Emily Dinan, Stephen Roller, Kurt Shuster, Angela Fan, Michael Auli, and Jason Weston. Wizard of wikipedia: Knowledge-powered conversational agents. *arXiv preprint arXiv:1811.01241*, 2018.

Ning Ding, Yulin Chen, Bokai Xu, Yujia Qin, Shengding Hu, Zhiyuan Liu, Maosong Sun, and Bowen Zhou. Enhancing chat language models by scaling high-quality instructional conversations. In *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 3029–3051. Association for Computational Linguistics, December 2023.

Yuyang Ding, Hanglei Hu, Jie Zhou, Qin Chen, Bo Jiang, and Liang He. Boosting large language models with socratic method for conversational mathematics teaching. In *Proceedings of the 33rd ACM International Conference on Information and Knowledge Management*, pp. 3730–3735, 2024.

Qingxiu Dong, Lei Li, Damai Dai, Ce Zheng, Jingyuan Ma, Rui Li, Heming Xia, Jingjing Xu, Zhiyong Wu, Baobao Chang, Xu Sun, Lei Li, and Zhifang Sui. A survey on in-context learning. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 1107–1128. Association for Computational Linguistics, November 2024a.

Yihong Dong, Xue Jiang, Zhi Jin, and Ge Li. Self-collaboration code generation via chatgpt. *ACM Transactions on Software Engineering and Methodology*, 33(7):1–38, 2024b.

Hanwen Du, Bo Peng, and Xia Ning. SAPIENT: Mastering multi-turn conversational recommendation with strategic planning and Monte Carlo tree search. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 2629–2648. Association for Computational Linguistics, April 2025.

Yilun Du, Shuang Li, Antonio Torralba, Joshua B. Tenenbaum, and Igor Mordatch. Improving factuality and reasoning in language models through multiagent debate. In *Forty-first International Conference on Machine Learning*, 2024. URL https://openreview.net/forum?id=zj7YuTE4t8.

Haodong Duan, Jueqi Wei, Chonghua Wang, Hongwei Liu, Yixiao Fang, Songyang Zhang, Dahua Lin, and Kai Chen. BotChat: Evaluating LLMs' capabilities of having multi-turn dialogues. In *Findings of the Association for Computational Linguistics: NAACL 2024*, pp. 3184–3200. Association for Computational Linguistics, June 2024.

Nouha Dziri, Ximing Lu, Melanie Sclar, Xiang Lorraine Li, Liwei Jiang, Bill Yuchen Lin, Sean Welleck, Peter West, Chandra Bhagavatula, Ronan Le Bras, et al. Faith and fate: Limits of transformers on compositionality. *Advances in neural information processing systems*, 36:70293–70332, 2023.

Elliot L Epstein, Kaisheng Yao, Jing Li, Xinyi Bai, and Hamid Palangi. Mmmt-if: A challenging multimodal multi-turn instruction following benchmark. *arXiv preprint arXiv:2409.18216*, 2024.

Kawin Ethayarajh, Winnie Xu, Niklas Muennighoff, Dan Jurafsky, and Douwe Kiela. KTO: Model alignment as prospect theoretic optimization. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

Zhiting Fan, Ruizhe Chen, Tianxiang Hu, and Zuozhu Liu. FairMT-bench: Benchmarking fairness for multi-turn dialogue in conversational LLMs. In *The Thirteenth International Conference on Learning Representations*, 2025.

Cathy Mengying Fang, Auren R. Liu, Valdemar Danry, Eunhae Lee, Samantha W. T. Chan, Pat Pataranutaporn, Pattie Maes, Jason Phang, Michael Lampe, Lama Ahmad, and Sandhini Agarwal. How AI and Human Behaviors Shape Psychosocial Effects of Chatbot Use: A Longitudinal Randomized Controlled Study. *arXiv preprint arXiv:2503.17473*, 2025.

Jiazhan Feng, Qingfeng Sun, Can Xu, Pu Zhao, Yaming Yang, Chongyang Tao, Dongyan Zhao, and Qingwei Lin. MMDialog: A large-scale multi-turn dialogue dataset towards multi-modal open-domain conversation. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7348–7363. Association for Computational Linguistics, July 2023.

Ty Feng, Sa Liu, and Dipak Ghosal. CourseAssist: Pedagogically Appropriate AI Tutor for Computer Science Education. In *Proceedings of the 2024 on ACM Virtual Global Computing Education Conference V. 2*, pp. 310–311, 2024.

Sarah E. Finch, James D. Finch, and Jinho D. Choi. Don't forget your ABC's: Evaluating the state-of-the-art in chat-oriented dialogue systems. In Anna Rogers, Jordan Boyd-Graber, and Naoaki Okazaki (eds.), *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15044–15071, Toronto, Canada, July 2023. Association for Computational Linguistics.

Jonas Flodén. Grading exams using large language models: A comparison between human and AI grading of exams in higher education using ChatGPT. *British educational research journal*, 51(1):201–224, 2025.

NBME FSMB. United states medical licensing examination sample test questions. https://www.usmle.org/exam-resources/step-1-materials/step-1-sample-test-questions, 2023. Accessed: 2025-03-31.

Yanjun Gao, Ruizhe Li, Emma Croxford, John Caskey, Brian W Patterson, Matthew Churpek, Timothy Miller, Dmitriy Dligach, and Majid Afshar. Leveraging medical knowledge graphs into large language models for diagnosis prediction: Design and application study. *Jmir Ai*, 4:e58670, 2025a.

Zhaolin Gao, Wenhao Zhan, Jonathan Daniel Chang, Gokul Swamy, Kianté Brantley, Jason D. Lee, and Wen Sun. Regressing the relative future: Efficient policy optimization for multi-turn RLHF. In *The Thirteenth International Conference on Learning Representations*, 2025b. URL `https://openreview.net/forum?id=cVyELMpMRS`.

Ahmad Ghazal, Tilmann Rabl, Minqing Hu, Francois Raab, Meikel Poess, Alain Crolotte, and Hans-Arno Jacobsen. Bigbench: Towards an industry standard benchmark for big data analytics. In *Proceedings of the 2013 ACM SIGMOD international conference on Management of data*, pp. 1197–1208, 2013.

Tom Gibbs, Ethan Kosak-Hine, George Ingebretsen, Jason Zhang, Julius Broomfield, Sara Pieri, Reihaneh Iranmanesh, Reihaneh Rabbany, and Kellin Pelrine. Emerging vulnerabilities in frontier models: Multi-turn jailbreak attacks. *arXiv preprint arXiv:2409.00137*, 2024.

Team GLM, Aohan Zeng, Bin Xu, Bowen Wang, Chenhui Zhang, Da Yin, Dan Zhang, Diego Rojas, Guanyu Feng, Hanlin Zhao, et al. Chatglm: A family of large language models from glm-130b to glm-4 all tools. *arXiv preprint arXiv:2406.12793*, 2024.

Tear Gosling, Alpin Dale, and Yinhe Zheng. Pippa: A partially synthetic conversational dataset. *arXiv preprint arXiv:2308.05884*, 2023.

Ziming Guo, Chao Ma, Yinggang Sun, Tiancheng Zhao, Guangyao Wang, and Hai Huang. Evaluating and enhancing llms for multi-turn text-to-sql with multiple question types. In *2025 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–10. IEEE, 2025.

Lewis Hammond, Alan Chan, Jesse Clifton, Jason Hoelscher-Obermaier, Akbir Khan, Euan McLean, Chandler Smith, Wolfram Barfuss, Jakob Foerster, Tomáš Gavenčiak, et al. Multi-agent risks from advanced AI. *arXiv preprint arXiv:2502.14143*, 2025.

Chi Han, Xin Liu, Haodong Wang, Shiyang Li, Jingfeng Yang, Haoming Jiang, Zhengyang Wang, Qingyu Yin, Liang Qiu, Changlong Yu, Yifan Gao, Zheng Li, Bing Yin, Jingbo Shang, and Heng Ji. Can language models follow multiple turns of entangled instructions? In Christos Christodoulopoulos, Tanmoy Chakraborty, Carolyn Rose, and Violet Peng (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2025*, pp. 25445–25460. Association for Computational Linguistics, November 2025.

Shanshan Han, Qifan Zhang, Yuhang Yao, Weizhao Jin, Zhaozhuo Xu, and Chaoyang He. LLM multi-agent systems: Challenges and open problems. *arXiv preprint arXiv:2402.03578*, 2024.

Xu Han, Bin Guo, Yoon Jung, Benjamin Yao, Yu Zhang, Xiaohu Liu, and Chenlei Guo. PersonaPKT: Building personalized dialogue agents via parameter-efficient knowledge transfer. In Nafise Sadat Moosavi, Iryna Gurevych, Yufang Hou, Gyuwan Kim, Young Jin Kim, Tal Schuster, and Ameeta Agrawal (eds.), *Proceedings of the Fourth Workshop on Simple and Efficient Natural Language Processing (SustaiNLP)*, pp. 264–273, Toronto, Canada (Hybrid), July 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.sustainlp-1.21. URL `https://aclanthology.org/2023.sustainlp-1.21/`.

Divij Handa, Zehua Zhang, Amir Saeidi, Shrinidhi Kumbhar, Md Nayem Uddin, Aswin RRV, and Chitta Baral. When" competency" in reasoning opens the door to vulnerability: Jailbreaking llms via novel complex ciphers. *arXiv preprint arXiv:2402.10601*, 2024.

Yun He, Di Jin, Chaoqi Wang, Chloe Bi, Karishma Mandyam, Hejia Zhang, Chen Zhu, Ning Li, Tengyu Xu, Hongjiang Lv, et al. Multi-IF: Benchmarking LLMs on Multi-Turn and Multilingual Instructions Following. *arXiv preprint arXiv:2410.15553*, 2024.

Zifan He, Yingqi Cao, Zongyue Qin, Neha Prakriya, Yizhou Sun, and Jason Cong. Hmt: Hierarchical memory transformer for efficient long context language processing. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 8068–8089, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. ISBN 979-8-89176-189-6. doi: 10.18653/v1/2025.naacl-long.410. URL `https://aclanthology.org/2025.naacl-long.410/`.

Dan Hendrycks, Collin Burns, Steven Basart, Andy Zou, Mantas Mazeika, Dawn Song, and Jacob Steinhardt. Measuring massive multitask language understanding. *Proceedings of the International Conference on Learning Representations (ICLR)*, 2021.

Sirui Hong, Mingchen Zhuge, Jonathan Chen, Xiawu Zheng, Yuheng Cheng, Jinlin Wang, Ceyao Zhang, Zili Wang, Steven Ka Shing Yau, Zijuan Lin, Liyang Zhou, Chenyu Ran, Lingfeng Xiao, Chenglin Wu, and Jürgen Schmidhuber. MetaGPT: Meta programming for a multi-agent collaborative framework. In *The Twelfth International Conference on Learning Representations*, 2024. URL https://openreview.net/forum?id=VtmBAGCN7o.

Bihao Hu, Jiayi Zhu, Yiying Pei, and Xiaoqing Gu. Exploring the potential of LLM to enhance teaching plans through teaching simulation. *npj Science of Learning*, 10(1):7, 2025a.

Edward J Hu, Yelong Shen, Phillip Wallis, Zeyuan Allen-Zhu, Yuanzhi Li, Shean Wang, Liang Wang, Weizhu Chen, et al. Lora: Low-rank adaptation of large language models. *Iclr*, 1(2):3, 2022.

Jinpeng Hu, Tengteng Dong, Gang Luo, Hui Ma, Peng Zou, Xiao Sun, Dan Guo, Xun Yang, and Meng Wang. Psycollm: Enhancing llm for psychological understanding and evaluation. *IEEE Transactions on Computational Social Systems*, 12(2):539–551, 2025b. doi: 10.1109/TCSS.2024.3497725.

Zefa Hu, Haozhi Zhao, Yuanyuan Zhao, Shuang Xu, and Bo Xu. T-agent: A term-aware agent for medical dialogue generation. In *2024 International Joint Conference on Neural Networks (IJCNN)*, pp. 1–8, 2024. doi: 10.1109/IJCNN60899.2024.10650649.

Parag Jain and Mirella Lapata. Integrating large language models with graph-based reasoning for conversational question answering, 2024.

Jiaming Ji, Mickel Liu, Josef Dai, Xuehai Pan, Chi Zhang, Ce Bian, Boyuan Chen, Ruiyang Sun, Yizhou Wang, and Yaodong Yang. Beavertails: Towards improved safety alignment of llm via a human-preference dataset. *Advances in Neural Information Processing Systems*, 36:24678–24704, 2023.

Qi Jia, Xiang Yue, Tuney Zheng, Jie Huang, and Bill Yuchen Lin. SimulBench: Evaluating language models with creative simulation tasks. In Luis Chiruzzo, Alan Ritter, and Lu Wang (eds.), *Findings of the Association for Computational Linguistics: NAACL 2025*, pp. 8118–8131. Association for Computational Linguistics, April 2025.

Qinjin Jia, Jialin Cui, Haoze Du, Parvez Rashid, Ruijie Xi, Ruochi Li, and Edward Gehringer. LLM-generated Feedback in Real Classes and Beyond: Perspectives from Students and Instructors. In *Proceedings of the 17th International Conference on Educational Data Mining*, pp. 862–867. International Educational Data Mining Society, July 2024a.

Qinjin Jia, Jialin Cui, Ruijie Xi, Chengyuan Liu, Parvez Rashid, Ruochi Li, and Edward Gehringer. On Assessing the Faithfulness of LLM-generated Feedback on Student Assignments. In *Proceedings of the 17th International Conference on Educational Data Mining*, pp. 491–499, 2024b.

Hang Jiang, Xiajie Zhang, Xubo Cao, Cynthia Breazeal, Deb Roy, and Jad Kabbara. PersonaLLM: Investigating the ability of large language models to express personality traits. In Kevin Duh, Helena Gomez, and Steven Bethard (eds.), *Findings of the Association for Computational Linguistics: NAACL 2024*, pp. 3605–3627, Mexico City, Mexico, June 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-naacl.229. URL https://aclanthology.org/2024.findings-naacl.229/.

Yifan Jiang, Kriti Aggarwal, Tanmay Laud, Kashif Munir, Jay Pujara, and Subhabrata Mukherjee. Red queen: Safeguarding large language models against concealed multi-turn jailbreaking. *arXiv preprint arXiv:2409.17458*, 2024b.

Di Jin, Eileen Pan, Nassim Oufattole, Wei-Hung Weng, Hanyi Fang, and Peter Szolovits. What disease does this patient have? a large-scale open domain question answering dataset from medical exams. *Applied Sciences*, 11(14):6421, 2021.

Hyoungwook Jin, Minju Yoo, Jeongeon Park, Yokyung Lee, Xu Wang, and Juho Kim. TeachTune: Reviewing Pedagogical Agents Against Diverse Student Profiles with Simulated Students. In *Proceedings of the 2025 CHI Conference on Human Factors in Computing Systems*, CHI '25. Association for Computing Machinery, 2025.

Qiao Jin, Bhuwan Dhingra, Zhengping Liu, William Cohen, and Xinghua Lu. PubMedQA: A dataset for biomedical research question answering. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pp. 2567–2577. Association for Computational Linguistics, November 2019.

Minki Kang, Jin Myung Kwak, Jinheon Baek, and Sung Ju Hwang. Knowledge graph-augmented language models for knowledge-grounded dialogue generation, 2023.

Priyanka Kargupta, Ishika Agarwal, Dilek Hakkani Tur, and Jiawei Han. Instruct, not assist: LLM-based multi-turn planning and hierarchical questioning for socratic code debugging. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 9475–9495. Association for Computational Linguistics, November 2024.

Vladimir Karpukhin, Barlas Oguz, Sewon Min, Patrick Lewis, Ledell Wu, Sergey Edunov, Danqi Chen, and Wen-tau Yih. Dense passage retrieval for open-domain question answering. In Bonnie Webber, Trevor Cohn, Yulan He, and Yang Liu (eds.), *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pp. 6769–6781, Online, November 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.emnlp-main.550. URL https://aclanthology.org/2020.emnlp-main.550/.

Yannis Katsis, Sara Rosenthal, Kshitij Fadnis, Chulaka Gunasekara, Young-Suk Lee, Lucian Popa, Vraj Shah, Huaiyu Zhu, Danish Contractor, and Marina Danilevsky. Mtrag: A multi-turn conversational benchmark for evaluating retrieval-augmented generation systems. *Transactions of the Association for Computational Linguistics*, 13:784–808, 2025.

Vivian Keating. Zero-shot mathematical problem solving with large language models via multi-agent conversation programming. In *AI for Education: Bridging Innovation and Responsibility at the 38th AAAI Annual Conference on AI*, 2024.

Mojtaba Komeili, Kurt Shuster, and Jason Weston. Internet-augmented dialogue generation. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 8460–8478, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.579. URL https://aclanthology.org/2022.acl-long.579/.

Aobo Kong, Shiwan Zhao, Hao Chen, Qicheng Li, Yong Qin, Ruiqi Sun, Xin Zhou, Enzhi Wang, and Xiaohang Dong. Better zero-shot reasoning with role-play prompting. In Kevin Duh, Helena Gomez, and Steven Bethard (eds.), *Proceedings of the 2024 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 4099–4113, Mexico City, Mexico, June 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024.naacl-long.228. URL https://aclanthology.org/2024.naacl-long.228/.

Chuyi Kong, Yaxin Fan, Xiang Wan, Feng Jiang, and Benyou Wang. PlatoLM: Teaching LLMs in multi-round dialogue via a user simulator. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7841–7863. Association for Computational Linguistics, August 2024b.

Milan Kostic, Hans Friedrich Witschel, Knut Hinkelmann, and Maja Spahic-Bogdanovic. Llms in automated essay evaluation: A case study. *Proceedings of the AAAI Symposium Series*, 3(1):143–147, May 2024.

Satwik Kottur, Xiaoyu Wang, and Vitor Carvalho. Exploring personalized neural conversational models. In *Proceedings of the Twenty-Sixth International Joint Conference on Artificial Intelligence, IJCAI-17*, pp. 3728–3734, 2017. doi: 10.24963/ijcai.2017/521. URL https://doi.org/10.24963/ijcai.2017/521.

Aviral Kumar, Vincent Zhuang, Rishabh Agarwal, Yi Su, John D Co-Reyes, Avi Singh, Kate Baumli, Shariq Iqbal, Colton Bishop, Rebecca Roelofs, Lei M Zhang, Kay McKinney, Disha Shrivastava, Cosmin Paduraru, George Tucker, Doina Precup, Feryal Behbahani, and Aleksandra Faust. Training language models to self-correct via reinforcement learning. In *The Thirteenth International Conference on Learning Representations*, 2025. URL `https://openreview.net/forum?id=CjwERcAU7w`.

Tzu-Lin Kuo, FengTing Liao, Mu-Wei Hsieh, Fu-Chieh Chang, Po-Chun Hsu, and Da-shan Shiu. RAD-Bench: Evaluating Large Language Models Capabilities in Retrieval Augmented Dialogues. In Weizhu Chen, Yi Yang, Mohammad Kachuee, and Xue-Yong Fu (eds.), *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 3: Industry Track)*, pp. 868–902, Albuquerque, New Mexico, April 2025. Association for Computational Linguistics. ISBN 979-8-89176-194-0. doi: 10.18653/v1/2025.naacl-industry.66. URL `https://aclanthology.org/2025.naacl-industry.66/`.

Wai-Chung Kwan, Xingshan Zeng, Yuxin Jiang, Yufei Wang, Liangyou Li, Lifeng Shang, Xin Jiang, Qun Liu, and Kam-Fai Wong. MT-Eval: A Multi-Turn Capabilities Evaluation Benchmark for Large Language Models. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 20153–20177. Association for Computational Linguistics, November 2024.

Bruno Latour. *Reassembling the social: An introduction to actor-network-theory*. Oxford university press, 2005.

Zachary Levonian, Owen Henkel, Chenglu Li, and Millie-Ellen Postle. Designing safe and relevant generative chats for math learning in intelligent tutoring systems. *Journal of Educational Data Mining*, 17(1), 2025.

Patrick Lewis, Ethan Perez, Aleksandra Piktus, Fabio Petroni, Vladimir Karpukhin, Naman Goyal, Heinrich Küttler, Mike Lewis, Wen-tau Yih, Tim Rocktäschel, et al. Retrieval-augmented generation for knowledge-intensive nlp tasks. *Advances in neural information processing systems*, 33:9459–9474, 2020.

Baokui Li, Sen Zhang, Wangshu Zhang, Yicheng Chen, Changlin Yang, Sen Hu, Teng Xu, Siye Liu, and Jiwei Li. S2m: Converting single-turn to multi-turn datasets for conversational question answering. In *ECAI 2023*, pp. 1365–1372. IOS Press, 2023a.

Cheng Li, Ziang Leng, Chenxi Yan, Junyi Shen, Hao Wang, Weishi Mi, Yaying Fei, Xiaoyang Feng, Song Yan, HaoSheng Wang, et al. Chatharuhi: Reviving anime character in reality via large language model. *arXiv preprint arXiv:2308.09597*, 2023b.

Dawei Li, Renliang Sun, Yue Huang, Ming Zhong, Bohan Jiang, Jiawei Han, Xiangliang Zhang, Wei Wang, and Huan Liu. Preference leakage: A contamination problem in LLM-as-a-judge. In *The Fourteenth International Conference on Learning Representations*, 2026.

Guohao Li, Hasan Abed Al Kader Hammoud, Hani Itani, Dmitrii Khizbullin, and Bernard Ghanem. CAMEL: Communicative agents for "mind" exploration of large language model society. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023c. URL `https://openreview.net/forum?id=3IyL2XWDkG`.

Haoxuan Li, Jifan Yu, Xin Cong, Yang Dang, Yisi Zhan, Huiqin Liu, and Zhiyuan Liu. Exploring LLM-based Student Simulation for Metacognitive Cultivation. *arXiv preprint arXiv:2502.11678*, 2025a.

Jiwei Li, Michel Galley, Chris Brockett, Georgios Spithourakis, Jianfeng Gao, and Bill Dolan. A persona-based neural conversation model. In Katrin Erk and Noah A. Smith (eds.), *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 994–1003, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-1094. URL `https://aclanthology.org/P16-1094/`.

Rongao Li, Jie Fu, Bo-Wen Zhang, Tao Huang, Zhihong Sun, Chen Lyu, Guang Liu, Zhi Jin, and Ge Li. Taco: Topics in algorithmic code generation dataset, 2023d.

Shuyue Stella Li, Vidhisha Balachandran, Shangbin Feng, Jonathan S. Ilgen, Emma Pierson, Pang Wei Koh, and Yulia Tsvetkov. Mediq: Question-asking LLMs and a benchmark for reliable interactive clinical reasoning. In *The Thirty-eighth Annual Conference on Neural Information Processing Systems*, 2024.

Xuechen Li, Tianyi Zhang, Yann Dubois, Rohan Taori, Ishaan Gulrajani, Carlos Guestrin, Percy Liang, and Tatsunori B. Hashimoto. Alpacaeval: An automatic evaluator of instruction-following models. `https://github.com/tatsu-lab/alpaca_eval`, 5 2023e.

Youquan Li, Miao Zheng, Fan Yang, Guosheng Dong, Bin Cui, Weipeng Chen, Zenan Zhou, and Wentao Zhang. Fb-bench: A fine-grained multi-task benchmark for evaluating llms' responsiveness to human feedback. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 9282–9302, 2025b.

Yubo Li, Yidi Miao, Xueying Ding, Ramayya Krishnan, and Rema Padman. Firm or fickle? evaluating large language models consistency in sequential interactions. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 6679–6700. Association for Computational Linguistics, July 2025c.

Yujia Li, David Choi, Junyoung Chung, Nate Kushman, Julian Schrittwieser, Rémi Leblond, Tom Eccles, James Keeling, Felix Gimeno, Agustin Dal Lago, et al. Competition-level code generation with alphacode. *Science*, 378(6624):1092–1097, 2022.

Zhenwen Liang, Dian Yu, Wenhao Yu, Wenlin Yao, Zhihan Zhang, Xiangliang Zhang, and Dong Yu. Math-Chat: Benchmarking Mathematical Reasoning and Instruction Following in Multi-Turn Interactions. *arXiv preprint arXiv:2405.19444*, 2024.

Yusheng Liao, Yutong Meng, Hongcheng Liu, Yanfeng Wang, and Yu Wang. An automatic evaluation framework for multi-turn medical consultations capabilities of large language models. *arXiv preprint arXiv:2309.02077*, 2023.

Yusheng Liao, Shuyang Jiang, Yu Wang, and Yanfeng Wang. Ming-moe: Enhancing medical multi-task learning in large language models with sparse mixture of low-rank adapter experts. *arXiv preprint arXiv:2404.09027*, 2024a.

Yusheng Liao, Yutong Meng, Yuhao Wang, Hongcheng Liu, Yanfeng Wang, and Yu Wang. Automatic interactive evaluation for large language models with state aware patient simulator. *arXiv preprint arXiv:2403.08495*, 2024b.

Hunter Lightman, Vineet Kosaraju, Yuri Burda, Harrison Edwards, Bowen Baker, Teddy Lee, Jan Leike, John Schulman, Ilya Sutskever, and Karl Cobbe. Let's verify step by step. In *The twelfth international conference on learning representations*, 2023.

Xi Victoria Lin, Chenglong Wang, Luke Zettlemoyer, and Michael D Ernst. Nl2bash: A corpus and semantic parser for natural language interface to the linux operating system. In *Proceedings of the eleventh international conference on language resources and evaluation (LREC 2018)*, 2018.

Ben Liu, Jihai Zhang, Fangquan Lin, Xu Jia, and Min Peng. One Size doesn't Fit All: A Personalized Conversational Tutoring Agent for Mathematics Instruction. In *Companion Proceedings of the ACM on Web Conference 2025*, WWW '25, pp. 2401–2410. Association for Computing Machinery, 2025a.

Jiayu Liu, Zhenya Huang, Tong Xiao, Jing Sha, Jinze Wu, Qi Liu, Shijin Wang, and Enhong Chen. Socraticlm: Exploring socratic personalized teaching with large language models. In *Advances in Neural Information Processing Systems*, volume 37, pp. 85693–85721. Curran Associates, Inc., 2024a.

Jiongnan Liu, Yutao Zhu, Shuting Wang, Xiaochi Wei, Erxue Min, Yu Lu, Shuaiqiang Wang, Dawei Yin, and Zhicheng Dou. LLMs + persona-plug = personalized LLMs. In Wanxiang Che, Joyce Nabende, Ekaterina Shutova, and Mohammad Taher Pilehvar (eds.), *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9373–9385, Vienna, Austria, July 2025b. Association for Computational Linguistics. ISBN 979-8-89176-251-0. doi: 10.18653/v1/2025.acl-long.461. URL `https://aclanthology.org/2025.acl-long.461/`.

Junling Liu, Peilin Zhou, Yining Hua, Dading Chong, Zhongyu Tian, Andrew Liu, Helin Wang, Chenyu You, Zhenhua Guo, Lei Zhu, and Michael Lingzhi Li. Benchmarking large language models on cmexam - a comprehensive chinese medical exam dataset. In *Proceedings of the 37th International Conference on Neural Information Processing Systems*, NIPS '23, Red Hook, NY, USA, 2023. Curran Associates Inc.

Ruoyu Liu, Kui Xue, Xiaofan Zhang, and Shaoting Zhang. Interactive evaluation for medical LLMs via task-oriented dialogue system. In *Proceedings of the 31st International Conference on Computational Linguistics*, pp. 4871–4896. Association for Computational Linguistics, January 2025c.

Shuo Liu, Kaining Ying, Hao Zhang, Yue Yang, Yuqi Lin, Tianle Zhang, Chuanhao Li, Yu Qiao, Ping Luo, Wenqi Shao, and Kaipeng Zhang. ConvBench: A Multi-Turn Conversation Evaluation Benchmark with Hierarchical Ablation Capability for Large Vision-Language Models. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*, NIPS '24. Curran Associates Inc., 2024b.

Xiao Liu, Liangzhi Li, Tong Xiang, Fuying Ye, Lu Wei, Wangyue Li, and Noa Garcia. Imposter.AI: Adversarial Attacks with Hidden Intentions towards Aligned Large Language Models. *arXiv preprint arXiv:2407.15399*, 2024c.

Xiao Liu, Hao Yu, Hanchen Zhang, Yifan Xu, Xuanyu Lei, Hanyu Lai, Yu Gu, Hangliang Ding, Kaiwen Men, Kejuan Yang, Shudan Zhang, Xiang Deng, Aohan Zeng, Zhengxiao Du, Chenhui Zhang, Sheng Shen, Tianjun Zhang, Yu Su, Huan Sun, Minlie Huang, Yuxiao Dong, and Jie Tang. Agentbench: Evaluating LLMs as agents. In *The Twelfth International Conference on Learning Representations*, 2024d.

Xiaogeng Liu, Nan Xu, Muhao Chen, and Chaowei Xiao. AutoDAN: Generating stealthy jailbreak prompts on aligned large language models. In *The Twelfth International Conference on Learning Representations*, 2024e.

Xiner Liu, Maciej Pankiewicz, Tanvi Gupta, Zhongtian Huang, and Ryan S Baker. A Step Towards Adaptive Online Learning: Exploring the Role of GPT as Virtual Teaching Assistants in Online Education. In *Future of Learning with Large Language Models*, pp. 149–166. CRC Press, 2025d.

Zhengyuan Liu, Stella Xin Yin, Geyu Lin, and Nancy F. Chen. Personality-aware Student Simulation for Conversational Intelligent Tutoring Systems. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 626–642. Association for Computational Linguistics, November 2024f.

Ziyu Liu, Tao Chu, Yuhang Zang, Xilin Wei, Xiaoyi Dong, Pan Zhang, Zijian Liang, Yuanjun Xiong, Yu Qiao, Dahua Lin, and Jiaqi Wang. Mmdu: a multi-turn multi-image dialog understanding benchmark and instruction-tuning dataset for lvlms. In *Proceedings of the 38th International Conference on Neural Information Processing Systems*, NIPS '24. Curran Associates Inc., 2024g.

Dominic Lohr, Hieke Keuning, and Natalie Kiesler. You're (Not) My Type-Can LLMs Generate Feedback of Specific Types for Introductory Programming Tasks? *Journal of Computer Assisted Learning*, 41(1): e13107, 2025.

Keming Lu, Bowen Yu, Chang Zhou, and Jingren Zhou. Large language models are superpositions of all characters: Attaining arbitrary role-play via self-alignment. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7828–7840, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.423. URL https://aclanthology.org/2024.acl-long.423/.

Xing Han Lù, Zdeněk Kasner, and Siva Reddy. WEBLINX: real-world website navigation with multi-turn dialogue. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

Xinyi Lu and Xu Wang. Generative Students: Using LLM-Simulated Student Profiles to Support Question Item Evaluation. In *Proceedings of the Eleventh ACM Conference on Learning @ Scale*, L@S '24, pp. 16–27. Association for Computing Machinery, 2024.

Jakub Macina, Nico Daheim, Sankalan Chowdhury, Tanmay Sinha, Manu Kapur, Iryna Gurevych, and Mrinmaya Sachan. MathDial: A dialogue tutoring dataset with rich pedagogical properties grounded in math reasoning problems. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 5602–5621. Association for Computational Linguistics, December 2023.

Jakub Macina, Nico Daheim, Ido Hakimi, Manu Kapur, Iryna Gurevych, and Mrinmaya Sachan. Mathtutorbench: A benchmark for measuring open-ended pedagogical capabilities of llm tutors. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 204–221, 2025.

Aman Madaan, Niket Tandon, Peter Clark, and Yiming Yang. Memory-assisted prompt editing to improve GPT-3 after deployment. In *ACL 2022 Workshop on Commonsense Representation and Reasoning*, 2022. URL https://openreview.net/forum?id=Bx-fUfKedZ5.

Rishabh Maheshwary, Vikas Yadav, Hoang H Nguyen, Khyati Mahajan, and Sathwik Tejaswi Madhusudhan. M2lingual: Enhancing multilingual, multi-turn instruction alignment in large language models. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers)*, pp. 9676–9713, 2025.

Costas Mavromatis and George Karypis. GNN-RAG: Graph neural retrieval for efficient large language model reasoning on knowledge graphs. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 16682–16699, Vienna, Austria, July 2025. Association for Computational Linguistics.

Mantas Mazeika, Long Phan, Xuwang Yin, Andy Zou, Zifan Wang, Norman Mu, Elham Sakhaee, Nathaniel Li, Steven Basart, Bo Li, David Forsyth, and Dan Hendrycks. HarmBench: a standardized evaluation framework for automated red teaming and robust refusal. In *Proceedings of the 41st International Conference on Machine Learning*, ICML'24. JMLR.org, 2024.

Emmanuel Mutabazi, Jianjun Ni, Guangyi Tang, and Weidong Cao. A review on medical textual question answering systems based on deep learning approaches. *Applied Sciences*, 11(12):5456, 2021.

Inderjeet Jayakumar Nair, Jiaye Tan, Xiaotian Su, Anne Gere, Xu Wang, and Lu Wang. Closing the Loop: Learning to Generate Writing Feedback via Language Model Simulated Student Revisions. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 16636–16657. Association for Computational Linguistics, November 2024.

Milad Nasr, Javier Rando, Nicholas Carlini, Jonathan Hayase, Matthew Jagielski, A. Feder Cooper, Daphne Ippolito, Christopher A. Choquette-Choo, Florian Tramèr, and Katherine Lee. Scalable extraction of training data from aligned, production language models. In *The Thirteenth International Conference on Learning Representations*, 2025.

Robert Osazuwa Ness, Katie Matton, Hayden Helm, Sheng Zhang, Junaid Bajwa, Carey E Priebe, and Eric Horvitz. Medfuzz: Exploring the robustness of large language models in medical question answering. *arXiv preprint arXiv:2406.06573*, 2024.

Jianmo Ni, Gustavo Hernandez Abrego, Noah Constant, Ji Ma, Keith Hall, Daniel Cer, and Yinfei Yang. Sentence-t5: Scalable sentence encoders from pre-trained text-to-text models. In *Findings of the Association for Computational Linguistics: ACL 2022*, pp. 1864–1874. Association for Computational Linguistics, May 2022.

Erik Nijkamp, Hiroaki Hayashi, Caiming Xiong, Silvio Savarese, and Yingbo Zhou. Codegen2: Lessons for training llms on programming and natural languages. *arXiv preprint arXiv:2305.02309*, 2023a.

Erik Nijkamp, Bo Pang, Hiroaki Hayashi, Lifu Tu, Huan Wang, Yingbo Zhou, Silvio Savarese, and Caiming Xiong. Codegen: An open large language model for code with multi-turn program synthesis. In *The Eleventh International Conference on Learning Representations*, 2023b.

Daniela Occhipinti, Serra Sinem Tekiroğlu, and Marco Guerini. PRODIGy: a PROfile-based DIalogue generation dataset. In Kevin Duh, Helena Gomez, and Steven Bethard (eds.), *Findings of the Association for Computational Linguistics: NAACL 2024*, pp. 3500–3514, Mexico City, Mexico, June 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-naacl.222. URL https://aclanthology.org/2024.findings-naacl.222/.

Long Ouyang, Jeffrey Wu, Xu Jiang, Diogo Almeida, Carroll Wainwright, Pamela Mishkin, Chong Zhang, Sandhini Agarwal, Katarina Slama, Alex Ray, John Schulman, Jacob Hilton, Fraser Kelton, Luke Miller, Maddie Simens, Amanda Askell, Peter Welinder, Paul F Christiano, Jan Leike, and Ryan Lowe. Training language models to follow instructions with human feedback. In S. Koyejo, S. Mohamed, A. Agarwal, D. Belgrave, K. Cho, and A. Oh (eds.), *Advances in Neural Information Processing Systems*, volume 35, pp. 27730–27744. Curran Associates, Inc., 2022.

Xinghan Pan. Enhancing RWKV-based Language Models for Long-Sequence Text Generation, 2025.

Joon Sung Park, Joseph O'Brien, Carrie Jun Cai, Meredith Ringel Morris, Percy Liang, and Michael S Bernstein. Generative agents: Interactive simulacra of human behavior. In *Proceedings of the 36th annual acm symposium on user interface software and technology*, pp. 1–22, 2023.

Bo Peng, Eric Alcaide, Quentin Anthony, Alon Albalak, Samuel Arcadinho, Stella Biderman, Huanqi Cao, Xin Cheng, Michael Chung, Leon Derczynski, Xingjian Du, Matteo Grella, Kranthi Gv, Xuzheng He, Haowen Hou, Przemyslaw Kazienko, Jan Kocon, Jiaming Kong, Bartłomiej Koptyra, Hayden Lau, Jiaju Lin, Krishna Sri Ipsit Mantri, Ferdinand Mom, Atsushi Saito, Guangyu Song, Xiangru Tang, Johan Wind, Stanisław Woźniak, Zhenyuan Zhang, Qinghua Zhou, Jian Zhu, and Rui-Jie Zhu. RWKV: Reinventing RNNs for the transformer era. In *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 14048–14077. Association for Computational Linguistics, December 2023.

Sara Pieri, Sahal Shaji Mullappilly, Fahad Shahbaz Khan, Rao Muhammad Anwer, Salman Khan, Timothy Baldwin, and Hisham Cholakkal. BiMediX: Bilingual medical mixture of experts LLM. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 16984–17002. Association for Computational Linguistics, November 2024.

Mathis Pink, Qinyuan Wu, Vy Ai Vo, Javier Turek, Jianing Mu, Alexander Huth, and Mariya Toneva. Position: Episodic memory is the missing piece for long-term llm agents, 2025.

Romain Puech, Jakub Macina, Julia Chatain, Mrinmaya Sachan, and Manu Kapur. Towards the pedagogical steering of large language models for tutoring: A case study with modeling productive failure. In *Findings of the Association for Computational Linguistics: ACL 2025*, pp. 26291–26311. Association for Computational Linguistics, July 2025.

Chen Qian, Wei Liu, Hongzhang Liu, Nuo Chen, Yufan Dang, Jiahao Li, Cheng Yang, Weize Chen, Yusheng Su, Xin Cong, Juyuan Xu, Dahai Li, Zhiyuan Liu, and Maosong Sun. Chatdev: Communicative agents for software development. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 15174–15186, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.810. URL https://aclanthology.org/2024.acl-long.810/.

Yanzhao Qin, Tao Zhang, Tao Zhang, Yanjun Shen, Wenjing Luo, sunhaoze, Yan Zhang, Yujing Qiao, weipeng chen, Zenan Zhou, Wentao Zhang, and Bin CUI. Sysbench: Can LLMs follow system message? In *The Thirteenth International Conference on Learning Representations*, 2025.

Huachuan Qiu, Hongliang He, Shuai Zhang, Anqi Li, and Zhenzhong Lan. SMILE: Single-turn to multi-turn inclusive language expansion via ChatGPT for mental health support. In *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 615–636. Association for Computational Linguistics, November 2024.

Alec Radford, Jeffrey Wu, Rewon Child, David Luan, Dario Amodei, Ilya Sutskever, et al. Language models are unsupervised multitask learners. *OpenAI blog*, 1(8):9, 2019.

Rafael Rafailov, Archit Sharma, Eric Mitchell, Christopher D Manning, Stefano Ermon, and Chelsea Finn. Direct preference optimization: Your language model is secretly a reward model. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023.

Traian Rebedea, Razvan Dinu, Makesh Narsimhan Sreedhar, Christopher Parisien, and Jonathan Cohen. Nemo guardrails: A toolkit for controllable and safe llm applications with programmable rails. In *Proceedings of the 2023 conference on empirical methods in natural language processing: system demonstrations*, pp. 431–445, 2023.

Qibing Ren, Hao Li, Dongrui Liu, Zhanxu Xie, Xiaoya Lu, Yu Qiao, Lei Sha, Junchi Yan, Lizhuang Ma, and Jing Shao. LLMs know their vulnerabilities: Uncover safety gaps through natural distribution shifts. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 24763–24785. Association for Computational Linguistics, July 2025.

Alireza Rezazadeh, Zichao Li, Wei Wei, and Yujia Bao. From isolated conversations to hierarchical schemas: Dynamic tree memory representation for LLMs. In *The Thirteenth International Conference on Learning Representations*, 2025. URL `https://openreview.net/forum?id=moXtEmCleY`.

Sara Riazi and Pedram Rooshenas. LLM-Driven Feedback for Enhancing Conceptual Design Learning in Database Systems Courses. In *Proceedings of the 56th ACM Technical Symposium on Computer Science Education V. 1*, SIGCSETS 2025, pp. 1001–1007. Association for Computing Machinery, 2025.

Bernardino Romera-Paredes, Mohammadamin Barekatain, Alexander Novikov, Matej Balog, M Pawan Kumar, Emilien Dupont, Francisco JR Ruiz, Jordan S Ellenberg, Pengming Wang, Omar Fawzi, et al. Mathematical discoveries from program search with large language models. *Nature*, 625(7995):468–475, 2024.

Andreas Rücklé, Gregor Geigle, Max Glockner, Tilman Beck, Jonas Pfeiffer, Nils Reimers, and Iryna Gurevych. AdapterDrop: On the efficiency of adapters in transformers. In *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing*, pp. 7930–7946. Association for Computational Linguistics, November 2021.

Mark Russinovich, Ahmed Salem, and Ronen Eldan. Great, now write an article about that: The crescendo {Multi-Turn}{LLM} jailbreak attack. In *34th USENIX Security Symposium (USENIX Security 25)*, pp. 2421–2440, 2025.

Alireza Salemi, Sheshera Mysore, Michael Bendersky, and Hamed Zamani. LaMP: When large language models meet personalization. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 7370–7392, Bangkok, Thailand, August 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.399. URL `https://aclanthology.org/2024.acl-long.399/`.

Alexander Scarlatos, Digory Smith, Simon Woodhead, and Andrew Lan. Improving the validity of automatically generated feedback via reinforcement learning. In *International Conference on Artificial Intelligence in Education*, pp. 280–294. Springer, 2024.

Alexander Scarlatos, Naiming Liu, Jaewook Lee, Richard Baraniuk, and Andrew Lan. Training LLM-Based Tutors to Improve Student Learning Outcomes in Dialogues. In *Artificial Intelligence in Education: 26th International Conference, AIED 2025, Palermo, Italy, July 22–26, 2025, Proceedings, Part I*, pp. 251–266. Springer-Verlag, 2025.

Timo Schick, Jane Dwivedi-Yu, Roberto Dessi, Roberta Raileanu, Maria Lomeli, Eric Hambro, Luke Zettlemoyer, Nicola Cancedda, and Thomas Scialom. Toolformer: Language models can teach themselves to use tools. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL `https://openreview.net/forum?id=Yacmpz84TH`.

Mohamed El Amine Seddik, Suei-Wen Chen, Soufiane Hayou, Pierre Youssef, and Merouane Abdelkader DEBBAH. How bad is training on synthetic data? a statistical analysis of language model collapse. In *First Conference on Language Modeling*, 2024. URL `https://openreview.net/forum?id=t3z6UlV09o`.

Omar Shaikh, Hongxin Zhang, William Held, Michael Bernstein, and Diyi Yang. On second thought, let's not think step by step! bias and toxicity in zero-shot reasoning. In *Proceedings of the 61st Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 4454–4470, 2023.

Yunfan Shao, Linyang Li, Junqi Dai, and Xipeng Qiu. Character-LLM: A trainable agent for role-playing. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 13153–13187, Singapore, December 2023. Association for Computational Linguistics. URL https://aclanthology.org/2023.emnlp-main.814/.

Noam Shazeer. Fast transformer decoding: One write-head is all you need. *arXiv preprint arXiv:1911.02150*, 2019.

Ryan Shea and Zhou Yu. Building persona consistent dialogue agents with offline reinforcement learning. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Proceedings of the 2023 Conference on Empirical Methods in Natural Language Processing*, pp. 1778–1795, Singapore, December 2023. Association for Computational Linguistics. doi: 10.18653/v1/2023.emnlp-main.110. URL https://aclanthology.org/2023.emnlp-main.110/.

Tianhao Shen, Sun Li, and Deyi Xiong. Roleeval: A bilingual role evaluation benchmark for large language models. 2023a.

Yongliang Shen, Kaitao Song, Xu Tan, Dongsheng Li, Weiming Lu, and Yueting Zhuang. HuggingGPT: Solving AI tasks with chatGPT and its friends in hugging face. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023b. URL https://openreview.net/forum?id=yHdTscY6Ci.

Wenqi Shi, Ran Xu, Yuchen Zhuang, Yue Yu, Jieyu Zhang, Hang Wu, Yuanda Zhu, Joyce C. Ho, Carl Yang, and May Dongmei Wang. EHRAgent: Code empowers large language models for few-shot complex tabular reasoning on electronic health records. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 22315–22339, Miami, Florida, USA, November 2024a. Association for Computational Linguistics.

Wentao Shi, Mengqi Yuan, Junkang Wu, Qifan Wang, and Fuli Feng. Direct multi-turn preference optimization for language agents. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 2312–2324. Association for Computational Linguistics, November 2024b.

Xiaoming Shi, Zeming Liu, Li Du, Yuxuan Wang, Hongru Wang, Yuhang Guo, Tong Ruan, Jie Xu, Xiaofan Zhang, and Shaoting Zhang. Medical dialogue system: A survey of categories, methods, evaluation and challenges. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 2840–2861. Association for Computational Linguistics, August 2024c.

Yuling Shi, Songsong Wang, Chengcheng Wan, and Xiaodong Gu. From code to correctness: Closing the last mile of code generation with hierarchical debugging, 2024d.

Noah Shinn, Federico Cassano, Ashwin Gopinath, Karthik R Narasimhan, and Shunyu Yao. Reflexion: language agents with verbal reinforcement learning. In *Thirty-seventh Conference on Neural Information Processing Systems*, 2023. URL https://openreview.net/forum?id=vAElhFcKW6.

Mohit Shridhar, Xingdi Yuan, Marc-Alexandre Cote, Yonatan Bisk, Adam Trischler, and Matthew Hausknecht. {ALFW}orld: Aligning text and embodied environments for interactive learning. In *International Conference on Learning Representations*, 2021.

Priscylla Silva and Evandro Costa. Assessing Large Language Models for Automated Feedback Generation in Learning Programming Problem Solving. In *Proceedings of the Innovation and Responsibility in AI-Supported Education Workshop*, volume 273 of *Proceedings of Machine Learning Research*, pp. 116–124. PMLR, 03 Mar 2025.

Hao Sun, Zhenru Lin, Chujie Zheng, Siyang Liu, and Minlie Huang. PsyQA: A Chinese dataset for generating long counseling text for mental health support. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Findings of the Association for Computational Linguistics: ACL-IJCNLP 2021*, pp. 1489–1503,

Online, August 2021. Association for Computational Linguistics. doi: 10.18653/v1/2021.findings-acl.130. URL https://aclanthology.org/2021.findings-acl.130/.

Yuchong Sun, Che Liu, Kun Zhou, Jinwen Huang, Ruihua Song, Wayne Xin Zhao, Fuzheng Zhang, Di Zhang, and Kun Gai. Parrot: Enhancing multi-turn instruction following for large language models. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9729–9750, 2024.

Alon Talmor, Jonathan Herzig, Nicholas Lourie, and Jonathan Berant. CommonsenseQA: A question answering challenge targeting commonsense knowledge. In *Proceedings of the 2019 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long and Short Papers)*, pp. 4149–4158. Association for Computational Linguistics, June 2019.

Xingyu Tan, Xiaoyang Wang, Qing Liu, Xiwei Xu, Xin Yuan, and Wenjie Zhang. Paths-over-graph: Knowledge graph enpowered large language model reasoning. In *THE WEB CONFERENCE 2025*, 2025. URL https://openreview.net/forum?id=ICJysB6LdA.

Meiling Tao, Liang Xuechen, Tianyu Shi, Lei Yu, and Yiting Xie. RoleCraft-GLM: Advancing personalized role-playing in large language models. In *Proceedings of the 1st Workshop on Personalization of Generative AI Systems (PERSONALIZE 2024)*, pp. 1–9. Association for Computational Linguistics, March 2024.

Zeyu Teng, Yong Song, Xiaozhou Ye, and Ye Ouyang. Fine-tuning llms for multi-turn dialogues: optimizing cross-entropy loss with kl divergence for all rounds of responses. In *Proceedings of the 2024 16th International Conference on Machine Learning and Computing*, pp. 128–133, 2024.

James Thorne, Andreas Vlachos, Christos Christodoulopoulos, and Arpit Mittal. Fever: a large-scale dataset for fact extraction and verification. In *Proceedings of the 2018 Conference of the North American Chapter of the Association for Computational Linguistics: Human Language Technologies, Volume 1 (Long Papers)*, pp. 809–819, 2018.

Yuanhe Tian, Weicheng Ma, Fei Xia, and Yan Song. ChiMed: A Chinese medical corpus for question answering. In *Proceedings of the 18th BioNLP Workshop and Shared Task*, pp. 250–260. Association for Computational Linguistics, August 2019.

Augustin Toma, Patrick R Lawler, Jimmy Ba, Rahul G Krishnan, Barry B Rubin, and Bo Wang. Clinical Camel: An Open Expert-Level Medical Language Model with Dialogue-Based Knowledge Encoding. *arXiv preprint arXiv:2305.12031*, 2023.

Mihaela Tomova, Iván Roselló Atanet, Victoria Sehy, Miriam Sieg, Maren März, and Patrick Mäder. Leveraging large language models to construct feedback from medical multiple-choice questions. *Scientific Reports*, 14(1):27910, 2024.

Hugo Touvron, Thibaut Lavril, Gautier Izacard, Xavier Martinet, Marie-Anne Lachaux, Timothée Lacroix, Baptiste Rozière, Naman Goyal, Eric Hambro, Faisal Azhar, et al. Llama: Open and efficient foundation language models. *arXiv preprint arXiv:2302.13971*, 2023.

Quan Tu, Chuanqi Chen, Jinpeng Li, Yanran Li, Shuo Shang, Dongyan Zhao, Ran Wang, and Rui Yan. Characterchat: Learning towards conversational ai with personalized social support. *arXiv preprint arXiv:2308.10278*, 2023.

Quan Tu, Shilong Fan, Zihang Tian, Tianhao Shen, Shuo Shang, Xin Gao, and Rui Yan. CharacterEval: A Chinese benchmark for role-playing conversational agent evaluation. In *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 11836–11850. Association for Computational Linguistics, August 2024.

Tao Tu, Mike Schaekermann, Anil Palepu, Khaled Saab, Jan Freyberg, Ryutaro Tanno, Amy Wang, Brenna Li, Mohamed Amin, Yong Cheng, et al. Towards conversational diagnostic artificial intelligence. *Nature*, 642(8067):442–450, 2025.

Mina Valizadeh and Natalie Parde. The AI doctor is in: A survey of task-oriented dialogue systems for healthcare applications. In *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 6638–6660. Association for Computational Linguistics, May 2022.

Andra Waagmeester, Gregory Stupp, Sebastian Burgstaller-Muehlbacher, Benjamin M Good, Malachi Griffith, Obi L Griffith, Kristina Hanspers, Henning Hermjakob, Toby S Hudson, Kevin Hybiske, et al. Wikidata as a knowledge graph for the life sciences. *Elife*, 9:e52614, 2020.

Fengxiang Wang, Ranjie Duan, Peng Xiao, Xiaojun Jia, Shiji Zhao, Cheng Wei, YueFeng Chen, Chongwen Wang, Jialing Tao, Hang Su, et al. MRJ-Agent: An Effective Jailbreak Agent for Multi-Round Dialogue. *arXiv preprint arXiv:2411.03814*, 2024a.

Guanzhi Wang, Yuqi Xie, Yunfan Jiang, Ajay Mandlekar, Chaowei Xiao, Yuke Zhu, Linxi Fan, and Anima Anandkumar. Voyager: An open-ended embodied agent with large language models. *Transactions on Machine Learning Research*, 2024b. ISSN 2835-8856. URL `https://openreview.net/forum?id=ehfRiFOR3a`.

Haochun Wang, Chi Liu, Nuwa Xi, Zewen Qiang, Sendong Zhao, Bing Qin, and Ting Liu. Huatuo: Tuning llama model with chinese medical knowledge. *arXiv preprint arXiv:2304.06975*, 2023a.

Jian Wang, Chak Tou Leong, Jiashuo Wang, Dongding Lin, Wenjie Li, and Xiaoyong Wei. Instruct once, chat consistently in multiple rounds: An efficient tuning framework for dialogue. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 3993–4010. Association for Computational Linguistics, August 2024c.

Junling Wang, Jakub Macina, Nico Daheim, Sankalan Pal Chowdhury, and Mrinmaya Sachan. Book2Dial: Generating Teacher Student Interactions from Textbooks for Cost-Effective Development of Educational Chatbots. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 9707–9731. Association for Computational Linguistics, August 2024d.

Xingyao Wang, Yangyi Chen, Lifan Yuan, Yizhe Zhang, Yunzhu Li, Hao Peng, and Heng Ji. Executable code actions elicit better llm agents. In *Forty-first International Conference on Machine Learning*, 2024e.

Xingyao Wang, Zihan Wang, Jiateng Liu, Yangyi Chen, Lifan Yuan, Hao Peng, and Heng Ji. MINT: Evaluating LLMs in multi-turn interaction with tools and language feedback. In *The Twelfth International Conference on Learning Representations*, 2024f.

Xintao Wang, Yunze Xiao, Jen-tse Huang, Siyu Yuan, Rui Xu, Haoran Guo, Quan Tu, Yaying Fei, Ziang Leng, Wei Wang, Jiangjie Chen, Cheng Li, and Yanghua Xiao. InCharacter: Evaluating personality fidelity in role-playing agents through psychological interviews. In Lun-Wei Ku, Andre Martins, and Vivek Srikumar (eds.), *Proceedings of the 62nd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 1840–1873, Bangkok, Thailand, August 2024g. Association for Computational Linguistics. doi: 10.18653/v1/2024.acl-long.102. URL `https://aclanthology.org/2024.acl-long.102/`.

Xinyu Wang, Yanzheng Xiang, Lin Gui, and Yulan He. Garlic: Llm-guided dynamic progress control with hierarchical weighted graph for long document qa, 2024h.

Yizhong Wang, Yeganeh Kordi, Swaroop Mishra, Alisa Liu, Noah A Smith, Daniel Khashabi, and Hannaneh Hajishirzi. Self-instruct: Aligning language models with self-generated instructions. In *Proceedings of the 61st annual meeting of the association for computational linguistics (volume 1: long papers)*, pp. 13484–13508, 2023b.

Yuandong Wang, Xuhui Ren, Tong Chen, Yuxiao Dong, Nguyen Quoc Viet Hung, and Jie Tang. Multi-turn response selection with commonsense-enhanced language models, 2024i.

Jason Wei, Xuezhi Wang, Dale Schuurmans, Maarten Bosma, Fei Xia, Ed Chi, Quoc V Le, Denny Zhou, et al. Chain-of-thought prompting elicits reasoning in large language models. *Advances in neural information processing systems*, 35:24824–24837, 2022.

Kyle Wiggers. Learnlm is Google's new family of AI models for education. `https://techcrunch.com/2024/05/14/learnlm-is-googles-new-family-of-ai-models-for-education/`, 2024.

Di Wu, Hongwei Wang, Wenhao Yu, Yuwei Zhang, Kai-Wei Chang, and Dong Yu. Longmemeval: Benchmarking chat assistants on long-term interactive memory. In *The Thirteenth International Conference on Learning Representations*, 2025. URL `https://openreview.net/forum?id=pZiyCaVuti`.

Qingyang Wu and Zhou Yu. Stateful memory-augmented transformers for efficient dialogue modeling. In Yvette Graham and Matthew Purver (eds.), *Findings of the Association for Computational Linguistics: EACL 2024*, pp. 853–867, St. Julian's, Malta, March 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-eacl.57. URL `https://aclanthology.org/2024.findings-eacl.57/`.

Tongtong Wu, Linhao Luo, Yuan-Fang Li, Shirui Pan, Thuy-Trang Vu, and Gholamreza Haffari. Continual learning for large language models: A survey. *arXiv preprint arXiv:2402.01364*, 2024a.

Yiran Wu, Feiran Jia, Shaokun Zhang, Hangyu Li, Erkang Zhu, Yue Wang, Yin Tat Lee, Richard Peng, Qingyun Wu, and Chi Wang. Mathchat: Converse to tackle challenging math problems with LLM agents. In *ICLR 2024 Workshop on Large Language Model (LLM) Agents*, 2024b.

Honglin Xiong, Sheng Wang, Yitao Zhu, Zihao Zhao, Yuxiao Liu, Linlin Huang, Qian Wang, and Dinggang Shen. Doctorglm: Fine-tuning your chinese doctor is not a herculean task. *arXiv preprint arXiv:2304.01097*, 2023.

Wei Xiong, Chengshuai Shi, Jiaming Shen, Aviv Rosenberg, Zhen Qin, Daniele Calandriello, Misha Khalman, Rishabh Joshi, Bilal Piot, Mohammad Saleh, Chi Jin, Tong Zhang, and Tianqi Liu. Building math agents with multi-turn iterative preference learning. In *The Thirteenth International Conference on Learning Representations*, 2025.

Austin Xu, Srijan Bansal, Yifei Ming, Semih Yavuz, and Shafiq Joty. Does context matter? Contextual-JudgeBench for evaluating LLM-based judges in contextual settings. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 9541–9564. Association for Computational Linguistics, July 2025.

Can Xu, Qingfeng Sun, Kai Zheng, Xiubo Geng, Pu Zhao, Jiazhan Feng, Chongyang Tao, Qingwei Lin, and Daxin Jiang. WizardLM: Empowering large pre-trained language models to follow complex instructions. In *The Twelfth International Conference on Learning Representations*, 2024. URL `https://openreview.net/forum?id=CfXh93NDgH`.

Jie Xu, Lu Lu, Sen Yang, Bilin Liang, Xinwei Peng, Jiali Pang, Jinru Ding, Xiaoming Shi, Lingrui Yang, Huan Song, et al. Medgpteval: A dataset and benchmark to evaluate responses of large language models in medicine. *arXiv preprint arXiv:2305.07340*, 2023.

Jing Xu, Arthur Szlam, and Jason Weston. Beyond goldfish memory: Long-term open-domain conversation. In Smaranda Muresan, Preslav Nakov, and Aline Villavicencio (eds.), *Proceedings of the 60th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 5180–5197, Dublin, Ireland, May 2022. Association for Computational Linguistics. doi: 10.18653/v1/2022.acl-long.356. URL `https://aclanthology.org/2022.acl-long.356/`.

John Yang, Akshara Prabhakar, Karthik Narasimhan, and Shunyu Yao. Intercode: Standardizing and benchmarking interactive coding with execution feedback. *Advances in Neural Information Processing Systems*, 36:23826–23854, 2023.

Sen Yang, Yafu Li, Wai Lam, and Yu Cheng. Multi-llm collaborative search for complex problem solving. *arXiv preprint arXiv:2502.18873*, 2025a.

Siwei Yang, Bingchen Zhao, and Cihang Xie. AQA-bench: An interactive benchmark for evaluating LLMs' sequential reasoning ability in algorithmic environments. *Transactions on Machine Learning Research*, 2025b. ISSN 2835-8856.

Songhua Yang, Hanjie Zhao, Senbin Zhu, Guangyu Zhou, Hongfei Xu, Yuxiang Jia, and Hongying Zan. Zhongjing: enhancing the chinese medical capabilities of large language model through expert feedback and real-world multi-turn dialogue. In *Proceedings of the Thirty-Eighth AAAI Conference on Artificial Intelligence and Thirty-Sixth Conference on Innovative Applications of Artificial Intelligence and Fourteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI'24/IAAI'24/EAAI'24. AAAI Press, 2024.

Yuxin Yang, Haoyang Wu, Tao Wang, Jia Yang, Hao Ma, and Guojie Luo. Pseudo-Knowledge Graph: Meta-Path Guided Retrieval and In-Graph Text for RAG-Equipped LLM, 2025c.

Zhenyu Yang, Yuhang Hu, Zemin Du, Dizhan Xue, Shengsheng Qian, Jiahong Wu, Fan Yang, Weiming Dong, and Changsheng Xu. SVBench: A benchmark with temporal multi-turn dialogues for streaming video understanding. In *The Thirteenth International Conference on Learning Representations*, 2025d.

Zhilin Yang, Peng Qi, Saizheng Zhang, Yoshua Bengio, William Cohen, Ruslan Salakhutdinov, and Christopher D. Manning. Hotpotqa: A dataset for diverse, explainable multi-hop question answering. In Ellen Riloff, David Chiang, Julia Hockenmaier, and Jun'ichi Tsujii (eds.), *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 2369–2380, Brussels, Belgium, October-November 2018. Association for Computational Linguistics. doi: 10.18653/v1/D18-1259. URL https://aclanthology.org/D18-1259/.

Shunyu Yao, Howard Chen, John Yang, and Karthik Narasimhan. Webshop: Towards scalable real-world web interaction with grounded language agents. *Advances in Neural Information Processing Systems*, 35: 20744–20757, 2022.

Shunyu Yao, Jeffrey Zhao, Dian Yu, Nan Du, Izhak Shafran, Karthik R Narasimhan, and Yuan Cao. React: Synergizing reasoning and acting in language models. In *The Eleventh International Conference on Learning Representations*, 2023. URL https://openreview.net/forum?id=WE_vluYUL-X.

Qichen Ye, Junling Liu, Dading Chong, Peilin Zhou, Yining Hua, Fenglin Liu, Meng Cao, Ziming Wang, Xuxin Cheng, Zhu Lei, et al. Qilin-med: Multi-stage knowledge injection advanced medical large language model. *arXiv preprint arXiv:2310.09089*, 2023.

Zihao Yi, Jiarui Ouyang, Zhe Xu, Yuwen Liu, Tianhao Liao, Haohao Luo, and Ying Shen. A survey on recent advances in llm-based multi-turn dialogue systems. *ACM Computing Surveys*, 58(6):1–38, 2025.

Haneul Yoo, Yongjin Yang, and Hwaran Lee. Code-switching red-teaming: LLM evaluation for safety and multilingual understanding. In *Proceedings of the 63rd Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 13392–13413. Association for Computational Linguistics, July 2025.

Erxin Yu, Jing Li, Ming Liao, Siqi Wang, Gao Zuchen, Fei Mi, and Lanqing Hong. Cosafe: Evaluating large language model safety in multi-turn dialogue coreference. In *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 17494–17508, 2024a.

Jiahao Yu, Xingwei Lin, Zheng Yu, and Xinyu Xing. GPTFUZZER: Red Teaming Large Language Models with Auto-Generated Jailbreak Prompts. *arXiv preprint arXiv:2309.10253*, 2023.

Tao Yu, Rui Zhang, Kai Yang, Michihiro Yasunaga, Dongxu Wang, Zifan Li, James Ma, Irene Li, Qingning Yao, Shanelle Roman, Zilin Zhang, and Dragomir Radev. Spider: A large-scale human-labeled dataset for complex and cross-domain semantic parsing and text-to-SQL task. In *Proceedings of the 2018 Conference on Empirical Methods in Natural Language Processing*, pp. 3911–3921. Association for Computational Linguistics, October-November 2018.

Xiaoyan Yu, Tongxu Luo, Yifan Wei, Fangyu Lei, Yiming Huang, Hao Peng, and Liehuang Zhu. Neeko: Leveraging dynamic LoRA for efficient multi-character role-playing agent. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 12540–12557, Miami, Florida, USA, November 2024b. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.697. URL https://aclanthology.org/2024.emnlp-main.697/.

Xinfeng Yuan, Siyu Yuan, Yuhan Cui, Tianhe Lin, Xintao Wang, Rui Xu, Jiangjie Chen, and Deqing Yang. Evaluating character understanding of large language models via character profiling from fictional works. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing*, pp. 8015–8036, Miami, Florida, USA, November 2024. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-main.456. URL https://aclanthology.org/2024.emnlp-main.456/.

Zhiyuan Zeng, Jiatong Yu, Tianyu Gao, Yu Meng, Tanya Goyal, and Danqi Chen. Evaluating large language models at evaluating instruction following. In *International Conference on Learning Representations (ICLR)*, 2024.

Chen Zhang, Xinyi Dai, Yaxiong Wu, Qu Yang, Yasheng Wang, Ruiming Tang, and Yong Liu. A survey on multi-turn interaction capabilities of large language models. *arXiv preprint arXiv:2501.09959*, 2025a.

Chenhao Zhang, Renhao Li, Minghuan Tan, Min Yang, Jingwei Zhu, Di Yang, Jiahao Zhao, Guancheng Ye, Chengming Li, and Xiping Hu. CPsyCoun: A report-based multi-turn dialogue reconstruction and evaluation framework for Chinese psychological counseling. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 13947–13966. Association for Computational Linguistics, August 2024a.

Hongbo Zhang, Junying Chen, Feng Jiang, Fei Yu, Zhihong Chen, Guiming Chen, Jianquan Li, Xiangbo Wu, Zhang Zhiyi, Qingying Xiao, Xiang Wan, Benyou Wang, and Haizhou Li. HuatuoGPT, towards taming language model to be a doctor. In Houda Bouamor, Juan Pino, and Kalika Bali (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2023*, pp. 10859–10885. Association for Computational Linguistics, December 2023.

Saizheng Zhang, Emily Dinan, Jack Urbanek, Arthur Szlam, Douwe Kiela, and Jason Weston. Personalizing dialogue agents: I have a dog, do you have pets too? In Iryna Gurevych and Yusuke Miyao (eds.), *Proceedings of the 56th Annual Meeting of the Association for Computational Linguistics (Volume 1: Long Papers)*, pp. 2204–2213, Melbourne, Australia, July 2018. Association for Computational Linguistics. doi: 10.18653/v1/P18-1205. URL https://aclanthology.org/P18-1205/.

Shengyu Zhang, Linfeng Dong, Xiaoya Li, Sen Zhang, Xiaofei Sun, Shuhe Wang, Jiwei Li, Runyi Hu, Tianwei Zhang, Guoyin Wang, et al. Instruction tuning for large language models: A survey. *ACM Computing Surveys*, 58(7):1–36, 2026.

Xiaoyu Zhang, Ruobing Xie, Yougang Lyu, Xin Xin, Pengjie Ren, Mingfei Liang, Bo Zhang, Zhanhui Kang, Maarten de Rijke, and Zhaochun Ren. Towards empathetic conversational recommender systems. In *Proceedings of the 18th ACM Conference on Recommender Systems*, pp. 84–93, 2024b.

Yaolun Zhang, Yinxu Pan, Yudong Wang, and Jie Cai. PyBench: Evaluating LLM Agent on various real-world coding tasks. *arXiv preprint arXiv:2407.16732*, 2024c.

Zhaoyang Zhang, Wenqi Shao, Yixiao Ge, Xiaogang Wang, Jinwei Gu, and Ping Luo. Cached Transformers: Improving Transformers with Differentiable Memory Cache. In *Proceedings of the Thirty-Eighth AAAI Conference on Artificial Intelligence and Thirty-Sixth Conference on Innovative Applications of Artificial Intelligence and Fourteenth Symposium on Educational Advances in Artificial Intelligence*, AAAI'24/IAAI'24/EAAI'24. AAAI Press, 2024d.

Zheyuan Zhang, Daniel Zhang-Li, Jifan Yu, Linlu Gong, Jinchang Zhou, Zhanxin Hao, Jianxiao Jiang, Jie Cao, Huiqin Liu, Zhiyuan Liu, Lei Hou, and Juanzi Li. Simulating Classroom Education with LLM-Empowered Agents. In *Proceedings of the 2025 Conference of the Nations of the Americas Chapter of the*

Association for Computational Linguistics: Human Language Technologies (Volume 1: Long Papers), pp. 10364–10379. Association for Computational Linguistics, April 2025b.

Lulu Zhao, Weihao Zeng, Xiaofeng Shi, Hua Zhou, Donglin Hao, and Yonghua Lin. Aqulia-med llm: pioneering full-process open-source medical language models. *arXiv preprint arXiv:2406.12182*, 2024.

Kunhao Zheng, Juliette Decugis, Jonas Gehring, Taco Cohen, benjamin negrevergne, and Gabriel Synnaeve. What makes large language models reason in (multi-turn) code generation? In *The Thirteenth International Conference on Learning Representations*, 2025.

Lianmin Zheng, Wei-Lin Chiang, Ying Sheng, Siyuan Zhuang, Zhanghao Wu, Yonghao Zhuang, Zi Lin, Zhuohan Li, Dacheng Li, Eric Xing, et al. Judging llm-as-a-judge with mt-bench and chatbot arena. *Advances in neural information processing systems*, 36:46595–46623, 2023.

Mingqian Zheng, Jiaxin Pei, Lajanugen Logeswaran, Moontae Lee, and David Jurgens. When" a helpful assistant" is not really helpful: Personas in system prompts do not improve performances of large language models. In Yaser Al-Onaizan, Mohit Bansal, and Yun-Nung Chen (eds.), *Findings of the Association for Computational Linguistics: EMNLP 2024*, pp. 15126–15154, Miami, Florida, USA, November 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024.findings-emnlp.888. URL `https://aclanthology.org/2024.findings-emnlp.888/`.

Tianyu Zheng, Ge Zhang, Tianhao Shen, Xueling Liu, Bill Yuchen Lin, Jie Fu, Wenhu Chen, and Xiang Yue. Opencodeinterpreter: Integrating code generation with execution and refinement. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 12834–12859, 2024b.

Li Zhong, Zilong Wang, and Jingbo Shang. Debug like a human: A large language model debugger via verifying runtime execution step by step. In *Findings of the Association for Computational Linguistics: ACL 2024*, pp. 851–870. Association for Computational Linguistics, August 2024.

Andy Zhou and Ron Arel. Siege: Multi-turn jailbreaking of large language models with tree search. In *ICLR 2025 Workshop on Building Trust in Language Models and Applications*, 2025.

Jeffrey Zhou, Tianjian Lu, Swaroop Mishra, Siddhartha Brahma, Sujoy Basu, Yi Luan, Denny Zhou, and Le Hou. Instruction-following evaluation for large language models. *arXiv preprint arXiv:2311.07911*, 2023.

Jinfeng Zhou, Zhuang Chen, Dazhen Wan, Bosi Wen, Yi Song, Jifan Yu, Yongkang Huang, Pei Ke, Guanqun Bi, Libiao Peng, JiaMing Yang, Xiyao Xiao, Sahand Sabour, Xiaohan Zhang, Wenjing Hou, Yijia Zhang, Yuxiao Dong, Hongning Wang, Jie Tang, and Minlie Huang. CharacterGLM: Customizing social characters with large language models. In Franck Dernoncourt, Daniel Preoţiuc-Pietro, and Anastasia Shimorina (eds.), *Proceedings of the 2024 Conference on Empirical Methods in Natural Language Processing: Industry Track*, pp. 1457–1476, Miami, Florida, US, November 2024a. Association for Computational Linguistics. doi: 10.18653/v1/2024.emnlp-industry.107. URL `https://aclanthology.org/2024.emnlp-industry.107/`.

Yifei Zhou, Andrea Zanette, Jiayi Pan, Sergey Levine, and Aviral Kumar. ArCHer: Training language model agents via hierarchical multi-turn RL. In *Forty-first International Conference on Machine Learning*, 2024b.

Yifei Zhou, Song Jiang, Yuandong Tian, Jason Weston, Sergey Levine, Sainbayar Sukhbaatar, and Xian Li. SWEET-RL: Training Multi-Turn LLM Agents on Collaborative Reasoning Tasks. *arXiv preprint arXiv:2503.15478*, 2025.

Zhenhong Zhou, Jiuyang Xiang, Haopeng Chen, Quan Liu, Zherui Li, and Sen Su. Speak out of turn: Safety vulnerability of large language models in multi-turn dialogue. *arXiv preprint arXiv:2402.17262*, 2024c.

Jiayuan Zhu, Jiazhen Pan, Yuyuan Liu, Fenglin Liu, and Junde Wu. Ask patients with patience: Enabling LLMs for human-centric medical dialogue with grounded reasoning. In *Proceedings of the 2025 Conference on Empirical Methods in Natural Language Processing*, pp. 2846–2857. Association for Computational Linguistics, November 2025.

Andy Zou, Zifan Wang, Nicholas Carlini, Milad Nasr, J Zico Kolter, and Matt Fredrikson. Universal and transferable adversarial attacks on aligned language models. *arXiv preprint arXiv:2307.15043*, 2023.

A   Appendix

You may include other additional sections here.