Multi-Prize Lottery Ticket Hypothesis:
FINDING GENERALIZABLE AND EFFICIENT BINARY SUBNETWORKS IN A RANDOMLY WEIGHTED NEURAL NETWORK

ABSTRACT

Recently, Frankle & Carbin (2018) demonstrated that randomly-initialized dense networks contain subnetworks that once found can be trained to reach test accuracy comparable to the trained dense network. However, finding these high performing trainable subnetworks is expensive, requiring iterative process of training and pruning weights. In this paper, we propose (and prove) a stronger *Multi-Prize Lottery Ticket Hypothesis*:

A sufficiently over-parameterized neural network with random weights contains several subnetworks (winning tickets) that (a) have comparable accuracy to a dense target network with learned weights (prize 1), (b) do not require any further training to achieve prize 1 (prize 2), and (c) is robust to extreme forms of quantization (i.e., binary weights and/or activation) (prize 3).

These multi-prize tickets enjoy a number of desirable properties including drastically reduced memory size, faster test-time inference, and lower power consumption compared to their dense and full-precision counterparts. Furthermore, we propose an algorithm for finding multi-prize tickets and test it by performing a series of experiments on CIFAR-10 and ImageNet datasets. Empirical results indicate that as models grow deeper and wider, untrained multi-prize tickets start to reach similar (and sometimes even higher) test accuracy compared to their significantly larger and full-precision counterparts that have been weight-trained. With minimal hyperparameter tuning, our binary weight multi-prize tickets outperform current state-of-the-art in binary neural networks.

1 INTRODUCTION

Deep learning (DL) has made a significant breakthroughs in a wide range of applications (Goodfellow et al., 2016). These performance improvements can be attributed to the significant growth in the model size and the availability of massive computational resources to train such models. Therefore, these gains have come at the cost of large memory consumption, high inference time and increased power consumption. This not only limits the potential applications where DL can make an impact but also have some serious consequences, such as, (a) generating huge carbon footprint, and (b) creating roadblocks to the democratization of AI. Note that significant parameter redundancy and a large number of floating-point operations are key factors incurring the these costs. Thus, for discarding the redundancy from DNNs, one can either (a) *Prune:* remove non-essential connections from an existing dense network, or (b) *Quantize:* constrain the weight and activation values to a set of discrete values, allowing them to be represented using fewer bits. Further, one can exploit the complementary nature of pruning and quantization to combining their strengths.

Although pruning and quantization[1] are typical approaches used for compressing the DNNs (Neill, 2020a), it is not clear under what conditions and to what extent compression can be achieved without sacrificing the accuracy. Along this direction, the most extreme form of quanitization is binarization, where weights and/or activations can only have two possible values, namely $-1(0)$ or $+1$ (the interest of this paper). In addition to saving memory, binarization results in more power efficient networks with significant computation acceleration since expensive multiply-accumulate operations (MACs) can be replaced by cheap XNOR and bit-counting operations (Qin et al., 2020a). In such a context, under what conditions can we prune a binarized DNN, yet achieving comparable accuracy to the original DNN? More importantly, even if these favourable conditions are met, how to find these extremely compressed (or compact), yet highly accurate subnetworks?

---

[1] A detailed discussion on related work on pruning and binarization is provided in Appendix E.

	Configuration	Model	Weights	Memory Savings	Comp. Savings	Params	Accuracy
CIFAR-10	Dense (32/32)	ResNet18	Learned	$1\times$	$1\times$	11.2 M	93.02%
	XNOR-Net (1/32)	VGG-Small	Learned	$\sim32\times$	$\sim2\times$	4.6 M	90.1%
	MPT (1/32)	**ResNet18**	**Untrained**	$\sim32\times$	$\sim2\times$	**2.6 M**	**94.15%**
ImageNet	Dense (32/32)	ResNet34	Learned	$1\times$	$1\times$	21.8 M	73.27%
	XNOR-Net (1/32)	ResNet18	Learned	$\sim32\times$	$\sim2\times$	11.2 M	60.8%
	MPT (1/32)	WRN-34	Untrained	$\sim32\times$	$\sim2\times$	9.6 M	68.88%
	MPT (1/32)	**WRN-50**	**Untrained**	$\sim32\times$	$\sim2\times$	**20.6 M**	**73.3%**

Figure 1: **Performance and Benefits of Multi-Prize Tickets**: Comparison of untrained multi-prize tickets (MPTs) with trained full precision and binary weight networks.

On the pruning front, traditional schemes have shown that a pretrained overparameterized network can be pruned without a significant loss in the performance. Recently, (Frankle & Carbin, 2018) made a breakthrough by showing that dense network contain sparse subnetworks that can match the performance of the original network when trained from scratch with weights being reset to their initialization (*Lottery Ticket Hypothesis*). Although the original approach to find these subnetworks still required training the dense network, some efforts (Wang et al., 2020b; You et al., 2019; Wang et al., 2020a) have been carried out to overcome this limitation. Recently a more intriguing phenomenon has been reported – a dense network with random initialization contains subnetworks that achieve high accuracy, without any further training (Zhou et al., 2019; Ramanujan et al., 2019; Malach et al., 2020; Orseau et al., 2020). These trends highlight that the community has made a good progress towards *efficiently* and *accurately* pruning DNNs.

In contrast to these positive developments for pruning, results on binarizing DNNs have been mostly negative. For example, to the best of our knowledge, none of the post-training schemes have been successful in binarizing pretrained models without retraining. Even with training binary neural networks (BNNs) from scratch (though inefficient), the community has not been able to make BNNs achieve comparable results to their full precision counterparts. The main reason being that network structures and back-propagation based weight optimization techniques are predominantly developed for full precision DNNs and may not be suitable for training BNNs. Thus, closing the gap in accuracy between the full precision and the binarized version may require a paradigm shift. Furthermore, this also makes one wonder if *efficiently* and *accurately* binarizing DNNs similar to the recent trends in pruning is ever feasible.

In this paper, we show that a randomly initialized dense network contains extremely sparse binary subnetworks that without any training have comparable performance to their trained dense and full-precision counterparts (i.e., *accurate*). Based on these results, we state the *Multi-Prize Lottery Ticket Hypothesis*:

Multi-Prize Lottery Ticket Hypothesis. *A sufficiently over-parameterized neural network with random weights contains several subnetworks (winning tickets) that (a) have comparable accuracy to a dense target network with learned weights (prize 1), (b) do not require any further training to achieve prize 1 (prize 2), and (c) is robust to extreme forms of quantization (i.e., binary weights and/or activation) (prize 3).*

Contributions. First, we propose the multi-prize lottery ticket hypothesis as a new perspective on finding neural networks with drastically reduced memory size, much faster test-time inference and lower power consumption compared to their dense and full-precision counterparts. Next, we provide theoretical evidence of the existence of highly accurate sparse binary subnetworks within a randomly weighted DNN (i.e., proving the multi-prize lottery ticket hypothesis). Specifically, we showed that we can find an ε-approximation of any neural network with width n and depth ℓ, by pruning and binarizing the weights of a randomly weighted neural network that is a factor $O(n^{3/2}\ell/\varepsilon)$ wider and 2ℓ deeper. To the best of our knowledge, this is the first theoretical work proving the existence of highly accurate yet untrained sparse binary subnetworks within a sufficiently overparameterized neural network. Finally, we propose **biprop** (**bi**narize-**pr**une **op**timizer) for uncovering multi-prize tickets within randomly weighted DNNs. This provides a completely new way to learn sparse BNNs without relying on weight-optimization.

Results. We explore two variants of multi-prize tickets – one with binary weights (MPT-1/32) and other with binary weights and activation (MPT-1/1) where x/y denotes x and y bits to represent weights and activation, respectively. MPTs we find have $60-80\%$ fewer parameters than the original network. In addition, compared to their full-precision (i.e., 32/32) counterparts, MPT–1/32 can provide $\sim 32\times$ memory saving and $\sim 2\times$ computation saving, and MPT–1/1 can provide $\sim 32\times$ memory saving and $\sim 58\times$ computation saving due to their binary nature (Rastegari et al., 2016). We perform a series of experiments on on small and large scale datasets for image recognition, namely CIFAR-10 (Krizhevsky et al., 2009) and ImageNet (Deng et al., 2009). On CIFAR-10, we test the performance of multi-prize tickets against the trend of making the model deeper and wider. We found that as models grow deeper and wider, both variants of multi-prize tickets start to reach similar (and sometimes even higher) test accuracy compared to the dense and full precision original network with learned weights. In other words, the performance of multi-prize tickets improves with the amount of redundancy in the original network. Note that our positive results are in sharp contrast with the existing belief of limited expressive power of BNNs. We also carry out experiments with state-of-the-art (SOTA) architectures on CIFAR-10 and ImageNet datasets with an aim to investigate their redundancy. We find that within most randomly weighted SOTA DNNs reside extremely compact (i.e., sparse and binary) subnetworks which are smaller than, but match the performance of trained target dense and full precision networks. Furthermore, with minimal hyperparameter tuning, our multi-prize tickets without any training achieve top-1 accuracy comparable (or higher) to SOTA BNNs. Specifically, our winning tickets MPT-1/32 set new state-of-the-art (in top-1 measure) w.r.t. trained BNN-1/32 – (a) on CIFAR-10 MPT-1/32 achieves 94.15% compared to the previous best 92.3% achieved by ProxQuant (Bai et al., 2018), and (b) on ImageNet MPT-1/32 achieves 73.3% compared to the previous best 72.8% achieved using Quantization-Networks (Yang et al., 2019). Furthermore, on both CIFAR-10 and ImageNet, MPT-1/32 subnetworks outperform their significantly larger and full-precision counterparts that have been weight-trained. MPT-1/1 performs comparable to SOTA on CIFAR-10, however, struggles on ImageNet. We discuss reasoning behind this and provide worthwhile future directions to further improve the performance.

2 Multi-Prize Lottery Tickets: Theory and Algorithms

We first prove the existence of multi-prize tickets in an overparameterized randomly weighted neural network. Then we explore two variants of tickets (MPT–1/32 and MPT–1/1) and present an algorithm to find them in randomly weighted networks.

2.1 Proving the Multi-Prize Lottery Tickets Hypothesis

In this section we seek to answer the following question: *What is the required amount of over-parameterization such that a randomly weighted neural network can be compressed to a sparse binary subnetwork that approximates a dense trained target network?*

Specifically, in Theorem 2 we derive a theoretical lower bound on the depth and the width of a randomly initialized neural network in which a binary weight subnetwork exists that can approximate a weight-optimized target network. For simplicity, we work under the assumption that the target network and randomly initialized neural network are fully-connected (FC) neural networks with ReLU activations. Motivated by recent works (Malach et al., 2020; Pensia et al., 2020) that establish the existence of real-valued subnetworks that approximate a target network, our approach can be summarized as follows. We first prove that a two-layer binary network of sufficient width contains a subnetwork that approximates a single-layer real-valued network. Then by composing the two-layer binary networks of sufficient width together, we are able to prove that the resulting FC binary network of depth 2ℓ is an ε-approximation of the FC real-valued network of depth ℓ. For ease of presentation, we state an informal version of the theorem here. A formal statement and proof of the theorem can be found in Appendix B in Theorem 2.

Theorem 1. *(Informal Statement of Theorem 2) Let $\varepsilon > 0$. For every target network of depth ℓ and width n with bounded weights, a random network of depth 2ℓ and width $O\left(\frac{\ell n^{3/2}}{\varepsilon}\right)$ contains, with high probability (over the randomness of the weights), a binary subnetwork that approximates the target network with error at most ε.*

Algorithm 1 biprop: Finding multi-prize tickets in randomly weighted neural networks
---
Initialize Parameters: Neural network $g(\boldsymbol{x}; \boldsymbol{W})$; Number of pruning and binarization passes P; Initial network weights $\boldsymbol{W}_0$; Initial pruning mask $\boldsymbol{M}_0 = \boldsymbol{1}$; Loss function $L(\cdot)$; Training features and labels $(\boldsymbol{X}, \boldsymbol{Y})$.

for $i = 0$ to $P - 1$ **do**

    Update Pruning Mask: Find $\boldsymbol{M}_{i+1}$ with $L\left((\boldsymbol{X}, \boldsymbol{Y}); \frac{\|\boldsymbol{M}_{i+1} \odot \boldsymbol{W}_0\|_1}{\|\boldsymbol{M}_{i+1}\|_1}(\boldsymbol{M}_{i+1} \odot \operatorname{sgn}(\boldsymbol{W}_0))\right) < L((\boldsymbol{X}, \boldsymbol{Y}); \boldsymbol{W}_i)$.

    Apply Pruning, Binarization, and Gain Term: $\boldsymbol{W}_{i+1} \leftarrow \frac{\|\boldsymbol{M}_{i+1} \odot \boldsymbol{W}_0\|_1}{\|\boldsymbol{M}_{i+1}\|_1}(\boldsymbol{M}_{i+1} \odot \operatorname{sgn}(\boldsymbol{W}_0))$

Return Binarized Subnetwork: $g(\boldsymbol{x}; \boldsymbol{W}_P))$.

2.2 FINDING MULTI-PRIZE WINNING TICKETS

Given the existence of multi-prize winning tickets from Theorem 2, a natural question arises – *How should we find them?* In this section we answer this question by introducing an algorithm for finding multi-prize tickets.[2] Specifically, we explore two variants of multi-prize tickets in this paper – 1) MPT-1/32 where weights are quantized to 1-bit with activation being real valued, i.e., 32-bits, and 2) MPT-1/1 where both weights and activation are quantized to 1-bit.

2.2.1 FINDING BINARY-WEIGHT TICKETS (MPT-1/32)

Now, we discuss our method for finding MPTs referred to as **biprop** (**bi**narize-**pr**une **op**timizer) that does not rely on weight-optimization but instead performs mask-optimization on a ranomly initialized network while applying binarization to the network weights. As the theoretical analysis in Section 2.1 suggests that the use of a gain term is beneficial in approximating a target network with a binary subnetwork, Algorithm 1 also incorporates a gain term into each layer of the identified MPT-1/32. The loss function, $L((\boldsymbol{X}, \boldsymbol{Y}), \boldsymbol{W})$, in Algorithm 1 corresponds to error of the model with parameters $\boldsymbol{W}$ on the training data $(\boldsymbol{X}, \boldsymbol{Y})$. Hence, the goal of the *Update Pruning Mask* step of Algorithm 1 is to reduce the training error by finding a pruning mask that reduces the error of the network on the training data when compared to the previous pruning mask. Motivation for the design of **biprop** is provided in Appendix C.

2.2.2 FINDING BINARY-ACTIVATION TICKETS (MPT-1/1)

When binarizing the activation function in the forward propagation, our MPT-1/1 networks make use of the sign function, $\operatorname{sgn}(z) = \frac{z}{|z|}$ for $z \neq 0$ and $\operatorname{sgn}(0) = 1$. Theoretically, Algorithm 1 can be used to identify MPT-1/1 within randomly initialized neural networks, however, binarizing the activation functions presents an issue when updating the pruning mask in Algorithm 1. This is because many techniques used to solve this optimization problem rely on gradient information but the gradient of the binary activation function is 0 almost everywhere. Fortunately, several techniques for approximating the gradient during propagation have been established (Bengio et al., 2013; Liu et al., 2018a; Wu et al., 2020). To test our approach empirically, we used the gradient estimator proposed in (Liu et al., 2018a) which is given by $2 - 2|z|$ for $z \in [-1, 1]$ and 0 for $z \notin [-1, 1]$.

3 EXPERIMENTAL RESULTS

The primary goal of the experiments in Section 3.1 is to empirically verify our *Multi-Prize Lottery Ticket Hypothesis*. As a secondary objective, we would like to determine tunable factors that make randomly-initialized networks amenable to containing readily identifiable Multi-Prize Tickets (MPTs). Thus, we test our hypothesis against the general trend of increasing the model size (depth and width) and monitor the accuracy of the identified MPTs. After verifying our *Multi-Prize Lottery Ticket Hypothesis*, we consider the performance of MPTs compared to state-of-the-arts in binary neural networks and their dense counterparts on CIFAR-10 and ImageNet datasets in Section 3.2.

In all of our experiments, we use Algorithm 1 to identify MPTs for each network configuration in Sections 3.1 and 3.2. In order to solve the optimization problem in line 3 of Algorithm 1, we make use of a modified version of the **edge-popup** algorithm (Ramanujan et al., 2019). As **edge-popup** requires a fixed number of parameters to be pruned, for each experiment we specify an additional parameter called *pruning percentage* that denotes the percentage of weights pruned from the randomly initialized network.

---

[2]Although our theoretical results are derived under certain assumptions (e.g., fully-connected, ReLU neural network approximated by a subnetwork with binary weights), our algorithms are not restricted by these assumptions.

3.1 WHERE CAN WE EXPECT TO FIND MULTI-PRIZE TICKETS?

In this section, we empirically test the effect of overparameterization on the performance of MPTs. We introduce overparameterization by making network architectures (a) deeper (Section 3.1.1) and (b) wider (Section 3.1.2).

Figure 2: **Effect of Varying Depth and Pruning Rate**: Comparing the Top-1 accuracy of sparse, binary, and untrained MPT-1/32 and MPT-1/1 to a dense, full-precision, and weight-optimized network on CIFAR-10.

We use VGG (Simonyan & Zisserman, 2014) variants as our network architectures for searching for MPTs. In each randomly weighted network, we find winning tickets MPT-1/32 and MPT-1/1 for different pruning rates using Algorithm 1. We choose our baselines as dense full-precision models with learned weights. In all experiments, we use three independent initializations and report the average of Top-1 accuracy with with error bars extending to the lowest and highest Top-1 accuracy. Additional experiment configuration details are provided in Appendix A.

3.1.1 DO WINNING TICKETS EXIST IN DEEP NETWORKS?

In this experiment, we empirically test the following hypothesis: *As a network grows deeper, the performance of untrained multi-prize tickets in the randomly initialized network will approach the performance of the same network with learned weights. We are further interested in exploring the required network depth for our hypothesis to be true.*

In Figure 2, we vary the depth of VGG architectures ($d = 2$ to 8) and compare the top-1 accuracy of MPT-1/32 and MPT-1/1 (at different pruning rates) with weight-trained dense network. We notice that there exist a range of pruning rates where the performance of MPTs are very similar, and beyond this range the performance drops quickly. Interestingly, as the network depth increases, more and more parameters can be pruned without hurting the performance of MPTs. As an example, MPT-1/32 can match the performance of trained Conv-8 without any training while having only $\sim 20\%$ of its parameter count. Interestingly, the performance gap between MPT-1/32 and MPT-1/1 does not change much with depth across different pruning rates. We further note that the performance of MPT-1/32 and MPT-1/1 improves when increasing the depth and both start to approach the performance of the dense model with learned weights. This gain starts to plateau beyond a certain depth, suggesting that the MPTs we identify might be approaching the limit of their achievable accuracy. Surprisingly, MPT-1/32 performs equally good (or better) than the dense model on all the architectures regardless of having $50 - 80\%$ lesser parameters and weights being binarized.

3.1.2 DO WINNING TICKETS EXIST IN WIDE NETWORKS?

Similar to the previous experiment, in this experiment, we empirically test the following hypothesis: *As a network grows wider, the performance of untrained multi-prize tickets in the randomly initialized network will approach the performance of the same network with learned weights. We are further interested in exploring the required layer width for our hypothesis to be true.*

In Figures 3 and 4, we vary the width of different VGG architectures and compare the top-1 accuracy of MPT-1/32 and MPT-1/1 tickets (at different pruning rates) with weight-trained dense network. A width multiplier of value 1 corresponds to the models in Figure 2. Performance of all the models improves when increasing the width and the performance of both MPT-1/32 and MPT-1/1 start to approach the performance of the dense model with learned weights. Although, this gain starts to plateau beyond a certain width. For both MPT-1/32 and MPT-1/1, as the width and depth increase the performance at different pruning rates approach the same value. This observed phenomenon yields a

Figure 3: **Effect of Varying Width with MPT-1/32**: Comparing the Top-1 accuracy of sparse, binary, and untrained MPT-1/32 networks to a dense, full-precision, and weight-optimized network on CIFAR-10.

Figure 4: **Effect of Varying Width with MPT-1/1**: Comparing the Top-1 accuracy of sparse, binary, and untrained MPT-1/1 networks to a dense, full-precision, and weight-optimized network on CIFAR-10.

more significant gain in the performance for MPTs with higher pruning rates. Similar to the previous experiment, the performance of MPT-1/32 matches (or exceeds) the performance of dense models for a large range of pruning rates. Furthermore, in the high width regime, a large number of weights ($\sim 90\%$) can be pruned without having a noticeable impact on the performance of MPTs. We also notice that the performance gap between MPT-1/32 and MPT-1/1 decreases significantly with an increase the width which is in sharp contrast with the with the depth experiments where the performance gap between MPT-1/32 and MPT-1/1 appeared to be largely independent of the depth.

Key Takeaways. Our experiments indeed verify our *Multi-Prize Lottery Ticket Hypothesis* and additionally convey the significance of choosing appropriate network depth and layer width for a given pruning rate. In particular, we find that a network with a large width can be pruned more aggressively without sacrificing much accuracy, while the accuracy of a network with smaller widths suffers when pruning a large percentage of the weights. Similar patterns hold for the depth of the networks as well. The amount of overparametrization needed to approach the performance of dense networks seems to differ for MPT-1/32 and MPT-1/1 – MPT-1/1 requires more higher depth and width compared to MPT-1/32 to achieve a certain performance.

3.2 HOW REDUNDANT STATE-OF-THE-ART DEEP NEURAL NETWORKS ACTUALLY ARE?

Having shown that MPTs can perform equally good (or better) than sufficiently overparameterized networks, this experiment aims to answer the following question: *Are state-of-the-art weight-trained DNNs overparametrized enough that significantly smaller and untrained MPTs can match (or beat) their performance?*

Experimental Configuration. Instead of focusing on extremely large DNNs, we experiment with small to moderate size DNNs. Specifically, we analyze the redundancy of following backbone models: (1) VGG-Small and ResNet-18 on

CIFAR-10, and (2) WideResNet-34 and WideResNet-50 on ImageNet. As we will show later that even these models are highly redundant, thus, our finding automatically extends to larger models. In this process, we also perform a comprehensive comparison of the performance of our multi-prize winning tickets with state-of-the-art in binary neural networks (BNNs). Details on the experimental configuration are provided in Appendix A.

In this experiment, we use Algorithm 1 to find multi-prize tickets within (a) randomly initialized VGG-Small and ResNet-18 for classifying the CIFAR-10 dataset, and (b) randomly initialized WideResNet-34 and WideResNet-50 for classifying the ImageNet dataset. We compare the Top-1 accuracy and number of parameters for our MPT-1/32 and MPT-1/1 tickets with selected baselines in binary neural networks (Qin et al., 2020a). A more comprehensive comparison can be found in Appendix D. Results for CIFAR-10 are shown in Tables 1 and 2, and results for ImageNet are shown in Tables 3 and 4. Next to the model name we include the layer width multiplier (if larger than 1) and the percentage of weights pruned for each of our listed configurations.

Method	Model	Top-1	Params
BinaryConnect	VGG-Small	91.7	4.6 M
ProxQuant	ResNet-56	92.3	0.85 M
DSQ	ResNet-20	90.2	0.27 M
MPT-1/32 (Ours)	VGG-Small (95)	90.58	0.23 M
MPT-1/32 (Ours)	**ResNet-18 (80)**	**94.15**	**2.2 M**
Full-Precision	ResNet-18	93.02	11.2 M

Table 1: Comparison of Untrained MPT-1/32 with Trained Binary (1/32) Networks on CIFAR-10.

Method	Model	Top-1	Params
BNN	VGG-Small	89.9	4.6 M
XNOR-Net	VGG-Small	89.8	4.6 M
DoReFa-Net	ResNet-20	79.3	0.27 M
DSQ	**VGG-Small**	**91.7**	**4.6 M**
MPT-1/1 (Ours)	VGG-Small (2x, 60)	88.22	3.68 M
Full-Precision	VGG-Small	93.6	4.6 M

Table 2: Comparison of Untrained MPT-1/1 with Trained Binary (1/1) Networks on CIFAR-10.

Method	Model	Top-1	Params
ABC-Net	ResNet-18	62.8	11.2 M
BWN	ResNet-18	60.8	11.2 M
Quantization-Networks	ResNet-50	72.8	25.6 M
MPT-1/32 (Ours)	WRN-34 (80)	68.88	9.6 M
MPT-1/32 (Ours)	**WRN-50 (70)**	**73.3**	**20.6 M**
Full-Precision	ResNet-34	73.27	21.8 M

Table 3: Comparison of Untrained MPT-1/32 with Trained Binary (1/32) Networks on ImageNet.

Method	Model	Top-1	Params
BNN	AlexNet	27.9	62.3 M
XNOR-Net	AlexNet	44.2	62.3 M
ABC-Net	ResNet-34	52.4	21.8 M
IR-Net	**ResNet-34**	**66.5**	**21.8 M**
MPT-1/1 (Ours)	WRN-34 (50)	38.98	24.1 M
Full-Precision	ResNet-34	73.27	21.8 M

Table 4: Comparison of Untrained MPT-1/1 with Trained Binary (1/1) Networks on ImageNet.

Our results highlight that SOTA DNN models are extremely redundant – in most cases our MPT models have similar performance of dense trained models with significantly lower number of parameters and binary weights/activation. For similar parameter count, our binary and untrained MPT-1/32 models outperform even full-precision models with learned weights. When compared to state-of-the-art in BNNs, with minimal hyperparameter tuning our multi-prize tickets achieve comparable (or higher) top-1 accuracy. Specifically, our winning tickets MPT-1/32 outperform trained binary neural networks with binary weights – (a) on CIFAR-10 MPT-1/32 with 80% pruned ResNet-18 model achieves 94.15% compared to the previous best 92.3% achieved using unpruned ResNet-56 (Bai et al., 2018), and (b) on ImageNet MPT-1/32 with 70% pruned Wide ResNet-50 achieves 73.3% compared to the previous best 72.8% achieved using unpruned ResNet-50 (Yang et al., 2019). Note that on CIFAR-10, MPT-1/32 outperforms its significantly larger dense and full precision counterpart with learned weights that achieves 93.02% accuracy. On ImageNet, a randomly weighted Wide ResNet-50 contains MPT-1/32 which is smaller than, but outperforms full precision ResNet-34 with learned weights (i.e., 73.27% top-1 accuracy).

Moving forward, we believe that there are several avenues for addressing the inability of MPT-1/1 to achieve state-of-the-art results. As this was our initial attempt to identify MPT-1/1 in moderate size networks, we used the baseline configurations of these networks with minimal modifications, such as our gradient estimator for the binary activation function. Hence, it is reasonable that our accuracy falls between the performance of BNN (Courbariaux et al., 2016) and XNOR-Net (Rastegari et al., 2016) which also make minimal modifications to the networks they are training. Searches for MPT-1/1 in networks more heavily modified for use with binary activation that are currently achieving

state-of-the-art results are likely to yield MPT-1/1 networks with improved performance. Additionally, alternative approaches for updating the pruning mask in **biprop**, which relied on gradient information in our empirical experiments, could alleviate issues with back-propagating gradient information through binary activation networks.

4 DISCUSSION AND IMPLICATIONS

Existing works on neural network compression (e.g., pruning and binarization) typically rely on some form of weight-training using gradient descent. In this paper we showed that a sufficiently overparametrized neural network with randomly initialized weights contains binary subnetworks that achieve high accuracy (comparable to dense and full precision original network with learned weights) without any training. We referred to this finding as *Multi-Prize Lottery Ticket Hypothesis.* We also proved the existence of such multi-prize winning tickets and presented a generic procedure to find them. Our empirical results on CIFAR-10 and ImageNet with state-of-the-art neural networks corroborate our hypothesis. With minimal hyperparameter tuning, our binary weight multi-prize tickets outperformed current state-of-the-art in binary neural networks and proved its practical importance.

Multi-prize lottery ticket hypothesis has several important practical and theoretical implications.

Algorithmic. We show that **biprop**, Algorithm 1, is capable of achieving solutions comparable (or better) to weight optimization of a sparse binary neural network. Note that joint pruning and binarization enjoys certain advantages over traditional weight-optimization approaches. First, contemporary experience suggests that training of sparse and binary neural networks from scratch using weight-optimization based approaches is challenging. Both sparseness and binarization bring their own challenges for gradient-based weight training – getting stuck at bad local minima in the sparse regime, incompatibility of back-propagation due to discontinuity in activation function, etc. Although we used gradient-based approaches in this paper, our **biprop** framework is flexible enough to easily accommodate different class of algorithms that might avoid the pitfalls of gradient-based weight training. Next, in contrast to weight-optimization that requires large model size and massive compute resources to achieve high performance, our multi-prize lottery ticket hypothesis suggests that one can achieve similar performance without ever training the large model. Therefore, strategies such as fast ticket search (You et al., 2019) or forward ticket selection Ye et al. (2020) can potentially be developed to enable more efficient ways of finding–or even designing–multi-prize tickets. Finally, weight-optimization results in models that are memory and computationally expensive. On the other hand, **biprop** by design achieves extremely compact yet accurate models, in turn, having excellent inference-time performance.

Theoretical. The multi-prize tickets achieve similar performance as the model with learned weights. First, this observation notes the benefit of overparameterization in the neural network learning and reinforces the idea that an important task of gradient descent (and learning in general) may be to effectively compress overparametrized models to find multi-prize tickets. Next, our results highlight the expressive power of MPTs – since we showed that compressed subnetworks can approximate any target neural network who are known to be universal approximators, our multi-prize tickets are also universal approximators. Finally, multi-prize lottery ticket hypothesis also uncovers the generalization properties of DNNs. Generalization theory for DL is still in its infancy and its not clear what and how NNs can learn Neyshabur et al. (2017). Multi-prize lottery ticket hypothesis maybe a valuable tool for answering such questions as it indicates that the generalization capability is determined by the compressiblity of a network.

Practical. Huge storage and heavy computation requirements of state-of-the-art deep neural networks inevitably limit their applications in practice. Multi-prize tickets are significantly lighter, faster, and efficient and still perform equally good. This unlocks a range of potential applications DL could be applied to, e.g., applications with resource-constrained devices (e.g. , the mobile phones, embedded devices, etc.). Our results also indicate that existing SOTA models might be spending far more compute and power than actually needed to achieve a certain performance. In other words, SOTA DL models have terrible energy efficiency and significant carbon footprint (Strubell et al., 2019). In this regards, MPTs have potential to enable environmental friendly artificial intelligence. Finally, due to their light weight nature and high efficiency, MPTs can also serve as an important building block in the effort on democratization of artificial intelligence (Moreau et al., 2019).

REFERENCES

Yu Bai, Yu-Xiang Wang, and Edo Liberty. Proxquant: Quantized neural networks via proximal operators. In *International Conference on Learning Representations*, 2018.

Yoshua Bengio, Nicholas Léonard, and Aaron Courville. Estimating or propagating gradients through stochastic neurons for conditional computation. *arXiv preprint arXiv:1308.3432*, 2013.

Matthieu Courbariaux, Yoshua Bengio, and Jean-Pierre David. Binaryconnect: Training deep neural networks with binary weights during propagations. In *Advances in neural information processing systems*, pp. 3123–3131, 2015.

Matthieu Courbariaux, Itay Hubara, Daniel Soudry, Ran El-Yaniv, and Yoshua Bengio. Binarized neural networks: Training deep neural networks with weights and activations constrained to+ 1 or-1. *arXiv preprint arXiv:1602.02830*, 2016.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks, 2018.

Adam Gaier and David Ha. Weight agnostic neural networks. In *Advances in Neural Information Processing Systems*, pp. 5364–5378, 2019.

Ruihao Gong, Xianglong Liu, Shenghu Jiang, Tianxiang Li, Peng Hu, Jiazhen Lin, Fengwei Yu, and Junjie Yan. Differentiable soft quantization: Bridging full-precision and low-bit neural networks. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 4852–4861, 2019.

Ian Goodfellow, Yoshua Bengio, Aaron Courville, and Yoshua Bengio. *Deep learning*, volume 1. MIT press Cambridge, 2016.

Jiaxin Gu, Ce Li, Baochang Zhang, Jungong Han, Xianbin Cao, Jianzhuang Liu, and David Doermann. Projection convolutional neural networks for 1-bit cnns via discrete back propagation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 8344–8351, 2019.

Masafumi Hagiwara. Removal of hidden units and weights for back propagation networks. In *Proceedings of 1993 International Conference on Neural Networks (IJCNN-93-Nagoya, Japan)*, volume 1, pp. 351–354. IEEE, 1993.

Kai Han, Yunhe Wang, Yixing Xu, Chunjing Xu, Enhua Wu, and Chang Xu. Training binary neural networks through learning with noisy supervision.

Song Han, Huizi Mao, and William J Dally. Deep compression: Compressing deep neural networks with pruning, trained quantization and huffman coding. *arXiv preprint arXiv:1510.00149*, 2015.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Delving deep into rectifiers: Surpassing human-level performance on imagenet classification, 2015.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. 2009.

Yann LeCun, John S Denker, and Sara A Solla. Optimal brain damage. In *Advances in neural information processing systems*, pp. 598–605, 1990.

Namhoon Lee, Thalaiyasingam Ajanthan, and Philip HS Torr. Snip: Single-shot network pruning based on connection sensitivity. *arXiv preprint arXiv:1810.02340*, 2018.

Xiaofan Lin, Cong Zhao, and Wei Pan. Towards accurate binary convolutional neural network. In *Advances in Neural Information Processing Systems*, pp. 345–353, 2017.

Zechun Liu, Baoyuan Wu, Wenhan Luo, Xin Yang, Wei Liu, and Kwang-Ting Cheng. Bi-real net: Enhancing the performance of 1-bit cnns with improved representational capability and advanced training algorithm. In *Proceedings of the European conference on computer vision (ECCV)*, pp. 722–737, 2018a.

Zhuang Liu, Mingjie Sun, Tinghui Zhou, Gao Huang, and Trevor Darrell. Rethinking the value of network pruning. *arXiv preprint arXiv:1810.05270*, 2018b.

Eran Malach, Gilad Yehudai, Shai Shalev-Shwartz, and Ohad Shamir. Proving the lottery ticket hypothesis: Pruning is all you need, 2020.

Asit Mishra, Eriko Nurvitadhi, Jeffrey J Cook, and Debbie Marr. Wrpn: Wide reduced-precision networks, 2017.

Erwan Moreau, Carl Vogel, and Marguerite Barry. A paradigm for democratizing artificial intelligence research. In *Innovations in Big Data Mining and Embedded Knowledge*, pp. 137–166. Springer, 2019.

James O' Neill. An overview of neural network compression. *arXiv preprint arXiv:2006.03669*, 2020a.

James O' Neill. An overview of neural network compression, 2020b.

Behnam Neyshabur, Srinadh Bhojanapalli, David McAllester, and Nati Srebro. Exploring generalization in deep learning. In *Advances in neural information processing systems*, pp. 5947–5956, 2017.

Laurent Orseau, Marcus Hutter, and Omar Rivasplata. Logarithmic pruning is all you need, 2020.

Ankit Pensia, Shashank Rajput, Alliot Nagle, Harit Vishwakarma, and Dimitris Papailiopoulos. Optimal lottery tickets via subsetsum: Logarithmic over-parameterization is sufficient, 2020.

Haotong Qin, Ruihao Gong, Xianglong Liu, Xiao Bai, Jingkuan Song, and Nicu Sebe. Binary neural networks: A survey. *Pattern Recognition*, pp. 107281, 2020a.

Haotong Qin, Ruihao Gong, Xianglong Liu, Mingzhu Shen, Ziran Wei, Fengwei Yu, and Jingkuan Song. Forward and backward information retention for accurate binary neural networks. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2250–2259, 2020b.

Vivek Ramanujan, Mitchell Wortsman, Aniruddha Kembhavi, Ali Farhadi, and Mohammad Rastegari. What's hidden in a randomly weighted neural network?, 2019.

Mohammad Rastegari, Vicente Ordonez, Joseph Redmon, and Ali Farhadi. Xnor-net: Imagenet classification using binary convolutional neural networks, 2016.

Mingzhu Shen, Xianglong Liu, Ruihao Gong, and Kai Han. Balanced binary neural networks with gated residual. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pp. 4197–4201. IEEE, 2020.

Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv 1409.1556*, 09 2014.

Emma Strubell, Ananya Ganesh, and Andrew McCallum. Energy and policy considerations for deep learning in nlp. *arXiv preprint arXiv:1906.02243*, 2019.

Chaoqi Wang, Guodong Zhang, and Roger Grosse. Picking winning tickets before training by preserving gradient flow. *arXiv preprint arXiv:2002.07376*, 2020a.

Yulong Wang, Xiaolu Zhang, Lingxi Xie, Jun Zhou, Hang Su, Bo Zhang, and Xiaolin Hu. Pruning from scratch. In *AAAI*, pp. 12273–12280, 2020b.

Andreas S Weigend, David E Rumelhart, and Bernardo A Huberman. Generalization by weight-elimination with application to forecasting. In *Advances in neural information processing systems*, pp. 875–882, 1991.

Mitchell Wortsman, Ali Farhadi, and Mohammad Rastegari. Discovering neural wirings. In *Advances in Neural Information Processing Systems*, pp. 2684–2694, 2019.

Qing Wu, Xiaojin Lu, Shan Xue, Chao Wang, Xundong Wu, and Jin Fan. Sbnn: Slimming binarized neural network. *Neurocomputing*, 401, 03 2020. doi: 10.1016/j.neucom.2020.03.030.

Saining Xie, Alexander Kirillov, Ross Girshick, and Kaiming He. Exploring randomly wired neural networks for image recognition. In *Proceedings of the IEEE International Conference on Computer Vision*, pp. 1284–1293, 2019.

Jiwei Yang, Xu Shen, Jun Xing, Xinmei Tian, Houqiang Li, Bing Deng, Jianqiang Huang, and Xian-sheng Hua. Quantization networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 7308–7316, 2019.

Mao Ye, Chengyue Gong, Lizhen Nie, Denny Zhou, Adam Klivans, and Qiang Liu. Good subnetworks provably exist: Pruning via greedy forward selection. *arXiv preprint arXiv:2003.01794*, 2020.

Haoran You, Chaojian Li, Pengfei Xu, Yonggan Fu, Yue Wang, Xiaohan Chen, Richard G Baraniuk, Zhangyang Wang, and Yingyan Lin. Drawing early-bird tickets: Towards more efficient training of deep networks. *arXiv preprint arXiv:1909.11957*, 2019.

Dongqing Zhang, Jiaolong Yang, Dongqiangzi Ye, and Gang Hua. Lq-nets: Learned quantization for highly accurate and compact deep neural networks, 2018.

Aojun Zhou, Anbang Yao, Yiwen Guo, Lin Xu, and Yurong Chen. Incremental network quantization: Towards lossless cnns with low-precision weights. *arXiv preprint arXiv:1702.03044*, 2017.

Hattie Zhou, Janice Lan, Rosanne Liu, and Jason Yosinski. Deconstructing lottery tickets: Zeros, signs, and the supermask, 2019.

Shuchang Zhou, Yuxin Wu, Zekun Ni, Xinyu Zhou, He Wen, and Yuheng Zou. Dorefa-net: Training low bitwidth convolutional neural networks with low bitwidth gradients. *arXiv preprint arXiv:1606.06160*, 2016a.

Shuchang Zhou, Yuxin Wu, Zekun Ni, Xinyu Zhou, He Wen, and Yuheng Zou. Dorefa-net: Training low bitwidth convolutional neural networks with low bitwidth gradients, 2016b.

A HYPERPARAMETER CONFIGURATIONS

A.1 HYPERPARAMETERS FOR SECTION 3.1

Experimental Configuration. For MPT-1/32 tickets, the network structure is not modified from the original. For MPT-1/1 tickets, the network structure is modified by moving the max-pooling layer directly after the convolution layer and adding a batch-normalization layer before the binary activation function, as is common in many BNN architectures (Rastegari et al., 2016). We choose our baselines as dense full precision models with learned weights. The baselines were obtained by training backbone networks using the Adam optimizer with learning rate of 0.0003 for 100 epochs and with a batch size of 60. In each randomly weighted backbone network, we find winning tickets MPT-1/32 and MPT-1/1 for different pruning rates using Algorithm 1. We use Adam optimizer with an initial learning rate of 0.1 and a cosine decay learning rate policy for 250 epochs with a batch size of 128 and a weight decay value of 0.0001. For both the weight-optimized and MPT networks, the weights are initialized using the Kaiming Normal distribution (He et al., 2015).

A.2 HYPERPARAMETERS FOR SECTION 3.2

Experimental Configuration. *CIFAR-10 Experiments:* MPT-1/32 Models: VGG-Small (Learning Rate Policy optimizer: adam, lr: 0.1, lr policy: cosine lr, Network training config epochs: 250, weight decay: 0.0001, momentum: 0.9, batchsize: 128)

ResNet-18: (Learning Rate Policy optimizer: sgd, lr: 0.1, lr policy: cosine lr, Network training config epochs: 100, weight decay: 0.0005, momentum: 0.9, batchsize: 256)

MPT-1/1 Models: VGG-Small(2x width) (Learning Rate Policy optimizer: adam, lr: 0.1, lr policy: cosine lr, Network training config epochs: 100, weight decay: 0.0001, momentum: 0.9, batchsize: 128)

ImageNet Experiments: MPT-1/32 Models: Wide ResNet-34 and Wide ResNet-50 (Learning Rate Policy optimizer: sgd, lr: 0.256, lr policy: cosine lr, warmup length: 5, Network training config epochs: 100, weight decay: 0.000030517578125, momentum: 0.875, batch size: 256, label smoothing: 0.1)

MPT-1/1 Models: Wide ResNet-34 (Learning Rate Policy optimizer: adam, lr: 0.256, lr policy: cosine lr, warmup length: 5, Network training config epochs: 100, weight decay: 0.000030517578125, momentum: 0.875, batchsize: 256, label smoothing: 0.1)

The weights are initialized using the Kaiming Normal distribution (He et al., 2015) for all the models except for MPT-1/32 on ImageNet where we use Signed Kaiming Constant following Ramanujan et al. (2019).

B EXISTENCE OF BINARY-WEIGHT SUBNETWORK APPROXIMATING TARGET NETWORK

Lemma 1. *Let $s \in [d]$, $\alpha \in \left[-\frac{1}{\sqrt{s}}, \frac{1}{\sqrt{s}}\right]$, $i \in [d]$, and $\varepsilon, \delta \geq 0$ be given. Let $\boldsymbol{B} \in \{-1, +1\}^{k \times d}$ be chosen randomly from $Bin(\{-1, 1\}^{k \times d})$ and $\boldsymbol{u} \in \{-1, +1\}^k$ be chosen randomly from $Bin(\{-1, +1\}^k)$. If*

$$k \geq \frac{16}{\varepsilon\sqrt{s}} + 16\log\left(\frac{2}{\delta}\right), \tag{1}$$

then with probability at least $1 - \delta$ there exist masks $\tilde{\boldsymbol{m}} \in \{0, 1\}^k$ and $\boldsymbol{M} \in \{0, 1\}^{k \times d}$ such that the function $g : \mathbb{R}^d \to \mathbb{R}$ defined by

$$g(\boldsymbol{x}) = (\tilde{\boldsymbol{m}} \odot \boldsymbol{u})^\mathsf{T} \sigma\left(\varepsilon(\boldsymbol{M} \odot \boldsymbol{B})\boldsymbol{x}\right), \tag{2}$$

satisfies

$$|g(\boldsymbol{x}) - \alpha x_i| \leq \varepsilon, \tag{3}$$

for all $\|\boldsymbol{x}\|_\infty \leq 1$. Furthermore, $\|\tilde{\boldsymbol{m}}\|_0 = \|\boldsymbol{M}\|_0 \leq \frac{2}{\varepsilon\sqrt{s}}$, and $\max_{1 \leq j \leq k} \|\boldsymbol{M}_{j,:}\|_0 \leq 1$.

Proof. If $|\alpha| \leq \varepsilon$ then taking $\boldsymbol{M} = \boldsymbol{0}$ yields the desired result. Suppose that $|\alpha| > \varepsilon$. Then there exists a $c_i \in \mathbb{N}$ such that

$$c_i\varepsilon \leq |\alpha| \leq (c_i + 1)\varepsilon \quad \text{and} \quad |c_i\varepsilon - |\alpha|| \leq \varepsilon. \tag{4}$$

Hence, it follows that

$$|c_i\varepsilon\,\mathrm{sgn}(\alpha)x_i - \alpha x_i| = |x_i||c_i\varepsilon - |\alpha|| \le \varepsilon, \tag{5}$$

where the final inequality follows from (4) and the hypothesis that $\|x\|_\infty \le 1$. Our goal now is to show that with probability $1 - \delta$ the random initialization of u and B yield masks $\tilde{m}$ and M such that $g(x) = c_i\varepsilon\,\mathrm{sgn}(\alpha)x_i$.

Now fix $i \in [d]$ and take $k' = \frac{k}{2}$. First, we consider the probability

$$P\left(|\{j \in [k'] : u_j = +1 \text{ and } B_{j,i} = \mathrm{sgn}(\alpha)\}| < c_i\right). \tag{6}$$

As u and $B_{:,i}$ are each sampled from a binomial distribution with k' trials, the distribution that the pair $(u_j, B_{j,i})$ is sampled from is a multinomial distribution with four possible events each having a probability of $1/4$. Since we are only interested in the event $(u_j, B_{j,i}) = (+1, \mathrm{sgn}(\alpha))$ occurring, we can instead consider a binomial distribution where $P((u_j, B_{j,i}) = (+1, \mathrm{sgn}(\alpha))) = \frac{1}{4}$ and $P((u_j, B_{j,i}) \ne (+1, \mathrm{sgn}(\alpha))) = \frac{3}{4}$. Hence, using Hoeffding's inequality we have that

$$P\left(|\{j \in [k'] : u_j = +1 \text{ and } B_{j,i} = \mathrm{sgn}(\alpha)\}| < c_i\right) \le \exp\left(-2k'\left(\frac{1}{4} - \frac{c_i}{k'}\right)^2\right) \tag{7}$$

$$= \exp\left(-\frac{1}{8}k' + c_i - 2\frac{c_i^2}{k'}\right) \tag{8}$$

$$< \exp\left(-\frac{1}{4}k' + 2c_i\right), \tag{9}$$

where the final inequality follows since $\exp()$ is an increasing function and $-2\frac{c_i^2}{k'} < 0$. From (4) and the fact that $|\alpha| \le \frac{1}{\sqrt{s}}$, it follows that

$$c_i \le \frac{1}{\varepsilon\sqrt{s}}. \tag{10}$$

Combining our hypothesis in (1) with (10) yields that

$$-\frac{1}{8}k' + c_i = -\frac{1}{16}k + c_i \le -\frac{1}{16}\left(\frac{16}{\varepsilon\sqrt{s}} + 16\log\left(\frac{2}{\delta}\right)\right) + \frac{1}{\varepsilon\sqrt{s}} = \log\left(\frac{\delta}{2}\right). \tag{11}$$

Substituting (11) into (9) yields

$$P\left(|\{j \in [k'] : u_j = +1 \text{ and } B_{j,i} = \mathrm{sgn}(\alpha)\}| < c_i\right) < \frac{\delta}{2}. \tag{12}$$

Additionally, it follows from the same argument that

$$P\left(|\{k' < j \le k : u_j = -1 \text{ and } B_{j,i} = -\mathrm{sgn}(\alpha)\}| < c_i\right) < \frac{\delta}{2}. \tag{13}$$

From (12) and (13) it follows with probability at least $1 - \delta$ that there exist sets $S_+ := \{j : u_j = +1 \text{ and } B_{j,i} = \mathrm{sgn}(\alpha)\}$ and $S_- := \{j : u_j = -1 \text{ and } B_{j,i} = -\mathrm{sgn}(\alpha)\}$ satisfying $|S_+| = |S_-| = c_i$ and $S_+ \cap S_- = \emptyset$. Using these sets, we define the components of the mask $\tilde{m}$ and M by

$$\tilde{m}_j = \begin{cases} 1 & : \quad j \in S_+ \cup S_- \\ 0 & : \quad \text{otherwise} \end{cases} \tag{14}$$

and

$$M_{j,\ell} = \begin{cases} 1 & : \quad j \in S_+ \cup S_- \text{ and } \ell = i \\ 0 & : \quad \text{otherwise} \end{cases}. \tag{15}$$

Using the definition of $g(x)$ in (2) we now have that

$$g(x) = \sum_{i \in S_+} \sigma\left(\varepsilon\,\mathrm{sgn}(\alpha)x_i\right) - \sum_{i \in S_-} \sigma\left(-\varepsilon\,\mathrm{sgn}(\alpha)x_i\right) \tag{16}$$

$$= c_i\sigma\left(\varepsilon\,\mathrm{sgn}(\alpha)x_i\right) - c_i\sigma\left(-\varepsilon\,\mathrm{sgn}(\alpha)x_i\right) \tag{17}$$

$$= c_i\varepsilon\,\mathrm{sgn}(\alpha)x_i, \tag{18}$$

where the final equality follows from the identity $\sigma(a) - \sigma(-a) = a$, for all $a \in \mathbb{R}$. This concludes the proof of (3).

Lastly, by our choice of $\tilde{m}$ in (14), M in (15), and (10), it follows that

$$\|\tilde{m}\|_0 = \|M\|_0 = 2c_i \le \frac{2}{\varepsilon\sqrt{s}}, \tag{19}$$

and

$$\max_{1 \le j \le k} \|M_{j,:}\|_0 \le 1, \tag{20}$$

which concludes the proof. $\qquad\square$

The next step is to consider an analogue for Lemma A.2 from (Malach et al., 2020) which we provide in Lemma 2.

Lemma 2. *Let $s \in [d]$, $w^* \in \left[-\frac{1}{\sqrt{s}}, \frac{1}{\sqrt{s}}\right]^d$ with $\|w^*\|_0 \le s$, and $\varepsilon, \delta > 0$ be given. Let $B \in \{-1, +1\}^{k \times d}$ be chosen randomly from $Bin(\{-1, 1\}^{k \times d})$ and $u \in \{-1, +1\}^k$ be chosen randomly from $Bin(\{-1, +1\}^k)$. If*

$$k \ge s \cdot \left\lceil \frac{16\sqrt{s}}{\varepsilon} + 16 \log\left(\frac{2s}{\delta}\right) \right\rceil, \tag{21}$$

then with probability at least $1 - \delta$ there exist masks $\tilde{m} \in \{0, 1\}^k$ and $M \in \{0, 1\}^{k \times d}$ such that the function $g : \mathbb{R}^d \to \mathbb{R}$ defined by

$$g(x) = (\tilde{m} \odot u)^\mathsf{T} \sigma\left(\varepsilon(M \odot B)x\right), \tag{22}$$

satisfies

$$|g(x) - \langle w^*, x \rangle| \le \varepsilon, \text{ for all } \|x\|_\infty \le 1. \tag{23}$$

Furthermore, $\|\tilde{m}\|_0 = \|M\|_0 \le \frac{2s\sqrt{s}}{\varepsilon}$ and $\max_{1 \le j \le k} \|M_{j,:}\|_0 \le 1$.

Proof. Assume $k = s \cdot \left\lceil \frac{16\sqrt{s}}{\varepsilon} + 16 \log\left(\frac{2s}{\delta}\right) \right\rceil$ and set $k' = \frac{k}{s}$. Note that if $k > s \cdot \left\lceil \frac{16\sqrt{s}}{\varepsilon} + 16 \log\left(\frac{2s}{\delta}\right) \right\rceil$ then the excess neurons can be masked yielding the desired value for k. We decompose u, $\tilde{m}$, B, and M into s equal size submatrices by defining

$$u^{(i)} := \begin{bmatrix} u_{k'(i-1)+1} & \cdots & u_{k'i} \end{bmatrix}^\mathsf{T} \in \{-1, +1\}^{k' \times 1} \tag{24}$$

$$\tilde{m}^{(i)} := \begin{bmatrix} \tilde{m}_{k'(i-1)+1} & \cdots & \tilde{m}_{k'i} \end{bmatrix}^\mathsf{T} \in \{0, 1\}^{k' \times 1} \tag{25}$$

$$B^{(i)} := \begin{bmatrix} b_{(k'(i-1)+1),1} & \cdots & b_{(k'(i-1)+1),d} \\ \vdots & \ddots & \vdots \\ b_{k'i,1} & \cdots & b_{k'i,d} \end{bmatrix} \in \{-1, +1\}^{k' \times d} \tag{26}$$

$$M^{(i)} := \begin{bmatrix} m_{(k'(i-1)+1),1} & \cdots & m_{(k'(i-1)+1),d} \\ \vdots & \ddots & \vdots \\ m_{k'i,1} & \cdots & m_{k'i,d} \end{bmatrix} \in \{0, 1\}^{k' \times d}, \tag{27}$$

for $i \in [s]$. Note that these submatrices satisfy

$$u = \begin{bmatrix} u^{(1)} \\ \vdots \\ u^{(s)} \end{bmatrix}, \ \tilde{m} = \begin{bmatrix} \tilde{m}^{(1)} \\ \vdots \\ \tilde{m}^{(s)} \end{bmatrix}, \ B = \begin{bmatrix} B^{(1)} \\ \vdots \\ B^{(s)} \end{bmatrix}, \ M = \begin{bmatrix} M^{(1)} \\ \vdots \\ M^{(s)} \end{bmatrix}. \tag{28}$$

Now let $\mathcal{I} := \{i \in [d] : w_i^* \ne 0\}$. By our hypothesis that $\|w^*\|_0 \le s$, it follows that $|\mathcal{I}| \le s$. WLOG, assume that $\mathcal{I} \subseteq [s]$. Now fix $i \in [s]$ and define $g_i : \mathbb{R}^d \to \mathbb{R}$ by

$$g_i(x) := \left(\tilde{m}^{(i)} \odot u^{(i)}\right)^\mathsf{T} \sigma\left(\varepsilon(M^{(i)} \odot B^{(i)})x\right) \tag{29}$$

By (21), taking $\varepsilon' = \frac{\varepsilon}{s}$ and $\delta' = \frac{\delta}{s}$ yields that $k' \geq \frac{16}{\varepsilon'\sqrt{s}} + 16 \log\left(\frac{2}{\delta'}\right)$. Hence, it follows from Lemma 1 that with probability at least $1 - \delta'$ there exist $\tilde{\boldsymbol{m}}^{(i)} \in \{0,1\}^{k'}$ and $\boldsymbol{M}^{(i)} \in \{0,1\}^{k' \times d}$ such that

$$|g_i(\boldsymbol{x}) - w_i^* x_i| \leq \varepsilon' = \frac{\varepsilon}{s}, \tag{30}$$

for every $\boldsymbol{x} \in \mathbb{R}^d$ with $\|\boldsymbol{x}\|_\infty \leq 1$, and

$$\|\tilde{\boldsymbol{m}}^{(i)}\|_0 = \|\boldsymbol{M}^{(i)}\|_0 \leq \frac{2}{\varepsilon'\sqrt{s}} = \frac{2\sqrt{s}}{\varepsilon} \quad \text{and} \quad \max_{k'(i-1)+1 \leq j \leq k'i} \|M_{j,i}^{(i)}\|_0 \leq 1. \tag{31}$$

By the definition of $g(\boldsymbol{x})$ in (22), using (28) yields

$$g(\boldsymbol{x}) = (\tilde{\boldsymbol{m}} \odot \boldsymbol{u})^\mathsf{T} \sigma\left(\varepsilon(\boldsymbol{M} \odot \boldsymbol{B})\boldsymbol{x}\right) = \sum_{i=1}^{s} \left(\tilde{\boldsymbol{m}}^{(i)} \odot \boldsymbol{u}^{(i)}\right)^\mathsf{T} \sigma\left(\varepsilon(\boldsymbol{M}^{(i)} \odot \boldsymbol{B}^{(i)})\boldsymbol{x}\right) = \sum_{i=1}^{s} g_i(\boldsymbol{x}). \tag{32}$$

Hence, combining (30) for all $i \in [s]$, it follows that with probability at least $1 - \delta$ we have

$$|g(\boldsymbol{x}) - \langle \boldsymbol{w}^*, \boldsymbol{x}\rangle| = \left|\sum_{i=1}^{s} g_i(\boldsymbol{x}) - \sum_{i=1}^{s} w_i^* x_i\right| \leq \sum_{i=1}^{s} |g_i(\boldsymbol{x}) - w_i^* x_i| \leq \varepsilon. \tag{33}$$

Finally, it follows from (28) and (31) that

$$\|\tilde{\boldsymbol{m}}\|_0 = \|\boldsymbol{M}\|_0 \leq \frac{2s\sqrt{s}}{\varepsilon} \quad \text{and} \quad \max_{1 \leq j \leq k} \|M_{j,:}\|_0 \leq 1, \tag{34}$$

which concludes the proof. $\square$

We now state and prove an analogue to Lemma A.5 in (Malach et al., 2020) which is the last lemma we will need to establish the desired result.

Lemma 3. *Let $s \in [d]$, $\boldsymbol{W}^* \in \left[-\frac{1}{\sqrt{s}}, \frac{1}{\sqrt{s}}\right]^{n \times d}$ with $\|\boldsymbol{W}^*\|_0 \leq s$, $F : \mathbb{R}^d \to \mathbb{R}^n$ defined by $F_i(\boldsymbol{x}) = \sigma(\langle \boldsymbol{w}_i^*, \boldsymbol{x}\rangle)$, and $\varepsilon, \delta > 0$ be given. Let $\boldsymbol{B} \in \{-1, +1\}^{k \times d}$ be chosen randomly from $Bin(\{-1,1\}^{k \times d})$ and $\boldsymbol{U} \in \{-1, +1\}^{k \times n}$ be chosen randomly from $Bin(\{-1,+1\}^{k \times n})$. If*

$$k \geq ns \cdot \left\lceil \frac{16\sqrt{ns}}{\varepsilon} + 16 \log\left(\frac{2ns}{\delta}\right)\right\rceil, \tag{35}$$

then with probability at least $1 - \delta$ there exist masks $\tilde{\boldsymbol{M}} \in \{0,1\}^{k \times n}$ and $\boldsymbol{M} \in \{0,1\}^{k \times d}$ such that the function $G : \mathbb{R}^d \to \mathbb{R}^n$ defined by

$$G(\boldsymbol{x}) = \sigma\left((\tilde{\boldsymbol{M}} \odot \boldsymbol{U})^\mathsf{T} \sigma\left(\varepsilon(\boldsymbol{M} \odot \boldsymbol{B})\boldsymbol{x}\right)\right), \tag{36}$$

satisfies

$$\|G(\boldsymbol{x}) - F(\boldsymbol{x})\|_2 \leq \varepsilon, \text{ for all } \|\boldsymbol{x}\|_\infty \leq 1. \tag{37}$$

Furthermore, $\|\tilde{\boldsymbol{M}}\|_0 = \|\boldsymbol{M}\|_0 \leq \frac{2ns\sqrt{ns}}{\varepsilon}$.

Proof. Assume $k = ns \cdot \left\lceil \frac{16\sqrt{ns}}{\varepsilon} + 16 \log\left(\frac{2ns}{\delta}\right)\right\rceil$ and set $k' = \frac{k}{n}$. Note that if $k > ns \cdot \left\lceil \frac{16\sqrt{ns}}{\varepsilon} + 16 \log\left(\frac{2ns}{\delta}\right)\right\rceil$ then excess neurons can be masked to yield the desired value for k. As in the proof of Lemma 2, we can split $\boldsymbol{U}$, $\tilde{\boldsymbol{M}}$, $\boldsymbol{B}$, and $\boldsymbol{M}$ into n submatrices, denoted $\boldsymbol{U}^{(i)} \in \{-1, +1\}^{k' \times n}$, $\tilde{\boldsymbol{M}}^{(i)} \in \{-1, +1\}^{k' \times n}$, $\boldsymbol{B}^{(i)} \in \{-1, +1\}^{k' \times d}$, and $\boldsymbol{M}^{(i)} \in \{-1, +1\}^{k' \times d}$ for $i \in [n]$, such that

$$\boldsymbol{U} = \begin{bmatrix} \boldsymbol{U}^{(1)} \\ \vdots \\ \boldsymbol{U}^{(n)} \end{bmatrix}, \quad \tilde{\boldsymbol{M}} = \begin{bmatrix} \tilde{\boldsymbol{M}}^{(1)} \\ \vdots \\ \tilde{\boldsymbol{M}}^{(n)} \end{bmatrix}, \quad \boldsymbol{B} = \begin{bmatrix} \boldsymbol{B}^{(1)} \\ \vdots \\ \boldsymbol{B}^{(n)} \end{bmatrix}, \quad \text{and } \boldsymbol{M} = \begin{bmatrix} \boldsymbol{M}^{(1)} \\ \vdots \\ \boldsymbol{M}^{(n)} \end{bmatrix}. \tag{38}$$

To simplify notation in the following definition, we define the vectors $\tilde{\boldsymbol{m}}^{(i)} := \tilde{\boldsymbol{M}}_{:,i}^{(i)}$ and $\tilde{\boldsymbol{u}}^{(i)} := \tilde{\boldsymbol{U}}_{:,i}^{(i)}$. Now we define the functions $g_i : \mathbb{R}^d \to \mathbb{R}$ by

$$g_i(\boldsymbol{x}) = \left(\tilde{\boldsymbol{m}}^{(i)} \odot \boldsymbol{u}^{(i)} \right)^{\mathsf{T}} \sigma \left(\beta (\boldsymbol{M}^{(i)} \odot \boldsymbol{B}^{(i)}) \boldsymbol{x} \right), \tag{39}$$

for each $i \in [n]$. Taking $\varepsilon' = \frac{\varepsilon}{\sqrt{n}}$ and $\delta' = \frac{\delta}{n}$, it follows from (35) that $k' \geq s \cdot \left\lceil \frac{16\sqrt{s}}{\varepsilon'} + 16 \log \left(\frac{2s}{\delta'} \right) \right\rceil$. As the hypotheses of Lemma 2 are satisfied, with probability at least $1 - \frac{\delta}{n}$ there exist masks $\tilde{\boldsymbol{m}}^{(i)}$ and $\boldsymbol{M}^{(i)}$ with

$$\|\tilde{\boldsymbol{m}}^{(i)}\|_0 = \|\boldsymbol{M}^{(i)}\|_0 \leq \frac{2s\sqrt{s}}{\varepsilon'} = \frac{2s\sqrt{ns}}{\varepsilon} \tag{40}$$

such that

$$|g_i(\boldsymbol{x}) - \langle \boldsymbol{W}_i^*, \boldsymbol{x} \rangle| \leq \frac{\varepsilon}{\sqrt{n}}, \text{ for all } \|\boldsymbol{x}\|_\infty \leq 1. \tag{41}$$

For each $i \in [n]$, note that this results in choosing the columns of the mask $\tilde{\boldsymbol{M}}^{(i)}$ by

$$\tilde{\boldsymbol{M}}_{:,\ell}^{(i)} = \begin{cases} \tilde{\boldsymbol{m}}^{(i)} & : \quad \ell = i \\ \boldsymbol{0} & : \quad \text{otherwise} \end{cases} \tag{42}$$

Combining this choice with (38) yields

$$(\tilde{\boldsymbol{M}} \odot \boldsymbol{U})^{\mathsf{T}} \sigma \left(\beta (\boldsymbol{M} \odot \boldsymbol{B}) \boldsymbol{x} \right) = \begin{bmatrix} g_1(\boldsymbol{x}) \\ \vdots \\ g_n(\boldsymbol{x}) \end{bmatrix}. \tag{43}$$

By the definition of $G(\boldsymbol{x})$ in (36), it follows from (43) that

$$G(\boldsymbol{x}) = \begin{bmatrix} \sigma(g_1(\boldsymbol{x})) \\ \vdots \\ \sigma(g_n(\boldsymbol{x})) \end{bmatrix}. \tag{44}$$

Combining (41) and (44), we have with probability at least $1 - \delta$ that

$$\|G(\boldsymbol{x}) - F(\boldsymbol{x})\|_2^2 = \sum_{i=1}^n \left(\sigma(g_i(\boldsymbol{x})) - \sigma(\langle \boldsymbol{w}_i^*, \boldsymbol{x} \rangle) \right)^2 \leq \sum_{i=1}^n \left(g_i(\boldsymbol{x}) - \langle \boldsymbol{W}_i^*, \boldsymbol{x} \rangle \right)^2 \leq \varepsilon^2. \tag{45}$$

Finally, it follows from (40) and (42) that

$$\|\tilde{\boldsymbol{M}}\|_0 = \|\boldsymbol{M}\|_0 \leq \frac{2ns\sqrt{ns}}{\varepsilon} \tag{46}$$

which concludes the proof. $\qquad\square$

We are now ready to prove the main result in Theorem 2.

Theorem 2. *Let $\ell, n, s \in \mathbb{N}$, $\boldsymbol{W}^{(1)*} \in \left[-\frac{1}{\sqrt{s}}, \frac{1}{\sqrt{s}} \right]^{d \times n}$, $\{\boldsymbol{W}^{(i)*}\}_{i=2}^{\ell-1} \in \left[-\frac{1}{\sqrt{n}}, \frac{1}{\sqrt{n}} \right]^{n \times n}$, and $\boldsymbol{W}^{(\ell)*} \in \left[-\frac{1}{\sqrt{n}}, \frac{1}{\sqrt{n}} \right]^{1 \times n}$. Assume that for each $i \in [\ell]$ we have $\|\boldsymbol{W}^{(i)*}\|_2 \leq 1$ and $\max_j \|\boldsymbol{W}_j^{(i)*}\|_0 \leq s$. Define $F(x) := F^{(\ell)} \circ \cdots \circ F^{(1)}(\boldsymbol{x})$ where $F^{(i)}(\boldsymbol{x}) = \sigma(\boldsymbol{W}^{(i)*}\boldsymbol{x})$ for $i \in [\ell-1]$ and $F^{(\ell)}(\boldsymbol{x}) = \boldsymbol{W}^{(\ell)*}\boldsymbol{x}$. Fix $\varepsilon, \delta \in (0,1)$.*

Let $\boldsymbol{B}^{(1)} \in \{-1,+1\}^{k \times d}$ be sampled from $Bin(\{-1,+1\}^{k \times d})$, $\{\boldsymbol{B}^{(i)}\}_{i=2}^{\ell} \in \{-1,+1\}^{k \times n}$ be sampled from $Bin(\{-1,+1\}^{k \times n})$, $\{\boldsymbol{U}^{(i)}\}_{i=1}^{\ell-1} \in \{-1,+1\}^{k \times n}$ be sampled from $Bin(\{-1,+1\}^{k \times n})$ and $\boldsymbol{U}^{(\ell)} \in \{-1,+1\}^{k \times 1}$ sampled from $Bin(\{-1,+1\}^{k \times 1})$. If

$$k \geq ns \cdot \left\lceil \frac{32\ell\sqrt{ns}}{\varepsilon} + 16 \log \left(\frac{2ns\ell}{\delta} \right) \right\rceil, \tag{47}$$

then with probability at least $1 - \delta$ there exist binary masks $\{\boldsymbol{M}^{(i)}\}_{i=1}^{\ell}$ and $\{\tilde{\boldsymbol{M}}^{(i)}\}_{i=1}^{\ell}$ for $\{\boldsymbol{B}^{(i)}\}_{i=1}^{\ell}$ and $\{\boldsymbol{U}^{(i)}\}_{i=1}^{\ell}$, respectively, such that the function $G : \mathbb{R}^d \to \mathbb{R}$ defined by

$$G(\boldsymbol{x}) := G^{(\ell)} \circ \cdots \circ G^{(1)}(\boldsymbol{x}), \tag{48}$$

where

$$G^{(i)}(\boldsymbol{x}) := \sigma\left((\tilde{\boldsymbol{M}}^{(i)} \odot \boldsymbol{U}^{(i)})^{\mathsf{T}} \sigma(\varepsilon(\boldsymbol{M}^{(i)} \odot \boldsymbol{B}^{(i)})\boldsymbol{x})\right), \textit{ for } i \in [\ell - 1] \tag{49}$$

$$G^{(\ell)}(\boldsymbol{x}) := (\tilde{\boldsymbol{M}}^{(i)} \odot \boldsymbol{U}^{(i)})^{\mathsf{T}} \sigma(\varepsilon(\boldsymbol{M}^{(i)} \odot \boldsymbol{B}^{(i)})\boldsymbol{x}), \tag{50}$$

satisfies

$$|G(\boldsymbol{x}) - F(\boldsymbol{x})| \leq \varepsilon, \textit{ for all } \|\boldsymbol{x}\|_2. \tag{51}$$

Additionally, $\|\tilde{\boldsymbol{M}}\|_0 = \|\boldsymbol{M}\|_0 \leq \frac{4ns\ell^2\sqrt{ns}}{\varepsilon}$.

Proof. Let $i \in [\ell - 1]$. Using Lemma 3 with $\varepsilon' = \frac{\varepsilon}{2\ell}$ and $\delta' = \frac{\delta}{\ell}$, with probability at least $1 - \frac{\delta}{\ell}$ there exist $\boldsymbol{M}^{(i)}$ and $\tilde{\boldsymbol{M}}^{(i)}$ such that

$$\|G^{(i)}(\boldsymbol{x}) - F^{(i)}(\boldsymbol{x})\|_2 \leq \frac{\varepsilon}{2\ell}, \textit{ for all } \|\boldsymbol{x}\|_\infty \leq 1 \tag{52}$$

and

$$\|\tilde{\boldsymbol{M}}^{(i)}\|_0 = \|\boldsymbol{M}^{(i)}\|_0 \leq \frac{2ns\sqrt{ns}}{\varepsilon'} = \frac{4ns\ell\sqrt{ns}}{\varepsilon}. \tag{53}$$

The remainder of the proof follows from applying the same argument as in the proof of Theorem A.6 from (Malach et al., 2020). $\square$

C   MOTIVATION FOR **BIPROP** (ALGORITHM 1)

Suppose that $f(\boldsymbol{x}; \boldsymbol{W}^*)$ with optimized weights $\boldsymbol{W}^*$ is a target network that we wish to approximate. Let $g(\boldsymbol{x}; \boldsymbol{W}_0)$ denote the network in which we want to identify a MPT-1/32 that is an ε-approximation of $f(\boldsymbol{x}; \boldsymbol{W}^*)$, for some $\varepsilon > 0$.

From theoretical analysis in (Malach et al., 2020; Pensia et al., 2020; Orseau et al., 2020) we know that if g is a sufficiently large network then there exists a binary mask $\boldsymbol{M}_0$ such that

$$|g(\boldsymbol{x}; \boldsymbol{M}_0 \odot \boldsymbol{W}_0) - f(\boldsymbol{x}; \boldsymbol{W}^*)| < \varepsilon. \tag{54}$$

Assuming that $g(\boldsymbol{x}; \cdot)$ is Lipschitz continuous with constant κ and letting $\boldsymbol{B}$ be binary parameters for g, it follows that

$$|g\left(\boldsymbol{x}; \alpha(\boldsymbol{M}_0 \odot \boldsymbol{B})\right) - f(\boldsymbol{x}; \boldsymbol{W}^*)| \leq |g\left(\boldsymbol{x}; \alpha(\boldsymbol{M}_0 \odot \boldsymbol{B}) - g(\boldsymbol{x}; \boldsymbol{M}_0 \odot \boldsymbol{B}_0)\right| + |g(\boldsymbol{x}; \boldsymbol{M}_0 \odot \boldsymbol{W}_0) - f(\boldsymbol{x}; \boldsymbol{W}^*)|$$
$$< \kappa\|(\boldsymbol{M}_0 \odot \boldsymbol{W}_0) - \alpha(\boldsymbol{M}_0 \odot \boldsymbol{B})\| + \varepsilon. \tag{55}$$

Hence, from (55) it follows that one approach for reducing the error for approximating $f(\boldsymbol{x}; \boldsymbol{W}^*)$ with the binarized subnetwork $g\left(\boldsymbol{x}; \alpha(\boldsymbol{M}_0 \odot \boldsymbol{B})\right)$ is to minimize the term $\|(\boldsymbol{M}_0 \odot \boldsymbol{W}_0) - \alpha(\boldsymbol{M}_0 \odot \boldsymbol{B})\|$ by choosing α and $\boldsymbol{B}$. As $\boldsymbol{M}_0$ is a fixed binary mask, we can determine a scaled binary approximation of $\boldsymbol{M}_0 \odot \boldsymbol{W}_0$ by solving the optimization problem

$$\begin{aligned} \min_{\alpha, \boldsymbol{B}} \quad & \|(\boldsymbol{M}_0 \odot \boldsymbol{W}_0) - \alpha(\boldsymbol{M}_0 \odot \boldsymbol{B})\|^2 \\ \text{s.t.} \quad & \alpha \in \mathbb{R}, \ \boldsymbol{B} \in \{-1, 1\}^n \end{aligned} \tag{56}$$

where $\boldsymbol{M}_0$, $\boldsymbol{W}_0$, and $\boldsymbol{B}$ are stacked into vectors of some length, say n. As the pruning mask $\boldsymbol{M}_0$ is applied to both $\boldsymbol{W}_0$ and $\boldsymbol{B}$, solving problem (56) is equivalent to solving problem (2) in (Rastegari et al., 2016) with a different dimension. Hence, it immediately follows that one closed form solution for $\boldsymbol{B}$ in problem (56) is

$$\boldsymbol{B}^* = \text{sgn}(\boldsymbol{W}_0). \tag{57}$$

Taking the derivative of the cost function in (56) with respect to α and setting it equal to zero yields

$$\alpha(\boldsymbol{M}_0 \odot \boldsymbol{B}^*)^{\mathsf{T}}(\boldsymbol{M}_0 \odot \boldsymbol{B}^*) - (\boldsymbol{M}_0 \odot \boldsymbol{W}_0)^{\mathsf{T}}(\boldsymbol{M}_0 \odot \boldsymbol{B}^*) = 0. \tag{58}$$

Recalling that $\boldsymbol{M}_0 \in \{0, 1\}^n$ and using (57), we have

$$(\boldsymbol{M}_0 \odot \boldsymbol{B}^*)^\mathsf{T}(\boldsymbol{M}_0 \odot \boldsymbol{B}^*) = \sum_{i=1}^n (M_{0i} B_i^*)^2 = \sum_{i=1}^n M_{0i}^2 (\mathrm{sgn}(W_{0i}))^2 = \sum_{i=1}^n M_{0i} = \|\boldsymbol{M}_0\|_1 \qquad (59)$$

and

$$(\boldsymbol{M}_0 \odot \boldsymbol{W}_0)^\mathsf{T}(\boldsymbol{M}_0 \odot \boldsymbol{B}^*) = \sum_{i=1}^n M_{0i}^2 W_{0i} \, \mathrm{sgn}(W_{0i}) = \sum_{i=1}^n M_{0i} |W_{0i}| = \|\boldsymbol{M}_0 \odot \boldsymbol{W}_0\|_1. \qquad (60)$$

Substituting (59) and (60) into (58) and solving for α yields the closed form solution

$$\alpha^* = \frac{\|\boldsymbol{M}_0 \odot \boldsymbol{W}_0\|_1}{\|\boldsymbol{M}_0\|_1}. \qquad (61)$$

Hence, α^* and $\boldsymbol{B}^*$ minimize the right hand side of (55) and, consequently, reduce the approximation error of the binarized subnetwork. So when the binarization error $\|(\boldsymbol{M}_0 \odot \boldsymbol{W}_0) - \alpha_0(\boldsymbol{M}_0 \odot \mathrm{sgn}(\boldsymbol{W}_0))\|$ is sufficiently small then the binarized subnetwork $g(\boldsymbol{x}; \alpha_0(\boldsymbol{M}_0 \odot \mathrm{sgn}(\boldsymbol{W}_0)))$ serves as a good approximation to the target network.

These closed form expressions for the gain term, α, and the binarized weights, $\mathrm{sgn}(\boldsymbol{W}_0)$, are the updates used for the gain term and binary weights in **biprop** when updating the binary mask used to prune network parameters.

D   COMPARISON OF MPTS WITH BINARY NEURAL NETWORK SOTA

Here we provide a more exhaustive comparison of MPT–1/32 and MPT–1/1 to SOTA methods on CIFAR-10 and ImageNet (Courbariaux et al., 2015; 2016; Zhou et al., 2016b; Zhang et al., 2018; Rastegari et al., 2016; Lin et al., 2017; Qin et al., 2020b; Mishra et al., 2017). Results for CIFAR-10 can be found in Tables 5 and 6 and results for ImageNet can be found in Tables 7 and 8.

Method	Model	Top-1	Params
BinaryConnect	VGG-Small	91.7	4.6 M
BWN	VGG-Small	90.1	4.6 M
DoReFa-Net	ResNet-20	90.0	0.27 M
LQ-Nets	ResNet-20	90.1	0.27 M
LAB	VGG-Small	89.5	4.6 M
ProxQuant	ResNet-56	92.3	0.85 M
DSQ	ResNet-20	90.2	0.27 M
IR-Net	ResNet-20	90.2	0.27 M
MPT-1/32 (Ours)	VGG-Small (95)	90.58	0.23 M
MPT-1/32 (Ours)	**ResNet-18 (80)**	**94.15**	**2.2 M**
Full-Precision	ResNet-18	93.02	11.2 M

Table 5: Comparison of Untrained MPT-1/32 with Trained Binary (1/32) Networks on CIFAR-10

Method	Model	Top-1	Params
BNN	VGG-Small	89.9	4.6 M
XNOR-Net	VGG-Small	89.8	4.6 M
DoReFa-Net	ResNet-20	79.3	0.27 M
BBG	ResNet-20	85.3	0.27 M
LAB	VGG-Small	87.7	4.6 M
DSQ	**VGG-Small**	**91.7**	**4.6 M**
IR-Net	VGG-Small	90.4	4.6 M
MPT-1/1 (Ours)	VGG-Small (2x, 60)	88.22	3.68 M
Full-Precision	VGG-Small	93.6	4.6 M

Table 6: Comparison of Untrained MPT-1/1 with Trained Binary (1/1) Networks on CIFAR-10

E   RELATED WORK

E.1   PRUNING

We categorize pruning methods based on whether a model is pruned either after the training or before the training (see (Neill, 2020b) for a comprehensive review).

Post-Training Pruning.   The traditional pruning methods leverage a three-stage pipeline – pre-training (a large model), pruning, and fine-tuning. The main distinction lies among these approaches is what type of criteria is used for pruning. One of the most popular approach is the magnitude-based pruning where the weights with the magnitude

Method	Model	Top-1	Params
ABC-Net	ResNet-18	62.8	11.2 M
BWN	ResNet-18	60.8	11.2 M
BWNH	ResNet-18	64.3	11.2 M
PACT	ResNet-18	65.8	11.2 M
IR-Net	ResNet-34	70.4	21.8 M
Quantization-Networks	ResNet-18	66.5	11.2 M
Quantization-Networks	ResNet-50	72.8	25.6 M
MPT-1/32 (Ours)	WRN-34 (80)	68.88	9.6 M
MPT-1/32 (Ours)	**WRN-50 (70)**	**73.3**	**20.6 M**
Full-Precision	ResNet-34	73.27	21.8 M

Table 7: Comparison of Untrained MPT-1/32 with Trained Binary (1/32) Networks on ImageNet

Method	Model	Top-1	Num. Params
BNN	AlexNet	27.9	62.3 M
XNOR-Net	AlexNet	44.2	62.3 M
ABC-Net	ResNet-18	42.7	11.2 M
ABC-Net	ResNet-34	52.4	21.8 M
TSQ	AlexNet	58.0	62.3 M
WRPN	ResNet-34	60.5	21.8 M
HWGQ	AlexNet	52.7	62.3 M
IR-Net	ResNet-18	58.1	11.2 M
IR-Net	**ResNet-34**	**66.5**	**21.8 M**
MPT-1/1 (Ours)	WRN-34 (50)	38.98	24.1 M
Full-Precision	ResNet-34	73.27	21.8 M

Table 8: Comparison of Untrained MPT-1/1 with Trained Binary (1/1) Networks on ImageNet

below a certain threshold are discarded (Hagiwara, 1993). Further, certain penalty term (e.g., l_1, l_2 or lasso weight regularization) can be used during training to encourage a model to learn certain smaller magnitude weights and removing them post-training (Weigend et al., 1991). Models can also be pruned by measuring the importance of weights by computing the sensitivity of the loss function when weights are removed and prune those which cause the smallest change in the loss (LeCun et al., 1990).

Pruning Before Training.   Thus far, we have have discussed methods for pruning pretrained DNNs.

Recently, (Frankle & Carbin, 2018) proposed the *Lottery Ticket Hypothesis* and showed that randomly-initialized neural networks contain sparse subnetworks that can be effectively trained from scratch when reset to their initialization. Further, (Liu et al., 2018b) showed that the training an over-parameterized model is often not necessary to obtain an efficient final model and network architecture itself is more important than the remaining weights after pruning pretrained networks. These findings has revived interest in finding approaches for searching sparse and trainable subnetworks. For example, (Lee et al., 2018; Wang et al., 2020b; You et al., 2019; Wang et al., 2020a) explored efficient approaches to search for these sparse and trainable subnetworks. Along this line of work, a striking finding was reported by (Zhou et al., 2019; Ramanujan et al., 2019) showing that randomly-initialized neural networks contain sparse subnetworks that achieve good performance without any training. (Malach et al., 2020; Pensia et al., 2020) provided theoretical evidences for this phenomenon and showed that one can approximate any target neural network, by pruning a sufficiently over-parameterized network of random weights.

E.2   BINARIZATION

Similar to pruning, we categorize binarization methods based on whether a model is binarized either after the training or during the training (see (Qin et al., 2020a) for a comprehensive review).

Post-Training Binarization.   To the best of our knowledge, none of the post-training schemes have been successful in binarizing pretrained models with or without retraining to achieve reasonable test accuracy. Most existing works (Han et al., 2015; Zhou et al., 2017) are limited to ternary weight quantization.

Training-Aware Binarization.   There are several efforts to improve the performance of binary neural network training. This is a challenging problem as binarization introduces discontinuities which makes differentiation during back-propogation difficult. Binaryconnect (Courbariaux et al., 2015) established how to train networks with binary weights within the familiar back-propagation paradigm. BinaryNet (Courbariaux et al., 2016) further quantize both the weights and the activations to 1-bit values. Unfortunately, these early schemes resulted in a staggering drop in the accuracy compared to their full precision counterparts. In an attempt to improve the performance, XNOR-Net (Rastegari et al., 2016) proposed to add a real-valued channel-wise scaling factor. Dorefa-Net (Zhou et al., 2016a) extends XNOR-Net to accelerate the training process using quantized gradients. ABC-Net (Lin et al., 2017) improved the performance by using more weight bases and activation bases at the cost of increase in memory and computation. There have also been efforts in making modifications to the network architectures to make them amenable for the binary neural network

training. For example, Bireal-Net (Liu et al., 2018a) added layer-wise identity short-cut, and AutoBNN (Shen et al., 2020) proposed to widen or squeeze the channels in an automatic manner. Han et al. proposed to learn to binarize neurons with noisy supervision. Some efforts also have been carried out to designing gradient estimators extending straight-through estimator (STE) (Bengio et al., 2013) for accurate gradient back-propagation. DSQ (Gong et al., 2019) used differentiable soft quantization to have accurate gradients in backward propagation. On the other hand, PCNN Gu et al. (2019) proposed a new discrete back-propagation via projection algorithm to build BNNs.

E.3 OTHER RELATED DIRECTIONS

Gaier & Ha (2019) proposed a search method for neural network architectures that can already perform a task without any explicit weight training, i.e., each weight in the network has the same shared value. Recent work in randomly wired neural networks (Xie et al., 2019) showed that constructing neural networks with random graph algorithms often outperforms a manually engineered architecture. As opposed to fixed wirings in (Xie et al., 2019), (Wortsman et al., 2019) learned the network parameters as well as the structure. This show that finding a good architecture is akin to finding a sparse subnetwork of the complete graph.