GARNET: A Spectral Approach to Robust and Scalable Graph Neural Networks

Abstract

Graph neural networks (GNNs) have been increasingly deployed in various applications that involve learning on non-Euclidean data. However, recent studies show that GNNs are vulnerable to graph adversarial attacks. Although there are several defense methods to improve GNN adversarial robustness, they fail to perform well on low homophily graphs. In addition, few of those defense models can scale to large graphs due to their high computational complexity and memory usage. In this paper, we propose GARNET, a scalable spectral method to boost the adversarial robustness of GNN models for both homophilic and heterophilic graphs. GARNET first computes a reduced-rank yet sparse approximation of the adversarial graph by exploiting an efficient spectral graph embedding and sparsification scheme. Next, GARNET trains an adaptive graph filter on the reduced-rank graph for node representation refinement, which is subsequently leveraged to guide label propagation for further enhancing the quality of node embeddings. GARNET has been evaluated on both homophilic and heterophilic datasets, including a large graph with millions of nodes. Our extensive experiment results show that GARNET increases adversarial accuracy over state-of-the-art GNN (defense) models by up to 9.96% and 15.17% on homophilic and heterophilic graphs, respectively.

1 Introduction

Recent years have witnessed a surge of interest in graph neural networks (GNNs), which incorporate both graph structure and node/edge attributes to produce low-dimensional embedding vectors that maximally preserve graph structural information (Hamilton, 2020). GNNs have achieved promising results in various real-world applications, such as recommendation systems (Ying et al., 2018), self-driving car (Casas et al., 2020), protein structure predictions (Senior et al., 2020), and chip placements (Mirhoseini et al., 2021). However, recent studies have shown that adversarial attacks on graph structure accomplished by inserting, deleting, or rewiring edges in an unnoticeable way, can easily fool GNN models and drastically degrade their accuracy in downstream tasks (e.g., node classification) (Zügner et al., 2018; Zügner & Günnemann, 2019).

In literature, there are several attempts to defend GNNs against graph adversarial attacks. Entezari et al. (2020) first observed that graph adversarial attacks mainly affect high-rank properties of the graph; consequently, a low-rank graph should be first constructed by performing truncated singular value decomposition (SVD) on the graph adjacency matrix, which can then be exploited for training a robust GNN model. Later, Jin et al. (2020) proposed Pro-GNN to jointly learn a new graph and its robust GNN model with the low-rank constraints imposed by the graph structure. However, such low-rank approximation methods involve dense adjacency matrices during the GNN training stage, which will lead to quadratic time and space complexity, prohibiting their applications in large-scale graph learning tasks. Another line of research aims at enhancing GNN robustness based on the graph homophily assumption, i.e., adjacent nodes in a natural graph tend to have similar attributes, while the graph attacks essentially insert adversarial edges by connecting nodes with dissimilar attributes. As a result, researchers proposed to compute attribute similarity scores between adjacent nodes as edge weights, and drop edges with small weights to increase graph homophily (Wu et al., 2019; Zhang & Zitnik, 2020). Although such approaches can successfully improve GNN robustness on high-homophily graphs, they may fail on low-homophily (i.e., heterophily) graphs (Zhu et al., 2020).

In this paper, we propose GARNET, a spectral method for constructing GNN models that are robust to graph adversarial attacks for both homophilic and heterophilic graphs. In addition, GARNET scales comfortably to large graphs due to its nearly-linear algorithm complexity. More concretely, GARNET consists of three major kernels: (1) reduced-rank approximation, (2) adaptive filter learning, and (3) adaptive label propagation. The reduced-rank approximation kernel first performs truncated SVD on graph adjacency matrix to obtain a few dominant singular values and their corresponding singular vectors that are further leveraged to construct a sparse yet reduced-rank graph adjacency matrix; the reduced-rank adjacency matrix can effectively mitigate the effects of adversarial attacks via connecting (disconnecting) nodes that are spectrally similar (dissimilar). The adaptive filter learning kernel aims to learn a polynomial graph filter whose coefficients are trainable; the learned graph filter can adapt to the homophilic/heterophilic properties of the underlying graph and thus will work effectively for both homophilic and heterophilic graphs. The adaptive label propagation stage will leverage the learned adaptive graph filter to guide the label propagation phase, which can further improve the adversarial accuracy by enhancing the quality of node representations.

We evaluate the proposed GARNET model on three high-homophily datasets: Cora, Citeseer, and Pubmed as well as two low-homophily datasets: Chameleon and Squirrel, under strong graph adversarial attacks such as Nettack (Zügner et al., 2018) and Metattack (Zügner & Günnemann, 2019) with various perturbation settings. Moreover, we further show the nearly-linear scalability of our approach on the ogbn-products dataset that consists of millions of nodes (Hu et al., 2020). Our experimental results indicate that GARNET largely improves adversarial accuracy over baselines in most cases. The major advantages of GARNET are summarized as follows:

- **GARNET is robust to graph adversarial attacks.** Exploiting the proposed reduced-rank approximation scheme allows GARNET to effectively filter out the noises potentially caused by adversarial attacks in the spectral domain. This immediately leads to substantial improvement (up to 15.17%) of adversarial accuracy when comparing with the state-of-the-art baselines under the strong graph attacks on various datasets.
- **GARNET is agnostic to graph homophily.** Unlike most existing defense models that do not work well on low-homophily adversarial graphs, GARNET leverages a trainable graph filter that can adapt to adversarial graphs with diverse levels of homophily. In addition, we theoretically demonstrate that the performance of the adaptive graph filter applied to an adversarial graph will be similar to the performance achieved on a clean graph.
- **GARNET is scalable to large graphs.** GARNET has a nearly-linear runtime/space complexity and thus can scale comfortably to very large graph data sets with millions of nodes. We have conducted experiments on the ogbn-products dataset that contains 2 million nodes and 60 million edges, which is over $100\times$ larger than the largest adversarial graph ever considered in the prior arts.

2 RELATED WORK

GNNs have received an increasing amount of attention in recent years due to its ability of learning on non-Euclidean (graph) data. In contrast to developing powerful GNN models on natural graph data, there is an active body of research focusing on adversarial attacks as well as defenses for GNNs. We summarize some of the recent efforts for graph adversarial attacks and defenses as follows.

Graph adversarial attacks aim at degrading the accuracy of GNN models by perturbing the graph structure in an unnoticeable way. For instance, most existing graph adversarial attacks insert/delete edges while maintaining node degree distribution (Sun et al., 2018). The most popular graph adversarial attacks fall into the following two categories: (1) targeted attack, (2) untargeted attack. The targeted attacks attempt to mislead a GNN model to produce a wrong prediction on a target sample (e.g., node), while the untargeted attacks strive to degrade the overall accuracy of a GNN model for the whole graph data set. Dai et al. (2018) first formulate the targeted attack as a combinatorial optimization problem and leverages reinforcement learning to insert/delete edges such that the target node is misclassified. Zügner et al. (2018) propose another targeted attack called Nettack, which produces an adversarial graph by maximizing the training loss of GNNs. Zügner & Günnemann (2019) further introduce Metattack, an untargeted attack that treats the graph as a hyperparameter and uses meta-gradients to perturb the graph structure. It is worth noting that graph adversarial attacks have two different settings: poison (perturb a graph prior to GNN training) and evasion (perturb a graph after GNN training). As shown by Zhu et al. (2021), the poison setting is typically

more challenging to defend, as it changes graph structure that fools GNN training. Thus, in this work, we evaluate our model against both targeted and untargeted attacks under the poison setting.

Graph adversarial defenses attempt to enhance GNN performance on the perturbed graphs generated by adversarial attacks. Entezari et al. (2020) first observe that Nettack, a strong targeted attack, only changes the high-rank information of the adjacency matrix after graph perturbation. Thus, they propose to construct a low-rank graph by performing truncated SVD to undermine the effects of adversarial attacks. Jin et al. (2020) propose Pro-GNN that adopts a similar idea yet jointly learns the low-rank graph and GNN model. However, such low-rank approximation based methods produce dense adjacency matrices that correspond to complete graphs, which would limit their applications for large graphs. Another line of research strives to purify the adversarial graph by assigning edge weights. Specifically, Wu et al. (2019) propose to modify the edge weights by computing the Jaccard similarity score per edge based on node attributes, which is followed by Zhang & Zitnik (2020) that propose GNNGuard to learn node attribute similarity score per edge through a trainable linear layer. Nonetheless, such approaches assume that nearby nodes should have similar attributes (i.e., graph homophily assumption), which is not valid for heterophilic graphs that have adjacent nodes with dissimilar attributes (Zhu et al., 2020). In contrast to the prior arts, GARNET achieves highly robust yet scalable performance on both homophilic and heterophilic graphs under adversarial attacks by leveraging novel reduced-rank approximation and adaptive graph filtering schemes.

3 OUR APPROACH

Figure 1 gives an overview of our proposed approach, GARNET, which consists of three major phases. The first phase (reduced-rank approximation) constructs a reduced-rank yet sparse graph model by exploiting scalable truncated SVD and nearest-neighbor graph algorithms (Baglama & Reichel, 2005; Malkov & Yashunin, 2018). The second phase (adaptive filter learning) is the only phase that involves training, which outputs a learned graph filter that can adapt to the homophilic/heterophilic properties of the underlying graph. The last phase (adaptive label propagation) leverages the learned adaptive graph filter to guide the subsequent label propagation process. In the rest of this section, we will describe each of these three phases in more detail.

Figure 1: An overview of the three major phases of GARNET.

3.1 REDUCED-RANK APPROXIMATION (PHASE 1)

The adjacency matrices of many real-world graphs (e.g., social network and biological network) are naturally low rank and sparse, as the nodes typically tend to form communities and have a small number of neighbors (Zhou et al., 2013). As a result, graph adversarial attacks can be viewed as compromising these properties by inserting edges that connect nodes from different communities (Zügner et al., 2018; Zügner & Günnemann, 2019). Recently, Entezari et al. (2020) and Jin et al. (2020) have shown that the well-known graph adversarial attacks (e.g., Nettack and Metattack) are essentially high-rank attacks, which mainly change the high-rank spectrum of the graph when perturbing the graph structure, while the low-rank spectrum remains almost the same. We empirically confirm that the graph rank indeed increases under adversarial attacks in Appendix A.7.

Consequently, a natural way for improving GNN robustness is to purify an adversarial graph by eliminating the high-rank components of its spectrum.

To enhance GNN robustness, Entezari et al. (2020) and Jin et al. (2020) reconstruct a graph that only preserves the low-rank components of its spectrum to mitigate the effects of adversarial attacks, via performing truncated SVD on the adjacency matrix. Specifically, given a graph adjacency matrix $\boldsymbol{A} \in \mathbb{R}^{n \times n}$, the rank-$r$ approximated adjacency matrix can be obtained via truncated SVD: $\hat{\boldsymbol{A}} = \boldsymbol{U}\Sigma\boldsymbol{V}^T$, where $\Sigma \in \mathbb{R}^{r \times r}$ is a diagonal matrix consisting of r largest singular values of $\boldsymbol{A}$. $\boldsymbol{U} \in \mathbb{R}^{n \times r}$ and $\boldsymbol{V} \in \mathbb{R}^{n \times r}$ contain the corresponding left and right singular vectors, respectively.

However, the reconstructed low-rank adjacency matrix $\hat{\boldsymbol{A}}$ is typically a dense matrix with $O(n^2)$ nonzero elements, which may result in prohibitively expensive storage as well as GNN training, where n represents number of nodes (Entezari et al., 2020; Jin et al., 2020). Thus, existing low-rank approximation methods are not scalable to large graphs.

Reduced-rank approximation via sparsification. To avoid the quadratic space complexity for obtaining $\hat{\boldsymbol{A}}$, one simple solution is to sparsify $\hat{\boldsymbol{A}}$ on the fly. More concretely, instead of directly computing $\hat{\boldsymbol{A}} = \boldsymbol{U}\Sigma\boldsymbol{V}^T$, we can compute $\hat{\boldsymbol{A}}$ row by row: $\hat{\boldsymbol{A}}_{i,:} = \boldsymbol{U}_{i,:}\Sigma\boldsymbol{V}^T$. Once we obtain $\hat{\boldsymbol{A}}_{i,:}$, we can sparsify it by setting $\tilde{\boldsymbol{A}}_{i,j} = 0$ if $\hat{\boldsymbol{A}}_{i,j} < \delta$ and $\tilde{\boldsymbol{A}}_{i,j} = \hat{\boldsymbol{A}}_{i,j}$ otherwise, where δ is a hyperparameter to control the sparsity. In this way, we only need to store a dense vector $\hat{\boldsymbol{A}}_{i,:}$ at a time and the final adjacency matrix $\tilde{\boldsymbol{A}}$ is sparse. Although the space complexity is reduced to $O(m)$, where m denotes the number of non-zero elements in $\tilde{\boldsymbol{A}}$, this sparsification method still has quadratic time complexity for computing $\tilde{\boldsymbol{A}}$. To tackle this issue, in this work a nearly-linear complexity algorithm for constructing a reduced-rank yet sparse matrix $\tilde{\boldsymbol{A}}$ is proposed by exploiting the following connection between matrix sparsification and spectral graph embedding.

Definition 1. *Given the top r smallest eigenvalues $\lambda_1, \lambda_2, ..., \lambda_r$ and their corresponding eigenvectors $\boldsymbol{v}_1, \boldsymbol{v}_2, ..., \boldsymbol{v}_r$ of normalized graph Laplacian matrix $\boldsymbol{L}_{norm} = \boldsymbol{I} - \boldsymbol{D}^{-\frac{1}{2}}\boldsymbol{A}\boldsymbol{D}^{-\frac{1}{2}}$, where $\boldsymbol{I}$ and $\boldsymbol{A}$ are the identity matrix and graph adjacency matrix, respectively, and $\boldsymbol{D}$ is a diagonal matrix of node degrees, the **weighted spectral embedding matrix** is defined as:*

$$\boldsymbol{V} \stackrel{\text{def}}{=} \left[\sqrt{|1 - \lambda_1|}\boldsymbol{v}_1, ..., \sqrt{|1 - \lambda_r|}\boldsymbol{v}_r \right], \tag{1}$$

*whose i-th row $\boldsymbol{V}_{i,:}$ is the **weighted spectral embedding** of the corresponding i-th node in the graph.*

Theorem 1. *Given a normalized graph adjacency matrix $\boldsymbol{A}_{norm} = \boldsymbol{D}^{-\frac{1}{2}}\boldsymbol{A}\boldsymbol{D}^{-\frac{1}{2}}$ of an undirected graph, let $\hat{\boldsymbol{A}}$ be the rank-r approximation of $\boldsymbol{A}_{norm}$ via truncated SVD. If the top r dominant eigenvalues of $\boldsymbol{A}_{norm}$ are non-negative, then $\hat{\boldsymbol{A}}_{i,j}$ corresponds to the dot product score between the weighted spectral embeddings of node i and j.*

Theorem 1 indicates that the reduced-rank approximation of the normalized adjacency matrix via truncated SVD captures the spectral similarity between nodes, which motivates us to leverage weighted spectral embeddings to capture graph spectral (low-rank) information, thereby identifying edges to be pruned (sparsified) from the graph. Unlike traditional spectral graph embedding methods that utilize the first r Laplacian eigenpairs to construct spectral embedding matrix, we exploit the top r largest singular values and their singular vectors of $\boldsymbol{A}_{norm}$ that may include both the smallest and largest Laplacian eigenpairs for capturing global and local structural information, respectively (Shuman et al., 2013). More specifically, given a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$ and its normalized adjacency matrix $\boldsymbol{A}_{norm}$, our approach first computes the r largest singular values (e.g., $r = 50$) and the corresponding singular vectors of $\boldsymbol{A}_{norm}$ leveraging efficient eigensolvers in $O(r|\mathcal{E}|)$ time to construct the weighted spectral embeddings (Baglama & Reichel, 2005); next, the embedding results are then used to construct a nearest neighbor (NN) graph, where each node will be connected to its k most spectrally similar nodes. Afterwards, we compute the dot product similarity scores between adjacent nodes in the NN graph. If the similarity score is less than a threshold δ, we prune the corresponding edge from the NN graph to further sparsify the graph. In this work, we exploit an approximate k-nearest neighbor algorithm for constructing the NN graph, which has $O(|\mathcal{V}| \log |\mathcal{V}|)$ complexity and thus can scale to very large graphs (Malkov & Yashunin, 2018). We say a graph is a reduced-rank graph if its adjacency matrix is obtained via the proposed reduced-rank approximation method. As a result, we can obtain a reduced-rank and sparse graph in $O(r|\mathcal{E}| + |\mathcal{V}| \log |\mathcal{V}|)$ time. We empirically verify that the reduced-rank graphs can effectively remove the high-rank adversarial properties in Appendix A.8.

3.2 Adaptive Filter Learning (Phase 2)

Most existing GNN defense models (implicitly) assume the underlying graph is homophilic, implying that nearby nodes will share similar attributes; however, this assumption is not valid for heterophilic graphs in which adjacent nodes may have dissimilar attributes (Ma et al., 2021). As a consequence, existing defense methods may not be robust against graph adversarial attacks on heterophilic graphs. To address this limitation, we adopt the concept of learning a polynomial graph filter that can adapt to graph homo/heterophily (NT et al., 2020; Chien et al., 2021), and apply it on the adversarial graphs. Specifically, given a graph and its node attribute matrix $\boldsymbol{X}$, our graph filter learning process works as follows:

$$\hat{\boldsymbol{X}} = MLP(\boldsymbol{X}) \tag{2}$$

$$\boldsymbol{Z} = softmax(\sum_{p=0}^{P} c_p \boldsymbol{F}^p \hat{\boldsymbol{X}}) \tag{3}$$

where $\boldsymbol{F}$ can be either a normalized adjacency matrix $\boldsymbol{A}_{norm} = \boldsymbol{D}^{-\frac{1}{2}} \boldsymbol{A} \boldsymbol{D}^{-\frac{1}{2}}$ or normalized Laplacian matrix $\boldsymbol{L}_{norm} = \boldsymbol{I} - \boldsymbol{A}_{norm}$, $c_0, c_1, ..., c_P$ are $P+1$ learnable polynomial coefficients. We use the output node embedding matrix $\boldsymbol{Z}$ and node training labels to calculate training loss. The weights of MLP as well as learnable polynomial coefficients are then updated via backpropagation.

Next, we are going to show that the learnable coefficients $c_0, c_1, ..., c_P$ enable the polynomial graph filter $g_P(\boldsymbol{F}) = \sum_{p=0}^{P} c_p \boldsymbol{F}^p$ in Equation 3 to adapt to a homo/heterophilic graph.

Lemma 1 (Chien et al. (2021)). *Assume the graph $\mathcal{G}$ is connected and $|c_p| \leq 1 \ \forall p \in \{0, 1, ..., P\}$. Let $\boldsymbol{F}$ to be the normalized adjacency matrix $\boldsymbol{F} = \boldsymbol{D}^{-\frac{1}{2}} \boldsymbol{A} \boldsymbol{D}^{-\frac{1}{2}}$. If $c_p \geq 0 \ \forall p \in \{0, 1, ..., P\}$, $\sum_{p=0}^{P} c_p = 1$, and $\exists p' > 0$ such that $c_{p'} > 0$, then $g_p(\boldsymbol{F})$ is a low-pass filter. Also, if $c_p = (-\alpha)^k, \alpha \in (0, 1)$ and P is large enough, then $g_p(\boldsymbol{F})$ is a high-pass filter.*

Intuitively, Lemma 1 indicates that for a homophilic graph the filter coefficients tend to be positive, whereas for a heterophilic graph both positive and negative coefficients can be observed. Consequently, $g_P(\boldsymbol{F})$ can be learned to serve as a low-pass (high-pass) graph filter to filter node intermediate embeddings $\hat{\boldsymbol{X}}$ over the homophilic (heterophilic) graph, such that nearby nodes will have similar (dissimilar) output embeddings. Thus, a natural idea for developing a robust GNN model on both homophilic and heterophilic graphs is to exploit both the reduced-rank graph in Section 3.1 and the aforementioned adaptive polynomial graph filter.

However, adaptive polynomial graph filters typically perform well on clean graphs that are entirely homophilic or heterophilic, while the adversarial graphs can be globally homophilic yet locally heterophilic (Zhu et al., 2021). Another important question is whether the polynomial filters can still be effective when combined with reduced-rank approximation of the adversarial graph. Next, we answer this question by showing the upper bound of the performance difference between the polynomial graph filter on a clean graph and that on the corresponding reduced-rank graph.

Theorem 2. *Let $\boldsymbol{A}_{clean}$, $\boldsymbol{A}_{adv}$, and $\boldsymbol{A}_r$ represent the normalized adjacency matrices of a clean graph, the corresponding adversarial graph, and the rank-r approximated adversarial graph, respectively. Also let σ_{r+1} denote the $(r+1)$-th largest singular value of $\boldsymbol{A}_{adv}$. Assume the spectral norm of graph adversarial perturbation is upper bounded by a constant ϵ, i.e., $\|\boldsymbol{A}_{clean} - \boldsymbol{A}_{adv}\|_2 \leq \epsilon$. Given a polynomial graph filter $g_P(\boldsymbol{F}) = \sum_{p=0}^{P} c_p \boldsymbol{F}^p$ with $|c_p| \leq 1$, we have:*

$$\|g_P(\boldsymbol{A}_{clean}) - g_P(\boldsymbol{A}_r)\|_2 \leq \frac{1}{2}(P^2 + P)(\epsilon + \sigma_{r+1}) \tag{4}$$

Note that the graph attacking algorithms are typically designed to perturb the graph structure in an unnoticeable way, which means that ϵ is a small value. Moreover, σ_{r+1} is within the range of $[0, 1]$ since $\boldsymbol{A}_{adv}$ is normalized. We further set $P \leq 10$ when learning the adaptive filter to further tighten the upper bound. As a result, Theorem 2 indicates that the performance of a polynomial filter on the reduced-rank graph will be similar to its performance on the clean graph. Hence, applying the adaptive graph filter on the reduced-rank graph constructed in Section 3.1 allows GARNET to work effectively for both homophilic and heterophilic graphs under adversarial attacks.

Scalability of adaptive filter learning. To scale the adaptive filter learning process to large graphs, we do not explicitly form the graph filter $g_P(\boldsymbol{F}) = \sum_{p=0}^{P} c_p \boldsymbol{F}^p$. Instead, we iteratively left-multiply $\hat{\boldsymbol{X}}$ by $\boldsymbol{F}$ in Equation 3 to leverage the sparsity of $\boldsymbol{F}$. Thus, the time complexity is linear to the

graph size. Besides, we can effectively exploit model parallelism (Castelló et al., 2019) , where the computation of a graph filter $g_P(\boldsymbol{F})$ is distributed onto multiple GPUs based on the index p that indicates the p-th term in $g_P(\boldsymbol{F})$. This way, we can dramatically reduce the memory usage per GPU, thereby allowing the adaptive filter learning process to scale to large graphs with millions of nodes.

3.3 ADAPTIVE LABEL PROPAGATION (PHASE 3)

Once the trained graph filter $g_P^*(\boldsymbol{F}) = \sum_{p=0}^{P} c_p^* \boldsymbol{F}^p$ is obtained, we further leverage it to enhance the quality of node embeddings $\boldsymbol{Z}$ in Equation 3 by correlating residue errors and propagating node labels, which is partly inspired by the correct and smooth (C&S) method recently proposed in (Huang et al., 2020). The key idea of C&S is to smooth the residue errors and node labels over the graph leveraging a low-pass graph filter, which assumes the underlying graph to be homophilic. In contrast, our approach works effectively for both homophilic and heterophilic graphs by exploiting adaptive filter learning. Specifically, let $\mathbb{N}_L$ and $\mathbb{N}_U$ be the set of nodes that are labelled and unlabelled, respectively. Given the one-hot label matrix $\boldsymbol{Y} \in \mathbb{R}^{n \times c}$, where n and c denote the numbers of nodes and classes, respectively, we define the residue error matrix by $\boldsymbol{R} \in \mathbb{R}^{n \times c}$ such that $\boldsymbol{R}_{\mathbb{N}_L} = \boldsymbol{Z}_{\mathbb{N}_L} - \boldsymbol{Y}_{\mathbb{N}_L}$ and $\boldsymbol{R}_{\mathbb{N}_U} = 0$. Our goal is to optimize the following objective:

$$\hat{\boldsymbol{R}} = \arg\min_{\boldsymbol{H}} \|\boldsymbol{H} - \boldsymbol{R}\|_F^2 + \lambda \operatorname{Tr}(\boldsymbol{H}^T (\boldsymbol{I} - \frac{1}{P} g_P^*(\boldsymbol{F})) \boldsymbol{H}) \tag{5}$$

where λ is a regularization parameter. The first term in Equation 5 enforces the solution to be close to the initial residue error $\boldsymbol{R}$ that contains the label information. The key difference between our approach and the prior C&S method lies in the second term: our method spreads the error over the graph guided by the trained adaptive filter $g_P^*(\boldsymbol{F})$, whereas the C&S method adopts a simple (non-adaptive) smoothing scheme. Note that there is no training involved in this phase and $\hat{\boldsymbol{R}}$ can be iteratively computed by $\hat{\boldsymbol{R}}^{t+1} = \alpha \frac{1}{P} g_P^*(\boldsymbol{F}) \hat{\boldsymbol{R}}^t + (1 - \alpha) \boldsymbol{R}$ in $O(m)$ time due to the sparsity of $\boldsymbol{F}$, where $\alpha = \frac{\lambda}{1+\lambda}$ and m is the number of edges in graph. After obtaining $\hat{\boldsymbol{R}}$, we update the node embeddings $\tilde{\boldsymbol{Z}}$ by $\tilde{\boldsymbol{Z}}_{\mathbb{N}_L} = \boldsymbol{Y}_{\mathbb{N}_L}$ and $\tilde{\boldsymbol{Z}}_{\mathbb{N}_U} = \boldsymbol{Z}_{\mathbb{N}_U} + \beta \hat{\boldsymbol{R}}_{\mathbb{N}_U}$, where β is a hyperparameter. As suggested in Huang et al. (2020), we further refine $\tilde{\boldsymbol{Z}}$ by substituting $\tilde{\boldsymbol{Z}}$ for $\boldsymbol{R}$ in Equation 5 to diffuse the label information over the graph, thereby obtaining the corresponding optimizer $\hat{\boldsymbol{Z}}$. Subsequently, $\hat{\boldsymbol{Z}}$ will be utilized as the final node embeddings in the following label prediction step.

4 EXPERIMENTS

We have conducted comparative evaluation of GARNET against state-of-the-art defense GNN models on both homophilic and heterophilic datasets, under targeted attack (Nettack) (Zügner et al., 2018) and non-targeted attack (Mettack) (Zügner & Günnemann, 2019) with different perturbation budgets. Besides, we further evaluate the scalability of GARNET on ogbn-products, which is over $100\times$ larger than the datasets used in Entezari et al. (2020); Zhang & Zitnik (2020); Jin et al. (2020). Finally, we perform ablation studies to understand the effectiveness of each kernel in GARNET.

Table 1: Statistics of datasets used in our experiments.

Dataset	Type	Homophily Score	Nodes	Edges	Classes	Features
Cora	Homophily	0.80	$2,485$	$5,069$	7	$1,433$
Citeseer	Homophily	0.74	$2,110$	$3,668$	6	$3,703$
Pubmed	Homophily	0.80	$19,717$	$44,324$	3	500
Chameleon	Heterophily	0.23	$2,277$	$62,792$	5	$2,325$
Squirrel	Heterophily	0.22	$5,201$	$396,846$	5	$2,089$
ogbn-arxiv	Homophily	0.66	$169,343$	$1,166,243$	40	128
ogbn-products	Homophily	0.81	$2,449,029$	$61,859,140$	47	100

Experimental Setup. Table 1 shows the statistics of the datasets used in our experiments. We follow Zhu et al. (2020) to compute the homophily score per dataset (lower score means more heterophilic). We evaluate unvaccinated GCN (Kipf & Welling, 2016) and GAT (Veličković et al., 2017) on homophilic datasets, and H2GCN (Zhu et al., 2020) on heterophilic datasets. Moreover, we choose as the defense baselines four state-of-the-art vaccinated GNN models: GCNJaccard (Wu et al., 2019), GCN-SVD (Entezari et al., 2020), GNNGuard (Zhang & Zitnik, 2020), and Pro-GNN Jin et al. (2020). For all baselines, we tune their hyperparameters against adversarial attacks

Table 2: Averaged node classification accuracy (%) $\pm$ std under targeted attack (Nettack) with different perturbation ratio — We denote the evaluated dataset by its name with the number of perturbations (e.g., Cora-0 means the clean Cora graph and Cora-1 denotes there is 1 adversarial edge perturbation per target node). We bold and underline the first and second highest accuracy, respectively. OOM means out of memory.

Dataset	GCN	GAT	GCNJaccard	GCNSVD	GNNGuard	Pro-GNN	GARNET
Cora-0	80.96 ± 0.95	$\mathbf{83.85} \pm 1.41$	79.64 ± 2.31	72.65 ± 2.29	$\underline{83.37} \pm 2.46$	81.54 ± 1.21	82.77 ± 1.89
Cora-1	75.06 ± 0.81	75.30 ± 6.80	75.66 ± 3.39	70.36 ± 1.63	78.31 ± 1.60	$\mathbf{82.65} \pm 0.59$	$\underline{82.17} \pm 1.95$
Cora-2	70.60 ± 1.81	61.45 ± 3.81	70.96 ± 2.31	65.66 ± 2.76	72.77 ± 2.06	$\underline{77.83} \pm 1.10$	$\mathbf{78.55} \pm 2.11$
Cora-3	69.04 ± 3.31	59.64 ± 7.50	64.58 ± 2.29	61.20 ± 1.93	68.19 ± 2.48	$\underline{71.08} \pm 1.20$	$\mathbf{79.40} \pm 1.35$
Cora-4	61.69 ± 1.48	54.22 ± 3.41	61.44 ± 2.41	57.34 ± 3.46	62.41 ± 2.65	$\underline{67.83} \pm 1.87$	$\mathbf{72.77} \pm 2.16$
Cora-5	55.66 ± 1.95	40.12 ± 4.58	61.32 ± 3.38	55.30 ± 2.25	57.59 ± 2.46	$\underline{65.38} \pm 1.65$	$\mathbf{71.45} \pm 2.73$
Citeseer-0	81.59 ± 0.82	78.89 ± 3.51	81.90 ± 0.78	80.95 ± 1.23	80.32 ± 1.34	$\underline{82.89} \pm 1.53$	$\mathbf{83.86} \pm 1.07$
Citeseer-1	79.04 ± 1.80	78.25 ± 4.17	78.25 ± 1.24	75.23 ± 2.67	78.57 ± 2.14	$\underline{81.74} \pm 0.79$	$\mathbf{83.49} \pm 1.14$
Citeseer-2	76.19 ± 3.89	66.03 ± 3.10	76.98 ± 2.38	60.15 ± 2.29	73.18 ± 4.56	$\underline{80.15} \pm 0.71$	$\mathbf{80.63} \pm 1.46$
Citeseer-3	62.54 ± 4.50	56.98 ± 7.68	72.69 ± 2.91	58.89 ± 5.28	64.38 ± 5.89	$\mathbf{78.36} \pm 2.56$	$\underline{76.67} \pm 2.25$
Citeseer-4	57.30 ± 3.62	51.59 ± 9.72	66.34 ± 2.64	51.74 ± 7.96	59.05 ± 5.96	$\mathbf{73.98} \pm 1.28$	$\underline{72.22} \pm 2.28$
Citeseer-5	51.75 ± 2.50	51.43 ± 9.11	60.15 ± 3.91	45.07 ± 2.77	54.13 ± 8.05	$\underline{67.46} \pm 6.36$	$\mathbf{68.19} \pm 4.03$
Pubmed-0	87.26 ± 0.51	88.71 ± 0.80	$\underline{89.95} \pm 0.25$	87.03 ± 0.48	89.57 ± 0.28	OOM	$\mathbf{90.99} \pm 0.52$
Pubmed-1	86.29 ± 0.68	85.11 ± 1.32	86.45 ± 0.82	84.46 ± 0.28	$\underline{87.84} \pm 0.51$	OOM	$\mathbf{90.91} \pm 0.47$
Pubmed-2	83.17 ± 0.67	81.45 ± 1.93	83.60 ± 0.49	82.68 ± 0.46	$\underline{85.00} \pm 0.59$	OOM	$\mathbf{90.75} \pm 0.55$
Pubmed-3	81.13 ± 0.53	77.15 ± 1.90	80.32 ± 1.05	$\underline{81.34} \pm 0.68$	81.29 ± 0.90	OOM	$\mathbf{90.70} \pm 0.37$
Pubmed-4	75.48 ± 0.52	74.19 ± 2.67	75.43 ± 0.68	$\underline{82.41} \pm 0.54$	76.07 ± 0.77	OOM	$\mathbf{90.11} \pm 0.57$
Pubmed-5	66.67 ± 1.34	66.24 ± 3.94	68.71 ± 1.69	$\underline{79.56} \pm 0.48$	69.89 ± 1.18	OOM	$\mathbf{89.52} \pm 0.45$

with a small perturbation, and keep the same hyperparameters for larger adversarial perturbations. We further show hyperparameter settings of GARNET and hardware information in Appendix A.9.

4.1 DEFENSE ON HOMOPHILIC GRAPHS

Defense against targeted attack. We first evaluate the model robustness against Nettack, a strong attack method to fool a GNN model to misclassify some target nodes with a few structure (edge) perturbations. We choose the same set of target nodes as in (Jin et al., 2020). We report the averaged accuracy over 10 runs on Cora, Citeseer, and Pubmed datasets with adversarial perturbations varying from 0 to 5 per target node. Table 2 shows that GARNET outperforms all the baselines in most cases, with the accuracy improvement up to 9.96% over existing defense methods. Note that the accuracy degradation of GARNET when increasing perturbation budget is much smaller than that of baselines. For instance, the accuracy drop of GARNET is only 1.39% with perturbations varying from 1 to 5 on Pubmed, while the accuracy of baseline defense methods drops $4.9\% \sim 17.95\%$, indicating that GARNET is indeed more robust to strong targeted attack on homophilic graphs.

Defense against non-targeted attack. We further evaluate model robustness against a strong non-targeted attack, i.e., Metattack, whose goal is to drop the overall accuracy of the whole test set with a given perturbation ratio budget (i.e., the number of adversarial edges over the number of total edges). We report the averaged accuracy over 10 runs on Cora, Citeseer, and Pubmed with perturbation ratio in $\{0\%, 10\%, 20\%\}$. As shown in Table 3, GARNET consistently achieves the highest adversarial accuracy across all datasets under different attack perturbation ratios, with accuracy improvement over baselines up to 9.06%, which verifies that GARNET can also successfully defend against the non-targeted attack on homophilic graphs. It is worth mentioning that Pro-GNN is the most competitive baseline since it achieves the second highest accuracy in most cases on both Cora and Citeseer datasets. However, Pro-GNN suffers from the scalability issue since it learns a new graph from scratch and involves a dense graph during training. In contrast, GARNET is not only robust to adversarial attacks, but also scalable to large graphs, as empirically shown in Section 4.3.

4.2 DEFENSE ON HETEROPHILIC GRAPHS

To evaluate the robustness on heterophilic graphs, we apply both targeted (Nettack) and non-targeted (Metattack) attacks on Chameleon and Squirrel datasets. Due to the space limitation, we only report the adversarial accuracy under Metattack in Table 4. The results under Nettack are available in Appendix A.4. As shown in Table 4, all defense baselines are not robust to graph adversarial attacks on heterophilic graphs. Moreover, the performance of those vaccinated models is in fact drastically worse than that of the unvaccinated model H2GCN, a model designed to handle heterophilic graphs.

Table 3: Averaged node classification accuracy (%) ± std under non-targeted attack (Metattack) with different perturbation ratio — We denote the evaluated dataset by its name with the perturbation ratio (e.g., Cora-0 means the clean Cora graph and Cora-10 denotes there are 10% adversarial edges). We bold and underline the first and second highest accuracy, respectively. OOM means out of memory.

Dataset	GCN	GAT	GCNJaccard	GCNSVD	GNNGuard	Pro-GNN	GARNET
Cora-0	83.35 ± 0.66	84.29 ± 0.86	81.92 ± 0.33	73.86 ± 0.53	$\underline{84.45} \pm 0.63$	$\mathbf{85.56} \pm 0.36$	82.67 ± 1.89
Cora-10	69.50 ± 1.46	75.17 ± 0.70	74.76 ± 0.85	69.45 ± 0.69	69.35 ± 2.29	$\underline{77.90} \pm 0.69$	$\mathbf{82.17} \pm 0.69$
Cora-20	56.28 ± 1.19	55.42 ± 1.98	64.09 ± 1.52	62.44 ± 1.16	64.17 ± 2.00	$\underline{72.28} \pm 1.67$	$\mathbf{81.34} \pm 0.79$
Citeseer-0	72.15 ± 0.75	73.24 ± 1.05	72.32 ± 0.55	68.33 ± 1.17	72.09 ± 1.09	$\underline{73.29} \pm 1.49$	$\mathbf{74.82} \pm 1.07$
Citeseer-10	67.38 ± 1.56	70.65 ± 0.55	69.29 ± 0.91	68.29 ± 0.70	67.22 ± 2.60	$\underline{72.50} \pm 0.53$	$\mathbf{74.25} \pm 0.63$
Citeseer-20	57.21 ± 1.26	57.61 ± 2.11	59.54 ± 2.07	68.47 ± 0.72	55.30 ± 2.23	$\underline{71.10} \pm 0.72$	$\mathbf{72.03} \pm 0.50$
Pubmed-0	$\mathbf{87.16} \pm 0.09$	85.71 ± 0.15	86.83 ± 0.09	84.53 ± 0.08	85.38 ± 0.17	OOM	$\underline{86.86} \pm 0.57$
Pubmed-10	81.16 ± 0.13	81.09 ± 0.58	81.21 ± 0.14	$\underline{84.56} \pm 0.10$	77.45 ± 0.20	OOM	$\mathbf{86.24} \pm 0.20$
Pubmed-20	77.20 ± 0.27	76.43 ± 0.57	76.84 ± 0.25	$\underline{84.30} \pm 0.08$	71.73 ± 0.32	OOM	$\mathbf{85.69} \pm 0.26$

Our approach, on the other hand, consistently outperforms all defense baselines by a large margin. For instance, GARNET achieves 15.17% accuracy improvement over the best vaccinated model (i.e., GCNJaccard) on Chameleon with a 20% perturbation ratio. Moreover, GARNET also increases adversarial accuracy over H2GCN by up to 7.57%. Apart from achieving the highest accuracy, the accuracy drop of GARNET is much smaller compared to that of baselines when increasing the perturbation ratio. Specifically, the accuracy of GARNET drops 1.15% on Chameleon when increasing the perturbation ratio from 0% to 20%, while the accuracy of baselines drops $2.10\% \sim 18.58\%$. Thus, GARNET is also robust against graph adversarial attacks on heterophilic graphs.

Table 4: Averaged node classification accuracy (%) ± std under non-targeted attack (Metattack) with different perturbation ratio — We denote the evaluated dataset by its name with the perturbation ratio (e.g., Chameleon-0 means the clean Chameleon graph and Chameleon-10 denotes there are 10% adversarial edges). We bold and underline the first and second highest accuracy, respectively.

Dataset	GCN	H2GCN	GCNJaccard	GCNSVD	GNNGuard	Pro-GNN	GARNET
Chameleon-0	58.16 ± 1.29	$\underline{59.17} \pm 1.37$	46.89 ± 0.43	45.08 ± 0.70	58.01 ± 1.57	47.37 ± 1.93	$\mathbf{61.11} \pm 2.46$
Chameleon-10	43.47 ± 0.78	$\underline{54.57} \pm 1.40$	46.74 ± 0.60	41.95 ± 0.39	41.75 ± 0.93	38.39 ± 1.35	$\mathbf{60.96} \pm 1.22$
Chameleon-20	39.58 ± 1.56	$\underline{52.39} \pm 2.10$	44.79 ± 0.60	40.90 ± 0.77	39.89 ± 1.34	32.24 ± 1.53	$\mathbf{59.96} \pm 0.84$
Squirrel-0	37.45 ± 0.76	$\mathbf{45.58} \pm 1.21$	35.54 ± 0.40	31.17 ± 0.47	37.46 ± 0.56	32.02 ± 2.11	$\underline{43.43} \pm 1.14$
Squirrel-10	26.96 ± 0.30	$\underline{37.56} \pm 1.24$	33.68 ± 0.25	25.83 ± 0.32	27.03 ± 0.54	26.03 ± 1.23	$\mathbf{42.62} \pm 1.09$
Squirrel-20	23.94 ± 0.45	$\underline{36.33} \pm 1.31$	29.18 ± 1.54	14.90 ± 0.60	23.69 ± 0.59	20.09 ± 3.55	$\mathbf{41.97} \pm 1.02$

4.3 DEFENSE ON LARGE GRAPHS

Table 5: Averaged accuracy (%) ± std and run time under non-targeted attack (DICE) with 60% perturbation ratio — We bold the highest accuracy. OOM indicates out of memory.

Method	ogbn-arxiv			ogbn-products		
	Clean	Adversarial	Time (mins)	Clean	Adversarial	Time (mins)
GNNGuard	68.22 ± 1.80	60.46 ± 2.71	22.21	74.82 ± 0.11	66.69 ± 0.12	567.11
Pro-GNN	OOM	OOM	OOM	OOM	OOM	OOM
GARNET	$\mathbf{70.23} \pm 0.45$	$\mathbf{62.89} \pm 0.22$	1.08	$\mathbf{81.65} \pm 0.11$	$\mathbf{75.61} \pm 0.14$	31.27

To demonstrate the scalability of GARNET on large graphs, we evaluate the robustness of GARNET on the attacked ogbn-arxiv and ogbn-products. Given that existing strongest attacks (Nettack and Metattack) are not scalable to large graphs, we leverage a less powerful yet more scalable attacking algorithm called DICE (Waniek et al., 2018), which randomly connects (disconnects) nodes from different (same) classes, to perturb the graph structure. To have a challenging defense scenario, we consider a large perturbation budget for DICE while keeping the overall graph size the same. Specifically, we use DICE to first randomly delete 30% edges linking nodes from the same class and then randomly insert 30% edges linking nodes from different classes. Note that we only use training labels for DICE. In regard to baselines, we evaluate GNNGuard and Pro-GNN as strongest defense baselines, since they perform better than other baselines in most cases as shown in Sections 4.1 and 4.2. Table 5 reports the accuracy and run time on large graphs under DICE attack, which shows that Pro-GNN cannot scale to large graphs due to its heavy memory usage for storing a dense adjacency

Figure 2: Comparisons of different kernel combinations in GARNET on Cora, Pubmed, and Squirrel datasets under Nettack — We denote the reduced-rank approximation kernel, adaptive filter learning kernel, and adaptive label propagation kernel by Reduced_Rank, Ada_Filter, and Ada_Label_Prop, respectively. Note that the red curve is basically GARNET. Besides, we choose GNNGuard as a strong baseline among existing defense GNN models.

matrix. While GNNGuard achieves a lower memory overhead by exploiting the graph sparsity, its training is much slower since a new adjacency matrix is reconstructed per layer. Besides, the adversarial accuracy of GNNGuard does not show a clear improvement over the accuracy of GCN under DICE attack. In contrast, GARNET is not only scalable to large graphs, but also achieves the accuracy improvement by a margin of 2.43% and 8.92% over the baselines on ogbn-arxiv and ogbn-products, respectively. We further show the run time per kernel of GARNET in Appendix A.5.

4.4 Abalation Analysis on GARNET Kernels

To study the effectiveness of our proposed GARNET kernels separately, we conduct experiments by adding three kernels one by one to see how each kernel affects the adversarial accuracy. Specifically, we evaluate the model robustness against Nettack with the number of perturbations varying from 1 to 5 per target node. We show results on three datasets (two homophilic datasets Cora & Pubmed and one heterophilic dataset Squirrel) in Figure 2. When we only train an adaptive graph filter for node prediction, the adversarial accuracy is slightly higher than the accuracy of GNNGuard on homophilic datasets, while it outperforms GNNGuard on a heterophilic dataset (i.e., Squirrel) by a large margin. This shows two benefits of the adaptive graph filter: (1) the adaptive filter can be trained to effectively adapt to the homo/heterophilic properties of an underlying graph; (2) leveraging an adaptive graph filter alone can achieve adversarial accuracy comparable to (or better than) the accuracy of existing defense GNN models. We attribute these gains to Equations 2 and 3 in Section 3.2: we first train an MLP that is agnostic to the perturbed graph structure, and then apply the adaptive graph filter whose performance is robust to adversarial attacks as shown in the Theorem 2.

Figure 2 further shows that adding the reduced-rank approximation kernel results in a much more graceful accuracy degradation when increasing the budget of adversarial perturbations. For instance, the accuracy achieved by combining reduced-rank approximation and adaptive filter remains almost the same when increasing the perturbation from 1 to 5 per target node on Pubmed. This implies that our reduced-rank approximation kernel can effectively remove the high-rank adversarial properties from the input graph, allowing GARNET to be more resistant to graph adversarial attacks. Moreover, incorporating the adaptive label propagation kernel also helps improve the adversarial accuracy, implying that propagating node labels by using the adaptive filter can effectively exploit the label information for further enhancing the quality of node representations under adversarial attacks.

5 Conclusions

This work introduces GARNET, a spectral approach to robust and scalable graph neural networks. GARNET first construct a reduced-rank yet sparse approximation of the adversarial graph. GARNET then trains an adaptive graph filter on the reduced-rank graph to obtain refined node representations as well as the learned adaptive filter that will subsequently guide the process of label propagation to further enhance the quality of node representations. Our experiments show that GARNET outperforms the state-of-the-art defense GNN models on various homophilic and heterophilic graphs under both targeted and non-targeted adversarial attacks.

REPRODUCIBILITY STATEMENT

The GARNET source code is available at github.com/gnngarnet/garnet. Besides, we provide our proofs for Theorems 1 and 2 in Appendices A.1 and A.2, respectively. Moreover, the proof for Lemma 1 is available in Chien et al. (2021). Finally, the details of all datasets used in our experiments are available in Appendix A.9.

REFERENCES

Takuya Akiba, Shotaro Sano, Toshihiko Yanase, Takeru Ohta, and Masanori Koyama. Optuna: A next-generation hyperparameter optimization framework. In *Proceedings of the 25th ACM SIGKDD international conference on knowledge discovery & data mining*, pp. 2623–2631, 2019.

James Baglama and Lothar Reichel. Augmented implicitly restarted lanczos bidiagonalization methods. *SIAM Journal on Scientific Computing*, 27(1):19–42, 2005.

Sergio Casas, Cole Gulino, Renjie Liao, and Raquel Urtasun. Spagnn: Spatially-aware graph neural networks for relational behavior forecasting from sensor data. In *2020 IEEE International Conference on Robotics and Automation (ICRA)*, pp. 9491–9497. IEEE, 2020.

Adrián Castelló, Manuel F Dolz, Enrique S Quintana-Ortí, and José Duato. Analysis of model parallelism for distributed neural networks. In *Proceedings of the 26th European MPI Users' Group Meeting*, pp. 1–10, 2019.

Eli Chien, Jianhao Peng, Pan Li, and Olgica Milenkovic. Adaptive universal generalized pagerank graph neural network. In *International Conference on Learning Representations*, 2021. URL https://openreview.net/forum?id=n6jl7fLxrP.

F. R. K. Chung. *Spectral Graph Theory*. American Mathematical Society, 1997.

Hanjun Dai, Hui Li, Tian Tian, Xin Huang, Lin Wang, Jun Zhu, and Le Song. Adversarial attack on graph structured data. In *International conference on machine learning*, pp. 1115–1124. PMLR, 2018.

Negin Entezari, Saba A Al-Sayouri, Amirali Darvishzadeh, and Evangelos E Papalexakis. All you need is low (rank) defending against adversarial attacks on graphs. In *Proceedings of the 13th International Conference on Web Search and Data Mining*, pp. 169–177, 2020.

William L Hamilton. Graph representation learning. *Synthesis Lectures on Artifical Intelligence and Machine Learning*, 14(3):1–159, 2020.

Weihua Hu, Matthias Fey, Marinka Zitnik, Yuxiao Dong, Hongyu Ren, Bowen Liu, Michele Catasta, and Jure Leskovec. Open graph benchmark: Datasets for machine learning on graphs. *arXiv preprint arXiv:2005.00687*, 2020.

Qian Huang, Horace He, Abhay Singh, Ser-Nam Lim, and Austin R Benson. Combining label propagation and simple models out-performs graph neural networks. *arXiv preprint arXiv:2010.13993*, 2020.

Wei Jin, Yao Ma, Xiaorui Liu, Xianfeng Tang, Suhang Wang, and Jiliang Tang. Graph structure learning for robust graph neural networks. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 66–74, 2020.

Thomas N Kipf and Max Welling. Semi-supervised classification with graph convolutional networks. *arXiv preprint arXiv:1609.02907*, 2016.

Ron Levie, Elvin Isufi, and Gitta Kutyniok. On the transferability of spectral graph filters. In *2019 13th International conference on Sampling Theory and Applications (SampTA)*, pp. 1–5. IEEE, 2019.

Yao Ma, Xiaorui Liu, Neil Shah, and Jiliang Tang. Is homophily a necessity for graph neural networks? *arXiv preprint arXiv:2106.06134*, 2021.

Yu A Malkov and Dmitry A Yashunin. Efficient and robust approximate nearest neighbor search using hierarchical navigable small world graphs. *IEEE transactions on pattern analysis and machine intelligence*, 42(4):824–836, 2018.

Azalia Mirhoseini, Anna Goldie, Mustafa Yazgan, Joe Wenjie Jiang, Ebrahim Songhori, Shen Wang, Young-Joon Lee, Eric Johnson, Omkar Pathak, Azade Nazi, et al. A graph placement methodology for fast chip design. *Nature*, 594(7862):207–212, 2021.

Hoang NT, Takanori Maehara, and Tsuyoshi Murata. Stacked graph filter. *arXiv preprint arXiv:2011.10988*, 2020.

Andrew W Senior, Richard Evans, John Jumper, James Kirkpatrick, Laurent Sifre, Tim Green, Chongli Qin, Augustin Žídek, Alexander WR Nelson, Alex Bridgland, et al. Improved protein structure prediction using potentials from deep learning. *Nature*, 577(7792):706–710, 2020.

David I Shuman, Sunil K. Narang, Pascal Frossard, Antonio Ortega, and Pierre Vandergheynst. The emerging field of signal processing on graphs: Extending high-dimensional data analysis to networks and other irregular domains. *IEEE Signal Processing Magazine*, 30(3):83–98, 2013. doi: 10.1109/MSP.2012.2235192.

Lichao Sun, Yingtong Dou, Carl Yang, Ji Wang, Philip S Yu, Lifang He, and Bo Li. Adversarial attack and defense on graph data: A survey. *arXiv preprint arXiv:1812.10528*, 2018.

Petar Veličković, Guillem Cucurull, Arantxa Casanova, Adriana Romero, Pietro Lio, and Yoshua Bengio. Graph attention networks. *arXiv preprint arXiv:1710.10903*, 2017.

Marcin Waniek, Tomasz P Michalak, Michael J Wooldridge, and Talal Rahwan. Hiding individuals and communities in a social network. *Nature Human Behaviour*, 2(2):139–147, 2018.

Huijun Wu, Chen Wang, Yuriy Tyshetskiy, Andrew Docherty, Kai Lu, and Liming Zhu. Adversarial examples on graph data: Deep insights into attack and defense. *arXiv preprint arXiv:1903.01610*, 2019.

Zhilin Yang, William Cohen, and Ruslan Salakhudinov. Revisiting semi-supervised learning with graph embeddings. In *International conference on machine learning*, pp. 40–48. PMLR, 2016.

Rex Ying, Ruining He, Kaifeng Chen, Pong Eksombatchai, William L Hamilton, and Jure Leskovec. Graph convolutional neural networks for web-scale recommender systems. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 974–983, 2018.

Xiang Zhang and Marinka Zitnik. Gnnguard: Defending graph neural networks against adversarial attacks. *arXiv preprint arXiv:2006.08149*, 2020.

Ke Zhou, Hongyuan Zha, and Le Song. Learning social infectivity in sparse low-rank networks using multi-dimensional hawkes processes. In *Artificial Intelligence and Statistics*, pp. 641–649. PMLR, 2013.

Jiong Zhu, Yujun Yan, Lingxiao Zhao, Mark Heimann, Leman Akoglu, and Danai Koutra. Beyond homophily in graph neural networks: Current limitations and effective designs. *arXiv preprint arXiv:2006.11468*, 2020.

Jiong Zhu, Junchen Jin, Michael T Schaub, and Danai Koutra. Improving robustness of graph neural networks with heterophily-inspired designs. *arXiv preprint arXiv:2106.07767*, 2021.

Daniel Zügner and Stephan Günnemann. Adversarial attacks on graph neural networks via meta learning. *arXiv preprint arXiv:1902.08412*, 2019.

Daniel Zügner, Amir Akbarnejad, and Stephan Günnemann. Adversarial attacks on neural networks for graph data. In *Proceedings of the 24th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pp. 2847–2856, 2018.

A   APPENDIX

A.1   PROOF FOR THEOREM 1

Proof. As the graph is undirected, we can perform eigendecomposition on both $\boldsymbol{A}_{norm}$ and $\boldsymbol{L}_{norm}$. Let λ_i, $\hat{\lambda}_i$, and σ_i, $i = 1, 2, ..., r$ denote the r smallest eigenvalues of $\boldsymbol{L}_{norm}$, r largest eigenvalues of $\boldsymbol{A}_{norm}$, and r largest singular values of $\boldsymbol{A}_{norm}$, respectively. Since $\boldsymbol{A}_{norm} = \boldsymbol{I} - \boldsymbol{L}_{norm}$, $\boldsymbol{A}_{norm}$ and $\boldsymbol{L}_{norm}$ share the same set of eigenvectors while their eigenvalues satisfy: $\hat{\lambda}_i = 1 - \lambda_i$, $i = 1, 2, ..., r$. Moreover, since we assume that the r largest magnitude eigenvalues of $\boldsymbol{A}_{norm}$ are non-negative, we have $\sigma_i = \left| \hat{\lambda}_i \right| = \hat{\lambda}_i$, $i = 1, 2, ..., r$. Thus, we have:

$$
\begin{aligned}
\boldsymbol{V}\boldsymbol{V}^T &= [\boldsymbol{v}_1, ..., \boldsymbol{v}_r]
\begin{bmatrix}
|1 - \lambda_1| & & \\
& \ddots & \\
& & |1 - \lambda_r|
\end{bmatrix}
[\boldsymbol{v}_1, ..., \boldsymbol{v}_r]^T \\
&= [\boldsymbol{v}_1, ..., \boldsymbol{v}_r]
\begin{bmatrix}
\left|\hat{\lambda}_1\right| & & \\
& \ddots & \\
& & \left|\hat{\lambda}_r\right|
\end{bmatrix}
[\boldsymbol{v}_1, ..., \boldsymbol{v}_r]^T \\
&= [\boldsymbol{v}_1, ..., \boldsymbol{v}_r]
\begin{bmatrix}
\sigma_1 & & \\
& \ddots & \\
& & \sigma_r
\end{bmatrix}
[\boldsymbol{v}_1, ..., \boldsymbol{v}_r]^T \\
&= \hat{\boldsymbol{A}}
\end{aligned}
$$

Since $\boldsymbol{V}_{i,:}$ is defined as the weighted spectral embedding of node i and $\hat{\boldsymbol{A}}_{i,j} = \boldsymbol{V}_{i,:}\boldsymbol{V}_{j,:}^T$, $\hat{\boldsymbol{A}}_{i,j}$ corresponds to the dot product score between the weighted spectral embeddings of node i and j, which completes the proof of the theorem. $\qquad\square$

A.2   PROOF FOR THEOREM 2

To prove Theorem 2, we first give two Lemmas below:

Lemma 2. *Given a graph adjacency matrix $\boldsymbol{A}$ and degree matrix $\boldsymbol{D}$, let $\boldsymbol{A}_{norm} = \boldsymbol{D}^{-\frac{1}{2}}\boldsymbol{A}\boldsymbol{D}^{-\frac{1}{2}}$, and $\hat{\boldsymbol{A}}_{norm}$ is the low-rank approximation of $\boldsymbol{A}_{norm}$ via truncated SVD, we have $\|\boldsymbol{A}_{norm}\|_2 \leq 1$ and $\|\hat{\boldsymbol{A}}_{norm}\|_2 \leq 1$*

The proof for Lamma 2 is trivial since the spectrum of $\boldsymbol{A}_{norm}$ and $\hat{\boldsymbol{A}}_{norm}$ lies in $[-1, 1]$ (Chung, 1997).

Lemma 3. *Given two matricies $\boldsymbol{M}$ and $\boldsymbol{N}$ such that $\|\boldsymbol{M}\|_2 \leq 1$ and $\|\boldsymbol{N}\|_2 \leq 1$, we have $\|\boldsymbol{M}^p - \boldsymbol{N}^p\|_2 \leq p\|\boldsymbol{M} - \boldsymbol{N}\|_2$ for every $p \geq 0$.*

The proof for Lamma 3 is available in Levie et al. (2019).

Next, we formally prove Theorem 2 in the following:

Proof.

$$
\begin{aligned}
\|g_P(\boldsymbol{A}_{clean}) - g_P(\boldsymbol{A}_r)\|_2 &= \|\sum_{p=0}^{P} c_p \boldsymbol{A}_{clean}^p - \sum_{p=0}^{P} c_p \boldsymbol{A}_r^p\|_2 \\
&= \sum_{p=1}^{P} \|c_p(\boldsymbol{A}_{clean}^p - \boldsymbol{A}_r^p)\|_2 \\
&\leq \sum_{p=1}^{P} |c_p| \|\boldsymbol{A}_{clean}^p - \boldsymbol{A}_r^p\|_2
\end{aligned}
$$

$$\leq \sum_{p=1}^{P} p \, |c_p| \, \|\boldsymbol{A}_{clean} - \boldsymbol{A}_r\|_2$$

$$\leq \sum_{p=1}^{P} p \, |c_p| \, (\|\boldsymbol{A}_{clean} - \boldsymbol{A}_{adv}\|_2 + \|\boldsymbol{A}_{adv} - \boldsymbol{A}_r\|_2)$$

$$\leq \sum_{p=1}^{P} p \, |c_p| \, (\epsilon + \sigma_{r+1})$$

$$\leq \frac{1}{2}(P^2 + P)(\epsilon + \sigma_{r+1})$$

The second inequality above is based on Lemmas 2 and 3, while the third inequality is derived by using the triangle inequality. The last inequality is obtained based on the constraints $|c_p| \leq 1$. $\qquad\square$

A.3 GARNET ALGORITHM AND COMPLEXITY ANALYSIS

Algorithm 1: GARNET algorithm

Input: Adjacency matrix $\boldsymbol{A} \in \mathbb{R}^{n \times n}$; node feature matrix $\boldsymbol{X} \in \mathbb{R}^{n \times d}$; node label matrix $\boldsymbol{Y} \in \mathbb{R}^{n \times c}$; truncated svd rank r; kNN graph k; polynomial filter degree P; error correction scale β; train node set $\mathbb{N}_L$; test node set $\mathbb{N}_U$; label propagation iteration s; regularization parameter α

Output: Node embedding matrix $\hat{\boldsymbol{Z}} \in \mathbb{R}^{n \times c}$

   /* Phase1:reduced-rank approximation   */

1   $\boldsymbol{U}, \boldsymbol{S}, \boldsymbol{V}^T = truncated\_svd(\boldsymbol{A}, rank = r)$;

2   $\tilde{\boldsymbol{A}} = kNN\_graph(\boldsymbol{U}\sqrt{\boldsymbol{S}}, k)$;

   /* Phase2:adaptive filter learning   */

3   **for** $1...epochs$ **do**

4       $\hat{\boldsymbol{X}} = MLP(\boldsymbol{X})$;

5       $\boldsymbol{Z} = Softmax(\sum_{p=0}^{P} c_p \tilde{\boldsymbol{A}}^p \hat{\boldsymbol{X}})$;

6       $loss = CrossEntropyLoss(\boldsymbol{Z}, \boldsymbol{Y})$;

7       $loss.backward()$;

8   **end**

   /* Phase3:adaptive label propagation   */

9   $\boldsymbol{R}_{\mathbb{N}_L} = \boldsymbol{Z}_{\mathbb{N}_L} - \boldsymbol{Y}_{\mathbb{N}_L}$;

10   $\boldsymbol{R}_{\mathbb{N}_U} = 0$;

11   $\hat{\boldsymbol{R}}^0 = \boldsymbol{R}$;

12   **for** $i = 0...s$ **do**

13       $\hat{\boldsymbol{R}}^{i+1} = \frac{\alpha}{P} \sum_{p=0}^{P} c_p^* \tilde{\boldsymbol{A}}^p \hat{\boldsymbol{R}}^i + (1-\alpha)\boldsymbol{R}$;

14   **end**

15   $\tilde{\boldsymbol{Z}}_{\mathbb{N}_L} = \boldsymbol{Y}_{\mathbb{N}_L}$;

16   $\tilde{\boldsymbol{Z}}_{\mathbb{N}_U} = \boldsymbol{Z}_{\mathbb{N}_U} + \beta \hat{\boldsymbol{R}}_{\mathbb{N}_U}$;

17   $\hat{\boldsymbol{Z}}^0 = \tilde{\boldsymbol{Z}}$;

18   **for** $i = 0...s$ **do**

19       $\hat{\boldsymbol{Z}}^{i+1} = \frac{\alpha}{P} \sum_{p=0}^{P} c_p^* \tilde{\boldsymbol{A}}^p \hat{\boldsymbol{Z}}^i + (1-\alpha)\tilde{\boldsymbol{Z}}$;

20   **end**

The algorithm of GARNET is shown in Algorithm 1. We further analyze the total complexity of GARNET on a graph $\mathcal{G} = (\mathcal{V}, \mathcal{E})$. Specifically, as we mention in Section 3.1, the complexity of the truncated SVD with rank r and approximate kNN graph construction is $O(r\,|\mathcal{E}|)$ and $O(|\mathcal{V}|\log|\mathcal{V}|)$, respectively. Thus, the complexity of the reduced-rank approximation kernel is $O(r\,|\mathcal{E}| + |\mathcal{V}|\log|\mathcal{V}|)$. Moreover, the complexity of computing adaptive filter is $O(c\,|\mathcal{E}|)$, where c is the column dimension of $\hat{\boldsymbol{X}}$, since we can leverage the sparsity of the graph for computing $\tilde{\boldsymbol{A}}\hat{\boldsymbol{X}}$. Similarly, the complexity of adaptive label propagation kernel is $O(sP\,|\mathcal{E}|)$, where s is the number of steps to iteratively compute $\hat{\boldsymbol{R}}$ and $\hat{\boldsymbol{Z}}$, and P denotes the polynomial degree. Consequently, the overall complexity of GARNET is $O((r + c + sP)\,|\mathcal{E}| + |\mathcal{V}|\log|\mathcal{V}|)$.

A.4 ACCURACY ON HETEROPHILIC DATASETS UNDER NETTACK

Table 6: Averaged node classification accuracy (%) $\pm$ std under targeted attack (Nettack) with different perturbation ratio — We denote the evaluated dataset by its name with the number of perturbations (e.g., Chameleon-0 means the clean Chameleon graph and Chameleon-1 denotes there is 1 adversarial edge perturbation per target node). We bold and underline the first and second highest accuracy, respectively.

Dataset	GCN	H2GCN	GCNJaccard	GCNSVD	GNNGuard	Pro-GNN	GARNET
Chameleon-0	70.66 ± 1.65	71.71 ± 3.22	53.41 ± 0.73	68.29 ± 0.54	$\mathbf{74.15} \pm 1.26$	60.66 ± 3.11	$\underline{72.89} \pm 2.65$
Chameleon-1	69.81 ± 1.34	70.61 ± 2.14	52.93 ± 1.12	67.93 ± 0.56	$\underline{71.82} \pm 1.86$	59.44 ± 3.13	$\mathbf{72.68} \pm 1.89$
Chameleon-2	68.51 ± 2.37	$\underline{69.76} \pm 2.90$	52.93 ± 1.11	68.29 ± 0.77	67.32 ± 2.36	56.44 ± 3.13	$\mathbf{72.20} \pm 2.31$
Chameleon-3	65.73 ± 2.78	67.76 ± 2.36	52.44 ± 0.77	$\underline{69.15} \pm 0.95$	66.22 ± 2.37	52.56 ± 3.28	$\mathbf{72.17} \pm 2.07$
Chameleon-4	63.04 ± 3.98	66.80 ± 2.45	52.56 ± 1.01	$\underline{70.24} \pm 0.60$	65.73 ± 2.72	51.95 ± 2.59	$\mathbf{72.06} \pm 2.94$
Chameleon-5	57.92 ± 3.69	65.93 ± 3.40	51.58 ± 0.56	$\underline{67.44} \pm 0.78$	63.42 ± 3.45	51.10 ± 2.58	$\mathbf{71.83} \pm 2.11$
Squirrel-0	25.46 ± 1.96	$\underline{37.00} \pm 2.75$	35.72 ± 0.86	31.73 ± 1.18	26.09 ± 2.35	20.45 ± 4.52	$\mathbf{44.91} \pm 1.53$
Squirrel-1	25.09 ± 2.97	$\underline{35.64} \pm 2.49$	34.73 ± 0.76	31.00 ± 1.11	23.46 ± 2.53	19.82 ± 4.23	$\mathbf{43.55} \pm 1.79$
Squirrel-2	25.00 ± 2.20	34.54 ± 2.18	$\underline{34.63} \pm 0.98$	30.99 ± 1.03	22.09 ± 1.36	18.82 ± 4.17	$\mathbf{44.09} \pm 2.35$
Squirrel-3	24.73 ± 1.76	33.82 ± 2.80	$\underline{34.54} \pm 1.00$	30.18 ± 1.67	22.00 ± 1.36	17.36 ± 4.06	$\mathbf{44.18} \pm 2.26$
Squirrel-4	24.09 ± 1.15	33.71 ± 2.54	$\underline{34.27} \pm 0.81$	30.00 ± 0.91	21.18 ± 1.91	16.36 ± 4.16	$\mathbf{43.73} \pm 1.62$
Squirrel-5	23.72 ± 1.09	31.45 ± 2.43	$\underline{34.00} \pm 0.83$	29.54 ± 2.51	21.09 ± 1.86	16.27 ± 3.78	$\mathbf{43.64} \pm 1.53$

As shown in Table 6, the four vaccinated baseline models, i.e., GCNJaccard, GCNSVD, GNN-Guard, and Pro-GNN, only achieve comparable or even worse accuracy than the unvaccinated model H2GCN in most cases, which indicates that those defense models lose its robustness on heterophilic graphs. In contrast, GARNET largely outperforms all baselines in most scenarios. For instance, the accuracy of GARNET is 9.64% higher than the accuracy of the best baseline (i.e., GCNJaccard) on Squirrel with 3 perturbations per target node. Moreover, the accuracy drop of GARNET when increasing the number of perturbations per target node is only 1.06% and 1.27% on Chameleon and Squirrel, respectively, which indicates that GARNET is also resistant to the targeted attack on heterophilic graphs.

A.5 RUN TIME PER KERNEL IN GARNET

Table 7: Run time (secs) of each kernel in GARNET— We decompose the reduced-rank approximation kernel into truncated SVD (TSVD) and approximate kNN graph construction (AKNN) steps. In addition, we denote the adaptive filter learning kernel and adaptive label propagation kernel by Ada_Filter, and Ada_Label_Prop, respectively.

Dataset	TSVD	AKNN	Ada_Filter	Ada_Label_Prop	Total
Cora	0.09	0.10	0.76	0.05	1.00
Pubmed	0.25	0.72	1.60	0.05	2.62
ogbn-arxiv	6.04	17.92	40.49	0.23	64.68
ogbn-products	368.37	363.32	1139.46	5.21	1876.36

Table 7 reports the run time of each sub-kernel in GARNET on Cora, Pubmed, ogbn-arxiv, and ogbn-products. It shows that training the adaptive graph filter is the most time consuming kernel in

GARNET. It is also worth mentioning that the run time of truncated SVD and approximate kNN graph construction is less than 7 minutes on ogbn-products, which contains 2 million of nodes and 60 million edges. This is consistent with their near-linear complexity analyzed in Section 3.1.

A.6 ABLATION STUDY ON kNN GRAPH CONSTRUCTION

Figure 3: Ablation Study on kNN Graph.

To evaluate the sensitivity of GARNET to approximate kNN (AKNN) graph construction, we show the adversarial accuracy of GARNET with different k values for constructing AKNN graphs in Figure 3, which indicates that the accuracy of GARNET does not change too much when varying k value within the range of $[30, 100]$, especially on the Cora and Pubmed datasets. Hence, we recommend choosing $k = 50 \sim 80$ for the AKNN graph construction.

A.7 GRAPH RANK UNDER ADVERSARIAL ATTACKS

Figure 4: Graph rank growth under Metattack.

To verify that applying adversarial attacks on a graph indeed increases its rank, we evaluate how the graph rank changes when increasing the perturbation ratio of Metattack. Specifically, we evaluate the graph rank growth rate on three homophilic graphs Cora, Citeseer, and Pubmed, as well as one heterophilic graph Chameleon. Figure 4 shows that the graph ranks grow with increasing perturba-

tion ratios (0% to 25%). For the results showing that other graph adversarial attacks increase graph ranks, we refer to Figure 3 in Entezari et al. (2020) and Figure 1 in Jin et al. (2020).

A.8 GRAPH RANK VIA REDUCED-RANK APPROXIMATION

Figure 5: Comparisons of the rank on adversarial graph under Metattack and that on the corresponding reduced-rank graph generated in Phase 1 of GARNET on Cora, Pubmed, and Chameleon datasets.

We compute the rank of each adversarial graph under Metattack with the perturbation ratio varying from 5% to 25%, and compare the result with its corresponding reduced-rank graph obtained via reduced-rank approximation (Section 3.1). Figure 5 shows that the reduced-rank graphs indeed exhibit much lower ranks than the original adversarial graphs, demonstrating the effectiveness of the proposed reduced-rank approximation scheme for removing high-rank adversarial graph properties.

A.9 EXPERIMENTAL SETUP

A.9.1 HYPERPARAMETER SETTINGS OF GARNET

We show the hyperparameters of the reduced-rank approximation kernel and the adaptive filter learning kernel on different datasets under Nettack (1 perturbation per node), Metattack (10% perturbation ratio), and DICE (60% perturbation ratio) in Table 8. For the adaptive label propagation kernel, we do not manually tune hyperparameters but instead leverage Optuna (Akiba et al., 2019) to optimize the hyperparameters such as the scale β for error correction based on the validation set, since this kernel is fast to compute. We refer to github.com/gnngarnet/garnet for details of hyperparameters used in the adaptive label propagation kernel.

Table 8: Summary of hyperparameters in GARNET— Apart from the notations r, k, and δ mentioned in Section 3.1, we denote polynomial degree, learning rate, number of epochs, weight_decay, dropout, and coefficient initialization in the adaptive filter learning kernel by P, lr, $epochs$, wd, dp, and c, respectively.

	Reduced-Rank Approximation			Adaptive Filter Learning					
Dataset	r	k	δ	P	lr	$epochs$	wd	dp	c
Cora-Nettack	50	50	0.05	10	0.01	50	0.0005	0.5	0.9
Cora-Metattack	50	50	0.05	10	0.01	50	0.0005	0.5	0.9
Citeseer-Nettack	50	30	0.003	10	0.01	50	0.0005	0.5	0.9
Citeseer-Metattack	50	60	0.05	10	0.01	50	0.0005	0.5	0.9
Pubmed-Nettack	50	80	0.05	10	0.01	150	0.0005	0.5	0.9
Pubmed-Metattack	50	80	0.05	10	0.01	150	0.0005	0.5	0.9
Chameleon-Nettack	50	60	0.003	10	0.05	300	0.0	0.5	0.9
Chameleon-Metattack	50	60	0.003	10	0.05	300	0.0	0.5	0.9
Squirrel-Nettack	50	50	0.003	10	0.1	300	0.0	0.5	0.3
Squirrel-Metattack	50	50	0.003	10	0.1	300	0.0	0.5	0.3
ogbn-arxiv-DICE	50	50	0.00003	10	0.01	500	0.0	0.0	0.9
ogbn-products-DICE	50	50	0.00003	5	0.01	300	0.0	0.0	0.9

A.9.2 DATASET DETAILS

As in Jin et al. (2020), we extract the largest connected components of the original Cora, Citeseer, and Pubmed datasets (Yang et al., 2016) for the adversarial evaluation, with the same train/validation/test split. For Chameleon and Squirrel, we keep the same split setting as Chien et al. (2021). Finally, we follow the split setting of Open Graph Benchmark (OGB) (Hu et al., 2020) on ogbn-arxiv and ogbn-products.

In addition, we follow Jin et al. (2020) for the selection of target nodes on Cora, Citeseer, and Pubmed under Nettack. For the Chameleon and Squirrel datasets under Nettack, we choose target nodes that have degrees within the range of $[20, 50]$ and $[20, 140]$, respectively. In regard to non-targeted attacks (i.e., Metattack and DICE), we choose nodes in the test set as target nodes for all datasets.

A.9.3 HARDWARE INFORMATION

For ogbn-arxiv and ogbn-products, we run experiments on a Linux machine with an Intel Xeon Silver 4214 CPU (8 cores @ 2.20GHz) and 4 NVIDIA RTX A6000 GPUs (48 GB memory per GPU). For the rest of the datasets, we conduct all experiments on a Linux machine with an Intel Xeon Gold 5218 CPU (8 cores @ 2.30GHz) CPU and an NVIDIA RTX 2080 Ti GPU (11 GB memory per GPU).