# Constraining Gaussian Processes to Systems of Linear Ordinary Differential Equations

## Abstract

Data in many applications follows systems of Ordinary Differential Equations (ODEs). This paper presents a novel algorithmic and symbolic construction for covariance functions of Gaussian Processes (GPs) with realizations strictly following a system of linear homogeneous ODEs with constant coefficients, which we call LODE-GPs. Introducing this strong inductive bias into a GP improves modelling of such data. Using smith normal form algorithms, a symbolic technique, we overcome two current restrictions in the state of the art: (1) the need for certain uniqueness conditions in the set of solutions, typically assumed in classical ODE solvers and their probabilistic counterparts, and (2) the restriction to controllable systems, typically assumed when encoding differential equations in covariance functions. We show the effectiveness of LODE-GPs in a number of experiments, for example learning physically interpretable parameters by maximizing the likelihood.

## 1 Introduction

Many real world tasks have underlying dynamic behavior, for example chemical reactions [19], systems in bioprocess engineering [23], or population dynamics [65]. One currently widely debated application are compartmental models in epidemiology [17, 31, 47]. Many such systems are linear or can be decently linearized, such in control theory [68], biology [13], process engineering [1, §9], or engines [6]. Including prior knowledge in the form of differential equations benefits the model fit and enhances interpretability for a model. Hence, modelling differential equations in Machine Learning (ML) has therefore been the focus of much research in both Gaussian Processes (GPs) (e.g. [34, 26, 46, 21, 58]) and Deep Learning (DL) (e.g. [44, 33, 59, 14]).

Probabilistic Ordinary Differential Equation (ODE) solvers allow to learn non-linear ODEs [47, 49, 48, 8]. However, they require some approximations and thereby do not strictly guarantee to yield solutions of the system of ODEs. Furthermore, these systems typically need to be well-posed, in particular the solution needs to be unique once a finite number of initial conditions is known. While this second limitation is typically irrelevant in physical or biological systems, it is strongly relevant in systems in engineering, such as in control systems with their freely choosable inputs.

With early works like [22], the introduction of derivatives as linear operators in GPs became prominent for partial differential equations. This inspired several works that encode differential equations in the covariance structure of GPs [26, 46, 21, 58, 43] to introduce a strong inductive bias into GPs. This motivated [34] to make these approaches algorithmic, build a mathematical foundation, and show the hidden assumption in previous works of being limited to controllable systems.

This paper overcomes the necessity of approximations, the restriction to systems where initial conditions lead to unique solutions, and the restriction to controllable systems. For that purpose, we algorithmically construct LODE-GPs (Theorem 1), a novel class of GPs whose realizations strictly follow a given system of homogenuous linear ODEs with constant coefficients.

Our construction of LODE-GPs starts by describing our system of ODEs via a so-called operator matrix $A$. Calculating its Smith Normal Form (SNF) gives us a decoupled representation of the system via a diagonal operator matrix $D$, at the cost of going through two invertible base change matrices $U, V$ with the relationship $U \cdot A \cdot V = D$. We can easily construct a multi-output GP $g = \mathcal{GP}(0, k)$ (cf. Lemma 1) with as many outputs as the system channels and whose covariance function encodes the decoupled system. Then, applying the base change matrix $V$ to $g$ yields the pushforward GP $V_* g = \mathcal{GP}(0, V k V')$ whose covariance function encodes the original system, i.e. the LODE-GP. We refer to Theorem 1 and its algorithmic proof for details.

Our paper makes the following contributions:

1. It develops and proves an algorithmic and symbolic construction of LODE-GPs, GPs with the strong inductive bias that their realizations strictly satisfy *any* given system of homogeneous linear ODEs with constant coefficients (see Theorem 1).

2. It demonstrates that the constructed GPs are numerically stable and robust (see Section 5).

3. It automatically includes ODE system parameters as GP parameters, learns them during the training process of the GP, and allows an interpretation of the data (see Subsection 5.2).

4. It provides a free and public implementation based on the GP library GPyTorch[1] [18].

We successfully test our approach on controllable and non-controllable systems of differential equations, with and without system parameters. The LODE-GP strictly satisfies the ODEs and outperforms GPs by several magnitudes in its precision, additionally it correctly reconstructs the system parameters used to generate the data with a small relative error, even despite noise. We also discuss how this strict behavior influences results for metrics like the RMSE with e.g. Figure 4.

## 2   Related Work

Using physical information in ML systems became a central research topic over recent years in both DL and GPs. With the GP research in two important categories: (1) Works that introduce derivative information as inductive bias into the GP [26, 34, 35, 22, 46, 21] and (2) works that train GPs without inductive bias on physical data, with specially selected standard kernels, as an approximate model for additional processing steps [64, 58, 52, 29, 7, 10, 11]. Of all the works on GPs, [34, 35] are the closest to us, as they also provide general algorithms to introduce inductive bias into GPs, based on Gröbner bases. These approaches are only applicable to controllable systems. By basing our algorithm on the SNF instead of Gröbner bases, we overcome this limitation to controllable systems, but are restricted to *ODEs*.

Probabilistic ODE solvers like [47, 30, 57, 8, 38, 48, 49, 10] are able to include inductive bias of ODEs but require a number of complex calculations and some approximations. We avoid any approximation through calculation of the SNF and the application of the pushforward with a linear differential operator. Hence, our work is limited to *linear* ODEs, whereas probabilistic ODE solvers are able to work with non-linear ODEs.

Of the other works that introduce inductive bias, [22] and [46] are the earliest works and already discuss a general formulation of differential equations by viewing derivatives as linear operators that can be applied to GPs. Subsequent works target specific ODEs and create covariance functions with inductive bias [21, 58]. They can be considered special cases of our approach with a specific manually constructed pushforward. Finally, others constructed covariance functions for *partial* differential equations from standard covariance functions with e.g. curl-free behaviour [64] to model

---

[1]github link will be added after acceptance of the paper; code is in the supplmentary material.

physical behaviour [64, 58, 52, 29] or use the GP as a surrogate model to learn physical problems like the inverse pole problem [11] or a variety of applications [7].

Most DL models explore physically informed models through additional loss terms that punish solutions that deviate from the system [59, 33, 44], or in the case of [14] show the equivalence of the loss to their assumed physical behavior. This is often combined with different modifications to the networks like additional features [14] or specific network structures [33].

# 3 Background

## 3.1 Gaussian Processes

A GP $g = \mathcal{GP}(\mu, k)$ defines a probability distribution over the space of functions $\mathbb{R}^d \to \mathbb{R}^\ell$, such that the outputs $g(x_i)$ at any set of $x_i \in \mathbb{R}^d$ are jointly Gaussian [67]. Such a (multi-output) GP is defined by its mean function (often set to zero)

$$\mu : \mathbb{R}^d \to \mathbb{R}^\ell : x \mapsto \mathbb{E}(g(x))$$

and its (multi-output) covariance function (also called kernel)

$$k : \mathbb{R}^d \times \mathbb{R}^d \to \mathbb{R}^\ell_{\succeq 0} : (x, x') \mapsto \mathbb{E}((g(x) - \mu(x))(g(x') - \mu(x'))^T).$$

A popular kernel is the Squared Exponential (SE) kernel $k_{SE}(x, x') = \sigma^2 \exp\left(-\frac{(x-x')^2}{2\ell^2}\right)$. It models smooth data very well and is thus usable for many datasets [67, p. 83], as its realizations are dense in the space of smooth, i.e. infinitely differentiable, functions $C^\infty(\mathbb{R}, \mathbb{R})$ [36, Prop. 1].

Manipulating existing GPs allows to introduce indutive biases in various ways [15, 16, 51, 9, 56]. One important example is the application of matrices of linear operators to a GP. Formally, this is the pushforward operation of an operator matrix $B$ on the GP $g$ as $B_* g = \mathcal{GP}(B\mu(x), Bk(x, x')(B')^T)$ [3], where $B'$ denotes the operation of $B$ on the second argument of $k(x, x')$ [35, Lemma 2.2]. These operators can, for example, be differential operators. The matrix $B$ induces the strong bias such that all realizations lie in the image of $B$. This pushforward is typical for applications in differential equations [26, 34, 35, 22, 46] or geometry [24].

**Example 1.** GPs can be constrained to realizations satisfying a system of linear equations given by a matrix $A$, e.g. $A = \begin{bmatrix} 2 & -3 \end{bmatrix}$

$$\text{sol}_{\mathcal{F}}(A) := \left\{ [f_1(x) \quad f_2(x)]^T \in \mathcal{F}^{2 \times 1} \,\middle|\, A \cdot [f_1(x) \quad f_2(x)]^T = 0 \right\}.$$

with $\mathcal{F} = C^\infty(\mathbb{R}, \mathbb{R})$ the space of smooth input functions. The matrix $B = \begin{bmatrix} 3 \\ 2 \end{bmatrix}$ is maximal in that it solves $A \cdot B = 0$ and hence $\text{sol}_{\mathcal{F}}(A) = B \cdot \mathcal{F} = \{B \cdot f(x) \,|\, f(x) \in \mathcal{F}\}$. Taking a GP prior $g = \mathcal{GP}(0, k)$ for $f(x) \in \mathcal{F}$ and applying the pushforward then yields a new, constrained GP prior

$$B_* g = \mathcal{GP}(0, Bk(B')^T) = \mathcal{GP}\left( \begin{bmatrix} 0 \\ 0 \end{bmatrix}, \begin{bmatrix} 9 \cdot k_{SE} & 6 \cdot k_{SE} \\ 6 \cdot k_{SE} & 4 \cdot k_{SE} \end{bmatrix} \right)$$

for $B \cdot f(x) \in \text{sol}_{\mathcal{F}}(A)$, whose realizations are guaranteed to lie in $\text{sol}_{\mathcal{F}}(A)$.

This example is similar to our use case of systems of differential equations for LODE-GPs, where we just replace the matrix $B$ of numbers with a suitable matrix of differential operators.

## 3.2 Smith normal form

The SNF [50, 40] is a normal form for a matrix $A \in \mathbb{R}[x]^{m \times n}$ over the polynomial ring $\mathbb{R}[x]$, such that $U \cdot A \cdot V = D$. Here, $D \in \mathbb{R}[x]^{m \times n}$ is a (not necessarily square) diagonal matrix of same size as $A$ and the base change matrices $U \in \mathbb{R}[x]^{m \times m}$ and $V \in \mathbb{R}[x]^{n \times n}$ are invertible square matrices, i.e. $\det(U), \det(V) \in \mathbb{R} \setminus \{0\}$ [20, 12]. Algorithms to construct the SNF are implemented in many computer algebra systems such as Matlab [39], Maple [37], or SageMath [55] (based on

Figure 1: A visualization of the bipendulum with its components (rope lengths $\ell_1, \ell_2$) and states (angles $f_1(t)$, $f_2(t)$, rod acceleration $x''(t)$).

PARI [54]) which is a free and open source python library for computer algebra. Intuitively, the SNF can be compared to the eigendecomposition of a $\mathbb{R}^{n \times n}$ matrix, which—if it exists—produces a square matrix of eigenvectors $W$ and the diagonal matrix of eigenvalues $\Lambda$. This analogy is lacking since e.g. the SNF produces two independent base change operator matrices $V$ resp. $U$ instead of a single eigenvector matrix $W$ resp. its inverse $W^{-1}$. Still, the matrix $D$ decouples and thereby simplifies a system given by the input matrix $A$, as does the diagonal eigenvalue matrix $\Lambda$ [45, 12].

Since the SNF exists for matrices over polynomial rings over any field, we can also compute it over a polynomial ring over the function field $\mathbb{R}(a_1, \ldots, a_k)$. Hence, we can model differential equations containing parameters $a_1, \ldots, a_k$. The heating example in Subsection 5.2 demonstrates how such parameters are being used in the SNF and subsequently learned from data.

**Example 2.** A bipendulum acts as our running example. It consists of a rod with a pendulum attached to each end of the rod, see Figure 2. The linearized equations of an idealized bipendulum are

$$\begin{bmatrix} x''(t) + \ell_1 f_1''(t) + g f_1(t) \\ x''(t) + \ell_2 f_2''(t) + g f_2(t) \end{bmatrix} = \mathbf{0} = \underbrace{\begin{bmatrix} \partial_t^2 + \frac{g}{\ell_1} & 0 & -\frac{1}{\ell_1} \\ 0 & \partial_t^2 + \frac{g}{\ell_1} & -\frac{1}{\ell_2} \end{bmatrix}}_{A} \cdot \begin{bmatrix} f_1(t) \\ f_2(t) \\ u(t) \end{bmatrix} \tag{1}$$

with the operator matrix $A$, $\ell_i > 0$ the length of the $i$-th pendulum, $g = 9.81$ the gravitational constant, $u(t) = -x''(t)$ the rod's acceleration, and $f_i(t), i = 1, 2$ the angle between the $i$-th pendulum and the vertical axis. The SNF of a bipendulum reveals its properties, specifically in the cases $\ell_1 = \ell_2$ and $\ell_1 \neq \ell_2$. An algorithm calculates the SNF $D$ of $A$ and the base change matrices $U, V$ as follows:

case $\ell_1 = 1 \neq \ell_2 = 2$:

$$\underbrace{\begin{bmatrix} 1 & 0 \\ -\frac{1}{2} & 1 \end{bmatrix}}_{U} \underbrace{\begin{bmatrix} \partial_t^2 + g & 0 & -1 \\ 0 & \partial_t^2 + \frac{g}{2} & -\frac{1}{2} \end{bmatrix}}_{A} \underbrace{\begin{bmatrix} 0 & -\frac{4}{g} & \frac{2\partial_t^2 + g}{2} \\ 0 & -\frac{2}{g} & \frac{\partial_t^2 + g}{2} \\ -1 & -\frac{4\partial_t^2 + 4g}{g} & (\partial_t^2 + \frac{g}{2})(\partial_t^2 + g) \end{bmatrix}}_{V} = \underbrace{\begin{bmatrix} 1 & 0 & 0 \\ 0 & 1 & 0 \end{bmatrix}}_{D}$$

case $l_1 = l_2 = 1$:

$$\underbrace{\begin{bmatrix} 1 & 0 \\ -1 & 1 \end{bmatrix}}_{U} \underbrace{\begin{bmatrix} \partial_t^2 + g & 0 & -1 \\ 0 & \partial_t^2 + g & -1 \end{bmatrix}}_{A} \underbrace{\begin{bmatrix} 0 & 0 & 1 \\ 0 & 1 & 1 \\ -1 & 0 & \partial_t^2 + g \end{bmatrix}}_{V} = \underbrace{\begin{bmatrix} 1 & 0 & 0 \\ 0 & \partial_t^2 + g & 0 \end{bmatrix}}_{D}$$

In case of unequal rope length, the controllability is intuitive when imagining that, by accelerating the rod at the right time, the two ropes can reach every combination of valid positions. Formally, this follows that $D \cdot [h_1(t) \quad h_2(t) \quad h_3(t)]^T = 0$ if and only if $h_1(t) = h_2(t) = 0$ and $h_3(t)$ is an arbitrarily choosable output. In case of equal rope length, the system is not controllable, indicated by the diagonal entry $\partial_t^2 + g$ of $D$ [41, p. 154].

## 4 Constructing a GP for differential equations

We introduce a polynomial time algorithm to construct LODE-GPs, a class of GPs with realizations dense in the space of solutions of linear ODEs with constant coefficients. This ensures that the LODE-GP is able to produce all possible solutions to the ODEs and nothing but solutions for the ODEs. All this is guaranteed to be strictly accurate, since we make no approximations.

Consider a system of linear homogenous ordinary differential equations with constant coefficients

$$A \cdot \mathbf{f}(t) = 0 \tag{2}$$

with operator matrix $A \in \mathbb{R}[\partial_t]^{m \times n}$ determining the relationship between the smooth functions $f_i(t) \in C^\infty(\mathbb{R}, \mathbb{R})$ of $\mathbf{f}(t) = (f_1(t) \quad \dots \quad f_n(t))^T$. For such systems our main result holds.

**Theorem 1.** *(LODE-GPs) For every system as in Equation* (2) *there exists a GP $g$, such that the set of realizations of $g$ is dense in the set of solutions of $A \cdot \mathbf{f}(t) = 0$.*

The following lemma play a crucial role in the proof of this theorem by constructing base covariance functions for a system as in Equation (2) that is *decoupled* (via the SNF) into scalar equations.

**Lemma 1.** *Covariance functions for solutions of the scalar linear differential equations $d \cdot f = 0$ with constant coefficients, i.e. $d \in \mathbb{R}[\partial_t]$, are given by Table 1 for $d$ is primary, i.e. a power of an irreducible real polynomial. In the case of a non-primary $d$, each primary factor $d_i$ of $d = \prod_{i=0}^{\ell-1} d_i$ is first translated to its respective covariance function $k_i$ separately before they are added up to give the full covariance function $k(t_1, t_2) = \sum_{i=0}^{\ell-1} k_i(t_1, t_2)$.*

Table 1: Primary operators $d$ and their corresponding covariance function $k(t_1, t_2)$.

| $d$ | $k(t_1, t_2)$ |
|---|---|
| $1$ | $0$ |
| $(\partial_t - a)^j$ | $\left(\sum_{i=0}^{j-1} t_1^i t_2^i\right) \cdot \exp(a \cdot (t_1 + t_2))$ |
| $((\partial_t - a - ib)(\partial_t - a + ib))^j$ | $\left(\sum_{i=0}^{j-1} t_1^i t_2^i\right) \cdot \exp(a \cdot (t_1 + t_2)) \cdot \cos(b \cdot (t_1 - t_2))$ |
| $0$ | $\exp(-\frac{1}{2}(t_1 - t_2)^2)$ |

For the case of single (i.e. $j = 1$) zeroes, the sum in the covariance function simplifies to a factor 1.

*Proof.* Proof of Theorem 1 We begin with a neutral multiplication of $A \cdot \mathbf{f} = 0$ with $V \cdot V^{-1}$ and a left multiplication by $U$ to decouple the system using the SNF $D = U \cdot A \cdot V$ (cf. Equation (2)):

$$
\begin{aligned}
& U \cdot A \cdot V \cdot V^{-1} \cdot \mathbf{f} = 0 \\
\Leftrightarrow \quad & D \cdot V^{-1} \cdot \mathbf{f} = 0 \\
\Leftrightarrow \quad & D \cdot \mathbf{p} = 0 \\
\Leftrightarrow \quad & \bigwedge_{i=1}^{\min(n,m)} D_{i,i} \cdot \mathbf{p}_i = 0 \quad \wedge \quad \bigwedge_{i=\min(n,m)+1}^{n} 0 \cdot \mathbf{p}_i = 0
\end{aligned} \tag{3}
$$

for decoupled latent vector $\mathbf{p} = V^{-1}\mathbf{f}$ of functions.

We assume the GP-prior $h \sim \mathcal{GP}(\mathbf{0}, k)$ for this vector $\mathbf{p}$ via a GP, where $k$ is a multi-output diagonal covariance function such that each diagonal entry of $k$ is given by Lemma 1. By this Lemma, the set of realizations of this prior $h$ is dense in the set of solutions of $D \cdot \mathbf{p} = 0$.

The pushforward of $h$ with $V$ yields a GP $g$ that can learn the original system of ODEs.

$$g \sim V_* h = \mathcal{GP}(\mathbf{0}, V \cdot k \cdot V') \tag{4}$$

with $V' = V^T$ the operation applied on the second entry of the kernel (i.e. $t_2$) using [35, Lemma 2.2]. As $V$ is invertible, the set of realizations of $g$ is dense in the set of solutions of $A \cdot \mathbf{f} = 0$. $\qquad \square$

This proof shows that diagonalizing the system to $D \cdot \mathbf{p} = 0$ decouples the components of $\mathbf{p}$ to expose the intrinsic behavior of the system. We can also easily interpret the controllability of a system in this decoupled form. A zero column (or $0 \cdot \mathbf{p}_i = 0$) stands for a freely choosable function in $\mathbf{p}$, i.e. an output of the system. A one in a column (or $1 \cdot \mathbf{p}_i = 0$) stands for something we have no choice in, e.g. an input or a state that is fixed once the desired output was chosen. Any other entry leads to sinusoidal-exponential behavior, which is uncontrollable in the sense that it cannot be influenced. Summing up, a system is controllable if and only if all diagonal entries of $D$ are either zero or one.

This paper improves upon [34] for two reasons: first, it decouples the uncontrollable part of a system via the SNF as a direct summand and, second, it constructs a covariance function for this uncontrollable summand. This is generally impossible for partial differential equations due to [2, 42].

The runtime of the construction of LODE-GPs in Theorem 1 is dominated by computing the SNF. This has a deterministic polynomial complexity in the size of the (usually small) operator matrices $A$ [60, 62, 32, 66] with quicker probabilistic Las Vegas algorithms [53], and it can be parallelized [61, 63]. For our examples, the SNF terminates instantaniously. The application of the base change matrix $V$ is cubic in the (usually small) size of matrices, assuming constant time to apply operators to the covariance functions from Lemma 1. Once the covariance function is constructed, the complexity of $\mathcal{O}(n^3)$ for GPs applies, where $n$ is the (potentially big) number of data points.

**Example 3.** We continue Example 2 and consider the SNF of the bipendulum for $l_1 \neq l_2$. Since the three diagonal entries of the matrix $D$ are $1, 1, 0$ we conclude that the latent kernel $k$ has diagonal entries $0, 0, \mathrm{k_{SE}}$ with Lemma 1. Now the pushforward creates the LODE-GP, which requires the following application of two operator matrices; we simplify by removing irrelevant zeroes of the latent covariance.

$$VkV' = \begin{bmatrix} \frac{2\partial_{t_1}^2 + g}{2} \\ \frac{\partial_{t_1}^2 + g}{2} \\ (\partial_{t_1}^2 + \frac{g}{2})(\partial_{t_1}^2 + g) \end{bmatrix} \cdot [\mathrm{k_{SE}}] \cdot \begin{bmatrix} \frac{2\partial_{t_2}^2 + g}{2} & \frac{\partial_{t_2}^2 + g}{2} & (\partial_{t_2}^2 + \frac{g}{2})(\partial_{t_2}^2 + g) \end{bmatrix}$$

Applying these two operators to the kernel $\mathrm{k_{SE}}$ results in the covariance function for the bipendulum.

# 5 Experimental evaluation

Table 2: The median results for the training and evaluation RMSE, the loss value and the mean ODE satisfaction error, over ten training iterations for the GP and LODE-GP on noisy training data. The mean ODE error is the average of each ODE error of a system, e.g. the average of the two ODE errors for the bipendulum system. The RMSEs were calculated with noiseless data in the training and evaluation interval, the ODE error only with the latter, for each respective experiment.

|  |  | training RMSE | evaluation RMSE | loss | mean ODE error |
|---|---|---|---|---|---|
| Bipendulum | LODE-GP | **0.006** | 0.231 | **-2.145** | **2.01e-06** |
|  | GP | 0.011 | **0.028** | -1.995 | 0.058 |
| Heating | LODE-GP | **0.008** | **0.188** | **-2.084** | **0.005** |
|  | GP | 0.010 | 0.365 | -1.564 | 0.262 |
| Three tank | LODE-GP | **0.026** | 0.089 | -0.961 | **1.25e-05** |
|  | GP | 0.029 | **0.057** | **-0.992** | 0.041 |

We demonstrate the effectiveness of LODE-GPs in three examples. The Gröbner basis approach of [34] yields precisely the same results for the two controllable examples and is not applicable to the uncontrollable example. No other state of the art in probabilistic ML exists for our class of differential equations,[2] which leaves us with only classic GPs for comparison.

---

[2]E.g. probabilistic ODE solvers are not applicable to systems with free functions in their solution set.

Figure 2: A posterior LODE-GP trained on noisy bipendulum data (black stars), its confidence (blue transparent), posterior mean (blue dashed line) and the original noise-free function (red line). The posterior mean fits the original data very well and shows that the behavior is learned despite noise.

Figure 3: The error in satisfying the bipendulum ODEs in Equation (1) for a GP (top) and LODE-GP (bottom), for noisy training data. The green dashed line shows the error of a solution in symbolic form. The low error shows that the LODE-GP strictly satisfies the ODEs, up to numerical precision.

Our comparison includes the error in satisfying the ODEs, specified by the median error the GPs posterior mean function has in satisfying the ODEs at evenly spread points, where we calculate derivatives through finite differences. All experiments ran numerically stable and robust using Adam [28]. The LODE-GPs hyperparameters (lengthscale and signal variance) are randomly initialized from a uniform distribution on $[-3, 3]$. The 25 training datapoints are created uniformly in the intervals $[1, 6]$ and $[-5, 5]$ for the bipendulum and three tank system, resp. the heating system. Training and evaluation is repeated ten times in each experiment using a GPyTorch [18] implementation of our LODE-GP construction with SageMath [55] to symbolically calculate the SNF. The training loss is the marginal log likelihood (c.f. [67, Eq. (2.30)]) which, in GPyTorch, is additionally divided by the number of training data points. Details of the training, data generation, verification process, additional experiments, e.g. without noise, and further system details can be found in the appendix.

## 5.1 Bipendulum - Controllable

We continue with the controllable variant of the bipendulum from Example 2 with the rope lengths $\ell_1 = 1$ and $\ell_2 = 2$. We create 25 points of training data from a solution of the ODEs as shown in Figure 2. We add white noise to the data with standard deviation of 2% of the maximal signal.

Figure 3 compares the error in satisfying the ODE of a LODE-GP and a GP. The LODE-GP is producing samples that satisfy the ODE with a median error[3] of 2e−6, for both differential equations. In comparison, the *symbolically computed solution* used to generate the training data, has an error of 1.75e−7, only one order of magnitude better than the LODE-GP. Hence, we conclude that, up to numerical precision, the LODE-GP produces samples that strictly satisfy the ODE, whereas regression models like GPs do not satisfy the differential equations. The LODE-GP produces roughly 30000 times more precise samples (0.06 to 2e−6) and deviates only slightly from this error.

Further we investigate the RMSE of the models by comparing their posterior mean to noiseless data in the training and evaluation intervals. The LODE-GP RMSE mostly performs similar compared

---

[3]The LODE-GPs trains into a local minimum at its value $10^{-10}$, with high lengthscale and miniscule signal variance. This models constant zero behaviour which satisfies the ODEs, but does not fit the training data.

Figure 4: The posterior mean functions of a LODE-GP (left) and a GP (right) trained on the bipendulum data as described in the text.

Figure 5: (left) A visualization of the heating system with input $u(t)$ and states $f_1(t)$, $f_2(t)$. (right) A solution of the differential equations, which are used to create the data.

to the GP RMSE (see Table 2). For the training interval, the LODE-GP achieves basically the same performance as the GP. For the evaluation interval the performance worsens due to a SE GP extrapolating to its (constant zero) prior mean. The GP can easily reach this mean zero, by smoothly modifying all channels without regard for the system equations. Since the ODE solution also approaches zero, this leads to a small error in extrapolation. The LODE-GP has to satisfy the system equations to move the mean function back to mean zero. Hence, the system produces a large spike[4] in the input channel $u(t)$, before the system can reach mean zero. This can be seen in Figure 4.

We additionally analyse the training runtime and see that the LODE-GP is as fast as the GP during the $\mathcal{O}(n^3)$ model inference and slower by only a factor smaller than two in the $\mathcal{O}(n^2)$ covariance matrix calculation.

## 5.2 Heating system - Controllable with parameters

In this experiment we use a parameterized heating system to show that a LODE-GP can learn physically interpretable system parameters during GP hyperparameter training. The controllable heating system is depicted in Figure 5. It uses an input $u(t)$ to control a heating element $f_1(t)$ which exchanges heat with an object $f_2(t)$. Two physical parameters $a$ and $b$ determine how quickly the heat moves between the objects according to the ODEs:

$$f_1'(t) = -a \cdot (f_1(t) - f_2(t)) + u(t)$$
$$f_2'(t) = -b \cdot (f_2(t) - f_1(t))$$

We generate training data using a solution of the differential equation (see Figure 5) with parameter values $a = 3, b = 1$. The LODE-GP can be constructed using parameters.

Learning the physical parameters $a$ and $b$ reconstructs the original values successfully with a maximal relative error of less than 2.8% in ten training runs on data without noise. After adding white

---

[4]The third data channel is particularly large due to its additional factor of $g = 9.81$, which has a different scale by an order of magnitude as the otherwise small data.

Figure 6: (left) A sketch of the three tank system and (right) a solution of the system.

noise to the data with standard deviation of 1% of the maximal signal, the parameters were successfully reconstructed with a maximal relative error of 5.3% in ten training runs. Again, the LODE-GP satisfies the original ODEs (with parameters $a = 3$ and $b = 1$) with an median error of $5\mathrm{e}{-}3$, trained on the noisy data. This is bigger than in the previous example, as the LODE-GP only uses approximate parameter values for $a$ and $b$, but still smaller than the error of a GP of $0.26$. Our interpretation of these results is that the LODE-GP can learn the physically interpretable parameters.

### 5.3 Three tank system - Non-controllable

We conclude the experiments with a non-controllable fluid system where the water level in three tanks is changed by two pipes. The system is non-controllable due to pipes' overlap over the center tank, whose changes directly affect the other tanks. This system requires multiple non-zero covariance functions in the latent GP to describe both the non-controllable subsystem and the two degrees of freedom, which corresponds to the columns of the SNFs matrix $D$ via Lemma 1:

$$D = \begin{bmatrix} 1 & 0 & 0 & 0 & 0 \\ 0 & 1 & 0 & 0 & 0 \\ 0 & 0 & -\partial_t & 0 & 0 \end{bmatrix}$$

We use a solution to the system of ODEs (see Figure 6) to generate 25 datapoints, to which we add white noise with standard deviation of 10% of the maximal signal.

The system ODEs are again strictly satisfied by the LODE-GP with a median error of $1\mathrm{e}{-}5$ in each ODE. Hence, LODE-GP can handle larger, non-controllable systems of ODEs, despite high noise.

## 6 Conclusion

In this paper we have introduced an algorithmical approach to automatically and symbolically create LODE-GP, a class of covariance functions for GPs such that their realizations strictly follow a given system of linear homogeneous ODEs. We have proven that this approach is mathematically sound and verified its effectiveness in experiments. We have demonstrated that the learned posterior mean strictly satisfies the given system of ODEs up to numerical precision and discussed the consequences of this strict behavior e.g. in their extrapolation, leading to drastic behavior when both following the ODEs and going back to the prior mean. Additionally, we automatically trained the physically interpretable parameters of the system and were able to reconstruct their original values with low relative error. The runtime of the LODE-GP is still asymptotically dominated by the $\mathcal{O}(n^3)$ Cholesky decomposition of the covariance matrix, despite bigger constants in the $\mathcal{O}(n^2)$ part of constructing the covariance matrix and a (usually very small) constant time precomputation of the covariance function. Of course, approximate GPs are applicable to our covariance functions. Beyond applications where the dynamic behavior is known through corresponding ODEs, the combination with kernel search methods [27, 16, 25, 5, 4] has the potential to detect unknown dynamical behavior in data by systematic exploration and use these findings to generate new interpretable knowledge about the data through the corresponding system.

## References

[1] William A Adkins and Mark G Davidson. Linear systems of differential equations. In *Ordinary Differential Equations*, pages 629–721. 2012.

[2] Mohamed Barakat. Purity Filtration and the Fine Structure of Autonomy. In *Proceedings of the 19th International Symposium on Mathematical Theory of Networks and Systems*, 2010.

[3] Alain Berlinet and Christine Thomas-Agnan. *Reproducing kernel Hilbert spaces in probability and statistics*. Springer Science & Business Media, 2011.

[4] Fabian Berns and Christian Beecks. Automatic Gaussian process model retrieval for big data. In *Proceedings of the 29th ACM International Conference on Information & Knowledge Management*, 2020.

[5] Fabian Berns, Kjeld Schmidt, Ingolf Bracht, and Christian Beecks. 3cs algorithm for efficient Gaussian process model retrieval. In *2020 25th International Conference on Pattern Recognition (ICPR)*, 2021.

[6] Yves Bertin, Etienne Videcoq, Sophie Thieblin, and Daniel Petit. Thermal behavior of an electrical motor through a reduced model. *IEEE Transactions on energy conversion*, 15(2): 129–134, 2000.

[7] Ilias Bilionis, Nicholas Zabaras, Bledar A Konomi, and Guang Lin. Multi-output separable Gaussian process: Towards an efficient, fully Bayesian paradigm for uncertainty quantification. *Journal of Computational Physics*, 241:212–239, 2013.

[8] Nathanael Bosch, Philipp Hennig, and Filip Tronarp. Calibrated adaptive probabilistic ODE solvers. In *AISTATS*, 2021.

[9] Roberto Calandra, Jan Peters, Carl Edward Rasmussen, and Marc Peter Deisenroth. Manifold Gaussian processes for regression. In *International Joint Conference on Neural Networks (IJCNN)*, 2016.

[10] Ben Calderhead, Mark Girolami, and Neil D Lawrence. Accelerating Bayesian inference over nonlinear differential equations with Gaussian processes. *NeurIPS*, 2009.

[11] Kian Chai, Christopher Williams, Stefan Klanke, and Vijayakumar Sethu. Multi-task Gaussian process learning of robot inverse dynamics. *NeurIPS*, 2008.

[12] Thomas Cluzeau, Victorita Dolean, Frédéric Nataf, and Alban Quadrat. Symbolic preconditioning techniques for linear systems of partial differential equations. 2011. URL `https://hal.archives-ouvertes.fr/hal-00664092`.

[13] Michiel JL De Hoon, Seiya Imoto, Kazuo Kobayashi, Naotake Ogasawara, and Satoru Miyano. Inferring gene regulatory networks from time-ordered gene expression data of bacillus subtilis using differential equations. In *Biocomputing 2003*, pages 17–28.

[14] Claudia Drygala, Benjamin Winhart, Francesca di Mare, and Hanno Gottschalk. Generative modeling of turbulence. *Physics of Fluids*, 34(3):035114, 2022.

[15] David Duvenaud. *Automatic model construction with Gaussian processes*. PhD thesis, University of Cambridge, 2014.

[16] David Duvenaud, James Lloyd, Roger Grosse, Joshua Tenenbaum, and Ghahramani Zoubin. Structure discovery in nonparametric regression through compositional kernel search. In *ICML*, 2013.

[17] Duccio Fanelli and Francesco Piazza. Analysis and forecast of covid-19 spreading in china, italy and france. *Chaos, Solitons & Fractals*, 134:109761, 2020.

[18] Jacob R Gardner, Geoff Pleiss, David Bindel, Kilian Q Weinberger, and Andrew Gordon Wilson. Gpytorch: Blackbox matrix-matrix gaussian process inference with gpu acceleration. In *Advances in Neural Information Processing Systems*, 2018.

[19] Alexandra Goeke, Christian Schilli, Sebastian Walcher, and Eva Zerz. Computing quasi-steady state reductions. *Journal of Mathematical Chemistry*, 50(6):1495–1513, 2012.

[20] Laurenz Göllmann. *Lineare Algebra.* Springer, 2017.

[21] Ítalo Gomes Gonçalves, Felipe Guadagnin, Sissa Kumaira, and Saulo Lopes Da Silva. A machine learning model for structural trend fields. *Computers & Geosciences*, 149:104715, 2021.

[22] Thore Graepel. Solving noisy linear operator equations by Gaussian processes: Application to ordinary and partial differential equations. In *ICML*, 2003.

[23] Tanja Hernández Rodríguez, Anton Sekulic, Markus Lange-Hegermann, and Björn Frahm. Designing robust biotechnological processes regarding variabilities using multi-objective optimization applied to a biopharmaceutical seed train design. *Processes*, 10(5):883, 2022.

[24] Michael Hutchinson, Alexander Terenin, Viacheslav Borovitskiy, So Takao, Yee Teh, and Marc Deisenroth. Vector-valued Gaussian processes on Riemannian manifolds via gauge independent projected kernels. *NeurIPS 2021*, 34, 2021.

[25] Jan David Hüwel, Fabian Berns, and Christian Beecks. Automated kernel search for Gaussian processes on data streams. In *2021 IEEE International Conference on Big Data (Big Data)*, 2021.

[26] Carl Jidling, Niklas Wahlström, Adrian Wills, and Thomas B Schön. Linearly constrained Gaussian processes. In *NeurIPS 2017*, 2017.

[27] Hyunjik Kim and Yee Whye Teh. Scaling up the automatic statistician: Scalable structure discovery using Gaussian processes. In *AISTATS*, 2018.

[28] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *ICLR*, 2015.

[29] Edgar D Klenske, Melanie N Zeilinger, Bernhard Schölkopf, and Philipp Hennig. Gaussian process-based predictive control for periodic error correction. *IEEE Transactions on Control Systems Technology*, 24(1):110–121, 2015.

[30] Nicholas Krämer and Philipp Hennig. Linear-time probabilistic solution of boundary value problems. *NeurIPS*, 2021.

[31] Naresh Kumar and Seba Susan. COVID-19 pandemic prediction using time series forecasting models. In *International Conference on Computing, Communication and Networking Technologies (ICCCNT)*, 2020.

[32] Salah Labhalla, Henri Lombardi, and Roger Marlin. Algorithmes de calcul de la réduction de hermite d'une matrice à coefficients polynomiaux. *Theoretical Computer Science*, 161(1-2): 69–92, 1996.

[33] Isaac E Lagaris, Aristidis C Likas, and Dimitris G Papageorgiou. Neural-network methods for boundary value problems with irregular boundaries. *IEEE Transactions on Neural Networks*, 11(5):1041–1049, 2000.

[34] Markus Lange-Hegermann. Algorithmic linearly constrained Gaussian processes. In *NeurIPS 2018*, pages 2141–2152, 2018.

[35] Markus Lange-Hegermann. Linearly constrained Gaussian processes with boundary conditions. In *AISTATS*, 2021.

[36] Markus Lange-Hegermann and Daniel Robertz. On boundary conditions parametrized by analytic functions. *arXiv:2205.03185*, 2022.

[37] Maplesoft, a division of Waterloo Maple Inc.. Maple.

[38] Alonso Marco, Philipp Hennig, Jeannette Bohg, Stefan Schaal, and Sebastian Trimpe. Automatic LQR tuning based on Gaussian process optimization: Early experimental results. In *Second Machine Learning in Planning and Control of Robot Motion Workshop at International Conference on Intelligent Robots and Systems*, 2015.

[39] MATLAB. The MathWorks Inc., Natick, Massachusetts.

[40] Morris Newman. The Smith normal form. *Linear algebra and its applications*, 254(1-3):367–381, 1997.

[41] Ulrich Oberst. Multidimensional constant linear systems. *Acta Applicandae Mathematica*, 20 (1):1–175, 1990.

[42] Alban Quadrat. Grade Filtration of Linear Functional Systems. *Acta Appl. Math.*, 127:27–86, 2013.

[43] Maziar Raissi, Paris Perdikaris, and George Em Karniadakis. Machine learning of linear differential equations using Gaussian processes. *Journal of Computational Physics*, 348:683–693, 2017.

[44] Maziar Raissi, Paris Perdikaris, and George E Karniadakis. Physics-informed neural networks: A deep learning framework for solving forward and inverse problems involving nonlinear partial differential equations. *Journal of Computational physics*, 378:686–707, 2019.

[45] Daniel Robertz. *Formal computational methods for control theory*. PhD thesis, RWTH Aachen University, 2006.

[46] Simo Särkkä. Linear operators and stochastic partial differential equations in Gaussian process regression. In *International Conference on Artificial Neural Networks*, pages 151–158, 2011.

[47] Jonathan Schmidt, Nicholas Krämer, and Philipp Hennig. A probabilistic state space model for joint inference from differential equations and data. *NeurIPS 2021*, 34, 2021.

[48] Michael Schober, David K Duvenaud, and Philipp Hennig. Probabilistic ODE solvers with Runge-Kutta means. *NeurIPS 2014*, 27, 2014.

[49] Michael Schober, Simo Särkkä, and Philipp Hennig. A probabilistic model for the numerical solution of initial value problems. *Statistics and Computing*, 29(1):99–122, 2019.

[50] Henry John Stephen Smith. I. on systems of linear indeterminate equations and congruences. *Proceedings of the Royal Society of London*, (11):86–89, 1862.

[51] Edward Snelson, Zoubin Ghahramani, and Carl Rasmussen. Warped Gaussian processes. *NeurIPS*, 2003.

[52] Arno Solin, Manon Kok, Niklas Wahlström, Thomas B Schön, and Simo Särkkä. Modeling and interpolation of the ambient magnetic field by Gaussian processes. *IEEE Transactions on robotics*, 34(4):1112–1127, 2018.

[53] Arne Storjohann and George Labahn. A fast Las Vegas algorithm for computing the Smith normal form of a polynomial matrix. *Linear Algebra and its Applications*, 253(1-3):155–173, 1997.

[54] *PARI/GP version 2.11.2*. The PARI Group, Univ. Bordeaux, 2019. available from `http://pari.math.u-bordeaux.fr/`.

[55] The Sage Developers. *SageMath, the Sage Mathematics Software System (Version 9.4)*, 2021. available from `https://www.sagemath.org`.

[56] Silja Thewes, Markus Lange-Hegermann, Christoph Reuber, and Ralf Beck. Advanced Gaussian process modeling techniques. *Design of Experiments (DoE) in Engine Development. Expert Verlag*, 2015.

[57] Filip Tronarp, Simo Särkkä, and Philipp Hennig. Bayesian ode solvers: The maximum a posteriori estimate. *Statistics and Computing*, 31(3):1–18, 2021.

[58] Selvakumar Ulaganathan, Ivo Couckuyt, Tom Dhaene, Joris Degroote, and Eric Laermans. Performance study of gradient-enhanced Kriging. *Engineering with computers*, 32(1):15–34, 2016.

[59] B Ph van Milligen, V Tribaldos, and JA Jiménez. Neural network differential equation and plasma equilibrium solver. *Physical review letters*, 75(20):3594, 1995.

[60] Gilles Villard. Computation of the Smith normal form of polynomial matrices. In *International symposium on Symbolic and algebraic computation*, pages 209–217, 1993.

[61] Gilles Villard. Fast parallel computation of the Smith normal form of polynomial matrices. In *International symposium on Symbolic and algebraic computation*, pages 312–317, 1994.

[62] Gilles Villard. Generalized subresultants for computing the Smith normal form of polynomial matrices. *Journal of Symbolic Computation*, 20(3):269–286, 1995.

[63] Gilles Villard. Fast parallel algorithms for matrix reduction to normal forms. *Applicable Algebra in Engineering, Communication and Computing*, 8(6):511–537, 1997.

[64] Niklas Wahlström, Manon Kok, Thomas B Schön, and Fredrik Gustafsson. Modeling magnetic fields using Gaussian processes. In *2013 IEEE International Conference on Acoustics, Speech and Signal Processing*, pages 3522–3526, 2013.

[65] Peter J Wangersky. Lotka-volterra population models. *Annual Review of Ecology and Systematics*, 9(1):189–218, 1978.

[66] Jon Wilkening and Jia Yu. A local construction of the Smith normal form of a matrix polynomial. *Journal of Symbolic Computation*, 46(1):1–22, 2011.

[67] Christopher K Williams and Carl Edward Rasmussen. *Gaussian processes for machine learning*. MIT press Cambridge, MA, 2006.

[68] Eva Zerz. *Topics in Multidimensional Linear Systems Theory*, volume 256 of *Lecture Notes in Control and Information Sciences*. London, 2000.