Learning Responsive Bayesian Networks
Submission #9689

Abstract

We propose new methods for learning a Bayesian network (BN) that admits reliably fast exact reasoning. We utilize a more fine-grained measure for the BN's reasoning complexity than the standard treewidth measure, thereby accommodating the possibility that variables range over domains of different sizes. Our methods combine heuristic Bayesian network structure learning algorithms with the recently introduced Max-SAT-based local improvement method (Peruvemba Ramaswamy and Szeider, AAAI'21). Our experiments show that our new learning methods reliably provide BNs that are significantly more responsive than BNs provided by treewidth-based methods.

1 Introduction

The time complexity of probabilistic reasoning on a Bayesian Network (BN) is dominated by the *maximum state space size* of clusters (i.e., bags of the BN's tree decomposition [Lauritzen and Spiegelhalter, 1988, Dechter, 1999, Kask et al., 2011]; a bag's state space size is the product of the domain sizes of all the variables it contains). We propose algorithms for learning BNs from data, keeping the state space size within a user-specified bound. This results in *responsive* BNs, i.e., BNs reliably admitting fast probabilistic reasoning. We compare our algorithms to the baseline of state-of-the-art bounded treewidth BN learning algorithms, on real-world benchmark data sets, with up to over a thousand variables. The results show a clear advantage for new bounded state space (*bss*) algorithms.

For our bss BN structure learning algorithms, we build upon recent work on bounded treewidth BN structure learning, in particular on the heuristic algorithms k-greedy and k-MAX by Scanagatta et al. [2016, 2018] as well BN-SLIM by Peruvemba Ramaswamy and Szeider [2021]. The latter is a post-processing algorithm which uses MaxSAT to improve BNs generated by the heuristics. All these algorithms assume a user-specified upper bound k for the treewidth of the learned BN, and optimize the BN's score under the given treewidth bound. The learning algorithms are highly optimized for dealing with large instances, and so the generalization of treewidth bounds to state space bounds isn't straightforward. The main challenge for extending BN-SLIM to bss learning is to replace BN-SLIM's simple cardinality constraints with a MaxSAT encoding that bounds the state-space of a bag, i.e., a product of integers. We achieve this, by switching to logarithms, and bounding the sum of real numbers, utilizing a MaxSAT encoding based on *binary decision diagrams (BDDs)*.

We consider several variants of bss learning algorithms, tested them on 16 real-world benchmark data sets with up to 1041 variables and compared them with bounded treewidth BN learning algorithms. For the comparison, we put pairs of scatter plots side by side, which show the tradeoff between responsiveness (reasoning speed) and data-fitting (score), one for the baseline methods and one for the bounded state space methods. The latter show a better performance throughout, with significantly higher reliability (small variance).

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

1.1 Related work

We discuss related work in terms of Figure 1. In approaches (a) and (b), the BN has already been

Figure 1: Various approaches to BN structure learning

learned by some other method, and one tries to find a tree decomposition that minimizes either the treewidth or the maximum state space size, respectively. For approach (a), general purpose tree decomposition algorithms can be applied, such as the one by Gogate and Dechter [2004]. As the significance of the state space of BNs was recognized [Lauritzen and Spiegelhalter, 1988], the research focused on approach (b) [Kask et al., 2011, Kærulff, 1992, Meila and Jordan, 1996, Otten and Dechter, 2008a,b]. However, once the BN has been fixed, the impact of the decomposition method is limited. Therefore, the research in the last decade focused on approach (c), where a treewidth bound is already considered during the BN learning; a suitable decomposition is produced simultaneously. On the one hand, exact learning algorithms have been proposed which scale only to small instances but find score-optimal BNs [Korhonen and Parviainen, 2013, Parviainen et al., 2014, Berg et al., 2014]; on the other hand, heuristic algorithms have been proposed, that scale to large instances but do not guarantee score optimality [Nie et al., 2015, 2016, Scanagatta et al., 2016, 2018, Benjumeda et al., 2019]. Very recently, Peruvemba Ramaswamy and Szeider [2021] proposed the hybrid approach BN-SLIM, which improves the score of a heuristically computed BN by multiple applications of a MaxSAT-based exact method.

In this paper, we follow for the first time approach (d) and implement it via various scalable algorithms. In our experiments, we compare approaches (c), and (d) in terms of the achieved score and responsiveness.

2 Preliminaries

2.1 Graphs and Digraphs

We consider both undirected and directed graphs G, where $V(G)$ denotes the set of vertices and $E(G)$ the set of edges of G, respectively. If G is directed, we refer to its edges as arcs. A directed graph is a DAG if it doesn't contain any directed cycles.

2.2 Structure learning

Assume we are given a data set of samples $D_1, \ldots, D_N$ over n categorical random variables, each variable v ranging over a domain of $\mathrm{ds}(v)$ many discrete values. The goal of the BN structure learning problem is to find a DAG D whose vertices are the random variables that fits the data best. The fitting is modelled by means of a real-valued *score function*. The BN is formed by the DAG D together with local parameters [Koller and Friedman, 2009]. More precisely, the score function f assigns each node $v \in V(D)$ and each subset $P \subseteq V \setminus \{v\}$ the *score* $f_P(v)$ of P for v. Let $P_D(v) = \{u \in V : (u, v) \in E\}$ denote the parent set of v in D. The score $f(D)$ of D is the sum of $f(v, P_D(v))$ over all $v \in V(D)$. Score functions defined in such a way (decomposable score functions) accommodate popular scores like AIC, BDeu, and BIC [Akaike, 1974, Heckerman et al., 1995, Schwarz, 1978]. A *score function cache* is obtained from a score function by disregarding any potential parent set P' of a node v if $f(v, P') \leq f(v, P)$ for another potential parent sets of v

73 with $P \subsetneq P'$. Consequently, a score function cache does not consider a nonempty potential parent
74 set if its score doesn't exceed the score of the empty parent set.

2.3 Tree Decomposition

76 Consider an undirected graph G. A *tree decomposition* $\mathcal{T}$ of G is a pair (T, χ), consisting of a tree T
77 and a mapping $\chi : V(T) \to 2^{V(G)}$, where the set $\chi(t)$ is called a *bag*, with the following properties.
78 1. For every edge $e \in E(G)$ there is some $t \in V(T)$ such that $e \subseteq \chi(t)$.
79 2. For every vertex $v \in V(G)$, the set $\{ t \in V(T) : v \in \chi(t) \}$ induces a non-empty subtree of T.

80 The *moralized graph* $M(D)$ of a DAG D is defined by $V(M(D)) = V(D)$ and $E(M(D)) =$
81 $\{ \{u, v\} : (u, v) \in E(D) \} \cup \{ \{u, v\} : (u, w), (v, w) \in E(D), u \neq v \}$. A tree decomposition
82 of a DAG is a tree decomposition of its moralized graph. A tree decomposition of a BN is a tree
83 decomposition of its underlying DAG.

3 Treewidth and Maximum State Space Size

85 In this section we discuss the different metrics that can be used to estimate the responsiveness of a
86 BN along with some empirical findings.

87 Consider a tree decomposition $\mathcal{T} = (T, \chi)$ of a DAG D, where $V(D)$ consists of random variables,
88 each $v \in V(D)$ ranging over a set of $\mathrm{ds}(v)$ many discrete values.

89 The *width* of $\mathcal{T}$ is

$$\max_{t \in V(T)} |\chi(t)| - 1,$$

i.e., is the size of a largest bag minus 1. The *treewidth* $\mathrm{tw}(D)$ of D is the minimum width over all tree decompositions of $M(D)$.

The *maximum state space size* of $\mathcal{T}$ is

$$\max_{t \in V(T)} \prod_{v \in \chi(t)} \mathrm{ds}(v),$$

i.e., largest state space size of all bags, where the state space of a bag is the product of the domain sizes of the variables it contains. The *maximum state space size* $\mathrm{msss}(D)$ of a D is the minimum msss over all tree decompositions of $M(D)$.

90 The maximum state space of a *binary* BN of treewidth t is 2^{t+1}. The *bounded treewidth (state space,*
91 *respectively) BN structure learning problem* takes as input a set V of nodes (i.e., random variables), a
92 decomposable score function f on V, and an integer k, and asks to compute a DAG D with $V(D) =$
93 V of treewidth (maximum state space size, respectively) at most k, with a maximal score $f(D)$.

3.1 Empirical influence on responsiveness

95 The complexity results for probabilistic reasoning (inference) suggest for BNs containing non-binary
96 variables, the maximum state space size is more accurate prediction for responsiveness than treewidth
97 [Lauritzen and Spiegelhalter, 1988, Dechter, 1999, Kask et al., 2011].

98 The aim of our initial experiments was to verify this theoretical assumption empirically. For this
99 purpose, we generated several BNs with varying treewidths and maximum state space sizes and
100 analyzed their relation to the BN's responsiveness. We define the *reasoning time* of a BN to be the
101 time required for computing the probability of evidence of 5 random variables set to random states,
102 averaged over 100 runs (same as [Scanagatta et al., 2016]). For more details on the experimental
103 setup, we refer to Section 5.

104 In Figure 2 we depict the distribution of the observed reasoning times for different treewidths and
105 maximum state space size ranges by means of boxplots, with dots signifying outliers. We can clearly
106 see that the correlation between reasoning time and maximum state space size is much stronger than
107 the correlation between reasoning time and treewidth. The number of outliers is much higher in the
108 treewidth plot as compared to the maximum state space size plot. Furthermore, for gradually increas-
109 ing reasoning time thresholds, the corresponding maximum state space size, for which none of the BNs
110 exceed the reasoning time, grows much more gradually as compared to the corresponding treewidths.

111 These results provide a solid basis for our objective to develop algorithms that already bound
112 maximum state space size during BN structure learning, as we will lay out in the next sections.

Figure 2: Comparison of correlation of treewidth and maximum state space size with reasoning time

4 BN Learning of bounded state space size

4.1 Modified Heuristics

We now describe the modifications we made to the k-MAX and k-greedy heuristics so that they can operate with a bound on the state space.

Now, we give a brief outline of the k-greedy algorithm. Let us assume a treewidth bound of k. The algorithm starts off from a random ordering of the random variables. *Initialization:* It then initializes the first bag with the first $k + 1$ variables. It computes the best DAG over these variables either by an exact method or by an approximate method depending on the value of $k + 1$. *Addition:* Then the algorithm iteratively adds variables to this DAG with parent sets that maximize local score. While doing so, the algorithm searches through the existing k-cliques as potential parent sets. *Termination:* The iteration continues until there are no variables left to add.

To make the k-greedy algorithm work for bounded state space, we first modify the Initialization step. Let $\sigma = v_1, v_2, \ldots, v_n$ be the randomly sampled ordering. Instead of simply picking the first k variables, we now pick the first p variables such that p is the largest integer satisfying the condition $\prod_{i=1}^{p} v_i \leq k$. In the Addition step, we no longer treat all existing k-cliques as potential parent sets. Instead, when adding variable v, we only consider those sets S for which $\prod_{u \in S \cup \{v\}} \text{ds}(u) \leq k$.

The k-MAX algorithm is similar to the k-greedy algorithm, but picks the variables based on a scoring system instead of following a particular variable ordering. The modifications we propose for the k-greedy algorithm can however be easily adjusted to work for the k-MAX algorithm as well, by incorporating domain-size checks in place of cardinality checks.

We thus obtain the following algorithms:

k-greedy and k-MAX refer to the original two heuristics proposed by Scanagatta et al. [2016, 2018] that return bounded treewidth BNs.

k-greedy^bss and k-MAX^bss refer to the modified versions of k-greedy and k-MAX with the proposed modifications that return bounded state space BNs.

All these algorithms produce, as a side effect, a tree decomposition which witnesses the treewidth or state space bound of the obtained BN.

4.2 Local Improvement

In this section, we explain how the local improvement framework of Peruvemba Ramaswamy and Szeider [2021] can be extended and utilized for the bounded state space BN structure learning problem.

Throughout this section, consider an instance of the bounded state space BN structure learning problem, consisting pf a set V of random variables, a score function f, and a state space bound k.

147 *Initialization:* We first use a heuristic (such as described in Subsection 4.1) to compute an *initial*
148 *solution* D, together with a tree decomposition $\mathcal{T} = (T, \chi)$ of the moralized graph $M(D)$ with
149 maximum state space size $\leq k$. The local improvement step uses the parameter *budget* B which
150 controls the size of the local instance. *Subtree selection:* We select a subtree S of T such that
151 $V_S := \bigcup_{t \in V(S)} \chi(t)$ does not exceed the budget B. Our aim is compute for each $v \in V_S$ a new
152 parent set, optimizing the score of the resulting DAG D^{new} with $V(D^{\text{new}}) = V$. We define D_S^{new} as
153 the DAG induced by V_S where $E(D_S^{\text{new}}) = \{(u, v) \in E(D^{\text{new}}) : \{u, v\} \subseteq V_S\}$. We distinguish
154 between different kinds of nodes:

- 155 • $v \in V_S$ a *boundary vertex* if there exists a tree node $t \in V(T) \setminus V(S)$ such that $v \in \chi(t)$;
- 156 • $v \in V_S$ is an *internal vertex* if v is not a boundary vertex;
- 157 • $v \in V \setminus V_S$ is an *external vertex*.

158 Two boundary vertices v, v' are *adjacent* if both occur together in some bag outside S. In that case we
159 call $\{v, v'\}$ a *virtual edge*. We let E_{virt} be the set of all virtual edges. The *extended moral graph* M_{ext}
160 is obtained from $M(D_S^{\text{new}})$ by adding all virtual edges. If v, v' are two adjacent boundary vertices
161 such that D^{new} contains a directed path from v' to v, where all the vertices on the path, except for v'
162 and v, are external, then (v', v) is a *virtual arc*. $E_{\text{virt}}^{\rightarrow}$ denotes the set of all virtual arcs.

163 We call D_S^{new} a *well-behaved* DAG with respect to DAG D and its tree decomposition (T, χ) if the
164 following conditions are satisfied:

- 165 1. D_S^{new} is acyclic.
- 166 2. For each $v \in V(M_{\text{ext}})$, if $P_{D^{\text{new}}}(v)$ contains external vertices, then there is some $t \in$
- 167 $V(T) \setminus V(S)$ such that $P_{D^{\text{new}}}(v) \cup \{v\} \subseteq \chi(t)$.
- 168 3. The digraph with vertex set $V(M_{\text{ext}})$ and arc set $E(D_S^{\text{new}}) \cup E_{\text{virt}}^{\rightarrow}$ is acyclic.

169 Let $\mathcal{T} = (T, \chi)$ be a tree decomposition of DAG D. We call $\mathcal{T}^{\text{new}} = (T^{\text{new}}, \chi^{\text{new}})$ a *conservative* tree
170 decomposition of DAG D^{new} with respect to set $S \subseteq T$ if

- 171 1. $\mathcal{T}^{\text{new}}$ is a tree decomposition of DAG D^{new},
- 172 2. T^{new} can be partitioned into $S^{\text{new}}, T_1, \ldots, T_r$, where $T_1, \ldots, T_r$ are the connected compo-
- 173 nents of $T \setminus V(S)$, and
- 174 3. $\chi^{\text{new}}(t) = \chi(t)$ for $t \in \bigcup_{i=1}^r V(T_i)$.

175 **Lemma 1.** *If D_S^{new} is well-behaved, then D^{new} is acyclic and $f(D^{\text{new}}) \geq f(D)$.*

176 *Proof.* The correctness follows from [Peruvemba Ramaswamy and Szeider, 2021, Theorem 1], as
177 the statement of the lemma is identical except the treewidth constraints. We note that any tree
178 decomposition of such a D_S^{new} is conservative with respect to S. ☐

179 Introducing a state space bound to Lemma 1, we obtain the following theorem.

180 **Theorem 1.** *If D_S^{new} is well-behaved and admits a tree decomposition with* msss *at most k, then*

- 181 *1. D^{new} is acyclic,*
- 182 *2. the score of D^{new} is at least the score of D, and*
- 183 *3. $\text{msss}(D^{\text{new}}) \leq k$.*

184 *Proof.* The first two properties follow from Lemma 1. Now, let $\mathcal{T} = (T, \chi)$ be the tree decomposition
185 of DAG D, $\mathcal{T}^{\text{new}} = (T^{\text{new}}, \chi^{\text{new}})$ be the tree decomposition of DAG D^{new} and $\mathcal{S}^{\text{new}} = (S^{\text{new}}, \chi_S^{\text{new}})$
186 be the tree decomposition of D_S^{new}. Since $\mathcal{S}^{\text{new}}$ is conservative with respect to S (from Lemma 1),
187 we can express χ^{new} as $\chi_S^{\text{new}}(t)$ if $t \in S$ and $\chi(t)$ otherwise. In order to prove the third property, we
188 need to bound the state space size of the bags of $\mathcal{T}^{\text{new}}$, i.e., we need to bound

$$\max_{t \in T^{\text{new}}} \prod_{v \in \chi^{\text{new}}(t)} \text{ds}(v) = \max \left(\max_{t \in S} \prod_{v \in \chi_S^{\text{new}}(t)} \text{ds}(v), \max_{t \in T \setminus V(S)} \prod_{v \in \chi(t)} \text{ds}(v) \right)$$

$$\leq \max \left(k, \max_{t \in T} \prod_{v \in \chi(t)} \text{ds}(v) \right) \qquad [\text{msss}(D_S^{\text{new}}) \leq k]$$

$$\leq \max (k, k) \qquad [\text{msss}(D) \leq k].$$

189 Thus, the maximum state space size of D^{new} is at most k. ☐

4.3 MaxSAT Encoding

We now describe how we construct the (weighted, partial) MaxSAT instance that encodes the conditions required on the local instance S. The instance is a propositional formula in conjunctive normal form (CNF), with hard clauses and soft clauses; each soft clause has a weight. The MaxSAT solver tries to find a truth assignment that satisfies all the hard clauses and maximizes the sum of weights of satisfied soft clauses. We take as input the local instance S, the set of virtual edges E_{virt}, the set of virtual arcs $E_{\text{virt}}^{\rightarrow}$, and the bound k on the maximum state space size and produce a MaxSAT instance Φ_S. We reuse parts of the encoding proposed by Peruvemba Ramaswamy and Szeider [2021] (we will refer to it as the *BN-SLIM encoding*), extending an encoding proposed by Samer and Veith [2009] for capturing the tree decompositions.

Let $n = |S|$ denote the size of the subinstance. We now reiterate the hard clauses from the BN-SLIM encoding and refer to the conjunction of these clauses as the formula Φ'_S. For an explanation of the semantics of these variables and clauses, we refer to the source [Peruvemba Ramaswamy and Szeider, 2021].

$$\left.\begin{array}{l}(\text{acyc}^*_{u,v} \wedge \text{acyc}^*_{v,w}) \rightarrow \text{acyc}^*_{u,w} \\ (\text{ord}^*_{u,v} \wedge \text{ord}^*_{v,w}) \rightarrow \text{ord}^*_{u,w}\end{array}\right\} \quad \text{for distinct } u,v,w \in S.$$

$$\neg\text{arc}_{v,v} \quad \text{for } v \in S.$$

$$\textstyle\sum_{P \in \mathcal{P}_v}\text{par}^P_v = 1 \quad \text{for } v \in S.$$

$$\text{par}^P_v \rightarrow \text{acyc}_{u,v} \quad \text{for } v \in S, P \in \mathcal{P}_v, \text{ and } u \in P.$$

$$\left.\begin{array}{l}(\text{par}^P_v \wedge \text{ord}_{u,v}) \rightarrow \text{arc}_{u,v} \\ (\text{par}^P_v \wedge \text{ord}_{v,u}) \rightarrow \text{arc}_{v,u}\end{array}\right\} \quad \text{for } v \in S, P \in \mathcal{P}_v, \text{ and } u \in P.$$

$$\left.\begin{array}{l}(\text{par}^P_v \wedge \text{ord}_{u,w}) \rightarrow \text{arc}_{u,w} \\ (\text{par}^P_v \wedge \text{ord}_{w,u}) \rightarrow \text{arc}_{w,u}\end{array}\right\} \quad \text{for } v \in S, P \in \mathcal{P}_v, \text{ and } u,w \in P.$$

$$\left.\begin{array}{l}(\text{arc}_{u,v} \wedge \text{arc}_{u,w} \wedge \text{ord}_{v,w}) \rightarrow \text{arc}_{v,w} \\ (\text{arc}_{u,v} \wedge \text{arc}_{u,w} \wedge \text{ord}_{w,v}) \rightarrow \text{arc}_{w,v}\end{array}\right\} \quad \text{for } u,v,w \in S.$$

$$\neg\text{arc}_{u,v} \vee \neg\text{arc}_{v,u} \quad \text{for } u,v \in S.$$

$$\text{ord}^*_{u,v} \rightarrow \text{arc}_{u,v} \wedge \text{ord}^*_{v,u} \rightarrow \text{arc}_{v,u} \quad \text{for } \{u,v\} \in E_{\text{virt}}.$$

$$\text{par}^P_v \rightarrow \text{acyc}^*_{u,v} \quad \text{for } v \in S, P \in \mathcal{P}_v, \text{ and } (u,v) \in A^{\rightarrow}_{\text{virt}}(v,P).$$

We also add the following soft clauses to Φ'_S, setting $f'_P(v) = f_P(v) - f_\emptyset(v)$ as their weight

$$(\text{par}^P_v) : \text{weight } f'_P(v) \quad \text{for } v \in S, P \in \mathcal{P}_v.$$

The weight of a solution to Φ'_S is given by the sum of weights of the satisfied soft clauses. Let $W = \sum_{v \in S} f'(v, P_D(v))$ be the core of the unmodified local instance S.

Lemma 2. Φ'_S *admits a solution of weight W^{new} if and only if there exists a well-behaved DAG D_S^{new} with respect to D, such that $f(D^{\text{new}}) - f(D) = W^{\text{new}} - W$*

Proof. We can use the proof of [Peruvemba Ramaswamy and Szeider, 2021, Theorem 2] to establish the lemma, since the only difference the clauses that upper bound treewidth of D_S^{new}. Therefore D_S^{new} is still acyclic. Further, an assignment that corresponds to setting $D_S^{\text{new}} = S_S$ achieves the lower bound on the score. □

4.4 BDD-based counter

In this section, we elaborate the counting mechanism we use to encode the condition $\sum_{w \in S, w \neq v, \text{arc}_{v,w}} \log(\text{ds}(w)) \leq \log(k)$ for $v \in S$. The technique we use was first proposed by Eén and Sörensson [2006]. Intuitively speaking, we construct an (Ordered) Binary Decision Diagram (BDD), where following a path from an input node to a terminal node corresponds to summing up weights. Each layer of nodes in the BDD is associated with a variable $v \in S$, and there are two outgoing edges from each node in the BDD corresponding to the existence and absence of $\text{arc}_{v,w}$.

Figure 3: Example BDD constructed for three variables v_1, v_2, v_3 with domain sizes 2, 3, and, 4 respectively and $k = 6$. The logarithms of the domain sizes are $1, 1.6$, and, 2 respectively. The solid and dashed edges represent the 'if' and 'else' arcs respectively. The path $(x_1, 0) \text{---} (x_2, 1) \text{---} (x_3, 2.6) \text{- -} \texttt{TRUE}$ represents the bag containing x_1 and x_2 with a state space size of $6 \leq k$, hence reaching $\texttt{TRUE}$. The path $(x_1, 0) \text{---} (x_2, 1) \text{- -} (x_3, 1) \text{---} \texttt{FALSE}$ represents the bag containing x_1 and x_3 with a state space size of $8 > k$, hence reaching $\texttt{FALSE}$. Note that both these bags have cardinality 2 and hence are treated the same when it comes to treewidth.

More formally, let us assume that the set S consists of the variables $v_1, \ldots, v_m$, where $m := |S|$. We construct a BDD, which is a directed graph with nodes of the form (x_i, l) where $i \in \{1, d \ldots m\}$ is an integer, and $l \in [0, k]$ is a real number. Here, x_i signifies that we branch on variable v_i next, and l denotes the level of the current sum of weights. Additionally, there are two special terminals (sink nodes) – $\texttt{TRUE}$ and $\texttt{FALSE}$. From each node (x_i, l) there are two outgoing arcs – the 'if' arc connecting it to the node $(x_{i+1}, l + \log(\mathrm{ds}(v_i)))$, and the 'else' arc connecting it to the node (x_{i+1}, l). In case $l + \log(\mathrm{ds}(v_i)) > k$, we instead connect it to the $\texttt{FALSE}$ terminal. Finally, for a node of the form (x_m, l), we connect it to the $\texttt{TRUE}$ terminal iff $l + \log(\mathrm{ds}(v_m)) \leq k$. We denote by $\mathrm{if}(x, l)$ and $\mathrm{else}(x, l)$, the nodes connected to (x, l) via the 'if' and 'else' arcs, respectively. Refer to Figure 3 for an example. There are at most $2^m + 1$ nodes in the BDD.

For each variable $v \in S$, we have one such BDD to ensure that the product of the domain sizes of the endpoints of the outgoing arcs does not exceed the bound k. It is straightforward to express this BDD in the form of a CNF formula $\mathcal{B}_v$. We introduce a variable $\mathrm{bdd}^v_{w,l}$ for each $w \in S \setminus \{v\}$ and each level l in the BDD. We then add the following clauses to $\mathcal{B}^v$

$$\left.\begin{array}{l} (\mathrm{bdd}^v_{w,l} \wedge \mathrm{arc}_{v,w}) \rightarrow \mathrm{bdd}^v_{\mathrm{if}(w,l)} \\ (\mathrm{bdd}^v_{w,l} \wedge \neg\mathrm{arc}_{v,w}) \rightarrow \mathrm{bdd}^v_{\mathrm{else}(w,l)} \end{array}\right\} \quad \text{for } (w, l) \in V(\mathcal{B}_v).$$

Next, we add the clause $\neg\mathrm{bdd}^v_{\texttt{FALSE}}$ to $\mathcal{B}^v$ that falsifies $\mathcal{B}^v$ if the $\texttt{FALSE}$ sink node is reached, i.e., if the outgoing arcs of variable v violate the bound. Finally, we conjoin all the formulas $\mathcal{B}^v$ for $v \in S$ with the formula Φ'_S to obtain our final formula Φ_S, giving us the following theorem.

Theorem 2. Φ_S *admits a solution of weight K^{new} if and only if there exists a well-behaved DAG D^{new}_S with respect to D, such that $f(D^{\mathrm{new}}) - f(D) = K^{\mathrm{new}} - K$ and $\mathrm{msss}(D^{\mathrm{new}}_S) \leq k$.*

Proof. By construction of the BDD, we see that $\mathcal{B}^v$ is falsified if and only if the outgoing arcs from variable v result in the state space size of that bag exceeding k. Thus, $\bigwedge_{v \in S} \mathcal{B}^v$ is satisfiable if and only if $\mathrm{msss}(D^{\mathrm{new}}_S) \leq k$. Combining this with Lemma 2, we obtain the desired result. $\square$

5 Experiments

5.1 Setup

We tested the various proposed methods on 4-core Intel Xeon E5540 2.53 GHz CPU (internal cluster), with each process having access to 8GB RAM. The k-greedy and k-MAX algorithms are available as a part of the BLIP package [Scanagatta, 2015] implemented in Java. We modified and extended these to obtain the implementations for k-greedy[bss] and k-MAX[bss]. We implemented BN-SLIM[bss] in Python making use of the NetworkX library [Hagberg et al., 2008]. We used UWrMaxSat[1] as the MaxSAT-solver, because of its reliable response to timeouts. For evaluating the reasoning time we used the Merlin package by Radu Marinescu.[2] We provide the source code as a part of the supplementary material.

We tested the algorithms on a subset of the `bnlearn` repository.[3] These networks are commonly used as benchmarks in the literature. Out of the 22 networks available in the repository, we only

---

[1] `https://maxsat-evaluations.github.io/2019/descriptions.html`
[2] `https://github.com/radum2275/merlin`
[3] `https://www.bnlearn.com/bnrepository/`

consider the 16 networks that contain non-binary variables. These networks range in size from 6 to 1041 random variables. Due to the smaller networks' behvaior being susceptible to random noise, we focus more on the larger networks.

5.2 Method

Next, we describe the method used to evaluate the performance of the BN structure learning algorithms enumerated in Section 4.1. We run the algorithms for a total time of 90 minutes and record the reasoning time and score at the end. We denote by BN-SLIM^{bss}(X) the algorithm composed of running the heuristic X for 30 minutes and then running the bounded state space local improvement algorithm on top of the heuristic solution for another 60 minutes. We run the algorithms with multiple bounds and multiple random seeds. Finally, for each instance, we visualize the distribution of scores and reasoning times on a scatter plot to capture the trade-off achieved between the two metrics. We set k-greedy and k-MAX as the *baseline* algorithms and always compare the newly proposed algorithms against these baseline algorithms. The baseline algorithms represent the state-of-the-art bounded treewidth BN structure learning methods while the heuristics represent the bounded state space based BN structure learning methods.

5.3 Results

We performed some preliminary tests to determine the most promising bounded state space (bss) methods for comparison against the baseline of tw-methods k-MAX and k-greedy. On the basis of these tests, we choose BN-SLIM^{bss}(k-MAX^{bss}) as the bss-method. In Figure 4 we see the scatter plots for a representative subset of instances. We include the complete set of plots in the supplementary material. The plots are presented in pairs with the left subplot depicting the tw-methods' performance and the right subplot depicting BN-SLIM^{bss}(k-MAX^{bss})'s performance.

In general, from Figure 4, we observe that BN-SLIM^{bss}(k-MAX^{bss}) achieves much faster reasoning times at the expense of slightly worse scores in some cases. Whereas in some cases, BN-SLIM^{bss}(k-MAX^{bss}) manages to match the score while reducing the reasoning time significantly. In most cases, we observe an reduction by an order of magnitude. Another point worth noting is that the clustering of the BNs output by BN-SLIM^{bss}(k-MAX^{bss}) along the reasoning time axis is much tighter than with the tw-methods. This highlights the reliability aspect of the bss-methods.

We also observe that the bss-method BN-SLIM^{bss}(k-MAX^{bss}) allows us to expand the search space much more carefully and predictably. For instance, consider a bound on the maximum state space size of 5×10^5. A reasonable equivalent bound on the treewidth would be $\log_2(5 \times 10^5) \approx 19$. However, networks with treewidth 19 can be expected to have much worse responsiveness as compared to networks with msss $\leq 5 \times 10^5$.

This confirms our hypothesis that maximum state space size is a much better estimator of reasoning time as compared to treewidth, and that one can construct algorithms like BN-SLIM^{bss}(k-MAX^{bss}) to learn such responsive BNs.

6 Conclusion

We have introduced the concept of bounded state space BN structure learning, devised it theoretically, implemented it, and tested it rigorously on a set of real-world data sets. We compared the new approach with state-of-the-art bounded treewidth BN structure learning algorithms on a two-dimensional setting to see the tradeoff between responsiveness and data fitting. Our results show that the new approach indeed provides overall better and more reliable results. In some cases, the advantage of bounded state space over bounded treewidth methods is significant.

Ethical Impact BNs are widely used in decision-making loops. We suspect our paper doesn't create any new negative social impacts than those that were already present. We propose methods to speed up the inference on BNs which does not significantly change their use case. However, it could lead to over-dependence on BNs which has it's own risks. In its current state, there are many areas where BNs cannot replace a domain expert.

Figure 4: Scatter plots

References

H. Akaike. A new look at the statistical model identification. *IEEE transactions on automatic control*, 19(6):716–723, 1974.

M. Benjumeda, C. Bielza, and P. Larrañaga. Learning tractable bayesian networks in the space of elimination orders. *Artificial Intelligence*, 274:66–90, 2019.

J. Berg, M. Järvisalo, and B. M. Malone. Learning optimal bounded treewidth bayesian networks via maximum satisfiability. In *Proceedings of the Seventeenth International Conference on Artificial Intelligence and Statistics, AISTATS 2014, Reykjavik, Iceland, April 22-25, 2014*, volume 33 of *JMLR Workshop and Conference Proceedings*, pages 86–95. JMLR.org, 2014.

R. Dechter. Bucket elimination: a unifying framework for reasoning. *Artificial Intelligence*, 113(1-2): 41–85, 1999.

N. Eén and N. Sörensson. Translating pseudo-boolean constraints into SAT. *J. Satisf. Boolean Model. Comput.*, 2(1-4):1–26, 2006. doi: 10.3233/sat190014. URL https://doi.org/10.3233/sat190014.

V. Gogate and R. Dechter. A complete anytime algorithm for treewidth. In *Proceedings of the Proceedings of the Twentieth Conference Annual Conference on Uncertainty in Artificial Intelligence (UAI-04)*, pages 201–208, Arlington, Virginia, 2004. AUAI Press.

A. A. Hagberg, D. A. Schult, and P. J. Swart. Exploring network structure, dynamics, and function using NetworkX. In *Proceedings of the 7th Python in Science Conference (SciPy2008)*, pages 11–15, Pasadena, CA USA, Aug. 2008.

D. Heckerman, D. Geiger, and D. M. Chickering. Learning Bayesian networks: The combination of knowledge and statistical data. *Machine Learning*, 20(3):197–243, 1995.

U. Kærulff. Optimal decomposition of probabilistic networks by simulated annealing. *Statistics and Computing*, 2:7–17, 1992.

K. Kask, A. Gelfand, L. Otten, and R. Dechter. Pushing the power of stochastic greedy ordering schemes for inference in graphical models. In W. Burgard and D. Roth, editors, *Proceedings of the Twenty-Fifth AAAI Conference on Artificial Intelligence (AAAI 2011)*, page 54–60. AAAI Press, 2011.

D. Koller and N. Friedman. *Probabilistic graphical models: principles and techniques*. MIT press, 2009.

J. H. Korhonen and P. Parviainen. Exact learning of bounded tree-width bayesian networks. In *Proceedings of the Sixteenth International Conference on Artificial Intelligence and Statistics, AISTATS 2013, Scottsdale, AZ, USA, April 29 - May 1, 2013*, volume 31 of *JMLR Workshop and Conference Proceedings*, pages 370–378. JMLR.org, 2013.

S. L. Lauritzen and D. J. Spiegelhalter. Local computations with probabilities on graphical structures and their application to expert systems. *J. R. Stat. Soc. Ser. B.*, 50(2):157–224, 1988.

M. Meila and M. I. Jordan. Triangulation by continuous embedding. In M. Mozer, M. I. Jordan, and T. Petsche, editors, *Advances in Neural Information Processing Systems 9, NIPS, Denver, CO, USA, December 2-5, 1996*, pages 557–563. MIT Press, 1996.

S. Nie, C. P. de Campos, and Q. Ji. Learning bounded tree-width bayesian networks via sampling. In S. Destercke and T. Denoeux, editors, *Symbolic and Quantitative Approaches to Reasoning with Uncertainty - 13th European Conference, ECSQARU 2015, Compiègne, France, July 15-17, 2015. Proceedings*, volume 9161 of *Lecture Notes in Computer Science*, pages 387–396. Springer Verlag, 2015.

S. Nie, C. P. de Campos, and Q. Ji. Learning bayesian networks with bounded tree-width via guided search. In D. Schuurmans and M. P. Wellman, editors, *Proceedings of the Thirtieth AAAI Conference on Artificial Intelligence, February 12-17, 2016, Phoenix, Arizona, USA*, pages 3294–3300. AAAI Press, 2016.

L. Otten and R. Dechter. Refined bounds for instance-based search complexity of counting and other #p problems. In P. J. Stuckey, editor, *Principles and Practice of Constraint Programming, 14th International Conference, CP 2008, Sydney, Australia, September 14-18, 2008. Proceedings*, volume 5202 of *Lecture Notes in Computer Science*, pages 576–581. Springer Verlag, 2008a. doi: 10.1007/978-3-540-85958-1_45.

L. Otten and R. Dechter. Bounding search space size via (hyper)tree decompositions. In D. A. McAllester and P. Myllymäki, editors, *UAI 2008, Proceedings of the 24th Conference in Uncertainty in Artificial Intelligence, Helsinki, Finland, July 9-12, 2008*, pages 452–459. AUAI Press, 2008b.

P. Parviainen, H. S. Farahani, and J. Lagergren. Learning bounded tree-width bayesian networks using integer linear programming. In *Proceedings of the Seventeenth International Conference on Artificial Intelligence and Statistics, AISTATS 2014, Reykjavik, Iceland, April 22-25, 2014*, volume 33 of *JMLR Workshop and Conference Proceedings*, pages 751–759. JMLR.org, 2014.

V. Peruvemba Ramaswamy and S. Szeider. Turbocharging treewidth-bounded bayesian network structure learning. In *Proceeding of AAAI-21, the Thirty-Fifth AAAI Conference on Artificial Intelligence*, 2021. Preprint available at `https://arXiv:2006.13843`.

M. Samer and H. Veith. Encoding treewidth into SAT. In *Theory and Applications of Satisfiability Testing - SAT 2009, 12th International Conference, SAT 2009, Swansea, UK, June 30 - July 3, 2009. Proceedings*, volume 5584 of *Lecture Notes in Computer Science*, pages 45–50. Springer Verlag, 2009.

M. Scanagatta. BLIP – Bayesian Network learning and inference package , 2015. URL `https://ipg.idsia.ch/software/blip`.

M. Scanagatta, G. Corani, C. P. de Campos, and M. Zaffalon. Learning treewidth-bounded bayesian networks with thousands of variables. In D. D. Lee, M. Sugiyama, U. von Luxburg, I. Guyon, and R. Garnett, editors, *Advances in Neural Information Processing Systems 29: Annual Conference on Neural Information Processing Systems 2016, December 5-10, 2016, Barcelona, Spain*, pages 1462–1470, 2016.

M. Scanagatta, G. Corani, M. Zaffalon, J. Yoo, and U. Kang. Efficient learning of bounded-treewidth bayesian networks from complete and incomplete data sets. *Int. J. Approx. Reason*, 95:152–166, 2018.

G. Schwarz. Estimating the dimension of a model. *The annals of statistics*, 6(2):461–464, 1978.