PARP: Prune, Adjust and Re-Prune
for Self-Supervised Speech Recognition

Abstract

Recent work on speech self-supervised learning (speech SSL) demonstrated the
benefits of scale in learning rich and transferable representations for Automatic
Speech Recognition (ASR) with limited parallel data. It is then natural to investi-
gate the existence of sparse and transferrable subnetworks in pre-trained speech
SSL models that can achieve even better low-resource ASR performance. However,
directly applying widely adopted pruning methods such as the Lottery Ticket Hy-
pothesis (LTH) is suboptimal in the computational cost needed. Moreover, contrary
to what LTH predicts, the discovered subnetworks yield minimal performance gain
compared to the original dense network. In this work, we propose Prune-Adjust-
Re-Prune (`PARP`), which discovers and finetunes subnetworks for much better ASR
performance, while only requiring a *single* downstream finetuning run. `PARP` is
inspired by our surprising observation that subnetworks pruned for pre-training
tasks only needed to be slightly adjusted to achieve a sizeable performance boost in
downstream ASR tasks. Extensive experiments on low-resource English and multi-
lingual ASR show (1) sparse subnetworks exist in pre-trained speech SSL, and (2)
the computational advantage and performance gain of `PARP` over baseline pruning
methods. On the 10min Librispeech split without LM decoding, `PARP` discovers
subnetworks from wav2vec 2.0 with an absolute 10.9%/12.6% WER decrease com-
pared to the full model. We demonstrate `PARP` mitigates performance degradation
in cross-lingual mask transfer, and investigate the possibility of discovering a single
subnetwork for 10 spoken languages in one run.

1   Introduction

For many low-resource spoken languages in the world, collecting large-scale transcribed corpora
is very costly and sometimes infeasible. Inspired by efforts such as the IARPA BABEL program,
Automatic Speech Recognition (ASR) trained without sufficient transcribed speech data has been
a critical yet challenging research agenda in speech processing [20, 22, 31, 21, 16]. Recently, Self-
Supervised Speech Representation Learning (speech SSL) has emerged as a promising pathway
toward solving low-resource ASR [60, 18, 82, 4, 19, 93, 42]. Speech SSL involves pre-training a
speech representation module on large-scale *unlabelled* data with a self-supervised learning objective,
followed by finetuning on a small amount of supervised transcriptions. Many recent studies have
demonstrated the empirical successes of speech SSL on low-resource English and multi-lingual ASR,
matching systems trained on fully-supervised settings [4, 19, 93]. Prior research attempts, however,
focus on pre-training objectives [60, 18, 82, 42], scaling up speech representation modules [3, 4],
or pre-training data selections [41]. In this work, we aim to develop an orthogonal approach that is
complementary to these existing speech SSL studies, that achieves 1) lower architectural complexity
and 2) higher performance (lower WER) under the same low-resource ASR settings.

Submitted to 35th Conference on Neural Information Processing Systems (NeurIPS 2021). Do not distribute.

Neural network pruning [48, 39, 37, 51], as well as the more recently proposed Lottery Ticket Hypothesis (LTH) [28], provide a potential solution that accomplishes both objectives. According to LTH, there exists sparse subnetworks that can achieve the same or *even better* accuracy than the original dense network. Such phenomena have been successfully observed in various domains: Natural Language Processing (NLP) [90, 15, 64, 56], Computer Vision (CV) [14, 33], and many others. All finding sparse subnetworks with comparable or better performance than the dense network. Given the lack of similar studies on pruning self-supervised ASR, we intend to fill this gap by finding sparse subnetworks *within a pre-trained* speech SSL that can achieve superior performance to the full pre-trained model on downstream ASR tasks.

However, directly applying widely-adopted pruning methods, such as One-Shot Magnitude Pruning (`OMP`) and Iterative Magnitude Pruning (`IMP`) [37, 28], to pre-trained speech SSL suffers from two challenges. First, adopting these methods in the conventional pruning framework is extremely time-consuming for SOTA speech SSL models. `OMP` and `IMP` involve more than one round of finetuning on downstream tasks (c.f. Figure 1), and finetuning for ASR is time-consuming and computationally demanding[1]. The second challenge is that we do not observe *any* performance improvement of the subnetworks over the original dense network with `OMP` or `IMP`. Figure 3 shows the WER under low-resource scenarios of the subnetworks identified by `OMP` (purple line) and `IMP` (blue dashed line) at different sparsity levels. None of the sparsity levels achieves a visible drop in WER compared to the zero sparsity case, corresponding to the original dense network. These two challenges have prompted us to ask – do there exist sparse subnetworks within pre-trained speech SSL with improved performance on low-resource ASR? How can we discover them efficiently in a *single* downstream finetuning run?

Figure 1: Number of ASR finetuning iterations needed v.s. target sparsities for *each* downstream task/language. Cross-referencing Figure 3, as the number of downstream tasks increase, `IMP` requires exponentially more compute to match the performance of `PARP`.

In this paper, we propose a magnitude-based unstructured pruning method [30, 9], termed Prune-Adjust-Re-Prune (`PARP`), for discovering sparse subnetworks within pre-trained speech SSL. `PARP` consists of the following two steps:

1. Directly prune the SSL pre-trained model at target sparsity, and obtain an initial subnetwork and an initial pruning mask.
2. Finetune the initial subnetwork on target downstream task/language. During finetuning, zero out the pruned weights specified by the pruning mask, but allow the weights be updated by gradient descent during backpropogation. After a few number of model updates, re-prune the updated subnetwork at target sparsity again.

Step 1 provides an initial subnetwork that is agnostic to the downstream task, and Step 2 makes learnable adjustments by reviving pruned out weights. A formal and generalized description and its extension are introduced in Section 3. Different from pruning methods in [37, 28], `PARP` allows pruned-out weights to be revived during finetuning. Although such a high-level idea was introduced in [36], we provide an alternative insight: despite its flexibility, Step 2 only makes **minimal adjustment** to the initial subnetwork, and obtaining a good initial subnetwork in Step 1 is the key. We empirically show in Section 3 that *any* task-agnostic subnetwork surprisingly provides a good basis for Step 2, suggesting that the initial subnetwork can be cheaply obtained either from a readily available task/language or directly pruning the pre-trained SSL model itself. In addition, this observation allows us to perform cross-lingual mask transfer experiments, where the initial subnetwork is obtained via a different language other than the target language.

We conduct extensive `PARP` and baseline (`OMP` and `IMP`) pruning experiments on low-resource ASR with mono-lingual (pre-trained wav2vec 2.0 [4]) and cross-lingual (pre-trained XLSR-53 [19]) transfer. `PARP` finds significantly superior speech SSL subnetworks for low-resource ASR, while only requiring a single pass of downstream finetuning. Due to its simplicity, `PARP` adds minimal computation overhead to existing SSL downstream finetuning. Our contributions are:

- We show that sparse subnetworks exist in pre-trained speech SSL. In addition, `PARP` achieves superior results to `OMP` and `IMP` across all sparsities, amount of finetuning supervision, pre-trained model scale, and downstream spoken languages. On Librispeech 10min without

---

[1]Standard wav2vec 2.0 finetuning setup [4] on any Librispeech/Libri-light splits requires at least 50∼100 V100 hours, which is more than 50 times the computation cost for finetuning a BERT on GLUE [80].

LM decoding/self-training, `PARP` discovers subnetworks from wav2vec 2.0 with an absolute 10.9%/12.6% WER decrease compared to the full model, without modifying the finetuning hyper-parameters or objective (Section 4.1).

- Ablation studies on demonstrating the importance of `PARP`'s initial subnetwork (Section 4.2).

- `PARP` achieves minimal performance drop in cross-lingual mask transfer, where a subnetwork pruned for ASR in one spoken language is adapted to another language (Section 4.3). `PARP` can also discover a single subnetwork for 10 spoken languages in a single pass (Section 4.4).

- Last but not least, we demonstrate `PARP`'s effectiveness on pre-trained BERT, mitigating the cross-task performance degradation reported in BERT-Ticket [15] (Section 4.5).

The findings of this work not only complement and advance current and future speech SSL for low-resource ASR, but also provide new insights for the rich body of pruning work.

2 Preliminaries

2.1 Problem Formulation

Consider the low-resource ASR problem, where there is only a small transcribed training set $(x, y) \in \mathcal{D}_l$. Here x represents input audio, and y represents output transcription. Subscript $l \in \{1, 2, \cdots\}$ represents the downstream spoken language identity. Because of the small dataset size, empirical risk minimization generally does not yield good results. Speech SSL instead assumes there is a much larger unannotated dataset $x \in \mathcal{D}_0$. SSL pre-trains a neural network $f(x; \theta)$, where $\theta \in \mathcal{R}^d$ represents the network parameters and d represents the number of parameters, on some self-supervised objective, and obtains the pre-trained weights θ_0. $f(x; \theta_0)$ is then finetuned on downstream ASR tasks specified by a downstream loss $\mathcal{L}_l(\theta)$, such as CTC, and evaluated on target dataset $\mathcal{D}_l$.

Our goal is to discover a subnetwork that minimizes downstream ASR WER on $\mathcal{D}_l$. Formally, denote $m \in \{0, 1\}^d$, as a binary pruning mask for the pre-trained weights θ_0, and θ^l as the finetuned weights on $\mathcal{D}_l$. The ideal pruning method should learn (m, θ^l), such that the subnetwork $f(x; m \odot \theta^l)$ (where $\odot$ is element-wise product) achieves minimal finetuning $\mathcal{L}_l(\theta)$ loss on $\mathcal{D}_l$.

2.2 Pruning Targets and Settings

We adopted pre-trained speech SSL `wav2vec2` and `xlsr` for the pre-trained initialization θ_0.

wav2vec 2.0 We took wav2vec 2.0 base (`wav2vec2-base`) and large (`wav2vec2-large`) pre-trained on Librispeech 960 hours [4]. During finetuning, a task specific linear layer is added on top of `wav2vec2` and jointly finetuned with CTC loss. More details can be found in Appendix A.

XLSR-53 (`xlsr`) shares the same architecture, pre-training and finetuning objectives as `wav2vec2-large`. `xlsr` is pre-trained on 53 languages sampled from CommonVoice, BABEL, and Multilingual LibriSpeech, totaling for 56k hours of multi-lingual speech data.

We consider three settings where `wav2vec2` and `xlsr` are used as the basis for low-resource ASR:

LSR: Low-Resource English ASR. Mono-lingual pre-training and finetuning – an English pre-trained speech SSL such as `wav2vec2` is finetuned for low-resource English ASR.

H2L: High-to-Low Resource Transfer for Multi-lingual ASR. Mono-lingual pre-training and multi-lingual finetuning – a speech SSL pre-trained on a high-resource language such as English is finetuned for low-resource multi-lingual ASR.

CSR: Cross-lingual Transfer for Multi-lingual ASR. Multi-lingual pre-training and finetuning – a cross-lingual pretrained speech SSL such as `xlsr` is finetuned for low-resource multi-lingual ASR.

2.3 Subnetwork Discovery in Pre-trained SSL

One obvious solution to the aforementioned problem in Section 2.1 is to directly apply pruning with rewinding to θ_0, which has been successfully applied to pre-trained BERT [15] and SimCLR [14]. All pruning methods, including our proposed `PARP`, are based on Unstructured Magnitude Pruning (`UMP`) [28, 30], where weights of the lowest magnitudes are pruned out regardless of the network structure to meet the target sparsity level. We introduce four pruning baselines below, and we also provide results with Random Pruning (`RP`) [28, 30, 15], where weights in θ_0 are randomly eliminated.

Task-Aware Subnetwork Discovery is pruning with target dataset D_l seen in advance, including One-Shot Magnitude Pruning (`OMP`) and Iterative Magnitude Pruning (`IMP`). `OMP` is summarized as:

142   1. Finetune pretrained weights θ_0 on target dataset $\mathcal{D}_l$ to get the finetuned weights θ^l.

143   2. Apply `UMP` on θ^l and retrieve pruning mask m.

`IMP` breaks down the above subnetwork discovery phase into multiple iterations – in our case multiple downstream ASR finetunings. Each iteration itself is an `OMP` with a fraction of the target sparsity pruned. We follow the `IMP` implementation described in BERT-Ticket [15], where each iteration prunes out 10% of the *remaining* weights. The main bottleneck for `OMP` and `IMP` is the computational cost, since multiple rounds of finetunings are required for subnetwork discovery.

Task-Agnostic Subnetwork Discovery refers to pruning without having seen D_l nor l in advance. One instance is applying `UMP` directly on θ_0 without any downstream finetuning to retrieve m, referred to as Magnitude Pruning at Pre-trained Initailizations (`MPI`). Another case is pruning weights finetuned for a different language t, *i.e.* applying `UMP` on θ^t for the target language l; in our study, we refer to this as cross-lingual mask transfer. While these approaches do not require target task finetuning, the discovered subnetworks generally have worse performance than those from `OMP` or `IMP`.

The above methods are only for subnetwork discovery via applying pruning mask m on θ_0. The discovered subnetwork $f(x; m \odot \theta_0)$ needs another downstream finetuning to recover the pruning loss[2], *i.e.* finetune $f(x; m \odot \theta_0)$ on D_l.

3   Method

In this section, we highlight our proposed pruning method, `PARP` (Section 3.1), its underlying intuition (Section 3.2), and an extension termed `PARP-P` (Section 3.3).

3.1   Algorithm

We formally describe `PARP` with the notations from Section 2. A visual overview of `PARP` is Figure 8.

Algorithm 1 Prune-Adjust-Re-Prune (PARP) to target sparsity s

---

1: Assume there are N model updates in target task/language l's downstream finetuning.
2: Take a pre-trained SSL $f(x; \theta_0)$ model. Apply task-agnostic subnetwork discovery, such as `MPI`[3], at target sparsity s to obtain initial subnetwork $f(x; m_0 \odot \theta_0)$. Set $m = m_0$ and variable $n_1 = 0$.
3: **repeat**
4:     Zero-out masked-out weights in θ_{n_1} given by m. Lift up m such that whole θ_{n_1} is updatable.
5:     Train $f(x; \theta_{n_1})$ for n model updates and obtain $f(x; \theta_{n_2})$.
6:     Apply `UMP` on $f(x; \theta_{n_2})$ and adjust m accordingly. The adjusted subnetwork is $f(x; m \odot \theta_{n_2})$. Set variable $n_1 = n_2$.
7: **until** total model updates reach N.
8: Return finetuned subnetwork $f(x; m \odot \theta_N)$.

Empirically, we found the choice of n has little impact. In contrast to `OMP/IMP/MPI`, `PARP` allows the pruned-out weights to take gradient descent updates. A side benefit of `PARP` is it jointly discovers and finetunes subnetwork in a single pass, instead of two or more in `OMP` and `IMP`.

3.2   Obtaining and Adjusting the Initial Subnetwork

`PARP` achieves superior or comparable pruning results as task-aware subnetwork discovery, while inducing similar computational cost as task-agnostic subnetwork discovery. How does it get the best of both worlds? The key is the discovered subnetworks from task-aware and task-agnostic prunings have high, non-trivial overlaps in LSR, H2L, and CSR. We first define Intersection over Union (`IOU`) for quantifying subnetworks' (represented by their pruning masks m^a and m^b) similarity:

$$\text{IOU}(m^a, m^b) \triangleq \frac{|(m^a = 1) \cap (m^b = 1)|}{|(m^a = 1) \cup (m^b = 1)|} \tag{1}$$

Take H2L and CSR for instance, Figure 2 visualizes language pairs' OMP pruning mask `IOU`s on `wav2vec2` and `xlsr`. Observe the high overlaps across all pairs, but also the high `IOU`s with the `MPI` masks (second to last row). We generalize these observations to the following:

Observation 1 *For any sparsity, any amount of finetuning supervision, any pre-training model scale, and any downstream spoken languages, the non-zero ASR pruning masks obtained from task-agnostic subnetwork discovery has high `IOU`s with those obtained from task-aware subnetwork discovery.*

---

[2]This step is referred to as subnetwork finetuning in the pruning literature [53, 69, 9].

Observation 1 suggests that *any* task-agnostic subnetwork could sufficiently be a good initial subnetwork in `PARP` due to the high similarities. In the same instance for H2L and CSR, we could either take `MPI` on `wav2vec2` and `xlsr`, or take `OMP` on a different spoken language as the initial subnetworks. Similarly in LSR, we take `MPI` on `wav2vec2` as the initial subnetwork. The underlying message is – the initial subnetwork can be obtained cheaply, without target task finetuning.

Now, because of the high similarity, the initial subnetwork (represented by its pruning mask m_0) needed merely a slight adjustment for the target downstream task. While there are techniques such as dynamic mask adjustment [36], important weights pruning [55], and deep rewiring [8], we provide an even simpler alternative suited for our setting. Instead of permanently removing the masked-out weights from the computation graph, `PARP` merely zeroes them out. Weights that are important for the downstream task (the "important weights") should emerge with gradient updates; those that are relatively irrelevant should decrease in magnitude, and thus be zero-outed at the end. Doing so circumvents the need of straight-through estimation or additional sparsity loss.

3.3 PARP-Progressive (`PARP-P`)

An extension to `PARP` is `PARP-P`, where the second P stands for Progressive. In `PARP-P`, the initial subnetwork starts at a lower sparsity, and progressively prune up to the target sparsity s in Step 2. The intuition is that despite Observation 1, *not any* subnetwork can be a good initial subnetwork, such as those obtained from `RP`, or those obtained at very high sparsities in `MPI`/`OMP`/`IMP`. We show later that `PARP-P` is especially effective in higher sparsity regions, e.g. 90% for LSR. Note that `PARP-P` has the same computational cost as `PARP`, and the only difference is the initial starting sparsity in Step 1.

Figure 2: `IOUs` over all spoken language pairs' `OMP` pruning masks on finetuned `wav2vec2` and `xlsr`. Second to last row is the `IOUs` between `OMP` masks and the `MPI` masks from pre-trained `wav2vec2` and `xlsr`. Here, we show the `IOUs` at 50% sparsity, and the rest can be found in Appendix. Surprisingly at any sparsities, there is a high, non-trivial (c.f. `RP` in the last row), similarity (>90%) between all spoken language `OMP` masks, as well as with the `MPI` masks. Language IDs are in Appendix B.

4 Experiments and Analysis

4.1 Comparing `PARP`, `OMP`, and `IMP` on LSR, H2L, and CSR

Our experimental setup can be found in Appendix B. We first investigate the existence of sparse subnetworks in speech SSL. Figure 3 shows the pruning results on LSR. Observe that subnetworks discovered by `PARP` and `PARP-P` can achieve 60∼80% sparsities with minimal degradation to the full models. The gap between `PARP` and other pruning methods also widens as sparsities increase. For instance, Table 1 compares `PARP` and `PARP-P` with `OMP` and `IMP` at 90% sparsity, and `PARP-P` has a 40% absolute WER reduction. In addition, observe the WER reduction with `PARP` in the low sparsity regions on the 10min split in Figure 3. The same effect is not seen with `OMP`, `IMP`, nor `MPI`. Table 2 compares the subnetworks discovered by `PARP` with the full `wav2vec2` and prior work on LSR under the same setting[4]. Surprisingly, the discovered subnetwork attains an absolute 10.9%/12.6% WER reduction over the full `wav2vec2-large`. We hypothesize that the performance gains are attributed to pruning out generic, unnecessary weights while preserving important weights, which facilitates training convergence. We also examined the effectiveness of `IMP` with different rewinding starting points as studied in [29, 69], and found rewinding initializations bear minimal effect on downstream ASR. Full rewinding details are in Appendix C.

---

[4]We underscore again that LM decoding/self-training are not included to isolate the effect of pruning.

Figure 3: Comparison of different pruning techniques on LSR (`wav2vec2` with 10min/1h/10h Librispeech finetuning splits). `PARP` (black line) and `PARP-P` (black dashed line) are especially effective under ultra-low data regime (e.g. 10min) and high-sparsity (70-100%) regions.

Table 1: WER comparison of pruning LSR: `wav2vec2-base` at 90% sparsity with 10h finetuning on Librispeech without LM decoding. At 90% sparsity, `OMP/IMP/MPI` perform nearly as bad as `RP`. sub-finetuning stands for subnetwork finetuning.

Method	# ASR finetunings	test clean	test other
RP + sub-finetuning	1	94.5	96.4
MPI + sub-finetuning	1	93.6	96.1
OMP + sub-finetuning	2	92.0	95.3
IMP + sub-finetuning	10	89.6	93.9
PARP (90% → 90%)	1	83.6	90.7
PARP-P			
70% → 90%	1	51.9	69.1
60% → 80% → 90%	2	33.6	53.3

Table 2: WER comparison of `PARP` for LSR with previous speech SSL results on Librispeech 10min. `PARP` discovers sparse subnetworks within `wav2vec2` with lower WER while adding minimal computational cost to the original ASR finetuning.

Method	test clean	test other
Continuous BERT [2] + LM	49.5	66.3
Discrete BERT [2] + LM	16.3	25.2
`wav2vec2-base` reported [4]	46.9	50.9
`wav2vec2-large` reported [4]	43.5	45.3
`wav2vec2-base` replicated	49.3	53.2
`wav2vec2-large` replicated	46.3	48.1
`wav2vec2-base` w/ 10% `PARP`	38.0	44.3
`wav2vec2-large` w/ 10% `PARP`	33.7	37.2

Next, we examine if the pruning results of LSR transfers to H2L and CSR. Figure 4 is pruning H2L and CSR with 1h of Dutch (*nl*) finetuning, and the same conclusion can be extended to other spoken languages. Comparing Figures 3 and 4, we notice that shapes of their pruning curves are different, which can be attributed to the effect of character versus phone predictions. Comparing left and center of Figure 4, we show that `PARP` and `OMP` reach 50% sparsity on H2L and 70% sparsity on CSR with minimal degradations. Furthermore, while `PARP` is more effective than `OMP` on H2L for all sparsities, such advantage is only visible in the higher sparsity regions on CSR. Lastly, Table 3 compares the subnetworks from H2L and CSR with prior work. Even with as high as 90% sparsities in either settings, subnetworks from `PARP` and `OMP` out-performs prior art.

Figure 4: Comparison of pruning techniques on H2L & CSR with 1h of Dutch (*nl*) ASR finetuning. (**Left**) Pruning H2L (`wav2vec2-base` + *nl*). (**Center**) Pruning CSR (`xlsr` + *nl*). (**Right**) Pruning jointly-finetuned `wav2vec2-base` and `xlsr` on *nl*. Trend is consistent for other 9 spoken languages.

Table 3: Comparing subnetworks discovered by `OMP` and `PARP` from `wav2vec2-base` and `xlsr` with prior work on H2L and CSR. PER is averaged over 10 languages.

Method	Pre-training	Sparsity	avg. PER
Bottleneck [27]	Babel-1070h	0%	44.9
CPC [60]	LS-100h	0%	50.9
Modified CPC [70]	LS-360h	0%	44.5
`wav2vec2-base`	LS-960h	0%	18.7
`wav2vec2 + OMP`	LS-960h	70%	41.3
`wav2vec2 + PARP`	LS-960h	90%	40.1
`xlsr` reported [19]	56,000h	0%	7.6
`xlsr` replicated	56,000h	0%	9.9
`xlsr + OMP`	56,000h	90%	33.9
`xlsr + PARP-P`	56,000h	90%	22.9

Figure 5: `PARP`'s final subnetwork and its initial `MPI` subnetwork exceeds 99.99% `IOU` after 20% sparsity (black line).

Figure 6: `PARP` with random (red line) v.s. with `MPI` (black line) initial subnetworks in LSR.

4.2 How Important is the Initial Subnetwork (Step 1) in `PARP`?

Obtaining a good initial subnetwork (Step 1) is critical for `PARP`, as Adjust & Re-Prune (Step 2) is operated on top of it. In this section, we isolate the effect of Step 1 from Step 2 and examine the role of the initial subnetwork in `PARP`. Figure 6 shows `PARP` with a random subnetwork from `RP`, instead of subnetwork from `MPI`, as the initial subnetwork. `PARP` with random initial subnetwork performs nearly as bad as `RP` (grey line), signifying the importance of the initial subnetwork.

Secondly, despite Observation 1, `MPI` in high sparsity regions (e.g. 90% in LSR) is not a good initial subnetwork, since the majority of the weights are already pruned out (thus is hard to be recovered from). From Figure 3, `PARP` performs only on par or even worse than `IMP` in high sparsity regions. In contrast, `PARP-P` starts with a relatively lower sparsity (e.g. 60% or 70% `MPI`), and progressively prunes up to the target sparsity. Doing so yields considerable performance gain (up to over 50% absolute WER reduction). Third, as shown in Figure 5, there is >99.99% `IOU` between the final "adjusted" subnetwork from `PARP` and its initial `MPI` subnetwork after 20% sparsity, confirming Step 2 indeed only made minimal "adjustment" to the initial subnetwork.

4.3 Are Pruning Masks Transferrable across Spoken Languages?

Is it possible to discover subnetworks with the wrong guidance, and how transferrable are such subnetworks? More concretely, we investigate the transferrability of `OMP` pruning mask discovered from a source language by finetuning its subnetwork on another target language. Such study should shed some insights on the underlying influence of spoken language structure on network pruning – that similar language pairs should be transferrable. From a practical perspective, consider pruning for an unseen new language in H2L, we could deploy the readily available discovered subnetworks and thus save the additional finetuning and memory costs.

In this case, the initial subnetwork of `PARP` is given by applying `OMP` on another spoken language. According to Observation 1, `PARP`'s Step 2 is effectively under-going cross-lingual subnetwork adaptation for the target language. Figure 7 shows the transferrability results on H2L with pre-trained `wav2vec2-base`. On the left is a subnetwork at 50% sparsity transfer with regular finetuning that contains subtle language clusters – for example, when finetuning on *ru*, source masks from *es, fr, it, ky, nl* induces a much higher PER compare to that from *sv-SE, tr, tt, zh-TW*. On the right of Figure 7, we show that there is no cross-lingual PER degradation with `PARP`, supporting our claim above.

4.4 Discovering a Single Subnetwork for 10 Spoken Languages

A major downside of pruning pre-trained SSL models for many downstream tasks is the exponential computational and memory costs. In H2L and CSR, the same pruning method needs to be repeatedly

Figure 7: (**Left**) Cross-lingual `OMP` mask transfer with regular subnetwork finetuning. (**Right**) Cross-lingual `OMP` mask transfer with PARP. Last rows are RP. Values are relative PER gains over same-language pair transfer (hence the darker the bettter). Both are on H2L with pretrained `wav2vec2`. The same observation is observed on CSR with pretrained `xlsr` in Appendix E.

re-run for each downstream spoken language at each given sparsity. Therefore, we investigate the possibility of obtaining a single shared subnetwork for all downstream languages. Instead of finetuning separately for each language, we construct a joint phoneme dictionary and finetune `wav2vec2` and `xlsr` on all 10 languages jointly in H2L and CSR. Note that PARP with joint-finetuning can retrieve a shared subnetwork in a single run. The shared subnetwork can then be decoded for each language separately. The right side of Figure 4 illustrates the results.

Comparing joint-finetuning and individual-finetuning, in H2L, we found that the shared subnetwork obtained via `OMP` has lower PERs between 60∼80% but slightly higher PERs in other sparsity regions; in CSR, the shared subnetwork from `OMP` has slightly worse PERs at all sparsities. Comparing PARP to `OMP` in joint-finetuning, we found that while PARP is effective in the individual-finetuning setting (left of Figure 4), its shared subnetworks are only slightly better than `OMP` in both H2L and CSR (right of Figure 4). The smaller performance gain of PARP over `OMP` in pruning jointly-finetuned models is expected, since the important weights for each language are disjoint and joint-finetuning may send mixed signal to the adjustment step in PARP (see Figure 8 for better illustration).

4.5 Does PARP work on Pre-trained BERT?

We also analyzed whether Observation 1 holds for pre-trained BERT on 9 GLUE tasks. Surprisingly, we found that there are also high (>98%) overlaps between the 9 tasks' IMP pruning masks. Given this observation, we replicated the cross-task subnetwork transfer experiment (take subnetwork found by IMP at task A and finetune it for task B) in BERT-Ticket [15] with PARP. Table 4 compares PARP (averaged for each target task) to those reported in BERT-Ticket, hinting the applicability of PARP to other domains and pre-trained models. Detailed scores and figures are in Appendix F.

Table 4: Comparison of cross-task transfer on GLUE (subnetwork from source task A is finetuned for target task B). Numbers are averaged acc. across source tasks for each target task.

Method	Averaged transferred subnetworks performance found at **70%** sparsity								
	CoLA	MRPC	QNLI	QQP	RTE	SST-2	STS-B	WNLI	MNLI
Same-task Transfer (top line)	40.65	76.23	89.36	91.07	59.93	90.60	86.85	56.34	82.87
PARP	**28.48**	**75.98**	**87.12**	**90.40**	**59.69**	**89.59**	**86.25**	**54.62**	**81.61**
BERT-Ticket [15]	10.12	71.94	86.54	88.50	57.59	88.80	80.27	54.03	80.48

4.6 Implications

Observation 1 is consistent with the findings of probing large pre-trained NLP models such as BERT, that pre-trained SSL models are over-parametrized and there exist task-oriented weights/neurons. Figure 2 implies that these important weights only account for a small part of the pre-trained speech SSL. In fact, a large body of NLP work is dedicated to studying task-oriented weights in pre-trained models. To name a few, [26, 24, 5, 84] measured, [5, 23, 46] leveraged, [57, 34] visualized, and [79, 25, 11] pruned out these important weights/neurons via probing and quantifying contextualized representations. Based on Observation 1, we can project that these NLP results should in general transfer to speech [7, 6, 17]. However, different from them, PARP leverages important weights for `UMP` on the whole network structure instead of just the contextualized representations.

Figure 8: Conceptual sketch of pruning the few task-specific important weights in pretrained SSL. **(A)** Task-aware subnetwork discovery(`OMP`/`IMP`) is more effective than task-agnostic pruning (`MPI`) since it foresees the important weights in advance, via multiple downstream finetunings. **(B)** `PARP` starts with an initial subnetwork given by `MPI`. Observation 1 suggests that the subnetwork is only off by the few important weights, and thus Step 2 revives them by adjusting the initial subnetwork.

We could further hypothesize that a good pruning algorithm avoids pruning out task-specific neurons in pre-trained SSL [49, 36, 55], see Figure 8. This hypothesis not only offers an explanation on why `PARP` is effective in high sparsity regions and cross-lingual mask transfer, it also suggests that an iterative method such as `IMP` is superior to `OMP` because `IMP` gradually avoids pruning out important weights in several iterations, at the cost of more compute[5]. Finally, we make connections to prior work that showed `RP` prevail [9, 15, 53, 54, 68] – under a certain threshold and setting, task-specific neurons are less likely to get "accidentally" pruned and thus accuracy is preserved even with `RP`.

5   Related Work

Modern ASR Paradigm and ASR Pruning. As model scale [76, 4, 38, 35, 91, 66, 65, 92, 13, 88, 50] and model pre-training [4, 93, 19, 45, 43, 47, 42, 86, 12, 44, 72, 71, 59, 62, 81] have become the two essential ingredients for obtaining SOTA performance in ASR and other speech tasks, applying and developing various forms of memory-efficient algorithms, such as network pruning, to these large-scale pre-trained models will predictably soon become an indispensable research endeavor. Early work on ASR pruning can be dated back to pruning decoding search spaces [1, 67, 75, 40, 85, 94] and HMM state space [77]. Since the seminal work of Yu et al. [89], ASR pruning has focused primarily on end-to-end network architecture: [73, 83] applied pruning and quantization to LSTM-based RNN-Transducers, [61] applied knowledge distillation to Conformer-based RNN-Transducers, [78, 74, 52] designed efficient architecture/mechanisms for LSTM, Transformer, Conformer-based ASR models, [58] applied pruning to Deep Speech, [10] introduced SNR-based probabilistic pruning on LSTM-based CTC model, [32] proposed entropy-regularizer for LSTM-based ASR model, [87, 63] applied SVD on ASR models' weight matrices. We emphasize that our work is the first on pruning large self-supervised pre-trained models for low-resource and multi-lingual ASR. In addition, to our knowledge, none of the prior speech pruning work demonstrated the pruned models attain superior performance than its original counterpart.

6   Conclusion and Broader Impact

We introduce `PARP`, a conceptually simple and intuitive pruning method for self-supervised speech recognition. We conduct extensive experiments on pruning pre-trained wav2vec 2.0 and XLSR-53 under three low-resource settings, demonstrating (1) `PARP` discovers better subnetworks than baseline pruning methods while requiring a fraction of their computational cost, (2) the discovered subnetworks yields over 10% WER reduction over the full model, (3) `PARP` induces minimal cross-lingual subnetwork adaptation errors, and (4) `PARP` can discover a shared subnetwork for multiple spoken languages in one pass. The broader impact of this research work lies in two orthogonal dimensions: (i) extending modern-day speech technology to many under-explored low-resource spoken languages, and (ii) introducing a new and flexible pruning technique to current and future speech SSL frameworks that reduces the computational costs required for adapting (finetuning) them to custom settings. We do not see its potential societal harm.

---

[5]In CV, it is standard to iterate the process hundreds of times [36].

References

[1] Sherif Abdou and Michael S Scordilis. Beam search pruning in speech recognition using a posterior probability-based confidence measure. *Speech Communication*, 42(3-4):409–428, 2004.

[2] Alexei Baevski, Michael Auli, and Abdelrahman Mohamed. Effectiveness of self-supervised pre-training for speech recognition. *arXiv preprint arXiv:1911.03912*, 2019.

[3] Alexei Baevski, Steffen Schneider, and Michael Auli. vq-wav2vec: Self-supervised learning of discrete speech representations. *arXiv preprint arXiv:1910.05453*, 2019.

[4] Alexei Baevski, Henry Zhou, Abdelrahman Mohamed, and Michael Auli. wav2vec 2.0: A framework for self-supervised learning of speech representations. *arXiv preprint arXiv:2006.11477*, 2020.

[5] Anthony Bau, Yonatan Belinkov, Hassan Sajjad, Nadir Durrani, Fahim Dalvi, and James Glass. Identifying and controlling important neurons in neural machine translation. *arXiv preprint arXiv:1811.01157*, 2018.

[6] Yonatan Belinkov, Ahmed Ali, and James Glass. Analyzing phonetic and graphemic representations in end-to-end automatic speech recognition. *arXiv preprint arXiv:1907.04224*, 2019.

[7] Yonatan Belinkov and James Glass. Analyzing hidden representations in end-to-end automatic speech recognition systems. *arXiv preprint arXiv:1709.04482*, 2017.

[8] Guillaume Bellec, David Kappel, Wolfgang Maass, and Robert Legenstein. Deep rewiring: Training very sparse deep networks. *arXiv preprint arXiv:1711.05136*, 2017.

[9] Davis Blalock, Jose Javier Gonzalez Ortiz, Jonathan Frankle, and John Guttag. What is the state of neural network pruning? *arXiv preprint arXiv:2003.03033*, 2020.

[10] Stefan Braun and Shih-Chii Liu. Parameter uncertainty for end-to-end speech recognition. In *ICASSP 2019-2019 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5636–5640. IEEE, 2019.

[11] Steven Cao, Victor Sanh, and Alexander M Rush. Low-complexity probing via finding subnetworks. *arXiv preprint arXiv:2104.03514*, 2021.

[12] William Chan, Daniel Park, Chris Lee, Yu Zhang, Quoc Le, and Mohammad Norouzi. Speechstew: Simply mix all available speech recognition data to train one large neural network. *arXiv preprint arXiv:2104.02133*, 2021.

[13] Sanyuan Chen, Yu Wu, Zhuo Chen, Jian Wu, Jinyu Li, Takuya Yoshioka, Chengyi Wang, Shujie Liu, and Ming Zhou. Continuous speech separation with conformer. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5749–5753. IEEE, 2021.

[14] Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Michael Carbin, and Zhangyang Wang. The lottery tickets hypothesis for supervised and self-supervised pre-training in computer vision models. *arXiv preprint arXiv:2012.06908*, 2020.

[15] Tianlong Chen, Jonathan Frankle, Shiyu Chang, Sijia Liu, Yang Zhang, Zhangyang Wang, and Michael Carbin. The lottery ticket hypothesis for pre-trained bert networks. *arXiv preprint arXiv:2007.12223*, 2020.

[16] Jaejin Cho, Murali Karthick Baskar, Ruizhi Li, Matthew Wiesner, Sri Harish Mallidi, Nelson Yalta, Martin Karafiat, Shinji Watanabe, and Takaaki Hori. Multilingual sequence-to-sequence speech recognition: architecture, transfer learning, and language modeling. In *2018 IEEE Spoken Language Technology Workshop (SLT)*, pages 521–527. IEEE, 2018.

[17] Yu-An Chung, Yonatan Belinkov, and James Glass. Similarity analysis of self-supervised speech representations. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3040–3044. IEEE, 2021.

[18] Yu-An Chung, Wei-Ning Hsu, Hao Tang, and James Glass. An unsupervised autoregressive model for speech representation learning. *arXiv preprint arXiv:1904.03240*, 2019.

[19] Alexis Conneau, Alexei Baevski, Ronan Collobert, Abdelrahman Mohamed, and Michael Auli. Unsupervised cross-lingual representation learning for speech recognition. *arXiv preprint arXiv:2006.13979*, 2020.

[20] Jia Cui, Xiaodong Cui, Bhuvana Ramabhadran, Janice Kim, Brian Kingsbury, Jonathan Mamou, Lidia Mangu, Michael Picheny, Tara N Sainath, and Abhinav Sethy. Developing speech recognition systems for corpus indexing under the iarpa babel program. In *2013 IEEE International Conference on Acoustics, Speech and Signal Processing*, pages 6753–6757. IEEE, 2013.

[21] Jia Cui, Brian Kingsbury, Bhuvana Ramabhadran, Abhinav Sethy, Kartik Audhkhasi, Xiaodong Cui, Ellen Kislal, Lidia Mangu, Markus Nussbaum-Thom, Michael Picheny, et al. Multilingual representations for low resource speech recognition and keyword search. In *2015 IEEE Workshop on Automatic Speech Recognition and Understanding (ASRU)*, pages 259–266. IEEE, 2015.

[22] Xiaodong Cui, Brian Kingsbury, Jia Cui, Bhuvana Ramabhadran, Andrew Rosenberg, Mohammad Sadegh Rasooli, Owen Rambow, Nizar Habash, and Vaibhava Goel. Improving deep neural network acoustic modeling for audio corpus indexing under the iarpa babel program. In *Fifteenth Annual Conference of the International Speech Communication Association*, 2014.

[23] Damai Dai, Li Dong, Yaru Hao, Zhifang Sui, and Furu Wei. Knowledge neurons in pretrained transformers. *arXiv preprint arXiv:2104.08696*, 2021.

[24] Fahim Dalvi, Nadir Durrani, Hassan Sajjad, Yonatan Belinkov, Anthony Bau, and James Glass. What is one grain of sand in the desert? analyzing individual neurons in deep nlp models. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pages 6309–6317, 2019.

[25] Fahim Dalvi, Hassan Sajjad, Nadir Durrani, and Yonatan Belinkov. Analyzing redundancy in pretrained transformer models. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, pages 4908–4926, 2020.

[26] Nadir Durrani, Hassan Sajjad, Fahim Dalvi, and Yonatan Belinkov. Analyzing individual neurons in pre-trained language models. *arXiv preprint arXiv:2010.02695*, 2020.

[27] Radek Fer, Pavel Matějka, František Grézl, Oldřich Plchot, Karel Veselỳ, and Jan Honza Černockỳ. Multilingually trained bottleneck features in spoken language recognition. *Computer Speech & Language*, 46:252–267, 2017.

[28] Jonathan Frankle and Michael Carbin. The lottery ticket hypothesis: Finding sparse, trainable neural networks. *arXiv preprint arXiv:1803.03635*, 2018.

[29] Jonathan Frankle, Gintare Karolina Dziugaite, Daniel Roy, and Michael Carbin. Linear mode connectivity and the lottery ticket hypothesis. In *International Conference on Machine Learning*, pages 3259–3269. PMLR, 2020.

[30] Trevor Gale, Erich Elsen, and Sara Hooker. The state of sparsity in deep neural networks. *arXiv preprint arXiv:1902.09574*, 2019.

[31] Mark JF Gales, Kate M Knill, Anton Ragni, and Shakti P Rath. Speech recognition and keyword spotting for low-resource languages: Babel project research at cued. In *Fourth International Workshop on Spoken Language Technologies for Under-Resourced Languages (SLTU-2014)*, pages 16–23. International Speech Communication Association (ISCA), 2014.

[32] Dawei Gao, Xiaoxi He, Zimu Zhou, Yongxin Tong, Ke Xu, and Lothar Thiele. Rethinking pruning for accelerating deep inference at the edge. In *Proceedings of the 26th ACM SIGKDD International Conference on Knowledge Discovery & Data Mining*, pages 155–164, 2020.

[33] Sharath Girish, Shishira R Maiya, Kamal Gupta, Hao Chen, Larry Davis, and Abhinav Shrivastava. The lottery ticket hypothesis for object recognition. *arXiv preprint arXiv:2012.04643*, 2020.

[34] Gabriel Goh, Nick Cammarata, Chelsea Voss, Shan Carter, Michael Petrov, Ludwig Schubert, Alec Radford, and Chris Olah. Multimodal neurons in artificial neural networks. *Distill*, 6(3):e30, 2021.

[35] Anmol Gulati, James Qin, Chung-Cheng Chiu, Niki Parmar, Yu Zhang, Jiahui Yu, Wei Han, Shibo Wang, Zhengdong Zhang, Yonghui Wu, et al. Conformer: Convolution-augmented transformer for speech recognition. *arXiv preprint arXiv:2005.08100*, 2020.

[36] Yiwen Guo, Anbang Yao, and Yurong Chen. Dynamic network surgery for efficient dnns. *arXiv preprint arXiv:1608.04493*, 2016.

[37] Song Han, Jeff Pool, John Tran, and William J Dally. Learning both weights and connections for efficient neural networks. *arXiv preprint arXiv:1506.02626*, 2015.

[38] Wei Han, Zhengdong Zhang, Yu Zhang, Jiahui Yu, Chung-Cheng Chiu, James Qin, Anmol Gulati, Ruoming Pang, and Yonghui Wu. Contextnet: Improving convolutional neural networks for automatic speech recognition with global context. *arXiv preprint arXiv:2005.03191*, 2020.

[39] Babak Hassibi and David G Stork. *Second order derivatives for network pruning: Optimal brain surgeon*. Morgan Kaufmann, 1993.

[40] Tianxing He, Yuchen Fan, Yanmin Qian, Tian Tan, and Kai Yu. Reshaping deep neural network for fast decoding by node-pruning. In *2014 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 245–249. IEEE, 2014.

[41] Wei-Ning Hsu, Anuroop Sriram, Alexei Baevski, Tatiana Likhomanenko, Qiantong Xu, Vineel Pratap, Jacob Kahn, Ann Lee, Ronan Collobert, Gabriel Synnaeve, et al. Robust wav2vec 2.0: Analyzing domain shift in self-supervised pre-training. *arXiv preprint arXiv:2104.01027*, 2021.

[42] Wei-Ning Hsu, Yao-Hung Hubert Tsai, Benjamin Bolte, Ruslan Salakhutdinov, and Abdelrahman Mohamed. Hubert: How much can a bad teacher benefit asr pre-training? In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6533–6537. IEEE, 2021.

[43] Dongwei Jiang, Wubo Li, Miao Cao, Ruixiong Zhang, Wei Zou, Kun Han, and Xiangang Li. Speech simclr: Combining contrastive and reconstruction objective for self-supervised speech representation learning. *arXiv preprint arXiv:2010.13991*, 2020.

[44] Naoyuki Kanda, Guoli Ye, Yu Wu, Yashesh Gaur, Xiaofei Wang, Zhong Meng, Zhuo Chen, and Takuya Yoshioka. Large-scale pre-training of end-to-end multi-talker asr for meeting transcription with single distant microphone. *arXiv preprint arXiv:2103.16776*, 2021.

[45] Qiuqiang Kong, Yin Cao, Turab Iqbal, Yuxuan Wang, Wenwu Wang, and Mark D Plumbley. Panns: Large-scale pretrained audio neural networks for audio pattern recognition. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 28:2880–2894, 2020.

[46] Olga Kovaleva, Alexey Romanov, Anna Rogers, and Anna Rumshisky. Revealing the dark secrets of bert. *arXiv preprint arXiv:1908.08593*, 2019.

[47] Cheng-I Lai, Yung-Sung Chuang, Hung-Yi Lee, Shang-Wen Li, and James Glass. Semi-supervised spoken language understanding via self-supervised speech and language model pretraining. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 7468–7472. IEEE, 2021.

[48] Yann LeCun, John S Denker, and Sara A Solla. Optimal brain damage. In *Advances in neural information processing systems*, pages 598–605, 1990.

[49] Namhoon Lee, Thalaiyasingam Ajanthan, and Philip HS Torr. Snip: Single-shot network pruning based on connection sensitivity. *arXiv preprint arXiv:1810.02340*, 2018.

[50] Bo Li, Ruoming Pang, Tara N Sainath, Anmol Gulati, Yu Zhang, James Qin, Parisa Haghani, W Ronny Huang, and Min Ma. Scaling end-to-end models for large-scale multilingual asr. *arXiv preprint arXiv:2104.14830*, 2021.

[51] Hao Li, Asim Kadav, Igor Durdanovic, Hanan Samet, and Hans Peter Graf. Pruning filters for efficient convnets. *arXiv preprint arXiv:1608.08710*, 2016.

[52] Shengqiang Li, Menglong Xu, and Xiao-Lei Zhang. Efficient conformer-based speech recognition with linear attention. *arXiv preprint arXiv:2104.06865*, 2021.

[53] Zhuang Liu, Mingjie Sun, Tinghui Zhou, Gao Huang, and Trevor Darrell. Rethinking the value of network pruning. *arXiv preprint arXiv:1810.05270*, 2018.

[54] Eran Malach, Gilad Yehudai, Shai Shalev-Schwartz, and Ohad Shamir. Proving the lottery ticket hypothesis: Pruning is all you need. In *International Conference on Machine Learning*, pages 6682–6691. PMLR, 2020.

[55] Pavlo Molchanov, Arun Mallya, Stephen Tyree, Iuri Frosio, and Jan Kautz. Importance estimation for neural network pruning. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11264–11272, 2019.

[56] Rajiv Movva and Jason Y Zhao. Dissecting lottery ticket transformers: Structural and behavioral study of sparse neural machine translation. *arXiv preprint arXiv:2009.13270*, 2020.

[57] Jesse Mu and Jacob Andreas. Compositional explanations of neurons. *arXiv preprint arXiv:2006.14032*, 2020.

[58] Sharan Narang, Erich Elsen, Gregory Diamos, and Shubho Sengupta. Exploring sparsity in recurrent neural networks. *arXiv preprint arXiv:1704.05119*, 2017.

[59] Edwin G Ng, Chung-Cheng Chiu, Yu Zhang, and William Chan. Pushing the limits of non-autoregressive speech recognition. *arXiv preprint arXiv:2104.03416*, 2021.

[60] Aaron van den Oord, Yazhe Li, and Oriol Vinyals. Representation learning with contrastive predictive coding. *arXiv preprint arXiv:1807.03748*, 2018.

[61] Sankaran Panchapagesan, Daniel S Park, Chung-Cheng Chiu, Yuan Shangguan, Qiao Liang, and Alexander Gruenstein. Efficient knowledge distillation for rnn-transducer models. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 5639–5643. IEEE, 2021.

[62] Adam Polyak, Yossi Adi, Jade Copet, Eugene Kharitonov, Kushal Lakhotia, Wei-Ning Hsu, Abdelrahman Mohamed, and Emmanuel Dupoux. Speech resynthesis from discrete disentangled self-supervised representations. *arXiv preprint arXiv:2104.00355*, 2021.

[63] Daniel Povey, Gaofeng Cheng, Yiming Wang, Ke Li, Hainan Xu, Mahsa Yarmohammadi, and Sanjeev Khudanpur. Semi-orthogonal low-rank matrix factorization for deep neural networks. In *Interspeech*, pages 3743–3747, 2018.

[64] Sai Prasanna, Anna Rogers, and Anna Rumshisky. When bert plays the lottery, all tickets are winning. *arXiv preprint arXiv:2005.00561*, 2020.

[65] Vineel Pratap, Anuroop Sriram, Paden Tomasello, Awni Hannun, Vitaliy Liptchinsky, Gabriel Synnaeve, and Ronan Collobert. Massively multilingual asr: 50 languages, 1 model, 1 billion parameters. *arXiv preprint arXiv:2007.03001*, 2020.

[66] Vineel Pratap, Qiantong Xu, Jacob Kahn, Gilad Avidov, Tatiana Likhomanenko, Awni Hannun, Vitaliy Liptchinsky, Gabriel Synnaeve, and Ronan Collobert. Scaling up online speech recognition using convnets. *arXiv preprint arXiv:2001.09727*, 2020.

[67] Janne Pylkkönen. New pruning criteria for efficient decoding. In *Ninth European Conference on Speech Communication and Technology*, 2005.

[68] Vivek Ramanujan, Mitchell Wortsman, Aniruddha Kembhavi, Ali Farhadi, and Mohammad Rastegari. What's hidden in a randomly weighted neural network? In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11893–11902, 2020.

[69] Alex Renda, Jonathan Frankle, and Michael Carbin. Comparing rewinding and fine-tuning in neural network pruning. *arXiv preprint arXiv:2003.02389*, 2020.

[70] Morgane Rivière, Armand Joulin, Pierre-Emmanuel Mazaré, and Emmanuel Dupoux. Unsupervised pretraining transfers well across languages. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 7414–7418. IEEE, 2020.

[71] Aaqib Saeed, David Grangier, and Neil Zeghidour. Contrastive learning of general-purpose audio representations. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3875–3879. IEEE, 2021.

[72] Ramon Sanabria, Austin Waters, and Jason Baldridge. Talk, don't write: A study of direct speech-based image retrieval. *arXiv preprint arXiv:2104.01894*, 2021.

[73] Yuan Shangguan, Jian Li, Qiao Liang, Raziel Alvarez, and Ian McGraw. Optimizing speech recognition for the edge. *arXiv preprint arXiv:1909.12408*, 2019.

[74] Yangyang Shi, Yongqiang Wang, Chunyang Wu, Ching-Feng Yeh, Julian Chan, Frank Zhang, Duc Le, and Mike Seltzer. Emformer: Efficient memory transformer based acoustic model for low latency streaming speech recognition. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6783–6787. IEEE, 2021.

[75] Vesa Siivola, Teemu Hirsimaki, and Sami Virpioja. On growing and pruning kneser–ney smoothed n-gram models. *IEEE Transactions on Audio, Speech, and Language Processing*, 15(5):1617–1624, 2007.

[76] Gabriel Synnaeve, Qiantong Xu, Jacob Kahn, Tatiana Likhomanenko, Edouard Grave, Vineel Pratap, Anuroop Sriram, Vitaliy Liptchinsky, and Ronan Collobert. End-to-end asr: from supervised to semi-supervised learning with modern architectures. *arXiv preprint arXiv:1911.08460*, 2019.

[77] Hugo Van Hamme and Filip Van Aelten. An adaptive-beam pruning technique for continuous speech recognition. In *Proceeding of Fourth International Conference on Spoken Language Processing. ICSLP'96*, volume 4, pages 2083–2086. IEEE, 1996.

[78] Ganesh Venkatesh, Alagappan Valliappan, Jay Mahadeokar, Yuan Shangguan, Christian Fuegen, Michael L Seltzer, and Vikas Chandra. Memory-efficient speech recognition on smart devices. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 8368–8372. IEEE, 2021.

[79] Elena Voita, David Talbot, Fedor Moiseev, Rico Sennrich, and Ivan Titov. Analyzing multi-head self-attention: Specialized heads do the heavy lifting, the rest can be pruned. *arXiv preprint arXiv:1905.09418*, 2019.

[80] Alex Wang, Amanpreet Singh, Julian Michael, Felix Hill, Omer Levy, and Samuel R Bowman. Glue: A multi-task benchmark and analysis platform for natural language understanding. *arXiv preprint arXiv:1804.07461*, 2018.

[81] Jun Wang, Max W Y Lam, Dan Su, and Dong Yu. Contrastive separative coding for self-supervised representation learning. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3865–3869. IEEE, 2021.

[82] Weiran Wang, Qingming Tang, and Karen Livescu. Unsupervised pre-training of bidirectional speech encoders via masked reconstruction. In *ICASSP 2020-2020 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6889–6893. IEEE, 2020.

[83] Zhaofeng Wu, Ding Zhao, Qiao Liang, Jiahui Yu, Anmol Gulati, and Ruoming Pang. Dynamic sparsity neural networks for automatic speech recognition. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6014–6018. IEEE, 2021.

[84] Ji Xin, Jimmy Lin, and Yaoliang Yu. What part of the neural network does this? understanding lstms by measuring and dissecting neurons. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing and the 9th International Joint Conference on Natural Language Processing (EMNLP-IJCNLP)*, pages 5827–5834, 2019.

[85] Hainan Xu, Tongfei Chen, Dongji Gao, Yiming Wang, Ke Li, Nagendra Goel, Yishay Carmiel, Daniel Povey, and Sanjeev Khudanpur. A pruned rnnlm lattice-rescoring algorithm for automatic speech recognition. In *2018 IEEE international conference on acoustics, speech and signal processing (ICASSP)*, pages 5929–5933. IEEE, 2018.

[86] Qiantong Xu, Alexei Baevski, Tatiana Likhomanenko, Paden Tomasello, Alexis Conneau, Ronan Collobert, Gabriel Synnaeve, and Michael Auli. Self-training and pre-training are complementary for speech recognition. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 3030–3034. IEEE, 2021.

[87] Jian Xue, Jinyu Li, and Yifan Gong. Restructuring of deep neural network acoustic models with singular value decomposition. In *Interspeech*, pages 2365–2369, 2013.

[88] Zhao You, Shulin Feng, Dan Su, and Dong Yu. Speechmoe: Scaling to large acoustic models with dynamic routing mixture of experts. *arXiv preprint arXiv:2105.03036*, 2021.

[89] Dong Yu, Frank Seide, Gang Li, and Li Deng. Exploiting sparseness in deep neural networks for large vocabulary speech recognition. In *2012 IEEE International conference on acoustics, speech and signal processing (ICASSP)*, pages 4409–4412. IEEE, 2012.

[90] Haonan Yu, Sergey Edunov, Yuandong Tian, and Ari S Morcos. Playing the lottery with rewards and multiple languages: lottery tickets in rl and nlp. *arXiv preprint arXiv:1906.02768*, 2019.

[91] Jiahui Yu, Wei Han, Anmol Gulati, Chung-Cheng Chiu, Bo Li, Tara N Sainath, Yonghui Wu, and Ruoming Pang. Universal asr: Unify and improve streaming asr with full-context modeling. *arXiv preprint arXiv:2010.06030*, 2020.

[92] Jiahui Yu, Wei Han, Anmol Gulati, Chung-Cheng Chiu, Bo Li, Tara N Sainath, Yonghui Wu, and Ruoming Pang. Dual-mode asr: Unify and improve streaming asr with full-context modeling. *Proceedings of ICLR*, 2021.

[93] Yu Zhang, James Qin, Daniel S Park, Wei Han, Chung-Cheng Chiu, Ruoming Pang, Quoc V Le, and Yonghui Wu. Pushing the limits of semi-supervised learning for automatic speech recognition. *arXiv preprint arXiv:2010.10504*, 2020.

[94] Yuekai Zhang, Sining Sun, and Long Ma. Tiny transducer: A highly-efficient speech recognition model on edge devices. In *ICASSP 2021-2021 IEEE International Conference on Acoustics, Speech and Signal Processing (ICASSP)*, pages 6024–6028. IEEE, 2021.