DECN: Evolution Inspired Deep Convolution Network for Black-box Optimization

Abstract

We design a deep evolutionary convolution network (DECN) for continuous black-box optimization. DECN is composed of two modules: convolution-based reasoning module (CRM) and selection module (SM), to force the random population to move near the optimal solution. CRM produces a population that is closer to the optimal solution based on the convolution operators, and SM removes poor solutions. We also design a proper loss function to support the training of DECN. The experimental results on unconstrained continuous optimization problems show that DECN surpasses black-box optimization baselines. Moreover, DECN obtains good performance when transferred to optimization problems unseen during the training stage. In addition, DECN is friendly to the acceleration with Graphics Processing Units (GPUs) and runs 102 times faster than unaccelerated EA when evolving 32 populations, each containing 6400 individuals.

1 Introduction

Optimization has been an old and essential research topic in history; Many tasks in computer vision, machine learning, and natural language processing can be abstracted as optimization problems. Moreover, many of these problems are black-box, such as neural architecture search Elsken et al. (2019) and hyperparameter optimization Hutter et al. (2019). Various approaches, such as Bayesian optimization Snoek et al. (2012), evolutionary algorithms (EAs) Jin et al. (2019); Khadka & Tumer (2018); Zhang & Li (2007), and evolutionary strategies (ES) Wierstra et al. (2014); Vicol et al. (2021); Hansen & Ostermeier (2001); Auger & Hansen (2005); Salimans et al. (2017), have been proposed to deal with these problems in the past.

Unlike the above methods, this paper attempts to develop a deep evolutionary convolution network (DECN) to learn to exploit structure in the problem of interest so that DECN can move a random population near the optimal solution for different black-box optimization tasks automatically. However, there are two key issues: *1) how to design the suitable DECN structure to implement the mapping from the initial population to the optimal population and 2) how to train the designed DECN.*

The DECN structure takes advantage of EAs and convolution neural networks (CNN) to overcome the first issue. Like EAs, we propose two critical components of DECN to generate and select potential solutions: a convolution-based reasoning module (CRM) and a selection module (SM). For CRM, we find a similar expression between the convolution operators and recombination operators, which gives us an idea to design a lattice-like environment organizing the population into convolution operators and then employ mirror padding Goodfellow et al. (2016) to generate the potential offspring. Inspired by the selection operator in EAs, SM updates the population to survive the fittest solutions. Moreover, SM is based on a pairwise comparison between the offspring and the input population regarding their fitness, implemented by employing the mask operator. Then, we design the evolution module (EM) based on CRM and SM to simulate one generation of EAs. Finally, we build the DECN by stacking several EMs to cope with the first issue.

Training DECN is a challenging task. Based on the back-propagation and supervised learning, the parameters of DECN can be updated when the optimal and initial populations are available. However, the optimal population is usually unknown. To overcome the second issue, the following questions must be solved: how to design a proper loss function and training dataset. We maximize the difference between the initial and output populations to train DECN towards the optimal solution. Moreover, for black-box optimization, the gradient is unavailable during the training process. We establish the

training set by designing a set of differentiable functions related to the optimization task, where the loss function can be optimized by back-propagation.

We test the performance of DECN on six standard black-box functions and protein docking problems. Three population-based optimization baselines, Bayesian optimization, and a learning-to-optimize method for black-box optimization Cao et al. (2019) are employed as references. The results indicate that DECN can automatically learn efficient mapping for unconstrained continuous optimization. In addition, DECN is transferred to unseen objective functions during the training stage. The results verify the good generalization capability of DECN. Finally, to verify that DECN is friendly to Graphics Processing Units (GPUs)' acceleration, we compare the runtime of DECNs on one 1080Ti GPU with the standard EA.

2 RELATED WORK

There are many efforts that can handle black-box optimization, such as Bayesian optimization Snoek et al. (2012) and EAs Mitchell (1998). Since the processing object of DECN is population, it has a strong relationship with EA; at the same time, DECN uses the CNN framework to replace the original crossover, mutation, and selection operations of EA, which is a learning-to-optimize (L2O) framework. Therefore, this section mainly introduces the differences between them and DECN.

EAs. EAs are inspired by the evolution of species and have provided surprising performance for black-box optimization. There are two essential parts to EAs: 1) crossover and mutation: how to generate individuals with the potential to approach the optimal solution; 2) selection: how to discard individuals with inferior performance while maintaining the ones with superior performance. In the past decades, many algorithmic components have been designed for different tasks in EAs. The performance of algorithms varies towards various tasks, as different optimization strategies may be required given diverse landscapes. This paper focuses on two critical issues of EAs: 1) for different problems, existing methods manually adjust genetic operators' hyperparameters and design the combination between them Kerschke et al. (2019); Tian et al. (2020); 2) The acceleration of EAs using GPUs is a challenging task. The support for multiple subpopulations to evolve simultaneously has paramount significance in practical applications. Besides, many available genetic operators are unfriendly to the GPU acceleration, as GPUs are weak in processing logical operations. For the evolutionary optimization community, the proposed DECN brings a new and efficient neural network model to this community. It is adapted to different optimization scenarios, based on which DECN automatically forms optimization strategies without relying on supervised information.

L2O. The most related work is about L2O Chen et al. (2021). These methods employ the long short-term memory architecture (LSTM) or multilayer perceptron (MLP) as the optimizer to achieve point-based optimization Sun et al. (2018); Chen et al. (2020); Andrychowicz et al. (2016); Chen et al. (2017); Vicol et al. (2021); Flennerhag et al. (2021); Li & Malik (2016); Metz et al. (2019); Wichrowska et al. (2017); Bello et al. (2017); Sun et al. (2018). However, none of the above methods can handle black-box optimization. Swarm-inspired meta-optimizer Cao et al. (2019) learns in the algorithmic space of both point-based and population-based optimization algorithms. This method does not consider the advantage of EAs and is a model-free method. Existing L2O techniques rarely focus on black-box optimization. Although several efforts like Cao et al. (2019); Chen et al. (2017) have coped with these problems, they all deal with small-scale problems. In EAs, the design of each operator after years of precipitation, their existence is justified, and they have shown high performance in various applications. We combine these advantages to design a CNN-based L2O framework for population-based black-box optimization.

3 BACKGROUND

Problem Definition. An unconstrained optimization problem can be transformed or represented by a minimization problem, as shown in Eq. 1, and constraints may exist for corresponding solutions:

$$\min\ f(s), s.t.\ x_i \in [d_i, u_i], \forall x_i \in s, \tag{1}$$

where $s = (x_1, x_2, \cdots, x_D)$, $d = (d_1, d_2, \cdots, d_D)$ and $u = (u_1, u_2, \cdots, u_D)$. s represents the solution of optimization problem f while d and u denote the corresponding lower and upper bounds of the solution's domain, respectively. Suppose n individuals of one population be $s_1 =$

$(x_1^1, x_2^1, \cdots, x_D^1), s_2 = (x_1^2, x_2^2, \cdots, x_D^2), \cdots, s_n = (x_1^n, x_2^n, \cdots, x_D^n)$. This paper aims to make the initial population move near the optimal solution, as shown in Fig. 1.

Recombination. The subtraction is applicable during the production of a new individual, such as DE Das & Suganthan (2010) and recombination operator in EAs, usually conducted on n individuals. After an expression expansion, this process can be summarized by a weighted recombination process as given in Eq. 2. These operators are manually designed with different parameters (a_i).

$$s^* = a_1 \times s_1 + a_2 \times s_2 + \cdots + a_n \times s_n = \sum_{i=1}^{n} a_i \times s_i. \quad (2)$$

Selection. Many selection operators exist, such as the binary tournament mating selection operator in Eq. 3. The selection operator is to retain individuals of higher quality for the next generation, which can be regarded as an information selection process.

$$p_i = \begin{cases} 1 & f(s_i) < f(s_k) \\ 0 & f(s_i) > f(s_k) \end{cases}, \quad (s_i, s_k) \in S, \quad (3)$$

where p_i reflects the probability that s_i is selected for the next generation, and (s_i, s_k) in Eq. 3 are randomly selected from the population S. The selection process will be repeated until the number of individuals is chosen.

4 DEEP EVOLUTIONARY CONVOLUTION NETWORK

The procedure of DECN can be formulated as $S_t = G_{\theta \leftarrow \varphi(f(s|\xi))}(S_0, f(s|\xi))$. DECN determines the optimization strategy θ based on the feature $\varphi(f(s|\xi))$ extracted from the optimization task $f(s|\xi)$; $\varphi(f(s|\xi))$ is mapped to θ, s is the target to be optimized, and ξ is the known parameters of f. Based on θ, DECN optimizes $f(s|\xi)$ by $S_t = G_\theta(S_0, f(s|\xi))$. To be noted, θ is the parameters (strategies) of G, while G is an abstract function remarking the optimization process, where S_0 is the initial population and S_t is the output population.

Figure 1: The goal of DECN in solving two dimensional problem.

4.1 CONVOLUTION-BASED REASONING MODULE

The capability to reason over available information is essential for learning to optimize. This part mainly describes (1) *the shared commonalities between convolution operator and recombination operators*; (2) *how to construct CRM to generate new offspring*.

The convolution operator Krizhevsky et al. (2012) is widely employed in computer vision to detect local features with the convolution kernel. With various parameters designed in the kernels, the convolution has a wide application to see different local features. We first introduce the formulation of the convolution operator given as follows,

$$g(i, j) = \sum_{k,l} f(k, l)h(i + k, j + l), \quad s.t. \quad f(k, l) = w_{k,l}, \quad h(i + k, j + l) = p_{i+k,j+l}, \quad (4)$$

where $p_{i,j}$ denotes the pixel value in the input image if we handle the image task, (i, j) locates the position of pixel, $g(i, j)$ denotes the output values (feature) of convolution, and $w_{k,l}$ represents the related parameters of convolution kernels. As seen, with a window sliding on the image, the pixels within the window are multiplied element-wise with the parameters in the convolution kernel and finally summed together.

We find that Eqs. 2 and 4 have a similar expression, which motivates us to construct a module to realize the function of generating new offspring. However, there are differences between Eq. 2 and Eq. 4: 1) the operative dimensions in Eqs. 2 and 4 are different; 2) $p_{i,j}$ in Eq. 4 is a pixel value, but s_i in Eq. 2 is an individual represented by a vector. After that, unlike pixel-level recombination

in image processing, recombination operators in EAs conduct the information interaction among individuals; 3) The feature patterns in images may not exist in the population of EAs. We need to establish the population patterns with the corresponding strategy. In this case, the following parts will discuss overcoming these issues.

Organize Population into Convolution. Current deep learning technology constructs a tensor (i, j, c) by concatenating the feature maps output by various convolution kernels operating upon the input image, where (i, j) locates the position of pixels and c determines the feature channels. To implement a recombination operator based on convolution, we arrange all individuals in a lattice-like environment with a size of $L \times L$. The population is organized as multi-channel image data. In this case, we can represent the population by using a tensor (i, j, d), where (i, j) locates the position of one individual in the $L \times L$ lattice and d is the dimension information of this individual. Appendix A.3 gives an illustration of the tensor data. As shown in Fig. 2, individuals in the lattice are sorted in descending order to construct a population tensor with a consistent pattern. Suppose a population $S = s_1, s_2, \cdots, s_{L \times L}$ and

Figure 2: Organizing a population into a tensor.

$f(s_1) < f(s_2) < \cdots < f(s_{L \times L})$, where $f(s)$ is a minimization task. $s_1, s_2, \cdots, s_{L \times L}$ are arranged in descending order within the $L \times L$ lattice. The number of channels in input tensors is $D+1$, where D is the dimension of the optimization task, and the fitness of individuals occupies one channel. The fitness channel does not participate in the convolution process but is essential for the information selection in the selection module.

How to Design CRM. The traditional convolution operator usually merges the information simultaneously among different channels and locations. Although a population can be organized as a tensor by the above subsection, the standard convolution operator cannot merge information in different dimensions similar to recombination operators. Thus, we employ the depthwise separable convolution (DSC) operator Chollet (2017), which includes a depthwise convolution followed by a pointwise convolution to handle this issue. The DSC operator is a widely employed convolution method to reduce computational costs. The DSC operator recombines the neighborhood information while separating the information into different dimensions. If convolving each channel, it is the depthwise convolution. Pointwise convolution maps the output channel of depthwise convolution to a new channel space. When applied to our task, we remove the pointwise convolution in DSC to avoid the information interaction between channels. Moreover, to adapt to optimization tasks with different dimensions, different channels share the same parameters.

After organizing the population into a tensor $(L, L, D + 1)$, we employ the modified DSC operator to generate new individuals. Besides, the parameters within convolution kernels record the strategies learned by this module to reason over available populations given different tasks. Eq. 5 provides the details about how to reproduce offspring by the DSC operator, and one example is shown in Appendix A.1.

$$S^{'}(i, j) = \sum_{k,l} f(k,l)S(i+k, j+l) = \sum_{k,l} w_{k,l}S_{i+k, j+l}, \tag{5}$$

where $S^{'}(i, j)$ denotes the individuals in the output population, $S(i, j)$ denotes the individuals in the input population, and $w_{k,l}$ records how DECN implements reproducing new offspring.

Since there does not exist a consistent pattern in the population, the gradient upon parameters is unstable as well as divergent. Thus, the proposed convolution-based module cannot work based on the back-propagation. Based on the characteristic of recombination operations within EAs, the module's attention to available information should be relative to the quality and diversity of the population.

Thus, a fitness-sensitive convolution is necessary. Here, $w_{k,l}$ reflects the module's attention during reasoning and is usually relative to the fitness of individuals. After that, this problem is resolved by simply sorting the population in the lattice based on individuals' fitness, as shown in Fig. 2. DECN may achieve reasoning functions like recombination operators to reproduce individuals with higher quality in the global search range. More importantly, we can train the parameters within convolution kernels without worrying about unstable and divergent gradients.

Another vital issue is the scale of the offspring. We conduct padding before the convolution operator to maintain the same scale as the input population. However, filling the tensor of the population with constant values '0' is not proper, as is usually done in computer vision. Instead, mirror padding copies the individuals to maintain the same scale between the offspring and the input population. Figure 3 gives an example of population arrangement and padding for the problem min $f(s) = x_1 \times x_1$, where $s = x_1, x_1 \in [0, 10]$. The blue part marks the population arranged in a 10×10 lattice, while the gray region marks the mirror padding part. As the recombination process conducts the information interaction among individuals, copying the individual is better than extending tensors with a constant value. The size of convolution kernels within CRM determines the number of individuals employed to implement reasoning of $S'(i, j)$. There are several essential issues necessary to be considered.

Figure 3: Population arrangement and padding.

1) **How many individuals should participate in the CRM reasoning progress**. It remains a challenge to implement information reasoning over multi-individuals in EAs. In most recombination operators, the participant number is usually set to 2. However, based on the gradient information provided by the back-propagation, it is easy to control an individual's element by adjusting $w_{k,l}$.

2) **How to integrate the offspring produced by different convolution kernels**. Since the convolution operation can be transformed as a multiplication between matrices, simply averaging over the results output by different convolution kernels does not influence the training process. For example, $a_1 Co^1 x_1^i + a_2 Co^2 x_2^i + a_3 Co^3 x_3^i \leftrightarrow Co'^1 x_1^i + Co'^2 x_2^i + Co'^3 x_3^i$, where x_1^i, x_2^i, and x_3^i are input elements of s_i, a_1, a_2, and a_3 are the constant, and Co denotes the convolution matrix.

Figure 4: Reproduction of the offspring based on CRM.

3) **How many convolution kernels should be used within CRM**. We suppose that these are three convolution kernels for x. We can find that the outcome $a_1 Co_{3\times3}^1 x + a_2 Co_{3\times3}^2 x + a_3 Co_{3\times3}^3 x$ is equivalent to $a' Co_{3\times3}' x$. The output of multiple convolution kernels can be replaced by one convolution kernel. Thus, the number of convolution kernels of the same size has no apparent influence on DECN.

4) **The impact of neighborhood recombination operation**. The neighborhood recombination operation has been commonly accepted in EAs to alleviate the selection pressure and prevent the premature convergence of populations. Moreover, the receptive field of convolution kernels expands as the number of layers increases.

After that, this paper employs convolution kernels with commonly used sizes. Different convolution kernels produce corresponding output tensors, while the final offspring are obtained by averaging multiple convolutions' output. Then, the fitness of this final offspring will be evaluated. For an individual s_i, its fitness value is evaluated by $f(Co(s_i))$. Suppose the domain of $x_j^i (j = 1, \cdots, D)$ be $[d_j, u_j]$, if $x_j^i > u_j$, $x_j^i = u_j$; if $x_j^i < d_j$, $x_j^i = d_j$. Fig. 4 provides a illustration of CRM.

Figure 5: SM. An indication matrix is produced by subtracting the fitness channel (c_1), based on which individuals within the input and output populations can be extracted to form offspring.

4.2 SELECTION MODULE

The selection module updates the population so as to survive the fittest individuals. SM updates individuals based on a pairwise comparison between the offspring and input population regarding their fitness for efficiency and simplicity. S_{i-1} and S'_{i-1} are the input and output populations of CRM, respectively. As shown in Figure 8 (see Appendix A.1), S_{i-1} and S'_{i-1} contain $D+1$ channels. The first channel stores the fitness value of an individual. Thereafter, a matrix subtraction of fitness channel corresponding to S_{i-1} and S'_{i-1} compares the quality of individuals from S_{i-1} and S'_{i-1} pairwise. A binary mask matrix indicating the selected individual can be obtained based on the indicator function $l_{x>0}(x)$, where $l_{x>0}(x) = 1$ if $x > 0$ and $l_{x>0}(x) = 0$ if $x < 0$. To extract selected individuals from S_{i-1} and S'_{i-1}, we construct a binary mask tensor by copying and extending the mask matrix to the same shape as S_{i-1} and S'_{i-1}. The selected information forms a new tensor S_i by employing Eq. 6 illustrated in Fig. 5.

$$S_i = tile(l_{x>0}(M_{F'} - M_F)) \bullet S_{i-1} + tile(1 - l_{x>0}(M_{F'} - M_F)) \bullet S'_{i-1}, \tag{6}$$

where the *tile* copy function extends the indication matrix to a tensor with size (L, L, D), $M_F(M_{F'})$ denotes the fitness matrix of $S_{i-1}(S'_{i-1})$, and $\bullet$ indicates the pairwise multiplication between inputs. SM contains operations upon matrix and tensors. The input population of CRM is sorted, and we can know where the best individual is. According to the operational characteristics of the convolution operation, the mass distribution of the CRM's output is similar to the sorted input population. At the same time, many observations have also found this phenomenon, and the point-to-point selection of S_{i-1} and S'_{i-1} can better retain good individuals.

4.3 CONSTRUCT DECN WITH CRM AND SM

In vanilla EAs, each generation consists of recombination and selection operations. Like EAs, in Fig. 6, a learnable module based on CRM and SM is designed to learn optimization strategies, termed evolution module (EM). Then, DECN is established by stacking several EMs to simulate generations within EAs. S_{i-1} is the input population of EM_i. S'_{i-1} is the output of CRM in order to further improve the quality of individuals in the global and local search scopes. Then, SM selects the valuable individuals from S_{i-1} and

Figure 6: A general view of DECN and EM.

S'_{i-1} according to their function fitness. Fig. 7 provides an intuitive description of data flow in EM.

4.4 TRAINING OF DECN

DECN with t EMs generates the offspring S_t from the input population S_0 and can be trained based on end-to-end mode. Then, given a proper loss function and training dataset, DECN can be trained to learn optimization strategies towards the objective function $f(s|\xi)$ by the back-propagation. We will generally establish a function set to train DECN, and f_i represents the ith function in this set.

How to Design Loss Function. The loss function tells how to adaptively adjust the DECN parameters to generate individuals closer to the optimal solution. We design a loss function formulated as Eq. 7 for a minimum optimization problem $min_s f(s|\xi)$,

$$l_i(S_0, f(s|\xi)) = \frac{\frac{1}{|S_0|} \sum\limits_{s \in S_0} f_i(s|\xi) - \frac{1}{|G_\theta(S_0)|} \sum\limits_{s \in G_\theta(S_0)} f_i(s|\xi)}{\left|\left(\frac{1}{|S_0|} \sum\limits_{s \in S_0} f_i(s|\xi)\right|\right|} \tag{7}$$

Eq. 7 calculates the average fitness difference between the input and output, further normalized within $[0, 1]$. This equation is to maximize the difference between the initial population and the output

Figure 7: An example to show the data flow in EM. Suppose $f(s = \{x_1, x_2\}, x_i = \{0, 0\}) = (x_1 - 0)^2(x_2 - 0)^2$, $x_i \in [-1, 1]$. L is set to 2. We first transfer the initial population with four individuals to the tensor and then sort and pad it into the new tensor with 16 channels. The modified DSC operator is employed to generate x_1, x_2, and the fitness tensor. x_1 and x_2 are handled by parameters shared across channels within a 3×3 convolution kernel. The fitness tensor is handled by Eq. 6. The new tensors of x_1, x_2, and the fitness tensor are averaged to generate the output.

population of DECN to ensure that the initial population is close to the optimal solution. Eq. 7 enables DECN to perform the exploitation operation well but does not strongly encourage DECN to explore the fitness landscape. However, we have many options to balance exploration and exploitation. For example, the constructed Bayesian posterior distribution over the global optimum Cao & Shen (2020) is added to Eq. 7. After that, how to minimize this loss and obtain the parameters of DECN? $f_i(s|\xi)$ plays an essential role in the training process of DECN when calculating the gradient information of Eq. 7. Suppose the objective functions are hard to be formulated. If the derivatives of these functions are not available at training time, then it would be necessary to approximate these derivatives via an algorithm, such as REINFORCE Williams (1992); Cao et al. (2019).

Algorithm 1 Training of DECN

Input: Batch size for Adm, Ω; Function set for training, Fs^{train}
Output: Parameters of DECN θ;
Randomly initialize θ of DECN;
Randomly initialize ξ_i to adjust f_i in Fs^{train};
repeat
    Randomly initialize a minibatch Ω comprised of K populations S_0;
    for f_i **in** Fs^{train} **do**
        Update θ by l_Ω given training data (S_0, f_i);
    end for
    Update θ by minimizing $-1/m \sum_i l_\Omega$;
    Re-initialize parameters ξ_i of f_i in Fs^{train} every T epochs;
until training is finished

How to Train DECN. The gradient is unnecessary during the test process. This paper establishes the training set by constructing a set of differentiable functions related to the optimization objective. At this time, Eq. 7 are generally differentiable. This training dataset only contains $(S_0, f(s|\xi))$, the initial population and objective function, respectively. The variance of ξ causes the shift in landscapes. We introduce the detailed strategy in Appendix A.2 due to the limited space.

To prepare DECN to learn a balanced performance upon different optimization problems, we design a joint-training process with a loss function formulated as $l_{joint} = \sum_i l_i(S_0, f(s|\xi))$. According to the Adam Kingma & Ba (2014) method, a minibatch Ω is sampled each epoch for the training of

DECN upon $f_i(s|\xi_i)$, which is comprised by employing K initialized S_0. We give the corresponding mean loss of minibatch Ω for Eq. 7 and l_{joint}: $l_\Omega = -\frac{1}{K}\sum_{S_0 \in \Omega} l_i(S_0, f_i(s|\xi_i^{train}))$. Algorithm 1 provides the training process of DECN, where m is the number of functions in Fs^{train}.

Table 1: The compared results on six functions.

D	F	DECNws3	DE	ES	CMA-ES	L2O-swarm	Dragonfly
	F4	**1e-6(1e-07)**	0.15(0.06)	0.14(0.07)	4e-3(4e-3)	0.30(0.01)	1310(1310)
	F5	**1e-3(6e-06)**	4.62(1.07)	0.47(0.13)	0.11(0.05)	0.25(8.70e-4)	48.4(9.58)
	F6	**8.89(1e2)**	244(95.1)	118(235)	1660(2540)	154(243)	4e08(1e08)
10	F7	**0(0)**	18.5(3.51)	48.1(8.68)	48.3(7.47)	12.8(5.49)	81.1(24.0)
	F8	**0(0)**	0.26(0.12)	0.30(0.17)	0.02(0.01)	0.06(3.39e-4)	35.4(22.0)
	F9	**1e-3(3e-4)**	1.86(0.36)	20.5(0.13)	20.7(0.10)	2.19(0.02)	16.2(3.64)
	F4	**7e-9(4e-11)**	8.5e3(396)	9.3e4(8.12e3)	7330(1e3)	0.66(0.04)	None
	F5	**4e-4(0)**	28.2(0.47)	82.5(2.16)	71.8(9.74)	0.96(0.04)	None
	F6	**96(0.02)**	2.3e8(2.8e7)	2.5e10(3.1e9)	3.4e8(9.5e7)	286(28.5)	None
100	F7	**0(0)**	9.3e3(504)	9.3e4(9.1e3)	8.7e3(1.5e3)	50.6(21.0)	None
	F8	**0(0)**	3.06(0.22)	24.2(2.91)	2.90(0.31)	0.15(1e-3)	None
	F9	**4e-3(8e-05)**	18.9(0.15)	21.4(0.01)	21.4(0.03)	3.06(0.02)	None

5 EXPERIMENTS

5.1 RESULTS ON SIX FUNCTIONS

We test DECN on six standard black-box functions (Appendix Table 6). We train DECNs on the original functions, and then we train six DECNs in this part. The optima randomly lie within the same domain of x during the training process. Here, $D = \{10, 100\}$ and $L = 10$. DECN is compared with standard EA baselines, including DE, ES, and CMA-ES. L2O-swarm Cao et al. (2019) is a representative L2O method for black-box optimization. Dragonfly Kandasamy et al. (2020) is the state-of-the-art Bayesian optimization. The parameters of DE, ES, CMA-ES, and Dragonfly are adjusted to be optimal. L2O-swarm and DECN use the same training set and loss function. All algorithms are run ten times for each function. DECNws3 contains 3 EMs, and the parameters of these three convolution kernels are consistent across different EMs (weight sharing). The detailed parameters of these models can be found in Table 7 of the Appendix. The results are provided in Table 1. DECN outperforms other algorithms in all cases, which shows the effectiveness of DECN.

Table 2: The compared results on *ab initio* protein docking problem.

Methods	1ATN_7	2JEL_1	7CEI_1
L2O-Swarm	2090.86(25.08)	2765.90(24.80)	1689.83(23.64)
DECNws3	**-6261.32(96.71)**	**-6249.59(84.38)**	**-6193.19(84.66)**

5.2 RESULTS ON PROTEIN DOCKING

Protein docking predicts the 3D structures of protein-protein complexes given individual proteins' 3D structures or 1D sequences. We consider the *ab initio* protein docking problem, which is formulated as optimizing the Gibbs binding free energy for conformation x: $f(x) = \nabla G(x)$. We calculate the energy function in a CHARMM 19 force field as in Moal & Bates (2010). And we parameterize the search space as $\mathbb{R}^{12}$ as in Smith & Sternberg (2002). We only consider 100 interface atoms. The training set includes 125 instances, which contains 25 protein-protein complexes from the protein docking benchmark set 4.0 Hwang et al. (2010), each of which has five starting points (top-5 models from ZDOCK Pierce et al. (2014)). The testing set includes three complexes (with one starting model each) of different levels of docking difficulty. In L2O-swarm, the part of Bayesian posterior distribution over the global optimum Cao & Shen (2020) is removed to keep fair with DECN. The

experimental results reported in Table 2 demonstrate that DECN outperforms L2O-swarm in three cases. Since L2O-swarm has no elite retention mechanism, its result is worse than the optimal value of the initial population.

5.3 TRANSFERABILITY

We investigate the generality of DECN on more tasks unseen during the training stage. Here, the whole functions in Table 5 are employed to train one DECN, and then the results on each function of Table 6 are shown in Table 3. We design three models, including DECNws3, DECNn15, and DEC-Nws30. DECNn15 does not share parameters across different EMs. Their parameters are shown in Table 7 (Appendix). DEC-Nws30 outperforms DECNws3 in all cases, demonstrating that deep architectures have stronger representation capabilities and can build more accurate mapping relationships between random populations and optimal solutions. DECNn15 outperforms DECNws3 and DECNws30 when $D = 100$. This case is

Table 3: The transferability of different structures.

D	F	DECNws3	DECNws30	DECNn15
10	F4	53.8(14.3)	1.17(0.58)	**0.09(0.02)**
	F5	4.26(0.61)	0.59(0.16)	**0.19(0.03)**
	F6	**4.5(2.3e4)**	131(67.1)	17.0(2.88)
	F7	24.4(4.01)	**0.35(0.22)**	5.93(1.40)
	F8	1.48(0.14)	0.29(0.08)	**0.17(0.04)**
	F9	4.33(0.41)	0.91(0.32)	**0.22(0.04)**
100	F4	1.15e4(744)	2.19e3(148)	**67.4(9.09)**
	F5	25.0(0.92)	10.4(0.39)	**2.22(0.15)**
	F6	3e8(4e7)	1e7(2e6)	**2e4(5e3)**
	F7	776(19.2)	549(18.3)	**81.5(11.9)**
	F8	105(6.12)	20.9(1.17)	**1.58(0.08)**
	F9	11.6(0.21)	6.79(0.14)	**3.77(0.16)**

more complex than the case with $D = 10$. Although the number of layers of DECNn15 is lower than that of DECNws30, its representation ability is stronger than that of DECNws30 because it does not share weights. However, when the number of layers becomes larger, this architecture is more difficult to train. The transferability of DECN is proportional to the fitness landscape similarity between the training set and the problem. When new problem attributes are not available in the training set, DECN can still perform better. However, if extreme attributes are not available, then DECN can be the less satisfactory performance for functions with this attribute. These results show that the optimization strategy learned by DECN has good generality and is transferable to many unseen objective functions.

5.4 ACCELERATE DECN WITH GPU

We show the surprising performance of DECN with GPU accelerated CRM and SM. To display the adaptability of DECN to GPUs, we offer the average runtime (second) of DECN and unaccelerated EA for three generations in Table 4. DECN and EA optimize $K = 32$ populations, each containing $L \times L$ individuals (number of individuals: $K \times L \times L$). Similarly, we employ the runtime of EA with SBX crossover and Breeder mutation operator without acceleration as a reference in this experiment. As can be seen, with the increase of L, the advantage of acceleration based on GPUs is clear. DECN is around 102 times faster than EA when $D \in \{10, 50, 500\}$. This case indicates that DECN is

Table 4: DECN's calculation efficiency upon one 1080Ti GPU.

D	Algorithm	L	
		10	80
10	DECN	0.0054	0.0500
	EA	0.6942	72.3664
50	DECN	0.008026	0.237182
	EA	0.6820	71.4425
500	DECN	0.0412	2.7274
	EA	0.7208	74.9417

adapted to the acceleration of GPUs and can be accelerated sufficiently.

6 CONCLUSIONS

We successfully designed the CNN-based L2O method for black-box optimization. The better performance than other black-box optimization methods demonstrates the effectiveness of DECN. Moreover, DECN can be well adapted to unknown black-box optimization. DECN has outstanding adaptability to GPU acceleration due to the tensor operator. The limitations are discussed in Appendix.A.6.

REFERENCES

Marcin Andrychowicz, Misha Denil, Sergio Gomez, Matthew W Hoffman, David Pfau, Tom Schaul, Brendan Shillingford, and Nando De Freitas. Learning to learn by gradient descent by gradient descent. In *Advances in Neural Information Processing Systems*, pp. 3981–3989, 2016.

A. Auger and N. Hansen. A restart cma evolution strategy with increasing population size. In *2005 IEEE Congress on Evolutionary Computation*, volume 2, pp. 1769–1776, 2005.

Irwan Bello, Barret Zoph, Vijay Vasudevan, and Quoc V Le. Neural optimizer search with reinforcement learning. In *International Conference on Machine Learning*, pp. 459–468. PMLR, 2017.

Yue Cao and Yang Shen. Bayesian active learning for optimization and uncertainty quantification in protein docking. *Journal of chemical theory and computation*, 16(8):5334–5347, 2020.

Yue Cao, Tianlong Chen, Zhangyang Wang, and Yang Shen. Learning to optimize in swarms. *Advances in Neural Information Processing Systems*, 32:15044–15054, 2019.

Tianlong Chen, Weiyi Zhang, Zhou Jingyang, Shiyu Chang, Sijia Liu, Lisa Amini, and Zhangyang Wang. Training stronger baselines for learning to optimize. In H. Larochelle, M. Ranzato, R. Hadsell, M. F. Balcan, and H. Lin (eds.), *Advances in Neural Information Processing Systems*, volume 33, pp. 7332–7343. Curran Associates, Inc., 2020.

Tianlong Chen, Xiaohan Chen, Wuyang Chen, Howard Heaton, Jialin Liu, Zhangyang Wang, and Wotao Yin. Learning to optimize: A primer and a benchmark. *arXiv preprint arXiv:2103.12828*, 2021.

Yutian Chen, Matthew W Hoffman, Sergio Gómez Colmenarejo, Misha Denil, Timothy P Lillicrap, Matt Botvinick, and Nando Freitas. Learning to learn without gradient descent by gradient descent. In *International Conference on Machine Learning*, pp. 748–756. PMLR, 2017.

John Runwei Cheng and Mitsuo Gen. Accelerating genetic algorithms with gpu computing: A selective overview. *Computers & Industrial Engineering*, 128:514–525, 2019.

François Chollet. Xception: Deep learning with depthwise separable convolutions. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1251–1258, 2017.

Swagatam Das and Ponnuthurai Nagaratnam Suganthan. Differential evolution: A survey of the state-of-the-art. *IEEE transactions on Evolutionary Computation*, 15(1):4–31, 2010.

Thomas Elsken, Jan Hendrik Metzen, and Frank Hutter. Neural architecture search: A survey. *The Journal of Machine Learning Research*, 20(1):1997–2017, 2019.

Sebastian Flennerhag, Yannick Schroecker, Tom Zahavy, Hado van Hasselt, David Silver, and Satinder Singh. Bootstrapped meta-learning. *arXiv preprint arXiv:2109.04504*, 2021.

Ian Goodfellow, Yoshua Bengio, and Aaron Courville. *Deep Learning*. MIT press, 2016.

Nikolaus Hansen and Andreas Ostermeier. Completely derandomized self-adaptation in evolution strategies. *Evolutionary Computation*, 9(2):159–195, 2001.

Yuxiao Huang, Liang Feng, A. K. Qin, Meng Chen, and Kay Chen Tan. Towards large-scale evolutionary multi-tasking: A gpu-based paradigm. *IEEE Transactions on Evolutionary Computation*, pp. 1–1, 2021. doi: 10.1109/TEVC.2021.3110506.

Frank Hutter, Lars Kotthoff, and Joaquin Vanschoren. *Automated machine learning: methods, systems, challenges*. Springer Nature, 2019.

Howook Hwang, Thom Vreven, Joël Janin, and Zhiping Weng. Protein–protein docking benchmark version 4.0. *Proteins: Structure, Function, and Bioinformatics*, 78(15):3111–3114, 2010.

Chen Jin and A Kai Qin. A gpu-based implementation of brain storm optimization. In *2017 IEEE Congress on Evolutionary Computation (CEC)*, pp. 2698–2705. IEEE, 2017.

Yaochu Jin, Handing Wang, Tinkle Chugh, Dan Guo, and Kaisa Miettinen. Data-driven evolutionary optimization: An overview and case studies. *IEEE Transactions on Evolutionary Computation*, 23 (3):442–458, 2019. doi: 10.1109/TEVC.2018.2869001.

Kirthevasan Kandasamy, Karun Raju Vysyaraju, Willie Neiswanger, Biswajit Paria, Christopher R. Collins, Jeff Schneider, Barnabas Poczos, and Eric P. Xing. Tuning hyperparameters without grad students: Scalable and robust bayesian optimisation with dragonfly. *Journal of Machine Learning Research*, 21(81):1–27, 2020.

Pascal Kerschke, Holger H. Hoos, Frank Neumann, and Heike Trautmann. Automated algorithm selection: Survey and perspectives. *Evolutionary Computation*, 27(1):3–45, 2019. doi: 10.1162/ evco_a_00242.

Shauharda Khadka and Kagan Tumer. Evolution-guided policy gradient in reinforcement learning. In S. Bengio, H. Wallach, H. Larochelle, K. Grauman, N. Cesa-Bianchi, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 31. Curran Associates, Inc., 2018.

Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. *Advances in neural information processing systems*, 25, 2012.

Ke Li and Jitendra Malik. Learning to optimize. *arXiv preprint arXiv:1606.01885*, 2016.

Luke Metz, Niru Maheswaranathan, Jeremy Nixon, Daniel Freeman, and Jascha Sohl-Dickstein. Understanding and correcting pathologies in the training of learned optimizers. In *International Conference on Machine Learning*, pp. 4556–4565. PMLR, 2019.

Melanie Mitchell. *An introduction to genetic algorithms*. MIT press, 1998.

Iain H Moal and Paul A Bates. Swarmdock and the use of normal modes in protein-protein docking. *International Journal of Molecular Sciences*, 11(10):3623–3648, 2010.

Brian G Pierce, Kevin Wiehe, Howook Hwang, Bong-Hyun Kim, Thom Vreven, and Zhiping Weng. Zdock server: interactive docking prediction of protein–protein complexes and symmetric multimers. *Bioinformatics*, 30(12):1771–1773, 2014.

Kai Qin, Federico Raimondo, Florence Forbes, and Yew Soon Ong. An improved cuda-based implementation of differential evolution on gpu. In *Proceedings of the 14th Annual Conference on Genetic and Evolutionary Computation*, pp. 991–998, 2012.

Tim Salimans, Jonathan Ho, Xi Chen, Szymon Sidor, and Ilya Sutskever. Evolution strategies as a scalable alternative to reinforcement learning. *arXiv preprint arXiv:1703.03864*, 2017.

Graham R Smith and Michael JE Sternberg. Prediction of protein–protein interactions by docking methods. *Current opinion in structural biology*, 12(1):28–35, 2002.

Jasper Snoek, Hugo Larochelle, and Ryan P Adams. Practical bayesian optimization of machine learning algorithms. In F. Pereira, C.J. Burges, L. Bottou, and K.Q. Weinberger (eds.), *Advances in Neural Information Processing Systems*, volume 25. Curran Associates, Inc., 2012.

Haoran Sun, Xiangyi Chen, Qingjiang Shi, Mingyi Hong, Xiao Fu, and Nicholas D. Sidiropoulos. Learning to optimize: Training deep neural networks for interference management. *IEEE Transactions on Signal Processing*, 66(20):5438–5453, 2018. doi: 10.1109/TSP.2018.2866382.

Ye Tian, Shichen Peng, Xingyi Zhang, Tobias Rodemann, Kay Chen Tan, and Yaochu Jin. A recommender system for metaheuristic algorithms for continuous optimization based on deep recurrent neural networks. *IEEE Transactions on Artificial Intelligence*, 1(1):5–18, 2020. doi: 10.1109/TAI.2020.3022339.

Paul Vicol, Luke Metz, and Jascha Sohl-Dickstein. Unbiased gradient estimation in unrolled computation graphs with persistent evolution strategies. In *International Conference on Machine Learning*, pp. 10553–10563. PMLR, 2021.

Olga Wichrowska, Niru Maheswaranathan, Matthew W Hoffman, Sergio Gomez Colmenarejo, Misha Denil, Nando Freitas, and Jascha Sohl-Dickstein. Learned optimizers that scale and generalize. In *International Conference on Machine Learning*, pp. 3751–3760. PMLR, 2017.

Daan Wierstra, Tom Schaul, Tobias Glasmachers, Yi Sun, Jan Peters, and Jürgen Schmidhuber. Natural evolution strategies. *Journal of Machine Learning Research*, 15(1):949–980, 2014.

Ronald J Williams. Simple statistical gradient-following algorithms for connectionist reinforcement learning. *Machine learning*, 8(3):229–256, 1992.

Qingfu Zhang and Hui Li. Moea/d: A multiobjective evolutionary algorithm based on decomposition. *IEEE Transactions on Evolutionary Computation*, 11(6):712–731, 2007.

A APPENDIX

A.1 HOW TO ORGANIZE A POPULATION INTO A TENSOR

Figure 8 gives an illustration of the tensor data. As can be seen, the number of channels of input tensors is $D+1$, where D is the dimension of the optimization task, and the fitness of individuals occupies one channel. The fitness channel does not participate in the convolution process but is essential for the selection module in DECN for the information selection.

Figure 8: The realization of similar functions as recombination operators based on convolution operator. Convolution kernels slip over the whole $L \times L$ lattice and conduct the information interaction within the neighborhood of (i, j). For the picture on the left, the small red square with many channals represents S_i.

Algorithm 2 Testing of DECN
___
> **Input:** Parameters of DECN θ, Testing function set, Fs^{test}
> **Output:** Optimal solution obtained by DECN, O
> Randomly initialize ξ_i to adjust f_i in Fs^{test};
> Randomly initialize a minibatch Ω comprised of K populations S_0;
> $O \leftarrow \varnothing$
> **for** f_i **in** Fs^{test} **do**
>   Randomly initialize an input population S_0;
>   Obtain the output population S_t of DECN;
>   Evaluate the individuals in S_t by f_i and obtain the optimal solution $s*$; $O \leftarrow O \cap s*$;
> **end for**

A.2 THE DETAILS OF TRANSFERABILITY

DECN is mainly trained based on the designed function set. We evaluate the transferability of DECN with learned strategies to other unseen functions, which are unseen during the training stage. We

show the designed training and testing datasets as follows:

$$Fs^{train} = \{f_1(s|\xi_{1,i}^{train}), \cdots, f_m(s|\xi_{m,i}^{train})\}$$
$$Fs^{transfer} = \{F_1(s|\xi_{1,i}^{transfer}), \cdots, F_k(s|\xi_{k,i}^{transfer})\}$$

(8)

where F_i is not employed in the training stage. $\xi_{m,i}^{train}$ represents the ith different values of ξ in mth function f_m or F_m, which is true for any index pair.

The initial population S_0 is always randomly generated before optimization. The transferring function set is comprised of different functions and has diverse landscapes from Fs^{train} and Fs^{test}. Since essential functions $Fs^{transfer}$ are not contained within Fs^{train}, the corresponding functions can be regarded as unseen objective functions. Details of the testing process of DECN are given in Algorithm 2. Here, a randomly initialized DECNws3 in this experiment is first trained with Fs^{train} and further applied to optimize the function set $Fs^{trasfer}$.

Table 5: Training functions.

ID	Functions	Range
F1	$\sum_i |w_i sin(x_i - b_i)|$	$x \in [-10, 10], b \in [-10, 10]$
F2	$\sum_i |x_i - b_i|$	$x \in [-10, 10], b \in [-10, 10]$
F3	$\sum_i |(x_i - b_i) - (x_{i+1} - b_{i+1})| + \sum_i |x_i - b_i|$	$x \in [-10, 10], b \in [-10, 10]$

Table 6: Testing Functions.

ID	Functions	Range
F4(Sphere)	$\sum_i z_i^2, z_i = x_i - b_i$	$x \in [-100, 100], b \in [-50, 50]$
F5	$\max\{|z_i|, 1 \le i \le D\}, z_i = x_i - b_i$	$x \in [-100, 100], b \in [-50, 50]$
F6(Rosenbrock)	$\sum_{i=1}^{D-1} (100(z_i^2 - z_{i+1})^2 + (z_i - 1)^2), z_i = x_i - b_i$	$x \in [-100, 100], b \in [-50, 50]$
F7(Rastrigin)	$\sum_{i=1}^{D} (z_i^2 - 10\cos(2\pi z_i) + 10), z_i = x_i - b_i$	$x \in [-5, 5], b \in [-2.5, 2.5]$
F8(Griewank)	$\sum_{i=1}^{D} \frac{z_i^2}{4000} - \prod_{i=1}^{D} \cos(\frac{z_i}{\sqrt{i}}) + 1, z_i = x_i - b_i$	$x \in [-600, 600], b \in [-300, 300]$
F9(Ackley)	$-20\exp(-0.2\sqrt{\frac{1}{D}\sum_{i=1}^{D} z_i^2})$ $\exp(\frac{1}{D}\sum_{i=1}^{D}\cos(2\pi z_i)) + 20 + \exp(1), z_i = x_i - b_i$	$x \in [-32, 32], b \in [-16, 16]$

A.3 ACCELERATE DECN WITH GPU

In addition, this paper has worked on another issue: how to design a deep neural network inspired by EAs that can still be quickly accelerated by Graphics Processing Units (GPUs). The acceleration of EAs using GPUs is challenging, and lots of research has contributed to this problem. The support for multiple subpopulations to evolve simultaneously has paramount significance in practical applications. Qin et al. Jin & Qin (2017); Qin et al. (2012) accelerated the K-Means process within the brain storm optimization algorithm through GPUs and proposed an improved CUDA-based implementation of differential evolution on GPUs. Many other EAs have benefited from the computing performance of GPUs Huang et al. (2021); Cheng & Gen (2019). However, all of them just parallelized the current EAs. No method has been proposed to design deep networked EAs. Besides, many available evolutionary operators are unfriendly to the GPU acceleration, as GPUs are weak in processing logical operations. As both CRM and SM are comprised of operations upon tensors, they can be sufficiently accelerated by GPUs.

DECN is a fully convolution neural network mainly containing operations upon tensors and is easily accelerated by GPUs. Current distributed EA methods usually separate a population into multiple

Table 7: Experimental setup for DECNws30, DECNws3 and DECNnws15. In DECNws3, parameters of these three convolution kernels are consistent across different EMs (weight sharing). Moreover, during the training process, the 2-norm of gradients is clipped to be not larger than 10, and the learning rate ($lr = 0.01$) shrinks every 100 epochs. The shrinking rate is set to 0.9. The generation of these reference algorithms is set to 100, while DECNws3 only evolves the population with 3 EMs. 5000 epochs are conducted during the training process. All experimental studies are performed on a Linux PC with Intel Core i7-10700K CPU at 3.80GHz and 32GB RAM.

Model	L	D	K	EMs	Convolution kernels	lr	Epochs	T	Weight share	Gradient norm
DECNws30	10	10	32	30	$3 \times 3: u = 0, \sigma = 0.5$
$5 \times 5: u = 0, \sigma = 0.5$
$7 \times 7: u = 0, \sigma = 0.5$	0.01	10000	10	True	10
DECNws3	10	2	32	3	$3 \times 3: u = 0, \sigma = 0.5$
$5 \times 5: u = 0, \sigma = 0.5$
$7 \times 7: u = 0, \sigma = 0.5$	0.0005	5000	10	True	10
DECNn15	10	30	16	15	$3 \times 3: u = 0, \sigma = 0.5$
$5 \times 5: u = 0, \sigma = 0.5$
$7 \times 7: u = 0, \sigma = 0.5$	0.0005	2000	10	False	10

Table 8: Investigation of DECN's calculation efficiency when accelerated upon one 1080Ti GPU. The results in this table are the average time (second) of algorithms to conduct the evolution of 32 input populations for three generations.

D	Algorithm	L			
		10	20	40	80
2	DECN(s)	0.004627	0.005978	0.007449	0.015492
	EA(s)	0.700342	2.863495	12.67563	71.74005
	Rate(DECN/EA)	0.006607	0.002088	0.000588	0.000216
10	DECN	0.005487	0.007838	0.01664	0.049973
	EA	0.694213	2.879791	12.87636	72.3664
	Rate(EM/EA)	0.007904	0.002722	0.001292	0.000691
30	DECN	0.007052	0.013323	0.039877	0.138544
	EA	0.693307	2.87876	13.00381	71.67544
	Rate(EM/ EA)	0.010171	0.004628	0.003067	0.001933
50	DECN	0.008026	0.01875	0.062079	0.237182
	EA	0.681967	2.868	12.80662	71.44253
	Rate(EM/ EA)	0.011769	0.006538	0.004847	0.00332
100	DECN	0.011725	0.033109	0.117593	0.478518
	EA	0.699074	2.865546	13.12218	71.83043
	Rate(EM/ EA)	0.016772	0.011554	0.008961	0.006662
500	DECN	0.041167	0.147843	0.610056	2.727426
	EA	0.720847	2.966926	13.59977	74.9417
	Rate(EM/ EA)	0.057109	0.04983	0.044858	0.036394

subpopulations that evolve simultaneously. Such separation is also a commonly accepted operation in many EAs However, none of them can accelerate the genetic operators. Here, we show the surprising performance of DECN with GPU accelerated CRM and SM. Moreover, Tensorflow has provided mature solutions for the acceleration upon GPUs, and DECN implemented by Tensorflow is supportable to load multiple populations as the input. To show the adaptability of DECN to GPUs, we offer the runtime of DECN and unaccelerated EA in Table 8, within which both DECN and EA optimize $K = 32$ populations with each containing $L \times L$ individuals (number of individuals: $K \times L \times L$). Similarly, we employ the runtime of EASBX without acceleration as a reference in this experiment. As can be seen, with the increase of L, the advantage of acceleration based on GPUs is clear. When the dimension $D \in \{2, 10\}$, DECN runs 103~104 times faster than EA. DECN is still

around 102 times faster than EA when $D \in \{30, 50, 100, 500\}$. This case indicates that DECN is adapted to the acceleration of GPUs and can be accelerated sufficiently. However, with increasing D, DECN increases the proportion of evaluations in the runtime and ultimately weakens the advantage of acceleration. These cases indicate the acceleration advantage of DECN when optimizing a larger population.

A.4 The Convergence of Loss Function in Training Process

This part is the change curve of the loss function of the training process of DECNnws15 on F4-F9. The results are shown in Fig. 9. Here, D=10.

Figure 9: The convergence of loss function in training process. (a) F4, (b) F5, (c) F6, (d) F7, (e) F8, and (f) F9.

A.5 Limitations

However, DECN has many drawbacks. We hope to address these deficiencies in future work. 1) The designed loss function enables DECN to perform the exploitation operation well but does not

Figure 10: Visualization of the optimization process.

strongly encourage DECN to explore the fitness landscape. However, we have many options to balance exploration and exploitation. For example, the constructed Bayesian posterior distribution Cao & Shen (2020) over the global optimum is added to Eq. 7. In addition to adding items that focus on the exploration ability of the loss function, new modules can also be designed to be added to the EM to help DECN jump out of the local optimum.

2) For the constructed training dataset, DECN does not have an advantage if it is utterly irrelevant to the optimization objective. Thus, establishing a suitable training dataset is essential.

3) DECN only focuses on continuous optimization problems without constraints. For problems such as expensive optimization, combinatorial optimization, constrained optimization, and multi-objective optimization, DECN needs to be adjusted according to the characteristics of the problem. We can think of DECN as standard optimizers like vanilla DE, ES, GA, and PSO. In order to deal with different types of problems, we need to make different corrections to DECN. For example, to deal with expensive problems, we need to build surrogate models to assist DECN. We need to redesign the CRM module to generate new feasible solutions for combinatorial optimization problems. For example, for TSP tasks, GNN may be a feasible option to generate new solutions instead of CRM. We can redesign the CRM module for constrained optimization problems to generate feasible solutions. Of course, the easiest way is to use constraint violations and fitness functions as criteria for selecting the next generation in the SM module.

A.6 VISUALIZATION

This section verifies that DECN can indeed advance the optimization of the algorithm. We take a two-dimensional F4 function as an example. The number of EMs is set to 15, and other settings are the same as in the above experiments. In Fig. 10, as the iteration proceeds, DECN gradually converges. When passing through the first EM module, the CRM is first passed, and the offspring S'_{i-1} are generated, which are more widely distributed in the search space, and the offspring are

closer to the optimal solution. Therefore, the CRM generates more potential offspring and is rich in diversity. After the SM update, the generated S_i is around the optimal solution, showing that the SM update can keep good solutions and remove poor ones. This phenomenon also leads to a vast improvement after passing through this module. From the population distribution results of the 2nd, 3rd, and 15th EMs, DECN continuously moves the population to the vicinity of the optimal solution.