Measuring CLEVRness: Black-box Testing of Visual Reasoning Models

Abstract

How to measure the reasoning capabilities of intelligence systems? Visual question answering provides a convenient framework for testing the model's abilities by interrogating the model through questions about the scene. However, despite the score of various visual QA datasets and architectures, which sometimes yield even a super-human performance, the question of whether those architectures can do reasoning remains open. To answer such a question, we extend the visual question answering framework and propose the following behavioural test in the form of a two-player game. We consider black-box neural models of CLEVR. Those models are trained on a diagnostic dataset benchmarking reasoning. Next, we train an adversarial player that re-configures the scene to fool the CLEVR model. We show that CLEVR models, which otherwise may perform at a human level, can easily be fooled by our agent. Our results question one more time whether data-driven approaches can do reasoning without exploiting numerous biases that are often present in those datasets. Finally, we also propose a controlled experiment measuring the efficiency of such models to learn and perform reasoning.

1 Introduction

Are our artificial intelligence systems capable of reasoning? Or like *Clever Hans*, they use various cues only tangentially related to the task and rely on rote memorization with poor generalization? (Pfungst, 1911; Johnson et al., 2017a) This work revisits such a question and proposes an interactive framework with the communication channel between two players. The first player, which reasoning capabilities we are about to test, performs visual reasoning tasks. The second player, which we call the *Adversarial Player*, is manipulating the scene so that it *fools* the first player even though those changes still lead to correct reasoning steps among humans. Both players interact with each other only through questions, answers and the visual scene as shown in Figure 1. Since we use the visual question answering framework as the interrogation medium, assuming that both players can deal with textual questions and answers, we also call the first player the *Visual-QA Player*.

If the *Adversarial Player* manipulating the scene causes the *Visual-QA Player* to change its answer even though the new scene is still valid for the same question and answer, it is then the reasoning failure. It is similar to the following situation. Imagine a box is placed between two spheres. If you ask a question, *is there a box between two spheres?*, the answer should be positive. Now, if we move the box anywhere so it does not cross any of the spheres, and ask the same question, the response should remain unchanged. In other words, we postulate that reasoning outputs of agents need to be invariant under scene configurations that are consistent with the questions-answer pairs. Moreover, in the spirit of generic adversarial attacks (Szegedy et al., 2014; Goodfellow et al., 2015), we seek configurations that also pose little if any reasoning challenges for humans.

In this work, we propose an automatic and agnostic pipeline to benchmark the reasoning capabilities of various models. The only assumption that we make about those models is that they can perceive the scene and communicate by answering questions about the scene. Due to the recent stream of research in vision-and-language (Zhang et al., 2021; Jiang et al., 2020; Guo et al., 2019b; Su et al., 2020; Wang et al., 2020; Kamath et al., 2021; Tan & Bansal, 2019; Chen et al., 2020), we believe there will be an increasing number of vision models that can operate through language. Moreover, we also consider the visual question answering framework set-up as a two-player system as an excellent benchmarking pipeline. We perform all tests by scene manipulations and observing how

a tested model behaves under such changes. The pipeline does not require any knowledge of the internals of the tested model. It also does not manipulate the sensory information of such a model, i.e., pixels in the images, and all the manipulations are physically meaningful.

Even though our current pipeline uses synthetic scenes as only those can easily be automatically manipulated, our results have also real-world ramifications. If models are susceptible to semantically *meaningless* changes[1] in scene configurations, in a synthetic setting, there are valid concerns that real-world robots could also be prone to manipulation of objects in a room.

Finally, our work also questions the possibility of training and benchmarking networks in a purely data-driven and offline, static manner. Although most of our CLEVR models can reach a 'super-human' performance on CLEVR, they are much less-CLEVR if another agent can manipulate the scene. Our results show that those models fail on various reasoning tasks, even though a relatively simple interpolation between configurations is possible; where even no new features are introduced. We also show that the existing models may be inefficient in learning to perform reasoning.

Contributions. The main contributions of our work could be summarized in three points.

First, we propose a strong *black-box* adversarial test, which makes no assumptions about underlying mechanics of a tested model, formulated as a game between two players. Our test does not require any direct access to the tested model, even through its sensory information. In particular, it does not require gradients, output probabilities, or any access to the perceived image. Our work also deviates from bounded perturbations and instead focuses on global scene manipulations that are still consistent with the task constraints, and can change the behaviour of a tested model.

Second, we reformulate visual reasoning by integrating visual question answering with zero-sum two-player game frameworks. Under our novel formulation, a visual and adversary agents compete against each other through content manipulation. We believe that this is an initial step towards more sophisticated frameworks that integrate computer vision with multi-agent systems.

Third, we explore the limits of the data-driven approaches in synthetic visual scenarios, and demonstrate that current CLEVR models are lacking the efficiency to learn robust reasoning steps.

2 RELATED WORK

Our work touches upon various research directions, which we briefly describe here.

Visual QA. Introduced as a visual counter-part of the Turing Test (Malinowski & Fritz, 2014; Geman et al., 2015), it became a computer vision task that requires a holistic visual understanding. Many other works have extended the task to larger datasets or videos or adversarial train-test splits (Antol et al., 2015; Agrawal et al., 2018; Tapaswi et al., 2016; Yu et al., 2019; Girdhar & Ramanan, 2019). More recently, we also observe the generalization of the task to become a part of the vision-plus-language suite of benchmarks (Lu et al., 2019; Chen et al., 2019; Wang et al., 2021). Johnson et al. (2017a) have introduced a synthetic variant of the Visual QA problem that is more focused on reasoning and the control of the experimentation. Although it was shown that traditional methods (Yang et al., 2016) are not enough to solve that dataset, newer methods can pass the human baseline on this task. Those methods are trained to operate on pixels and text directly (Santoro et al., 2017; Perez et al., 2018; Hudson & Manning, 2018; Malinowski et al., 2018; Kamath et al., 2021) or they induce programs as an intermediate representation (Johnson et al., 2017b; Mascharka et al., 2018; Yi et al., 2018). We extend this line of research by reformulating the Visual QA task as an interactive two-agents system, where we automatically test the reasoning capabilities of some methods above in the controlled setting. We also show that CLEVR under such a new setting is still an unsolved problem. **Adversarial perturbations.** Szegedy et al. (2014); Goodfellow et al. (2015); Kurakin et al. (2016); Moosavi-Dezfooli et al. (2016); Carlini & Wagner (2016) have introduced early methods that can 'fool' networks by performing tiny, visually imperceptible, perturbations of the input image. Moosavi-Dezfooli et al. (2017) have also shown universal and untargeted adversarial perturbations that are more transferable than previous approaches. Most methods perform *white-box* attacks, where an adversarial model has access to the target model's parameters or gradients. In *black-box* attacks such access is removed and, e.g., only output probabilities are available (Guo et al., 2019a). Other *black-box* attacks involve the use of surrogates to estimate gradients of the real target (Papernot

---

[1]Changes that are consistent with the task constraints.

et al., 2017; Cheng et al., 2019) or gradient-free methods (Alzantot et al., 2018). More related to our work, Cheng et al. (2018) describe a *black-box* system, which only assumes the access to outputs, so called hard-labels, of the network for a given query. However, all the perturbations described above are continuous-based where individual pixels are changed independently. This leads to improbable images and assumes the access to the sensory inputs of the neural network. In contrary, *semantic* perturbations (Joshi et al., 2019; Zeng et al., 2019), operate on semantically meaningful chunks of the input, leading to more plausible and physically interpretable perturbations. However, they still assume a direct access to either images or ideally differentiable renderers. We can interpret our work within the adversarial perturbations framework, where the adversarial model can change the original scene by its manipulations, with zero access to the target model, including its sensory information and not limited to tiny changes but instead to semantically and globally *meaningless* modifications.

Reinforcement learning. The game between the *Visual-QA Player* and *Adversarial Player* is a zero-sum two-player game. Conneau et al. (2017) use a conceptually similar two-player game to find a better word alignment between two languages without parallel corpus. Inspired by such a problem formulation, we consider our two-player game as a tool to achieve better reasoning models. We optimize the *Adversarial Player* with Advantage Actor-Critic (A2C) algorithm (Sutton & Barto, 2018; Degris et al., 2012). Though there are two players in the game between *Visual-QA Player* and *Adversarial Player*, in experiments presented in this work, the *Visual-QA Player* is frozen. Thus, technically, simpler optimization methods used for single-player games are applicable.

Probing and measuring intelligence. Turing Test (Turing, 2009) is considered to be among the earliest works on measuring the intelligence of artificial systems. Crucially to us, it is also formulated as a two-player game with an interrogation protocol. Legg (2008) systematizes and relates notion of intelligence from different fields with the main focus on 'universality'. Similarly, Chollet (2019) investigates various attempts at defining or measuring intelligence and highlights the role of skill-acquisition efficiency. Johnson et al. (2017a) have transferred the notion of intelligence onto the visual ground and emphasize reasoning rather than universality. Nonetheless, it seems there is no a single widely acceptable dataset or a definition that encompasses our intuitions about intelligence. However, there are a few recent directions showing the lack thereof, mainly highlighting bias amplification or absence of mathematical capabilities (Hendricks et al., 2018; Bhardwaj et al., 2021; Piekos et al., 2021). Here, we are mostly interested in visual reasoning and use the visual question answering framework as a form of communication with the otherwise *black-box* system.

3 PRELIMINARIES

In this section, we explain briefly how the CLEVR dataset (Johnson et al., 2017a) is constructed and introduce our notation and definitions.

CLEVR is a synthetic visual question answering dataset introduced by Johnson et al. (2017a), which consists of about 700k training and 150k validation image-question-answer triplets. Images are artificially constructed and rendered from scene graphs – a special structure containing information about object attributes such as position or color. Such a scene graph is also used to synthesize the ground-truth question-answer pairs by expanding templates according to the depth-first-search ordering. Ambiguous scenes are rejected. Each image represents an isometric view on the scene containing from two to ten objects. There are three classes of objects: spheres, cubes and cylinders. Each object can also be either large or small and has one colour out of four (brown, purple, cyan, yellow). It can also be either metallic or rubber-made. Every object has x and y coordinates that are confined within the $(-3, +3)$ range. We use the same generation process to render modified scenes.

CLEVR models. Various models have been introduced to work with the CLEVR dataset, some even 'solving' the dataset by achieving near perfect performance. Despite of strong offline performance, we test if those models performance perpetuates in the more interactive setting where configurations of the scene could be changed. Whenever possible, we use pre-trained CLEVR models. Otherwise, we train the remaining models from scratch by making sure we achieve results similar to published accuracy numbers on the validation set. We summarize all the models in Table 1. We show the accuracy on the CLEVR dataset (*Accuracy*), indicate if an architecture is trained from scratch (*Re-trained*), briefly describe how multimodal fusion and reasoning is conducted (*Reasoning Mechanism*), and indicate any extra privileged information required during the training process (*Extra*). For instance, some models require extra access to functional programs used during the dataset generation, use scene graphs as a supervisory signal (states), or always operate on scene graphs (input-states). Otherwise the models were trained only from image-question-answer triples.

Mini-games. We formulate our problem as a *Game* between two players: *Visual-QA Player* and *Adversarial Player*. The *Visual-QA Player* takes as input question-image pairs and provide answers to such questions. Some models use states (scene-graphs) that replace images or require programs (Johnson et al., 2017a). The whole game consists of all CLEVR data points. For our purpose, we extend the notion of the *Game* into *Mini-games*. The rules of *Mini-games* are identical to the whole *Game*. The only difference is that each *Mini-game* operates on a subset of the CLEVR dataset. We define the size of a *Mini-game* by the number of datapoints that are attached to that *Mini-game*. We sample data points for each *Mini-game* randomly and mutually exclusively. *Mini-games* have analogies in the adversarial perturbations literature. *Mini-games* of size one resemble per-image adversarial perturbations (Goodfellow et al., 2015; Moosavi-Dezfooli et al., 2016) whereas a *Mini-game* that has all data pointsis similar to universal adversarial perturbations (Moosavi-Dezfooli et al., 2017). In this work, we investigate various *Mini-game* sizes but due to the sheer scale we were unable to use the whole game as the *Mini-game*. Larger *Mini-games* make the optimization process more difficult as the domain where the *Adversarial Player* needs to operate increases. The training is also much more time-consuming and a sequential process. Instead, we can train multiple players on different *Mini-games* independently and thus massively. We leave the arduous training of the universal *Adversarial Player* on the whole *Game* as a possible future direction.

Table 1: CLEVR models that we use as *Visual-QA Players*.

Model Name	Accuracy	Re-trained	Reasoning Mechanism	Extra Data
SAN (Yang et al., 2016)	72.1		Attention	
FiLM (Perez et al., 2018)	96.2	✓	Feature Conditioning	
RN (Santoro et al., 2017)	93.2	✓	Relational	
IEP (Johnson et al., 2017b)	96.9		Neural Program Induction	Programs
TbD (Mascharka et al., 2018)	99.1		Neural Program Induction	Programs
Mdetr (Kamath et al., 2021)	99.7		Multimodal Transformer Querying	States
State-Input Transformer (ours)	96.8	✓	Cross Attention	Input-States

4 ENVIRONMENT

We need to ensure that *Adversarial Players* create valid scenes that are *consistent* and *in-distribution*. Both properties are guaranteed by our environment enforcers.

Consistency. Since scene manipulation may change the answer for a given question, we need to ensure this does not happen. That is, the new scene is still *consistent* with the question-answer pair. The question-relevance enforcer achieves that by running functional programs associated with each question (Johnson et al., 2017a) on the modified scene-graph. Hence, it gets the new ground-truth answer. The enforcer rejects the new scene if that new answer differs from the previous one. In this way, it guarantees the newly generated scenes give the same answers as the original scenes on the same question. Thus, we can generate equivalent scenes containing the same objects that have identical answers for the same questions. Using that enforcer, we can test if the *Visual-QA Player*'s answers are invariant under such an equivalent class of scenes.

In-distribution. Even with the question-relevance enforcer, the *Adversarial Player* may still produce undesired outputs. For instance, it can stretch the whole scene thus violating the scene boundaries from the original CLEVR dataset, making, e.g., everything to look very small (Section A.9 in the appendix). Although it is still an interesting form of the adversarial scene manipulation, we focus rather on the *in-distribution* scene manipulations that respect the original boundaries. To enforce that property, we use scene-constraint enforcer that checks the boundaries of the scene. Without that enforcer, the *Adversarial Player* would quickly resort to stretching the whole scenes, achieving a form of adversarial attack that uses distribution shifts rather than content manipulation. It does so, e.g., by moving the camera away until objects are barely visible. We give a few such examples in the appendix (Section A.9).

5 *Adversarial Player*

In this section, we describe our *Adversarial Player* in details. Meaningful scene manipulations require not only generic scene understanding, but also the ability to distinguish which objects to

displace and how. Hence, the player is a composition of a multi-modal module, which creates input representation, and a decision maker, which decide how to manipulate the scene. In the following, we will describe that composition of modules, the game of scene manipulations, and the training protocol. Figure 1 illustrates the *Adversarial Player* and the game between both players.

Multi-modal module. We have experimented with the same multi-modal modules as those in Table 1, but found out we have a better performance and the convergence rate if the *Adversarial Player* operates on the scene-graphs (states) instead of pixels. For that, we use *state-input* variant of Relation Networks (Santoro et al., 2017). The model receives as the input $10 * 6$ object tokens, and question tokens. Every object token represents one-out-of-ten possible objects in the scene by its attributes such as position, color, shape, material and size. If the scene has fewer than ten objects, we use $\emptyset$ token to indicate that, which also acts as a padding. We also have special tokens that separate questions from the objects which we add as a latent embedding, e.g., $\text{emb}(\text{material}) + \text{emb}(\text{object})$. Such an input encoding is similar to our *State-Input Transformer* and described in Section A.3. The embedded vectors are given to the Relation Network (RN). Finally, we train that network on the CLEVR visual question answering task, where we achieve 97.6% on the validation set, and use the representation just after the last relational layer for the decision maker.

Decision maker. Inspired by the work on reinforcement learning (Mnih et al., 2016; Wu et al., 2017; Lillicrap et al., 2016; Wang et al., 2016; Schulman et al., 2015), we use an actor-critic module that acts on scenes. The actor is a general-purpose fully connected layer with ten object-specific heads. Each head is randomly assigned to a unique object in the scene for its manipulation. Every head produces a displacement in x and y coordinates of the corresponding object. Although we have initially experimented with the continuous output space, we have found out the following simple strategy is more effective. First, we discretise all the x and y coordinates into N bins each. Now, each head produces two N-dimensional vectors that are next projected into a probabilistic space via softmax. Next, we sample displacements in x and y axis independently from both softmax distributions. Note that, even though we do not model the joint distribution explicitly due to computational reasons, both samples condition on the common head and thus are only *conditionally* independent of each other. We discretise the scene where each axis has values in $[-3, 3]$ onto $N = 7$ bins per axis. Our

Figure 1: Our game between two players: *Adversarial Player* and *Visual-QA Player*. *Adversarial Player* uses a *multi-modal module* to extract features conditioned on the visual and textual inputs. After transforming such features with a feed-forward architecture, it samples an action using object-specific heads. Each action corresponds to manipulating the corresponding object in the scene. In the case of missing objects, we use an $\emptyset$ token. After alternating the original scene graph, we use various environment enforcers to ensure validity of the constructed scene. A valid scene graph is rendered and introduced to the *Visual-QA Player* together with the original image. Finally, we collect responses of the *Visual-QA Player* and calculate suitable rewards based on them, and we repeat the whole cycle during the training phase.

critic is a simple three layer feed-forward network (with relu as activations) that predicts a reward score between -1 and $+1$ via tanh activation ($1.2 * $ tanh for better numerical properties).

The game of scene manipulations. Due to our formulation of *Adversarial Player* and the environment, we can benchmark various reasoning models purely in the *black-box* setting via a series of questions about the scene. *Adversarial Player* manipulates the scene so that it is still consistent with the question-answer pair. The manipulations are applied to scene-graphs, and the resulting scene-graph is evaluated by the environment enforcers described in Section 4. Invalid scenes are thus discarded. In this way, we ensure the *in-distribution* and *consistency* in the scene generation. Original image-question pairs are fed to a *Visual-QA Player* that produces corresponding answers. We refer to that answers as *old answers*. After the scene manipulation, new images paired with the same questions are also given to the *Visual-QA Player* that produces *new answers*. We construct rewards based on *old answers*, *new answers* and *ground-truth answers*.

If the *Adversarial Player* forces the *Visual-QA Player* to change the answer, i.e., an *old answer* is different than a *new answer*, it gets *Consistency Drop Reward* (*cr*). If an *old answer* is the *ground-truth* answer, it gets instead *Accuracy Drop Reward* (*dr*). Both rewards differentiate between simply confusing the model and causing a drop in its performance. If *Adversarial Player* produces an invalid scene it gets *Invalid Scene Reward* (*isr*). This reward encourages producing scenes that pass the environment enforcers tests. Finally, if *Adversarial Player* does not manage to fool the model, it gets *Fail Reward* (*fr*). We use the following values: $dr = 1, cr = 0.1, fr = -0.1, isr = -0.8$.

Training algorithm. To train *Adversarial Player* we use the A2C algorithm with the episode length set to one as we do not need to model long-range consequences of the decision-making mechanism. Batches contain images, question, answers, programs and scene-graphs. We train the *Adversarial Player* for each *Mini-game* independently using the same architecture. We experiment with the following *Mini-game* sizes $10, 100, 1000$. All *Mini-games* are constructed randomly. Under our discretisation scheme, the action space is N^k where N is the number of bins and k is the number of objects in the scene. In practice, it is up to 49^{10}.

6 EXPERIMENTS

Main experimental results are presented in Table 2. First, we explain the terminology and this is followed by analysis of quantitative and qualitative results, additional experiments and limitations.

In our experiments, we consider *Adversarial Player* with a multi-modal module pre-trained either on states (*state-input*) or directly from pixels (*pixel-input*). As explained in Section 5, we train *Adversarial Player* for each *Mini-game* independently. We use different *Mini-game* sizes in our experiments: 10, 100 and 1000. To obtain statistically significant results, we run each *Mini-game* thirty times with randomly initialized *Adversarial Players*, each with different seed per trial. We report the results that are averaged over all those runs. We compute two metrics for each *Mini-game*. *Consistency* refers to the fraction of times *Adversarial Player* has changed the *Visual-QA Player*'s answer, regardless if that answer was correct. *Drop* refers to the fraction of times *Adversarial Player* has changed the *correct Visual-QA Player*'s answer. We aggregate the results using the following statistics. *Average Accuracy* averages accuracies over all *Mini-games*. *Maximal Accuracy* refers to the maximal accuracy over all *Mini-games* (so it refers to accuracy of a single *Mini-game*). It is the worst (best) case from the *Visual-QA Player* (*Adversarial Player*) perspective. We also computed p-values of T-Test, with the null hypothesis that a manipulation is unsuccessful. In almost all cases we reject the null hypothesis with small p-values. We only did not 'fool' TbD and MDetr, and only if *pixel-input Adversarial Player* is considered (Section A.11, in the appendix).

Quantitative results. We show our results in Table 2 for the *state-input* and *pixel-input Adversarial Players*, and for each *Visual-QA Player* presented in Table 1. All the *Visual-QA Players* in the comparison are trained from pixels, apart form our custom *State-Input Transformer* architecture (Section A.3 in the appendix). When comparing both *Adversarial Players*, we can observe that the *state-input Adversarial Player* is significantly more successful than the *pixel-input* one. We hypothesize that this is the effect of having more structured and less ambiguous input information. It could also be the case that multi-modal modules trained from pixels ignore features in the same way and hence smaller discrepancy between all models operating on pixels. Another observation is that in the case of TbD and MDetr, *pixel-input Adversarial Players* are unable to solve the smallest-size *Mini-games*. Moreover, as the size of *Mini-games* increases, it is becoming more difficult for the *Adversarial Player* to successfully manipulate the model on all examples from the *Mini-game*. It is

an expected behavior resembling standard adversarial perturbations (Goodfellow et al., 2015) and their universal variants (Moosavi-Dezfooli et al., 2017). The highest performing CLEVR models, TbD and MDetr, are the most robust under the manipulation. However, they are still susceptible to the scene manipulations in some *Mini-games* as the *Maximal Consistency* metric indicates, especially if our *Adversarial Player* uses states as the input. Section A.8 (appendix) also shows richer performance statistics. Our detailed investigation shows that the models above are particularly sensitive to manipulations of scenes associated with *counting* or *existence* questions. Questions of those types are often more complex, hence, increasing the likelihood of the reasoning failure at some stage (Section A.6 in the appendix).

Qualitative results. Figure 4 shows qualitative results of the scene manipulations for the three highest performing and distinctive models from Table 1; e.g., simple feed-forward or program induction models. For the reader's convenience, we provide in Section A.2 (appendix) examples of CLEVR object attributes. We can observe that the scene manipulations are surprisingly minimal and are semantically *meaningless*, i.e., they should not 'fool' human players.

Saturation of *Adversarial Player*. Training an *Adversarial Player* on larger *Mini-games* become an increasingly more difficult task as the player needs to operate successfully on more diverse examples. Figure 2 shows the performance of the *Adversarial Player* against *Mini-game* sizes, where FiLM, TbD, MDetr and *Input-State Transformer* (Trans.) are chosen as *Visual-QA Players*. We can see that the performance of *Adversarial Player* saturates around *Mini-games* of size 10k, which we call the *Critical mini-game size*. We use two trials for our experiments, and the *Accuracy Drop* as a metric. It measures the drop in accuracy of a *Visual-QA Player*.

Adversarial training. In initial experiments, we have adapted a widely used adversarial training (Goodfellow et al., 2018), where we include manipulated scenes in the training protocol of a *Visual-QA Player*. We use *pixel-input* RN (Santoro et al., 2017) as the *Visual-QA Player*. Using this method, we have obtained only marginal improvements in robustness at the cost of a slight performance degradation on the original CLEVR dataset.

Limitations of data-driven CLEVR models. If we can't achieve robustness under scene manipulations with the adversarial training, what fraction of all data is sufficient then? Intuitively, if the network has enough capacity, and was trained on all possible data points or its manipulations, it should rely on a look-up strategy to solve the problem accurately. We propose the following experiment to address such a question. We create a dataset containing three objects in six different starting positions and seven templated questions. We consider only object displacements on the grid 7×7, and thus $49^3 = 117649$ combinations are possible. We use a few architectures from Table 1 as a *pixel-input Visual-QA Player*. We train them on $X\%$ data and next evaluate on $(100-X)\%$ remaining, unseen data. We have conducted ten trials by forming $X\%$ training data randomly. Figure 3 shows that when trained on 10% of data, the model becomes resistant to 40% of unseen manipulations. The robustness of the model increases linearly, saturating at roughly 97% accuracy after observing almost all data (90%). The behaviour of all tested models is similar with slightly better overall performance of TbD. The results indicate that a lot of training examples are needed to cover most configurations of our task in the absence of stronger inductive biases.

7 CONCLUSIONS

We present a novel approach to benchmarking the reasoning capabilities of various visual models by formulating a game between two players. Both players are independent and can only communicate through a common interface: an environment and question-answer pairs. One player, named *Adversarial Player*, is trying to manipulate the environment so that the second player, named *Visual-QA Player*, can't answer the given question anymore. To test our framework, we run our game against a few popular CLEVR models that achieve solid results on the CLEVR dataset; often surpassing the human baseline. We show that such models are susceptible to scene manipulations, and their performance may degrade significantly. Moreover, we also conducted a controlled study on the generalization capabilities of such models. We did so by creating a synthetic and simplified dataset of all possible scene manipulations. We show that the existing models are not particularly efficient learners and require significantly more than 50% of all data to generalize to all possible scene configurations. One possible direction to increase efficiency could be the use of stronger inductive biases. Another to change a training paradigm that is more interactive. However, the environment is synthetic, and it could be that learning from real-world and multi-modal data is somewhat more efficient. Finally, we believe that melding two-player games with the visual question answering framework is both natural

and beneficial for testing the reasoning capabilities of various models; and potentially can also be generalized to other settings. In the long term, we plan to test such models through web interfaces.

Table 2: Results of the game with the *state-input* and *pixel-input Adversarial Players*. *Before* refers to the original accuracy of the CLEVR model, before manipulations are applied. Other columns show the results after scene manipulations, using average or maximum (worst-case manipulations) accuracies. We also report in brackets a relative drop in the performance, in percentages. All *Visual-QA Players* but *State-Input Transformer* use pixels as the input. The latter uses states as the input.

Model	*Mini-game size*	Before	Average Accuracy		Maximal Accuracy	
			State-Input	Pixel-Input	State-Input	Pixel-Input
SAN	10		61.86 (-14.2%)	63.88 (-11.4%)	28.84 (-60.0%)	43.26 (-40.0%)
	100	72.1	66.11 (-8.3%)	69.28 (-3.9%)	47.65 (-33.9%)	66.32 (-8.0%)
	1000		70.29 (-2.5%)	71.09 (-1.4%)	68.42 (-5.1%)	70.87 (-1.7%)
FiLM	10		83.98 (-12.7%)	93.69 (-2.6%)	48.10 (-50.0%)	86.58 (-10.0%)
	100	96.2	89.17 (-7.3%)	94.85 (-1.4%)	75.61 (-21.4%)	92.44 (-3.9%)
	1000		93.89 (-2.4%)	95.81 (-0.4%)	90.81 (-5.6%)	94.75 (-1.5%)
RN	10		80.52 (-13.6%)	86.48 (-7.2%)	46.60 (-50.0%)	74.56 (-20.0%)
	100	93.2	85.55 (-8.2%)	90.87 (-2.5%)	63.28 (-32.1%)	87.42 (-6.2%)
	1000		90.59 (-2.8%)	91.61 (-1.7%)	90.03 (-3.4 %)	91.05 (-2.3%)
IEP	10		84.30 (-13.0%)	94.47 (-2.5%)	48.45 (-50.0%)	87.21 (-10.0%)
	100	96.9	90.31 (-6.8%)	95.64 (-1.3%)	74.41 (-23.2%)	93.50 (-3.5%)
	1000		94.18 (-2.8%)	96.60 (-0.3%)	93.99 (-3.0%)	95.73 (-1.2%)
TbD	10		94.04 (-5.1%)	99.10 (-0.0%)	69.37 (-40.0%)	99.10 (-0.0%)
	100	99.1	96.62 (-2.5%)	98.70 (-0.4%)	91.17 (-8.0%)	98.00 (-1.1%)
	1000		98.00 (-1.1%)	99.00 (-0.1%)	95.53 (-3.6%)	98.80 (-0.3%)
Mdetr	10		93.71 (-6.0%)	99.70 (-0.0%)	59.82 (-40.0%)	99.70 (-0.0%)
	100	99.7	96.11 (-3.6%)	98.60 (-1.1%)	86.43 (-13.3%)	97.80 (-1.9%)
	1000		98.50 (-1.2%)	99.40 (-0.3%)	94.51 (-5.2%)	99.10 (-0.6%)
State Input Transf.	10		89.34 (-7.7%)	96.02 (-0.8%)	77.44 (-20.0%)	91.96 (-5.0%)
	100	96.8	94.76 (-2.1%)	96.12 (-0.7%)	92.63 (-4.3%)	95.05 (-1.8%)
	1000		95.73 (-1.1%)	96.50 (-0.3%)	95.15 (-1.7%)	95.83 (-1.0%)

Figure 2: The performance of *Adversarial Player* with respect to *Mini-game* sizes. We use *Accuracy Drop* to measure the drop in performance of the *Visual-QA Player*. The lower the value, the less successful the adversarial manipulation is.

Figure 3: Performance of *Visual-QA Players* on our custom dataset of all possible manipulations. We train the *Visual-QA Player* on different fractions of data (x-axis) and test on the remaining data using standard accuracy measure (y-axis).

Figure 4: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

REFERENCES

Aishwarya Agrawal, Dhruv Batra, Devi Parikh, and Aniruddha Kembhavi. Don't just assume; look and answer: Overcoming priors for visual question answering. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition*, pp. 4971–4980, 2018.

Moustafa Alzantot, Yash Sharma, Supriyo Chakraborty, and Mani B. Srivastava. Genattack: Practical black-box attacks with gradient-free optimization. *CoRR*, abs/1805.11090, 2018. URL http://arxiv.org/abs/1805.11090.

Stanislaw Antol, Aishwarya Agrawal, Jiasen Lu, Margaret Mitchell, Dhruv Batra, C. Lawrence Zitnick, and Devi Parikh. Vqa: Visual question answering. In *Proceedings of the IEEE International Conference on Computer Vision (ICCV)*, 2015.

Rishabh Bhardwaj, Navonil Majumder, and Soujanya Poria. Investigating gender bias in bert. *Cognitive Computation*, pp. 1–11, 2021.

Nicholas Carlini and David A. Wagner. Towards evaluating the robustness of neural networks. *CoRR*, abs/1608.04644, 2016. URL http://arxiv.org/abs/1608.04644.

Yen-Chun Chen, Linjie Li, Licheng Yu, Ahmed El Kholy, Faisal Ahmed, Zhe Gan, Yu Cheng, and Jingjing Liu. Uniter: Learning universal image-text representations. 2019.

Yen-Chun Chen, Linjie Li, Licheng Yu, Ahmed El Kholy, Faisal Ahmed, Zhe Gan, Yu Cheng, and Jingjing Liu. Uniter: Universal image-text representation learning. In *ECCV*, 2020.

Minhao Cheng, Thong Le, Pin-Yu Chen, Huan Zhang, JinFeng Yi, and Cho-Jui Hsieh. Query-efficient hard-label black-box attack: An optimization-based approach. In *International Conference on Learning Representations*, 2018.

Shuyu Cheng, Yinpeng Dong, Tianyu Pang, Hang Su, and Jun Zhu. Improving black-box adversarial attacks with a transfer-based prior. In H. Wallach, H. Larochelle, A. Beygelzimer, F. d'Alché-Buc, E. Fox, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 32. Curran Associates, Inc., 2019. URL https://proceedings.neurips.cc/paper/2019/file/32508f53f24c46f685870a075eaaa29c-Paper.pdf.

François Chollet. On the measure of intelligence. *arXiv preprint arXiv:1911.01547*, 2019.

Alexis Conneau, Guillaume Lample, Marc'Aurelio Ranzato, Ludovic Denoyer, and Hervé Jégou. Word translation without parallel data. *arXiv preprint arXiv:1710.04087*, 2017.

Thomas Degris, Patrick M. Pilarski, and Richard S. Sutton. Model-free reinforcement learning with continuous action in practice. In *2012 American Control Conference (ACC)*, pp. 2177–2182, 2012. doi: 10.1109/ACC.2012.6315022.

Donald Geman, Stuart Geman, Neil Hallonquist, and Laurent Younes. Visual turing test for computer vision systems. *Proceedings of the National Academy of Sciences*, 112(12):3618–3623, 2015.

Rohit Girdhar and Deva Ramanan. Cater: A diagnostic dataset for compositional actions and temporal reasoning. *arXiv preprint arXiv:1910.04744*, 2019.

Ian Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples. In *International Conference on Learning Representations*, 2015. URL http://arxiv.org/abs/1412.6572.

Ian Goodfellow, Patrick McDaniel, and Nicolas Papernot. Making machine learning robust against adversarial inputs. *Communications of the ACM*, 61(7):56–66, 2018.

Chuan Guo, Jacob R. Gardner, Yurong You, Andrew G. Wilson, and Kilian Q. Weinberger. Simple black-box adversarial attacks, 2019a. URL https://openreview.net/forum?id=rJeZS3RcYm.

Dalu Guo, Chang Xu, and Dacheng Tao. Graph reasoning networks for visual question answering. *CoRR*, abs/1907.09815, 2019b. URL http://arxiv.org/abs/1907.09815.

FR Helmert. Die genauigkeit der formel von peters zur berechnung des wahrscheinlichen beobachtungsfehlers director beobachtungen gleicher genauigkeit. *Astronomische Nachrichten*, 88:113, 1876.

Lisa Anne Hendricks, Kaylee Burns, Kate Saenko, Trevor Darrell, and Anna Rohrbach. Women also snowboard: Overcoming bias in captioning models. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 771–787, 2018.

Drew A Hudson and Christopher D Manning. Compositional attention networks for machine reasoning. *arXiv preprint arXiv:1803.03067*, 2018.

Andrew Jaegle, Felix Gimeno, Andrew Brock, Andrew Zisserman, Oriol Vinyals, and Joao Carreira. Perceiver: General perception with iterative attention. *arXiv preprint arXiv:2103.03206*, 2021.

Huaizu Jiang, Ishan Misra, Marcus Rohrbach, Erik Learned-Miller, and Xinlei Chen. In defense of grid features for visual question answering. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Li Fei-Fei, C. Lawrence Zitnick, and Ross Girshick. Clevr: A diagnostic dataset for compositional language and elementary visual reasoning. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, July 2017a.

Justin Johnson, Bharath Hariharan, Laurens van der Maaten, Judy Hoffman, Li Fei-Fei, C Lawrence Zitnick, and Ross Girshick. Inferring and executing programs for visual reasoning. In *ICCV*, 2017b.

Ameya Joshi, Amitangshu Mukherjee, Soumik Sarkar, and Chinmay Hegde. Semantic adversarial attacks: Parametric transformations that fool deep classifiers. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pp. 4773–4783, 2019.

Aishwarya Kamath, Mannat Singh, Yann LeCun, Ishan Misra, Gabriel Synnaeve, and Nicolas Carion. Mdetr–modulated detection for end-to-end multi-modal understanding. *arXiv preprint arXiv:2104.12763*, 2021.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial machine learning at scale. *arXiv preprint arXiv:1611.01236*, 2016.

Shane Legg. *Machine super intelligence*. PhD thesis, Università della Svizzera italiana, 2008.

Timothy P. Lillicrap, Jonathan J. Hunt, Alexander Pritzel, Nicolas Heess, Tom Erez, Yuval Tassa, David Silver, and Daan Wierstra. Continuous control with deep reinforcement learning. In *ICLR (Poster)*, 2016. URL http://arxiv.org/abs/1509.02971.

Locatello. Object-centric learning with slot attention. In *Neural Information Processing Systems (NeurIPS)*, 2020.

Jiasen Lu, Dhruv Batra, Devi Parikh, and Stefan Lee. Vilbert: Pretraining task-agnostic visiolinguistic representations for vision-and-language tasks. *arXiv preprint arXiv:1908.02265*, 2019.

J Lüroth. Vergelichung von zwei werthen des wahrscheinlichen fehlers. *Astronomische Nachrichten*, 87:209, 1876.

Mateusz Malinowski and Mario Fritz. A multi-world approach to question answering about real-world scenes based on uncertain input. *Advances in neural information processing systems*, 27: 1682–1690, 2014.

Mateusz Malinowski, Carl Doersch, Adam Santoro, and Peter Battaglia. Learning visual question answering by bootstrapping hard attention. In *Proceedings of the European Conference on Computer Vision (ECCV)*, pp. 3–20, 2018.

David Mascharka, Philip Tran, Ryan Soklaski, and Arjun Majumdar. Transparency by design: Closing the gap between performance and interpretability in visual reasoning. In *The IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

Volodymyr Mnih, Adria Puigdomenech Badia, Mehdi Mirza, Alex Graves, Timothy Lillicrap, Tim Harley, David Silver, and Koray Kavukcuoglu. Asynchronous methods for deep reinforcement learning. In Maria Florina Balcan and Kilian Q. Weinberger (eds.), *Proceedings of The 33rd International Conference on Machine Learning*, volume 48 of *Proceedings of Machine Learning Research*, pp. 1928–1937, New York, New York, USA, 20–22 Jun 2016. PMLR. URL `https://proceedings.mlr.press/v48/mniha16.html`.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, and Pascal Frossard. Deepfool: A simple and accurate method to fool deep neural networks. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, June 2016.

Seyed-Mohsen Moosavi-Dezfooli, Alhussein Fawzi, Omar Fawzi, and Pascal Frossard. Universal adversarial perturbations. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 1765–1773, 2017.

Nicolas Papernot, Patrick McDaniel, Ian Goodfellow, Somesh Jha, Z Berkay Celik, and Ananthram Swami. Practical black-box attacks against machine learning. In *Proceedings of the 2017 ACM on Asia conference on computer and communications security*, pp. 506–519, 2017.

Ethan Perez, Florian Strub, Harm de Vries, Vincent Dumoulin, and Aaron C. Courville. Film: Visual reasoning with a general conditioning layer. In *AAAI*, 2018.

Oskar Pfungst. *Clever Hans:(the horse of Mr. Von Osten.) a contribution to experimental animal and human psychology*. Holt, Rinehart and Winston, 1911.

Piotr Piekos, Henryk Michalewski, and Mateusz Malinowski. Measuring and improving bert's mathematical abilities by predicting the order of reasoning. In Chengqing Zong, Fei Xia, Wenjie Li, and Roberto Navigli (eds.), *Proceedings of the 59th Annual Meeting of the Association for Computational Linguistics and the 11th International Joint Conference on Natural Language Processing, ACL/IJCNLP 2021, (Volume 2: Short Papers), Virtual Event, August 1-6, 2021*. Association for Computational Linguistics, 2021.

Adam Santoro, David Raposo, David G Barrett, Mateusz Malinowski, Razvan Pascanu, Peter Battaglia, and Timothy Lillicrap. A simple neural network module for relational reasoning. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30, 2017.

John Schulman, Sergey Levine, Pieter Abbeel, Michael Jordan, and Philipp Moritz. Trust region policy optimization. In Francis Bach and David Blei (eds.), *Proceedings of the 32nd International Conference on Machine Learning*, volume 37 of *Proceedings of Machine Learning Research*, pp. 1889–1897, Lille, France, 07–09 Jul 2015. PMLR. URL `https://proceedings.mlr.press/v37/schulman15.html`.

Weijie Su, Xizhou Zhu, Yue Cao, Bin Li, Lewei Lu, Furu Wei, and Jifeng Dai. Vl-bert: Pre-training of generic visual-linguistic representations. In *International Conference on Learning Representations*, 2020. URL `https://openreview.net/forum?id=SygXPaEYvH`.

Richard S. Sutton and Andrew G. Barto. *Reinforcement Learning: An Introduction*. The MIT Press, second edition, 2018. URL `http://incompleteideas.net/book/the-book-2nd.html`.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks, 2014.

Hao Tan and Mohit Bansal. Lxmert: Learning cross-modality encoder representations from transformers. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*, 2019.

Makarand Tapaswi, Yukun Zhu, Rainer Stiefelhagen, Antonio Torralba, Raquel Urtasun, and Sanja Fidler. Movieqa: Understanding stories in movies through question-answering. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pp. 4631–4640, 2016.

Alan M Turing. Computing machinery and intelligence. In *Parsing the turing test*, pp. 23–65. Springer, 2009.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N Gomez, Łukasz Kaiser, and Illia Polosukhin. Attention is all you need. In *Advances in neural information processing systems*, pp. 5998–6008, 2017.

Tan Wang, Jianqiang Huang, Hanwang Zhang, and Qianru Sun. Visual commonsense r-cnn. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 10760–10770, 2020.

Zirui Wang, Jiahui Yu, Adams Wei Yu, Zihang Dai, Yulia Tsvetkov, and Yuan Cao. Simvlm: Simple visual language model pretraining with weak supervision. *arXiv preprint arXiv:2108.10904*, 2021.

Ziyu Wang, Victor Bapst, Nicolas Heess, Volodymyr Mnih, Rémi Munos, Koray Kavukcuoglu, and Nando de Freitas. Sample efficient actor-critic with experience replay. *CoRR*, abs/1611.01224, 2016. URL http://arxiv.org/abs/1611.01224.

Yuhuai Wu, Elman Mansimov, Roger B Grosse, Shun Liao, and Jimmy Ba. Scalable trust-region method for deep reinforcement learning using kronecker-factored approximation. In I. Guyon, U. V. Luxburg, S. Bengio, H. Wallach, R. Fergus, S. Vishwanathan, and R. Garnett (eds.), *Advances in Neural Information Processing Systems*, volume 30. Curran Associates, Inc., 2017. URL https://proceedings.neurips.cc/paper/2017/file/361440528766bbaaaa1901845cf4152b-Paper.pdf.

Zichao Yang, Xiaodong He, Jianfeng Gao, Li Deng, and Alex Smola. Stacked attention networks for image question answering. In *Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2016.

Kexin Yi, Jiajun Wu, Chuang Gan, Antonio Torralba, Pushmeet Kohli, and Joshua B Tenenbaum. Neural-symbolic vqa: Disentangling reasoning from vision and language understanding. *arXiv preprint arXiv:1810.02338*, 2018.

Zhou Yu, Dejing Xu, Jun Yu, Ting Yu, Zhou Zhao, Yueting Zhuang, and Dacheng Tao. Activitynet-qa: A dataset for understanding complex web videos via question answering. In *Proceedings of the AAAI Conference on Artificial Intelligence*, volume 33, pp. 9127–9134, 2019.

Xiaohui Zeng, Chenxi Liu, Yu-Siang Wang, Weichao Qiu, Lingxi Xie, Yu-Wing Tai, Chi-Keung Tang, and Alan L Yuille. Adversarial attacks beyond the image space. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 4302–4311, 2019.

Pengchuan Zhang, Xiujun Li, Xiaowei Hu, Jianwei Yang, Lei Zhang, Lijuan Wang, Yejin Choi, and Jianfeng Gao. Vinvl: Revisiting visual representations in vision-language models. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pp. 5579–5588, June 2021.

A APPENDIX

A.1 URLs OF CLEVR MODELS

Table 3 shows the URLs to models used in our investigations (also Table 1 in the main paper). We also report if we re-trained a model from scratch (type *Architecture*) or used already trained models (type *Model*). Please note that the latter type proves that our testing procedure is fully black-box.

Model Name	Link	Type
SAN (Yang et al., 2016)	https://github.com/facebookresearch/clevr-iep	Model
IEP (Johnson et al., 2017b)	https://github.com/facebookresearch/clevr-iep	Model
FiLM (Perez et al., 2018)	https://github.com/ethanjperez/film	Architecture
RN (Santoro et al., 2017)	https://github.com/mesnico/RelationNetworks-CLEVR	Architecture
TbD (Mascharka et al., 2018)	https://github.com/davidmascharka/tbd-nets	Model
Mdetr (Kamath et al., 2021)	https://github.com/ashkamath/mdetr	Model

Table 3: URLs to Models. *Architecture* denotes that we use the code but re-trained the model on CLEVR. *Model* refers to already trained models.

A.2 OBJECT CATEGORIES

Figure 5 shows a made-up image that contains all available CLEVR object categories: shapes, sizes and materials. Small objects are rendered at approximately 40% of the size of their large counterparts. Metalic materials can be identified by the high albedo property and 'shininess' of the object. We provide it as the reference point for a reader to make it easier to compare our qualitative results.

Figure 5: Object categories in the CLEVR dataset.

A.3 STATE-INPUT TRANSFORMER

To test our two-player game against a *state-input Visual-QA Player*, we have designed a transformer-based architecture Vaswani et al. (2017) that receives six types of input features – object sizes, object shapes, object materials, object colors, object positions, and question tokens – and uses a cross-modal attention mechanism. In that mechanism, queries from one modality attend to keys and values from the another modality. Since each data point contains a variable-length inputs describing the all objects in the scene as well as question tokens that compose the question itself, we do padding with a special token $\emptyset$ to the maximal input length. We set the maximal length for the objects tokens to be $10 * 6 = 60$ and 50 for the question tokens. All in all, we have 110 input tokens. Each token type is projected into a different embedding space and a learnable type embedding is added to it, separately for object and question tokens. For instance, emb(material) + emb(object). Furthermore, three special learnable embeddings are used as an additional input. We use them as queries to reduce the overall computational costs of the cross-attention mechanism. The same mechanism is also used in Perceiver (Jaegle et al., 2021). The input tokens (concatenated object and question tokens) form keys and values. In every transformer block, we apply cross-attention between all input embeddings and those three special tokens. This is repeated five times. As the final block, a feed-forward network (classifier) receives as inputs the three latent token and outputs answer probabilities. We show that architecture in Figure 6.

Figure 6: Our State-Input Transformer that operates on the graph scene (states).

A.4 MANIPULATIONS OF *State-Input Visual-QA Player*

Figures 7 and 8 show manipulations of *Visual-QA Player* that is trained to take *states* instead of *pixels* as the input. Such a *state-input Visual-QA Player* receives a direct overview of the scene, bypassing any need for any image renderings. We use *State-Input Transformer* (Section A.3) as the *multi-modal* component of that player. Since such a model gets the perfect visual information as the input, it makes it more robust under scene manipulations. As a consequence, our *Adversarial Player* tend to manipulate the scene so that objects are placed closely together. Often, simpler questions, which require fewer stages of reasoning, are safer to *Visual-QA Player*. Let us consider the last example in Figure 8. If the question was *What is the material of the cyan cube?*, the model would answer rightfully *metal*. Here, *Adversarial Player* 'breaks' the spatial reasoning step by creating ambiguity between the cubes and thus a wrong answer is derived.

Figure 7: Qualitative results on *state-input Visual-QA Player*. For each example, a top-down view of the scene is presented. The eye at the bottom right of each view represents the rendering camera. It corresponds to the *Visual-QA Player*'s viewpoint. Each scene is also rendered and presented side-by-side for comparison.

How many other things are both behind the purple rubber sphere
and to the right of the gray cylinder?

Figure 8: Qualitative results on *state-input Visual-QA Player*. For each example, a top-down view of the scene is presented. The eye at the bottom right of each view represents the rendering camera. It corresponds to the *Visual-QA Player*'s viewpoint. Each scene is also rendered and presented side-by-side for comparison.

A.5 ALGORITHMS

We show pseudo-algorithms that we use to (Algorithm 1) calculate rewards, (Algorithm 2) train *Adversarial Player*, (Algorithm 3) play a game, (Algorithm **??**) create a defence mechanism.

Algorithm 1 Calculate Rewards

1: new_answer : Answer produced by Visual Agent on perturbed image
2: old_answer : Answer produced by Visual Agent on original image
3: gt_answer : Ground Truth Answer
4: dr : Drop Reward
5: cr : Consistency Reward
6: fr : Fail Reward
7: $reward \leftarrow 0$
8: **if** $new\_answer \neq old\_answer$ **then**
9:     **if** $old\_answer \neq gt\_answer$ **then**
10:        $reward = reward + cr$
11:     **else**
12:        $reward = reward + dr$
13:     **end if**
14: **else**
15:     $reward = reward + fr$
16: **end if**
17: **return** $reward$

Algorithm 2 Training Pipeline

1: M : Minigames
2: Va : Visual Agent, Fe : Feature Extractor
3: A : Actor, C : Critic
4: Qre : Question Relevance Enforcer, Sce : Scene Constraint Enforcer
5: **for** $batch\ in\ M$ **do**
6:     $rewards, state\_values, logprobs \leftarrow DataGame(M, Va, Fe, A, C, Qre, Sce)$
7:     $n \leftarrow |rewards|$
8:     $advantage \leftarrow rewards - state\_values$
9:     $ploss \leftarrow -logprobs \times advantage$
10:     $vloss \leftarrow (state\_values - stop\_grad(rewards))^2/n$
11:     $loss \leftarrow ploss + vloss$
12:     $backprop(loss, A, C)$
13: **end for**
14: **return**

Algorithm 3 Game between players (Game)

1: M : *Mini-game*
2: $\mathcal{P}_{\text{VQA}}$: Visual Agent, $\mathcal{S}_k$: Multi-modal Backbone
3: A : Actor, C : Critic
4: Qre : Question Relevance Enforcer, Sce : Scene Constraint Enforcer
5: isr : Invalid Scene Reward
6: **for** $batch\ in\ M$ **do**
7:     $rewards \leftarrow \{\}$
8:     $state\_values \leftarrow \{\}$
9:     $logprobs \leftarrow \{\}$
10:     **for** $(image, scene, question, program, gt\_answer)\ in\ batch$ **do**
11:         $old\_answer \leftarrow \mathcal{P}_{\text{VQA}}(image, question)$
12:         $extracted\_features \leftarrow \mathcal{S}_k(scene, question)$
13:         $dx\_probs, dy\_probs \leftarrow A(extracted\_features)$
14:         $CatX \leftarrow Categorical(dx\_probs)$
15:         $CatY \leftarrow Categorical(dy\_probs)$
16:         $state\_value \leftarrow C(extracted\_features)$
17:         $dx \leftarrow$ sample $CatX$
18:         $dy \leftarrow$ sample $CatY$
19:         $new\_scene \leftarrow Perturbate(scene, dx, dy)$
20:         $check\_scene \leftarrow Sce(new\_scene)$
21:         $check\_question \leftarrow Qre(new\_scene, program, gt\_answer)$
22:         **if** $check\_scene \wedge check\_question = \ True$ **then**
23:             $new\_image \leftarrow Render(new\_scene)$
24:             $new\_answer \leftarrow \mathcal{P}_{\text{VQA}}(new\_image, question)$
25:             $rewards \leftarrow rewards \,||\, CalcRewards(new\_answer, old\_answer, gt\_answer)$
26:         **else**
27:             $rewards \leftarrow rewards \,||\, isr$
28:         **end if**
29:         $state\_values \leftarrow state\_values \,||\, state\_value$
30:         $logprob \leftarrow logprob \,||\, log(p(dx|CatX))) + log(p(dy|CatY)))$
31:     **end for**
32: **end for**
33: **return** $rewards, state\_values, logprobs$

A.6 SENSITIVITY TO QUESTION TYPES

Figure 9 shows the susceptibility of CLEVR models to scene manipulations of *Adversarial Player*. We observe that especially *counting* and *existence* questions are the 'back-doors' for our scene manipulations. Questions of those two types typically involves multiple steps of reasoning. *Adversarial Player*'s scene manipulations make them more likely that reasoning will fail at some stage.

Figure 9: Histograms of the model's susceptibility to scene manipulations conditioned on a question type.

A.7 CONVERGENCE

Figure 10 shows convergence plots of *Adversarial Player* during training against FiLM, TbD and MDetr. We use different initialization seeds and 30 trials. *Adversarial Player* is trained either from *states* or *pixels*. The former yields higher performance and sometimes better convergence. We use the *Drop* metric that measures the accuracy drop after the *Visual-QA Player* is manipulated. The higher *Drop*, the more successful manipulations are.

Figure 10: Performance of *Adversarial Player* for different training snapshots. We show the mean and variance over thirty trials. *Adversarial Player* is either trained from *states* (blue) or *pixels* (orange).

A.8   PERFORMANCE DISTRIBUTION PLOTS

Figures 11 and 12 show the distribution of the *Adversarial Player* performance, where we show how often (y-axis) the given *Drop* score is achieved (x-axis). The *Drop* metric measures the accuracy drop after the *Visual-QA Player* is manipulated. The higher *Drop*, the more successful manipulations are. Larger *Mini-games* lead to more consistent (narrower distributions) but lower performance. This behaviour suggests that scene diversity present in larger *Mini-games* lead to more stable scene manipulations. However, they do so at the cost of increasing the complexity of the optimization problem.

Figure 11: *Mini-games* performance distribution for *state-input Adversarial Player*.

Figure 12: *Mini-games* performance distribution for *pixel-input Adversarial Player*.

A.9 OUT-OF-DISTRIBUTION MANIPULATIONS

If we do not provide extra constraints on the scene generation process with our environment enforcers, *Adversarial Player* may find an easy manipulation that changes the camera pose or location, effectively 'zooming out' the whole scene. It does so by stretching all the object coordinates in the scene. Figure 13 illustrates that. For instance, *large* objects look much smaller than typical examples. As such constructed scenes are quite different from the ones that *Visual-QA Player* has observed during training, we categorize such manipulations to be *out-of-distribution*. Note that, due to our *in-distribution* environment enforcers, such scenes are prohibited in our pipeline.

(a) Shape of the blue cube is misclassified as sphere. (b) Large, brown cylinder is misclassified as small.

(c) Large, yellow cube is misclassified as small.

Figure 13: Out-of-distribution examples.

A.10 Additional Qualitative Results

In Figures 14-23, we provide more qualitative results.

Figure 14: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 15: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 16: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 17: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 18: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 19: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 20: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 21: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 22: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

Figure 23: Manipulations of CLEVR models. We show results *before* and *after* scene manipulations.

A.11 QUANTITATIVE RESULTS WITH p-VALUES

We extend the quantitative results of the main paper by also reporting p-values of the one-sample hypothesis testing. Here, we also use the *Accuracy Drop* metric that measures the accuracy drop after the *Visual-QA Player* is manipulated, and the *Consistency Drop* that measures how many times the manipulated *Visual-QA Player* changes its answer, independently if that is a correct or wrong answer. The higher *Drop Accuracy* or *Consistency Drop*, the more successful manipulations are. Note that we use the same metrics as rewards to our *Adversarial Player*. We use T-Test (Helmert, 1876; Lüroth, 1876) for each metric all the runs. Our null hypothesis is that the population mean of all the games is zero, indicating that a manipulation is unsuccessful, and the results of our *Adversarial Players* are extreme cases of a good performance, i.e, $H_0 : \mu_l = 0, l \in [\text{Drop}, \text{Consistency}]$. As an alternative hypothesis, we assume that the population mean is greater than zero, i.e., $H_A : \mu_l > 0, l \in [\text{Drop}, \text{Consistency}]$. The same setup stands for both the *Consistency* and the *Drop* metric. Tables 4 and 5 show the full table with p-values computed. Note that only in two cases, *Adversarial Player* does not manipulate the scene convincingly (TbD and Mdetr for the *pixel-input Adversarial Player*).

Table 4: Results of the game with the *state-input Adversarial Player*.

Model	*Mini-game* size	Average Consistency Drop %	Accuracy Drop %	Maximum Consistency Drop %	Accuracy Drop %	p-value Consistency Drop	Accuracy Drop
SAN	10	-23.9	-14.2	-60.0	-60.0	0.000	0.000
	100	-10.7	-8.3	-34.1	-33.9	0.000	0.000
	1000	-3.5	-2.5	-8.0	-5.1	0.001	0.000
FiLM	10	-14.8	-12.7	-50.0	-50.0	0.003	0.006
	100	-7.8	-7.3	-22.3	-21.4	0.000	0.000
	1000	-3.1	-2.4	-5.7	-5.6	0.000	0.000
RN	10	-20.9	-13.6	-50.0	-50.0	0.000	0.000
	100	-10.5	-8.2	-32.1	-32.1	0.000	0.000
	1000	-3.3	-2.8	-4.1	-3.4	0.000	0.000
IEP	10	-13.9	-13.0	-50.0	-50.0	0.001	0.003
	100	-6.9	-6.8	-23.2	-23.2	0.000	0.000
	1000	-2.9	-2.8	-3.2	-3.0	0.000	0.000
TbD	10	-5.3	-5.1	-40.0	-40.0	0.011	0.012
	100	3.8	-2.5	-8.0	-8.0	0.000	0.000
	1000	-1.1	-1.1	-3.6	-3.6	0.000	0.000
Mdetr	10	-6.6	-6.0	-40.0	-40.0	0.018	0.021
	100	-4.9	-3.6	-14.2	-13.3	0.000	0.000
	1000	-1.3	-1.2	-5.4	-5.2	0.000	0.000
State Input Model	10	-8.5	-7.7	-20.0	-20.0	0.020	0.034
	100	-2.3	-2.1	-5.1	-4.3	0.000	0.000
	1000	-1.2	-1.1	- 1.7	-1.7	0.000	0.000

Table 5: Results of the game with the *pixel-input Adversarial Player*.

Model	*Mini-game* size	Average Consistency Drop %	Accuracy Drop %	Maximum Consistency Drop %	Accuracy Drop %	*p*-value Consistency Drop	Accuracy Drop
SAN	10	-12.8	-11.4	-40.0	-40.0	0.008	0.018
	100	-6.4	-3.9	-13.3	-8.0	0.000	0.001
	1000	-2.3	-1.4	-3.4	-1.7	0.000	0.000
FiLM	10	-3.62	-2.6	-10.0	-10.0	0.056	0.154
	100	-1.7	-1.4	-4.4	-3.9	0.000	0.000
	1000	-0.6	-0.4	-1.6	-1.5	0.000	0.000
RN	10	-9.4	-7.2	-30.0	-20.0	0.021	0.065
	100	-3.2	-2.5	-9.8	-6.2	0.000	0.000
	1000	-2.3	-1.7	-2.8	-2.3	0.000	0.000
IEP	10	-2.9	-2.5	-10.0	-10.0	0.111	0.171
	100	-1.5	-1.3	-3.5	-3.5	0.001	0.004
	1000	-0.4	-0.3	-1.3	-1.2	0.000	0.000
TbD	10	0.0	0.0	0.0	0.0	1.000	1.000
	100	-0.6	-0.4	-1.2	-1.1	0.017	0.078
	1000	-0.2	-0.1	-0.3	-0.3	0.000	0.000
Mdetr	10	0.0	0.0	0.0	0.0	1.000	1.000
	100	-1.2	-1.1	-2.0	-1.9	0.002	0.003
	1000	-0.4	-0.3	-0.9	-0.6	0.000	0.000
State Input Model	10	-0.9	-0.8	-5.0	-5.0	0.033	0.038
	100	-0.7	-0.7	-1.8	-1.8	0.031	0.031
	1000	-0.3	-0.3	-1.0	-1.0	0.000	0.000

B APPENDIX B

B.1 MODEL PERFORMANCE ON MAXIMAL DROP MINIGAMES.

In the table below, we present model accuracy on each of the minigames where the maximal drop was observed. The second and third column refer to unmanipulated image-question pair accuracy in the minigame. The fourth and fifth columns refer to the measured model accuracy in those minigames after the *Adversarial Player* manipulation. This indicates that minigames of maximal drop do not necessarily consist of "hard" CLEVR examples, but rather exploit model and instance-specific vulnerabilities of the architecture under test.

Model	*Mini-game* size	Original Data		Manipulated Data	
		Mini-game Accuracy (State)	*Mini-game* Accuracy (Pixel)	*Mini-game* Accuracy (State)	*Mini-game* Accuracy (Pixel)
SAN	10	80.00	80.00	28.84	43.26
	100	74.00	75.00	47.65	66.32
	1000	72.30	72.20	68.42	70.87
FiLM	10	100.0	100.0	48.10	86.58
	100	98.00	100.0	75.61	92.44
	1000	96.40	96.10	90.81	94.75
RN	10	100.0	100.0	46.60	74.56
	100	94.00	95.00	63.28	87.42
	1000	93.10	93.30	90.03	91.05
IEP	10	100.0	100.0	48.45	87.21
	100	98.00	96.00	74.41	93.50
	1000	97.10	97.30	93.99	95.73
TbD	10	100.0	100.0	69.37	99.10
	100	100.0	100.0	91.17	98.00
	1000	99.40	99.70	95.53	98.80
Mdetr	10	100.0	100.0	59.82	99.70
	100	100.0	100.0	86.43	97.80
	1000	99.50	100.0	94.51	99.10
State Input Transf.	10	100.0	100.0	77.44	91.96
	100	97.00	99.00	92.63	95.05
	1000	97.20	96.40	95.15	95.83

B.2 SCENE GENERATION METHOD AND UNINTENDED ISSUES.

In this section we will elaborate more on how we enforce that generated scenes are *visually fair*, in the sense that unintended issues such as object occlusion, or object placement out of field of view are not existent, as well as *answerable* meaning that they can still be answered and the ground truth answer of the posed question before and after the scene manipulations remains the same.

For the generation of new images/scenes we use the open-source Blender Graphics Engine [2] (v2.79b), and the original 3D models of the CLEVR dataset. Scenes suggested by our *Adversarial Player*, are encoded in the form of arguments for Blender, which renders the new images according to those directives. In order to guarantee visual fairness, and question validity, we employ two modules (scene-constraint enforcer / question relevance enforcer), presented briefly - in Section 4 in the Consistency and In-Distribution paragraphs.

The scene-constraint enforcer is responsible for ensuring that the creation of a scene/image that respects all constraints and statistical properties of the original dataset. This piece of code is borrowed

---

[2]Blender - a 3D modelling and rendering package. https://www.blender.org

from the original CLEVR codebase[3] and as in the original CLEVR paper the following constraints are checked (Lines 66-83 in the python code):

1. **Minimum / Maximum Number of Objects:** 3 / 10.

2. **Minimum allowed distance between object centers:** 0.25

3. **Margin along with cardinal directions:** 0.4 (This ensures lack of ambiguity by keeping objects at least 0.4 points of distance apart. This distance is a Blender-specific measure that spans from -3 to +3.)

4. **Min pixels per object:** 200 (This ensures that an object will not be occluded, by requiring at least 200 pixels of it being visible.)

The question-relevance enforcer checks if the newly generated scene is indeed answerable and has the same "ground truth" answer as the old scene. By not enforcing this, every manipulation will be falsely "successful" as the question (which is kept the same before and after the attack) will have a different answer in the newly generated scene.

This is also resolved by using the same question engine module provided by the CLEVR authors in their codebase[4].

This module receives a question and a scene and calculates the ground truth answer based on a set of functional programs that are apriori known and used to generate the questions. (Supplementary Material A in the CLEVR paper (Johnson et al., 2017a))

The full training pipeline should be the following: Our *Adversarial Player* initially receives an input image-question pair. Then, it suggests a new scene, that passes through the scene-constraint enforcer. If the new scene respects all boundaries and constraints it is then evaluated alongside the question by the question-relevance enforcer. If the new ground truth answer to the suggested scene/image is the same as the original answer, the image-question pair is marked as in-distribution and valid. In any other case, it is removed from the training pipeline.

---

[3]`https://github.com/facebookresearch/clevr-dataset-gen/blob/main/image_generation/render_images.py`

[4]`https://github.com/facebookresearch/clevr-dataset-gen/blob/main/question_generation/question_engine.py`

B.3 COMPARISON WITH RANDOMLY SAMPLED EQUIVALENT SCENES.

Arguably, out of the semantically equivalent space of images given a question and an accompanying answer, the *Adversarial Player* player effectively discovers cases for which the model under test can be fooled. This however, does not indicate how rare those examples are, neither the degree of robustness of the model under test against other examples in this space. Given a specific initial image-question pair, a tractable estimate would be the number of manipulated scenes (F) discovered that are able to fool the model, divided by all the possible permutations of available objects (N) in our discrete 7x7 grid. $Rarity = \frac{F}{49^N}, N \in [3, 10]$. A scene of only 3 objects and 1 discovered successful manipulation would make it 0.00085% possible to find it by chance and would indicate 99.9915% robustness against that sphere of equivalent image-question pairs.

Of course not all of those configurations are valid due to scene constraint violations, as well as objects can theoretically move freely on the scene. As a way to approach this question, we compare our *Adversarial Player* player against a random scene generator (RSG). The random scene generator is able to manipulate any object freely, on the constraint that the resulting scene is valid under the scene constraint enforcer as well as the question relevance enforcer. Manipulations of lighting or camera angles, as well as addition or removal of objects is not permitted. In order to reduce the huge rendering times needed for each random search, we allow the RSG to operate on a 10 length *Mini-game* where scene manipulations that cause accuracy drop have been discovered by the *Adversarial Player*. For each image-question pair the RSG has a budget of 5000 queries, and if not successful it proceeds to the next *Mini-game* entry.

Model	CLEVR Accuracy	Adv.Player Accuracy (Drop %)	RSG Accuracy (Drop %)
SAN	72.1	61.86 (-14.2%)	71.59 (-0.7%)
FiLM	96.2	83.98 (-12.7%)	95.81 (-0.4%)
RN	93.2	80.52 (-13.6%)	92.73 (-0.5%)
IEP	96.9	84.30 (-13.0%)	96.70 (-0.2%)
TbD	99.1	94.04 (-5.1%)	99.10 (-0.0%)
MDetr	99.7	93.71 (-6.0%)	99.70 (-0.0%)
ST	96.8	89.34 (-7.7%)	96.50 (-0.3%)

As it can be seen, randomly question-uninformed suggested object placements do not seem to be effective into fooling the models under test. This further supports the argument that models under test theoretically and statistically seem robust, but nevertheless have vulnerabilities that can be effectively exploited by our *Adversarial Player*.

B.4 BEHIND THE SCENES VISUALIZATION OF FAILURE MODES.

Since the models under test are operating under different assumptions and architectural designs, we set up a visualization experiment to analyse visually their inner working mechanisms under a normal and a manipulated scene scenario. Specifically, we choose to visualize:

1. The attention maps of Stack-Attention Networks.
2. The gradients of the pre-ultimate and ultimate convolutional blocks of FiLM.
3. The programs that are synthesized alongside their soft-attention maps of each module block in TbD network.
4. The objects that were detected during the computation steps of a MDetr model.

For each experiment, we choose two image-question pairs. The first consists of the original image and the second of a scene created by our *Adversarial Player* that succesfully fools the model under test.

As we can observe, in Stack-Attention Network the model seems to concentrate all its focus on a single final object in manipulated examples, while in the original ones, the relational jumps required for the answer are still visible on the attention map. The final attention map that is presented is ultimately passed to a fully-connected classifier in order for the final answer to be created. Hence, limited focus to all the necessary objects / locations may create lack of necessary features for the correct answer derivation.

In the case of FiLM model we observe a similar scenario. In the first example, the gradient-weighted activations of the model seem to be focusing on multiple irrelevant objects regarding the final answer, while in the second example the model seems to include the purple cube mistakenly as one of the possible spheres of the image.

In the case of the MDetr model, a specific pattern could not be identified. All objects were correctly classified and the reasoning steps towards the derivation of the answer are presented. This object-detection experiment, strengthens our claim of visually fair scene manipulations that respect the original dataset properties and do not promote object or attribute hindrance.

Finally, in the case of the TbD, in both the original and manipulated scenes the programs that the model generates are exactly the same. This is to no surprise since the program generator module is using exclusively the question as input. Nevertheless, a similar pattern of scattered model focus is presented here as well. The attention maps in both examples are the same between the original and manipulated scenes, in all but the final reasoning step. In the first example the attention is leaked towards the gray cube that has nothing to do with the correct answer, while in the second the attention is spread among many matte objects but peaks near the big yellow ball. This is wrong since the word "other" that exists in the question should drive the model focus exclusively to other objects apart from the starting point of the reasoning chain.

Figure 24: Visualization of attention maps in SAN model on original and manipulated scenes.

Figure 25: Gradient weighted activation visualization of FiLM model's pre-ultimate and ultimate blocks on original and manipulated scenes

Figure 26: Visualization of MDetr model's detection stages on original and manipulated scenes.

Figure 27: Visualization of MDetr model's detection stages on original and manipulated scenes.

Figure 28: Visualization of TbD model's program generation and attention map visualization on original and manipulated scenes

B.5 Human-in-the-loop Experiment

Would a human be fooled from scene manipulations of this kind? The perceptual abilities of human observers have been previously measured (92.6%) on this dataset, however human robustness is a totally different question. In our experiment, a human observer is presented with a set of 2 images and a question. Then the observer is required to answer to each image image question pair: (Image Before - Question / Image After - Question), and report whether the answer has changed or remained the same. Participants were first made familiar with the concepts of the CLEVR dataset (colors/shapes/materials/sizes) and then were left unsupervised to answer a set of 20 such examples. Each contained 1 CLEVR question and 2 CLEVR scenes, before and after the *Adversarial Player* manipulations. Half of those scenes successfully fooled models and half of those did not. An example of what a survey question looks like is given below: Here is the confusion matrix from the

Figure 29: Questionnaire example

survey results:

Figure 30: Confusion Matrix of Results

As we can see, our human observers exhibit 91% precision in identifying cases where scene manipulations are not causing change to the questions answer, and 95% precision in identifying cases where the manipulations do cause a change. While this small scale experiment may not reflect a universal truth about human robustness in VQA scenarios, it is a suggestion that human observation is still reliable.

B.6 OBJECT DETECTION EXPERIMENT

As an extra step towards quantitatively testing if the adversarial manipulations make the image indeed visually ambiguous, we decided to used a pre-trained CLEVR object detector to measure the difference in performance between original and manipulated images. Theoretically if the objects before and after the manipulations remain detected by the model, as well as their attributes remain correctly classified, that would signify that our *Adversarial Player* manipulations do not cause any situation that would hinder the identification of an object.

For this experiment, we used Slot Attention Locatello (2020) with pre-trained weights. It is an unsupervised method for object discovery that achieves almost perfect performance on CLEVR. We were not able to find a pair of images in which an object that was identified initially was not after the manipulations. The same findings stood for the object identification part, since not a pair of initially classified object was misclassified after the manipulations. That concludes that our *Adversarial Player* manipulations do not cause any specific visual obstacle for an object to be correctly identified.

Figure 31: Visualization of Slot Attention model's detection results

Figure 32: Visualization of Slot Attention model's detection results