Towards Defending Multiple Adversarial Perturbations via Gated Batch Normalization

Abstract

There is now extensive evidence demonstrating that deep neural networks are vulnerable to adversarial examples, motivating the development of defenses against adversarial attacks. However, existing adversarial defenses typically improve model robustness against individual specific perturbation types. Some recent methods improve model robustness against adversarial attacks in multiple ℓ_p balls, but their performance against each perturbation type is still far from satisfactory. To better understand this phenomenon, we propose the *multi-domain* hypothesis, stating that different types of adversarial perturbations are drawn from different domains. Guided by the multi-domain hypothesis, we propose *Gated Batch Normalization (GBN)*, a novel building block for deep neural networks that improves robustness against multiple perturbation types. GBN consists of a gated subnetwork and a multi-branch batch normalization (BN) layer, where the gated subnetwork separates different perturbation types, and each BN branch is in charge of a single perturbation type and learns domain-specific statistics for input transformation. Then, features from different branches are aligned as domain-invariant representations for the subsequent layers. We perform extensive evaluations of our approach on MNIST, CIFAR-10, and Tiny-ImageNet, and demonstrate that GBN outperforms previous defense proposals against multiple perturbation types, *i.e.*, ℓ_1, ℓ_2, and ℓ_∞ perturbations, by large margins of 10-20%.[1]

1 Introduction

Deep neural networks (DNNs) have achieved remarkable performance across a wide areas of applications (Krizhevsky et al., 2012; Bahdanau et al., 2014; Hinton et al., 2012), but they are susceptible to *adversarial examples* (Szegedy et al., 2013). These elaborately designed perturbations are imperceptible to humans but can easily lead DNNs to wrong predictions, threatening both digital and physical deep learning applications (Kurakin et al., 2016; Liu et al., 2019a).

To improve model robustness against adversarial perturbations, a number of *adversarial defense* methods have been proposed (Papernot et al., 2015; Engstrom et al., 2018; Goodfellow et al., 2014). Many of these defense methods are based on adversarial training (Goodfellow et al., 2014; Madry et al., 2018), which augment training data with adversarial examples. However, most adversarial defenses are designed to counteract a single type of perturbation (*e.g.*, small ℓ_∞-noise) (Madry et al., 2018; Alexey et al., 2017; Dong et al., 2018). These defenses offer no guarantees for other perturbations (*e.g.*, ℓ_1, ℓ_2), and sometimes even increase model vulnerability (Kang et al., 2019; Tramèr & Boneh, 2019). To address this problem, other adversarial training strategies have been proposed with the goal of simultaneously achieving robustness against multiple types of attacks, *i.e.*, ℓ_∞, ℓ_1, and ℓ_2 attacks (Tramèr & Boneh, 2019; Pratyush et al., 2020). Although these methods improve overall model robustness against adversarial attacks in multiple ℓ_p balls, the performance for each individual perturbation type is still far from satisfactory.

In this work, we propose the multi-domain hypothesis, which states that different types of adversarial perturbation arise in different domains, and thus have separable characteristics. Training on data from multiple domains can be regarded as solving the invariant risk minimization problem (Ahuja et al., 2020), in which an invariant predictor is learnt to achieve the minimum risk for different environments. For a deep learning model, instance-related knowledge can be stored in the weight matrix

---

[1]Our code will be available upon publication.

of each layer, whereas domain-related knowledge can be represented by the batch normalization (BN) layer statistics (Li et al., 2017).

Inspired by the multi-domain hypothesis, we propose to improve model robustness against multiple perturbation types by separating domain-specific information for different perturbation types, and using BN layer statistics to better align data from the mixture distribution and learn domain-invariant representations for multiple adversarial examples types. In particular, we propose a novel building block for DNNs, referred to as *Gated Batch Normalization* (GBN), which consists of a gated sub-network and a multi-branch BN layer. GBN first learns to separate perturbations from different domains on-the-fly and then normalizes them by obtaining domain-specific features. Specifically, each BN branch handles a single perturbation type (*i.e.*, domain). Then, features computed from different branches are aligned as domain-invariant representations that are aggregated as the input to subsequent layers. Extensive experiments on MNIST, CIFAR-10, and Tiny-ImageNet demonstrate that our method outperforms previous defense strategies by large margins, *i.e.*, 10-20%.

2 BACKGROUND AND RELATED WORK

In this section, we provide a brief overview of existing work on adversarial attacks and defenses, as well as batch normalization techniques.

2.1 ADVERSARIAL ATTACKS AND DEFENSES

Adversarial examples are inputs intentionally designed to mislead DNNs (Szegedy et al., 2013; Goodfellow et al., 2014). Given a DNN f_Θ and an input image $\mathbf{x} \in \mathbb{X}$ with the ground truth label $\mathbf{y} \in \mathbb{Y}$, an adversarial example $\mathbf{x}_{adv}$ satisfies

$$f_\Theta(\mathbf{x}_{adv}) \neq \mathbf{y} \quad s.t. \quad \|\mathbf{x} - \mathbf{x}_{adv}\| \leq \epsilon,$$

where $\| \cdot \|$ is a distance metric. Commonly, $\| \cdot \|$ is measured by the ℓ_p-norm ($p \in \{1,2,\infty\}$).

Various defense approaches have been proposed to improve model robustness against adversarial examples (Papernot et al., 2015; Xie et al., 2018; Madry et al., 2018; Liao et al., 2018; Cisse et al., 2017), among which adversarial training has been widely studied and demonstrated to be the most effective (Goodfellow et al., 2014; Madry et al., 2018). Specifically, adversarial training minimizes the worst case loss within some perturbation region for classifiers, by augmenting the training set $\{\mathbf{x}^{(i)}, \mathbf{y}^{(i)}\}_{i=1...n}$ with adversarial examples. However, these defenses only improve model robustness for one type of perturbation (*e.g.*, ℓ_∞) and typically offer no robustness guarantees against other attacks (Kang et al., 2019; Tramèr & Boneh, 2019; Schott et al., 2019).

To address this problem, recent works have attempted to improve the robustness against several types of perturbation (Schott et al., 2019; Tramèr & Boneh, 2019; Pratyush et al., 2020). Schott et al. (2019) proposed Analysis by Synthesis (ABS), which used multiple variational autoencoders to defend ℓ_0, ℓ_2, and ℓ_∞ adversaries. However, ABS only works on the MNIST dataset. Croce & Hein (2020a) proposed a provable adversarial defense against all ℓ_p norms for $p \geq 1$ using a regularization term. However, it is not applicable to the empirical setting, since it only guarantees robustness for very small perturbations (*e.g.*, 0.1 and 2/255 for ℓ_2 and ℓ_∞ on CIFAR-10). Tramèr & Boneh (2019) tried to defend against multiple perturbation types (ℓ_1, ℓ_2, and ℓ_∞) by combining different types of adversarial examples for adversarial training. Specifically, they introduced two training strategies, "MAX" and "AVG", where for each input image, the model is either trained on its strongest adversarial example or all types of perturbations. More recently, Pratyush et al. (2020) proposed multi steepest descent (MSD), and showed that a simple modification to standard PGD adversarial training improves robustness to ℓ_1, ℓ_2, and ℓ_∞ adversaries. In this work, we follow (Tramèr & Boneh, 2019; Pratyush et al., 2020) to focus on defense against ℓ_1, ℓ_2, and ℓ_∞ adversarial perturbations, which are the most representative and commonly used perturbations. However, we propose a completely different perspective and solution to the problem.

2.2 BATCH NORMALIZATION

BN (Ioffe & Szegedy, 2015) is typically used to stabilize and accelerate DNN training. Let $\mathbf{x} \in \mathbb{R}^d$ denote the input to a neural network layer. During training, BN normalizes each neuron/channel

within m mini-batch data by

$$\hat{\mathbf{x}}_j = BN(\mathbf{x}_j) = \gamma_j \frac{\mathbf{x}_j - \mu_j}{\sqrt{\sigma_j^2 + \xi}} + \beta_j, \;\; j = 1, 2, ..., d, \tag{1}$$

where $\mu_j = \frac{1}{m} \sum_{i=1}^{m} \mathbf{x}_j^{(i)}$ and $\sigma_j^2 = \frac{1}{m} \sum_{i=1}^{m} (\mathbf{x}_j^{(i)} - \mu_j)^2$ are the mini-batch mean and variance for each neuron, respectively, and ξ is a small number to prevent numerical instability. The learnable parameters γ and β are used to recover the representation capacity. During inference, the population statistics of mean $\hat{\mu}$ and variance $\hat{\sigma}^2$ are used in Eqn. 1, which are usually calculated as the running average over different training iterations t with update factor α:

$$\hat{\mu}^t = (1 - \alpha)\hat{\mu}^{t-1} + \alpha\mu^{t-1}, \;\; (\hat{\sigma}^t)^2 = (1 - \alpha)(\hat{\sigma}^{t-1})^2 + \alpha(\sigma^{t-1})^2. \tag{2}$$

A number of normalization techniques have been proposed to improve BN for style-transfer (Huang & Belongie, 2017) and domain adaption (Li et al., 2017; Chang et al., 2019; Lucas et al., 2019). Compared to studies for domain adaptation, our GBN does not require input domain knowledge during inference. In contrast to Mode Normalization (Lucas et al., 2019), which aims to learn a mixture distribution for multi-task learning, GBN separates domain-specific statistics for different input types and then aligns the data to build domain-invariant representations. Recently, Xie & Yuille (2020); Xie et al. (2020) applied separate BNs to clean and adversarial examples for statistics estimation. In contrast to the above two studies that improve image recognition or analyze the properties of BN to adversarial training, we aim to defend against multiple adversarial perturbations. Furthermore, GBN can predict the domain for an input sample and then jointly incorporate the outputs of multiple BN branches to provide the final classification result. Conversely, Xie & Yuille (2020); Xie et al. (2020) manually selected the BN branch for each input image, which requires prior knowledge of whether the input is an adversarial or clean example (the same as domain adaptation).

3 GATED BATCH NORMALIZATION

In this section, we present our proposed Gated Batch Normalization (GBN) approach, to improve the model robustness against multiple adversarial perturbations. We first illustrate our multi-domain hypothesis, which states that adversarial examples of different perturbation types are drawn from different domains. Motivated by this hypothesis, we demonstrate the architecture of our GBN block, then describe the training and inference procedures.

3.1 MOTIVATION: MULTI-DOMAIN HYPOTHESIS

We assume N *adversarial perturbation types*[2], each characterized by a set $\mathbb{S}^k$ of perturbations for an input $\mathbf{x}$. Let $\mathbb{D}^0$ denote the set of clean examples, and $\mathbb{D}^k(k = 1, ..., N)$ denote the set of adversarial examples generated by the k-th adversarial perturbation type $\mathbb{S}^k$. An adversarial example of the k-th type $\mathbf{x}_{adv}^k$ is generated by the pixel-wise addition of the perturbation δ^k, *i.e.*, $\mathbf{x}_{adv}^k = \mathbf{x} + \delta^k$. Our *multi-domain hypothesis* states that different types of perturbations $\mathbb{D}^k$ (for all $k \geq 0$, including the clean examples) are drawn from different domains, inspired by the following observations:

(1) Training on a single perturbation type is insufficient for achieving the robustness against other perturbations. Further, training on a mixture of different perturbation types still fail to achieve acceptable performance for each type of perturbation (Tramèr & Boneh, 2019; Pratyush et al., 2020).

(2) Adversarial examples are separable from clean examples (Metzen et al., 2018). Xie & Yuille (2020) also suggested that clean and adversarial examples are drawn from two different domains.

To formally validate our hypothesis, we first theoretically demonstrate that for a linear classifier $f(\mathbf{x}) = sign(w^T\mathbf{x} + b)$, different types of adversarial perturbations belong to different domains, with pair-wise Wasserstein distances greater than 0. Specifically, in Appendix B, we prove that $W_2(\mathbb{D}_\mathbf{y}^{\ell_1}, \mathbb{D}_\mathbf{y}^{\ell_\infty}) = \epsilon\sqrt{d-1}, W_2(\mathbb{D}_\mathbf{y}^{\ell_1}, \mathbb{D}_\mathbf{y}^{\ell_2}) = \epsilon\sqrt{2 - 2|w_i|/||w||_2}$, and $W_2(\mathbb{D}_\mathbf{y}^{\ell_2}, \mathbb{D}_\mathbf{y}^{\ell_\infty}) = \epsilon\sqrt{d + 1 - 2||w||_1/||w||_2}$ where $W_2(\cdot, \cdot)$ is the Wasserstein distance, $i = \arg\max_j |w_j|$ and $\mathbb{D}_\mathbf{y}^k$ represents the conditional distribution of $\mathbb{D}^k$ given any label $\mathbf{y} \in \mathbb{Y}$ ($\mathbb{D}^{\ell_1}$, $\mathbb{D}^{\ell_2}$, and $\mathbb{D}^{\ell_\infty}$ denote the domain of ℓ_1, ℓ_2, and ℓ_∞, respectively).

---

[2]In this work, we consider $N = 3$ adversarial perturbation types: ℓ_1, ℓ_2 and ℓ_∞.

Further, we empirically investigate the hypothesis for deep neural networks. Specifically, we train separate BNs for different input domains $\mathbb{D}^k (k \geq 0)$. As illustrated in Figure 1(b), we construct separate mini-batches to estimate BN statistics for different $\mathbb{D}^k$, *i.e.*, ℓ_1, ℓ_2, and ℓ_∞ adversarial images, as well as for clean images. We defer the implementation details to Appendix A. Figure 1(c) and 1(d) show that different $\mathbb{D}^k$ induce significantly different running statistics, according to the running means and variances of different BN branches.

These theoretical and empirical results support our multi-domain hypothesis, and motivate our design of GBN, as discussed below.

(a) standard BN   (b) multiple BN branches

(c) running mean   (d) running variance

Figure 1: (a) the standard BN structure; (b) the structure with 4 BN branches, which construct different mini-batches for different $\mathbb{D}^k$ to estimate the normalization statistics; (c) and (d): running means and variances of multiple BN branches on 16 randomly sampled channels in a VGG-16's $conv2\_1$ layer, showing that different perturbation types induce different normalization statistics.

3.2 MODEL ARCHITECTURE WITH GATED BATCH NORMALIZATION (GBN)

Training a model that generalizes well on multiple domains can be regarded as solving an invariant risk minimization problem (Ahuja et al., 2020). Define a predictor $f : \mathbb{X} \to \mathbb{Y}$ and the risk achieved by f in domain $\mathbb{D}^k$ as $R_k(f) = \sum_{(\mathbf{x},\mathbf{y}) \sim \mathbb{D}^k} \ell(f(\mathbf{x}),\mathbf{y})$, where $\ell(\cdot)$ is the cross entropy loss. We say that a data representation $\pi: \mathbb{X} \to \mathbb{Z}$ elicits an invariant predictor $\omega \circ \pi$ across all domains $k \in \{0, 1, \cdots, N\}$ if there is a classifier $\omega: \mathbb{Z} \to \mathbb{Y}$ that achieves the minimum risk for all domains.

To obtain a domain-invariant representation π, we use the BN layer statistics to align data from the mixture distribution. Specifically, GBN uses a BN layer with multiple branches $\Psi = \{BN^k(\cdot), k = 0, ..., N\}$ during training, where each branch $BN^k(\cdot)$ is exclusively in charge of domain $\mathbb{D}^k$. The aligned data are then aggregated as the input to subsequent layers to train a classifier ω which achieves the minimum risk across different domains (*i.e.*, model robust to different perturbations).

One remaining problem is that the model does not know the input domain during inference. To calculate the normalized output in this case, GBN utilizes a gated sub-network $\Phi_\theta(\mathbf{x})$ to predict the domain for each layer input $\mathbf{x}$; we will illustrate how to train $\Phi_\theta(\mathbf{x})$ in Section 3.3. Given the output

of sub-network $\mathbf{g} = \Phi_\theta(\mathbf{x}) \in \mathbb{R}^{N+1}$, we calculate the normalized output in a soft-gated way:

$$\hat{\mathbf{x}} = GBN(\mathbf{x}) = \sum_{k=0}^{N} \mathbf{g}_k \hat{\mathbf{x}}^k, \tag{3}$$

where $\mathbf{g}_k$ represents the confidence of the k-th domain for $\mathbf{x}$, and $\hat{\mathbf{x}}^k$ is the normalized output of $BN^k(\cdot)$, which uses the population statistics of the domain $\mathbb{D}^k$ to perform standardization.

We provide an overview of the inference procedure in Figure 2(b), and the details are presented in Algorithm 1. In Appendix E.5, we discussed an alternative approach that takes the top-1 prediction of $\mathbf{g}$ (the hard label), and it achieved comparable performance.

Our GBN aims to disentangle domain-invariant features and domain-specific features: (1) the distributions in different domains are aligned by their normalized outputs (all are standardized distributions), which ensures that the following linear layers learn domain-invariant representations; and (2) the domain-specific features for each domain $\mathbb{D}^k$ are obtained by the population statistics $\{\hat{\mu}^k, \hat{\sigma}^k\}$ of its corresponding BN branch $BN^k(\cdot)$. We show empirically that $\{\hat{\mu}^k, \hat{\sigma}^k\}$ of $BN^k(\cdot)$ learns the domain-specific representation well, as shown in Figure 1.

Algorithm 1 Inference of Gated Batch Normalization (GBN)

Input: Layer input $\mathbf{x}$
Output: Normalized output by GBN

1: Compute the output of gated sub-network $\mathbf{g} = \Phi_\theta(\mathbf{x})$
2: **for** k in N+1 domains **do**
3:     Let $\mathbf{x}$ go through $BN^k(\cdot)$ and obtain the normalized output $\hat{\mathbf{x}}^k$ based on Eqn. 1.
4: **end for**
5: Compute GBN output based on Eqn. 3.

(a) Training of GBN   (b) Inference of GBN

Figure 2: The training and inference procedures of GBN. During training, samples from different domains (denoted by different colors) are fed into corresponding BN branches to update the running statistics. During inference, given mini-batch data, the gated sub-network first predicts the domain of input $\mathbf{x}$ and then jointly normalizes it using multiple BN branches.

3.3 TRAINING

We provide an overview of the training procedure in Figure 2(a), and the details are in Algorithm 2. Specifically, for each mini-batch $\mathcal{B}^0$ consisting of clean samples, we use PGD attack (Madry et al., 2018) to generate batches of adversarial examples $\mathcal{B}^k$ ($k \in \{1, ..., N\}$) for each domain $\mathbb{D}^k$. To capture the domain-specific statistics for different perturbation types, given mini-batch data $\mathcal{B}^k$ from

domain $\mathbb{D}^k$, we ensure that $\mathcal{B}^k$ goes through its corresponding BN branch $BN^k(\cdot)$, and we use Eqn. 1 to compute the normalized output $\widehat{\mathcal{B}}^k$. The population statistics $\{\hat{\mu}^k, \hat{\sigma}^k\}$ of $BN^k(\cdot)$ are updated based on Eqn. 2. In other words, we disentangle the mixture distribution for normalization and apply separate BN branches to different perturbation types for statistics estimation.

To train the gated sub-network $\mathbf{g}$, we provide the supervision of the input domain for each training sample. Specifically, we introduce the domain prediction loss $\mathcal{L}_{DP}$:

$$\mathcal{L}_{DP} = \sum_{k=0}^{N} \sum_{(\mathbf{x},k) \in \mathbb{D}^k} \ell(\Phi_\theta(\mathbf{x}), k). \tag{4}$$

Finally, we optimize the parameters Θ of the entire neural network (*e.g.*, the weight matrices of the convolutional layers, except for the gated sub-network) using the classification loss $\mathcal{L}_{cls}$:

$$\mathcal{L}_{cls} = \sum_{k=0}^{N} \sum_{(\mathbf{x},\mathbf{y}) \in \mathbb{D}^k} \ell(f_\Theta(\mathbf{x}; BN^k(\cdot)), \mathbf{y}), \tag{5}$$

Computational cost. With respect to the parameters, we have $N{+}1$ pairs of $\{\hat{\mu}, \hat{\sigma}\}$ to estimate compared to one in standard BN. With respect to the time consumption, in the adversarial learning literature, the most time-consuming procedure in adversarial training is generating adversarial examples. Although we introduce more parameters, our time cost is close to other adversarial defensive baselines (see Appendix E.2 for more details).

Algorithm 2 Training of Gated Batch Normalization (GBN) for Each Iteration.

Input: Network f with GBN
Output: Robust model parameters Θ and θ

1: Given mini-batch data $\mathcal{B}^0$, generate corresponding adversarial example batch $\mathcal{B}^k$ ($k \in \{1, ..., N\}$) with specific perturbation type by PGD attacks
2: **for** k in $N{+}1$ domains **do**
3:     Let $\mathcal{B}^k$ go through $BN^k(\cdot)$ at each layer to obtain normalized outputs $\widehat{\mathcal{B}}^k$ based on Eqn. 1.
4:     Update the population statistics $\{\hat{\mu}^k, \hat{\sigma}^k\}$ of $BN^k(\cdot)$ at each layer based on Eqn. 2.
5: **end for**
6: Update parameters θ of the gated sub-network at each layer based on Eqn. 4.
7: Update parameters Θ of the whole network based on Eqn. 5.

---

4 EXPERIMENTS

We evaluate the effectiveness of our GBN block to simultaneously achieve robustness against ℓ_1, ℓ_2, and ℓ_∞ perturbations, which are the most representative and commonly used adversarial perturbation. We conduct experiments on the image classification benchmarks MNIST (LeCun, 1998), CIFAR-10 (Krizhevsky & Hinton, 2009), and Tiny-ImageNet (Wu et al., 2017).

4.1 EXPERIMENT SETUP

Architecture and hyperparameters. We use LeNet architecture (LeCun et al., 1998) for MNIST; ResNet-20 (He et al., 2016) for CIFAR-10; and ResNet-34 (He et al., 2016) for Tiny-ImageNet. For fair comparisons, we keep the architecture and main hyper-parameters the same for GBN and other baselines. A detailed description of the hyper-parameters can be found in Appendix D.

Adversarial attacks. To evaluate the model robustness, we follow existing guidelines (Schott et al., 2019; Tramèr & Boneh, 2019; Pratyush et al., 2020) and incorporate multiple adversarial attacks for different perturbation types. For MNIST, the magnitude of perturbation for ℓ_1, ℓ_2, and ℓ_∞ is $\epsilon = 10$, 2, 0.3. For CIFAR-10 and Tiny-ImageNet, the magnitude of perturbation for ℓ_1, ℓ_2, and ℓ_∞ is $\epsilon = 12$, 0.5, 0.03. We use FoolBox (Rauber et al., 2017) as the implementation for the attacks. We also

adopt the recently proposed AutoAttack (Croce & Hein, 2020b), which is a very strong ensemble of parameter-free attacks. We adopt both the white-box and the black-box or gradient-free adversarial attacks. A complete details of all attacks can be found in Appendix D.1.

Adversarial defenses. We compare with works that aim to achieve robustness against multiple perturbation types. All of them consider the union of ℓ_1, ℓ_2, ℓ_∞ adversaries.[3] We compare with ABS (Schott et al., 2019), MAX, AVG (Tramèr & Boneh, 2019), and MSD (Pratyush et al., 2020).

Normalization techniques. We further compare our methods to some normalization techniques (*i.e.*, MN (Lucas et al., 2019) and MBN (Xie & Yuille, 2020)). MN extends BN to more than a single mean and variance, detects the modes of the data, and then normalize samples that share common features. For MBN, since manually selecting the BN branch is infeasible in the adversarial setting, we add a 2-way gated sub-network to each MBN block.

4.2 Adversarial Robustness for multiple perturbations

In this section, we evaluate model robustness against multiple perturbation types (*i.e.*, ℓ_1, ℓ_2, and ℓ_∞) in both the white-box and black-box setting. We use the *worst case* top-1 classification accuracy, where we report the worst result among various attacks for each perturbation type.

The results on MNIST using LeNet, CIFAR-10 using ResNet-20, and Tiny-ImageNet using ResNet-34 are shown in Table 1. We present the detailed breakdown results for individual attacks in Appendix E.3. We observe that: (1) on multiple perturbation types (*i.e.*, ℓ_1, ℓ_2, ℓ_∞), our GBN consistently outperforms the baselines by large margins of over 10% on all three datasets; (2) due to the trade-off between adversarial robustness and standard accuracy (Tsipras et al., 2019), our clean accuracy is lower than the vanilla model. However, GBN maintains a comparatively high clean accuracy compared to other adversarial defenses; and (3) GBN is easy to train on different datasets, while the other methods (*e.g.*, MSD) are difficult to converge on large datasets such as Tiny-ImageNet.

Comparison with other normalization techniques. As shown in Table 1, GBN outperforms MN and MBN by large margins. As for the modified MBN, the data from different perturbations are mixed in the same BN. MN aims to learn a mixture distribution for different domains. By contrast, GBN is trained to separate domain-specific features and then align the data from different input domains to build domain-invariant representations. The results further confirm our multi-domain hypothesis.

4.3 Ablation Study

Attacks outside the perturbation model. To examine whether GBN could generalize to perturbation types that the model was not trained on, we trained a variant of GBN models that only includes 3 BN branches. Specifically, these GBN models are trained on two ℓ_p perturbation types only, but are evaluated on all the three ℓ_p perturbations, including the held-out perturbation that is not trained. Unsurprisingly, compared to the full GBN model with 4 BN branches, the robustness of the held-out perturbation type decreases to some degree. However, the robustness is still significantly better than the vanilla model, and sometimes even outperforms other baseline defenses that are trained on all perturbation types (*c.f.* Appendix E.6).

Adding GBN into different layers. The proposed GBN block can be inserted at any layer in a deep network. In this part, we study GBN by single-layer and layer-group studies. We first add GBN to different single layers: as shown in Figure 3(a), the standard performance and adversarial robustness decrease as we add GBN into the deeper layers; we then add GBN to layer groups (*i.e.*, top-m layers): according to the results in Figure 3(b), the adversarial robustness improves (but the clean accuracy remains comparatively stable) as more layers are involved. In summary, adding GBN into shallow layers achieves better performance with respect to both clean and adversarial accuracy. The reasons for this might be two-fold: (1) as shown in (Liu et al., 2019b), shallow layers are more critical to model robustness, while conversely deeper layers are somewhat less important; and (2) as the layer depth increases, the features from different domains are highly entangled and mixed, making it harder for models to separate them (*c.f.* Appendix E.8.).

---

[3]Schott et al. (2019) consider the ℓ_0 perturbations, which is subsumed within the ℓ_1 ball of the same radius.

Table 1: Model robustness on different datasets (the higher the better).

(a) LeNet on MNIST

	Vanilla	AVG	MAX	ABS	MSD	MN	MBN	GBN(ours)
ℓ_1 attacks	5.2%	30.9%	31.8%	/	41.9%	24.2%	60.9%	**73.2%**
ℓ_2 attacks	1.4%	60.2%	59.0%	83.0%	71.4%	18.9%	65.1%	**93.2%**
ℓ_∞ attacks	0.0%	45.8%	58.8%	17.0%	38.9%	0.0%	19.2%	**69.1%**
All attacks	0.0%	29.7%	31.2%	17.0%	38.9%	0.0%	19.2%	**68.9%**
Clean accuracy	**99.3%**	98.7%	98.2%	99.0%	97.3%	98.1%	98.7%	98.7%

(b) ResNet-20 on CIFAR-10

	Vanilla	AVG	MAX	MSD	MN	MBN	GBN(ours)
ℓ_1 attacks	0.0%	44.9%	33.3%	43.7%	39.8%	44.9%	**57.7%**
ℓ_2 attacks	0.0%	59.1%	56.0%	58.9%	30.0%	20.8%	**68.9%**
ℓ_∞ attacks	0.0%	29.2%	25.1%	38.0%	13.2%	40.1%	**49.9%**
All attacks	0.0%	28.2%	24.9%	37.9%	13.0%	20.7%	**48.7%**
Clean accuracy	**89.7%**	80.6%	77.0%	79.1%	82.3%	79.4%	80.7%

(c) ResNet-34 on Tiny-ImageNet

	Vanilla	AVG	MAX	MSD	MN	MBN	GBN(ours)
ℓ_1 attacks	5.8%	27.3%	17.0%	7.6%	8.6%	36.6%	**44.2%**
ℓ_2 attacks	10.3%	29.1%	24.2%	11.0%	17.9%	31.1%	**42.1%**
ℓ_∞ attacks	0.0%	4.5%	2.7%	5.1%	6.8%	19.4%	**38.7%**
All attacks	0.0%	4.6%	2.2%	5.0%	6.7%	20.0%	**38.9%**
Clean accuracy	**54.2%**	41.6%	36.3%	28.8%	46.7%	45.7%	43.4%

(a) single layer

(b) top-m layers

Figure 3: (a) demonstrates the results of adding GBN to different single layers. (b) shows the results of adding GBN to top-m layers. All the experiments are conducted using a VGG-16 on CIFAR-10.

5 CONCLUSIONS

Most adversarial defenses are typically tailored to a single perturbation type (*e.g.*, small ℓ_∞-noise), but offer no guarantees against other attacks. To better understand this phenomenon, we explored the *multi-domain* hypothesis that different types of adversarial perturbations are drawn from different domains. Guided by this hypothesis, we propose a novel building block for DNNs, *Gated Batch Normalization* (GBN), which consists of a gated network and a multi-branches BN layer. The gated sub-network separates different perturbation types, and each BN branch is in charge of a single perturbation type and learns the domain-specific statistics for input transformation. Then, features from different branches are aligned as domain-invariant representations for the subsequent layers. Extensive experiments on MNIST, CIFAR-10, and Tiny-ImageNet demonstrate that our method outperforms previous proposals against multiple perturbation types by large margins of 10-20%.

REFERENCES

Kartik Ahuja, Karthikeyan Shanmugam, Kush Varshney, and Amit Dhurandhar. Invariant risk minimization games. In *International Conference on Machine Learning*, 2020.

Kurakin Alexey, Goodfellow Ian, and Bengio Samy. Adversarial machine learning at scale. In *International Conference on Learning Representations*, 2017.

Maksym Andriushchenko, Francesco Croce, Nicolas Flammarion, and Matthias Hein. Square attack: a query-efficient black-box adversarial attack via random search. In *European Conference on Computer Vision*, 2020.

Dzmitry Bahdanau, Kyunghyun Cho, and Yoshua Bengio. Neural machine translation by jointly learning to align and translate. *arXiv preprint arXiv:1409.0473*, 2014.

Wieland Brendel, Jonas Rauber, and Matthias Bethge. Decision-based adversarial attacks: Reliable attacks against black-box machine learning models. In *International Conference on Learning Representations*, 2018.

Wieland Brendel, Jonas Rauber, Matthias Kümmerer, Ivan Ustyuzhaninov, and Matthias Bethge. Accurate, reliable and fast robustness evaluation. In *Advances in Neural Information Processing Systems*, 2019.

Nicholas Carlini and David Wagner. Towards evaluating the robustness of neural networks. In *IEEE Symposium on Security and Privacy*, 2017.

Woong-Gi Chang, Tackgeun You, Seonguk Seo, Suha Kwak, and Bohyung Han. Domain-specific batch normalization for unsupervised domain adaptation. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2019.

Moustapha Cisse, Piotr Bojanowski, Edouard Grave, Yann Dauphin, and Nicolas Usunier. Parseval networks: Improving robustness to adversarial examples. In *International Conference on Machine Learning*, 2017.

Francesco Croce and Matthias Hein. Provable robustness against all adversarial l_p-perturbations for $p \geq 1$. In *International Conference on Learning Representations*, 2020a.

Francesco Croce and Matthias Hein. Reliable evaluation of adversarial robustness with an ensemble of diverse parameter-free attacks. In *International Conference on Machine Learning*, 2020b.

Francesco Croce and Matthias Hein. Minimally distorted adversarial examples with a fast adaptive boundary attack. In *International Conference on Machine Learning*, 2020c.

Yinpeng Dong, Fangzhou Liao, Tianyu Pang, and Hang Su. Boosting adversarial attacks with momentum. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2018.

Logan Engstrom, Andrew Ilyas, and Anish Athalye. Evaluating and understanding the robustness of adversarial logit pairing. *arXiv preprint arXiv:1807.10272*, 2018.

Ian J Goodfellow, Jonathon Shlens, and Christian Szegedy. Explaining and harnessing adversarial examples (2014). *arXiv preprint arXiv:1412.6572*, 2014.

Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2016.

Geoffrey Hinton, Li Deng, Dong Yu, George E. Dahl, Abdelrahman Mohamed, Navdeep Jaitly, Andrew Senior, Vincent Vanhoucke, Patrick Nguyen, and Tara N. Sainath. Deep neural networks for acoustic modeling in speech recognition: The shared views of four research groups. *IEEE Signal Processing Magazine*, 2012.

Xun Huang and Serge Belongie. Arbitrary style transfer in real-time with adaptive instance normalization. In *IEEE International Conference on Computer Vision*, 2017.

Sergey Ioffe and Christian Szegedy. Batch normalization: Accelerating deep network training by reducing internal covariate shift. In *International Conference on Machine Learning*, 2015.

Daniel Kang, Yi Sun, Dan Hendrycks, Tom Brown, and Jacob Steinhardt. Testing robustness against unforeseen adversaries. *arXiv preprint arXiv:1908.08016*, 2019.

Alex Krizhevsky and Geoffrey Hinton. Learning multiple layers of features from tiny images. Technical report, Citeseer, 2009.

Alex Krizhevsky, Ilya Sutskever, and Geoffrey E. Hinton. Imagenet classification with deep convolutional neural networks. In *International Conference on Neural Information Processing Systems*, 2012.

Alexey Kurakin, Ian Goodfellow, and Samy Bengio. Adversarial examples in the physical world. *arXiv preprint arXiv:1607.02533*, 2016.

Yann LeCun. The mnist database of handwritten digits. *http://yann. lecun. com/exdb/mnist/*, 1998.

Yann LeCun, Léon Bottou, Yoshua Bengio, and Patrick Haffner. Gradient-based learning applied to document recognition. *Proceedings of the IEEE*, 1998.

Yandong Li, Lijun Li, Liqiang Wang, Tong Zhang, and Boqing Gong. Nattack: Learning the distributions of adversarial examples for an improved black-box attack on deep neural networks. In *International Conference on Machine Learning*, 2019.

Yanghao Li, Naiyan Wang, Jianping Shi, Jiaying Liu, and Xiaodi Hou. Revisiting batch normalization for practical domain adaptation. In *International Conference on Learning Representations*, 2017.

Fangzhou Liao, Ming Liang, Yinpeng Dong, Tianyu Pang, Xiaolin Hu, and Jun Zhu. Defense against adversarial attacks using high-level representation guided denoiser. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2018.

Aishan Liu, Xianglong Liu, Jiaxin Fan, Yuqing Ma, Anlan Zhang, Huiyuan Xie, and Dacheng Tao. Perceptual-sensitive gan for generating adversarial patches. In *33rd AAAI Conference on Artificial Intelligence*, 2019a.

Aishan Liu, Xianglong Liu, Chongzhi Zhang, Hang Yu, Qiang Liu, and Junfeng He. Training robust deep neural networks via adversarial noise propagation. *arXiv preprint arXiv:1909.09034*, 2019b.

Deecke Lucas, Murray Iain, and Bilen Hakan. Mode normalization. In *International Conference on Learning Representations*, 2019.

Aleksander Madry, Aleksandar Makelov, Ludwig Schmidt, Dimitris Tsipras, and Adrian Vladu. Towards deep learning models resistant to adversarial attacks. In *International Conference on Learning Representations*, 2018.

Jan Hendrik Metzen, Volker Fischer, and Bastian Bischoff. On detecting adversarial perturbations. In *International Conference on Learning Representations*, 2018.

Nicolas Papernot, Patrick Mcdaniel, Xi Wu, Somesh Jha, and Ananthram Swami. Distillation as a defense to adversarial perturbations against deep neural networks. *arXiv preprint arXiv:1511.04508*, 2015.

Maini Athalye Pratyush, Wong Eric, and Kolter J. Zico. adversarial robustness against the union of multiple perturbation model. In *International Conference on Machine Learning*, 2020.

Jonas Rauber, Wieland Brendel, and Matthias Bethge. Foolbox: A python toolbox to benchmark the robustness of machine learning models. 2017.

Lukas Schott, Jonas Rauber, Matthias Bethge, and Wieland Brendel. Towards the first adversarially robust neural network model on mnist. In *International Conference on Learning Representations*, 2019.

Christian Szegedy, Wojciech Zaremba, Ilya Sutskever, Joan Bruna, Dumitru Erhan, Ian Goodfellow, and Rob Fergus. Intriguing properties of neural networks. *arXiv preprint arXiv:1312.6199*, 2013.

Florian Tramèr and Dan Boneh. Adversarial training and robustness for multiple perturbations. In *Advances in Neural Information Processing Systems*, 2019.

Dimitris Tsipras, Shibani Santurkar, Logan Engstrom, Alexander Turner, and Aleksander Madry. Robustness may be at odds with accuracy. In *International Conference on Learning Representations*, 2019.

Jonathan Uesato, Brendan O'Donoghue, Aäron van den Oord, and Pushmeet Kohli. Adversarial risk and the dangers of evaluating against weak attacks. In *International Conference on Machine Learning*, 2018.

Jiayu Wu, Qixiang Zhang, and Guoxi Xu. Tiny imagenet challenge. 2017.

Cihang Xie and Alan Yuille. Intriguing properties of adversarial training at scale. In *International Conference on Learning Representations*, 2020.

Cihang Xie, Jianyu Wang, Zhishuai Zhang, Zhou Ren, and Alan Yuille. Mitigating adversarial effects through randomization. In *International Conference on Learning Representations*, 2018.

Cihang Xie, Mingxing Tan, Boqing Gong, Jiang Wang, Alan L Yuille, and Quoc V Le. Adversarial examples improve image recognition. In *IEEE Conference on Computer Vision and Pattern Recognition*, 2020.

Dong Yin, Gontijo Raphael Lopes, Jonathon Shlens, D Ekin Cubuk, and Justin Gilmer. A fourier perspective on model robustness in computer vision. In *Advances in Neural Information Processing Systems*, 2019.

A   EXPERIMENTAL SETTING FOR SEPARATING BNS

We provide the experimental setting for separating BNs study in Section 3.1. Specifically, we train a DNN on CIFAR-10 with each BN layer composed of 4 branches (*i.e.*, we replace each BN with 4 BN branches). During training, we construct different mini-batch for clean, ℓ_1, ℓ_2, and ℓ_∞ adversarial images to estimate the normalization statistics of each branch of BN; during inference, given a mini-batch of data from a specific domain, we manually activate the corresponding BN branch and deactivate the others. We update the running statistics of each BN branch separately but optimize the model parameters using the sum of the four losses.

B   PROOF IN SECTION 3.1

We first calculate the optimal perturbation δ^p in the l_p ball of radius ϵ. For simplicity, we assume that the classification loss is given by $-\mathbf{y}f(\mathbf{x})$. The objective of the adversary is to find a perturbation δ^p which maximizes the loss. For the linear classifier, δ^p can be explicitly calculated as follows

$$
\begin{aligned}
\delta^p &= \arg\max\nolimits_{||\delta||_p \le \epsilon} l(f(\mathbf{x}+\delta), \mathbf{y}) = \arg\max\nolimits_{||\delta||_p \le \epsilon} -\mathbf{y}f(\mathbf{x}+\delta) \\
&= \arg\max\nolimits_{||\delta||_p \le \epsilon} -\mathbf{y}w^T\delta \\
&= \epsilon \cdot \arg\max\nolimits_{||\delta||_p \le 1} -\mathbf{y}w^T\delta \\
&= \epsilon\partial|| -\mathbf{y}w||_q,
\end{aligned}
$$

where $1/p + 1/q = 1$ and the last equality uses the property that $\partial||x||_q = \arg\max_{||s||_p \le 1} s^T\mathbf{x}$. Notice that the optimal perturbation δ^p is independent of the inputs corresponding to a particular label. Therefore, the new distribution $\mathbb{D}_{\mathbf{y}}^p$ of the adversarial examples generated from the perturbation type S^p can be written as $\mathbb{D}_{\mathbf{y}}^0 + \epsilon\partial|| - \mathbf{y}w||_q$, where $\mathbb{D}^0$ represents the clean example domain.

For $p = 1$ or $p = \infty$, it is easy to verify that $\partial|| - \mathbf{y}w||_q = (0, 0, \cdots, sign(-\mathbf{y}w_i), \cdots, 0)$ where $i = \arg\max_j |w_j|$ or $\partial|| - \mathbf{y}w||_q = (sign(-\mathbf{y}w_1), \cdots, sign(-\mathbf{y}w_j), \cdots, sign(-\mathbf{y}w_d))$ respectively.

For $p = 2$, we can simply obtain that $\partial|| - \mathbf{y}w||_2 = (-\mathbf{y}w_i/||w||_2, \cdots, -\mathbf{y}w_d/||w||_2)$.

Thus, we have the Wasserstain distance between $\mathbb{D}_{\mathbf{y}}^{\ell_1}$ and $\mathbb{D}_{\mathbf{y}}^{\ell_\infty}$ as

$$
W_2(\mathbb{D}_{\mathbf{y}}^{\ell_1}, \mathbb{D}_{\mathbf{y}}^{\ell_\infty}) = W_2(\mathbb{D}_{\mathbf{y}}^0 + \epsilon\partial|| - \mathbf{y}w||_\infty, \mathbb{D}_y^0 + \epsilon\partial|| - \mathbf{y}w||_1) = \epsilon\sqrt{d-1},
$$

where the last equality follows from the translation invariance of Wasserstein distance. Similarly, the Wasserstein distance between $\mathbb{D}_{\mathbf{y}}^{\ell_2}$ and $\mathbb{D}_{\mathbf{y}}^{\ell_1}$ is

$$
W_2(\mathbb{D}_{\mathbf{y}}^{\ell_1}, \mathbb{D}_{\mathbf{y}}^{\ell_2}) = \epsilon\sqrt{2 - 2|w_i|/||w||_2}.
$$

Finally, the Wasserstein distance between $\mathbb{D}_{\mathbf{y}}^{\ell_2}$ and $\mathbb{D}_{\mathbf{y}}^{\ell_\infty}$ can be calculated as

$$
W_2(\mathbb{D}_{\mathbf{y}}^{\ell_2}, \mathbb{D}_{\mathbf{y}}^{\ell_\infty}) = \epsilon\sqrt{d + 1 - 2||w||_1/||w||_2}.
$$

C   GBN IMPLEMENATION DETAILS

Network architecture. We first illustrate the architecture of the gated sub-network $\mathbf{g}$ in GBN. As shown in Figure 4, we devise two types of gated sub-network, namely *Conv gate* and *FC gate*.

The notation Conv2d(d, s, k) refers to a convolutional layer with k filters whose size are $d \times d$ convolved with stride s. The notation ReLU$(\cdot)$ denotes the rectified linear unit used as the activation function in the network. FC(m) denotes a fully connected layer with output size m.

Conv gate is a convolutional neural network consisting of two convolutional layers, two ReLU layers and one fully-connected layer. c denotes the input channel of this gate. In the default setting, we use stride 1 for the first convolutional layer and 2 for the second. For the filter sizes in both layers, padding is set to 3 and 1, respectively. We set the fully-connected layer output size m=4 to match the four data distributions used in our experiment.

```
Conv2d(3, 1, c)
    ReLU()                      FC(512)
Conv2d(3, 2, 2 * c)             ReLU()
    ReLU()                       FC(4)
    FC(4)                      Softmax()
  Softmax()
```

(a) Conv gate   (b) FC gate

Figure 4: The architecture of the gated sub-network used in this paper.

FC gate is a simple fully-connected neural network that includes two fully-connected layers and one ReLU layer. We use m=512 and m=4 for the two fully-connected layers.

To train models containing GBN, we add the GBN block into all layers within a model. Specifically, we set the **g** in the first GBN as the *Conv gate* and use the *FC gates* for other GBN blocks to further capture domain-specific information and improve model robustness. We use the default values for ξ and α in PyTorch.

Discussion. To empirically prove the effectiveness of the above strategy, we conduct additional experiments using the *Conv gate* and *FC gate* for all GBN blocks. In other words, we train a VGG-16 model with all GBN blocks using the *Conv gate* denoted "Conv$_{all}$", and train another model with all GBN blocks using the *FC gate* denoted "FC$_{all}$". As shown in Table 2, our strategy (denoted "Conv+FC") achieves the greatest robustness. Thus, we use *Conv gate* for all the GBN blocks in the single layer study, and use *Conv gate* for the first GBN and *FC gates* for the other GBN blocks in the layer group study (Section 4.3).

We conjecture that there are two reasons for this: (1) the running statistics between different domains in the first layer are almost indistinguishable (*c.f.* Appendix E.8). Thus, solely using the FC layer (*FC gate*) fails to extract sufficient features from the first layer to perform correct classification; (2) using conv layers for all GBN blocks may suffer from over-fitting problem, since only adding GBN into the first layer achieves considerable robustness (as shown in Figure 3(a)). We will further address it in the future studies.

Table 2: Model robustness of VGG-16 on CIFAR-10 (the higher the better).

	Conv$_{all}$	FC$_{all}$	Conv+FC
PGD-ℓ_1	30.9%	35.5%	58.5%
PGD-ℓ_2	29.9%	34.6%	69.5%
PGD-ℓ_∞	20.6%	32.6%	60.1%
Clean accuracy	41.6%	39.6%	80.7%

D EXPERIMENTAL SETTINGS

Dataset details. MNIST is a dataset containing 10 classes of handwritten digits of size 28×28 with 60,000 training examples and 10,000 test instances. CIFAR-10 consists of 60,000 natural scene color images in 10 classes of size 32×32. Tiny-Imagenet has 200 classes of size 64×64, and each class contains 500 training images, 50 validation images, and 50 test images.

Implementation details. Here, we provide the details of the experimental settings for GBN and other baselines on different datasets. All the models for each method on MNIST, CIFAR-10, and Tiny-ImageNet are trained for 40, 40, and 20 epochs, respectively. We set the mini-batch size=64, use the SGD optimizer with weight decay 0.0005 for Tiny-ImageNet and use no weight decay for MNIST and CIFAR-10. We set the learning rate as 0.1 for MNIST and 0.01 for CIFAR-10 and

Tiny-ImageNet. For these baselines, we use the published implementations for ABS[4], MAX/AVG[5], and MSD[6].

D.1 ADVERSARIAL ATTACKS

In this paper, we adopt both the white-box and black-box adversarial attacks. In the white-box setting, adversaries have the complete knowledge of the target model and can fully access the model; while in the black-box setting, adversaries have limited knowledge of the target classifier (*e.g.*, its architecture) but can not access the model weights.

For ℓ_1 attacks, we use PGD attack (Madry et al., 2018), and Brendel & Bethge attack (BBA) (Brendel et al., 2019).

For ℓ_2 attacks, we use PGD attack (Madry et al., 2018), C&W attack (Carlini & Wagner, 2017) the Gaussian noise attack (Rauber et al., 2017), the boundary attack (BA) (Brendel et al., 2018).

For ℓ_∞ attacks, though ℓ_∞ PGD adversary is quite effective, for completeness, we additionally use attacks including, Fast Gradient Sign Method (FGSM) (Goodfellow et al., 2014), SPSA (Uesato et al., 2018), Nattack (Li et al., 2019), Momentum Iterative Method (MI-FGSM) (Dong et al., 2018), and AutoAttack (Croce & Hein, 2020b) (a stronger ensemble of parameter-free attacks, including APGD, FAB (Croce & Hein, 2020c), and Square Attack (Andriushchenko et al., 2020)) .

Among the attacks mentioned above, BA, SPSA, Nattack, and Square Attack are black-box attacks. We then provide the hyper-parameters of each attack.

PGD-ℓ_1. On MNIST, we set the perturbation magnitude ϵ=10, iteration number k=50, and step size $\alpha=\epsilon/10$. On CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=12, iteration number k=50, and step size α=0.05.

PGD-ℓ_2. On MNIST, we set the perturbation magnitude ϵ=2.0, iteration number k=100, and step size α=0.1. On CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=0.5, iteration number k=50, and step size $\alpha=\epsilon/10$.

PGD-ℓ_∞. On MNIST, we set the perturbation magnitude ϵ=0.3, iteration number k=50, and step size α=0.01. On CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=0.03, iteration number k=40, and step size $\alpha=\epsilon/10$.

BBA. On MNIST, CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=10, 12, 12 in terms of ℓ_1 norm, respectively. For all datasets, we set the number of optimization steps as 1000, learning rate as 0.001, momentum as 0.8, and the binary search steps as 10.

C&W. On MNIST, CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=2.0, 0.5, 0.5 in terms of ℓ_2 norm, respectively. For all datasets, we set the number of optimization steps as 10000, each step size as 0.01, and the confidence required for an example to be marked as adversarial as 0.

Gaussian noise. On MNIST, CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=2.0, 0.5, 0.5 in terms of ℓ_2 norm, respectively.

BA. On MNIST, CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=2.0, 0.5, 0.5 in terms of ℓ_2 norm, respectively. For all datasets, we set the maximum number of steps as 25000, initial step size for the orthogonal step as 0.01, and initial step size for the step towards the target as 0.01.

FGSM. On MNIST, we set the perturbation magnitude ϵ=0.3 in terms of ℓ_∞ norm. On CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=0.03 in terms of ℓ_∞ norm.

MI-FGSM. On MNIST, we set the perturbation magnitude ϵ=0.3, the decay factor μ=1 in terms of ℓ_∞ norm, and set the step number k=10. On CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=0.03, the decay factor μ=1 in terms of ℓ_∞ norm, and set the step number k=10. The step size $\alpha=\epsilon/k$.

---

[4] https://github.com/bethgelab/AnalysisBySynthesis
[5] https://github.com/ftramer/MultiRobustness
[6] https://github:com/locuslab/robust_union

SPSA. We set the maximum iteration as 100, the batch size as 8192, and the learning rate as 0.01. The magnitude of perturbation is 0.3 in terms of ℓ_∞ norm on MNIST, and 0.03 in terms of ℓ_∞ norm on CIFAR-10 and Tiny-ImageNet.

NATTACK. We set T=600 as the maximum number of optimization iterations, b=300 for the sample size, variance of the isotropic Gaussian σ^2=0.01, and learning rate as 0.008. The magnitude of perturbation is 0.3 in terms of ℓ_∞ norm on MNIST, and 0.03 in terms of ℓ_∞ norm on CIFAR-10 and Tiny-ImageNet.

AutoAttack. AutoAttack selects the following variants of adversarial attacks: APGD_{CE} without random restarts, APGD_{DLR}, the targeted version of FAB as FAB^T, and Square Attack with one run of 5000 queries. We use 100 iterations for each run of the white-box attacks. For APGD, we set the momentum coefficient α=0.75, ρ=0.75, initial step size $\eta^{(0)}$=2ϵ, where ϵ is the perturbation magnitude in terms of the ℓ_∞ norm. For FAB, we keep the standard hyper-parameters based on the implementation of AdverTorch. For Square Attack, we set the initial value for the size of the squares p = 0.8.

D.2 Adversarial Defenses

ABS. ABS uses multiple variational autoencoders to construct a complex generative architecture to defend against adversarial examples in the MNIST dataset. As for the limited code released by the authors, we directly use the results reported in Schott et al. (2019). They set the perturbation magnitude ϵ=12, 1.5, 0.3 for ℓ_0, ℓ_2, and ℓ_∞ attack, respectively. ABS used an ℓ_0 perturbation model of a higher radius and evaluated against ℓ_0 attacks. So the reported number is a near estimate of the ℓ_1 adversarial accuracy.

AVG. For each batch of clean data (size=64), we generate corresponding adversarial examples (ℓ_1, ℓ_2, and ℓ_∞) using PGD attack. We train the model using a combination of clean, ℓ_1, ℓ_2, and ℓ_∞ adversarial examples simultaneously. The hyper-parameters of PGD adversaries can be found in Appendix D.1.

MAX. For each batch of clean data (size=64), we generate the strongest adversarial examples (one of the ℓ_1, ℓ_2, and ℓ_∞ attack) using PGD attack. We train the model using a combination of clean examples and the strongest attack. The hyper-parameters of PGD adversaries can be found in Appendix D.1.

MSD. MSD creates a single adversarial perturbation by simultaneously maximizing the worst-case loss over all perturbation models at each projected steepest descent step. For MNIST, we set the perturbation magnitude ϵ=10, 2.0, 0.3 for ℓ_1, ℓ_2, and ℓ_∞ attack, respectively, and iteration number k=100. For CIFAR-10 and Tiny-ImageNet, we set the perturbation magnitude ϵ=12, 0.5, 0.03 for ℓ_1, ℓ_2, and ℓ_∞ attack respectively, and iteration number k=50.

D.3 Normalization Techniques

MN. We set the number of modes in MN to 2, which achieves the best performance according to the original paper (Lucas et al., 2019). During training, we feed the model with a mixture of clean, ℓ_1, ℓ_2, and ℓ_∞ adversarial examples using the same setting as AVG.

MBN. The original MBN (Xie et al., 2020; Xie & Yuille, 2020) manually selects the BN branches for clean and adversarial examples during inference, which is infeasible in adversarial defense setting (the model is unaware of the type of inputs). Thus, we add the 2-way gated sub-network in MBN to predict the input domain label; we then keep the following 2 BN branches the same. During training, we compel the clean examples to go through the first BN branch and the adversarial examples (*i.e.*, ℓ_1, ℓ_2, and ℓ_∞) to the second BN branch. The adversarial examples are generated via PGD using the same setting as AVG.

E More Experimental Results

In this section, we provide further experimental results.

E.1 Multiple Perturbations from the Fourier Perspective

Figure 5: Model sensitivity to additive noise aligned with different Fourier basis vectors on CIFAR-10. From left to right: vanilla, ℓ_1-trained, ℓ_2-trained, and ℓ_∞-trained models. The numbers indicate the model error rates.

We study the differences between different perturbation types from the Fourier perspective (Yin et al., 2019). We evaluate four different ResNet-20 models: a vanilla model and 3 adversarially-trained models using only ℓ_1, ℓ_2, and ℓ_∞ adversarial examples, respectively. We visualize the Fourier heatmap following (Yin et al., 2019) and shift the low frequency components to the center of the spectrum. Error rates are averaged over 1000 randomly sampled images from the test set on CIFAR-10. The redder the zone, the higher the error rate of the model to perturbations of specific frequency. As shown in Figure 5, models trained using different ℓ_p perturbations demonstrate different model weaknesses in the Fourier heatmap (*i.e.*, different hot zones). For example, ℓ_2-PAT is more susceptible to high-frequency perturbations while less susceptible to some low-frequency perturbations (the smaller blue zone in the center), while ℓ_∞-PAT is comparatively more robust to middle-frequency perturbations (light yellow zones). Therefore, different perturbation types have different frequency properties, and models trained on different perturbations are sensitive to noise from different frequencies. This observation further demonstrates that different perturbation types may arise from different domains (our multi-domain hypothesis).

E.2 Computational cost

Here, we provide the time consumption of AVG, MAX, MSD, MN, MBN, and our GBN. All the experiments are conducted on a NVIDIA Tesla V100 GPU cluster. We compute the overall training time using ResNet-20 on CIFAR-10 for 40 epochs. We compute the inference time using ResNet-20 on CIFAR-10 for 10000 images. As seen in Table 3, our method achieves comparable results to other baselines, demonstrating its applicability in practice.

Table 3: Runtime analysis of different methods on CIFAR-10 (the lower the better).

	AVG	MAX	MSD	MN	MBN	**GBN(ours)**
Training speed (seconds/ epoch)	1837.9	1113.2	689.8	19329.1	2737.9	2802.6
Training duration (hours)	20.4	12.4	7.7	214.8	30.4	31.1
Inference speed (seconds/ 10000 images)	0.60	0.58	0.61	4.8	1.9	2.0

E.3 Adversarial Robustness against multiple perturbations

In this part, we provide the breakdown for each individual attack on MNIST, CIFAR-10, and Tiny-ImageNet in Tabel 4, 5, and 6. We also report the results for individual attacks of AutoAttack in 7.

Table 4: Model robustness of LeNet on MNIST over each individual attack (the higher the better).

		Vanilla	AVG	MAX	ABS	MSD	MN	MBN	GBN
ℓ_1 attacks	PGD-ℓ_1	74.4%	77.9%	77.3%	/	77.0%	80.4%	79.6%	**86.8%**
	BBA	6.5%	31.2%	33.1%	/	42.6%	25.2%	64.5%	**79.6%**
ℓ_2 attacks	PGD-ℓ_2	24.7%	73.5%	74.6%	/	69.5%	77.2%	78.5%	**97.8%**
	C&W	2.0%	68.1%	67.6%	/	72.4%	20.0%	67.3%	**98.1%**
	Gaussian Noise	99.2%	98.7%	98.2%	98.0%	97.3%	97.6%	98.6%	**99.2%**
	BA	10.5%	60.9%	59.2%	83.0%	78.7%	24.2%	90.2%	**97.7%**
ℓ_∞ attacks	PGD-ℓ_∞	64.2%	72.6%	74.7%	/	51.6%	78.9%	80.3%	**96.3%**
	FGSM	48.7%	87.5%	86.3%	34.0%	69.7%	**97.5%**	75.4%	89.5%
	MI-FGSM	36.2%	82.1%	81.5%	17.0%	60.9%	90.7%	40.7%	85.2%
	SPSA	37.6%	64.2%	60.5%	/	71.4%	77.8%	77.8%	**98.2%**
	NATTACK	40.4%	79.5%	78.9%	/	85.2%	90.2%	89.3%	**97.7%**
	AutoAttack	0.0%	46.1%	60.1%	/	39.0%	0.0%	20.0%	**71.7%**
All attacks	-	0.0%	29.7%	31.2%	17.0%	38.9%	0.0%	19.2%	**68.9%**
Clean accuracy	-	**99.3%**	98.7%	98.2%	99.0%	97.3%	98.1%	98.7%	98.7%

Table 5: Model robustness of ResNet-20 on CIFAR-10 over each individual attack (the higher the better).

		Vanilla	AVG	MAX	MSD	MN	MBN	GBN
ℓ_1 attacks	PGD-ℓ_1	31.7%	47.4%	38.1%	49.9%	44.1%	47.7%	**58.5%**
	BBA	0.0%	45.0%	33.4%	43.8%	40.0%	45.8%	**69.1%**
ℓ_2 attacks	PGD-ℓ_2	32.1%	59.2%	58.0%	62.8%	49.4%	60.5%	**69.5%**
	C&W	0.0%	59.7%	56.0%	62.5%	30.1%	20.8%	**74.9%**
	Gaussian Noise	**81.2%**	76.4%	62.9%	69.1%	60.2%	49.5%	79.1%
	BA	0.3%	62.0%	57.8%	59.9%	39.1%	47.8%	**73.2%**
ℓ_∞ attacks	PGD-ℓ_∞	3.2%	42.1%	39.7%	44.5%	34.6%	58.4%	**60.1%**
	FGSM	9.2%	39.9%	42.7%	46.4%	40.1%	**62.4%**	56.0%
	MI-FGSM	0.0%	37.8%	31.6%	45.3%	31.2%	60.1%	**72.9%**
	SPSA	0.4%	33.2%	30.4%	44.9%	38.4%	68.2%	**69.8%**
	NATTACK	1.9%	34.3%	30.9%	45.1%	40.2%	45.4%	**64.2%**
	AutoAttack	0.0%	29.3%	25.4%	38.1%	13.2%	40.8%	**50.9%**
All attacks	-	0.0%	28.2%	24.9%	37.9%	13.0%	20.7%	**48.7%**
Clean accuracy	-	**89.7%**	80.6%	77.0%	79.1%	82.3%	79.4%	80.7%

In summary, our proposed GBN trains robust models in terms of multiple perturbation types (*i.e.*, $\ell_1, \ell_2, \ell_\infty$) and outperforms other methods by large margins.

E.4 PREDICTION RESULTS OF THE GATED SUB-NETWORK

In this part, we show the prediction results of the gated sub-network in GBN, *i.e.*, the classification accuracy for the domain of different input samples. The results of LeNet on MNIST and ResNet-

Table 6: Model robustness of ResNet-34 on Tiny-ImageNet over each individual attack (the higher the better).

		Vanilla	AVG	MAX	MSD	MN	MBN	**GBN**
ℓ_1 attacks	PGD-ℓ_1	10.0%	28.1%	17.1%	9.0%	12.4%	45.2%	**55.7%**
	BBA	5.8%	27.5%	26.2%	7.6%	8.8%	37.0%	**45.2%**
ℓ_2 attacks	PGD-ℓ_2	12.3%	30.5%	24.4%	14.2%	18.1%	31.7%	**53.9%**
	C&W	10.9%	29.1%	25.2%	11.2%	19.2%	31.4%	**44.8%**
	Gaussian Noise	**54.2%**	41.6%	36.3%	26.7%	40.2%	46.2%	42.8%
	BA	27.1%	35.2%	24.9%	13.7%	30.2%	38.4%	**44.1%**
ℓ_∞ attacks	PGD-ℓ_∞	7.1%	6.9%	4.7%	7.6%	19.8%	40.2%	**50.2%**
	FGSM	3.4%	11.1%	6.8%	8.9%	22.4%	41.4%	**50.3%**
	MI-FGSM	1.4%	9.4%	6.0%	8.0%	15.1%	36.3%	**53.7%**
	SPSA	0.3%	7.1%	6.5%	10.0%	29.8%	39.2%	**52.0%**
	NATTACK	0.8%	8.2%	7.5%	12.3%	29.9%	40.3%	**48.5%**
	AutoAttack	0.0%	4.6%	2.9%	5.1%	6.8%	20.1%	**39.8%**
All attacks	-	0.0%	4.6%	2.2%	5.0%	6.7%	20.0%	**38.9%**
Clean accuracy	-	**54.2%**	41.6%	36.3%	28.8%	46.7%	45.7%	43.4%

Table 7: Robustness evaluation by AutoAttack (the higher the better). We report the clean accuracy, the robust accuracy of the individual attacks as well as the combined one of AutoAttack (AA column in light green background).

	Vanilla	AVG	MAX	MSD	MN	MBN	**GBN**
MNIST - ℓ_∞							
APGD$_{CE}$	34.0%	48.4%	60.2%	39.3%	74.7%	20.2%	80.9%
APGD$_{DLR}$	0.0%	41.2%	55.7%	33.9%	0.0%	52.2%	88.4%
FAB^T	0.2%	52.1%	60.1%	37.3%	0.0%	80.7%	96.1%
Square	0.0%	50.2%	53.1%	38.5%	0.0%	59.7%	79.3%
AA	0.0%	46.1%	60.1%	39.0%	0.0%	20.0%	71.7%
CIFAR-10 - ℓ_∞							
APGD$_{CE}$	0.0%	30.8%	29.9%	44.3%	20.8%	53.5%	60.8%
APGD$_{DLR}$	0.0%	28.1%	25.7%	39.1%	29.9%	62.4%	58.9%
FAB^T	0.0%	29.6%	26.3%	39.3%	30.1%	40.9%	70.2%
Square	0.1%	40.5%	31.6%	46.1%	17.8%	14.5%	60.3%
AA	0.0%	29.3%	25.4%	38.1%	13.2%	40.8%	50.9%
Tiny-ImageNet - ℓ_∞							
APGD$_{CE}$	0.0%	5.7%	3.7%	6.3%	8.7%	39.3%	44.3%
APGD$_{DLR}$	0.0%	5.1%	2.6%	4.2%	10.4%	41.0%	43.8%
FAB^T	0.2%	5.2%	2.7%	4.3%	9.1%	37.3%	50.0%
Square	0.7%	10.1%	4.0%	5.9%	6.4%	29.3%	39.4%
AA	0.0%	4.6%	2.9%	5.1%	6.8%	20.1%	39.8%

20 on CIFAR-10 are presented in Table 8. For MNIST, the gated sub-network of LeNet at different layers achieves high prediction accuracy for the input domains (*i.e.*, clean, ℓ_1, ℓ_2, and ℓ_∞ adversarial examples). However, on CIFAR-10, the prediction accuracy of the gated sub-network drops with the increasing of the layer depth. From the results, we can also confirm our findings in Section 4.3: (1) shallow layers are more critical to model robustness; and (2) as the layer depth increases, the features from different domains are highly entangled and mixed, making it harder for models to separate them. To further improve model robustness against multiple perturbations, we suggest to improve the prediction accuracy of the gated sub-network. We will further address it in the future studies.

Table 8: Gated sub-network prediction accuracy on inputs from different domains on different datasets (the higher the better). We demonstrate the prediction accuracy of gated sub-network at each layer from top to bottom. The adversarial examples are generated by PGD attacks.

(a) LeNet on MNIST

	Clean	ℓ_1	ℓ_2	ℓ_∞
gate$_1$	96.7%	78.2%	92.3%	98.6%
gate$_2$	94.2%	74.5%	89.9%	98.8%

(b) ResNet-20 on CIFAR-10

	Clean	ℓ_1	ℓ_2	ℓ_∞
gate$_1$	79.7%	85.2%	88.7%	84.8%
gate$_2$	77.2%	84.5%	85.9%	83.7%
gate$_3$	77.4%	84.2%	82.3%	83.9%
gate$_4$	75.2%	83.5%	75.2%	82.1%
gate$_5$	74.7%	82.2%	73.4%	81.6%
gate$_6$	73.2%	82.5%	69.1%	79.8%
gate$_7$	71.7%	81.2%	67.9%	78.3%
gate$_8$	65.2%	74.5%	67.2%	75.7%
gate$_9$	64.7%	74.2%	66.8%	75.5%
gate$_{10}$	64.2%	73.6%	65.7%	74.8%
gate$_{11}$	64.7%	73.2%	64.6%	74.5%
gate$_{12}$	64.2%	72.9%	64.4%	73.9%
gate$_{13}$	63.9%	71.2%	64.1%	73.7%
gate$_{14}$	63.0%	69.5%	64.0%	72.3%
gate$_{15}$	64.1%	69.1%	64.2%	71.6%
gate$_{16}$	64.2%	68.7%	63.9%	70.9%
gate$_{17}$	62.5%	68.2%	63.9%	70.6%
gate$_{18}$	63.2%	68.5%	63.6%	69.5%
gate$_{19}$	62.7%	67.9%	63.4%	69.4%

E.5 ALTERNATIVE PREDICTION APPROACH OF THE GATED SUB-NETWORK

In the main body of our paper, we calculate the normalized output using the gated sub-network in a soft-gated way (denoted "soft") based on Eqn. 3. In this section, we also try taking the top-1 prediction of $\mathbf{g}$ (the hard label) to normalize the output as an alternative approach (denoted "hard"). As shown in Table 9, the two approaches achieve comparable performance in terms of both robustness and standard accuracy.

E.6 ATTACKS OUTSIDE THE PERTURBATION MODEL

In this section, we present some additional experiments exploring our model's performance on attacks which lying outside the perturbation model.

Table 9: Model robustness of ResNet-20 on CIFAR-10 using different prediction approaches of the gated sub-network (the higher the better).

	vanilla	hard	soft
PGD-ℓ_1	31.4%	58.2%	58.5%
PGD-ℓ_2	32.1%	69.6%	69.5%
PGD-ℓ_∞	3.2%	59.9%	60.1%
Clean accuracy	89.7%	80.4%	80.7%

We conduct two experiments: (1) adversarially train a GBN model on ℓ_1 and ℓ_∞ perturbations, and evaluate it on ℓ_2 adversaries (denoted GBN$_{\ell_1+\ell_\infty}$); and (2) adversarially train a GBN model on ℓ_2 and ℓ_∞ perturbations, and evaluate it on ℓ_1 adversaries (denoted GBN$_{\ell_2+\ell_\infty}$). The results are shown in Table 10.

We empirically observe that training on 2 perturbation types actually improves overall robustness against all three perturbation adversaries. Unsurprisingly, the robustness of GBN$_{\ell_1+\ell_\infty}$ for ℓ_2 adversarial examples and the robustness of GBN$_{\ell_2+\ell_\infty}$ for ℓ_1 adversarial examples decrease to some degree, but the models still perform better than vanilla, and sometimes even outperform baseline methods.

In addition, we further evaluate model robustness on attacks outside the perturbation model using different prediction approaches of the gated sub-network (*i.e.*, soft label and hard label). As shown in Table 11, we achieve the similar results using the soft or hard label.

Table 10: Attacks outside the perturbation model of ResNet-20 on CIFAR-10 (the higher the better).

	Vanilla	AVG	MAX	MSD	GBN	GBN$_{\ell_1+\ell_\infty}$	GBN$_{\ell_2+\ell_\infty}$
PGD-ℓ_1	31.7%	47.4%	38.1%	49.9%	58.5%	57.4%	40.9%
PGD-ℓ_2	32.1%	59.2%	58.0%	62.8%	69.5%	41.8%	65.4%
PGD-ℓ_∞	3.2%	42.1%	39.7%	44.5%	60.1%	57.2%	56.8%
Clean accuracy	89.7%	80.6%	77.0%	79.1%	80.7%	81.3%	81.1%

Table 11: Attacks outside the perturbation model of ResNet-20 on CIFAR-10 using different prediction approaches of the gated sub-network ("h" denotes the hard label and "s" denotes the soft label).

	GBN$_{\ell_1+\ell_\infty}$(s)	GBN$_{\ell_2+\ell_\infty}$(s)	GBN$_{\ell_1+\ell_\infty}$(h)	GBN$_{\ell_2+\ell_\infty}$(h)
PGD-ℓ_1	57.4%	40.9%	57.9%	41.5%
PGD-ℓ_2	41.8%	65.4%	40.2%	67.9%
PGD-ℓ_∞	57.2%	56.8%	58.2%	56.1%
Clean accuracy	81.3%	81.1%	81.2%	80.9%

E.7 DIFFERENT VARIANTS OF WHITE-BOX ATTACKS

Here, we examine the performance of GBN in a more rigorous white-box attack scenario. In this case, the adversary not only knows every detail of the GBN architecture, but also can manually select the BN branch to generate adversarial attacks. Note that this is presented only for exploratory reasons and there is no principled reason why adversaries could manually manipulate the model.

Specifically, we generate ℓ_1, ℓ_2, and ℓ_∞ adversarial examples through BN^0, BN^1, BN^2, and BN^3 in GBN, respectively. Note that their statistics are estimated by clean, ℓ_1, ℓ_2, and ℓ_∞ adversarial examples during training, respectively. As presented in Table 12, the model achieves good robustness on different datasets in the more rigorous white-box attack scenario.

Table 12: Different variants of white-box attacks on MNIST and CIFAR-10 (BN^0, BN^1, BN^2, and BN^3 denotes the BN branch for clean, ℓ_1, ℓ_2, and ℓ_∞ adversarial examples in GBN, respectively).

(a) LeNet on MNIST

	BN^0	BN^1	BN^2	BN^3
PGD-ℓ_1	86.8%	88.5%	86.9%	97.1%
PGD-ℓ_2	97.8%	98.9%	97.8%	98.7%
PGD-ℓ_∞	97.1%	98.6%	96.3%	95.4%
Clean accuracy	98.7%	98.7%	98.7%	98.7%

(b) ResNet-20 on CIFAR-10

	BN^0	BN^1	BN^2	BN^3
PGD-ℓ_1	58.5%	56.4%	59.9%	60.3%
PGD-ℓ_2	69.7%	69.4%	68.2%	69.5%
PGD-ℓ_∞	60.3%	61.1%	61.3%	59.2%
Clean accuracy	80.7%	80.7%	80.7%	80.7%

E.8 RUNNING STATISTICS OF MULTIPLE BN BRANCHES AT DIFFERENT LAYERS

We train a VGG-16 model with a multiple BN branch structure and inspect the running statistics of each BN at different layers, as shown in Figure 6. Surprisingly, the running statistics between different domains in the first layer are almost indistinguishable.

(a) running mean of layer $conv1\_1$

(b) running variance of layer $conv1\_1$

(c) running mean of layer $conv2\_2$

(d) running variance of layer $conv2\_2$

(e) running mean of layer $conv3\_1$

(f) running variance of layer $conv3\_1$

(g) running mean of layer $conv4\_1$

(h) running variance of layer $conv4\_1$

Figure 6: Running statistics (running mean and running variance) of each BN in the multiple BN branches at different layers of a VGG-16 model on CIFAR-10.