InsPro: Propagating Instance Query and Proposal for Online Video Instance Segmentation

Abstract

Video instance segmentation (VIS) aims at segmenting and tracking objects in videos. Prior methods typically first generate frame-level or clip-level object instances and then associate them by either additional tracking heads or complex instance matching algorithms. This explicit instance association approach increases system complexity and fails to fully exploit temporal cues in videos. In this paper, we design a simple, fast and yet effective query-based framework for online VIS, where we propose an instance query and proposal propagation mechanism to perform instance association implicitly. Specifically, we generate frame-level object instances based on a set of instance query-proposal pairs propagated from previous frames. This instance query-proposal pair is learned to represent one specific instance across frames through several developed strategies. When using such a query-proposal pair to predict an object instance on the current frame, not only the generated instance is automatically associated with its precursors on previous frames, but the model gets a good prior for predicting the same object. In this way, we naturally achieve implicit instance association in parallel with segmentation and elegantly take advantage of temporal clues in videos. To show the effectiveness of our method which is dubbed as InsPro, we evaluate it on two popular VIS benchmarks, *i.e.*, YouTube-VIS 2019 and YouTube-VIS 2021. Without bells-and-whistles, our InsPro with ResNet-50 backbone achieves 43.2 AP and 37.6 AP on these two benchmarks respectively, outperforming all other online VIS methods. Code will be made publicly available.

1 Introduction

Video instance segmentation (VIS) [1] is a challenging but important computer vision task. It requires not only segmenting object instances on each video frame but also associating them across all frames. Due to its fine-grained object representation form, it has got a wide range of applications such as autonomous driving and video editing.

Existing VIS methods can be categorized into two groups: frame-level methods and clip-level methods. Frame-level methods [1, 2, 3, 4] generally follow a 'tracking-by-detection' paradigm, which first generate per-frame object instances by existing instance segmentation models [5, 6], and then associate them across frames via additional tracking heads (as shown in Figure 1 (a)). In comparison, clip-level methods [7, 8, 9, 10] take a 'clip-matching' paradigm, which divide a video into multiple overlapped clips and generate instance predictions of each clip, and then associate these clip-level predictions by some hand-crafted instance matching algorithms. Whether frame-level or

Submitted to 36th Conference on Neural Information Processing Systems (NeurIPS 2022). Do not distribute.

Figure 1: (a) Previous methods take a two-step approach to VIS. They first generate object instances and then perform explicit instance association to link them across frames. (b) Our InsPro implements implicit instance association through a temporal propagation mechanism, and achieves object instance segmentation and tracking in one shot. It generates frame-level object instances based on a set of instance query and proposal pairs propagated from previous frames. Since the instance query-proposal pair is learned to represent one specific object, the object instance association is naturally achieved in parallel with segmentation and video temporal clues are elegantly exploited meanwhile.

clip-level methods, both of them inevitably need an explicit instance association step to fulfill object tracking. This generally requires to design a complicated association strategy to achieve good tracking performance, which is not trivial. More importantly, the explicit association step increases model complexity and slows inference speed. Furthermore, this extra step also indicates that the temporal clues intrinsic in videos are not well utilized, as the instance prediction is performed separately on each frame or each clip.

In this work, inspired by the recent success of query-based object detectors [11, 12], we propose a simple, fast and yet effective query-based framework for online VIS. Our system, dubbed as InsPro, segments and tracks objects in one shot through a designed instance query and proposal propagation strategy (Figure 1 (b)), which eliminates the explicit instance association step. Specifically, our approach generates frame-level object instances based on a set of instance query-proposal pairs propagated from previous frames. In the learning process, we develop several techniques to make sure that the generated instance query-proposal pair corresponds to one specific object across frames. Thus, when an object instance is generated using such a query-proposal pair on the current frame, it is automatically associated with its precursors on all previous frames. In this way, we achieve the implicit object association without a linking step. Meanwhile, the proposed instance query-proposal propagation mechanism also enables our VIS system to perform better in terms of object instance accuracy (see Table 1). This is because the instance query-proposal pair implicitly encodes one object's temporal and spatial information across all previous frames, which provides a very good prior for the model to infer the same object on the current frame. In this sense, our query-based VIS method actually implements an efficient way to exploit the intrinsic temporal clues in videos.

To fulfill the advantages of our VIS system, learning exclusive and expressive instance query-proposal pairs is the key. We develop several strategies to ensure learning effectiveness. First, we propose an intra-query attention module that enhances instance query with its predecessors encoding the same object. This explicitly aggregates long-range object information into the query, augmenting its representation capacity. Second, we design a temporally consistent matching mechanism to enforce the one-to-one correspondence between the instance query-proposal pair and a specific ground truth object across frames during training. Third, we propose a box deduplication loss to enlarge the distance between instance proposals. This helps suppress duplicate proposals on the same object and increase the exclusivity of the generated instance query-proposal pair.

To validate the effectiveness and efficiency of our InsPro, we conduct extensive experiments on two popular VIS benchmarks [1], *i.e.*, YouTube-VIS 2019 and YouTube-VIS 2021. Without bells-and-whistles, our InsPro with ResNet-50 [13] backbone achieves 43.2 AP on YouTube-VIS 2019 and 37.6 AP on YouTube-VIS 2021 respectively, outperforming all other online VIS models. Moreover, our lite variant, InsPro-lite, reaches 38.7 AP at impressive 45.7 FPS on YouTube-VIS 2019 on a Nvidia RTX2080Ti GPU.

2 Related Work

Frame-level VIS Methods mainly adopt a 'tracking-by-detection' paradigm and can run in an online fashion. They first generate instance predictions frame by frame and then perform explicit instance association. MaskTrack R-CNN [1] proposes the VIS task for the first time and provides an example VIS method. It simply adds an additional tracking head to Mask R-CNN [5] for instance association. Follow-up works [2, 3, 4] improve either the image instance segmentation model or the tracking algorithm to achieve better performance. On the other hand, some works [8, 14, 15, 16, 17] attempt to perform temporal feature fusion to improve instance segmentation and association. All these methods require additional modules to achieve explicit instance association, which expands model complexity and reduces inference speed. Additionally, they do instance segmentation on each frame independently, ignoring the temporal and spatial consistency between video frames. By contrast, our method performs the instance association implicitly through an instance query and proposal propagation mechanism, which is simpler and naturally exploits the temporal and spatial consistency in videos.

Clip-level VIS Methods take a 'clip-matching' paradigm, which process multiple frames within a clip simultaneously and then perform instance matching between clips to complete VIS. While some methods [7, 18, 9] propagate instance information within a clip with well-designed propagation modules to model temporal context, recent works [8, 10] utilize transformer [19] to model temporal context in an end-to-end manner. These methods normally need hand-crafted matching algorithms to complete instance association after getting the instances of each clip. Although they usually achieve high performance, they can only run in an offline mode, which restricts their application in limited areas. In contrast, our method achieves comparable performance but can run online.

Query-based Methods have attracted increasing attention in recent years. DETR [11] first introduces a query-based architecture with transformer [19] to reformulate object detection as a set prediction problem. It uses a set of learned queries interacting with image features to encode objects, and then directly outputs detection predictions by decoding the transformed queries. Following works [20, 21, 22, 23, 24] improve DETR in terms of either training efficiency or detection performance. Similarly, Sparse R-CNN [12] builds a query-based detector on top of R-CNN architecture [25, 26]. Its follow-up works [3, 27] extend it to instance segmentation and video object detection. TrackFormer [28], TransTrack [29] and MOTR [30] utilize DETR to build query-based multiple object tracking methods. Besides, Max-DeepLab [31] proposes a box-free panoptic segmentation method with external query. DAFL [32] uses a set of queries to encode pedestrian information for pedestrian attribute recognition. Query-based methods have shown great potential in computer vision due to their flexibility and simplicity. In this work, we develop a new query-based paradigm for VIS to achieve implicit tracking and video temporal information exploitation.

3 InsPro

We aim to design a simple and fast VIS system that performs instance association implicitly and exploits video temporal clues elegantly. To this end, we take a query-based VIS approach that predicts object instances on each frame based on a set of instance query-proposal pairs propagated from previous frames. In this section, we introduce our VIS system, InsPro, including an instance query and proposal propagation mechanism and an instance segmentation head. Meanwhile, we also describe those proposed techniques that make our propagation mechanism work well.

3.1 Instance Query and Proposal Propagation

The instance query and proposal propagation mechanism enables our VIS system to perform object instance association implicitly in parallel with instance segmentation. Since it is inspired by the recent query-based object detector Sparse R-CNN [12], we first review Sparse R-CNN.

Sparse R-CNN [12] formulates object detection as a set prediction problem and achieves state-of-the-art performance. It simplifies the detection pipeline and removes heuristic components like NMS.

(a) Overview of InsPro	(b) Details of SegHead

Figure 2: (a) Overview of our InsPro. It performs VIS by propagating instance query-proposal pairs across frames. $\boldsymbol{q}_{init} \in \mathbb{R}^{N \times C}$ and $\boldsymbol{p}_{init} \in \mathbb{R}^{N \times 4}$ are initial instance queries and proposals on the first video frame, respectively. They are used in SegHead to predict instance results $\boldsymbol{r}_0$ on frame I_0, and to produce updated $\boldsymbol{q}_0$ and $\boldsymbol{p}_0$ which are propagated to the next frame. By repeating this process, we complete the VIS task. (b) Details of SegHead. It is a multi-stage network, consisting of a dynamic instance interaction module (DIIM) and an instance segmentation module. The former transforms instance queries with RoI features of corresponding proposals and produces object features, while the latter predicts object instances based on the object features and conditional convolution [33].

118 Specifically, it first initializes a fixed set of learnable instance queries ($N \times C$, N denotes the number
119 of queries and C the query dimension) paired with learnable instance proposals ($N \times 4$) to describe
120 objects in an image. As illustrated in Figure 2 (b), each instance query is then convolved with the RoI
121 feature of the corresponding proposal to output a more discriminate feature $\boldsymbol{o}_t$ [12]. After multi-stage
122 iterative updating, the instance query encodes more accurate object appearance information while the
123 proposal captures more precise location information. Finally, through decoding the object feature $\boldsymbol{o}_t$
124 produced based on the instance query-proposal pairs, we get the detection results.

125 Inspired by the instance query-proposal representation of an object, we design a query-proposal
126 temporal propagation mechanism (as shown in Figure 2 (a)) to achieve implicit object instance associ-
127 ation and temporal cue utilization in VIS. Our key insight is that there is a one-to-one correspondence
128 between the learned instance query-proposal pair and a specific object. If we manage to preserve this
129 correspondence from the first frame to the one where the object disappears, then we realize object
130 tracking and object information propagation spontaneously.

131 To this end, we first initialize a set of instance queries $\boldsymbol{q}_{init} \in \mathbb{R}^{N \times C}$ and proposals $\boldsymbol{p}_{init} \in \mathbb{R}^{N \times 4}$ on
132 the first video frame I_0, where $\boldsymbol{q}_{init}$ and $\boldsymbol{p}_{init}$ are learnable parameters and arranged in pairs. After
133 learning, they are able to encode objects on the first frame. Decoding them with the first frame image
134 feature inside the SegHead, we obtain instance results $\boldsymbol{r}_0$ as well as a new set of updated pairs ($\boldsymbol{q}_0$,
135 $\boldsymbol{p}_0$). Then we propagate this pair set ($\boldsymbol{q}_0$, $\boldsymbol{p}_0$) to the next frame as input to the SegHead. Similarly,
136 we get the instance results $\boldsymbol{r}_1$ and another new set of ($\boldsymbol{q}_1$, $\boldsymbol{p}_1$) on this frame. Among them, the object
137 instance produced on this frame shares the same ID with the one on the previous frame *if they are*
138 *both decoded by the same slice of the instance queries.* In this way, we automatically link object
139 instances belonging to an identical object across frames and elegantly make use of object priors from
140 the past. Repeating the above process until the last video frame, we then accomplish the VIS task on
141 this video.

142 **Intra-query Attention**   Since frame-by-frame temporal propagation encodes only short-range
143 temporal cues, the instance query from just the last frame shows limitations in dealing with tough
144 scenarios, *e.g.*, occlusion and motion blur. To boost the representation capacity of instance query,
145 we augment it in practice with instance features from previous T frames. Specifically, we build a
146 feature bank that caches instance features from previous T frames and perform intra-query attention
147 inside this bank to aggregate long-range temporal cues into the current instance query, as shown in
148 the upper part of Figure 2 (b). Formally, at frame I_t, instance features $\boldsymbol{o}$ from previous T frames are

put together to form a feature bank $fb = \{o_{t-T+1}, \ldots, o_t\}$. Then, the enhanced instance query is computed as:

$$q_t^i = \frac{\sum_{n=0}^{T-1} o_{t-n}^i \exp(\varepsilon(o_{t-n}^i))}{\sum_{m=0}^{T-1} \exp(\varepsilon(o_{t-m}^i))} + o_t^i, \tag{1}$$

where i denotes the i-th query and ε is a linear transformation function. The enhanced q_t is basically a weighted sum of instance features inside the feature bank, and the weights are learned upon the quality of the queries. Experiments (Table 2 (b)) show that this augmentation improves the query representation capacity greatly.

3.2 Segmentation Head

The segmentation head transforms the instance query and performs instance segmentation on each frame. As illustrated in Figure 2 (b), it is a multi-stage network and has two main parts: a dynamic instance interaction module and an instance segmentation module.

Dynamic Instance Interaction Module transforms the instance query with the proposal RoI feature and yields object features. It has M stages to form an iterative structure. At the first stage, given a pair of instance queries $q_{t-1} \in \mathbb{R}^{N \times C}$ and proposals $p_{t-1} \in \mathbb{R}^{N \times 4}$ that propagated from the previous frame I_{t-1}, it first augments the instance queries by a self-attention module [19], which models the inter-query relations. At the same time, it extracts the RoI feature of each proposal on the feature map by RoIAlign [5]. Then, each enhanced instance query convolves with its corresponding RoI feature through dynamic convolution [34] to get the object feature $o_t \in \mathbb{R}^{N \times C}$. Since the object feature absorbs temporal cues encoded in instance queries, it has better representation ability than the single-frame RoI feature (see Table 2 (d)). The object feature is used to predict object instances in the following instance segmentation module, and the newly generated object boxes together with object features proceed as input to the next stage in the iterative process. At the final stage, the object feature is processed together with its precursors from previous frames through the aforementioned intra-query attention module, to produce instance queries for the next frame.

Instance Segmentation Module decodes the object feature o_t and produces VIS predictions. It has three main heads. While the classification head predicts object classes, the regression one generates object boxes and the predicted boxes at the final stage are passed to the next frame. Another mask head is responsible for producing instance masks through a conditional convolution [33] approach. Specifically, it first uses o_t to generate conditional convolution weights in weight generator. As shown in Figure 2 (b), it inputs o_t^i that represents the i-th object instance feature to the weight generator and outputs a set of convolution parameters ω_i. Meanwhile, it produces mask feature maps by transforming FPN [35] feature maps through a mask branch. Note that the output mask feature maps have 8 channels and a $\frac{1}{8}$ resolution of the input image, and are boosted by concatenating a 2-channel relative coordinates map. This relative coordinates map is computed using the center of predicted object boxes and provides strong location cues for predicting instance masks. Finally, we feed the combined feature maps $f_t^{mask} \in \mathbb{R}^{10 \times \frac{H}{8} \times \frac{W}{8}}$ and convolution parameters ω_i to a mask FCN head, predicting the i-th object instance mask via a conditional convolution:

$$m_t^i = \text{CondConv}(f_t^{mask}, \omega_i). \tag{2}$$

For more details about the instance segmentation, please refer to [33].

3.3 Temporally Consistent Matching

The key to the success of our InsPro is to make sure the evolving instance query-proposal pair corresponds to the same object across frames in a video. To ensure this, one technique we propose is temporally consistent matching. This technique matches predictions and ground truth during training, assigns each ground truth object a proper prediction, and propagates the matching made on previous frames to subsequent frames.

Specifically, given a training batch consisting of multiple consecutive frames, following [11, 12], we first compute the matching cost L_{match} between predictions and ground truth objects on the first

Figure 3: (a) Multiple duplicate boxes exist on the same object across frames. (b) After applying the proposed box deduplication loss (BDL) in training, the duplicate predictions are significantly suppressed along with temporal propagation.

frame:

$$\mathcal{L}_{match} = \lambda_{cls} \cdot \mathcal{L}_{cls} + \lambda_{L1} \cdot \mathcal{L}_{L1} + \lambda_{\text{giou}} \cdot \mathcal{L}_{\text{giou}}, \tag{3}$$

where $\mathcal{L}_{cls}$ is the focal loss [36] between predicted classifications and ground-truth labels, $\mathcal{L}_{L1}$ and $\mathcal{L}_{\text{giou}}$ are L1 loss and the generalized IoU loss [37] between predicted boxes and ground-truth boxes, respectively. λ_{cls}, λ_{L1} and λ_{giou} are loss weights and set as 2, 5, and 2, respectively. We search for the best bipartite matching that minimizes the matching cost L_{match} with the Hungarian algorithm [38]. After finding the best matching on the first frame, we propagate this matching to other frames. Concretely, on subsequent frames, if one ground truth object still exists, it will be matched to the prediction that is generated by the same instance query on the first frame. If there are new ground truth objects emerging, new matching will be made between the new objects and yet unmatched predictions. If a ground truth object disappears, its corresponding predictions will not participate in a new matching process. Through this temporally consistent matching mechanism, we bind one ground truth object to a single instance query during training.

3.4 Loss Function

Box Deduplication Loss Although the self-attention mechanism between queries has driven the model to generate fewer duplication predictions [11], we still observe multiple overlapped proposal boxes on the same object across many frames, as displayed in Figure 3 (a). We conjecture this is caused by those unmatched queries that cannot be pushed away from those matched queries due to lack of supervision. To address this problem, we propose a new box deduplication loss to push away prediction boxes in terms of the center-to-center distance between them. It is defined as:

$$\mathcal{L}_{dedup} = \max(\beta - \frac{c^2(b^i, \hat{b}^i_{neg})}{d^2(b^i)}, \ 0), \tag{4}$$

where b^i is a ground truth box, $\hat{b}^i_{neg}$ is a negative box that has the largest IoU with b^i among those unmatched predicted boxes, $c(\cdot)$ is the center distance, and $d(\cdot)$ is the diagonal length. β is set as 0.1. This loss penalizes the short distance between b^i and $\hat{b}^i_{neg}$, and drags all other duplicate boxes away from b^i [39]. With this new loss, our final box loss function is formed as:

$$\mathcal{L}_{box} = \lambda_{L1} \cdot \mathcal{L}_{L1} + \lambda_{\text{giou}} \cdot \mathcal{L}_{\text{giou}} + \lambda_{dedup} \cdot \mathcal{L}_{dedup}, \tag{5}$$

where λ_{L1} and λ_{giou} have the same values in Equation 3, and λ_{dedup} is set as 1.

Overall Loss Given the one-to-one matching results, the final loss on each training frame is a sum of classification, box and mask losses:

$$\mathcal{L} = \lambda_{cls} \cdot \mathcal{L}_{cls} + \lambda_{box} \cdot \mathcal{L}_{box} + \lambda_{dice} \cdot \mathcal{L}_{dice} + \lambda_{focal} \cdot \mathcal{L}_{focal}, \tag{6}$$

where $\mathcal{L}_{dice}$ and $\mathcal{L}_{focal}$ are dice loss [40] and focal loss [36] for foreground mask prediction, respectively. We set $\lambda_{box} = 1$, $\lambda_{dice} = 5$ and $\lambda_{focal} = 5$. Finally, the losses of all training frames inside a batch are summed together and normalized by the number of frames.

4 Experiments

4.1 Datasets and Evaluation Metrics

We evaluate our method on YouTube-VIS 2019 and 2021 benchmarks [1]. YouTube-VIS 2019 consists of 2,238 training videos and 302 validation videos, and labels 40 object categories. YouTube-VIS 2021 is an extended version, which comprises 2,985 training videos and 421 validation videos, and labels improved 40 categories. All videos in these two datasets are annotated every 5 frames with object bounding box, object category, instance mask and instance ID. Following [1], we report the video-level average precision (AP) and average recall (AR) on the validation sets as the evaluation metrics, where both accurate instance segmentation and instance association are necessary to achieve high performance.

4.2 Implementation Details

We implement our InsPro with detectron2 [41], and most hyperparameters are set following Sparse R-CNN [12] and CondInst [33] unless otherwise specified.

Training Details We employ AdamW [42] with an initial learning rate of 2.5×10^{-5} and weight decay 0.0001 as our model optimizer. We initialize our model with parameters pre-trained on COCO [43], and train it for 32k iterations where the learning rate is divided by 10 at iterations 28k and 24k, respectively. The training is performed end-to-end on 8 Nvidia RTX2080Ti GPUs and each GPU holds one mini-batch which contains three frame images randomly sampled from the same video. Data augmentation includes only random horizontal flip and multi-scale training where the training image is resized with the shortest side at least 288 and at most 512. Unless otherwise noted, our InsPro adopts 100 instance queries and ResNet-50 [13] as backbone in our experiments.

Inference Details In inference, we resize the frame image size to 640×360, which follows MaskTrack R-CNN [1]. The length of the feature bank is set to 18 by default. If the generated proposal box size exceeds the frame's, it will be reset to the frame size. No multi-scale testing is adopted in our experiments.

InsPro-lite we also build a lite version of our method, named InsPro-lite. In this variant, inspired by [27], we divide video frames into key frames and non-key frames, *i.e.*, we select one key frame per K frames in a video and treat other frames as non-key ones. K is 10 by default. On key frames, we conduct the dynamic instance interaction 6 times while only once on non-key frames. This takes advantage of the redundancy of videos and helps reduce inference computation time. Our InsPro-lite reaches a high inference speed of 45.7 FPS at a small accuracy loss (Table 1).

4.3 Main Results

We perform a thorough comparison of our InsPro to state-of-the-art VIS methods on YouTube-VIS 2019 and 2021. Existing VIS methods can be divided into two categories according to whether they run online or offline [46]. Since some methods [7, 9] also use 80k transformed COCO images [43] as extra training data to prevent overfitting to YouTube-VIS, for a fair comparison, we also report our results with and without extra COCO training data. Table 1 present all the results obtained with a ResNet-50 backbone on a Nvidia RTX2080Ti GPU.

YouTube-VIS 2019 Table 1 (a) shows the comparison between our InsPro and other state-of-the-art methods on YouTube-VIS 2019 validation set. We can see that, in the online group, our InsPro outperforms all other popular methods under the same data setting. Specifically, our InsPro achieves 40.2 AP without COCO data and 43.2 AP with COCO data respectively, surpassing other online VIS methods by a large margin. Even our lite version, InsPro-lite, performs better than all other online methods trained without COCO data, reaching 38.7 AP at an impressive speed of 45.7 FPS. Compared to those offline methods, our InsPro beats most of them and is only inferior to IFC [10] which takes a transformer-based approach to VIS. However, IFC is a clip-level method and can only run offline, which is not suitable in real-time video processing settings.

Table 1: Comparison of our InsPro to state-of-the-art methods. All methods use ResNet-50 as backbone. Y: YouTube-VIS train set. C: COCO train2017 images that contain YouTube-VIS categories. The inference speed is tested on a Nvidia RTX2080Ti GPU. $\ddagger$ indicates that the FPS is measured by parallel processing of images in one clip rather than sequential processing.

(a) Results on YouTube-VIS 2019 validation set. Methods with superscript '*' indicates using deformable convolution [44] in backbone.

Method	Online	Data	AP	AP_{50}	AP_{75}	AR_1	AR_{10}	FPS
STEm-Seg [7]	✗	$Y + C$	30.6	50.7	33.5	31.6	37.1	4.4
VisTR [8]	✗	Y	34.4	55.7	36.5	33.6	38.9	$30.0^{\ddagger}$
Propose-Reduce [9]	✗	$Y + C$	40.4	63.0	43.8	41.1	49.7	< 20
MaskProp* [18]	✗	Y	40.0	-	42.9	-	-	< 10
IFC [10]	✗	Y	41.0	62.1	45.4	**43.5**	**52.7**	$46.5^{\ddagger}$
EfficientVIS [45]	✗	Y	37.9	59.7	43.0	40.3	46.6	$36^{\ddagger}$
MaskTrack R-CNN [1]	✓	Y	30.3	51.1	32.6	31.0	35.5	26.1
SipMask [4]	✓	Y	33.7	54.1	35.8	35.4	40.1	30
STMask* [16]	✓	Y	33.5	52.1	36.9	31.1	39.2	28.6
SG-Net [2]	✓	Y	34.8	56.1	36.8	35.8	40.8	23.0
CrossVIS [14]	✓	Y	36.3	56.8	38.9	35.6	40.7	25.6
HybridVIS [17]	✓	$Y + C$	41.3	61.5	43.5	42.7	47.8	< 20
InsPro-lite	✓	Y	38.7	60.9	41.7	36.9	43.6	45.7
InsPro	✓	Y	40.2	62.9	43.1	37.6	44.5	26.3
InsPro	✓	$Y + C$	**43.2**	**65.3**	**48.0**	38.8	49.0	26.3

(b) Results on YouTube-VIS 2021 validation set.

Method	Online	Data	AP	AP_{50}	AP_{75}	AR_1	AR_{10}	FPS
IFC [10]	✗	Y	36.6	57.9	39.3	-	-	$46.5^{\ddagger}$
EfficientVIS [45]	✗	Y	34.0	57.5	37.3	**33.8**	**42.5**	$36^{\ddagger}$
MaskTrack R-CNN [1]	✓	Y	28.6	48.9	29.6	26.5	33.8	26.1
SipMask [4]	✓	Y	31.7	52.5	34.0	30.8	37.8	30
CrossVIS [14]	✓	Y	34.2	54.4	37.9	30.4	38.2	25.6
HybridVIS [17]	✓	$Y + C$	35.8	56.3	39.1	33.6	40.3	< 20
InsPro	✓	Y	36.1	57.6	39.6	30.9	40.4	26.3
InsPro	✓	$Y + C$	**37.6**	**58.7**	**40.9**	32.7	41.4	26.3

Table 2: Ablation studies.

(a) Effectiveness of instance query and proposal propagation, and temporally consistent matching (TCM).

	query	proposal	TCM	AP	AP_{50}	AP_{75}
(A)				24.0	41.3	24.2
(B)	✓	✓		36.3	56.3	38.9
(C)	✓	✓	✓	**37.4**	**57.6**	**41.1**
(D)	✓		✓	36.7	57.3	39.9
(E)		✓	✓	36.6	55.5	40.3

(b) Effectiveness of the intra-query attention. T is the length of the feature bank.

	AP	AP_{50}	AP_{75}	FPS
T=1	38.4	57.7	41.6	26.3
T=9	39.7	61.6	42.1	26.3
T=18	**40.2**	**62.9**	**43.1**	26.3
T=27	40.1	62.6	42.2	26.3
T=36	40.1	62.5	42.2	26.3

(c) Effectiveness of the proposed box deduplication loss (BDL).

	AP	AP_{50}	AP_{75}	FPS
w/o BDL	37.4	57.6	41.1	26.3
w/ BDL	**38.4**	**57.7**	**41.6**	26.3

(d) Comparison between 'track-by-detect' paradigm and our temporal propagation paradigm.

	AP	AP_{50}	AP_{75}	FPS
Track-by-detect	31.5	49.3	34.1	25.4
Ours	**37.4**	**57.6**	**41.1**	**26.3**

YouTube-VIS 2021 Table 1 (b) displays results on YouTube-VIS 2021 validation set. It shows a similar comparison pattern to YouTube-VIS 2019 and our InsPro achieves the state-of-the-art performance once again.

4.4 Ablation Study

We conduct extensive experiments on YouTube-2019 to study the effectiveness and individual performance contribution of our proposed modules.

Temporal Propagation and Matching   Our InsPro is built on the proposed mechanism of instance query and proposal temporal propagation. Table 2 (a) shows how this mechanism contributes to our high performance. In this table, method A represents the image instance segmentation baseline, where each frame is processed individually without any temporal propagation, and object instances generated on each frame are linked if they are produced from the same instance query slice. Since this method lacks the mechanism to ensure the instance query-proposal pair corresponds to the same object across frames, it only achieves 24.0 AP due to inaccurate instance association. By contrast, when we add the temporal propagation (method B), we can easily improve the performance significantly to 36.3 AP. This evidences the importance and effectiveness of the proposed temporal propagation technique in a query-based VIS framework. If we further adopts the temporally consistent matching strategy during training (method C), we achieve an even better performance of 37.4 AP.

We also analyze the separate performance of propagating only instance query (method D) or instance proposal (method E). The results show that these two settings achieve a similar performance boost (36.7 AP vs 36.6 AP). Applying them together yields 37.4 AP, bringing further performance gain.

Intra-query Attention   We perform intra-query attention inside a feature bank to augment the instance query so that it can capture long-range temporal cues. As we can see in Table 2 (b), this simple method works well and improves the performance considerably. In particular, $T = 1$ indicates no intra-query attention is used and 38.4 AP is achieved. When we increase the volume T of the feature bank, the performance also rises and saturates at 40.2 AP with $T = 18$. It is worthwhile to note that this lightweight yet effective intra-query attention operation brings almost no speed drop.

Box Deduplication Loss   We propose a box deduplication loss to suppress the duplicate proposal boxes on the same object across frames. While the qualitative results can be found in Figure 3, we show the quantitative comparison in Table 2 (c). We can see that supervising the learning with this loss during training can lead 1.0 AP improvement (38.4 AP vs 37.4 AP). This performance gain is brought by less false positives.

Track-by-Detect *vs*. Temporal Propagation   Despite the fact that our InsPro does not perform explicit instance association, it still outperforms all other online methods implementing explicit tracking or matching. To verify that our superior performance comes from the temporal propagation mechanism rather than the image instance segmentation model design, we compare our temporal propagation VIS approach to the typical 'track-by-detect' paradigm with the same instance segmentation baseline. We implement a 'track-by-detect' VIS system by replacing the Mask R-CNN part in MaskTrack R-CNN [1] with our instance segmentation model. In this case, the only independent variable is the object tracking method.

As shown in Table 2 (d), our InsPro surpasses the 'track-by-detect' model by a large margin even if our design is simpler and faster, which soundly proves the effectiveness of our method. We argue again this is because the evolving instance query-proposal pair in propagation encodes object temporal and spatial cues intrinsic in videos, whereas 'track-by-detect' methods are generally incapable of exploiting this advantage.

5   Conclusion

In this paper, we propose a simple, fast and yet effective query-based framework for online VIS. In this framework, we rely on a novel instance query and proposal propagation mechanism to undertake VIS, where we generate object instances based on a set of evolving instance query-proposal pairs propagated from previous frames. This mechanism enables our model not only to associate object instances implicitly, but to utilize video temporal cues elegantly. To make this propagation mechanism work well, we develop several modules to ensure that the learned instance query-proposal pair keeps being bound to one object, These modules include an intra-query attention unit, a temporally consistent matching mechanism and a box deduplication loss. Extensive experiments on YouTube-VIS 2019 and 2021 verify the effectiveness of our designs, and show that our InsPro achieves superior VIS performance, outperforming all other online VIS methods.

References

[1] Yang, L., Y. Fan, N. Xu. Video instance segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 5188–5197. 2019.

[2] Liu, D., Y. Cui, W. Tan, et al. Sg-net: Spatial granularity network for one-stage video instance segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9816–9825. 2021.

[3] Fang, Y., S. Yang, X. Wang, et al. Instances as queries. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 6910–6919. 2021.

[4] Cao, J., R. M. Anwer, H. Cholakkal, et al. Sipmask: Spatial information preservation for fast image and video instance segmentation. In *European Conference on Computer Vision*, pages 1–18. Springer, 2020.

[5] He, K., G. Gkioxari, P. Dollár, et al. Mask r-cnn. In *Proceedings of the IEEE international conference on computer vision*, pages 2961–2969. 2017.

[6] Bolya, D., C. Zhou, F. Xiao, et al. Yolact: Real-time instance segmentation. In *Proceedings of the IEEE/CVF international conference on computer vision*, pages 9157–9166. 2019.

[7] Athar, A., S. Mahadevan, A. Osep, et al. Stem-seg: Spatio-temporal embeddings for instance segmentation in videos. In *European Conference on Computer Vision*, pages 158–177. Springer, 2020.

[8] Wang, Y., Z. Xu, X. Wang, et al. End-to-end video instance segmentation with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 8741–8750. 2021.

[9] Lin, H., R. Wu, S. Liu, et al. Video instance segmentation with a propose-reduce paradigm. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 1739–1748. 2021.

[10] Hwang, S., M. Heo, S. W. Oh, et al. Video instance segmentation using inter-frame communication transformers. *Advances in Neural Information Processing Systems*, 34, 2021.

[11] Carion, N., F. Massa, G. Synnaeve, et al. End-to-end object detection with transformers. In *European conference on computer vision*, pages 213–229. Springer, 2020.

[12] Sun, P., R. Zhang, Y. Jiang, et al. Sparse r-cnn: End-to-end object detection with learnable proposals. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 14454–14463. 2021.

[13] He, K., X. Zhang, S. Ren, et al. Deep residual learning for image recognition. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 770–778. 2016.

[14] Yang, S., Y. Fang, X. Wang, et al. Crossover learning for fast online video instance segmentation. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 8043–8052. 2021.

[15] Fu, Y., L. Yang, D. Liu, et al. Compfeat: Comprehensive feature aggregation for video instance segmentation. In *Proceedings of the AAAI Conference on Artificial Intelligence*, vol. 35, pages 1361–1369. 2021.

[16] Li, M., S. Li, L. Li, et al. Spatial feature calibration and temporal fusion for effective one-stage video instance segmentation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11215–11224. 2021.

[17] Li, X., J. Wang, X. Li, et al. Hybrid instance-aware temporal fusion for online video instance segmentation. In *Proceedings of the AAAI Conference on Artificial Intelligence*. 2022.

[18] Bertasius, G., L. Torresani. Classifying, segmenting, and tracking object instances in video with mask propagation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 9739–9748. 2020.

[19] Vaswani, A., N. Shazeer, N. Parmar, et al. Attention is all you need. *Advances in neural information processing systems*, 30, 2017.

[20] Zhu, X., W. Su, L. Lu, et al. Deformable detr: Deformable transformers for end-to-end object detection. In *International Conference on Learning Representations*. 2020.

[21] Meng, D., X. Chen, Z. Fan, et al. Conditional detr for fast training convergence. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 3651–3660. 2021.

[22] Dai, Z., B. Cai, Y. Lin, et al. Up-detr: Unsupervised pre-training for object detection with transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 1601–1610. 2021.

[23] Dai, X., Y. Chen, J. Yang, et al. Dynamic detr: End-to-end object detection with dynamic attention. In *Proceedings of the IEEE/CVF International Conference on Computer Vision*, pages 2988–2997. 2021.

[24] Liu, S., F. Li, H. Zhang, et al. Dab-detr: Dynamic anchor boxes are better queries for detr. In *International Conference on Learning Representations*. 2021.

[25] Girshick, R., J. Donahue, T. Darrell, et al. Rich feature hierarchies for accurate object detection and semantic segmentation. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 580–587. 2014.

[26] Ren, S., K. He, R. Girshick, et al. Faster r-cnn: Towards real-time object detection with region proposal networks. *Advances in neural information processing systems*, 28, 2015.

[27] He, F., N. Gao, J. Jia, et al. Queryprop: Object query propagation for high-performance video object detection. In *Proceedings of the AAAI Conference on Artificial Intelligence*. 2022.

[28] Meinhardt, T., A. Kirillov, L. Leal-Taixe, et al. Trackformer: Multi-object tracking with transformers. *arXiv preprint arXiv:2101.02702*, 2021.

[29] Sun, P., J. Cao, Y. Jiang, et al. Transtrack: Multiple object tracking with transformer. *arXiv preprint arXiv:2012.15460*, 2020.

[30] Zeng, F., B. Dong, T. Wang, et al. Motr: End-to-end multiple-object tracking with transformer. *arXiv preprint arXiv:2105.03247*, 2021.

[31] Wang, H., Y. Zhu, H. Adam, et al. Max-deeplab: End-to-end panoptic segmentation with mask transformers. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 5463–5474. 2021.

[32] Jia, J., N. Gao, F. He, et al. Learning disentangled attribute representations for robust pedestrian attribute recognition. In *Proceedings of the AAAI Conference on Artificial Intelligence*. 2022.

[33] Tian, Z., C. Shen, H. Chen. Conditional convolutions for instance segmentation. In *European Conference on Computer Vision*, pages 282–298. Springer, 2020.

[34] Jia, X., B. De Brabandere, T. Tuytelaars, et al. Dynamic filter networks. *Advances in neural information processing systems*, 29, 2016.

[35] Lin, T.-Y., P. Dollár, R. Girshick, et al. Feature pyramid networks for object detection. In *Proceedings of the IEEE conference on computer vision and pattern recognition*, pages 2117–2125. 2017.

[36] Lin, T.-Y., P. Goyal, R. Girshick, et al. Focal loss for dense object detection. In *Proceedings of the IEEE international conference on computer vision*, pages 2980–2988. 2017.

[37] Rezatofighi, H., N. Tsoi, J. Gwak, et al. Generalized intersection over union: A metric and a loss for bounding box regression. In *Proceedings of the IEEE/CVF conference on computer vision and pattern recognition*, pages 658–666. 2019.

[38] Kuhn, H. W. The hungarian method for the assignment problem. *Naval research logistics quarterly*, 2(1-2):83–97, 1955.

[39] Hermans, A., L. Beyer, B. Leibe. In defense of the triplet loss for person re-identification. *arXiv preprint arXiv:1703.07737*, 2017.

[40] Milletari, F., N. Navab, S.-A. Ahmadi. V-net: Fully convolutional neural networks for volumetric medical image segmentation. In *2016 fourth international conference on 3D vision (3DV)*, pages 565–571. IEEE, 2016.

[41] Wu, Y., A. Kirillov, F. Massa, et al. Detectron2. `https://github.com/facebookresearch/detectron2`, 2019.

[42] Loshchilov, I., F. Hutter. Decoupled weight decay regularization. In *International Conference on Learning Representations*. 2018.

[43] Lin, T.-Y., M. Maire, S. Belongie, et al. Microsoft coco: Common objects in context. In *European conference on computer vision*, pages 740–755. Springer, 2014.

[44] Dai, J., H. Qi, Y. Xiong, et al. Deformable convolutional networks. In *Proceedings of the IEEE international conference on computer vision*, pages 764–773. 2017.

[45] Wu, J., S. Yarram, H. Liang, et al. Efficient video instance segmentation via tracklet query and proposal. In *Proceedings of the IEEE conference on computer vision and pattern recognition*. 2022.

[46] Luo, W., J. Xing, A. Milan, et al. Multiple object tracking: A literature review. *Artificial Intelligence*, 293:103448, 2021.