Adversarial Reweighting for Partial Domain Adaptation

Abstract

Partial domain adaptation (PDA) has gained much attention due to its practical setting. The current PDA methods commonly adapt the feature extractor by aligning the target and reweighted source domain distributions. In this paper, we experimentally find that the feature adaptation by the reweighted distribution alignment in the PDA methods is not robust to the "noisy" weights of source domain data, leading to negative domain transfer on some challenging benchmarks. To tackle the challenges, we propose a novel Adversarial Reweighting (AR) approach that adversarially learns the weights of source domain data to align the source and target domain distributions, and the transferable deep recognition network is learned on the reweighted source domain data. Based on this idea, we propose a training algorithm that alternately updates the parameters of network and optimizes the weights of source domain data. Extensive experiments show that our method achieves state-of-the-art results on the challenging benchmarks of ImageNet-Caltech, Office-Home, VisDA-2017, and DomainNet. Ablation studies also confirm the effectiveness of our approach.

1 Introduction

Deep learning has achieved impressive success in image recognition [15, 20, 36]. However, deep learning models often rely on massive labeled training data, requiring expensive and time-consuming labeling process. To alleviate the dependency of deep learning models on a large number of labeled data, domain adaptation (DA) [26] transfers the knowledge from a relevant source domain with rich labeled data to the target domain. The core of DA is to build a predictive model for the target domain using the training data of the source domain, and the model is expected to be robust to the distribution discrepancy (*a.k.a., domain shift*) between source and target domains. Domain adaptation methods often train the robust model by aligning distributions of different domains by moment matching [17, 19, 23, 27, 37, 45] or adversarial training [8, 24, 35, 37, 38, 39, 47]. The conventional closed-set DA methods generally assume that the source and target domains share the same label space. However, this assumption is often not realistic in practice. It is usually difficult to find a relevant source domain with identical label space as the target domain. This motivates the research on the learning problem of partial domain adaptation (PDA) [3, 46].

Partial domain adaptation is an important subcategory of domain adaptation. PDA [3, 4, 46] tackles the scenario that the label space of the target domain is a subset of that of the source domain. Partial domain adaptation is more challenging than vanilla closed-set domain adaptation. Because, besides the challenge of the domain shift, the existence of source-only classes that do not exist in the target domain can cause class-wise feature mismatch when aligning distributions. This potentially leads to *negative transfer* [26], *i.e.*, the DA approaches hurt the performance of learning in the target domain. To mitigate the negative transfer, current PDA methods [3, 4, 5, 21, 22, 43, 46] commonly reweight

the source domain data to decrease the importance of data belonging to the source-only classes. The target and reweighted source domain data are used to train the feature extractor by adversarial training [3, 4, 5, 22, 43, 46] or kernel mean matching [21] to align distributions.

In this paper, we observe that the above reweighted distribution alignment does not work well on challenging benchmarks of VisDA-2017 [31] and DomainNet [30]. Specifically, learning/adapting the feature extractor by aligning the feature distributions of the reweighted source and target domain data can even worsen the performance of baseline model without feature distribution alignment. We find that the above negative domain transfer effect is mainly because that the reweighted feature distribution alignment methods are not robust to the "noises" of source data weights, *i.e.*, some source-only-class data are mistakenly assigned with high weights.

To tackle the challenges in PDA, we propose a novel adversarial reweighting (AR) approach, which adversarially learns to reweight the source domain data for aligning the distributions of the source and target domains. Specifically, our approach relies on adversarial training to learn the weights of source domain data to minimize the Wasserstein distance between the reweighted source domain and target domain distributions. The weight learning process is conducted in an adversarial reweighting model, using the dual form of the Wasserstein distance. We then define a reweighted cross-entropy loss on the reweighted source domain data to train the transferable recognition network for the target domain. The network training and weight learning are performed alternately in an iterative training algorithm.

The current PDA methods [3, 4, 5, 21, 22, 43, 46] heuristically design source data weights based on the classifier [3, 4, 21, 22, 43] or discriminator [5, 46]. They then train the feature extractor using a reweighted distribution alignment loss defined on the target and reweighted source data. Different from them, first, we learn the weights of source data automatically in an adversarial reweighting model, instead of heuristically setting them. Second, our approach reduces the domain gap by reweighting the source domain data, instead of directly optimizing the feature extractor to match feature distributions. This strategy may mitigate the negative domain transfer when the source domain data contain "noisy" weights. Note that Balaji *et al.* [2] and Huang *et al.* [16] also align data distributions by data reweighing. Huang *et al.* [16] proposes a shallow method that reweights the source data using the density ratio estimated by kernel mean matching for closed-set DA. Differently, we reweight the source data using an adversarial reweighting model for PDA in deep learning framework. Balaji *et al.* [2] proposes a robust optimal transport model to decrease the importance of the outliers of target data in distribution alignment for closed-set DA. Different from Balaji *et al.* [2], we reweight the source domain data to decrease the importance of source-only-class data in the source classification loss to mitigate the negative transfer for PDA.

We conduct extensive experiments on five benchmark datasets (*i.e.*, Office-31, ImageNet-Caltech, Office-Home, VisDA-2017, and DomainNet). The results show that our method achieves state-of-the-art results on the challenging datasets of ImageNet-Caltech, Office-Home, VisDA-2017, and DomainNet, and competitive results on the less challenging dataset of Office-31. Ablation studies indicate that our method significantly outperforms its baseline on all datasets.

In the following sections, we discuss the limitations of feature adaptation by domain distribution alignment in Sect. 2. Section 3 presents the details of our approach. Section 4 reports the results and Section 5 concludes this work.

2   Limitations of Feature Adaptation by Domain Distribution Alignment

In this section, we first introduce the setting of PDA and summarize the popular reweighted distribution alignment methods for PDA [3, 4, 5, 21, 22, 46]. We then show the limitations of these PDA methods. In PDA, we are given a labeled dataset $\mathcal{S} = \{x_i^s, y_i^s\}_{i=1}^{n_s}$ from source domain and an unlabeled dataset $\mathcal{T} = \{x_j^t\}_{j=1}^{n_t}$ from target domain, where x^s and $x^t \in \mathbb{R}^d$ respectively denote the source and target data, $y_i^s \in \mathcal{Y}^s$ is the label of x_i^s, and $\mathcal{Y}^s = \{0, 1, \cdots, K\}$ is the label space of source domain. The goal is to train a recognition network to predict the label of x_j^t. Notably, in PDA, the target label space $\mathcal{Y}^t$ is a subset of $\mathcal{Y}^s$, *i.e.*, $\mathcal{Y}^t \subset \mathcal{Y}^s$, which is different from the setting ($\mathcal{Y}^t = \mathcal{Y}^s$) in the closed-set DA. The PDA methods often use a feature extractor F to extract the features of data, a classifier C to predict class labels, and a discriminator D to discriminate domains.

Summary of reweighted distribution alignment methods in PDA. The challenges of PDA come from two aspects: the domain shift between source and target domains, and the negative effect

Table 1: Accuracy (%) comparisons for different reweighted distribution alignment losses and w/o distribution alignment for PDA.

Alignment loss	Office-31	ImageNet-Caltech	Office-Home	VisDA-2017	DomainNet
w/o alignment	94.23	77.78	70.72	**75.66**	**63.23**
MMD	94.26	79.50	**71.69**	46.37	62.79
PADA [4]	94.14	75.32	69.32	61.69	55.36
BAA [22]	**94.91**	**79.72**	71.26	59.86	60.20

of source-only-class data in domain adaptation. To tackle these challenges, most popular PDA methods (*e.g.*, SAN [3], PADA [4], ETN [5], DRCN [21], BAA [22], and IWAN [46]) commonly adapt the feature extractor by minimizing the feature distribution distance between the reweighted source domain and the target domain, measured by *the reweighted distribution alignment losses*. The weights in the reweighted distribution alignment losses are usually designed based on the output of the classifier or the discriminator. The widely adopted distribution distance metrics include the Maximization Mean Discrepancy (MMD) and the Jensen–Shannon (JS) divergence. Minimizing the MMD matches the kernel mean embedding of distributions in the Reproducing Kernel Hilbert Space. Minimizing the JS divergence is equivalent to the adversarial training as in the Generative Adversarial Network [10]. More comparisons of the PDA methods are given in Supp. A. We observe that adapting the feature extractor by the reweighted distribution alignment faces great challenges on some benchmark datasets, which will be discussed in the following.

Adapting feature extractor by reweighted distribution alignment may lead to negative domain transfer. If we ignore the domain shift and the mismatch of label space, the PDA degenerates to a typical semi-supervised learning problem. Therefore, the semi-supervised learning approach based on the cross-entropy loss on labeled data (source domain) and the conditional entropy on unlabeled data (target domain) [11], is naturally the baseline of PDA methods. We observe that additionally minimizing the reweighted distribution alignment losses by the feature extractor worsens the performance of the baseline on some challenging datasets with large domain gaps, *e.g.*, VisDA-2017 and DomainNet, as shown in Table 1. This indicates that adapting the feature extractor by the reweighted distribution alignment losses leads to negative transfer on the datasets. In Table 1, we report the average classification accuracies for different reweighted distribution alignment losses on five benchmark datasets. The reweighted distribution alignment losses include the reweighted adversarial training losses in PADA [4] and BAA [22], and the reweighted MMD loss [21]. The source data weights in these losses are designed based on the classifier, as in [3, 4, 21, 22], which seems to yield better performance than that based on the discriminator. We also give the full results and the source code

(a) S→R   (b) C→P

Figure 1: The results for reweighted distribution alignment losses with generated source data weights with varying noise levels in the tasks of (a) S→R (VisDA-2017) and (b) C→P (DomainNet).

in Supp. B. From Table 1, it can be observed that the domain gaps on VisDA-2017 and DomainNet datasets are large, and adapting the feature extractor with all reweighted distribution alignment losses degrades the performance of the baseline. Even on Office-31, ImageNet-Caltech, and Office-Home, adapting with the losses can only marginally improve the performance of the baseline.

Adapting feature extractor by reweighted distribution alignment is not robust to noisy weights. In the methods of [3, 4, 21, 22], the weight of source domain data (x_i^s, y_i^s) is defined as the average predicted probability for category of y_i^s on the target domain data, *i.e.*, the y_i^s-th element of $\frac{1}{n_t} \sum_{j=1}^{n_t} C(F(x_j^t))$. If the domain gap is large, the predictions may not be reliable on the target domain. Therefore, the designed weights may contain "noises", *e.g.*, some source-only-class data may be assigned with large weights. We analyze that the ineffectiveness of adapting the feature extractor by the reweighted distribution alignment could be because it is not robust to the "noisy" weights. To illustrate this, we simulate the source domain data weights with different noise levels.

Figure 2: Architecture of our Adversarial Reweighting approach for PDA. Red (resp. blue) arrows indicate the computational flow for source (resp. target) domain data. Both source and target images are mapped to feature space by the feature extractor. Our adversarial reweighting model automatically reweights the importance of source domain data to match the target domain distribution in feature space to decrease the importance of the data of source-only classes. We define a reweighted cross-entropy loss on the reweighted source domain data distribution and the conditional entropy losses on target domain data to learn a transferable recognition network for the target domain.

The weights of source domain data of the source-only classes (resp. shared classes) are defined as $p/(K - |\mathcal{Y}^t|)$ (resp. $(1 - p)/|\mathcal{Y}^t|$), for a noise level $p \in [0, 1]$. If $p = 0$, the source domain data of source-only classes are ideally assigned with weights of 0, and as the p increases, these data are assigned with larger weights, which are taken as the "noisy" weights. Figure 1 shows the results for different reweighted distribution alignment losses with the generated weights in varying noise levels. We observe that the results for all reweighted distribution alignment losses decrease as the noise level p increases. We also compute the sum of weights defined in [3, 4, 21, 22] over the source-only classes for approaches in Table 1, and the values (can be taken as noise levels of weights) in task S→R (resp. C→P) are larger than 0.3 (resp. 0.4). This may explain the observation that adapting the feature extractor by the reweighted distribution alignment degrades the performance of domain adaptation on these challenging datasets due to the "noises" in weights.

The above findings indicate that partial domain adaptation is still an unsolved problem. We need to rethink it and propose some new ideas.

3 Adversarial Reweighting for Partial Domain Adaptation

According to the observations in Sect. 2, adapting the feature extractor by the reweighted distribution alignment losses may cause negative domain transfer, when the domain gaps are large. In this work, we propose a novel adversarial reweighting (AR) approach for PDA, which relies on adversarial learning of source data weights for aligning the distributions of source and target domain features. Figure 2 illustrates the idea of our approach. We map the source and target data to the feature space by the feature extractor F. We then design an adversarial reweighting model to reweight the importance of the source domain data in order to match the target domain distribution in the feature space. In this adversarial reweighting model, we reduce the domain gap by reweighting the source domain data features, instead of adapting the feature extractor. We define a reweighted cross-entropy loss on the source domain data (with the weights learned by the adversarial reweighting model) and a conditional entropy loss on the target domain data to learn a transferable recognition network for the target domain. In the following, we first introduce our network training loss, then discuss the detailed adversarial reweighting model, and finally present our training algorithm.

3.1 Loss for Training Recognition Network

The loss for training the recognition network of our approach is the combination of the reweighted cross-entropy loss on source domain and the conditional entropy loss on target domain, defined by

$$\mathcal{L}(\theta_F, \theta_C, \mathbf{w}) = \frac{1}{n_s} \sum_{i=1}^{n_s} w_i \mathcal{J}(C(F(x_i^s; \theta_F); \theta_C), y_i^s) + \frac{1}{n_t} \sum_{j=1}^{n_t} H(C(F(x_j^t; \theta_F); \theta_C)), \quad (1)$$

where $\mathcal{J}(\cdot, \cdot)$ is the cross-entropy loss defined by $\mathcal{J}(\mathbf{p}, y) = -\sum_k \mathbb{I}_{\{y=k\}} \log p_k$, $H(\cdot)$ is the conditional entropy defined as $H(\mathbf{p}) = -\sum_k p_k \log p_k$ for distribution $\mathbf{p} = (p_1, p_2, \cdots, p_K)$, $\mathbf{w} = (w_1, w_2, \cdots, w_{n_s})^T$ is the weights specifying the importance of source domain data such that

$\sum_{i=1}^{n_s} w_i = n_s$, and θ_F and θ_C are respectively the parameters of F and C. The weights are learned in an adversarial reweighting model in Sect. 3.2. Minimizing the reweighted cross-entropy loss enforces the recognition network being able to predict the labels of input images. Minimizing the conditional entropy loss encourages the low-density separation between classes [11] on target domain. Following [46], we only use the conditional entropy loss to update θ_F.

3.2 Adversarial Reweighting Model

Following [5], we assume that the source domain data of shared classes $\mathcal{Y}^t$ are closer to the target domain data than those source domain data belonging to the source-only classes $\mathcal{Y}^s \backslash \mathcal{Y}^t$. To decrease the importance of the source-only-class data and meanwhile reduce the domain shift, we learn the weights of source domain data by minimizing the Wasserstein distance between the reweighted source domain distribution and target domain distribution. The weight learning process is formulated as an adversarial reweighting model. We first introduce the Wasserstein distance.

Wasserstein distance. The Wasserstein distance is a metric that measures the discrepancy between two distributions. The Wasserstein distance between distributions μ and ν is defined by $W(\mu, \nu) = \min_{\pi \in \Pi} \mathbb{E}_{(x,y) \sim \pi} [\|x - y\|]$, where Π is the set of couplings of μ and ν, *i.e.*, $\Pi = \{\pi | \int \pi(x, y) dy = \mu(x), \int \pi(x, y) dx = \nu(y)\}$, and $\|\cdot\|$ is the l_2-norm. Leveraging the Kantorovich-Rubinstein duality, the Wasserstein distance has the dual form of $W(\mu, \nu) = \max_{\|f\|_L \leq 1} \mathbb{E}_{x \sim \mu}[f(x)] - \mathbb{E}_{x' \sim \nu}[f(x')]$, where the maximization is over all 1-Lipschitz functions $f : \mathbb{R}^d \to \mathbb{R}$. Following [14], for computing the Wasserstein distance, we parameterize f by a neural network D (discriminator) with parameters θ_D. Then, the Wasserstein distance becomes

$$W(\mu, \nu) \approx \max_{\theta_D \in \Theta} \mathbb{E}_{x \sim \mu}[D(x; \theta_D)] - \mathbb{E}_{x' \sim \nu}[D(x'; \theta_D)], \tag{2}$$

where $\Theta = \{\theta_D : \|D(\cdot; \theta_D)\|_L \leq 1\}$. We enforce the constraint in Eq. (2) with the gradient penalty technique as in [14]. Equation (2) allows us to approximately compute the Wasserstein distance using gradient-based optimization algorithms on large-scale datasets. We give more details for computing the Wasserstein distance in Supp. C. Compared with the other popular statistical distances, *e.g.*, the JS divergence, the Wasserstein distance enjoys better continuity for learning distributions [1, 41].

Adversarial reweighting. Our adversarial reweighting model is defined in the feature space. We denote the extracted feature as $z_i^s = F(x_i^s; \theta_F)$ and $z_j^t = F(x_j^t; \theta_F)$ for source and target domain data. The empirical distribution of the target domain data $\mathcal{T}$ is denoted as $\mathcal{P}_{\mathcal{T}} = \frac{1}{n_t} \sum_{j=1}^{n_t} \delta(z_j^t)$, where $\delta(\cdot)$ is the Dirac delta function. The reweighted source domain distribution is denoted as $\mathcal{P}_{\mathcal{S}}(\mathbf{w}) = \frac{1}{n_s} \sum_{i=1}^{n_s} w_i \delta(z_i^s)$. Different from the heuristic ways to design the weights $\mathbf{w}$ in current PDA methods, we automatically learn the weights in the following principled model. Based on the aforementioned assumption that the source-only-class data are more distant from target domain data than the source data of shared classes, we minimize the Wasserstein distance between the reweighted source domain distribution and target domain distribution to learn the weights as follows,

$$\min_{\mathbf{w} \in \mathcal{W}} W(\mathcal{P}_{\mathcal{S}}(\mathbf{w}), \mathcal{P}_{\mathcal{T}}). \tag{3}$$

To avoid the mode collapse, *i.e.*, the reweighted distribution is only supported on few data, we enforce $\sum_{i=1}^{n_s} (w_i - 1)^2 < \rho n_s$. Then, the solution space is $\mathcal{W} = \{\mathbf{w} : \mathbf{w} = (w_1, w_2, \cdots, w_{n_s})^T, w_i \geq 0, \sum_{i=1}^{n_s} w_i = n_s, \sum_{i=1}^{n_s} (w_i - 1)^2 < \rho n_s\}$. With the approximation of the dual form in Eq. (2), Eq. (3) is transformed to the following adversarial reweighting model,

$$\min_{\mathbf{w} \in \mathcal{W}} \max_{\theta_D \in \Theta} \frac{1}{n_s} \sum_{i=1}^{n_s} w_i D(z_i^s; \theta_D) - \frac{1}{n_t} \sum_{j=1}^{n_t} D(z_j^t; \theta_D). \tag{4}$$

In Eq. (4), the discriminator is trained to maximize (resp. minimize) the average of its outputs on the source (resp. target) domain to discriminate the source and target domains. Adversarially, the source data weights are learned to minimize the reweighted average of the outputs of the discriminator on the source domain. As a result, the source data (closer to the target domain) with smaller discriminator outputs will be assigned with larger weights. Therefore, defining the reweighted cross-entropy loss on the reweighted source data distribution encourages the transferability of the trained recognition network for the target domain. We will discuss the adversarial training of Eq. (4) in Sect. 3.3.

Automatically adjusting ρ. The proper magnitude of ρ is important to our method. If the ratio $(|\mathcal{Y}^t|/|\mathcal{Y}^s|)$ of the sizes of label spaces of target to source domains is large, ρ needs to be small to force more source data to contribute to the reweighted cross-entropy loss, and vice versa. Since the target label space is unknown, we automatically adjust ρ to enforce the computed Wasserstein distance (the loss value in Eq. (4) and is denoted as A^ρ) in a preset interval $[A^{low}, A^{up}]$. To do this, we choose an initial value ρ^0 of ρ and a constant $c > 1$, and adjust ρ as follows. If $A^\rho > A^{up}$ (resp. $A^\rho < A^{low}$), we adjust ρ by $\rho = c\rho$ (resp. $\rho = \rho/c$) and resolve Eq. (4). The adjustment is performed till $A^{low} \leq A^\rho \leq A^{up}$. We set $A^{up} = 5.0, A^{low} = -5.0, c = 1.2$, and $\rho^0 = 5.0$. We show that the performance of our method is not sensitive to these hyper-parameters, in Sect 4.2.

3.3 Training Algorithm

To train the recognition network to minimize the loss in Eq. (1), we alternately optimize the network parameters (θ_F, θ_C) and learn the weights $\mathbf{w}$ by fixing others as known. We initialize $\mathbf{w}$ by $w_i = 1$ for all i. Then, we alternately run the following two procedures when training the network.

Updating θ_F and θ_C with fixed w. Fixing $\mathbf{w}$, we update θ_F and θ_C to minimize the loss in Eq. (1) for M steps, using the mini-batch stochastic gradient descent algorithm.

Updating w with fixed θ_F and θ_C. Fixing θ_F and θ_C, we extract the features for all training data on both source and target domains, and learn $\mathbf{w}$ in Eq. (4). Since Eq (4) is a min-max optimization problem, we can alternately optimize the weights $\mathbf{w}$ and the parameters θ_D of the discriminator by fixing the other one as known. For reducing the computational cost, we only perform the alternate optimization once, which yields satisfactory performance in experiments. Therefore, we first fix $w_i = 1$ for all i and optimize θ_D to maximize the objective function in Eq. (4) using the gradient penalty technique, as in [14]. Then, fixing the discriminator, we optimize $\mathbf{w}$ as follows. We denote $d_i = D(z_i^s; \theta_D)$ and $\mathbf{d} = (d_1, d_2, \cdots, d_{n_s})^T$. The optimization problem for $\mathbf{w}$ becomes

$$\min_{\mathbf{w}} \mathbf{d}^T \mathbf{w}, \quad s.t. \ w_i \geq 0, \sum_{i=1}^{n_s}(w_i - 1)^2 \leq \rho n_s, \sum_{i=1}^{n_s} w_i = n_s. \tag{5}$$

Equation (5) is a second-order cone program. We use the CVXPY [7] package to solve Eq. (5). We also automatically adjust ρ as in Sect. 3.2.

We give the pseudo-code of the training algorithm in Supp. D. When the size of source domain dataset is larger than 100k, solving Eq. (5) for all source data at once is infeasible. In such case, we randomly sample a subset (with size N) of the source dataset to update their weights w, and then update θ_F and θ_C using them, and iterate these two above procedures.

4 Experiments

We conduct experiments on five benchmark datasets to evaluate our adversarial reweighting (AR) approach, and compare it with state-of-the-art PDA methods. The code will be released online.

Datasets. Office-31 dataset [33] contains 4,652 images of 31 categories, collected from three domains: Amazon (A), DSLR (D), and Webcam (W). Following [3], we select images from the 10 categories shared by Office-31 and Caltech-256 [12] to build new target domains. **ImageNet-Caltech** is built with ImageNet (I) [32] and Caltech-256 (C) [12], respectively including 1000 and 256 classes. We utilize the 84 shared classes to build the target domain. As most networks are pre-trained on the training set of ImageNet, we use images from ImageNet validation set to build the target domain for task C→I. **Office-Home** [40] consists of four domains: Artistic (Ar), Clip Art (Cl), Product (Pr), and Real-World (Rw), sharing 65 classes. We use images of the first 25 classes in alphabetical order as the target domain. **VisDA-2017** [31] is a large-scale challenging dataset, containing two domains: synthetic (S) and real (R), with 12 classes. We use the first 6 classes in alphabetical order as the target domain. **DomainNet** [30] is another large-scale challenging dataset, composed of six domains with 345 classes. Since the labels of some domains and classes are very noisy, we follow [34] to adopt four domains (Clipart (C), Painting (P), Real (R), and Sketch (S)) with 126 classes. We use the first 40 classes in alphabetical order to build the target domain. On these datasets, we set every domain as the source domain in turn and use each of the rest domain(s) to build the target domain.

Network structure. For the feature extractor F, we use the ResNet-50 [15] pre-trained on ImageNet [32], which excludes the last fully-connected layer. Following [13], we use the spherical

Table 2: Accuracy (%) on Office-Home for partial domain adaptation.

Method	Ar→Cl	Ar→Pr	Ar→Rw	Cl→Ar	Cl→Pr	Cl→Rw	Pr→Ar	Pr→Cl	Pr→Rw	Rw→Ar	Rw→Cl	Rw→Pr	Avg
ResNet-50 [15]	46.33	67.51	75.87	59.14	59.94	62.73	58.22	41.79	74.88	67.40	48.18	74.17	61.35
ADDA [39]	45.23	68.79	79.21	64.56	60.01	68.29	57.56	38.89	77.45	70.28	45.23	78.32	62.82
CDAN+E [24]	47.52	65.91	75.65	57.07	54.12	63.42	59.60	44.30	72.39	66.02	49.91	72.80	60.73
IWAN [46]	53.94	54.45	78.12	61.31	47.95	63.32	54.17	52.02	81.28	76.46	56.75	82.90	63.56
SAN [3]	44.42	68.68	74.60	67.49	64.99	77.80	59.78	44.72	80.07	72.18	50.21	78.66	65.30
PADA [4]	51.95	67.00	78.74	52.16	53.78	59.03	52.61	43.22	78.79	73.73	56.60	77.09	62.06
ETN [5]	59.24	77.03	79.54	62.92	65.73	75.01	68.29	55.37	84.37	75.72	57.66	84.54	70.45
DRCN [21]	54.00	76.40	83.00	62.10	64.50	71.00	70.80	49.80	80.50	77.50	59.10	79.90	69.00
SAFN [42]	58.93	76.25	81.42	70.43	**72.97**	77.78	72.36	55.34	80.40	75.81	60.42	79.92	71.83
RTNet$_{adv}$ [6]	63.20	80.10	80.70	66.70	69.30	77.20	71.60	53.90	84.60	77.40	57.90	85.50	72.30
BAA [22]	56.20	79.55	86.21	70.86	69.94	81.06	72.51	57.91	86.47	77.10	59.34	83.64	73.40
DPDAN [43]	59.40	–	79.04	–	–	–	–	–	81.79	76.77	58.67	82.18	–
Baseline	61.61	78.21	86.20	73.19	71.76	79.62	75.11	59.76	86.31	79.16	61.67	83.59	74.68
AR (ours)	**67.40**	**85.32**	**90.00**	**77.32**	70.59	**85.15**	**78.97**	**64.78**	**89.51**	**80.44**	**66.21**	**86.44**	**78.29**

Table 3: Accuracy (%) on DomainNet for partial domain adaptation.

Method	C→P	C→R	C→S	P→C	P→R	P→S	R→C	R→P	R→S	S→C	S→P	S→R	Avg
ResNet-50 [15]	41.21	60.01	42.13	54.52	70.80	48.32	63.1	58.63	50.26	45.43	39.3	49.75	51.96
DANN [9]	27.83	36.64	29.91	31.79	41.98	36.58	47.64	46.81	40.85	25.82	29.54	32.72	35.68
CDAN+E [24]	37.46	48.26	46.61	45.50	60.96	52.63	62.01	60.63	54.74	35.37	38.50	43.63	48.86
SAN [3]	34.35	51.62	46.23	57.13	70.21	58.25	69.61	67.49	67.88	41.69	41.15	48.44	54.50
PADA [4]	22.49	32.85	29.95	25.71	56.47	30.45	65.28	63.35	54.17	17.45	23.89	26.91	37.41
BAA [22]	43.02	61.87	53.28	58.89	70.49	61.88	74.43	71.00	**72.42**	46.64	34.8	48.13	58.07
Baseline	49.40	65.69	**58.89**	65.92	74.82	70.77	75.87	70.72	68.26	50.45	**55.70**	**62.23**	64.06
AR (ours)	**52.66**	**68.24**	58.29	**66.78**	**77.53**	**74.38**	**76.70**	**71.77**	70.48	**53.66**	53.60	61.57	**65.47**

logistic layer as the classifier C. We also set the radius in the spherical logistic layer as the lower bound deduced in [13]. For the discriminator D, we use the same architecture with [8] (three fully connected layers with 1024, 1024 and 1 nodes), excluding the sigmoid function in the last layer.

Implementation details. We implement our method using Pytorch [29] on a Nvidia Tesla v100 GPU. We use the SGD algorithm with momentum 0.9 to update θ_F and θ_C. The learning rate of θ_C is ten times of that of θ_F. θ_D is updated by the Adam [18] algorithm with learning rate 0.001. Following [8], we adjust the learning rate η of θ_C by $\eta = \frac{0.01}{(1+10p)^{-0.75}}$, where p is the training progress linearly changing from 0 to 1. We set the batchsize to 36, $M = 500$, and $N = 36M$.

4.1 Results

The results on Office-Home and DomainNet are reported in Tables 2 and 3, respectively. The results on Office-31, ImageNet-Catech, and VisDA-2017 are reported in Table 4. Note the results of the compared methods on DomainNet in Table 3 are obtained by running their official codes on DomainNet dataset. We can observe that on ImageNet-Caltech, Office-Home, VisDA-2017, and DomainNet, our method of AR achieves state-of-the-art (SOTA) classification accuracies of 84.69%, 78.29%, 83.62%, and 65.47%, respectively. On Office-31, the result (96.93%) achieved by our AR is also competitive compared with the results of previous SOTA methods. It is worth noting that on VisDA-2017 datasets, our approach outperforms the previous SOTA method DRCN [21] with a large margin (17.92%). On ImageNet-Caltech, Office-Home, and DomainNet datasets, our proposed AR also significantly outperforms BAA [22] by 3.53%, 4.89%, and 7.40%, respectively. These performance improvements achieved by our approach imply the effectiveness of our method.

In Tables 2, 3, and 4, the Baseline denotes the approach that uses cross-entropy instead of the reweighted cross-entropy in the training loss of Eq (1). The other components of the Baseline and AR are the same. Our AR improves the classification accuracies of the Baseline by 3.61%, 1.41%, 5.27%, 3.59%, and 7.94% on Office-Home, DomainNet, Office-31, ImageNet-Caltech, and VisDA-2017,

Table 4: Accuracy (%) on Office-31, ImageNet-Caltech, and VisDA-2017 for PDA.

Method	Office-31							ImageNet-Caltech			VisDA-2017		
	A→D	A→W	D→A	D→W	W→A	W→D	Avg	C→I	I→C	Avg	R→S	S→R	Avg
ResNet-50 [15]	83.44	75.59	83.92	96.27	84.97	98.09	87.05	71.29	69.69	70.49	64.28	45.26	54.77
DAN [23]	61.78	59.32	74.95	73.90	67.64	90.45	71.34	60.13	71.30	65.72	68.35	47.60	57.98
DANN [9]	81.53	73.56	82.78	96.27	86.12	98.73	86.50	67.71	70.80	69.23	73.84	51.01	62.43
IWAN [46]	90.45	89.15	95.62	99.32	94.26	99.36	94.69	73.33	78.06	75.70	71.30	48.60	59.95
SAN [3]	94.27	93.90	94.15	99.32	88.73	99.36	94.96	75.26	77.75	76.51	69.70	49.90	59.80
PADA [4]	82.17	86.54	92.69	99.32	95.41	**100.0**	92.69	70.48	75.03	72.76	76.50	53.50	65.00
ETN [5]	95.03	94.52	96.21	**100.0**	94.64	**100.0**	96.73	74.93	83.23	79.08	–	–	–
DRCN [21]	86.00	88.50	95.60	**100.0**	95.80	**100.0**	94.30	78.90	75.30	77.10	73.20	58.20	65.70
RTNet$_{adv}$ [6]	96.20	**97.60**	92.30	**100.0**	95.40	**100.0**	97.20	–	–	–	–	–	–
BAA [22]	93.63	93.90	94.89	**100.0**	94.78	**100.0**	96.20	79.34	82.97	81.16	–	–	–
DPDAN [43]	96.27	96.82	**96.35**	**100.0**	95.62	**100.0**	**97.51**	–	–	–	–	65.26	–
Baseline	80.89	87.12	94.05	94.58	93.95	99.36	91.66	79.60	82.59	81.10	66.63	84.72	75.68
AR (ours)	**96.82**	93.54	95.51	**100.0**	**96.04**	99.67	96.93	**82.24**	**87.12**	**84.69**	78.52	88.75	83.62

(a) (b) (c) (d)

Figure 3: (a) Results for different reweighting strategies. (b-d) Accuracy with varying number of target classes (b), convergence of target errors (c), and sensitivity analysis of hyper-parameters of our approach (d) in task Ar→Cl on Office-Home.

respectively. The accuracy boosts over the Baseline achieved by our method on all five datasets indicate that the negative transfer can be mitigated in our approach.

4.2 Analysis

Comparison with the other reweighting strategies. We compare different reweighting strategies for obtaining the weights in our loss of Eq. (1), including our adversarial reweighting (AR), reweighting based on the classifier as in [3, 4, 21, 22], and reweighting by the output of discriminator on source data as in [46]. The details of these strategies are given in Supp. A. The results in Fig. 3(a) show that our adversarial reweighting significantly outperforms the other two reweighting strategies on VisDA-2017 and Office-Home datasets. This confirms that our adversarial reweighting strategy of learning source data weights is more effective than the compared heuristic weight setting strategies.

Accuracy with varying number of target classes. We study our methods with different numbers of target classes in Fig. 3(b). Our method of AR significantly outperforms the Baseline when the number of classes is smaller than 35. When the number of classes is larger in the target domain, the difference in label space becomes smaller, and our proposed AR devised for PDA can only marginally outperform the baseline. This shows that our method is effective for PDA when the label space mismatch between the source domain and the target domain is larger.

Convergence. In Fig. 3(c), we take the task Ar→Cl (Office-Home) as an example to study the convergence of our method. The approach of "ResNet-50" that trains the network using only source data converges fast but has high target error (the test error on target domain). Our proposed AR achieves the lowest target error. We observe that our AR converges slightly slower than the Baseline, which may be because the source data weights in our reweighted cross-entropy loss are updated throughout the training process. We report more empirical evidence, *e.g.*, the training loss, for justifying the convergence of the training algorithm in Supp. E.

(a) Cost   (b) ResNet-50   (c) Baseline   (d) AR

Figure 4: (a) Computational cost of PDA methods in task Ar→Cl on Office-Home. (b-d) The t-SNE visualization of the learned source (blue) and target features (red) by ResNet-50 (b), Baseline (c), and AR (d) in task Ar→Cl on Office-Home.

(a) Ar→Cl (65→25)   (b) S→R (12→6)

Figure 5: The t-SNE visualization of learned source data weights in tasks (a) Ar→Cl (Office-Home) and (b) S→R (VisDA-2017). In both Fig. (a) and Fig. (b), the left figure plots the learned source (blue) and target (brown) features. The right figure plots the weighted source (blue) features and target (brown) features, where the source points with more clear blue color are with larger weights.

Sensitivity of hyper-parameters. We testify the sensitivity of hyper-parameters A^{up}, A^{low}, and ρ^0 mentioned in Sect. 3.2, as in Fig. 3(d). Figure 3(d) indicates that the performance of our proposed adversarial reweighting is not sensitive to these hyper-parameters.

Computational cost. We compare the computational cost of different methods with the total training time in the same training steps (5000 steps), as in Fig. 4(a). Figure 4(a) shows that our approach (AR) is comparable to other methods in terms of computational cost.

Feature and weight visualization. We show the t-SNE embeddings [25] of learned features in task Ar→Cl (Office-Home) in Fig. 4(b), 4(c), and 4(d). It is observed that the approach of ResNet-50 does not align the cross-domain features, since it trains the network with only source data. With the conditional entropy minimization, the target features in Fig. 4(c) learned by the Baseline are aligned with source features of all classes (including the source-only classes), which is unexpected in PDA. In Fig. 4(d), our proposed AR aligns the target features with partial source features. This may partially explain the success of our approach for tackling the problem of PDA. In Fig. 5, we visualize the learned weights of source domain data in tasks Ar→Cl (Office-Home) and S→R (VisDA-2017). We can see that the source domain data distant from the target domain are assigned with smaller weights.

5 Conclusion

In this paper, we experimentally observe that adapting the feature extractor by reweighted distribution alignment is not robust to the "noisy" weights of source domain data and may hurt the performance of learning in target domain. We further propose a novel adversarial reweighting approach to tackle the problem of PDA. We learn the source data weights in an adversarial reweighting model to reduce the domain gap and mitigate the negative effect of the data of source-only classes. We then train the recognition network on the reweighted source data to enforce its transferability for the target domain. Extensive experiments show that our proposed approach achieves SOTA results on challenging datasets of ImageNet-Caltech, Office-Home, VisDA-2017, and DomainNet. In our future work, we are interested in applying our approach to the open-set DA [28] and universal DA [44].

References

[1] Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein generative adversarial networks. In *ICML*, 2017.

[2] Yogesh Balaji, Rama Chellappa, and Soheil Feizi. Robust optimal transport with applications in generative modeling and domain adaptation. In *NeurIPS*, 2020.

[3] Zhangjie Cao, Mingsheng Long, Jianmin Wang, and Michael I Jordan. Partial transfer learning with selective adversarial networks. In *CVPR*, 2018.

[4] Zhangjie Cao, Lijia Ma, Mingsheng Long, and Jianmin Wang. Partial adversarial domain adaptation. In *ECCV*, 2018.

[5] Zhangjie Cao, Kaichao You, Mingsheng Long, Jianmin Wang, and Qiang Yang. Learning to transfer examples for partial domain adaptation. In *CVPR*, 2019.

[6] Zhihong Chen, Chao Chen, Zhaowei Cheng, Boyuan Jiang, Ke Fang, and Xinyu Jin. Selective transfer with reinforced transfer network for partial domain adaptation. In *CVPR*, 2020.

[7] Steven Diamond and Stephen Boyd. Cvxpy: A python-embedded modeling language for convex optimization. *JMLR*, 17(1):2909–2913, 2016.

[8] Yaroslav Ganin and Victor Lempitsky. Unsupervised domain adaptation by backpropagation. In *ICML*, 2015.

[9] Yaroslav Ganin, Evgeniya Ustinova, Hana Ajakan, Pascal Germain, Hugo Larochelle, François Laviolette, Mario Marchand, and Victor Lempitsky. Domain-adversarial training of neural networks. *JMLR*, 17(1):2096–2030, 2016.

[10] Ian J Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *arXiv preprint arXiv:1406.2661*, 2014.

[11] Yves Grandvalet and Yoshua Bengio. Semi-supervised learning by entropy minimization. In *NeurIPS*, 2005.

[12] Gregory Griffin, Alex Holub, and Pietro Perona. Caltech-256 object category dataset. 2007.

[13] Xiang Gu, Jian Sun, and Zongben Xu. Spherical space domain adaptation with robust pseudo-label loss. In *CVPR*, 2020.

[14] Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron C Courville. Improved training of wasserstein gans. In *NeurIPS*, 2017.

[15] Kaiming He, Xiangyu Zhang, Shaoqing Ren, and Jian Sun. Deep residual learning for image recognition. In *CVPR*, 2016.

[16] Jiayuan Huang, Arthur Gretton, Karsten Borgwardt, Bernhard Schölkopf, and Alex Smola. Correcting sample selection bias by unlabeled data. In *NeurIPS*, 2006.

[17] Guoliang Kang, Lu Jiang, Yi Yang, and Alexander G Hauptmann. Contrastive adaptation network for unsupervised domain adaptation. In *CVPR*, 2019.

[18] Diederik P Kingma and Jimmy Ba. Adam: A method for stochastic optimization. *arXiv preprint arXiv:1412.6980*, 2014.

[19] Piotr Koniusz, Yusuf Tas, and Fatih Porikli. Domain adaptation by mixture of alignments of second-or higher-order scatter tensors. In *CVPR*, 2017.

[20] Alex Krizhevsky, Ilya Sutskever, and Geoffrey E Hinton. Imagenet classification with deep convolutional neural networks. In *NeurIPS*, 2012.

[21] Shuang Li, Chi Harold Liu, Qiuxia Lin, Qi Wen, Limin Su, Gao Huang, and Zhengming Ding. Deep residual correction network for partial domain adaptation. *IEEE Trans PAMI*, In press, 2020.

[22] Jian Liang, Yunbo Wang, Dapeng Hu, Ran He, and Jiashi Feng. A balanced and uncertainty-aware approach for partial domain adaptation. In *ECCV*, 2020.

[23] Mingsheng Long, Yue Cao, Jianmin Wang, and Michael Jordan. Learning transferable features with deep adaptation networks. In *ICML*, 2015.

[24] Mingsheng Long, ZhangJie Cao, Jianmin Wang, and Michael I Jordan. Conditional adversarial domain adaptation. In *NeurIPS*, 2018.

[25] Laurens van der Maaten and Geoffrey Hinton. Visualizing data using t-sne. *JMLR*, 9(Nov):2579–2605, 2008.

[26] Sinno Jialin Pan and Qiang Yang. A survey on transfer learning. *IEEE TKDE*, 22(10):1345–1359, 2010.

[27] Yingwei Pan, Ting Yao, Yehao Li, Yu Wang, Chong-Wah Ngo, and Tao Mei. Transferrable prototypical networks for unsupervised domain adaptation. In *CVPR*, 2019.

[28] Pau Panareda Busto and Juergen Gall. Open set domain adaptation. In *ICCV*, 2017.

[29] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *NeurIPS*, 2019.

[30] Xingchao Peng, Qinxun Bai, Xide Xia, Zijun Huang, Kate Saenko, and Bo Wang. Moment matching for multi-source domain adaptation. In *ICCV*, 2019.

[31] Xingchao Peng, Ben Usman, Neela Kaushik, Judy Hoffman, Dequan Wang, and Kate Saenko. Visda: The visual domain adaptation challenge. *arXiv preprint arXiv:1710.06924*, 2017.

[32] Olga Russakovsky, Jia Deng, Hao Su, Jonathan Krause, Sanjeev Satheesh, Sean Ma, Zhiheng Huang, Andrej Karpathy, Aditya Khosla, Michael Bernstein, et al. Imagenet large scale visual recognition challenge. *IJCV*, 115(3):211–252, 2015.

[33] Kate Saenko, Brian Kulis, Mario Fritz, and Trevor Darrell. Adapting visual category models to new domains. In *ECCV*, 2010.

[34] Kuniaki Saito, Donghyun Kim, Stan Sclaroff, Trevor Darrell, and Kate Saenko. Semi-supervised domain adaptation via minimax entropy. In *ICCV*, 2019.

[35] Kuniaki Saito, Kohei Watanabe, Yoshitaka Ushiku, and Tatsuya Harada. Maximum classifier discrepancy for unsupervised domain adaptation. In *CVPR*, 2018.

[36] Karen Simonyan and Andrew Zisserman. Very deep convolutional networks for large-scale image recognition. *arXiv:1409.1556*, 2014.

[37] Baochen Sun and Kate Saenko. Deep coral: Correlation alignment for deep domain adaptation. In *ECCV*, 2016.

[38] Eric Tzeng, Judy Hoffman, Trevor Darrell, and Kate Saenko. Simultaneous deep transfer across domains and tasks. In *ICCV*, 2015.

[39] Eric Tzeng, Judy Hoffman, Kate Saenko, and Trevor Darrell. Adversarial discriminative domain adaptation. In *CVPR*, 2017.

[40] Hemanth Venkateswara, Jose Eusebio, Shayok Chakraborty, and Sethuraman Panchanathan. Deep hashing network for unsupervised domain adaptation. In *CVPR*, 2017.

[41] Cédric Villani. *Optimal transport: old and new*, volume 338. 2008.

[42] Ruijia Xu, Guanbin Li, Jihan Yang, and Liang Lin. Larger norm more transferable: An adaptive feature norm approach for unsupervised domain adaptation. In *ICCV*, 2019.

[43] Junchi Yan, Zhongliang Jing, and Henry Leung. Discriminative partial domain adversarial network. In *ECCV*, 2020.

[44] Kaichao You, Mingsheng Long, Zhangjie Cao, Jianmin Wang, and Michael I. Jordan. Universal domain adaptation. In *CVPR*, 2019.

[45] Werner Zellinger, Thomas Grubinger, Edwin Lughofer, Thomas Natschläger, and Susanne Saminger-Platz. Central moment discrepancy (cmd) for domain-invariant representation learning. *arXiv preprint arXiv:1702.08811*, 2017.

[46] Jing Zhang, Zewei Ding, Wanqing Li, and Philip Ogunbona. Importance weighted adversarial nets for partial domain adaptation. In *CVPR*, 2018.

[47] Yuchen Zhang, Tianle Liu, Mingsheng Long, and Michael Jordan. Bridging theory and algorithm for domain adaptation. In *ICML*, 2019.