Shape, Light & Material Decomposition from Images using Monte Carlo Rendering and Denoising

Abstract

Recent advances in differentiable rendering have enabled high-quality reconstruction of 3D scenes from multi-view images. Most methods rely on simple rendering algorithms: pre-filtered direct lighting or learned representations of irradiance. We show that a more realistic shading model, incorporating ray tracing and Monte Carlo integration, substantially improves decomposition into shape, materials & lighting. Unfortunately, Monte Carlo integration provides estimates with significant noise, even at large sample counts, which makes gradient-based inverse rendering very challenging. To address this, we incorporate multiple importance sampling and denoising in a novel inverse rendering pipeline. This substantially improves convergence and enables gradient-based optimization at low sample counts. We present an efficient method to jointly reconstruct geometry (explicit triangle meshes), materials, and lighting, which substantially improves material and light separation compared to previous work. We argue that denoising can become an integral part of high quality inverse rendering pipelines.

1 Introduction

Differentiable rendering shows great promise for accurate multi-view 3D reconstruction from image observations. NeRF [39] use differentiable volume rendering to create high quality view interpolation through neural, density-based light-fields. Surface-based methods apply signed distance fields [43, 47, 67, 61, 71] or triangle meshes [41, 54] to capture high quality geometry. Recent work [6, 41, 73] further decompose these representations into geometry, material, and environment light.

Most aforementioned methods rely on appearance baked into neural light fields or apply simple shading models. Typically, direct lighting without shadows is considered, combined with pre-filtered representations of environment lighting [41, 71]. Some methods account for shadowing and indirect illumination [6, 73, 75], but often lock the geometry optimization when sampling the shadow term, or rely on learned representations of irradiance. While results are impressive, the deviations from physically-based shading models makes it harder for these methods to plausibly disentangle shape, material and lighting, as shown in Figure 1.

In theory, it is straightforward to replace the rendering engines of these 3D reconstruction methods with photorealistic differentiable renderers [31, 36, 46, 45, 69, 70] and optimize in a setting with more accurate light simulation, including global illumination effects. In practice, however, the noise in multi-bounce Monte Carlo rendering makes gradient-based optimization challenging. Very high sample counts are required, which result in intractable iteration times.

In this paper, we bridge the gap between current multi-view 3D reconstruction and physically-based differentiable rendering, and demonstrate high-quality reconstructions at competitive runtime performance. We attack the challenging case of extracting *explicit triangle meshes*, PBR materials and environment lighting from a set of multi-view images, in a format directly compatible with

| NVDIFFREC | Our | NVDIFFREC (relit) | Our (relit) | Ref (relit) |

Figure 1: NVDIFFREC [41] successfully reconstructs complex geometry from multi-view images, but struggles with the material & light separation. On the left side, we visualize split-screens of the rendered reconstruction and the diffuse albedo texture. Note that NVDIFFREC bakes most of the lighting in the albedo texture, which hurts quality in relighting scenarios (shown to the right). In contrast, by leveraging a more advanced renderer, we successfully disentangle material and lighting (note the lack of shading in the albedo texture), and improve relighting quality. The dataset consists of 200 views of the Rollercoaster from LDraw resources [29] (CC BY-2.0).

current DCC tools and game engines. For improved visual fidelity, we compute direct illumination using Monte Carlo integration with ray tracing, and add several techniques to combat the increased noise levels. By carefully trading variance for bias, we enable efficient gradient-based optimization in a physically-based inverse rendering pipeline. Compared to previous 3D reconstruction methods, our formulation primarily improves material and light separation.

Concretely, we reduce variance by combining multiple importance sampling [57] and differentiable denoisers. We evaluate both neural denoisers [2, 10, 22] and cross-bilateral filters [52] in our pipeline. Furthermore, we decompose the rendering equation into albedo, demodulated diffuse lighting and specular lighting, which enable precise regularization to improve light and material separation.

2   Previous Work

Neural methods for multi-view reconstruction   These methods fall in two categories: *implicit* or *explicit* scene representations. NeRF [39] and follow-ups [38, 42, 49, 72, 63, 15, 40, 50, 68, 65], use volumetric representations and compute radiance by ray marching through a neurally encoded 5D light field. While achieving impressive results on novel view synthesis, geometric quality suffers from the ambiguity of volume rendering [72]. Surface-based rendering methods [43, 47, 67, 61] optimizing the underlying surface directly using implicit differentiation, or gradually morph from a volumetric representation into a surface representation. Methods with explicit representation estimate 3D meshes from images, where most approaches assume a given mesh topology [35, 11, 12], but recent work also include topology optimization [34, 14, 54, 41].

BRDF and lighting estimation   To estimate surface radiometric properties from images, previous work on BTF and SVBRDF estimation rely on special viewing configurations, lighting patterns or complex capturing setups [30, 16, 17, 18, 64, 5, 8, 53, 20]. Recent methods exploit neural networks to predict BRDFs from images [13, 19, 32, 33, 44, 37]. Differentiable rendering methods [35, 11, 74, 12, 21] learn to predict geometry, SVBRDF and, in some cases, lighting via photometric loss.

Most related to our work are neural 3D reconstruction methods with *intrinsic decomposition* of shape, materials, and lighting from images [6, 7, 41, 71, 73, 75]. Illumination is represented using mixtures of spherical Gaussians [6, 41, 71, 75], pre-filtered approximations [7, 41], or low resolution environment maps [73]. When the shadowing term is accounted for [73], optimization is split into two passes where geometry is locked before the shadow term is sampled. Other approaches represent indirect illumination with neural networks [62, 75].

Image denoisers   Denoisers are essential tools in both real-time- and production renderers. Traditionally, variants of cross-bilateral filters are used [76], which require scene-specific manual adjustments. More recently, neural denoisers [2, 10, 22] trained on large datasets have shown impressive quality without the need for manual tuning, and are now incorporated in most production renderers. We directly incorporate differentiable versions of these denoisers in our pipeline. We are currently unaware of image denoisers applied in differentiable rendering, but we see a lot of potential for denoisers in physically-based inverse rendering going forward.

Figure 2: We extend NVDIFFREC [41] with a differentiable Monte Carlo renderer for direct illumination. Additionally, to reduce variance, we add a differentiable denoiser. These novel steps are highlighted in green. Following NVDIFFREC, the topology is parameterized using an SDF, and a triangular surface mesh is extracted in each iteration using DMTet [54], combined with spatially-varying PBR materials and HDR environment lighting. The system is supervised using only photometric loss on the rendered, denoised image compared to a reference, and gradients are back-propagated to the denoiser, shape, materials, and lighting parameters. All parameters are optimized jointly.

3 System

We target the challenging task of joint optimization of shape, material and environment lighting from a set of multi-view images with known foreground segmentation masks and camera poses. Our goal is to use physically-based rendering techniques to improve the intrinsic decomposition of lighting and materials, producing assets that can be relit, edited, animated, or used in simulation. As a proof-of-concept, we extend a recent approach, NVDIFFREC [41], which targets the same optimization task (shape, materials and environment lighting). Notably, they directly optimize a *triangular* 3D model, which has obvious benefits: it is easy to import and modify the reconstructed models in existing DCC tools, and can exploit hardware-accelerated differentiable rasterization [28]. In our setting, triangular 3D models also means we can leverage hardware-accelerated ray-tracing for efficient shadow tests. NVDIFFREC reports competitive results on view interpolation, material reconstruction, and relighting, and we will use their pipeline as a baseline in our evaluations.

Our system is summarized in Figure 2. A triangular mesh with arbitrary topology is optimized from a set of images through 2D supervision. Geometry is represented by a signed distance field defined on a three-dimensional grid and reduced to a triangular surface mesh through deep marching tetrahedra (DMTet) [54]. Next, the extracted surface mesh is rendered in a differentiable renderer, using the physically-based (PBR) material model from Disney [9]. This material model combines a diffuse term with an isotropic, specular GGX lobe [60]. A tangent space normal map is also included to capture high frequency shading detail. Finally, the rendered image is evaluated against a reference image using a photometric loss. In contrast to NVDIFFREC, which uses a simple renderer with deferred shading and the split-sum approximation for direct lighting (without shadows), we instead leverage a renderer which evaluates the direct lighting integral using Monte Carlo integration and ray tracing (shadow rays). We represent the scene lighting using a high dynamic range light probe stored as a floating point texture, typically at a resolution of 256×256 texels. Finally, to combat the inherent variance that comes with Monte Carlo integration, we leverage differentiable image denoising and multiple importance sampling.

Optimization task   Let ϕ denote the optimization parameters (shape, spatially varying materials and light probe). For a given camera pose, c, our differentiable renderer produces an image $I_\phi(c)$. Given that we use Monte Carlo integration during rendering, this image inherently includes noise, and we apply a differentiable image denoiser, D_θ, with parameters, θ, to reduce the variance, $I_\phi^{\text{denoised}}(c) = D_\theta(I_\phi(c))$. The reference image $I_{\text{ref}}(c)$ is a view from the same camera. Given a photometric loss function L, we minimize the empirical risk

$$\underset{\phi,\theta}{\text{argmin}} \ \mathbb{E}_c\big[L\big(D_\theta(I_\phi(c)), I_{\text{ref}}(c)\big)\big] \tag{1}$$

using Adam [26] based on gradients w.r.t. the optimization parameters, $\partial L/\partial \phi$, and $\partial L/\partial \theta$, which are obtained through differentiable rendering. We use the same loss function as NVDIFFREC. An example of the optimization process is illustrated in Figure 3,

| 1 | 10 | 100 | 1000 | 5000 | Reference |

Figure 3: Visualization of the optimization process. Note that the initial guess for topology are randomized SDF values on the grid. After 1000 iterations, we already have a high quality topology and plausible materials and lighting for this complicated asset. Synthetic dataset with 200 frames, generated from a part of the Apollo capsule, courtesy of the Smithsonian [55] (CC0-1.0).

3.1 Direct Illumination

The outgoing radiance $L(\omega_o)$ in direction ω_o can be expressed using the rendering equation [24] as:

$$L(\omega_o) = \int_\Omega L_i(\omega_i)f(\omega_i, \omega_o)(\omega_i \cdot \mathbf{n})d\omega_i. \tag{2}$$

This is an integral of the product of the incident radiance, $L_i(\omega_i)$ from direction ω_i and the BSDF $f(\omega_i, \omega_o)$. The integration domain is the hemisphere Ω around the surface normal, $\mathbf{n}$.

Spherical Harmonics (SH) [11] or Spherical Gaussians (SG) [6, 71] are often used as efficient approximations of direct illumination, but only work well for low- to medium-frequency lighting. In contrast, the *split sum* approximation [25, 41] captures all-frequency image based lighting, but does not incorporate shadows. Our goal is all-frequency lighting *including* shadows, which we tackle by evaluating the rendering equation using Monte Carlo integration:

$$L(\omega_o) \approx \frac{1}{N} \sum_{i=1}^{N} \frac{L_i(\omega_i)f(\omega_i, \omega_o)(\omega_i \cdot \mathbf{n})}{p(\omega_i)}, \tag{3}$$

with samples drawn from some distribution $p(\omega_i)$. Note that $L_i(\omega_i)$ includes a visibility test, which can be evaluated by tracing a shadow ray in direction ω_i. Unfortunately, the variance levels in Monte Carlo integration with low number of samples makes gradient-based optimization hard, particularly with complex lighting. In Section 4 we propose several variance reduction techniques, which enable an inverse rendering pipeline that efficiently reconstructs complex geometry, a wide range of lighting conditions and spatially-varying BSDFs.

Shadow gradients In single view optimization [59], shape from shadows [56], or direct optimization of the position/direction of analytical light sources, shadow ray visibility gradients [36, 3] are highly beneficial. However, in our multi-view setting (50+ views), similar to Loubet et al. [36], we observed that gradients of diffuse scattering are negligible compared to the gradients of primary visibility. Hence, for performance reasons, in the experiment presented in this paper, the shadow ray visibility gradients are detached when evaluating the hemisphere integral, and shape optimization is driven by primary visibility gradients, obtained from `nvdiffrast` [28].

4 Variance Reduction

We evaluate direct illumination with high frequency environment map lighting combined with a wide range of materials (diffuse, dielectrics, and metals). Strong directional sunlight, highly specular, mirror-like materials, and the visibility component can all introduce significant levels of noise. To enable optimization in an inverse rendering setting at practical sample counts, we carefully sample each of these contributing factors to obtain a signal with low variance. Below, we describe how we combat noise by using multiple importance sampling and denoising.

4.1 Multiple Importance Sampling

We leverage *multiple importance sampling* [57] (MIS), a framework to weigh a set of different sampling techniques to reduce variance in Monte Carlo integration. Given a set of sampling techniques,

$$c \qquad\qquad c_d \qquad\qquad k_d \qquad\qquad c_s$$

Figure 4: We separate lighting into diffuse lighting, $\mathbf{c}_d$, diffuse reflectance, $\mathbf{k}_d$, and specular lighting, $\mathbf{c}_s$. This enables fine-grained regularization and denoising without smearing texture detail.

141 each with a sampling distribution p_i, the Monte Carlo estimator for an integral $\int_\Omega g(x)dx$ given by
142 MIS is

$$\sum_{i=1}^n \frac{1}{n_i} \sum_{j=1}^{n_i} w_i(X_{i,j}) \frac{g(X_{i,j})}{p_i(X_{i,j})}, \quad w_i(x) = \frac{n_i}{p_i(x)} \sum_k n_i p_k(x). \tag{4}$$

143 The weighting functions $w_i(x)$ are chosen using the *balance heuristic*. Please refer to Veach's
144 thesis [57] or the excellent PBRT book [48] for further details.

145 In our case, we apply MIS with three sampling techniques: light importance sampling, $p_{\text{light}}(\omega)$,
146 using a piecewise-constant 2D distribution sampling technique [48], cosine sampling, $p_{\text{diffuse}}(\omega)$, for
147 the diffuse lobe, and GGX importance sampling [23], $p_{\text{specular}}(\omega)$, for the specular lobe. Unlike in
148 forward rendering with known materials and lights, our material and light parameters are optimization
149 variables. Thus, the sampling distributions, p_i, are recomputed in each optimization iteration.
150 Following the taxonomy of differentiable Monte Carlo estimators of Zeltner et al. [69], our importance
151 sampling is *detached*, i.e., we do not back-propagate gradients to the scene parameters in the sampling
152 step, only in the material evaluation. Please refer to Zeltner et al. for a careful analysis of Monte
153 Carlo estimators for differentiable light transport.

154 MIS is unbiased, but chaining multiple iterations of our algorithm exhibits *bias*, as the current,
155 importance sampled, iteration dictates the sampling distributions used in the next iteration. Light probe
156 intensities, for example, are optimized based on an importance sampled image, which are then used
157 to construct the sampling distribution for the subsequent pass. For unbiased rendering, the sampling
158 distribution must be estimated using a second set of uncorrelated samples instead. Furthermore, we
159 explicitly re-use the random seed from the forward pass during gradient backpropagation to scatter
160 gradients to the exact same set of parameters that contributed to the forward rendering. This approach
161 is clearly biased [58], but we empirically note that this is very effective in reducing variance, and in
162 our setting this variance-bias trade-off works in our favor.

4.2 Denoising

164 For differentiable rendering, the benefits of denoising are twofold. First, it improves the image
165 quality of the rendering in the forward pass, reducing the optimization error and the gradient noise
166 introduced in the image loss. Second, as gradients back-propagate through the denoiser's spatial
167 filter kernel, gradient sharing between neighboring pixels is enabled. To see this, let's consider a
168 simple denoiser, $O = X \circledast F$, where the noisy rendered image X is filtered by a low-pass filter, F
169 ($\circledast$ represents an image space 2D convolution). Given a loss gradient, $\frac{\partial L}{\partial O}$, the gradients propagated
170 back to the renderer are $\frac{\partial L}{\partial X} = \frac{\partial L}{\partial O} \circledast F^T$, which applies the same low-pass filter in case the filter is
171 rotationally symmetric $F = F^T$. In other words, the renderer sees *filtered* loss gradients in a local
172 spatial footprint. While denoisers inherently trade a reduction in variance for increased bias, we
173 empirically note that denoising significantly helps convergence at lower sample counts, and help to
174 reconstruct higher frequency environment lighting. We show an illustrative example in Figure 9.

175 Following previous work in denoising for production rendering [2], Figure 4 shows how we separate
176 lighting into diffuse, $\mathbf{c}_d$, and specular, $\mathbf{c}_s$ terms. This lets us denoise each term separately, creating
177 denoised buffers, $D_\theta(\mathbf{c}_d)$, and $D_\theta(\mathbf{c}_s)$. More importantly, we can use *demodulated* diffuse lighting,
178 which means that the lighting term has not yet been multiplied by material diffuse albedo, $\mathbf{k}_d$. In
179 forward rendering, this is important as it decorrelates the noisy lighting from material textures, thus
180 selectively denoising the noisy Monte-Carlo estimates and avoiding to low-pass filter high-frequent
181 texture information. In inverse rendering, we can additionally use it to improve material and light
182 decomposition by adding regularization on the lighting terms, as disucssed in Section 5. We compose
183 the final image as $\mathbf{c} = \mathbf{k}_d \cdot D_\theta(\mathbf{c}_d) + D_\theta(\mathbf{c}_s)$. We currently do not demodulate specular lighting
184 because of the view dependent Fresnel term, but expect this to be improved in future work.

Figure 5: Ablation study on the effect of using different denoising algorithms during optimization at low sample counts on three different scenes of increasing complexity (from left to right). We plot averaged PSNR scores over 200 novel views, rendered without denoising, using high sample counts. In this experiment, we used decorrelated samples in the backward pass to highlight the effect of denoising. The most complex scene failed to converge at 8 spp without denoising.

Cross-bilateral filters Cross-bilateral filters are commonly used to remove noise in rendered images [76]. To evaluate this family of denoisers in our inverse pipeline, we adapted Spatio-temporal Variance-Guided Filtering [52] (SVGF), which is a popular cross-bilateral filter using surface normals and per-pixel depth as edge-stopping guides. The denoiser is applied to *demodulated* diffuse lighting, to avoid smearing texture detail. We disabled the temporal component of SVGF, as we focus on single frame rendering, and implemented the filter as a differentiable module to allow for loss gradients to propagate back to our scene parameters.

Neural denoisers As a representative neural denoiser, we deploy the Open Image Denoiser (OIDN) [1], which is a U-Net [51] pre-trained on a large corpus of rendered images. The denoiser is applied to the rendered image before computing the image space loss. As the network model is fully convolutional, it is trivially differentiable, and we can propagate gradients from the image space loss, through the denoiser back to the renderer.

In Figure 5, we provide an overview on the effect of denoisers during 3D scene reconstruction. We observe that denoising is especially helpful at low sample counts, where we obtain similar reconstruction results at 8 spp with denoising, compared to 32 spp without a denoiser. At higher sample counts, however, the benefit from denoising diminishes, as variance in the Monte-Carlo estimates decreases. Given that denoisers enable significantly faster iteration times, we consider it a valuable tool for saving computational resources when fine-tuning model parameters for subsequent runs with high sample counts. Additionally, we empirically found that using a denoiser during reconstruction yields higher quality light probes, as can be seen in Figure 9, both at low and high sample counts.

We can also jointly optimize the denoiser parameters, θ, with the 3D scene reconstruction task. i.e., the denoiser is *fine-tuned* for the current scene. Unfortunately, this approach has undesirable side-effects: Features tend to get baked into the denoiser network weights instead of the materials or light probe. This is especially apparent with the OIDN [1] denoiser, which produced color shifts due to lack of regularization on the output. We got notably better results with the hierarchical kernel prediction architecture from Hasselgren et al. [22], which is more constrained. However, the results still lagged behind denoisers with locked weights. We refer to the supplemental material for details.

5 Priors

In our setting: 3D reconstruction from multi-view images with constant lighting, regularization is essential in order to disentangle lighting and materials. Following previous work [73, 41], we apply smoothness priors for albedo, specular, and normal map textures. Taking the albedo as an example, if $\boldsymbol{k}_d(\mathbf{x})$ denotes the diffuse albedo at world space position, $\mathbf{x}$, and ϵ is a small random displacement vector, we define the smoothness prior for albedo as:

$$L_{\boldsymbol{k}_d} = \sum_{\mathbf{x}_{\mathrm{surf}}} \left| \boldsymbol{k}_d(\mathbf{x}_{\mathrm{surf}}) - \boldsymbol{k}_d(\mathbf{x}_{\mathrm{surf}} + \epsilon) \right|, \tag{5}$$

where $\mathbf{x}_{\mathrm{surf}}$ are the world space positions at the primary hit point on the object. We note that the smoothness prior is not sufficient to disentangle material parameters and light, especially for scenes with high frequency lighting and sharp shadows. Optimization tends to bake shadows into the albedo

Table 1: Summarized relighting results for NeRFactor (CC-BY-3.0), NeRF (CC-BY-3.0) and our synthetic datasets. The NeRFactor dataset contains four scenes, each scene has eight validation views and eight different light probes (256 validation images). For the NeRF dataset (which contain higher frequency lighting), we use the `Chair`, `Hotdog`, `Lego`, `Materials` and `Mic` scenes, with eight validation views and four light probe configurations (160 validation images). Our dataset contains a variation of high and low frequency lighting with geometrically complex objects. The image metric scores are arithmetic means over all images.

	NeRFactor synthetic			Nerf synthetic			Our synthetic		
	PSNR↑	SSIM↑	LPIPS↓	PSNR↑	SSIM↑	LPIPS↓	PSNR↑	SSIM↑	LPIPS↓
Our	26.0 dB	0.924	0.060	26.5 dB	0.932	0.055	27.1 dB	0.950	0.027
NVDIFFREC	24.8 dB	0.910	0.063	23.3 dB	0.889	0.076	23.7 dB	0.925	0.049
NERFACTOR	22.2 dB	0.896	0.087	-	-	-	-	-	-

Figure 6: Relighting examples from the NeRFactor and NeRF synthetic datasets. The NeRF dataset contains high frequency lighting and global illumination, and is substantially more challenging than the NeRFactor version, which uses downsampled probes. Our results contain visible artifacts, but outperform the material separation of previous work.

texture (easy) rather than reconstruct a high intensity, small area in the environment map (hard). To enable high quality relighting, we explicitly want to enforce shading detail represented by lighting, and only bake remaining details into the material textures. We propose a novel regularizer term that is surprisingly effective. We compute a monochrome image loss between the demodulated lighting terms and the reference image:

$$L_{\text{light}} = | Y (\mathbf{c}_d + \mathbf{c}_s) - V (I_{\text{ref}}) |. \tag{6}$$

Here, $Y (\mathbf{x}) = (\mathbf{x}_r + \mathbf{x}_g + \mathbf{x}_b)/3$ is a simple luminance operator, and $V (\mathbf{x}) = \max (\mathbf{x}_r, \mathbf{x}_g, \mathbf{x}_b)$ is the HSV value component. The rationale for using HSV-value for the reference image is that the max operation approximates demodulation, e.g., a red and white pixel have identical values. We assume that the demodulated lighting is mostly monochrome, in which case $Y (\mathbf{x}) \sim V (\mathbf{x})$, and given that we need to propagate gradients to $\mathbf{c}_d$ and $\mathbf{c}_s$, Y avoids discontinuities. This regularizer is limited by our inability to demodulate the reference image. The HSV-value ignores chrominance, but we cannot separate a shadow from a darker material. This has not been a problem in our tests, but could interfere with optimization if the regularizer is given too much weight. Please refer to the supplemental materials for complete regularizer details.

6 Experiments

In our experiments, we use NVDIFFREC [41] as a baseline, and refer to their work for thorough comparisons against related work. We focus the evaluation on the quality of material and light separation. Table 1 shows a quantitative comparison with NVDIFFREC and NeRFactor [73] on the NeRFactor relighting setup. Note that there is an indeterminate scale factor between material reflectance (e.g., albedo) and the light intensity. This is accounted for by scaling each image to match the average luminance of the reference for the corresponding scene. The same methodology

| Our recon. | Scene edit | Material edits | Relighting |

Figure 7: Manipulations of our extracted 3D model of the Family dataset in Blender. This scene is part of the Tanks&Temples [27] dataset (CC BY-NC-SA 3.0) and the Spot model is courtesy of Keenan Crane (CC0).

Ref   Our   Geometry $\mathbf{k}_d$ $\mathbf{k}_{orm}$ Normal   Probe

Figure 8: We show explicit decomposition of shape, materials and lighting, directly from photos with known poses. Character is part of the BlendedMVS [66] dataset (CC BY-4.0) and Gold Cape is part of the NeRD [6] dataset (CC BY-NC-SA 4.0).

is applied for all algorithms in our comparisons. We outperform previous work, providing better material reconstruction. Figure 6 shows visual examples.

We additionally perform relighting on the synthetic NeRF dataset, which is substantially more challenging than the NeRFactor variant, due to high frequency lighting and global illumination effects. NVDIFFREC produces severe artifacts, as exemplified by the Hotdog scene in Figure 6. Table 1 shows a significant increase in image quality for our approach. The visual examples show that our results are plausible, though not without artifacts. Finally, we constructed a novel synthetic dataset with three scenes with highly complex geometry to stress-test the system. Each scene contains 200 training views and 200 novel views for evaluation. The three scenes are shown in Figures 1 , 3 ,and 9. Quantitatively we outperform previous work by a larger margin, and Figure 1 shows very little shading in the albedo textures.

In Figures 7 and 8, we apply our method to datasets with real photos. These sets are more difficult, due to inaccuracies in foreground segmentation masks and camera poses. We extract triangle meshes that can be trivially edited in 3D modeling software, and in Figure 7 we use Blender to perform scene editing, material editing, and relighting. Note that the results look plausible with the inserted object being properly shaded and casting shadows on the statue, material editing looks good with the learned environment lighting and relighting interacts properly with the learned materials. Figure 8 shows a breakdown of geometry, material parameters and environment light.

To study the impact of denoising, we optimized the Porsche scene both with and without denoising enabled. As shown in Figure 9, denoising improves both visual quality and environment lighting detail at equal sample counts. The noise levels varies throughout the scene, and we note that denoising

| | PSNR | 24.4 dB | 25.7 dB | 25.6 dB | 26.0 dB |
| | Reference | 8 spp | 8 spp denoised | 128 spp | 128 spp denoised |

Figure 9: We show the benefits of denoising on the Porsche scene from LDraw resources [29] (CC BY-2.0). At low sample counts, denoising helps both with geometric reconstruction (in the cockpit) and to capture specular highlights. Even at 128 spp, denoising improves specular highlight and high frequency lighting details.

Table 2: View interpolation results. For reference, the NERFACTOR scores are 26.9 dB PSNR and SSIM of 0.930 on the NerFactor synthetic dataset, and Mip-NeRF has 35.0 dB PSNR and SSIM 0.978 on the Nerf synthetic dataset. The image metric scores are arithmetic means over all test images.

| | NeRFactor synthetic | | Nerf synthetic | | Our synthetic | | Real-world | |
	PSNR↑	SSIM↑	PSNR↑	SSIM↑	PSNR↑	SSIM↑	PSNR↑	SSIM↑
Our	29.6 dB	0.951	28.4 dB	0.938	25.6 dB	0.934	25.29 dB	0.899
NVDIFFREC	31.7 dB	0.967	30.4 dB	0.958	25.8 dB	0.944	26.58 dB	0.918

is particularly helpful in regions with complex lighting or occlusion, such as the specular highlight and cockpit.

View interpolation quality typically degrades with improved material and light separation, and neural light-fields, e.g, Mip-NeRF [4] typically performs best. While not our target, we include view interpolation results in Table 2. Our view interpolation scores are slightly below NVDIFFREC, but, as shown above, we provide considerably better material and lighting separation.

Compute resources Tracing rays to evaluate the direct illumination is considerably more expensive than pre-filtered environment light approaches. We leverage hardware-accelerated ray intersections, but note that our implementation is far from fully optimized. Our method scales linearly with sample count, which gives us a simple way to trade quality for performance. With a batch size 8 at a rendering resolution of 512×512, we get the following iteration times on a single NVIDIA A6000 GPU.

	NVDIFFREC	Our 2 spp	Our 8 spp	Our 32 spp	Our 128 spp
Iteration time	340 ms	310 ms	330 ms	490 ms	1050 ms

Our denoising strategies enable optimization at low sample counts. Unless otherwise mentioned, for the results presented in the paper, we use high quality settings of 128+ rays per pixel with 5000×2 iterations (second pass with fixed topology and 2D textures), which takes ~10 hours (A6000).

7 Conclusions

Our restriction to direct illumination shows up in scenes with global illumination. Similarly, we do not handle specular chains (geometry seen through a glass window). For this, we need to integrate multi-bounce path tracing, which is a clear avenue for future work, but comes with additional challenges in increased noise-levels, visibility gradients through specular chains, and drastically increased iteration times. Our renderer is intentionally biased to improve optimization times, but unbiased rendering could expect to generate better results for very high sample counts. Other limitations include lack of efficient regularization of material specular parameters and reliance on a foreground segmentation mask. Our approach is computationally intense, requiring a high-end GPU for optimization runs.

To summarize, we have shown that differentiable Monte-Carlo rendering combined with variance-reduction techniques is practical and applicable to multi-view 3D object reconstruction of explicit triangular 3D models. Our physically-based renderer clearly improves material and light reconstruction over previous work. By leveraging hardware accelerated ray-tracing and differentiable image denoisers, we remain competitive to previous work in terms of optimization time.

References

[1] Attila T. Áfra. Open Image Denoise, 02 2022. https://www.openimagedenoise.org/.

[2] Steve Bako, Thijs Vogels, Brian McWilliams, Mark Meyer, Jan Novák, Alex Harvill, Pradeep Sen, Tony DeRose, and Fabrice Rousselle. Kernel-Predicting Convolutional Networks for Denoising Monte Carlo Renderings. *ACM Trans. Graph.*, 36(4), 2017.

[3] Sai Bangaru, Tzu-Mao Li, and Frédo Durand. Unbiased Warped-Area Sampling for Differentiable Rendering. *ACM Trans. Graph.*, 39(6):245:1–245:18, 2020.

[4] Jonathan T. Barron, Ben Mildenhall, Matthew Tancik, Peter Hedman, Ricardo Martin-Brualla, and Pratul P. Srinivasan. Mip-NeRF: A Multiscale Representation for Anti-Aliasing Neural Radiance Fields. In *International Conference on Computer Vision (ICCV)*, 2021.

[5] Sai Bi, Zexiang Xu, Pratul Srinivasan, Ben Mildenhall, Kalyan Sunkavalli, Miloš Hašan, Yannick Hold-Geoffroy, David Kriegman, and Ravi Ramamoorthi. Neural reflectance fields for appearance acquisition, 2020.

[6] Mark Boss, Raphael Braun, Varun Jampani, Jonathan T. Barron, Ce Liu, and Hendrik P.A. Lensch. NeRD: Neural Reflectance Decomposition from Image Collections. In *International Conference on Computer Vision (ICCV)*, 2021.

[7] Mark Boss, Varun Jampani, Raphael Braun, Ce Liu, Jonathan T. Barron, and Hendrik P.A. Lensch. Neural-pil: Neural pre-integrated lighting for reflectance decomposition. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[8] Mark Boss, Varun Jampani, Kihwan Kim, Hendrik Lensch, and Jan Kautz. Two-shot spatially-varying BRDF and shape estimation. In *Proc. of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, pages 3982–3991, 2020.

[9] Brent Burley. Physically Based Shading at Disney. In *SIGGRAPH Courses: Practical Physically Based Shading in Film and Game Production*, 2012.

[10] Chakravarty R. Alla Chaitanya, Anton S. Kaplanyan, Christoph Schied, Marco Salvi, Aaron Lefohn, Derek Nowrouzezahrai, and Timo Aila. Interactive Reconstruction of Monte Carlo Image Sequences Using a Recurrent Denoising Autoencoder. *ACM Trans. Graph.*, 36(4), jul 2017.

[11] Wenzheng Chen, Jun Gao, Huan Ling, Edward Smith, Jaakko Lehtinen, Alec Jacobson, and Sanja Fidler. Learning to predict 3d objects with an interpolation-based differentiable renderer. In *Advances In Neural Information Processing Systems (NeurIPS)*, 2019.

[12] Wenzheng Chen, Joey Litalien, Jun Gao, Zian Wang, Clement Fuji Tsang, Sameh Khalis, Or Litany, and Sanja Fidler. DIB-R++: Learning to predict lighting and material with a hybrid differentiable renderer. In *Advances in Neural Information Processing Systems (NeurIPS)*, 2021.

[13] Duan Gao, Xiao Li, Yue Dong, Pieter Peers, Kun Xu, and Xin Tong. Deep Inverse Rendering for High-Resolution SVBRDF Estimation from an Arbitrary Number of Images. *ACM Trans. Graph.*, 38(4), 2019.

[14] Jun Gao, Wenzheng Chen, Tommy Xiang, Clement Fuji Tsang, Alec Jacobson, Morgan McGuire, and Sanja Fidler. Learning Deformable Tetrahedral Meshes for 3D Reconstruction. In *Advances In Neural Information Processing Systems*, 2020.

[15] Stephan J Garbin, Marek Kowalski, Matthew Johnson, Jamie Shotton, and Julien Valentin. FastNeRF: High-Fidelity Neural Rendering at 200FPS. *arXiv:2103.10380*, 2021.

[16] Andrew Gardner, Chris Tchou, Tim Hawkins, and Paul Debevec. Linear Light Source Reflectometry. *ACM Trans. Graph.*, 22(3):749–758, 2003.

[17] Abhijeet Ghosh, Tongbo Chen, Pieter Peers, Cyrus A. Wilson, and Paul Debevec. Estimating Specular Roughness and Anisotropy from Second Order Spherical Gradient Illumination. *Computer Graphics Forum*, 28(4):1161–1170, 2009.

[18] D. Guarnera, G. C. Guarnera, A. Ghosh, C. Denk, and M. Glencross. BRDF Representation and Acquisition. In *Proceedings of the 37th Annual Conference of the European Association for Computer Graphics: State of the Art Reports*, pages 625–650, 2016.

[19] Yu Guo, Cameron Smith, Miloš Hašan, Kalyan Sunkavalli, and Shuang Zhao. MaterialGAN: Reflectance Capture Using a Generative SVBRDF Model. *ACM Trans. Graph.*, 39(6), 2020.

[20] M. Haindl and J. Filip. *Visual Texture*. Springer-Verlag, 2013.

[21] Jon Hasselgren, Jacob Munkberg, Jaakko Lehtinen, Miika Aittala, and Samuli Laine. Appearance-driven automatic 3d model simplification. In *Eurographics Symposium on Rendering*, 2021.

[22] Jon Hasselgren, Jacob Munkberg, Anjul Patney, Marco Salvi, and Aaron Lefohn. Neural Temporal Adaptive Sampling and Denoising. *Computer Graphics Forum*, 39:147–155, 2020.

[23] Eric Heitz. Sampling the GGX Distribution of Visible Normals. *Journal of Computer Graphics Techniques (JCGT)*, 7(4):1–13, 2018.

[24] James T. Kajiya. The rendering equation. In *Proceedings of the 13th annual conference on Computer graphics and interactive techniques - SIGGRAPH'86*. ACM Press, 1986.

[25] Brian Karis. Real shading in unreal engine 4. *SIGGRAPH 2013 Course: Physically Based Shading in Theory and Practice*, 2013.

[26] Diederik P. Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. In *Proceedings of the 3rd International Conference for Learning Representations*, 2015.

[27] Arno Knapitsch, Jaesik Park, Qian-Yi Zhou, and Vladlen Koltun. Tanks and temples: Benchmarking large-scale scene reconstruction. *ACM Transactions on Graphics*, 36(4), 2017.

[28] Samuli Laine, Janne Hellsten, Tero Karras, Yeongho Seol, Jaakko Lehtinen, and Timo Aila. Modular primitives for high-performance differentiable rendering. *ACM Transactions on Graphics*, 39(6), 2020.

[29] Gerald Lasser. LDraw.org, 05 2022. https://www.ldraw.org/.

[30] Hendrik P.A. Lensch, Jochen Lang, Asla M. Sa, and Hans-Peter Seidel. Planned sampling of spatially varying BRDFs. *Computer Graphics Forum*, 2003.

[31] Tzu-Mao Li, Miika Aittala, Frédo Durand, and Jaakko Lehtinen. Differentiable Monte Carlo Ray Tracing through Edge Sampling. *ACM Trans. Graph. (Proc. SIGGRAPH Asia)*, 37(6):222:1–222:11, 2018.

[32] Zhengqin Li, Mohammad Shafiei, Ravi Ramamoorthi, Kalyan Sunkavalli, and Manmohan Chandraker. Inverse rendering for complex indoor scenes: Shape, spatially-varying lighting and svbrdf from a single image. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 2475–2484, 2020.

[33] Zhengqin Li, Zexiang Xu, Ravi Ramamoorthi, Kalyan Sunkavalli, and Manmohan Chandraker. Learning to reconstruct shape and spatially-varying reflectance from a single image. In *SIGGRAPH Asia 2018 Technical Papers*, page 269. ACM, 2018.

[34] Yiyi Liao, Simon Donné, and Andreas Geiger. Deep Marching Cubes: Learning Explicit Surface Representations. In *Conference on Computer Vision and Pattern Recognition (CVPR)*, 2018.

[35] Shichen Liu, Tianye Li, Weikai Chen, and Hao Li. Soft rasterizer: A differentiable renderer for image-based 3d reasoning. In *International Conference on Computer Vision (ICCV)*, Oct 2019.

[36] Guillaume Loubet, Nicolas Holzschuch, and Wenzel Jakob. Reparameterizing Discontinuous Integrands for Differentiable Rendering. *Transactions on Graphics (Proceedings of SIGGRAPH Asia)*, 38(6), 2019.

[37] Fujun Luan, Shuang Zhao, Kavita Bala, and Zhao Dong. Unified shape and svbrdf recovery using differentiable monte carlo rendering. *ArXiv*, 2021.

[38] Ricardo Martin-Brualla, Noha Radwan, Mehdi SM Sajjadi, Jonathan T Barron, Alexey Dosovitskiy, and Daniel Duckworth. Nerf in the wild: Neural radiance fields for unconstrained photo collections. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 7210–7219, 2021.

[39] Ben Mildenhall, Pratul P. Srinivasan, Matthew Tancik, Jonathan T. Barron, Ravi Ramamoorthi, and Ren Ng. NeRF: Representing Scenes as Neural Radiance Fields for View Synthesis. In *ECCV*, 2020.

[40] Thomas Müller, Alex Evans, Christoph Schied, and Alexander Keller. Instant Neural Graphics Primitives with a Multiresolution Hash Encoding. *arXiv:2201.05989*, 2022.

[41] Jacob Munkberg, Jon Hasselgren, Tianchang Shen, Jun Gao, Wenzheng Chen, Alex Evans, Thomas Mueller, and Sanja Fidler. Extracting Triangular 3D Models, Materials, and Lighting From Images. *arXiv:2111.12503*, 2021.

[42] Michael Niemeyer and Andreas Geiger. Giraffe: Representing scenes as compositional generative neural feature fields. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 11453–11464, 2021.

[43] Michael Niemeyer, Lars Mescheder, Michael Oechsle, and Andreas Geiger. Differentiable volumetric rendering: Learning implicit 3d representations without 3d supervision. In *Proceedings IEEE Conf. on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[44] Merlin Nimier-David, Zhao Dong, Wenzel Jakob, and Anton Kaplanyan. Material and Lighting Reconstruction for Complex Indoor Scenes with Texture-space Differentiable Rendering. In *Eurographics Symposium on Rendering*, 2021.

[45] Merlin Nimier-David, Sébastien Speierer, Benoît Ruiz, and Wenzel Jakob. Radiative Backpropagation: An Adjoint Method for Lightning-Fast Differentiable Rendering. *ACM Trans. Graph.*, 39(4), 2020.

[46] Merlin Nimier-David, Delio Vicini, Tizian Zeltner, and Wenzel Jakob. Mitsuba 2: A retargetable forward and inverse renderer. *Transactions on Graphics (Proceedings of SIGGRAPH Asia)*, 38(6), 2019.

[47] Michael Oechsle, Songyou Peng, and Andreas Geiger. UNISURF: unifying neural implicit surfaces and radiance fields for multi-view reconstruction. *CoRR*, abs/2104.10078, 2021.

[48] Matt Pharr and Greg Humphreys. *Physically Based Rendering, Second Edition: From Theory To Implementation*. Morgan Kaufmann Publishers Inc., 2nd edition, 2010.

[49] Albert Pumarola, Enric Corona, Gerard Pons-Moll, and Francesc Moreno-Noguer. D-nerf: Neural radiance fields for dynamic scenes. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pages 10318–10327, 2021.

[50] Christian Reiser, Songyou Peng, Yiyi Liao, and Andreas Geiger. KiloNeRF: Speeding up Neural Radiance Fields with Thousands of Tiny MLPs. *arXiv:2103.13744*, 2021.

[51] Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-Net: Convolutional Networks for Biomedical Image Segmentation. In *Medical Image Computing and Computer-Assisted Intervention – MICCAI 2015*, volume 9351, pages 234–241, 2015.

[52] Christoph Schied, Anton Kaplanyan, Chris Wyman, Anjul Patney, Chakravarty R. Alla Chaitanya, John Burgess, Shiqiu Liu, Carsten Dachsbacher, Aaron Lefohn, and Marco Salvi. Spatiotemporal Variance-guided Filtering: Real-time Reconstruction for Path-traced Global Illumination. In *Proceedings of High Performance Graphics*, HPG '17, pages 2:1–2:12, 2017.

[53] Carolin Schmitt, Simon Donne, Gernot Riegler, Vladlen Koltun, and Andreas Geiger. On joint estimation of pose, geometry and svBRDF from a handheld scanner. In *Proc. of the IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2020.

[54] Tianchang Shen, Jun Gao, Kangxue Yin, Ming-Yu Liu, and Sanja Fidler. Deep Marching Tetrahedra: a Hybrid Representation for High-Resolution 3D Shape Synthesis. In *NeurIPS*, 2021.

[55] Smithsonian. Smithsonian 3D Digitization, 2018. https://3d.si.edu/.

[56] Kushagra Tiwary, Tzofi Klinghoffer, and Ramesh Raskar. Towards learning neural representations from shadows. *arXiv:2203.15946*, 2022.

[57] Eric Veach and Leonidas J. Guibas. Optimally Combining Sampling Techniques for Monte Carlo Rendering. In *Proceedings of the 22nd Annual Conference on Computer Graphics and Interactive Techniques*, volume 29, page 419–428, 1995.

[58] Delio Vicini, Sébastien Speierer, and Wenzel Jakob. Path replay backpropagation: differentiating light paths using constant memory and linear time. *ACM Transactions on Graphics (TOG)*, 40(4):1–14, 2021.

[59] Delio Vicini, Sébastien Speierer, and Wenzel Jakob. Differentiable Signed Distance Function Rendering. *ACM Trans. Graph.*, –(-), 2022.

[60] Bruce Walter, Stephen R. Marschner, Hongsong Li, and Kenneth E. Torrance. Microfacet Models for Refraction through Rough Surfaces. In *Proceedings of the 18th Eurographics Conference on Rendering Techniques*, page 195–206, 2007.

[61] Peng Wang, Lingjie Liu, Yuan Liu, Christian Theobalt, Taku Komura, and Wenping Wang. Neus: Learning neural implicit surfaces by volume rendering for multi-view reconstruction. *NeurIPS*, 2021.

[62] Zian Wang, Jonah Philion, Sanja Fidler, and Jan Kautz. Learning indoor inverse rendering with 3d spatially-varying lighting. In *Proceedings of International Conference on Computer Vision (ICCV)*, 2021.

[63] Zirui Wang, Shangzhe Wu, Weidi Xie, Min Chen, and Victor Adrian Prisacariu. NeRF−−: Neural radiance fields without known camera parameters. *arXiv preprint arXiv:2102.07064*, 2021.

[64] Michael Weinmann and Reinhard Klein. Advances in Geometry and Reflectance Acquisition (Course Notes). In *SIGGRAPH Asia 2015 Courses*, 2015.

[65] Suttisak Wizadwongsa, Pakkapon Phongthawee, Jiraphon Yenphraphai, and Supasorn Suwajanakorn. NeX: Real-time View Synthesis with Neural Basis Expansion. In *IEEE Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

[66] Yao Yao, Zixin Luo, Shiwei Li, Jingyang Zhang, Yufan Ren, Lei Zhou, Tian Fang, and Long Quan. Blendedmvs: A large-scale dataset for generalized multi-view stereo networks. *Computer Vision and Pattern Recognition (CVPR)*, 2020.

[67] Lior Yariv, Yoni Kasten, Dror Moran, Meirav Galun, Matan Atzmon, Basri Ronen, and Yaron Lipman. Multiview neural surface reconstruction by disentangling geometry and appearance. *Advances in Neural Information Processing Systems*, 33, 2020.

[68] Alex Yu, Ruilong Li, Matthew Tancik, Hao Li, Ren Ng, and Angjoo Kanazawa. PlenOctrees for Real-time Rendering of Neural Radiance Fields. In *International Conference on Computer Vision (ICCV)*, 2021.

[69] Tizian Zeltner, Sébastien Speierer, Iliyan Georgiev, and Wenzel Jakob. Monte Carlo Estimators for Differential Light Transport. *ACM Trans. Graph.*, 40(4), 2021.

[70] Cheng Zhang, Bailey Miller, Kai Yan, Ioannis Gkioulekas, and Shuang Zhao. Path-Space Differentiable Rendering. *ACM Trans. Graph.*, 39(4):143:1–143:19, 2020.

[71] Kai Zhang, Fujun Luan, Qianqian Wang, Kavita Bala, and Noah Snavely. PhySG: Inverse Rendering with Spherical Gaussians for Physics-based Material Editing and Relighting. In *The IEEE/CVF Conference on Computer Vision and Pattern Recognition (CVPR)*, 2021.

[72] Kai Zhang, Gernot Riegler, Noah Snavely, and Vladlen Koltun. Nerf++: Analyzing and improving neural radiance fields. *arXiv:2010.07492*, 2020.

[73] Xiuming Zhang, Pratul P. Srinivasan, Boyang Deng, Paul Debevec, William T. Freeman, and Jonathan T. Barron. NeRFactor: Neural Factorization of Shape and Reflectance Under an Unknown Illumination. *CoRR*, abs/2106.01970, 2021.

[74] Yuxuan Zhang, Wenzheng Chen, Huan Ling, Jun Gao, Yinan Zhang, Antonio Torralba, and Sanja Fidler. Image GANs meet Differentiable Rendering for Inverse Graphics and Interpretable 3D Neural Rendering. In *International Conference on Learning Representations*, 2021.

[75] Yuanqing Zhang, Jiaming Sun, Xingyi He, Huan Fu, Rongfei Jia, and Xiaowei Zhou. Modeling Indirect Illumination for Inverse Rendering. *arXiv:2204.06837*, 2022.

[76] Matthias Zwicker, Wojciech Jarosz, Jaakko Lehtinen, Bochang Moon, Ravi Ramamoorthi, Fabrice Rousselle, Pradeep Sen, Cyril Soler, and Sung-Eui Yoon. Recent Advances in Adaptive Sampling and Reconstruction for Monte Carlo Rendering. *Computer Graphics Forum (Proceedings of Eurographics - State of the Art Reports)*, 34(2):667–681, 2015.