Linear-Time Gaussian Processes Using Binary Tree Kernels

Abstract

Gaussian processes (GPs) produce good probabilistic models of functions, but most GP kernels require $O((n + m)n^2)$ time, where n is the number of data points and m the number of predictive locations. We present a new kernel that allows for Gaussian process regression in $O(n + m)$ time. Our "binary tree" kernel places all data points on the leaves of a binary tree, with the kernel depending only on the depth of the deepest common ancestor. We can store the resulting kernel matrix in $O(n)$ space, as a sum of sparse rank-one matrices, and approximately invert the kernel matrix in $O(n)$ time. Sparse GP methods also offer $O(n)$ run time, but they predict less well than higher dimensional kernels. On a classic suite of regression tasks, we compare our kernel against Matérn, sparse, and sparse variational kernels. The binary tree GP assigns the highest likelihood to the test data on a plurality of datasets, usually achieves lower mean squared error than the sparse methods, and often ties or beats the Matérn GP. On large datasets, the binary tree GP is fastest, and much faster than a Matérn GP.

1 Introduction

Gaussian processes (GPs) can be used to perform regression with high-quality uncertainty estimates, but they are slow. Naïvely, GP regression requires $O(n^3 + n^2m)$ computation time and $O(n^2)$ computation space when predicting at m locations given n data points [24]. A kernel matrix of size $n \times n$ must be inverted (or Cholesky decomposed), and then m matrix-vector multiplications must be done with that inverse matrix (or m linear solves with the Cholesky factors). A few methods that we will discuss later achieve $O(n^2m)$ time complexity [21, 26].

With special kernels, GP regression can be faster and use less space. Inducing point methods, using z inducing points, allow regression to be done in $O(z^2(n + m))$ time and in $O(z^2 + zn)$ space [16, 17, 18, 9]. We will discuss the details of these inducing point kernels later, but they are kernels in their own right, not just approximations to other kernels. Unfortunately, if we have observed the function value at a location x, and have to predict the function value at that location x, these inducing point kernels do not automatically predict the observed value at x with very little uncertainty (unless x is one of our inducing points). This is the easiest possible prediction problem—simple recall. Inducing point methods fail it.

We present a new kernel, the *binary tree kernel*, that also allows for GP regression in $O(n + m)$ time and space (both model fitting and prediction). Unlike inducing point kernels, with the binary tree kernel, if x is both a training data point and a predictive location, it will produce an accurate and appropriately confident prediction. The fact that inducing point kernels fail this sanity check should make us suspicious of their performance in general.

A simple depiction of our kernel is shown in Figure 1, which we will define precisely in Section 3. First, we create a procedure for placing all data points on the leaves of a binary tree. Given the

binary tree, the kernel between two points depends only on the depth of the deepest common ancestor. Because very different tree structures are possible for the data, we can easily form an ensemble of diverse GP regression models. Figure 2 depicts a schematic sample from a binary tree kernel. Tree-based models are a well-known tool in machine learning [20].

On a standard suite of benchmark regression tasks [21], we show that, on average, our kernel achieves better negative log likelihood (NLL) than state-of-the-art sparse methods and conjugate-gradient-based "exact" methods, at lower computational cost in the big-data regime.

There are not many limitations to using our kernel. The main limitation is that other kernels sometimes capture the relationships in the data better. We do not have a good procedure for understanding when data has more Matérn character or more binary tree character (except through running both and comparing training NLL). But given that the binary tree kernel usually outperforms the Matérn, we'll tentatively say the best first guess is that a new dataset has more binary tree character. One concrete limitation for some applications, like Bayesian Optimization, is that the posterior mean is piecewise-flat, so gradient-based heuristics for finding extrema would not work.

Figure 1: A binary tree kernel with four data points. In this example, $k(x_1, x_1) = 1$, $k(x_1, x_2) = 0$, $k(x_1, x_3) = 0.8$, and $k(x_1, x_4) = 0.3$.

In contexts where a piecewise-flat posterior mean is suitable, we struggle to see when one would prefer a sparse or sparse variational GP to a binary tree kernel. The most thorough approach would be to run both and see which has a better training NLL, but if you had to pick one, the binary tree GP seems to be better performing and comparably fast. If minimizing mean-squared error is the objective, the Matérn kernel seems to do slightly better than the binary tree. If the dataset is small, and one needs a very fast prediction, a Matérn kernel may be the best option. But otherwise, if one cares about well-calibrated predictions, these initial results we present tentatively suggest using a binary tree kernel over the widely-used Matérn kernel.

The linear time and space complexity of the binary tree GP, with performance *exceeding* a "normal" kernel, could profoundly expand the viability of Gaussian process regression to larger datasets.

2 Preliminaries

Our problem setting is regression. Given a function $f : \mathcal{X} \to \mathbb{R}$, for some arbitrary set $\mathcal{X}$, we would like to predict $f(x)$ for various $x \in \mathcal{X}$. What we have are observations of $f(x)$ for various (other) $x \in \mathcal{X}$. Let $X \in \mathcal{X}^n$ be an n-tuple of elements of $\mathcal{X}$, and let $y \in \mathbb{R}^n$ be an n-tuple of real numbers, such that $y_i \sim f(X_i) + \mathcal{N}(0, \lambda)$, for $\lambda \in \mathbb{R}^{\geq 0}$. X and y comprise our training data.

With an m-tuple of test locations $X' \in \mathcal{X}^m$, let $y' \in \mathbb{R}^m$, with $y'_i = f(X'_i)$. y' is the ground truth for the target locations. Given training data, we would like to produce a distribution over $\mathbb{R}$ for each target location X'_i, such that it assigns high marginal probability to the unknown y'_i. Alternatively, we sometimes would like to produce point estimates $\hat{y}'_i$ in order to minimize the squared error $(\hat{y}'_i - y'_i)^2$.

A GP prior over functions is defined by a mean function $m : \mathcal{X} \to \mathbb{R}$, and a kernel $k : \mathcal{X} \times \mathcal{X} \to \mathbb{R}$. The expected function value at a point x is defined to be $m(x)$, and the covariance of the function values at two points x_1 and x_2 is defined to be $k(x_1, x_2)$.

Figure 2: A schematic diagram of a function sampled from a binary tree kernel. The function is over the interval [0, 1], and points on the interval are placed onto the leaves of a depth-4 binary tree according to the first 4 bits of their binary expansion. The sampled function is in black. Purple represents the sample if the tree had depth 3, green depth 2, orange depth 1, and red depth 0.

Let $K_{XX} \in \mathbb{R}^{n \times n}$ be the matrix of kernel values $(K_{XX})_{ij} = k(X_i, X_j)$, and let $m_X \in \mathbb{R}^n$ be the vector of mean values $(m_X)_i = m(X_i)$. For a GP to be well-defined, the kernel must be such that K_{XX} is positive semidefinite for any $X \in \mathcal{X}^n$. For a point $x \in \mathcal{X}$, Let $K_{Xx} \in \mathbb{R}^n$ be the vector of kernel values: $(K_{Xx})_i = k(X_i, x)$, and let $K_{xX} = K_{Xx}^\top$. Let $\lambda \geq 0$ be the variance of observation noise. Let μ_x and σ_x^2 be the mean and variance of our posterior predictive distribution at x. Then, with $K_{XX}^{\lambda\text{inv}} = (K_{XX} + \lambda I)^{-1}$,

$$\mu_x := (y - m_X)^\top K_{XX}^{\lambda\text{inv}} K_{Xx} + m(x) \quad (1) \qquad \sigma_x^2 := k(x,x) - K_{xX} K_{XX}^{\lambda\text{inv}} K_{Xx} + \lambda. \quad (2)$$

See Williams and Rasmussen [24] for a derivation. We compute Equations 1 and 2 for all $x \in X'$.

3 Binary tree kernel

We now introduce the binary tree kernel. First, we encode our data points as binary strings. So we have $\mathcal{X} = \mathbb{B}^q$, where $\mathbb{B} = \{0, 1\}$, and $q \in \mathbb{N}$.

If $\mathcal{X} = \mathbb{R}^d$, we must map $\mathbb{R}^d \mapsto \mathbb{B}^q$. First, we rescale all points (training points and test points) to lie within the box $[0,1]^d$. (If we have a stream of test points, and one lands outside of the box $[0,1]^d$, we can either set K_{xX} to $\mathbf{0}$ for that point or we rescale and retrain in $O(n)$ time.) Then, for each $x \in [0,1]^d$, for each dimension, we take the binary expansion up to some precision p, and for those $d \times p$ bits, we permute them using some fixed permutation. We call this permutation the bit order, and it is the same for all $x \in [0,1]^d$. Note that now $q = dp$. See Figure 3 for an example. We optimize the bit order during training, and we can also form an ensemble of GPs using different bit orders.

For $x \in \mathbb{B}^q$, let $x^{\leq i}$ be the first i bits of x. $[\![\text{expression}]\!]$ evaluates to 1, if expression is true, otherwise 0. We now define the kernel:

Definition 1 (Binary Tree Kernel). *Given a weight vector $w \in \mathbb{R}^q$, with $w \succeq 0$ and $||w||_1 = 1$,*

$$k_w(x_1, x_2) = \sum_{i=1}^q w_i \left[\!\left[x_1^{\leq i} = x_2^{\leq i} \right]\!\right]$$

So the more leading bits shared by x_1 and x_2, the larger the covariance between the function values. Consider, for example, points x_1 and x_4 from Figure 1, where x_1 is (left, left, right), and x_4 is (left, right, right); they share only the first leading "bit". We train the weight vector w to maximize the likelihood of the training data.

$x_1 (0 . 1 1 0 1 , 0 . 0 1 0 0)$
$x_2 (0 . 1 1 1 0 , 0 . 1 0 1 0)$

$x_1\ 1 0 0 1 1 0 0 1$
$x_2\ 1 1 1 1 0 1 0 0$

Figure 3: Function from $[0,1]^2 \to \mathbb{B}^8$.

Proposition 1 (Positive Semidefiniteness). *For $X \in \mathcal{X}^n$, for $k = k_w$, $K_{XX} \succeq 0$.*

Proof. Let $s \in \bigcup_{r=1}^q \mathbb{B}^r$ be a binary string, and let $|s|$ be the length of s. Let $X_{[s]} \in \mathbb{R}^n$ with $(X_{[s]})_i = \left[\!\left[X_i^{\leq |s|} = s \right]\!\right]$. $X_{[s]} X_{[s]}^\top$ is clearly positive semidefinite. Finally,

$$K_{XX} = \sum_{i=1}^q \sum_{s \in \mathbb{B}^i} w_i X_{[s]} X_{[s]}^\top \tag{3}$$

and recall $w_i \geq 0$, so $K_{XX} \succeq 0$. $\qquad\square$

4 Sparse rank one sum representation

In order to do GP regression in $O(n)$ space and time, we develop a "Sparse Rank One Sum" representation of linear operators (SROS). In SROS form, linear transformation of a vector can be done in $O(n)$ time instead of $O(n^2)$. We will store our kernel matrix and inverse kernel matrix in SROS form. The proof of Proposition 1 exemplifies representing a matrix as the sum of sparse rank one matrices. Note that each $X_{[s]}$ is sparse—if q is large, most $X_{[s]}$'s are the zero vector.

We now show how to interpret an SROS representation of an $n \times n$ matrix. Let $[n] = \{1, 2, ..., n\}$. For $m \in \mathbb{N}$, let $L : [m]^n \times [m]^n \times \mathbb{R}^n \times \mathbb{R}^n \to \mathbb{R}^{n \times n}$ construct a linear operator from four vectors.

Definition 2 (Linear Operator from Simple SROS Representation). *Let $p, p' \in [m]^n$, and let $u, u' \in \mathbb{R}^n$. Let $u^{p=i} \in \mathbb{R}^n$ be the vector where $u_j^{p=i} = u_j [\![p_j = i]\!]$, and likewise for u' and p'. Then:*

$$L(p, p', u, u') \mapsto \sum_{i=1}^{m} (u^{p=i})((u')^{p'=i})^\top.$$

We depict Definition 2 in Figure 4. p and p' represent partitions over n elements: all elements with the same integer value in the vector p belong to the same partition. If $p = p'$ (which is almost always the case for us) and the elements of p, u, and u' were shuffled so that all elements in the same partition were next to each other, then $L(p, p', u, u')$ would be block diagonal. Note that $L(p, p', u, u')$ is not necessarily low rank. If p is the finest possible partition, and $p = p'$, $L(p, p', u, u')$ is diagonal. SROS matrices can be thought of as a generalization of two types of matrix that are famously amenable to fast computation: rank one matrices (all points in the same partition) and diagonal matrices (each point in its own partition).

Figure 4: A matrix in standard form constructed from a matrix in SROS form. The large square depicts the matrix $L(p, p', u, u') \in \mathbb{R}^{5 \times 5}$ with elements colored by value. See $u^{p=0}$ for a color legend.

We now extend the definition of L to allow for multiple p, p', u, and u' vectors.

Definition 3 (Linear Operator from SROS Representation). *Let $L : [m]^{n \times q} \times [m]^{n \times q} \times \mathbb{R}^{n \times q} \times \mathbb{R}^{n \times q} \to \mathbb{R}^{n \times n}$. Let $P, P' \in [m]^{n \times q}$, and let $U, U' \in \mathbb{R}^{n \times q}$. Let $P_{:,i}, U_{:,i}$, etc. be the i^{th} columns of the respective arrays. Then: $L(P, P', U, U') \mapsto \sum_{i=1}^{q} L(P_{:,i}, P'_{:,i}, U_{:,i}, U'_{:,i})$.*

Algorithm 1 performs linear transformation of a vector using SROS representation in $O(nq)$ time.

Algorithm 1 Linear Transformation with SROS Linear Operator. This can be vectorized on a Graphical Processing Unit (GPU), using e.g. `torch.Tensor.index_add_` for Line 5 and non-slice indexing for Line 6 [14]. Slight restructuring allows vectorization over $[q]$ as well.

Require: $P, P' \in [m]^{n \times q}$, $U, U' \in \mathbb{R}^{n \times q}$, $x \in \mathbb{R}^n$
Ensure: $y = L(P, P', U, U')x$
1: $y \leftarrow \mathbf{0} \in \mathbb{R}^n$
2: **for** $i \in [q]$ **do** $\triangleright O(nq)$ time
3:     $p, p', u, u' \leftarrow P_{:,i}, P'_{:,i}, U_{:,i}, U'_{:,i}$
4:     $z \leftarrow \mathbf{0} \in \mathbb{R}^m$ $\triangleright z_i$ will store the dot product $((u')^{p'=i})^\top x^{p'=i}$
5:     **for** $j \in [n]$ **do** $z_{p'_j} \leftarrow z_{p'_j} + u'_j x_j$ $\triangleright O(n)$ time
6:     **for** $j \in [n]$ **do** $y_j \leftarrow y_j + z_{p_j} u_j$ $\triangleright O(n)$ time
    return y

We now discuss how to approximately invert a certain kind of symmetric SROS matrix, but our methods could be extended to asymmetric matrices. First, we define a partial ordering over partitions. For two partitions p, p', we say $p' \leq p$ if p' is finer than or equal to p; that is, $p'_i = p'_j \implies p_i = p_j$. Using that partial ordering, a symmetric SROS matrix can be approximately inverted efficiently if for all $1 \leq i, j \leq q$, $P_{:,i} \leq P_{:,j}$ or $P_{:,j} \leq P_{:,i}$. As the reader may have recognized, our kernel matrix K_{XX} can be written as an SROS matrix with this property.

We will write symmetric SROS matrices in a slightly more convenient form. All $(u')^{p=i}$ must be a constant times $u^{p=i}$. We will store these constants in an array C. Let $L(P, C, U)$ be shorthand for $L(P, P, U, C \odot U)$, where $\odot$ denotes element-wise multiplication. For $L(P, C, U)$ to be symmetric, it must be the case that $P_{kj} = P_{lj} \implies C_{kj} = C_{lj}$. Then, all elements of U corresponding to a given $u^{p=i}$ are multiplied by the same constant. We now present an algorithm for calculating $(L(P, C, U) + \lambda I)^{-1}$, for $\lambda \neq 0$. We have not yet analyzed numerical sensitivity for $\lambda \to 0$, but we conjecture that all floating point numbers involved need to be stored to at least $\log_2(1/\lambda)$ bits. Without loss of generality, let $\lambda = 1$, and note $(L(P, C, U) + \lambda I)^{-1} = \lambda^{-1}(L(P, \lambda^{-1}C, U) + I)^{-1}$.

By assumption, all columns of P are comparable with respect to the partial ordering above, so we can reorder the columns of P such that $P_{:,i} \geq P_{:,j}$ for $i < j$. The key identity that we use to develop our fast inversion algorithm is the Sherman–Morrison Formula:

$$(A + cuu^\top)^{-1} = A^{-1} - \frac{A^{-1}uu^\top A^{-1}}{c^{-1} + u^\top A^{-1}u} \tag{4}$$

Starting with $A = I$, we add the sparse rank one matrices iteratively, from the finest partition to the coarsest one, updating A^{-1} as we go. We represent $(L(P,C,U) + I)^{-1}$ in the form $I + L(P,C',U')$, so we write an algorithm that returns C' and U'. We can also quickly calculate $\log|L(P,C,U) + I|$ at the same time, using the matrix determinant lemma: $|A + cuu^\top| = (1 + cu^\top A^{-1}u)|A|$.

Theorem 1 (Fast Inversion). *For $P \in [m]^{n \times q}$ and $C, U \in \mathbb{R}^{n \times q}$, if $P_{:,i} \overset{\text{(is coarser than)}}{\geq} P_{:,j}$ for $i < j$, then there exists $C', U' \in \mathbb{R}^{n \times q}$, such that $(L(P,C,U) + I)^{-1} = I + L(P,C',U')$. There exists an algorithm for computing C' and U' that takes $O(nq^2)$ time.*

Proof. For $X \in \mathbb{R}^{n \times m}$, let $X_{:,i+1:m} \in \mathbb{R}^{n \times (m-i)}$ be columns $i + 1$ through m of matrix X (inclusive). Let $A_i = I + L(P_{:,i+1:q}, C_{:,i+1:q}, U_{:,i+1:q})$, and $A_q = I$. Now suppose A_i^{-1} can be written as $I + L(P_{:,i+1:q}, C'_{:,i+1:q}, U'_{:,i+1:q})$ for some C' and U'. For the base case of $i = q$, this holds trivially. We show it also holds for $i - 1$, and we can compute $C'_{:,i:q}, U'_{:,i:q}$ in $O(n(q-i))$ time. Let $p = P_{:,i}$, $u = U_{:,i}$, and $c = C_{:,i}$. Consider $u^{p=j}$, where each element is zero unless the corresponding element of p equals j. What do we know about the product $A_i^{-1} u^{p=j}$ (as seen in Equation 4)?

Because we have reordered the columns of P from coarse partitions to fine ones, all of the vectors generating the sparse rank one components of $L(P_{:,i+1:q}, C'_{:,i+1:q}, U'_{:,i+1:q})$ are from partitions that are equal to or finer than p. Thus, they are either zero everywhere $u^{p=j}$ is zero, or zero everywhere $u^{p=j}$ is nonzero. Vectors v of the second kind can be ignored, as $cvv^\top u^{p=j} = 0$. Thus, when multiplying $L(P_{:,i+1:q}, C'_{:,i+1:q}, U'_{:,i+1:q})$ by $u^{p=j}$, the only relevant vectors are filled with zeros except where the corresponding element of p equals j. So we can get rid of those rows of $P_{:,i+1:q}$, $C_{:,i+1:q}$, and $U_{:,i+1:q}$. Suppose there are n_j elements of p that equal j. Then $L(P_{:,i+1:q}, C'_{:,i+1:q}, U'_{:,i+1:q})u^{p=j}$ involves n_j rows, and can be computed in $O(n_j(q-i))$ time. Moreover, this product, which we will call $(u')^{p=j}$, is only nonzero when the corresponding element of p equals j, so it has the same sparsity pattern as $u^{p=j}$. The other component of A_i^{-1} is the identity matrix, and $Iu^{p=j}$ clearly has the same sparsity as $u^{p=j}$. Thus, returning to Equation 4, when we add $u^{p=j}(u^{p=j})^\top$ to A_i, we update A_i^{-1} with an outer product of vectors whose sparsity pattern is the same as that of $u^{p=j}$.

For each j, A_i^{-1} need not be updated with each $u^{p=j}$ one at a time. For $j \neq j'$, $u^{p=j}$ and $u^{p=j'}$ are nonzero at separate indices, so $u^{p=j}$ and $(u')^{p=j'}$ are nonzero at separate indices, so the extra component of A_i^{-1} that appears after after the $u^{p=j'}$ update is irrelevant to the $u^{p=j}$ update. Since the $u^{p=j}$ update takes $O(n_j(q-i))$ time, all of them together take $O(\sum_j n_j(q-i))$ time, which equals $O(n(q-i))$ time. Calculating c'_i only involves computing the denominator in Equation 4, using a matrix-vector product already computed. So we can write $C'_{:,i:q}$ and $U'_{:,i:q}$ by adding a preceding column to $C'_{:,i+1:q}$ and $U'_{:,i+1:q}$, using the same partition p, and we can do it in $O(n(q-i))$ time.

Following the induction down to $i = 0$, we have $(L(P,C,U) + I)^{-1} = I + L(P,C',U')$, and a total time of $O(nq^2)$. $\qquad\square$

Algorithm 2 also performs approximate inversion, which we prove in Appendix A, but differs slightly from the algorithm in the proof above. Algorithm 2 can take full advantage of a GPU speedup. In the special setting where all the columns of U are identical, observe that in Lines 10 and 11, the same computation is being repeated for all $k \in [i]$. Indeed, in this setting, this block of code can be modified to run in $O(n)$ time and space rather than $O(ni)$, making the whole algorithm run in $O(nq)$ time, as shown in Proposition 4 in Appendix A.

Algorithm 2 Inverse and determinant of $I+$ SROS Linear Operator. Lines 5 through 11 can all be easily vectorized on a GPU. Lines 5 and 10 require `torch.Tensor.index_add_` or equivalent, and lines 6 and 11 require non-slice indexing, which are not quite as fast as some GPU operations.

Require: $P \in [m]^{n \times q}, C, U \in \mathbb{R}^{n \times q}$
Ensure: $I + L(P, C', U') = (I + L(P, C, U))^{-1}; x = \log |I + L(P, C, U)|$
1: $x, C', U' \leftarrow 0, \mathbf{0} \in \mathbb{R}^{n \times q}, U$
2: **for** $i \in (q, q-1, ..., 1)$ **do** $\qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad \triangleright O(nq^2)$ time
3: $\qquad p, c, u, u' \leftarrow P_{:,i}, C_{:,i}, U_{:,i}, U'_{:,i}$
4: $\qquad z \leftarrow \mathbf{0} \in \mathbb{R}^m \qquad\qquad \triangleright z_i$ will store $c^{(i)}((u')^{p=i})^\top u^{p=i}$, where $c^{(i)} = c_k$ if $p_k = i$
5: $\qquad$ **for** $j \in [n]$ **do** $z_{p_j} \leftarrow z_{p_j} + c_j u'_j u_j \qquad\qquad\qquad\qquad\qquad \triangleright O(n)$ time
6: $\qquad$ **for** $j \in [n]$ **do** $C'_{ji} \leftarrow -c_j/(1 + z_{p_j}) \qquad\qquad\qquad\qquad\qquad \triangleright O(n)$ time
7: $\qquad$ **for** $i \in [m]$ **do** $x \leftarrow x + \log(1 + z_i) \qquad\qquad\qquad\qquad\qquad \triangleright O(n)$ time
8: $\qquad$ **if** i > 0 **then**
9: $\qquad\qquad y \leftarrow \mathbf{0} \in \mathbb{R}^{n \times i} \qquad\qquad\qquad\qquad\qquad\qquad\qquad\qquad \triangleright O(ni)$ time
10: $\qquad\qquad$ **for** $j, k \in [n] \times [i-1]$ **do** $y_{p_j k} \leftarrow y_{p_j k} + u'_j U_{jk} \qquad\qquad \triangleright O(ni)$ time
11: $\qquad\qquad$ **for** $j, k \in [n] \times [i-1]$ **do** $U'_{jk} \leftarrow U'_{jk} + C'_{ji} u'_j y_{p_j k} \qquad \triangleright O(ni)$ time
$\qquad$ **return** C', U', x

---

5 Binary tree Gaussian process

We now show that our kernel matrix K_{XX} can be written in SROS form, with P containing successively finer partitions. Thus, K_{XX} can be approximately inverted quickly, for use in Equations 1 and 2. Next, we'll show that we can efficiently optimize the log likelihood of the training data by tuning the weight vector w along with the bit order. The log likelihood can be calculated in $O(nq)$ time and the gradient w.r.t. w in $O(nq^2)$ time.

Recall Equation 3 in the proof of Proposition 1: $K_{XX} = \sum_{i=1}^q \sum_{s \in \mathbb{B}^i} w_i X_{[s]} X_{[s]}^\top$, where $X_{[s]} \in \mathbb{R}^n$ with $(X_{[s]})_i = \left[\left[X_i^{\leq |s|} = s \right]\right]$. So we will set $P_{:,i}$, $C_{:,i}$, and $U_{:,i}$, so that $L(P_{:,i}, C_{:,i}, U_{:,i}) = \sum_{s \in \mathbb{B}^i} w_i X_{[s]} X_{[s]}^\top$. Let $P_{:,i}$ partition the set of points X so that points are in the same partition if the first i bits match. Now, requiring the first $i+1$ bits to match is a stricter criterion than requiring the first i bits to match, so the $P_{:,i}$ grow successively finer. For any piece of the partition where the first i bits of the constituent points equals the bitstring s, the corresponding sparse rank one component of K_{XX} is $w_i X_{[s]} X_{[s]}^\top$. So let $U_{:,i} = \mathbf{1}^n$, and let $C_{:,i} = w_i \mathbf{1}^n$.

Proposition 2 (SROS Form Kernel). $K_{XX} = L(P, C, U)$, *as defined above.*

This follows immediately from the definitions. To compute these partitions $P_{:,i}$, we sort X, which is a set of bit strings. And then we can easily compute which points have the same first i bits. This all takes $O(nq \log n)$ time. Now note that $U_{:,i} = U_{:,j}$ for all i, j, so $(K_{XX} + \lambda I)^{-1}$ and $|K_{XX} + \lambda I|$ can be computed in $O(nq)$ time, rather than $O(nq^2)$.

The training negative log likelihood of a GP is that of the corresponding multivariate Gaussian on the training data. So: $\text{NLL}(w) = \frac{1}{2}\left(y^\top (K_{XX}(w) + \lambda I)^{-1} y + \log |K_{XX}(w) + \lambda I| + n \log(2\pi)\right)$. This can be computed in $O(nq)$ time, since matrix-vector multiplication takes $O(nq)$ time for a matrix in SROS form. So if the bit order is unchanged, an optimization step can be done in $O(nq)$ time, and if the data needs to be resorted, then in $O(nq \log n)$ time. On the largest dataset we tested (House Electric), with $n \approx 1.3$ million and $q = 88$, sorting the data and computing P takes about 0.96 seconds on a GPU, and then calculating the negative log likelihood takes about another 1.08 seconds. We show in Appendix B how to compute $\nabla_w \text{NLL}$ in $O(nq^2)$ time.

To optimize the bit order and weight vector at the same time, we represent both with a single parameter vector $\theta \in \mathbb{R}_+^q$, with $||\theta||_\infty = 1$. To get the bit order from θ, we start with a default bit order and permute the bit order according to a permutation that would sort θ in descending order. To get the weight vector, we sort θ in descending order, add a 0 at the end, and compute the differences between adjacent elements. When there are ties in the elements of θ, the choice of bit order does not affect the negative log likelihood (or the kernel at all) because the relevant associated weight is 0. The negative

232 log likelihood is continuous with respect to θ, and when all values of θ are unique, it is differentiable
233 with respect to θ. Letting $\theta = e^\phi / ||e^\phi||_\infty$, we minimize loss w.r.t. ϕ using BFGS [6].

234 To calculate the predictive mean at a list of predictive locations X', we first multiply y by $(K_{XX} +$
235 $\lambda I)^{-1}$, and then we multiply that vector by $K_{XX'}$. We obtain both K_{XX} and $K_{XX'}$ in SROS
236 form using the following procedure. Let $\tilde{X} = X \circ X'$ be the concatenation of the two tuples,
237 now an $(n+m)$-tuple. Writing $K_{\tilde{X}\tilde{X}} = L(\tilde{P}, \tilde{C}, \tilde{U})$, the arrays on the r.h.s. can be computed in
238 $O((n+m)q \log(n+m))$ time. Then, with P, C, and U being the first n rows of $\tilde{P}, \tilde{C}, \tilde{U}$, $K_{XX} =$
239 $L(P, C, U)$. And letting P'' and U'' be the last m rows, $K_{XX'} = L(P, P'', C \odot U, U'')$. Thus, the
240 predictive mean μ_x from Equation 1 can be computed at m locations in $O((n+m)q \log(n+m))$
241 time.

242 The predictive covariance matrix, which extends the predictive variance from Equation 2, is calculated
243 $\Sigma_{X'} = K_{X'X'} + \lambda I_m - K_{X'X}(K_{XX} + \lambda I_n)^{-1}K_{XX'} = (K_{\tilde{X}\tilde{X}} + \lambda I_{m+n})/K_{XX}$, where $/$ denotes
244 the Schur complement. From a property of block matrix inversion, the last m columns of the last
245 m rows of $(K_{\tilde{X}\tilde{X}} + \lambda I)^{-1}$ equals $((K_{\tilde{X}\tilde{X}} + \lambda I_{m+n})/K_{XX})^{-1}$. So we get the predictive precision
246 matrix in $O((n+m)q \log(n+m))$ time by inverting $K_{\tilde{X}\tilde{X}} + \lambda I$ and taking the bottom right $m \times m$
247 block. Then, we get the predictive covariance matrix by inverting that. This takes $O(mq^2)$ time,
248 since it does not have the property of all the columns of U being equal. If we only want the diagonal
249 elements of an SROS matrix (the independent predictive variances in this case), we can simply sum
250 the rows of $C \odot U \odot U$ in $O(mq)$ time. Thus, in total, computing the independent predictive variances
251 requires $O((n+m)q \log(n+m) + mq^2)$ time. See Algorithm 3.

Algorithm 3 GP Regression with a binary tree kernel.

Require: $X \in \mathbb{B}^{n \times q}$, $y \in \mathbb{R}^n$, $X' \in \mathbb{B}^{m \times q}$, $w \in \mathbb{R}^q$, $\lambda \in \mathbb{R}^+$
Ensure: $\mu_{X'}$ and $\sigma_{X'}^2$ are the predictive means and variances at X', and nll the training negative log likelihood.
1: $\tilde{X} \leftarrow X \circ X'$
2: $\tilde{X}^\uparrow$, perm $\leftarrow$ Sort($\tilde{X}$)   ▷ The rows of X are sorted lexically from leading bit to trailing bit. $O((n+m)q \log(n+m))$ time.
3: **for** $i, j \in [n+m] \times [q]$ **do** $\tilde{P}_{ij}^\uparrow \leftarrow$ #of unique rows in $X_{1:i,1:j}^\uparrow$
4:      ▷ $M_{1:i,1:j}$ is the first i rows and j columns of M. $O((n+m)q)$ time.
5: $\tilde{P} \leftarrow$ perm$^{-1}(P^\uparrow)$ ▷ This "unsorts" the input. $O((n+m)q)$ time.
6: $P, P' \leftarrow \tilde{P}_{1:n}, \tilde{P}_{n+1:n+m}$
7: $U, U', \tilde{U} \leftarrow \mathbf{1}^{n \times q}, \mathbf{1}^{m \times q}, \mathbf{1}^{(n+m) \times q}$
8: $C, \tilde{C} \leftarrow \mathbf{1}^n w^T, \mathbf{1}^{n+m} w^T$
9: $C_\lambda^{-1}, U^{-1}, \text{logdet}_\lambda \leftarrow$ Invert($P, \lambda^{-1}C, U$)   ▷ Uses Algorithm 2. Speedup to $O(nq)$ time because columns of $\lambda^{-1}U$ are identical.
10: $C^{-1}, \text{logdet} \leftarrow \lambda^{-1}C_\lambda^{-1}, \text{logdet}_\lambda + n \log(\lambda)$
11: $z \leftarrow$ LinTransform($P, P, U^{-1}, C^{-1} \odot U^{-1}, y$) $+ \lambda^{-1}y$ ▷ Uses Algorithm 1 to compute the Woodbury vector. $O(nq)$ time.
12: $\mu_{X'} \leftarrow$ LinTransform($P', P, U', C \odot U, z$)   ▷ $O((n+m)q)$ time.
13: nll $\leftarrow (y^\top z + \text{logdet} + n \log(2\pi))/2$
14: $\tilde{C}^{\text{prec}}, \tilde{U}^{\text{prec}} \leftarrow$ Invert($\tilde{P}, \lambda^{-1}\tilde{C}, \lambda^{-1}\tilde{U}$)   ▷ $O((n+m)q)$ time.
15: $C^{\text{prec}}, U^{\text{prec}} \leftarrow \tilde{C}_{n+1:n+m}^{\text{prec}}, \tilde{U}_{n+1:n+m}^{\text{prec}}$
16: $C^{\text{cov}}, U^{\text{cov}} \leftarrow$ Invert($P', C^{\text{prec}}, U^{\text{prec}}$)   ▷ $O(mq^2)$ time; extra factor of q because columns of U^{prec} are not identical.
17: $\sigma_{X'}^2 \leftarrow \lambda(\mathbf{1}^m + \text{SumEachRow}(C^{\text{cov}} \odot U^{\text{cov}} \odot U^{\text{cov}}))$ ▷ $O(mq)$ time.
18: **return** $\mu_{X'}, \sigma_{X'}^2$, nll

---

6 Related Work

253 All existing kernels of which we are aware for $O(n)$ time GP regression on unstructured data involve
254 inducing points (related to the Nyström approximation [23]) or inducing frequencies. For a given set
255 of inducing points Z, for some base kernel k, the inducing point kernel (in its most basic form) is the
256 following, although subtle variants exist: $k^Z(x, x') = K_{xZ}K_{ZZ}^{-1}K_{Zx'}$ [16].

257 Sparse Gaussian Process Regression (SGPR) involves selecting Z, and then using k^Z (or a variant).
258 Notably, $K_{XX}^Z = K_{XZ}K_{ZZ}^{-1}K_{ZX}$ is low rank, providing computational efficiency. The predictive
259 mean and covariance have compact form, with observational noise λ: $\mu_x(Z) = K_{xZ}(\lambda K_{ZZ} + k_{ZX}k_{XZ})^{-1}K_{ZX}y$ and $\sigma_{xx'}^2(Z) = K_{xZ}(K_{ZZ} + \lambda^{-1}k_{ZX}k_{XZ})^{-1}K_{Zx'}$.
260

261 Titsias's [19] sparse variational kernel is also low rank and uses inducing points. The sparse variational
262 GP (SVGP) is constructed as the solution to a variational inference problem. It depends on inducing
263 points Z, data points X, and observed function values y. We have focused on Gaussian processes with
264 0 mean, but the SVGP method uses a nonzero prior mean along with a kernel: $m^{\text{SVGP}}(x) = \mu_x(Z)$
265 and $k^{\text{SVGP}}(x, x') = k(x, x') - K_{xZ}K_{ZZ}^{-1}K_{Zx'} + \sigma_{xx'}^2(Z)$. Given the dependence on X and y, this
266 is not a true probability distribution over function space. The variational problem underlying this
267 kernel also provides guidance in how to select the inducing points Z. For further discussion of the
268 kernel underlying the SVGP method, see Wild et al. [22].

269 An inducing point kernel with z inducing points produces a z-dimensional reproducing kernel Hilbert
270 space (RKHS). The dimensionality of the RKHS relates to the expressivity of the kernel. Whereas an
271 inducing point method buys a z-dimensional RKHS for the price of $O(z^2 n)$ time and $O(zn)$ space,
272 the binary tree kernel produces a 2^q-dimensional RKHS in $O(qn)$ time and space—an exponential
273 improvement. (Observe that we can find 2^q linearly independent functions of the form $k(\cdot, x)$—one
274 for each of the 2^q leaves x might belong to.) Wilson and Nickisch [25] develop a method for speeding
275 up inducing point methods significantly, especially in low-dimensional settings.

276 Lázaro-Gredilla et al. [11] propose an inducing frequencies kernel: given a set of m inducing vectors
277 s_i, $k(x, x') = 1/m \sum_{i=1}^{m} \cos(2\pi s_i^\top (x - x'))$. Dutordoir et al. [5] propose an inducing frequencies
278 kernel for low dimensional data, in which $k(x, x')$ is a special function of $x^\top x'$.

279 On one-dimensional data, filtering/smoothing methods perform Bayesian inference over functions
280 in $O(n)$ time [10, 8]. A few non-$O(n)$ methods bear mentioning. We are not the first to consider a
281 kernel over points on the leaves of a tree [13, 12], but their methods take $O(n^3)$ time. On certain kinds
282 of structured data, Toeplitz solvers achieve $O(n^2)$ time complexity [26]. Cutajar et al.'s [2], Wang
283 et al.'s [21], and others' use of a conjugate gradients solver to replace inversion/factorization has
284 unclear time complexity between $O(n^2)$ and $O(n^3)$, depending on the kernel matrix spectrum. [1]

7 Experiments

286 In Table 1, we compare our binary tree kernel and a binary tree ensemble (see Appendix C for details
287 on the ensemble) against three baseline methods: exact GP regression using a Matérn kernel, sparse
288 Gaussian process regression (SGPR) [18], and a stochastic variational Gaussian process (SVGP)
289 [9]. We evaluate our method on the same open-access UCI datasets [3] as Wang et al. [21], using
290 their same training, validation, and test partitions, and we compare against the baseline results they
291 report. For the binary tree (BT) kernels, we use $p = \min(8, \lfloor 150/d \rfloor + 1)$, and recall $q = pd$. We set
292 $\lambda = 1/n$. We train the bit order and weights to minimize training NLL. For the binary tree ensemble
293 (BTE), we use 20 kernels. For the Matérn kernel, we use Blackbox Matrix-Matrix multiplication
294 (BBMM) [7], which uses the conjugate gradients method to calculate $(K_{XX} + \lambda I)^{-1}$. SGPR uses
295 512 data points and SVGP uses 1,024 inducing points. We report the mean and two standard errors
296 across 3 replications with different dataset splits. For further experimental details, see Appendix C.
297 BTE achieves the best NLL on 6/12 datasets, and best RMSE on 5/12 datasets (including some ties).
298 Out of the 4 largest datasets, BT/BTE is fastest on 3. The run times are plotted in Figure 5. The code
299 is included in the supplementary material, and we will open source our code upon publication.

300 BT performs noticeably worse than BTE for test NLL on CTSlice due to over-fitting. There are
301 enough degrees of freedom when optimizing the bit order ($d = 385$) that BT kernel can over-fit to
302 the training data. The ensemble over multiple bit orders is much more robust.

---

[1]The conjugate gradients method takes $O(n^2 \sqrt{\kappa})$ time, where κ is the condition number of the kernel matrix. Poggio et al. [15] say "claims about the condition number of a random matrix A should also apply to kernel matrices with random data." If they mean a Wishart random matrix (which it should be if, e.g., $k(x, x') = x^\top x'$), that would be the square of the condition number of the corresponding Gaussian random matrix, which grows as $O(n)$ [1]. Putting it all together, we get $O(n^3)$ for conjugate gradients. We don't know how quickly preconditioning can reduce the condition number.

Dataset	n	d	BTE	BT	Matérn (BBMM)	SGPR	SVGP
PoleTele	9,600	26	$\mathbf{-0.625} \pm 0.035$	-0.490 ± 0.040	-0.180 ± 0.036	-0.094 ± 0.008	-0.001 ± 0.008
Elevators	10,623	18	0.649 ± 0.032	0.646 ± 0.023	0.619 ± 0.054	0.580 ± 0.060	$\mathbf{0.519} \pm 0.022$
Bike	11,122	17	$\mathbf{-0.708} \pm 0.433$	$\mathbf{-0.806} \pm 0.273$	0.119 ± 0.044	0.291 ± 0.032	0.272 ± 0.018
Kin40k	25,600	8	0.869 ± 0.004	0.881 ± 0.008	$\mathbf{-0.258} \pm 0.084$	0.087 ± 0.067	0.236 ± 0.077
Protein	29,267	9	$\mathbf{0.781} \pm 0.023$	0.845 ± 0.026	1.018 ± 0.056	0.970 ± 0.010	1.035 ± 0.006
KeggDir	31,248	20	-1.031 ± 0.020	-1.029 ± 0.021	-0.199 ± 0.381	$\mathbf{-1.123} \pm 0.016$	-0.940 ± 0.020
CTslice	34,240	385	$\mathbf{-2.527} \pm 0.147$	-1.092 ± 0.147	-0.894 ± 0.188	-0.073 ± 0.097	1.422 ± 0.005
Keggu	40,708	27	-0.667 ± 0.007	-0.667 ± 0.007	-0.419 ± 0.027	$\mathbf{-0.984} \pm 0.012$	-0.666 ± 0.007
3DRoad	278,319	3	$\mathbf{-0.251} \pm 0.009$	-0.252 ± 0.006	0.909 ± 0.001	0.943 ± 0.002	0.697 ± 0.002
Song	329,820	90	1.330 ± 0.003	1.331 ± 0.003	$\mathbf{1.206} \pm 0.024$	1.213 ± 0.003	1.417 ± 0.000
Buzz	373,280	77	1.198 ± 0.003	1.198 ± 0.003	0.267 ± 0.028	$\mathbf{0.106} \pm 0.008$	0.224 ± 0.050
HouseElec	1,311,539	11	$\mathbf{-2.569} \pm 0.006$	-2.492 ± 0.012	-0.152 ± 0.001	—	-1.010 ± 0.039
PoleTele	9,600	26	$\mathbf{0.154} \pm 0.006$	0.161 ± 0.004	$\mathbf{0.151} \pm 0.012$	0.217 ± 0.002	0.215 ± 0.002
Elevators	10,623	18	0.478 ± 0.021	0.476 ± 0.018	$\mathbf{0.394} \pm 0.006$	0.437 ± 0.018	$\mathbf{0.399} \pm 0.009$
Bike	11,122	17	$\mathbf{0.118} \pm 0.057$	$\mathbf{0.103} \pm 0.029$	0.220 ± 0.002	0.362 ± 0.004	0.303 ± 0.004
Kin40k	25,600	8	0.580 ± 0.003	0.587 ± 0.006	$\mathbf{0.099} \pm 0.001$	0.273 ± 0.025	0.268 ± 0.022
Protein	29,267	9	0.608 ± 0.008	0.623 ± 0.011	$\mathbf{0.536} \pm 0.012$	0.656 ± 0.010	0.668 ± 0.005
KeggDir	31,248	20	$\mathbf{0.086} \pm 0.003$	$\mathbf{0.086} \pm 0.003$	$\mathbf{0.086} \pm 0.005$	0.104 ± 0.003	0.096 ± 0.001
CTslice	34,240	385	$\mathbf{0.116} \pm 0.009$	0.132 ± 0.009	0.262 ± 0.448	0.218 ± 0.011	1.003 ± 0.005
Keggu	40,708	27	0.120 ± 0.001	0.121 ± 0.001	$\mathbf{0.118} \pm 0.000$	0.130 ± 0.001	0.124 ± 0.002
3DRoad	278,319	3	0.187 ± 0.002	0.186 ± 0.001	$\mathbf{0.101} \pm 0.007$	0.661 ± 0.010	0.481 ± 0.002
Song	329,820	90	0.914 ± 0.003	0.916 ± 0.003	$\mathbf{0.807} \pm 0.024$	0.803 ± 0.002	0.998 ± 0.000
Buzz	373,280	77	0.801 ± 0.002	0.801 ± 0.002	0.288 ± 0.018	0.300 ± 0.004	$\mathbf{0.304} \pm 0.012$
HouseElec	1,311,539	11	$\mathbf{0.029} \pm 0.001$	$\mathbf{0.029} \pm 0.001$	0.055 ± 0.000	—	0.084 ± 0.005
PoleTele	9,600	26	5.16 ± 0.58		$\mathbf{0.69} \pm 0.018$	1.16 ± 0.34	1.15 ± 0.068
Elevators	10,623	18	2.6 ± 0.19		$\mathbf{0.68} \pm 0.012$	1.16 ± 0.38	1.27 ± 0.092
Bike	11,122	17	2.68 ± 0.15		$\mathbf{0.69} \pm 0.015$	1.17 ± 0.38	1.28 ± 0.093
Kin40k	25,600	8	1.44 ± 0.028		$\mathbf{0.71} \pm 0.045$	1.62 ± 0.96	3.26 ± 0.23
Protein	29,267	9	2.92 ± 0.2		$\mathbf{0.8} \pm 0.17$	2.27 ± 0.9	3.31 ± 0.27
KeggDir	31,248	20	7.14 ± 0.39		$\mathbf{0.85} \pm 0.1$	2.2 ± 1.09	3.8 ± 0.38
CTslice	34,240	385	52.01 ± 0.92		$\mathbf{3.32} \pm 5.0$	2.16 ± 0.99	3.87 ± 0.34
Keggu	40,708	27	7.46 ± 0.54		$6.32^{*} \pm 0.41^{*}$	$\mathbf{2.22} \pm 1.05$	4.78 ± 0.4
3DRoad	278,319	3	$\mathbf{1.93} \pm 0.12$		$126.37^{*} \pm 20.92^{*}$	12.01 ± 5.51	34.09 ± 3.19
Song	329,820	90	31.87 ± 3.79		$33.79^{*} \pm 10.45^{*}$	$\mathbf{7.89} \pm 3.12$	39.55 ± 3.08
Buzz	373,280	77	$\mathbf{20.18} \pm 6.66$		$571.15^{*} \pm 66.34^{*}$	29.25 ± 18.33	46.35 ± 2.93
HouseElec	1,311,539	11	$\mathbf{118.41} \pm 3.93$		$575.64^{*} \pm 6.94^{*}$	—	367.71 ± 4.7

Table 1: NLL (top), RMSE (middle), and run time in minutes (bottom) on regression datasets, using a single GPU (Tesla V100-SXM2-16GB for BT and BTE and Tesla V100-SXM2-32GB for the other methods). The asterisk indicates an estimate of the time from the reported training time on 8 GPUS, assuming linear speedup in number of GPUs and independent noise in training times per GPU.

8 Discussion

We have proven that the binary tree kernel GP is scalable. Our empirical results suggest that it often outpredicts not just other scalable methods, but even the popular Matérn GP. If the results in this paper replicate in other domains, it could obviate wide usage of classic GP kernels like the Matérn kernel, as well as inducing point kernels. Sometimes, our kernel fails to capture patterns in the data; some functions' values simply do not covary this way. But other kernels we tested seemed to fail like that even more.

The SROS representation of linear operators, which we developed for this kernel, is conceptually general, and could potentially be useful in other domains where linear algebra is applied. Low-rank approximations are widely used to speed up linear transformations, and SROS representations might be an alternative in many settings.

Figure 5: Run times given dataset size. For BT, the trendline is calculated controlling for $\log(q)$ with affine regression, and then setting $q = 150$. The slope w.r.t. $\log(q)$ is 2.82 ± 1.06. Theoretically, all slopes are too low except for that of SVGP, presumably because of overhead in the small-data regime.

Our contributions to linear algebra and kernel design may significantly increase the size of data sets on which GPs can do state-of-the-art modelling.

References

[1] Zizhong Chen and Jack J Dongarra. Condition numbers of Gaussian random matrices. *SIAM Journal on Matrix Analysis and Applications*, 27(3):603–620, 2005.

[2] Kurt Cutajar, Michael Osborne, John Cunningham, and Maurizio Filippone. Preconditioning kernel matrices. In *International conference on machine learning*, pages 2529–2538. PMLR, 2016.

[3] Dheeru Dua and Casey Graff. UCI machine learning repository, 2017. URL http://archive.ics.uci.edu/ml.

[4] Philippe Duchon, Philippe Flajolet, Guy Louchard, and Gilles Schaeffer. Boltzmann samplers for the random generation of combinatorial structures. *Comb. Probab. Comput.*, 13(4–5): 577–625, jul 2004. ISSN 0963-5483. doi: 10.1017/S0963548304006315.

[5] Vincent Dutordoir, Nicolas Durrande, and James Hensman. Sparse Gaussian processes with spherical harmonic features. In *International Conference on Machine Learning*, pages 2793–2802. PMLR, 2020.

[6] Roger Fletcher. *Practical methods of optimization*. John Wiley & Sons, New York, 2nd edition, 2013.

[7] Jacob Gardner, Geoff Pleiss, Kilian Q Weinberger, David Bindel, and Andrew G Wilson. Gpytorch: Blackbox matrix-matrix Gaussian process inference with gpu acceleration. *Advances in neural information processing systems*, 31, 2018.

[8] Jouni Hartikainen and Simo Särkkä. Kalman filtering and smoothing solutions to temporal Gaussian process regression models. In *2010 IEEE international workshop on machine learning for signal processing*, pages 379–384. IEEE, 2010.

[9] James Hensman, Nicolò Fusi, and Neil D. Lawrence. Gaussian processes for big data. In *Proceedings of the Twenty-Ninth Conference on Uncertainty in Artificial Intelligence*, UAI'13, page 282–290, Arlington, Virginia, USA, 2013. AUAI Press.

[10] RE Kalman. A new approach to linear filtering and prediction problems. *Journal of Basic Engineering*, 83(1):95–108, 1960.

[11] Miguel Lázaro-Gredilla, Joaquin Quinonero-Candela, Carl Edward Rasmussen, and Aníbal R Figueiras-Vidal. Sparse spectrum Gaussian process regression. *The Journal of Machine Learning Research*, 11:1865–1881, 2010.

[12] Julien-Charles Lévesque, Audrey Durand, Christian Gagné, and Robert Sabourin. Bayesian optimization for conditional hyperparameter spaces. In *2017 International Joint Conference on Neural Networks (IJCNN)*, pages 286–293, 2017.

[13] Xingchen Ma and Matthew Blaschko. Additive tree-structured covariance function for conditional parameter spaces in Bayesian optimization. In Silvia Chiappa and Roberto Calandra, editors, *Proceedings of the Twenty Third International Conference on Artificial Intelligence and Statistics*, volume 108 of *Proceedings of Machine Learning Research*, pages 1015–1025. PMLR, 26–28 Aug 2020.

[14] Adam Paszke, Sam Gross, Francisco Massa, Adam Lerer, James Bradbury, Gregory Chanan, Trevor Killeen, Zeming Lin, Natalia Gimelshein, Luca Antiga, Alban Desmaison, Andreas Kopf, Edward Yang, Zachary DeVito, Martin Raison, Alykhan Tejani, Sasank Chilamkurthy, Benoit Steiner, Lu Fang, Junjie Bai, and Soumith Chintala. Pytorch: An imperative style, high-performance deep learning library. In *Advances in Neural Information Processing Systems 32*, pages 8024–8035. Curran Associates, Inc., 2019. URL http://papers.neurips.cc/paper/9015-pytorch-an-imperative-style-high-performance-deep-learning-library.pdf.

[15] Tomaso Poggio, Gil Kur, and Andrzej Banburski. Double descent in the condition number. *arXiv preprint arXiv:1912.06190*, 2019.

[16] Joaquin Quinonero-Candela and Carl Edward Rasmussen. A unifying view of sparse approximate Gaussian process regression. *The Journal of Machine Learning Research*, 6:1939–1959, 2005.

[17] Edward Snelson and Zoubin Ghahramani. Sparse Gaussian processes using pseudo-inputs. In Y. Weiss, B. Schölkopf, and J. Platt, editors, *Advances in Neural Information Processing Systems*, volume 18. MIT Press, 2005.

[18] Michalis Titsias. Variational learning of inducing variables in sparse Gaussian processes. In David van Dyk and Max Welling, editors, *Proceedings of the Twelth International Conference on Artificial Intelligence and Statistics*, volume 5 of *Proceedings of Machine Learning Research*, pages 567–574, Hilton Clearwater Beach Resort, Clearwater Beach, Florida USA, 16–18 Apr 2009. PMLR. URL `https://proceedings.mlr.press/v5/titsias09a.html`.

[19] Michalis Titsias. Variational learning of inducing variables in sparse Gaussian processes. In *Artificial intelligence and statistics*, pages 567–574. PMLR, 2009.

[20] William N Venables and Brian D Ripley. Tree-based methods. In *Modern applied statistics with S-Plus*, pages 303–327. Springer, 1999.

[21] Ke Wang, Geoff Pleiss, Jacob Gardner, Stephen Tyree, Kilian Q Weinberger, and Andrew Gordon Wilson. Exact Gaussian processes on a million data points. *Advances in Neural Information Processing Systems*, 32, 2019.

[22] Veit Wild, Motonobu Kanagawa, and Dino Sejdinovic. Connections and equivalences between the Nyström method and sparse variational Gaussian processes. *arXiv preprint arXiv:2106.01121*, 2021.

[23] Christopher Williams and Matthias Seeger. Using the Nyström method to speed up kernel machines. In T. Leen, T. Dietterich, and V. Tresp, editors, *Advances in Neural Information Processing Systems*, volume 13. MIT Press, 2000. URL `https://proceedings.neurips.cc/paper/2000/file/19de10adbaa1b2ee13f77f679fa1483a-Paper.pdf`.

[24] Christopher K Williams and Carl Edward Rasmussen. *Gaussian processes for machine learning*, volume 2. MIT press Cambridge, MA, 2006.

[25] Andrew Wilson and Hannes Nickisch. Kernel interpolation for scalable structured gaussian processes (kiss-gp). In *International conference on machine learning*, pages 1775–1784. PMLR, 2015.

[26] Yunong Zhang, William E Leithead, and Douglas J Leith. Time-series Gaussian process regression based on Toeplitz computation of $O(n^2)$ operations and $O(n)$-level storage. In *Proceedings of the 44th IEEE Conference on Decision and Control*, pages 3711–3716. IEEE, 2005.