EmbedKGQA: Improving Multi-hop Question Answering over Knowledge Graphs using Knowledge Base Embeddings

Reproducibility Summary

Scope of Reproducibility

Our work consists of four parts: (1) Reproducing results from Saxena et al. [2020] (2) Adding more experiments by replacing the knowledge graph embedding method (3) and exploring the question embedding method using various transformer models (4) Verifying the importance of Relation Matching (RM) module. Based on the code shared by the authors, we have reproduced the results for the EmbedKGQA method. We have not purposely performed relation matching to validate point-4.

Methodology

We have used the code provided by Saxena et al. [2020] with some customization for reproducibility. In addition to making the codebase more modular and easy to navigate, we have made changes to incorporate different transformers in the question embedding module. Question-Answering models were trained from scratch as no pre-trained models were available for our particular dataset. The code for this work is available on GitHub[1].

Results

We were able to reproduce the Hits@1 to be within $\pm$**2.35%** of reported value (in most cases). Anomalies were observed in 3 cases. [1] In MetaQA-KG-Full (3-hop) dataset [2] In WebQSP-KG-50 and [3] WebQSP-KG-Full datasets. From our experiments on the QA model, we have found that a recent transformer architecture, SBERT (Reimers and Gurevych [2019]) produced even better accuracy than the paper. Replacing RoBERTa (Liu et al. [2019]) with SBERT (Reimers and Gurevych [2019]) increased the absolute accuracy by $\approx$3.4% in half KG case and $\approx$0.6% in the full KG case. (KG: Knowledge Graph, "$\approx$": Approximately)

What was easy

As the code was open-sourced, we didn't have to implement the paper giving us the liberty to customize the codebase to focus on the author's claim validation, perform extended experiments and explore shared as well as new models. In addition to this, pretrained KG embedding models were shared which helped in the reproduction experiment.

What was difficult

The lack of a comprehensive documentation alongwith missing comments defining functions/classes/attributes etc., made it laborious to review the code and modify it. In addition to large training times for question answering models, the knowledge graph embeddings also required a significant amount of computing resources.

Communication with original authors

We had a couple of virtual meetings with Apoorv Saxena [2], the primary author of EmbedKGQA.

---

[1] `https://github.com/jishnujayakumar/MLRC2020-EmbedKGQA`
[2] `https://apoorvumang.github.io`

1 Introduction

Knowledge is the key to question answering task. Knowledge Graph (KG) is a multi-relational graph consisting of entities as nodes and relations among them as typed edges. KGs can accommodate a wide variety of facts, making them one of the potential candidates for intelligent decision-making. Question Answering over KG (KGQA) task aims to answer natural language queries posed over the KG. Multi-hop KGQA is a trending topic and has gained traction from both academia and industry recently. Multi-hop KGQA task involves reasoning over multiple edges of the KG to arrive at the correct answer.

Earlier works on KGs(e.g. Suchanek et al. [2007], Google [2013], Lehmann et al. [2015], Mitchell et al. [2018]) have some element of sparsity, i.e. they do not capture all the facts available in the real world. Recent research on multi-hop KGQA has attempted to reduce this sparsity with the help of relevant external textual resources that are not readily available. On the other side, KG embeddings have emerged as an effective tool to overcome the KG sparsity by predicting missing links in the KG. Although effective, KG embeddings have not been explored for the multi-hop KGQA task. Saxena et al. [2020] fills this gap with the proposed EmbedKGQA method.

This work intends to reproduce and perform an ablation (removing relation matching module) as well as extended study on EmbedKGQA(Saxena et al.[2020]). EmbedKGQA claims to be the first of its kind to use KG embeddings for multi-hop KGQA and improves over other state-of-the-art baselines.

2 Scope of reproducibility

According to Saxena et al. [2020], using ComplEx (Trouillon et al. [2016]) KG embeddings significantly improves Hits@1 for multi-hop KGQA task and it has been proved with the help of the results on MetaQA (Zhang et al. [2018]) and WebQSP (Yih et al. [2016]) datasets. This reproducibility work tries to test this claim and conducts experiments as mentioned in table:{2,3} of the original paper. Section 4.1 contains the corresponding results which support the claim with some anomalies.

3 Methodology

The authors of the original paper have open-sourced the code along with the data and pre-trained ComplEx KG embedding models. We have used the same codebase (commit:5d8fdbd4) and customized it for our purposes. In addition to this, we have added a comprehensive documentation to make it more interpretable. Moreover, a command-line functionality is also added to easily configure various transformers models in the training workflow.

3.1 Model descriptions

As shown in Figure:1, EmbedKGQA has three modules:

1. KG Embedding Module - This module contains a KG embedding model called ComplEx (Trouillon et al. [2016]) to learn embeddings for all entities in the input KG. 4 pretrained models have been shared by the author which contains 2 models for MetaQA-KG-{Full, 50} as well as 2 models WebQSP-KG-{Full,50} dataset. Details about the dataset are mentioned in section:3.2.

2. Question Embedding Module: Given a question q, head entity h and set of answer entities A, this module learns the question embeddings based on the score function defined by the KG embedding method used in 1.

3. Answer Selection Module: This module uses the outputs of module:1 and 2 to select the final answer by scoring the (head entity and question) pair against all possible answers. The strategy is mentioned in section:4.4 and 4.4.1 of Saxena et al. [2020].

3.2 Datasets

There are two datasets used in the original paper. MetaQA (Zhang et al. [2018]) and WebQSP (Yih et al. [2016]). Both datasets have two portions. (1) KG data (2) QA data. KG data for both are further divided into two categories. (1) Using the full KG (indicated by suffix KG-Full) and (2) Using only 50% of the facts in the respective KGs (indicated by suffix KG-50). The details of generating custom KG datasets are discussed here[3]. Both datasets are taken from here[4]. Statistics for table:1 and 2 have been taken from Saxena et al. [2020]. For generating question embeddings the

---

[3] https://github.com/malllabiisc/EmbedKGQA
[4] https://drive.google.com/drive/folders/1RlqGBMo45lTmWz9MUPTq-0KcjSd3ujxc (As of 01/2021)

Figure 1: Overview of EmbedKGQA, the proposed method for Multi-hop KGQA.
Image source: Saxena et al. [2020].

Dataset	Train	Dev	Test
MetaQA 1-hop	96,106	9,992	9.947
MetaQA 2-hop	118,948	14,872	14,872
MetaQA 3-hop	114,196	14,274	14,274
WebQSP	2,998	100	1,639

Table 1: QA data statistics for each dataset according to Saxena et al. [2020]

Dataset	Triples	Entities	Relations	Experiment-Alias
MetaQA-KG-Full	135k	43k	9	MetaQA_full
WebQSP-KG-Full	5.7 million	1.8 million	γ	fbwq_full
MetaQA-KG-50	ϕ	-	-	MetaQA_half
WebQSP-KG-50	ψ	-	-	fbwq_half

Table 2: KG data statistics for each dataset. Refer[3] for more details.

Experiment-Alias is the name used for the respective datasets in experiments.
γ = Contains all facts that are within 2-hops of any entity mentioned in the questions of WebQSP.
ϕ = Contains only 50% of the triples (randomly selected without replacement).
ψ = Contains 50% of the edges sampled randomly from fbwq_full.

question is placed between and tags for all transformers except SentenceTransformer as it takes the input sentence in its pure form. The preprocessing used in the original code has been used here. No additional preprocessing has been performed from our end.

3.3 Hyper-Parameters

Hyper-parameters used to train the models aren't explicitly shared in the codebase or the paper, hence we decided to use the default values provided in the codebase[3] to compensate the lack of time. For reproduction, a pretrained model shared along with the data was used; ComplEx(Trouillon et al. [2016]) was used as the knowledge graph embedding method for all the KG types, i.e., full and half of both datasets types.

Type	MetaQA-KG-Full			MetaQA-KG-50		
	1-hop	2-hop	3-hop	1-hop	2-hop	3-hop
Train (t)	350 seconds	380 seconds	380 seconds	280 seconds	330 seconds	320 seconds
Validation (v)	42 seconds	95 seconds	147 seconds	47 seconds	108 seconds	182 seconds
T	10.89 hours	13.19 hours	14.64 hours	9.08 hours	12.16 hours	13.94 hours

Type	WebQSP-KG-Full	WebQSP-KG-50
Train (t)	280 seconds	300 seconds
Validation (v)	95 seconds	105 seconds
T	10.42 hours	10.92 hours

Table 3: Time for training/validation. Refer section:3.3 for hyper-parameters. (r=1, total_epochs=100)

For table-3, validate_every = The number of train routines before validation for a single epoch
Total runs (r) = Number of times the training has been performed for a particular task
Total train time (GPU hours) excluding early stopping, T = $(total\_epochs \times (t + v)) \times r$

For the purpose of reproducibility, hyper-parameters for training MetaQA and WebQSP QA models have been taken from Section:MetaQA[5] and Section:WebQuestionsSP[6] of the original codebase respectively. For RoBERTa (Liu et al. [2019]), a pretrained model 'roberta-base' has been taken from HuggingFace transformers package (Wolf et al. [2020]). Other hyper-parameters are populated by default values in the codebase[3].

3.4 Experimental setup and code

Experiments have been performed on the NVIDIA DGX-1 server with 8xV100 GPUs, out of which 6 were used in this work. The metric used for validating the claims is Hits@1. According to Wang et al. [2019b], Hits@k is the proportion of test triples ranking in the top-k results. The code for this work is open-sourced on GitHub[1]. In addition to this, we have shared couple of Docker images[7] for easy kick-starting of experiments without the hassle of setting up the environment.

Following trained models are made available in our Docker image[7], chosen on the basis of better performance in our extended study.

- TuckER KG embedding model for Meta-QA-{Full, 50}

- QA models trained using ComplEx as KG embedding model and SBERT mentioned in table:4 as question embedding model for WebQSP-KG-{Full, 50}

3.5 Computational requirements

This work has been performed on 6 V100-16GB GPUs connected via NVLink. NVLink reduced multi-GPU training time by 1/4. The time required for various reproductions are mentioned in table:{5,6}.

3.6 Extended Experiments

Apart from reproducing the results mentioned in the original paper, a couple of extended experiments have been performed to find answers to the following two questions:

1. Can recent KG embedding methods like TuckER (Balažević et al. [2019]) give higher accuracy on higher levels of hops, i.e., 3-hop scenario to be specific compared to Trouillon et al. [2016] used in the original paper?

---

[5]https://github.com/malllabiisc/EmbedKGQA#metaqa
[6]https://github.com/malllabiisc/EmbedKGQA#webquestionssp
[7]https://github.com/jishnujayakumar/MLRC2020-EmbedKGQA#helpful-pointers

Transformer	Pretrained-Model
RoBERTa	roberta-base
XLNet	xlnet-base-cased
ALBERT	albert-base-v2
SentenceTransformer (SBERT)	sentence-transformers/bert-base-nli-mean-tokens
Longformer	allenai/longformer-base-4096

Table 4: Pretrained models from HuggingFace transformers package (Wolf et al. [2020])

2. Can other transformer architectures like ALBERT (Lan et al. [2019]), XLNet (Yang et al. [2019]), Long-former (Beltagy et al. [2020]) and SBERT (Reimers and Gurevych [2019]) improve the results on WebQSP (Yih et al. [2016])?

Details of hyper-parameters used for these experiments are available in our GitHub repository[1]. Various transformer models used for experiment-2 are mentioned in table:4.

4   Results

We report results for reproducibility as well as our extended experiments. The results of reproduction have a mixed nature while the ones for our extended experiments show positive signs to support claim-1, 2. The results are discussed in Section:5 in detail. For all tables in this report, bold values indicate better performance.

4.1   Results reproducing original paper

We perform two experiments based on the two datasets introduced in section:3.2. These experiments provide vital information about the results mentioned in table:{2,5} of the original paper. The results of the two are reported in table-5 and 6 respectively. From the results of table:5 in Saxena et al. [2020] and table-6 in this report, it is evident that relation matching(RM) is an important component to aid the multi-hop KGQA when the given KG is considerably large, i.e. {MetaQA, WebQSP} KG-Full; Definitely, WebQSP KG-50 also shows improvement in presence of RM but the performance significantly improves when applied to KG-Full setting. The original author, Apoorv has also expressed the same opinion during one of the virtual meetings.

4.2   Results beyond the original paper

We have conducted two additional experiments from our end to find an answer to claim:{1,2}. The results in table:{7,8} support claim-1 but with a caveat. On the other hand, values in table-9 improve upon the results reported by the original paper and creating a new SOTA baseline. Additional experiments ingest custom hyper-parameters mentioned in our codebase in absence of the original hyper-parameters. None of these experiments include the relation matching module.

5   Discussion

The reproducibility results from table-5,6 corroborates the claims mentioned in Section:2 to some extent. The reproduced version is within ± 2.4 range (positive value indicates better performance and vice-versa) except for MetaQA-KG-Full dataset's 3-hop and WebQSP-KG-Full scenario which has a significant drop of 22.5% and 18.5% respectively. This happened due to the absence relation matching module (discussed here[8,9,10]) and hence it can be concluded that relation matching is a vital component in multi-hop question answering, especially in KG-Full setting where more number of the edges would be present w.r.t. KG-50 setting or any smaller KG w.r.t. the KG-Full setting. Relation matching module can make maximum use of the available edges in the KG and incorporate this knowledge to aid the answer selection module to select more appropriate answers. Moreover, 3-hop KG-50 outperforms the original model by a margin of +0.9%.

---

[8]`https://github.com/malllabiisc/EmbedKGQA/issues/1`

[9]`https://github.com/malllabiisc/EmbedKGQA/issues/51`

[10]`https://github.com/malllabiisc/EmbedKGQA/issues/56`

Model	RM	MetaQA KG-Full			MetaQA KG-50		
		1-hop	2-hop	3-hop	1-hop	2-hop	3-hop
EmbedKGQA	✔	**97.5**	**98.8**	**94.8**	**83.9**	**91.8**	70.3
EmbedKGQA (Reproduced)	✗	95.4	96.4	72.3	83.2	91.6	**71.2**
Δ	-	−2.1	−2.4	−22.5	−0.7	−0.2	**0.9**

Table 5: Hits@1 results for original and reproduced experiments using MetaQA-KG-{Full, 50} datasets. Δ = (Reproduced Hits@1 without RM) - (Original Hits@1 with RM)

.

Model	RM	WebQSP KG-Full	WebQSP KG-50
EmbedKGQA	✔	**66.6**	**53.2**
EmbedKGQA	✗	48.1	47.4
EmbedKGQA (Reproduced)	✗	54.9	41.3
Δ	-	6.8	-6.1
$\Delta_{original}$	-	18.5	5.8

Table 6: Hits@1 results for original and reproduced experiments using WebQSP-KG-{Full, 50} datasets. Δ=(Reproduced Hits@1 without RM) - (Original Hits@1 without RM), $\Delta_{original}$ = (Original Hits@1 with RM) - (Original Hits@1 without RM).

For table:{5, 6}, KG-Embedding-Model=ComplEx. RM=Relation Matching, ✔= inclusion, ✗= exclusion. The original values for EmbedKGQA are taken from Saxena et al. [2020]. Underline indicates the anomaly due to the absence of relation matching (RM) module.

KG-Model	MetaQA-KG-Full								
	1-hop			2-hop			3-hop		
	Hits@1	Hits@5	Hits@10	Hits@1	Hits@5	Hits@10	Hits@1	Hits@5	Hits@10
ComplEx	95.39	**99.83**	99.97	**96.46**	**99.02**	99.27	72.33	93.27	95.66
TuckER	**95.51**	99.81	99.97	93.13	98.7	**99.28**	**73.81**	**93.6**	**96.09**
Δ	**0.12**	−0.02	0	−3.33	−0.32	**0.01**	**1.48**	**0.33**	**0.43**

Table 7: Comparison of ComplEx with TuckER based on Hits@k results for MetaQA-KG-Full dataset. $k \in \{1, 5, 10\}$.

KG-Model	MetaQA-KG-50								
	1-hop			2-hop			3-hop		
	Hits@1	Hits@5	Hits@10	Hits@1	Hits@5	Hits@10	Hits@1	Hits@5	Hits@10
ComplEx	**83.24**	**89.83**	**91.22**	**91.63**	**97.08**	**98.04**	71.2	90.77	93.72
TuckER	83	89.36	90.41	86.07	94.66	96.4	**71.96**	**91.16**	**93.94**
Δ	−0.24	−0.47	−0.81	−5.56	−2.42	−1.64	**0.76**	**0.39**	**0.22**

Table 8: Comparison of ComplEx with TuckER based on Hits@k results for MetaQA-KG-50 dataset. $k \in \{1, 5, 10\}$.

For table:{7, 8}, Δ= (TuckER Hits@k) - (ComplEx Hits@k).

Question-Embedding-Method	WebQSP-KG-Full			WebQSP-KG-50		
	Hits@1	Hits@5	Hits@10	Hits@1	Hits@5	Hits@10
RoBERTa (Liu et al. [2019])	54.96	67.62	71.97	41.27	51.14	54.19
XLNet (Yang et al. [2019]	51.98	64.44	69.11	39.33	49.25	52.04
ALBERT (Lan et al. [2019])	47.31	59.83	63.98	31.15	42.31	45.68
Longformer (Beltagy et al. [2020])	54.9	66.77	70.47	41.92	51.98	54.83
SBERT (Reimers and Gurevych [2019]	**55.55**	**68.98**	**72.74**	**44.65**	**53.86**	**56.13**
Δ	**0.59**	**1.36**	**0.77**	**3.38**	**2.72**	**1.94**

Table 9: Hits@k results for recent transformer models by Wolf et al. [2020] used for generating question embeddings. KG-Embedding-Method=ComplEx, Δ= (SBERT_Hits@k - RoBERTa_Hits@k), $k \in \{1, 5, 10\}$

From table:{7, 8}, it is clear that TuckER (Balažević et al. [2019]) performs better than ComplEx (Trouillon et al. [2016] for the 3-hop scenario for both MetaQA-KG datasets, i.e., Full and 50. Though these results strengthen claim-1, a more comprehensive set of tests may lead to a concrete conclusion. (e.g., experiments employing a broader set of hyper-parameters).

According to table-9, in all the cases, SBERT (Reimers and Gurevych [2019]) outperforms RoBERTa (Liu et al. [2019]) used in the original paper creating a new SOTA benchmark which supports claim-2.

There were some experiments which didn't work out due to the lack of time. E.g. Using RelationalTucker3 (Wang et al. [2019a]) and SimplE (Kazemi and Poole [2018]) to test claim-1. Furthermore, hyper-parameter search couldn't be done due to the same reason hence we had to pick the default ones mentioned in the codebase. All these create a room for further experiments and improvements.

5.1 What was easy

The paper was straightforward to understand. The open-sourced codebase helped us get kick-started.

5.2 What was difficult

The structure of the codebase made it difficult to navigate it. Since the code relied upon different techniques for the two datasets, the development of one function that trains different kinds of KG embeddings and another function that trains different kinds of QA models for both datasets was difficult. MetaQA uses LSTM/GRU (Hochreiter and Schmidhuber [1997] / Chung et al. [2014] while WebQSP uses / RoBERTa (Liu et al. [2019]) to perform the same task of generating question embeddings. Also, training KG embeddings for MetaQA yields files in the form of NumPy files while WebQSP uses LibKGE (Broscheit et al. [2020]) for the same purpose which produces LibKGE specific KGE models. Reproduction and the extensive study was a bit hard in the beginning as KG embeddings and question embedding methodology varied for both datasets. After having a couple of virtual meetings with the author and code review, it became easier to conduct the planned experiments. The unavailability of hyper-parameters used to train each module increased the experiment cycle by multi-fold.

5.3 Communication with original authors

We had a couple of virtual meetings with Apoorv, the primary author. Though it was daunting to understand the codebase due to the reasons mentioned in Section:5.2 with the help and support of the author, it became easier to navigate the codebase.

5.4 Future Scope

We think that there is a wide range of empirical analysis and experimentation that can be performed for multi-hop QA task, out of which we're sharing a few here:

1. KG embedding compression (Sachan [2020])

2. Using recent transformer models like Performer (Choromanski et al. [2020]), Reformer (Kitaev et al. [2020]) etc. for generating question embeddings.

3. Using low-dimensional hyperbolic KG embeddings (Chami et al. [2020]) in KG embedding module along with hyperbolic word embeddings (Dhingra et al. [2018]) for question embedding module.

4. A new approach for sentence embedding, SBERT-WK (Wang and Kuo [2020]) instead of SBERT (Reimers and Gurevych [2019]) can be tried out.

References

Ivana Balažević, Carl Allen, and Timothy M Hospedales. Tucker: Tensor factorization for knowledge graph completion. *arXiv preprint arXiv:1901.09590*, 2019.

Iz Beltagy, Matthew E. Peters, and Arman Cohan. Longformer: The long-document transformer, 2020.

Samuel Broscheit, Daniel Ruffinelli, Adrian Kochsiek, Patrick Betz, and Rainer Gemulla. Libkge-a knowledge graph embedding library for reproducible research. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 165–174, 2020.

Ines Chami, Adva Wolf, Da-Cheng Juan, Frederic Sala, Sujith Ravi, and Christopher Ré. Low-dimensional hyperbolic knowledge graph embeddings. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 6901–6914, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.617. URL https://www.aclweb.org/anthology/2020.acl-main.617.

Krzysztof Choromanski, Valerii Likhosherstov, David Dohan, Xingyou Song, Andreea Gane, Tamas Sarlos, Peter Hawkins, Jared Davis, Afroz Mohiuddin, Lukasz Kaiser, David Belanger, Lucy Colwell, and Adrian Weller. Rethinking attention with performers, 2020.

Junyoung Chung, Caglar Gulcehre, KyungHyun Cho, and Yoshua Bengio. Empirical evaluation of gated recurrent neural networks on sequence modeling, 2014.

Bhuwan Dhingra, Christopher Shallue, Mohammad Norouzi, Andrew Dai, and George Dahl. Embedding text in hyperbolic spaces. In *Proceedings of the Twelfth Workshop on Graph-Based Methods for Natural Language Processing (TextGraphs-12)*, pages 59–69, New Orleans, Louisiana, USA, June 2018. Association for Computational Linguistics. doi: 10.18653/v1/W18-1708. URL https://www.aclweb.org/anthology/W18-1708.

Google. Freebase data dumps. https://developers.google.com/freebase/data, 2013.

Sepp Hochreiter and Jürgen Schmidhuber. Long short-term memory. *Neural computation*, 9(8):1735–1780, 1997.

Seyed Mehran Kazemi and David Poole. Simple embedding for link prediction in knowledge graphs, 2018.

Nikita Kitaev, ukasz Kaiser, and Anselm Levskaya. Reformer: The efficient transformer, 2020.

Zhenzhong Lan, Mingda Chen, Sebastian Goodman, Kevin Gimpel, Piyush Sharma, and Radu Soricut. Albert: A lite bert for self-supervised learning of language representations. *arXiv preprint arXiv:1909.11942*, 2019.

Jens Lehmann, Robert Isele, Max Jakob, Anja Jentzsch, Dimitris Kontokostas, Pablo N Mendes, Sebastian Hellmann, Mohamed Morsey, Patrick Van Kleef, Sören Auer, et al. Dbpedia–a large-scale, multilingual knowledge base extracted from wikipedia. *Semantic web*, 6(2):167–195, 2015.

Yinhan Liu, Myle Ott, Naman Goyal, Jingfei Du, Mandar Joshi, Danqi Chen, Omer Levy, Mike Lewis, Luke Zettlemoyer, and Veselin Stoyanov. Roberta: A robustly optimized bert pretraining approach, 2019.

T. Mitchell, W. Cohen, E. Hruschka, P. Talukdar, B. Yang, J. Betteridge, A. Carlson, B. Dalvi, M. Gardner, B. Kisiel, J. Krishnamurthy, N. Lao, K. Mazaitis, T. Mohamed, N. Nakashole, E. Platanios, A. Ritter, M. Samadi, B. Settles, R. Wang, D. Wijaya, A. Gupta, X. Chen, A. Saparov, M. Greaves, and J. Welling. Never-ending learning. *Commun. ACM*, 61(5):103115, April 2018. ISSN 0001-0782. doi: 10.1145/3191513. URL https://doi.org/10.1145/3191513.

Nils Reimers and Iryna Gurevych. Sentence-bert: Sentence embeddings using siamese bert-networks. In *Proceedings of the 2019 Conference on Empirical Methods in Natural Language Processing*. Association for Computational Linguistics, 11 2019. URL https://arxiv.org/abs/1908.10084.

Mrinmaya Sachan. Knowledge graph embedding compression. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 2681–2691, 2020.

Apoorv Saxena, Aditay Tripathi, and Partha Talukdar. Improving multi-hop question answering over knowledge graphs using knowledge base embeddings. In *Proceedings of the 58th Annual Meeting of the Association for Computational Linguistics*, pages 4498–4507, Online, July 2020. Association for Computational Linguistics. doi: 10.18653/v1/2020.acl-main.412. URL https://www.aclweb.org/anthology/2020.acl-main.412.

Fabian M. Suchanek, Gjergji Kasneci, and Gerhard Weikum. Yago: A core of semantic knowledge. In *Proceedings of the 16th International Conference on World Wide Web*, WWW '07, page 697706, New York, NY, USA, 2007. Association for Computing Machinery. ISBN 9781595936547. doi: 10.1145/1242572.1242667. URL https://doi.org/10.1145/1242572.1242667.

Théo Trouillon, Johannes Welbl, Sebastian Riedel, Éric Gaussier, and Guillaume Bouchard. Complex embeddings for simple link prediction. In *Proceedings of the 33rd International Conference on International Conference on Machine Learning - Volume 48*, ICML'16, page 20712080. JMLR.org, 2016.

B. Wang and C. . J. Kuo. SBERT-WK: A sentence embedding method by dissecting BERT-based word models. *IEEE/ACM Transactions on Audio, Speech, and Language Processing*, 28:2146–2157, 2020.

Yanjie Wang, Samuel Broscheit, and Rainer Gemulla. A relational tucker decomposition for multi-relational link prediction, 2019a.

Yanjie Wang, Daniel Ruffinelli, Rainer Gemulla, Samuel Broscheit, and Christian Meilicke. On evaluating embedding models for knowledge base completion, 2019b.

Thomas Wolf, Lysandre Debut, Victor Sanh, Julien Chaumond, Clement Delangue, Anthony Moi, Pierric Cistac, Tim Rault, Rémi Louf, Morgan Funtowicz, Joe Davison, Sam Shleifer, Patrick von Platen, Clara Ma, Yacine Jernite, Julien Plu, Canwen Xu, Teven Le Scao, Sylvain Gugger, Mariama Drame, Quentin Lhoest, and Alexander M. Rush. Transformers: State-of-the-art natural language processing. In *Proceedings of the 2020 Conference on Empirical Methods in Natural Language Processing: System Demonstrations*, pages 38–45, Online, October 2020. Association for Computational Linguistics. URL https://www.aclweb.org/anthology/2020.emnlp-demos.6.

Zhilin Yang, Zihang Dai, Yiming Yang, Jaime Carbonell, Russ R Salakhutdinov, and Quoc V Le. Xlnet: Generalized autoregressive pretraining for language understanding. In *Advances in neural information processing systems*, pages 5753–5763, 2019.

Wen-tau Yih, Matthew Richardson, Chris Meek, Ming-Wei Chang, and Jina Suh. The value of semantic parse labeling for knowledge base question answering. In *Proceedings of the 54th Annual Meeting of the Association for Computational Linguistics (Volume 2: Short Papers)*, pages 201–206, Berlin, Germany, August 2016. Association for Computational Linguistics. doi: 10.18653/v1/P16-2033. URL https://www.aclweb.org/anthology/P16-2033.

Yuyu Zhang, Hanjun Dai, Zornitsa Kozareva, Alexander J Smola, and Le Song. Variational reasoning for question answering with knowledge graph. In *AAAI*, 2018.