OPTIMIZING FEW-STEP DIFFUSION SAMPLERS BY GRADIENT DESCENT

ABSTRACT

Denoising Diffusion Probabilistic Models (DDPMs) have emerged as a flexible family of generative models rivaling GANs and autoregressive models in sample quality and likelihoods. DDPMs however typically require hundreds of inference steps to generate a high-fidelity image, despite recent progress on speeding up diffusion model sampling. We introduce Differentiable Diffusion Sampler Search (DDSS): a method that learns few-step samplers for any pre-trained DDPM by using gradient descent. We propose Generalized Gaussian Diffusion Processes (GGDP), a family of non-Markovian samplers for diffusion models, and we show how to improve the generated samples of pre-trained DDPMs by optimizing the degrees of freedom of the GGDP sampler family with respect to a perceptual loss. Our optimization procedure backpropagates through the sampling process using the reparameterization trick. Searching our novel GGDP family with DDSS, we achieve strong results on unconditional image generation on both CIFAR and ImageNet 64x64 (e.g., 7.59 on CIFAR10 with only 10 inference steps, and 4.67 with 25 steps, compared to 13.62 and 6.56 with the strongest respective DDIM($\eta = 0$) baselines). Our method is compatible with any pre-trained DDPM without re-training, only needs to be applied once, and does not finetune the parameters of the pre-trained DDPM.

1 INTRODUCTION

Denoising Diffusion Probabilistic Models (DDPM) (Sohl-Dickstein et al., 2015; Song & Ermon, 2019; Ho et al., 2020) have emerged as a powerful family of generative models, capable of synthesizing high-quality samples across various modalities, *e.g.,* images, audio, and 3D shapes (Ho et al., 2020; 2021; Cai et al., 2020; Chen et al., 2021a;b; Luo & Hu, 2021). Recent work (Dhariwal & Nichol, 2021; Ho et al., 2021) shows that DDPMs can outperform Generative Adversarial Networks (GAN) (Goodfellow et al., 2014; Brock et al., 2018) in generation quality, but unlike GANs, DDPMs admit likelihood computation and much more stable training dynamics (Arjovsky et al., 2017; Gulrajani et al., 2017). That being said, GANs are much more efficient at generation time, typically

Figure 1: Non-cherrypicked samples for a DDPM trained on ImageNet 64x64, comparing the strongest DDIM($\eta = 0$) baseline and our approach. All samples were generated with the same random seeds. For reference, we include DDPM samples using all 4,000 stpes (top right) and real images (bottom right).

requiring a single forward pass through the generator network, whereas DDPMs require hundreds of inference steps. Instead of learning a generator directly, DDPMs learn to model the score function of the marginals of a diffusion process that interpolates between the data distribution and a simple prior, leading to a wide variety of feasible strategies for sampling (Song et al., 2021b). In particular, at inference time, DDPMs allow controlling the number of forward passes to the modeled score function (a.k.a. *inference steps*) (Song et al., 2020; Nichol & Dhariwal, 2021).

It has been shown both empirically and mathematically that, for any sufficiently good DDPM, more inference steps leads to better log-likelihood and sample quality (Nichol & Dhariwal, 2021; Kingma et al., 2021). In practice, the minimum number of inference steps to achieve competitive sample quality is highly problem-dependent, *e.g.,* depends on the complexity of the dataset, and the strength of the conditioning signal if the task is conditional. Given the importance of generation speed, recent work (Song et al., 2020; Chen et al., 2021a; Watson et al., 2021) has explored reducing the number of steps required for high quality sampling with pretrained diffusion models.

This paper treats the selection of efficient samplers for diffusion models as a differentiable optimization problem, and proposes *Differentiable Diffusion Sampler Search* (DDSS). Our key observation is that one can unroll the sampling chain of a diffusion model and use reparametrization trick (Kingma & Welling, 2013) and gradient rematerialization (Kumar et al., 2019a) to optimize over a class of parametric few-step samplers with respect to a global objective function. Our class of parameteric samplers, which we call Generalized Gaussian Diffusion Processes (GGDP), includes Denoising Diffusion Implicit Models (DDIM) (Song et al., 2020) as a special case and is motivated by the success of DDIM at few-step diffusion model sampling.

An important challenge for efficient DDPM sampling is the mismatch between the training objective (*e.g.,* ELBO or weighted ELBO) and sample quality. Prior work (Watson et al., 2021; Song et al., 2021a) finds that samplers that are optimal with respect to ELBO often lead to worse sample quality and Fréchet Inception Distance (FID) scores (Heusel et al., 2017), especially with few inference steps. We propose the use of a *perceptual* loss within the DDSS framework to find high-fidelity diffusion samplers, motivated by the observation that perceptual losses correlate better with human perception (Johnson et al., 2016). Our perceptual loss simply computes the L2 distance between average InceptionV3 (Szegedy et al., 2016) features of a minibatch of real images *vs.* synthetic samples. We show that using DDSS to minimize our simple perceptual loss in the GGDP space leads to effective few-step samplers with significantly better image quality than prior work (see Figure 1).

Our main contributions are as follows:

1. We propose Differentiable Diffusion Sampler Search (DDSS), using the reparametrization trick and gradient rematerialization to optimize in a parametric space of few-step diffusion samplers.
2. We identify a parametric family of Generalized Gaussian Diffusion Processes (GGDP) that admits high-fidelity few-step samplers for diffusion models.
3. We show that using DDSS to optimize samplers by minimizing a simple perceptual loss leads to few-step diffusion samplers with state-of-the-art sample quality scores.

2 BACKGROUND ON DENOISING DIFFUSION IMPLICIT MODELS

We start with a brief review on DDPM (Ho et al., 2020) and DDIM (Song et al., 2020). Following the notation of Watson et al. (2021), DDPMs fix a forward process $q(\boldsymbol{x}_0, ..., \boldsymbol{x}_T) = q(\boldsymbol{x}_0) \prod_{t=1}^{T} q(\boldsymbol{x}_t | \boldsymbol{x}_{t-1})$ with $q(\boldsymbol{x}_t | \boldsymbol{x}_0) = \mathcal{N}(\boldsymbol{x}_t | f_{t0} \boldsymbol{x}_0, g_{t0}^2 \boldsymbol{I}_d)$ where $q(\boldsymbol{x}_0)$ is the data distribution, and are then trained to model $\nabla_{\boldsymbol{x}_t} \log q(\boldsymbol{x}_t)$ by maximizing a (possibly reweighted) evidence lower bound (ELBO), which is equivalent to minimizing a weighted sum of denoising score matching objectives (DSM) (Vincent, 2011):

$$\mathbb{E}_q \left[D_{\text{KL}}[q(\boldsymbol{x}_T | \boldsymbol{x}_0) \| p(\boldsymbol{x}_T)] + \sum_{t=2}^{T} D_{\text{KL}}[q(\boldsymbol{x}_{t-1} | \boldsymbol{x}_t, \boldsymbol{x}_0) \| p_\theta(\boldsymbol{x}_{t-1} | \boldsymbol{x}_t)] - \log p_\theta(\boldsymbol{x}_0 | \boldsymbol{x}_1) \right] \quad (1)$$

and the model is parametrized as

$$p_\theta(\boldsymbol{x}_s|\boldsymbol{x}_t) = q\left(\boldsymbol{x}_s \middle| \boldsymbol{x}_t, \hat{\boldsymbol{x}}_0 = \frac{1}{f_{t0}}(\boldsymbol{x}_t - g_{t0}\epsilon_\theta(\boldsymbol{x}_t, t))\right) \tag{2}$$

$$= \mathcal{N}\left(\boldsymbol{x}_s \middle| \frac{1}{g_{t0}^2}(f_{s0}g_{ts}^2\boldsymbol{x}_0 + f_{ts}g_{s0}^2\boldsymbol{x}_t), \frac{g_{s0}^2 g_{ts}^2}{g_{t0}^2}\boldsymbol{I}_d\right) \tag{3}$$

for each contiguous $s < t$.

The seminal work of Song et al. (2020) presents Denoising Diffusion Implicit Models (DDIM): a family of evidence lower bounds (ELBOs) with corresponding forward diffusion processes and samplers. All of these ELBOs share the same marginals as DDPM, but allow arbitrary choices of posterior variances. Specifically, Song et al. (2020) note that is it possible to construct alternative ELBOs with only a subsequence of the original timesteps $S \subset \{1, ..., T\}$ that shares the same marginals as the construction above (i.e., $q_S(\boldsymbol{x}_t|\boldsymbol{x}_0) = q(\boldsymbol{x}_t|\boldsymbol{x}_0)$ for every $t \in S$, so q_S defines a faster sampler compatible with the pre-trained model) by simply using the new contiguous timesteps in the equations above. They also show it is also possible to construct an *infinite* family of non-Markovian processes $\{q_\sigma : \sigma \in [0,1]^{T-1}\}$ where each q_σ also shares the same marginals as the original forward process with the following construction:

$$q_\sigma(\boldsymbol{x}_0, ..., \boldsymbol{x}_t) = q(\boldsymbol{x}_0)q(\boldsymbol{x}_T|\boldsymbol{x}_0)\prod_{t=1}^{T-1} q_\sigma(\boldsymbol{x}_t|\boldsymbol{x}_{t+1}, \boldsymbol{x}_0) \tag{4}$$

where the posteriors are defined as

$$q(\boldsymbol{x}_s|\boldsymbol{x}_t, \boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t \middle| f_{s0}\boldsymbol{x}_0 + \frac{\sqrt{g_{s0}^2 - \sigma_t^2}}{g_{t0}}(\boldsymbol{x}_t - f_{t0}\boldsymbol{x}_0), \sigma_t^2 \boldsymbol{I}_d\right) \tag{5}$$

Song et al. (2020) empirically find that the extreme case of using all-zero variances (*a.k.a.* DDIM($\eta = 0$)) consistently helps with sample quality in the few-step regime. Combined with a good selection of timesteps to evaluate the modeled score function (*a.k.a. strides*), DDIM($\eta = 0$) establishes the current state-of-the-art for few-step diffusion model sampling.

3 GENERALIZING THE FAMILY OF PROCESSES COMPATIBLE WITH A DDPM

We now present Generalized Gaussian Diffusion Processes (GGDP), a family of Gaussian diffusion processes that includes DDIM as a special case. We define a joint distribution with no independence assumptions

$$q_{\mu,\sigma}(\boldsymbol{x}_0, ..., \boldsymbol{x}_T) = q(\boldsymbol{x}_0)q(\boldsymbol{x}_T|\boldsymbol{x}_0)\prod_{t=1}^{T-1} q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_{>t}, \boldsymbol{x}_0) \tag{6}$$

where the new factors are defined as

$$q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_{>t}, \boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t \middle| \sum_{u \in S_t} \mu_{tu}\boldsymbol{x}_u, \sigma_t^2 \boldsymbol{I}_d\right) \tag{7}$$

(letting $S_t = \{0, ..., T\} \setminus \{1, ..., t\}$ for notation compactness), with σ_t and μ_{tu} free parameters $\forall t \in \{1, ..., T\}, u \in S_t$. In other words, when predicting the next, less noisy image, the sampler can take into account *all* the previous, noisier images in the sampling chain, and similarly to DDIM, we can also control the sampler's variances. As we are about to show, this construction admits Gaussian marginals, and we can differentiably compute the marginal coefficients from arbitrary choices of μ and σ:

Theorem 1. Given some $t \in \{1, ..., T\}$, let $a_{tu}^{(1)} = \mu_{tu} \ \forall u \in S_t$ and $v_t^{(1)} = \sigma_t^2$. For each $i \in \{1, ..., T-t\}$, recursively define

- $a_{tu}^{(i+1)} = a_{t,t+i}^{(i)}\mu_{t+i,u} + a_{tu}^{(i)} \ \forall u \in S_{t+i}$

- $v_t^{(i+1)} = v_t^{(i)} + \left(a_{t,t+i}^{(i)}\sigma_{t+i}\right)^2$

Then, it follows that

$$q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_{>t+i},\boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t\left|\sum_{u\in S_{t+i}} a_{tu}^{(i+1)}\boldsymbol{x}_u, v_t^{(i+1)}\boldsymbol{I}_d\right.\right) \tag{8}$$

Proof sketch. Note that, for each such t, we have by definition that

$$q_{\mu,\sigma}(\boldsymbol{x}_{t+1}|\boldsymbol{x}_{>t+1},\boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t\left|\sum_{u\in S_{t+1}}\mu_{t+1,u}\boldsymbol{x}_u, \sigma_{t+1}^2\boldsymbol{I}_d\right.\right)$$

$$q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_{t+1},\boldsymbol{x}_{>t+1},\boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t\left|\sum_{u\in S_t}\mu_{tu}\boldsymbol{x}_u, \sigma_t^2\boldsymbol{I}_d\right.\right) = \mathcal{N}\left(\boldsymbol{x}_t\left|\sum_{u\in S_t} a_{tu}^{(1)}\boldsymbol{x}_u, v_t^{(1)}\boldsymbol{I}_d\right.\right)$$

Therefore, following Svensén & Bishop (2007) (2.115), by prior conjugacy it follows that

$$q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_{>t+1},x_0) = \mathcal{N}\left(\boldsymbol{x}_t\left|a_{t,t+1}^{(1)}\sum_{u\in S_{t+1}}\mu_{t+1,u}\boldsymbol{x}_u + \sum_{u\in S_{t+1}} a_{tu}^{(1)}, \left(v_t^{(1)} + a_{t,t+1}^{(1)}\sigma_{t+1}^2 a_{t,t+1}^{(1)}\right)\boldsymbol{I}_d\right.\right)$$

$$= \mathcal{N}\left(\boldsymbol{x}_t\left|\sum_{u\in S_{t+1}}\left(a_{t,t+1}^{(1)}\mu_{t+1,u} + a_{tu}^{(1)}\right)\boldsymbol{x}_u, v_t^{(2)}\boldsymbol{I}_d\right.\right)$$

$$= \mathcal{N}\left(\boldsymbol{x}_t\left|\sum_{u\in S_{t+1}} a_{tu}^{(2)}\boldsymbol{x}_u, v_t^{(2)}\boldsymbol{I}_d\right.\right).$$

Now, combining the next "prior" $q(\boldsymbol{x}_{t+2}|\boldsymbol{x}_{>t+2},\boldsymbol{x}_0)$ with the "likelihood" $q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_{>t+1},\boldsymbol{x}_0) = q(\boldsymbol{x}_t|\boldsymbol{x}_{t+2},\boldsymbol{x}_{>t+2},\boldsymbol{x}_0)$ that we just derived, by prior conjugacy it follows again that

$$q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_{>t+2},\boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t\left|\sum_{u\in S_{t+2}} a_{tu}^{(3)}\boldsymbol{x}_u, v_t^{(3)}\boldsymbol{I}_d\right.\right),$$

and so on. With a simple inductive argument, we thus have for each $i \geq 0$ that

$$q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_{>t+i},\boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t\left|\sum_{u\in S_{t+i}} a_{tu}^{(i+1)}\boldsymbol{x}_u, v_t^{(i+1)}\boldsymbol{I}_d\right.\right).$$

In particular,

$$q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t\left|a_{t0}^{(T-t+1)}\boldsymbol{x}_0, v_t^{(T-t+1)}\boldsymbol{I}_d\right.\right). \quad \square$$

3.1 IGNORING THE MATCHING MARGINALS CONDITION

Unlike DDIM, the GGDP family does not guarantee that the marginals of the new forward process match that of the original DDPM. We empirically find, however, that this condition can often be too restrictive and better samplers exist where the marginals $q_{\mu,\sigma}(\boldsymbol{x}_t|\boldsymbol{x}_0) = \mathcal{N}\left(\boldsymbol{x}_t\left|a_{t0}^{(T-t+1)}\boldsymbol{x}_0, v_t^{(T-t+1)}\boldsymbol{I}_d\right.\right)$ of the new forward process differ from the original DDPM's marginals. This is also true without applying the methodology in this paper, e.g., simply grid searching the sampler's variances without adjusting the means following DDIM, we obtain an FID of 7.0 on CIFAR10 with just 25 inference steps, whereas DDIM($\eta = 0$) with the same stride achieves a worse FID score of 10.5. We hypothesize that this occurs simply because in practice, the estimate of the score function is not exact.

4 DIFFERENTIABLE DIFFUSION SAMPLER SEARCH

We now describe DDSS, our approach to search for high-fidelity samplers with a limited budget of $K < T$ steps. We observe we can backpropagate through the diffusion sampling process via the reparamterization trick. Equipped with this, we can now use gradient-descent to optimize any given differentiable loss function over model samples.

We begin with a family of samplers that we wish to search, and we parametrize the family's degrees of freedom with trainable variables. For example, in a subsequence $S \subset \{0, ..., T\}$ of $K + 1$ time points (i.e., K inference steps after including $t = 0$), one can parametrize the DDIM space with K trainable variables $v_1, ..., v_K$ and set each $\sigma_t = g_{s0}$ sigmoid(v_t), where $t \in S$ and s is the immediately previous step to t in S (the g_{s0} constant ensures real-valued mean coefficients; see the square root in Equation 5). For our GGDP space, we simply use a sigmoid parametrization for all the relevant μ_{tu} (i.e., $u \in S_t$) and σ_t coefficients.

4.1 PERCEPTUAL LOSS

We can find our sampler in this family by optimizing the desired search family's trainable variables; however, the question of which objective to use remains. Prior work has shown that optimizing log-likelihood can actually worsen sample quality and FID scores in the few-step regime (Watson et al., 2021; Song et al., 2021a). Thus, we instead design a *perceptual* loss which simply compares mean statistics between the DDPM's samples against real samples in neural network feature space; this approach is simple yet highly effective. These types of objectives have been shown in prior work to prefer minima that better correlate with human perception of sample quality (Johnson et al., 2016; Heusel et al., 2017), which we also empirically observe. Specifically, we rely on the representations of the penultimate layer of a pre-trained InceptionV3 classifier (Szegedy et al., 2016). Letting such features of an image be $f(\boldsymbol{x})$ and ψ the collection of all the introduced trainable variables, our exact objective is the following:

$$\psi^* = \arg\min_{\psi} \mathcal{L}_{\text{DDSS}} = \arg\min_{\psi} \left\| \mathbb{E}_{\boldsymbol{x}_p \sim p_\psi(\boldsymbol{x}_p)} f(\boldsymbol{x}_p) - \mathbb{E}_{\boldsymbol{x}_0 \sim q(\boldsymbol{x}_0)} f(\boldsymbol{x}_0) \right\|_2^2 \tag{9}$$

where $p_\psi(\boldsymbol{x}_p)$ is the marginal distribution of the final generated sample of the sampler family parameterized by ψ, and $q(\boldsymbol{x}_0)$ is the distribution of real data. In practice, the expectations are replaced with empirical expectations: the expectation over $p_\psi(\boldsymbol{x}_p)$ is taken over a generated batch, and the expectation over $q(\boldsymbol{x}_0)$ is taken over the training dataset.

Since the sampling chain of any Gaussian diffusion process admits using the reparametrization trick (Kingma & Welling, 2013), our loss function is fully differentiable with respect to the trainable variables ψ. We empirically find that using the perceptual loss is crucial; i.e., by trying $f(\boldsymbol{x}) = \boldsymbol{x}$ to compare images directly on pixel space rather than neural network feature space (as above), we observe that our method makes samples consistently worsen in apparent quality as training progresses.

4.2 LEARNING THE TIMESTEPS

We find that instead of fixing the calls to the score function used by the model to some initial stride (e.g., linear or quadratic strides as done by Nichol & Dhariwal (2021); Watson et al. (2021)), parametrizing the timesteps as additional trainable variables helps improve results further, especially when using the smallest budgets of inference steps. We achieve this by introducing K additional trainable variables v_i, and then letting the timesteps be `t = cumsum(softmax([*v, 1.]))[:-1]` to ensure they are bounded and monotonically increasing. In principle, this should only be possible for DDPMs trained with continuous time sampling (Chen et al., 2021a; Song et al., 2021b; Kingma et al., 2021), but in practice we find that DDPMs trained with continuously embedded discrete timesteps are still well-behaved when applied at a timestep not present during training. We hypothesize that this is due to the regularity of the sinusoidal positional encodings (following Vaswani et al. (2017)) used by these models when trained with a sufficiently large number of timesteps T.

4.3 GRADIENT REMATERIALIZATION

In order for backpropagation to be feasible under reasonable memory constraints, one final problem must be addressed: since we are taking gradients with respect to model samples, the cost in memory to maintain the state of the forward pass scales linearly with the number of inference steps, which can quickly become unfeasible considering the large size of typical DDPM architectures. To address this issue, we can use gradient rematerialization (Kumar et al., 2019b). Instead of storing a particular computation's output from the forward pass required by the backward pass computation, we recompute it on the fly. To trade $\mathcal{O}(K)$ memory cost for $\mathcal{O}(K)$ computation time, we simply rematerialize calls to the pre-trained DDPM (i.e., the estimated score function), but keep in memory all the progressively denoised images from the sampling chain. In JAX (Bradbury et al., 2018), this is trivial to implement by simply wrapping the score function calls with `jax.remat`.

Table 1: FID and IS scores of different sampling strategies for a DDPM trained on CIFAR10 with the L_{simple} objective. FID scores (lower is better) are the numbers at the left of each entry, and IS scores (higher is better) are at the right. All DDSS results are for the GGDP family.

Sampler \ K	5	10	15	20	25
DDPM (linear stride)	84.27 / 5.396	43.39 / 7.034	31.40 / 7.609	25.94 / 7.879	22.60 / 8.043
DDPM (quadratic stride)	76.25 / 5.435	42.03 / 6.965	27.78 / 7.714	20.21 / 8.128	16.17 / 8.350
DDIM (linear stride)	44.41 / 6.750	19.11 / 7.965	14.06 / 8.190	11.82 / 8.420	10.52 / 8.512
DDIM (quadratic stride)	32.66 / 7.090	13.62 / 8.190	9.318 / 8.495	7.500 / 8.641	6.560 / 8.759
DDSS (learned stride)	**12.05 / 8.374**	**7.441 / 8.886**	**6.039 / 8.847**	**5.515 / 8.907**	**4.839 / 9.079**

Table 2: FID / IS scores of different sampling strategies for a DDPM trained on ImageNet 64x64 with the L_{hybrid} objective proposed by Nichol & Dhariwal (2021). All DDSS results are for the GGDP family.

Sampler \ K	5	10	15	20	25
DDPM (linear stride)	122.0 / 5.878	58.78 / 10.67	39.30 / 13.22	31.36 / 14.72	26.36 / 15.71
DDPM (quadratic stride)	394.8 / 1.351	129.5 / 5.997	80.10 / 9.595	61.34 / 11.60	49.60 / 13.01
DDIM (linear stride)	135.4 / 5.898	40.70 / 12.23	28.54 / 13.99	24.23 / 14.75	22.13 / 15.16
DDIM (quadratic stride)	409.1 / 1.380	148.6 / 5.533	67.65 / 9.842	45.60 / 11.99	36.11 / 13.23
DDSS (learned stride)	**54.82 / 12.76**	**31.68 / 15.00**	**25.57 / 16.47**	**21.90 /17.12**	**19.15 / 18.22**

5 EXPERIMENTS

In order to emphasize that our method is compatible with any pre-trained DDPM, we apply our method on pre-trained DDPM checkpoints from prior work. Specifically, we experiment with the DDPM trained by Ho et al. (2020) with L_{simple} on CIFAR10, as well as a DDPM following the exact configuration of Nichol & Dhariwal (2021) trained on ImageNet 64x64 (Deng et al., 2009) with their L_{hybrid} objective (with the only difference being that we trained the latter ourselves for 3M rather than 1.5M steps). Both of these models utilize adaptations of the UNet architecture (Ronneberger et al., 2015) that incorporate self-attention layers (Vaswani et al., 2017).

We evaluate all of our models on both FID and Inception Score (IS) (Salimans et al., 2016), comparing the samplers discovered by DDSS against DDPM and DDIM baselines with linear and quadratic strides. As previously mentioned, more recent methods for fast sampling are outperformed by DDIM when the budget of inference steps is as small as those we utilize in this work (5, 10, 15, 20, 25). All reported results on both of these approximate sample quality metrics were computed by comparing 50,000 model and training data samples, as is standard in the literature. Also as is standard, IS scores are computed 10 times, each time on 5,000 samples, and then averaged.

In all of our experiments, we optimize the DDSS objective presented in Section 4.1 with the following hyperparameters:

1. For every family of models we search over, we initialize the degrees of freedom such that training begins with a sampler matching DDPM with K substeps following Song et al. (2020); Nichol & Dhariwal (2021).
2. We apply gradient updates using the Adam optimizer (Kingma & Ba, 2015). We swept over the learning rate and used $\lambda = 0.0005$. We did not sweep over other Adam hyperparameters and kept $\beta_1 = 0.9$, $\beta_2 = 0.999$, and $\epsilon = 1 \times 10^{-8}$.
3. We tried batch sizes of 128 and 512 and opted for the latter, finding that it leads to better sample quality upon inspection. Since the loss depends on averages over examples as our experiments are on unconditional generation, this choice was expected.
4. We run all of our experiments for 50,000 training steps and evaluate the discovered samplers at this exact number of training steps, unless otherwise stated. We did not sweep over this value.

We include results in Table 1 for CIFAR10 and Table 2 for ImageNet 64x64, comparing DDSS with a learned stride (as detailed in Section 4.2) to DDPM and DDIM baselines with linear and quadratic strides. We omit the use of the learned variances of the ImageNet 64x64 model (i.e., following Nichol & Dhariwal (2021)), as we search for the variances ourselves via DDSS. We include samples

Table 3: FID / IS scores for the DDSS search space ablation on CIFAR10 and ImageNet 64x64. All runs fix the timesteps to a linear stride.

Sampler \ K	5	10	15	20	25
CIFAR10 L_{simple}					
DDSS + DDIM	44.85 / 6.825	20.74 / 7.935	15.21 / 8.239	12.71 / 8.386	11.30 / 8.451
DDSS + GGDP	**17.84 / 8.020**	**8.452 / 8.676**	**6.366 / 8.940**	**5.203 / 8.988**	**4.743 / 9.112**
ImageNet 64x64 L_{hybrid}					
DDSS + DDIM	77.22 / 9.133	40.74 / 12.12	33.35 / 13.45	28.94 / 14.12	26.29 / 14.87
DDSS + GGDP	**60.02 / 10.74**	**35.96 / 14.25**	**28.34 / 16.06**	**24.53 / 16.72**	**20.12 / 18.03**

for 5, 10 and 25 steps comparing the strongest DDIM baselines to DDSS + GGDP with a learned stride; see Figures 1 and 2. We include additional samples in the appendix (A.1).

5.1 SEARCH SPACE ABLATION

In order to show the importance of our proposed GGDP family to find high-fidelity samplers, we also apply DDSS to the DDIM family and compare both choices of search spaces with the same metrics as before. We find that optimizing the DDIM sigma coefficients does not outperform the corresponding DDIM($\eta = 0$) baseline on CIFAR10, which is not a surprising result as Song et al. (2020) show empirically that most choices of the σ_t degrees of freedom lead to worse FID scores than setting them all to 0. We had to stop DDSS at 25,000 training steps when searching the DDIM family with $K = 5$, as we found that the loss for this run became unstable after this point; however, all other runs were stopped after the usual 50,000 training steps. All models use a linear stride in their calls to the pre-trained DDPM (i.e., we don't learn the timesteps in this ablation). Results are included in Table 3.

We also ablate learning the timesteps when applying DDSS to these models. On CIFAR10, we also experiment with quadratic strides as the aforementioned baselines have significantly better overall scores with this stride (this is not the case at all with ImageNet 64x64, so we omit trying a quadratic stride for that model). We find that removing the timesteps from the optimized degrees of freedom still allows DDSS to find samplers that significantly outperform the strongest DDIM($\eta = 0$) baselines. Still, we get better results consistently on ImageNet 64x64 and for the smallest step budgets on CIFAR10 when learning the timesteps. Results are included in table 4. On both CIFAR10 and ImageNet 64x64, we had to early stop our procedure (at 7,500 steps on ImageNet 64x64 and 25,000 steps on CIFAR10) when applied to a budget of $K = 5$ inference steps and using a linear stride, as the loss suddenly became unstable in these two runs. This was unnecessary in all other cases.

5.2 IDENTIFYING DEGENERATE DDSS SOLUTIONS

We note that, assuming sufficient flexibility in the optimization family, a global minimum of our $\mathcal{L}_{\text{DDSS}}$ objective (Equation 9) can be achieved when the perceptual features corresponding to model samples collapse to the mean of the training data perceptual features. Qualitatively, samples generated from DDSS solutions do not appear to show collapse behavior, but in order to *quantitatively* demonstrate that DDSS does not find such degenerate solutions, we compute the FID scores that

Table 4: FID / IS scores for the timestep learning ablation on CIFAR10 and ImageNet 64x64. The GGDP results are no different than the results in Tables 1 and 2; we only include them here for ease of comparison. All DDSS results are for the GGDP family.

Sampler \ K	5	10	15	20	25
CIFAR10 L_{simple}					
DDSS (linear stride)	17.84 / 8.020	8.452 / 8.676	6.366 / **8.940**	5.203 / **8.988**	4.743 / **9.112**
DDSS (quadratic stride)	14.39 / **8.376**	7.585 / 8.791	**5.976** / 8.886	**4.935** / 8.939	**4.666** / 9.029
DDSS (learned stride)	**12.05** / 8.374	**7.441** / **8.886**	6.039 / 8.847	5.515 / 8.907	4.839 / 9.079
ImageNet 64x64 L_{hybrid}					
DDSS (linear stride)	60.02 / 10.74	35.96 / 14.25	28.34 / 16.06	24.53 / 16.72	20.12 / 18.03
DDSS (learned stride)	**54.82 / 12.76**	**31.68 / 15.00**	**25.57 / 16.47**	**21.90 / 17.12**	**19.15 / 18.22**

Figure 2: Non-cherrypicked samples for a DDPM trained on CIFAR10, comparing the strongest DDIM($\eta = 0$) baseline and our approach. All samples were generated with the same random seeds. For reference, we include DDPM samples using all 1,000 stpes (top right) and real images (bottom right).

the aforementioned global minimum would achieve. These are 193.0 and 196.9 for CIFAR10 and ImageNet 64x64, respectively. Considering the FID scores from samplers found by DDSS, it is clear that we are not reaching these degenerate solutions.

6 DISCUSSION

When applied to a sufficiently flexible family (such as the GGDP family proposed in this work), DDSS consistently finds samplers that achieve better image generation quality than the strongest baselines in the literature for very few steps. This is qualitatively apparent in non-cherrypicked samples (e.g., DDIM($\eta = 0$) tends to generate blurrier images and with less background details as the budget decreases), and multiple quantitative sample quality metrics (FID and IS) also reflect these results. Still, we observe limitations to our method. Finding samplers with inference step budgets as small as $K < 10$ that have little apparent loss in quality remains challenging with our proposed search family. And, while on CIFAR10 the metrics indicate significant relative improvement over sample quality metrics, the relative improvement on ImageNet 64x64 is less pronounced. We hypothesize that this is an inherent difficulty of ImageNet due to its high diversity of samples, and that in order to retain sample quality and diversity, it might be impossible to escape some minimum number of inference steps with score-based models as they might be crucial to mode-breaking.

Beyond the empirical gains of applying our procedure, our findings shed further light into properties of pre-trained score-based generative models. First, we show that without fine-tuning a DDPM's parameters, these models are already capable of producing high-quality samples with very few inference steps, though the default DDPM sampler in this regime is usually suboptimal when using a few-step sampler. We further show that better sampling paths exist, and interestingly, these are determined by alternative variational lower bounds to the data distribution that make use of the score-based model but do not necessarily share the same marginals as the original DDPM forward process. Our findings thus suggest that enforcing this marginal-sharing constraint is unnecessary and can be too restrictive in practice.

Finally, the GGDP family and Theorem 1 show yet another "definition duality" for Gaussian forward processes of diffusion models: just like one can define a forward process by letting either the stochastic differential equation (SDE) coefficients (Song et al., 2021b) (or the β coefficients used by Ho et al. (2020) for discrete time) or the marginal coefficients (Song et al., 2020; Nichol & Dhariwal, 2021; Watson et al., 2021; Kingma et al., 2021) be the degrees of freedom, the coefficients of the posteriors can also be posited as the degrees of freedom that determine all other coefficients via prior conjugacy. This has the general advantage of admitting processes with no independence assumptions on the joint distribution.

7 OTHER RELATED WORK

Besides DDIM (Song et al., 2020), there have been more recent attempts at reducing the number of inference steps for DDPMs. Jolicoeur-Martineau et al. (2021) proposed a dynamic step size SDE solver that can reduce the number of calls to the modeled score function to ~ 150 on CIFAR10 (Krizhevsky et al., 2009) with minimal cost in FID scores, but quickly falls behind DDIM($\eta = 0$) with as many as 50 steps. Watson et al. (2021) proposed a dynamic programming algorithm that chooses log-likelihood optimal strides, but find that log-likelihood reduction has a mismatch with FID scores, particularly with in the very few step regime, also falling behind DDIM($\eta = 0$) in this front. Other methods that have been shown to help sample quality in the few-step regime include non-Gaussian variants of diffusion models (Nachmani et al., 2021) and adaptively adjusting the sampling path by introducing a noise level estimating network (San-Roman et al., 2021), but more thorough evaluation of sample quality achieved by these approaches is needed with budgets as small as those considered in this work.

Other approaches to sampling DDPMs have also been recently proposed, though not for the explicit purpose of efficient sampling. Song et al. (2021b) derive a reverse SDE that, when discretized, uses different coefficients than the ancestral samplers considered in this work. The same authors also derive "corrector" steps, which introduce additional calls to the pre-trained DDPM as a form of gradient ascent (Langevin dynamics) that help with quality but introduce computation cost, as well as an alternative sampling procedure using a probability flow ODE that shares the same marginals as the DDPM's original forward process. Huang et al. (2021) generalize this family of samplers to a "plug-in reverse SDE" that interpolates between a probability flow ODE and the reverse SDE, similarly to how the DDIM η interpolates between an implicit probabilistic model and a stochastic reverse process. Our proposed search family includes discretizations of most of these cases for Gaussian processes, notably missing corrector steps, where reusing a single timestep is considered.

8 CONCLUSION AND FUTURE WORK

We propose Differentiable Diffusion Sampler Search (DDSS), a method for finding few-step samplers for Denoising Diffusion Probabilistic Models. We show how to optimize a perceptual loss over a space of diffusion processes that makes use of a pre-trained DDPM's samples by leveraging the reparametrization trick and gradient rematerialization. Our results qualitatively and quantitatively show that DDSS is able to significantly improve sample quality for unconditional image generation over prior methods on efficient DDPM sampling. The success of our method hinges on searching a novel, wider family of Generalized Gaussian Diffusion Processes (GGDP) than those identified in prior work (Song et al., 2020). DDSS does not fine-tune the pre-trained DDPM, only needs to be applied once, has few hyperparameters, and does not require re-training the DDPM.

Our findings suggest future directions to further reduce the number of inference steps while retaining high fidelity in generated samples. For instance, it is plausible to use different representations for the perceptual loss instead of those of a classifier, e.g., use representations from an unsupervised model such as SimCLR (Chen et al., 2020), to using internal representations learned by the pre-trained DDPM itself, which would eliminate the burden of additional computation. Moreover, considering the demonstrated benefits of applying DDSS to our proposed GGDP family of samplers (as opposed to narrower families like DDIM), we motivate future work on identifying more general families of samplers and investigating whether they help uncover even better samplers or lead to overfitting. Finally, identifying other variants of perceptual losses (e.g., that do not sample from the model), or alternative optimization strategies (e.g., gradient-free methods) that lead to similar results is important future work. This would make DDSS itself a more efficient procedure, as gradient-based optimization of our proposed loss requires extensive memory or computation requirements to back-propagate through the whole sampling chain.

REPRODUCIBILITY STATEMENT

We plan to open source our work for the camera-ready version of the paper. Still, we provide sufficient details in the paper to completely reproduce our work, and the datasets and model checkpoints we experiment with are already publicly available. We include a theorem that shows how to compute the coefficients of the marginals of GGDP (Equation 8), which is a necessary and the most non-trivial step to reproduce our results. We also include a proof in the paper, immediately after the theorem statement. Additionally, we indicate the reader how to implement key ideas in the paper. E.g., in Section 4.1 we provide pseudocode showing exactly how we parametrize learnable, monotonically increasing timesteps, and in Section 4.3 we explain how to implement gradient rematerialization with JAX. Finally, our experiments section is thorough on all the hyperparameters we use, and any exceptions such as early stopping are always documented where appropriate.

ETHICS STATEMENT

We acknowledge that generative models have potentially dangerous applications, and that making them more efficient (as we do in our work) allows more people to utilize them. Still, methods outside the scope of this work like GANs are already much more efficient and can still achieve high-fidelity samples. Bias is also an important concern when working on such image generative models, more work needs to be done to investigate and mitigate bias of our samplers. We do not believe that our research will be directly used for harmful purposes, nor that its release or open sourcing will pose any risk to the community.

REFERENCES

Martin Arjovsky, Soumith Chintala, and Léon Bottou. Wasserstein GAN. In *arXiv*, 2017.

James Bradbury, Roy Frostig, Peter Hawkins, Matthew James Johnson, Chris Leary, Dougal Maclaurin, George Necula, Adam Paszke, Jake VanderPlas, Skye Wanderman-Milne, and Qiao Zhang. JAX: composable transformations of Python+NumPy programs, 2018. URL http://github.com/google/jax.

Andrew Brock, Jeff Donahue, and Karen Simonyan. Large scale GAN training for high fidelity natural image synthesis. *arXiv preprint arXiv:1809.11096*, 2018.

Ruojin Cai, Guandao Yang, Hadar Averbuch-Elor, Zekun Hao, Serge Belongie, Noah Snavely, and Bharath Hariharan. Learning Gradient Fields for Shape Generation. In *ECCV*, 2020.

Nanxin Chen, Yu Zhang, Heiga Zen, Ron J. Weiss, Mohammad Norouzi, and William Chan. Wave-Grad: Estimating Gradients for Waveform Generation. In *ICLR*, 2021a.

Nanxin Chen, Yu Zhang, Heiga Zen, Ron J. Weiss, Mohammad Norouzi, Najim Dehak, and William Chan. WaveGrad 2: Iterative Refinement for Text-to-Speech Synthesis . In *INTERSPEECH*, 2021b.

Ting Chen, Simon Kornblith, Kevin Swersky, Mohammad Norouzi, and Geoffrey Hinton. Big Self-Supervised Models are Strong Semi-Supervised Learners. In *NeurIPS*, 2020.

Jia Deng, Wei Dong, Richard Socher, Li-Jia Li, Kai Li, and Li Fei-Fei. Imagenet: A large-scale hierarchical image database. In *2009 IEEE conference on computer vision and pattern recognition*, pp. 248–255. Ieee, 2009.

Prafulla Dhariwal and Alex Nichol. Diffusion models beat gans on image synthesis. *arXiv preprint arXiv:2105.05233*, 2021.

Ian J Goodfellow, Jean Pouget-Abadie, Mehdi Mirza, Bing Xu, David Warde-Farley, Sherjil Ozair, Aaron Courville, and Yoshua Bengio. Generative adversarial networks. *arXiv preprint arXiv:1406.2661*, 2014.

Ishaan Gulrajani, Faruk Ahmed, Martin Arjovsky, Vincent Dumoulin, and Aaron Courville. Improved training of wasserstein gans. *arXiv preprint arXiv:1704.00028*, 2017.

Martin Heusel, Hubert Ramsauer, Thomas Unterthiner, Bernhard Nessler, and Sepp Hochreiter. Gans trained by a two time-scale update rule converge to a local nash equilibrium. *arXiv preprint arXiv:1706.08500*, 2017.

Jonathan Ho, Ajay Jain, and Pieter Abbeel. Denoising Diffusion Probabilistic Models. *NeurIPS*, 2020.

Jonathan Ho, Chitwan Saharia, William Chan, David J Fleet, Mohammad Norouzi, and Tim Salimans. Cascaded diffusion models for high fidelity image generation. *arXiv preprint arXiv:2106.15282*, 2021.

Chin-Wei Huang, Jae Hyun Lim, and Aaron Courville. A variational perspective on diffusion-based generative models and score matching. *arXiv preprint arXiv:2106.02808*, 2021.

Justin Johnson, Alexandre Alahi, and Li Fei-Fei. Perceptual losses for real-time style transfer and super-resolution. In *European conference on computer vision*, pp. 694–711. Springer, 2016.

Alexia Jolicoeur-Martineau, Ke Li, Rémi Piché-Taillefer, Tal Kachman, and Ioannis Mitliagkas. Gotta go fast when generating data with score-based models. *arXiv preprint arXiv:2105.14080*, 2021.

Diederik Kingma and Jimmy Ba. Adam: A Method for Stochastic Optimization. In *ICLR*, 2015.

Diederik P Kingma and Max Welling. Auto-Encoding Variational Bayes. In *ICLR*, 2013.

Diederik P Kingma, Tim Salimans, Ben Poole, and Jonathan Ho. Variational diffusion models. *arXiv preprint arXiv:2107.00630*, 2021.

Alex Krizhevsky, Geoffrey Hinton, et al. Learning multiple layers of features from tiny images. *Technical Report*, 2009.

Kundan Kumar, Rithesh Kumar, Thibault de Boissiere, Lucas Gestin, Wei Zhen Teoh, Jose Sotelo, Alexandre de Brebisson, Yoshua Bengio, and Aaron Courville. MelGAN: Generative Adversarial Networks for Conditional Waveform Synthesis. In *NeurIPS*, 2019a.

Ravi Kumar, Manish Purohit, Zoya Svitkina, Erik Vee, and Joshua R Wang. Efficient rematerialization for deep networks. In *Proceedings of the 33rd International Conference on Neural Information Processing Systems*, pp. 15172–15181, 2019b.

Shitong Luo and Wei Hu. Diffusion probabilistic models for 3d point cloud generation. In *Proceedings of the IEEE/CVF Conference on Computer Vision and Pattern Recognition*, pp. 2837–2845, 2021.

Eliya Nachmani, Robin San Roman, and Lior Wolf. Non gaussian denoising diffusion models. *arXiv preprint arXiv:2106.07582*, 2021.

Alex Nichol and Prafulla Dhariwal. Improved denoising diffusion probabilistic models. *arXiv preprint arXiv:2102.09672*, 2021.

Olaf Ronneberger, Philipp Fischer, and Thomas Brox. U-net: Convolutional networks for biomedical image segmentation. In *International Conference on Medical image computing and computer-assisted intervention*, pp. 234–241. Springer, 2015.

Tim Salimans, Ian Goodfellow, Wojciech Zaremba, Vicki Cheung, Alec Radford, and Xi Chen. Improved techniques for training gans. *Advances in neural information processing systems*, 29: 2234–2242, 2016.

Robin San-Roman, Eliya Nachmani, and Lior Wolf. Noise estimation for generative diffusion models. *arXiv preprint arXiv:2104.02600*, 2021.

Jascha Sohl-Dickstein, Eric Weiss, Niru Maheswaranathan, and Surya Ganguli. Deep unsupervised learning using nonequilibrium thermodynamics. In *International Conference on Machine Learning*, pp. 2256–2265. PMLR, 2015.

Jiaming Song, Chenlin Meng, and Stefano Ermon. Denoising diffusion implicit models. *arXiv preprint arXiv:2010.02502*, 2020.

Yang Song and Stefano Ermon. Generative Modeling by Estimating Gradients of the Data Distribution. *NeurIPS*, 2019.

Yang Song, Conor Durkan, Iain Murray, and Stefano Ermon. Maximum likelihood training of score-based diffusion models. *arXiv e-prints*, pp. arXiv–2101, 2021a.

Yang Song, Jascha Sohl-Dickstein, Diederik P. Kingma, Abhishek Kumar, Stefano Ermon, and Ben Poole. Score-Based Generative Modeling through Stochastic Differential Equations. In *ICLR*, 2021b.

Markus Svensén and Christopher M Bishop. Pattern recognition and machine learning, 2007.

Christian Szegedy, Vincent Vanhoucke, Sergey Ioffe, Jonathon Shlens, and Zbigniew Wojna. Rethinking the Inception Architecture for Computer Vision. In *CVPR*, 2016.

Ashish Vaswani, Noam Shazeer, Niki Parmar, Jakob Uszkoreit, Llion Jones, Aidan N. Gomez, Lukasz Kaiser, and Illia Polosukhin. Attention Is All You Need. In *NIPS*, 2017.

Pascal Vincent. A connection between score matching and denoising autoencoders. *Neural Computation*, 23(7):1661–1674, 2011.

Daniel Watson, Jonathan Ho, Mohammad Norouzi, and William Chan. Learning to efficiently sample from diffusion probabilistic models. *arXiv preprint arXiv:2106.03802*, 2021.

A APPENDIX

A.1 ADDITIONAL IMAGENET 64X64 SAMPLES

We provide additional samples for our results on ImageNet 64x64. The DDIM($\eta = 0$) samples (left) use a linear stride, while our DDSS + GGDP samples (right) use a learned stride. For reference, we include DDPM samples with all 4,000 steps (bottom left) and real samples (bottom right).